

Kurt U. Schaefer Director

OFFICIAL COPY VIA EMAIL: rfrye52@gmail.com

August 18, 2025

Rick Frye Owner Whispering Woods Land, LLC 803 P.C.A. Road Warrensburg, MO 64093

Dear Rick Frye:

Pursuant to the Missouri Clean Water Law, we have issued and are enclosing a General Permit for Sewer Extension Construction to Whispering Woods Land, LLC for Whispering Woods 3rd Plat project. Please review the requirements of your permit.

If you were adversely affected by this decision, you may be entitled to an appeal before the Administrative Hearing Commission (AHC) pursuant to 10 CSR 20-1.020 and Sections 644.051.6 and 621.250, RSMo. To appeal, you must file a petition with the Administrative Hearing Commission within 30 days after the date this decision was mailed or the date it was delivered, whichever date was earlier. If any such petition is sent by registered mail or certified mail, it will be deemed filed on the date it is mailed; if it is sent by any method other than registered mail or certified mail, it will be deemed filed on the date it is received by the Administrative Hearing Commission. Contact information for the AHC is as follows: Administrative Hearing Commission, United States Post Office Building, 131 West High Street, P.O. Box 1557, Jefferson City, MO 65102, Phone: 573-751-2422, Fax: 573-751-5018, Website: www.oa.mo.gov/ahc.

Nothing in this permit removes any obligations to comply with county or other local ordinances or restrictions.

If you have any questions concerning this permit, please do not hesitate to contact the Water Protection Program at P.O. Box 176, Jefferson City, MO 65102, 573-751-1300.

Sincerely,

WATER PROTECTION PROGRAM

Cindy LePage, P.E., Chief Engineering Section

CL:sdj

STATE OF MISSOURI DEPARTMENT OF NATURAL RESOURCES

MISSOURI CLEAN WATER COMMISSION



GENERAL PERMIT for SEWER EXTENSION CONSTRUCTION

The	Missouri	Depa	artment	of]	Natural	R	lesources !	here	bv	issues	a i	permit	to:

Construction Permit ID: MOGC00924

Title of Project: Whispering Woods 3rd Plat
Owner: Whispering Woods Land, LLC

Address: 803 P.C.A. Rd

Warrensburg, MO 64093

The project will also include general site work appropriate to the scope and purpose of the project and will include all the necessary appurtenances to make a complete and usable collection system. The construction of this project will be in the vicinity of the county below and discharge to Receiving Permit ID below:

County: Jackson Receiving Permit ID: MO0101087

for the construction of (described construction project):

Whispering Woods 3rd Plat-Construction of approximately 1,785 lf of 8-inch PVC SDR-26 and 163 lf of 8-inch ductile iron gravity sewer lines with approximately 13 manholes to serve 111 PE and a design average flow of 11,100 gpd.

Project is in the vicinity of SW Pryor Road and SW Hook Road intersection in Lee's Summit, Jackson County and discharges to an existing system to be treated at LBVSD, Atherton WWTF, MO-0101087. Amanda Bagwell, P.E., Engineering Manager with City of Lee's Summit provided a continuing authority acceptance letter dated March 27, 2025. David Lilly, P.E., District Engineer with Little Blue Valley Sewer District provided a receiving WWTF acceptance letter dated August 12, 2025.

Construction of such proposed facilities shall be in accordance with the provisions of the Missouri Clean Water Law, Chapter 644, RSMo, and regulation promulgated thereunder, or this permit may be revoked by the Department of Natural Resources (Department) As the Department does not examine structural features of design or the efficiency of mechanical equipment, the issuance of this permit does not include approval of these features.

This permit applies only to the construction of water pollution control components; it does not apply to other environmentally regulated areas.

August 18, 2025	Halle Stels	
Issue Date	Heather S Peters, Director	
	Water Protection Program	

August 17, 2027 Expiration Date

APPLICABILITY

- 1. This permit authorizes the construction of gravity sewer extensions, force mains, and lift stations. Non-earthen flow equalization storage basins at lift stations and inline storage, which flows back into the lift station or collection system, are also included.
- 2. The Missouri Department of Natural Resources may require a site-specific sewer extension construction permit due to compliance and enforcement actions in accordance with 10 CSR 20-6.010(13)(C).
- 3. This permit does not apply to:
 - A. Earthen storage basins;
 - B. Exempt projects in accordance with 10 CSR 20-6.010(1)(B), 10 CSR 20-6.010(5)(B), and RSMo 644.051 unless requested by the applicant or required by enforcement.

PREREQUISITES:

- 1. The Sewer Extension Construction Permit application, appropriate fee, and documentation in accordance with 10 CSR 20-6.010(5)(G).
- 2. Submit the Sewer Extension Construction Permit application at least sixty (60) days in advance of the start of construction in accordance with 10 CSR 20-6.010(5)(F).
- 3. Submit an electronic copy of the construction permit application and documents to DNR.WPPEngineerSection@dnr.mo.gov in accordance with 10 CSR 20-6.010(5)(G)3.
- 4. The plans and specifications, each signed, sealed, and dated by a professional engineer registered in the State of Missouri in accordance with 10 CSR 20-8 and 10 CSR 20-6.010.
- 5. The Design Certification form, Engineering Report, or Summary of Design, signed, sealed, and dated by a professional engineer registered in the State of Missouri, certifying the design of the system is in accordance with 10 CSR 20-6 and 10 CSR 20-8.
- 6. A statement from the continuing authority, as defined in 10 CSR 20-6.010, accepting the wastewater for treatment and indicating the permitted treatment facility has the available capacity.
- 7. A statement from the continuing authority, as defined in 10 CSR 20-6.010, accepting responsibility for the operation and maintenance of these facilities.

PERMIT CONDITIONS:

- 1. This permit authorizes the activities and scope of work detailed in the plans and specifications submitted with the request.
- 2. The construction must be in accordance with the final plans and specifications received by the Department. Revisions that affect capacity, flow, or system layout must be approved by the Department prior to construction.

PERMIT CONDITIONS: (continued)

- 3. If construction will incorporate minor changes from previously submitted plans and specifications (i.e., changes that do not affect the capacity, flow, or system layout), submit an electronic copy of the as-built plans and specifications in accordance with 10 CSR 20-8.110(11).
- 4. State and Federal Law does not permit bypassing of raw wastewater; therefore, the applicant must take steps to ensure that raw wastewater does not discharge during construction. If a sanitary sewer overflow or bypass occurs, report the appropriate information to the Department's regional office per 10 CSR 20-7.015(9)(E) or through the Online Bypass/SSO Reporting service on the Missouri Gateway for Environmental Management (MoGEM) portal found at https://dnr.mo.gov/data-e-services/missouri-gateway-environmental-management-mogem.

See https://dnr.mo.gov/document-search/missouri-gateway-environmental-management-mogem-frequently-asked-questions-pub2988/pub2988 for more information.

- 5. Protection of drinking water supplies must meet the requirements of 10 CSR 20-8.120(5).
 - A. There shall be no physical connections between a public or private potable water supply system and a sewer or appurtenance that would permit the passage of any wastewater or polluted water into the potable supply.
 - B. Lay sewers at least 50 feet (50') in a horizontal direction from any existing or proposed public water supply well or other water supply sources or structures.
- 6. Position manholes so that the top access is at or above grade level.
- 7. In addition to the requirements for a construction permit, see 10 CSR 20-6.200 for land disturbance requirements to obtain a Missouri State Operating Permit to discharge stormwater. The permit requires Best Management Practices sufficient to control runoff and sedimentation to protect waters of the state. Applicants shall obtain land disturbance permits through the Department's ePermitting system, available online at <a href="https://dnr.mo.gov/data-e-services/water/electronic-permitting-ep

See https://dnr.mo.gov/water/business-industry-other-entities/permits-certification-engineering-fees/stormwater/construction-land-disturbance for more information.

8. Entities applying for funding under 10 CSR 20-4, "Grants and Loans" will need to comply with those requirements in addition to the requirements of 10 CSR 20-8.

PERMIT CONDITIONS: (continued)

9. The Department may require a United States (U.S.) Army Corps of Engineers (COE) permit (404) and a Water Quality Certification (401) or a permit waiver for the activities described in this permit. If construction activity will disturb any land below the ordinary high water mark of Jurisdictional Waters of the U.S., then a 404/401 is required. Fulfillment of these requirements is necessary before the permit is considered valid. Since the COE makes determinations on what is jurisdictional, you must contact the COE to determine permitting requirements. You may call the Department's Operating Permits Section at 573-522-4502 for more information.

See https://dnr.mo.gov/water/business-industry-other-entities/permits-certification-engineering-fees/section-401-water-quality for more information.

- 10. If this project eliminates a wastewater treatment facility under the jurisdiction of the Department, then the applicant shall submit a full closure plan with a Facility Closure Request Form, Form MO 780-2512, to the Department's appropriate regional office for review and approval. In accordance with 10 CSR 20-6.010(12), the closure plan must meet the requirements outlined in Standard Conditions Part III of the Missouri State Operating Permit. Closure shall not commence until the Department approves the submitted closure plan.
- 11. If this project is part of a project to resolve an enforcement action or is receiving funding from the Department, submit a <u>statement of work complete</u> following the completion of construction.
- 12. Applicants may submit, prior to the expiration date of this permit, a written request that additional time is needed in accordance with 10 CSR 20-6.010(5)(H)3.



MISSOURI DEPARTMENT OF NATURAL RESOURCES WATER PROTECTION PROGRAM APPLICATION FOR CONSTRUCTION PERMIT — **SEWER EXTENSION**

FOR DEP	ARTMENT USE ONLY	
APP NO.	CP NO.	
FEE RECEIVED	CHECK NO.	
DATE RECEIVED		

CONTINUED AND BEST OF SERVICE SERVICES AND AND ADDRESS OF SERVICES.	<u></u>		<u> </u>	engales and an analysis		
NOTE ► PLEASE READ THE ACCOMPAN' 1.0 APPLICATION INFORMATION (Note –	and the second control of the contro		The state of the s	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7		olication may be
considered incomplete and returned.)	n any or m	e questions	111 1113 3601	ion are ansv	velou NO, illig ap	
1.1 Is this a Federal/State funded project?	☐ YES	☑ N/A F	unding Ag	ency:		Project#:
1.2 Has the Department of Natural Resource ☐ YES Date of Approval:	s approve	d the propos	sed project'	s engineerin	g report*?	
1.3 Is a copy of the appropriate plans* and s	pecificatio	ns* included	with this a	oplication?	☑ YES ☐ NO	
1.4 Is a summary of design* included with the	is applicati	on? 🗹 Y	ES 🗌 N	o		
1.5 Is the appropriate fee or JetPay confirma See Section 7.0	tion includ	ed with this	application	? ☑ YES	□NO	
* Must be affixed with a Missouri registered p	rofessiona	l engineer's	seal, signa	ture and dat	e.	
2.0 PROJECT INFORMATION 2.1 NAME OF PROJECT						
WHISPERING WOODS 3RD PLAT						
ADDRESS	CITY			STATE	ZIP CODE 64082	Jackson
O O Land Danninking 1/	Lee's Sur			47N , R		Jackson
2.2 Legal Description: ¼,	∕₄, SW	1⁄4, Sec.	24 , '	4/N , K	3277	
2.3 Project Components (check all that apply ☑ Gravity sewers ☐ Pumping station		rce mains	☐ Alterna	itive sewer s	system	r (Describe below.)
2.4 PROJECT DESCRIPTION						44,000 50
NEW SUBDIVISION FOR 30 HOUSING LOT	S WITH A	PPROXIMA ⁻	TELY 1948	SLF OF 8" S	5DR-26, AND 13 N	MANHOLES
2.5 DESIGN INFORMATION						
A. Population or number of lots to be served	by this ex	tension: 30 l	Lots			
B. Estimated flow to be contributed by this e	xtension:	Design Ave	rage Flow:	11100 gpd	Design Peak Ho	ourly Flow: 9560 gph
C. Industrial Wastes: Type:	Flo	w: g	od			
D. Receiving Sewer: Size: 24 inches	Сар	acity:6645	gpm			
3.0 PROJECT OWNER						
NAME		TELEPHONE N	IUMBER WITH A	REA CODE	EMAIL ADDRESS	Loom
WHISPERING WOODS LAND, LLC	1				rfrye52@gmail	I.COM
ADDRESS 803 P.C.A. Rd	Warrensk	oura		STATE MO	ZIP CODE 64093	
4.0 CONTINUING AUTHORITY: A continuin			nv. busines	s, entity or p	person(s) that will	be operating the facility
or ensuring compliance with the permit requi	rements. A	A continuing	authority is	not, howev	er, an entity or ind	lividual that is
contractually hired by the permittee to sampl	e or opera	te and main	tain the sys	tem for a de	fined time period,	such as a certified
operator or analytical laboratory. To access t visit https://s1.sos.mo.gov/cmsimages/adrule	ne regulat elestleur	ory requiren ent/10csr/10	ierit regard)c20-6 ndf	ng continuina A continuina	ig authority, 10 Cc	must be listed exactly as
it appears on the Missouri Secretary of State	's (SoS's)	webpage:				
https://bsd.sos.mo.gov/BusinessEntity/BESe	arch.aspx'	?SearchType	e=0, unless	the continu	ing authority is an	individual(s),
government, or otherwise not required to reg	ister with t	TELEPHONE N	IUMBER WITH A	AREA CODE	EMAIL ADDRESS	<u> 28 (m. 1942) (m. 1944) (m. 1944) (m. 1944)</u> -
CITY OF LEE'S SUMMIT		816.969.19			amanda.bagw	ell@cityofls.net
ADDRESS	CITY			STATE	ZIP CODE	
1200 SE Hamblen Rd	Lee's Su		 	МО	64081	F 111 A
4.1 A letter from the continuing authority or if different than the owner, is included with the	he Continu	uing Authorit ion. 🛮 YE	ty and Rece S □ NC		ewater Treatment I	racility Acceptance form,
MO 780-1632 (10-19)	is applicat	IOII. ELIL		, LIN/A		Page 1 of 2

5.0 ENGINEER				
ENGINEER NAME / COMPANY NAME			BER WITH AREA CODE	EMAIL ADDRESS
Shawn Duke, PE /Snyder & Ass	ociates, Inc.	816-364-522	2	sduke@snyder-associates.com
ADDRESS	CITY	CITY S		ZIP CODE
802 Francis Street	Sair	nt Joseph	MO	64501
6.0 RECEIVING WASTEWATE	R TREATMENT F	ACILITY		
NAME		TELEPHONE NUM	MBER WITH AREA CODE	EMAIL ADDRESS
Little Blue Valley Sewer District	Atherton WWTP	816.796.9191	1	flathers@lbvsd.org
MISSOURI STATE OPERATING PERMIT #	** .	REMAINING CAPA	ACITY (GPD)	
MO-0101087		10 MGD		
6.1 Has the receiving treatment	t facility agreed to	accept the additions	al wastewater flow?	☑ YES □ NO
6.2 A letter from the receiving w ☐ YES ☐ NO ☑ N/A		ent facility, if differer	nt than the continuing	authority, is included with this application.
7.0 Application Fee				
☐Check Number			✓ JetPay Confirm	nation Number
supervision in accordance with submitted. Based on my inquiry gathering the information, the in	a system designed of the person or partification of a submitter of the system of the s	d to assure that qua persons who manag ed is, to the best of	lified personnel prope the system, or thos my knowledge and b	ents were prepared under my direction or erly gather and evaluate the information se persons directly responsible for elief, true, accurate, and complete. I am ssibility of fine and imprisonment for
CAC TAN				
PRINTED NAME	· · · · · · · · · · · · · · · · · · ·			DATE
Rick Frye, Whispering Woods La	and, LLC			
TITLE OR COPORATE POSITION		TELEPHONE NUM	MBER WITH AREA CODE	EMAIL ADDRESS
Owner ' ·				rfrye52@gmail.com
Mail completed copy to:	WATER PROTI P.O. BOX 176	PARTMENT OF NA ECTION PROGRAM ITY, MO 65102-01		
MO 780-1632 (10-19)	***************************************			Page 2 of 2

INSTRUCTIONS FOR COMPLETING APPLICATION FOR CONSTRUCTION PERMIT – SEWER EXTENSION

All blanks must be filled in when the application is submitted to the Missouri Department of Natural Resources. This includes the **required signature**.

In accordance with Missouri State law RSMo 644.051.3.(2), sewer extension projects installing up to a total of 1,000 linear feet of gravity sewer or force main with less than two pump stations are exempt from obtaining a construction permit. Since these projects are exempt, a construction permit will not be issued for this activity and completion of this form is not required.

Note: Use the form *Application for Construction Permit – Wastewater Treatment Facility*, MO 780-2189, if any wastewater treatment component(s) are to be constructed.

After receiving a complete application, the department enters the application information into the Missouri Clean Water Information System. You may search for the status of a construction permit online at https://apps5.mo.gov/mocwis public/applicationInprocessSearch.do.

- 1.1 Check appropriate box. If the project is funded with federal or state monies, supply the funding agency name and project number.
- 1.2 Check appropriate box and provide the date of department approval.

 The department has developed a fact sheet to aid in the development of an approvable engineering report. This document is available online at dnr.mo.gov/pubs/pub2415.htm. Engineering report exemptions are listed in 10 CSR 20-6.010(4)(B). Per 10 CSR 20-8.110(2), engineering reports must be approved by the department prior to the submittal of plans and specifications and a construction permit application. The department has developed a fact sheet to aid in the development of an approvable engineering report, Engineering Report Guidance for Collection Systems, Fact Sheet—PUB2415.
- 1.3 Check appropriate box. Provide a copy of the appropriate plans and specifications for department review when applying for a construction permit per 10 CSR 20-8.110 and 10 CSR 20-6.010. A Missouri registered professional engineering seal, signature and date is required on each sheet of the plans and the cover of the technical specifications. An electronic copy of the construction permit application and the information listed below in Portable Document Format (PDF) searchable format or department approved equivalent per 10 CSR 20-6.010(5) (G), along with one paper copy for projects not seeking department funding or two paper copies for projects seeking department funding under 10 CSR 20-4.
- 1.4 Check appropriate box. A summary of design shall accompany the plans and specifications when applying for a construction permit per 10 CSR 20-8.110. The department has developed a fact sheet to aid in the development of an acceptable summary of design , <u>Summary of Design Guidance</u>, Fact Sheet--PUB2417.
- 1.5 Check the appropriate box. Include fee with application per 10 CSR 20-6.011(2) and Wastewater Treatment Facility Permit Fees -- PUB2564.
- Note: The department returns incomplete construction permit applications and related engineering documents and the application forfeits the fees. See 10 CSR 20-6.011(5)(A). The applicant forfeits the fees when the applicant withdraws construction applications. See 10 CSR 20-6.011(5)(B).2.1. Provide the project name and location by street name or address.
- 2.2 Provide the project legal description. The department's mapping system is available online at dnr.mo.gov/gis/.
- 2.3 Check all of the applicable boxes.

 The department considers anything other than a gravity sewer system to be an alternative sewer system.

 Examples of these systems are grinder pump pressure sewers, septic tank effluent pump, or STEP, sewers, septic tank effluent gravity, or STEG, sewers or small diameter gravity sewers.
- 2.4 Briefly describe the project by providing the following information:
 - A. Total number of manholes.
 - B. Size of sewers and the total linear feet of each size.
 - C. Number of lift stations and design average flow and peak hourly flow capacities of each lift station.
 - D. Size and length of force mains.
 - E. Alternative sewer size and length, plus the number of components (e.g. septic tanks, grinder pumps, etc.)
- 2.5 Provide the project design information and when required in the units specified.
 - A. Provide the population or number of lots to be served by the proposed sewer extension.

- B. Provide the estimated design flow information in accordance with 10 CSR 20-8.110(4)(C)4.A.

 Design average flow The design average flow is the average of the daily volumes to be received for a continuous 12 month period expressed as a volume per unit time. However, the design average flow for facilities having critical seasonal high hydraulic loading periods (e.g., recreational areas, campuses and industrial facilities) shall be based on the daily average flow during the seasonal period.

 Design peak hourly flow The design peak hourly flow is the largest volume of flow to be received during a one hour period expressed as a volume per unit time.
- C. Provide the type and flow in gallons per day of industrial wastes received by the propose sewer extension.
- D. Provide the receiving sewer size in inches and capacity in gallons per minute.
- 3.0 Complete Project Owner information. Include the legal name and address.
- 4.0 Continuing Authority A continuing authority is a company, business, entity or person(s) that will be operating the facility or ensuring compliance with the permit requirements. A continuing authority is not, however, an entity or individual that is contractually hired by the permittee to sample or operate and maintain the system for a defined time period, such as a certified operator or analytical laboratory. To access the regulatory requirement regarding continuing authority, 10 CSR 20-6.010(2), please visit http://s1.sos.mo.gov/cmsimages/adrules/csr/current/10csr/10c20-6.pdf. A continuing authority's name must be listed exactly as it appears on the Missouri Secretary of State's (SoS's) webpage: https://bsd.sos.mo.gov/BusinessEntity/BESearch.aspx?SearchType=0, unless the continuing authority is an individual(s), government, or otherwise not required to register with the SoS. If same as the Project Owner, write "Same as above".
- 4.1 Check appropriate box. Include a letter signed by the continuing authority (if not same as the project owner) stating they will "accept, operate and maintain" the sewer extension. The continuing authority may also complete the Continuing Authority and Receiving Wastewater Treatment Facility Acceptance form in lieu of a letter. If the continuing authority will not accept and agree to operate and maintain the sewer extension, this application will be considered incomplete.
- 5.0 Complete Engineer contact information.
- 6.0 Complete Receiving Wastewater Treatment Facility information. Include the Missouri State Operating Permit number and the available remaining capacity in gallons per day, or gpd.
- Check appropriate box. The receiving wastewater treatment facility must be notified and agree to the proposed sewer extension and additional flow, prior to submitting a construction permit to the department.

 If the receiving wastewater treatment facility will not accept the wastewater, this application will be considered incomplete.
- 6.2 Check appropriate box. Include a letter from the receiving wastewater treatment facility (if not same as the continuing authority) acknowledging and accepting the additional flow from the proposed sewer extension.
- 7.0 Check the appropriate box and include check or confirmation number. Applicants can pay fees online by credit card or eCheck through a system called JetPay.
 - Per Section 37.001, RSMo, a transaction fee will be included. The transaction fee is paid to the third party vendor JetPay, not the Department of Natural Resources.
 - Be sure to select the correct fee type and corresponding URL to ensure your payment is applied appropriately. If you are unsure what type of fee to pay, please contact the Water Protection Program's Budget, Fees, and Grants Management Unit by phone at 573-522-1485 for assistance.
 - Upon successful completion of your payment, JetPay provides a payment confirmation. Submit this form
 with a copy of the payment confirmation if requesting a new permit or a permit modification. For permit
 renewals of active permits, the Department will invoice fees annually in a separate request.
 - If you are unable to make your payment online, but want to pay with credit card, you may email your name, phone number, and invoice number, if applicable, to <u>WPPFEES@dnr.mo.gov</u>. The Budget, Fees, and Grants Management Unit will contact you to assist with the credit card payment. Please do not include your credit card information in the email.
 - Applicants can find fee rates in 10 CSR 20-6.011 and Wastewater Treatment Facility Permit Fees-PUB2564 (https://dnr.mo.gov/pubs/pub2564.htm).

WP 04 Construction Permits: https://magic.collectorsolutions.com/magic-ui/payments/mo-natural-resources/592/8.0
The owner of the construction project must sign the application.

Mail the completed form and applicable fee to the department.

If there are any questions concerning this form, please contact the Department of Natural Resources, Water Protection Program at 800-361-4827 or 573-751-1300 or visit dnr.mo.gov/env/wpp/permits/ww-construction-permitting.htm.

SEWER EXTENSION DESIGN CERTIFICATION

Answer all questions yes, no, or N/A. Answer N/A only if the question is clearly not applicable to the design of the proposed sewer extension **OR** if a deviation was previously allowed by the Department in the approval of Standard specifications or Standard Detail Sheets.

	REGULATION		YES	NO	N/A
1	8.110(9)(B)	Are detailed plans showing tributary area, boundaries, pertinent elevations, topography, existing and proposed facilities provided?	~		
2	8.110(3)(A)	Is the design flow based on actual flow data for an existing system?	V		
3	8.110(3)(B)	Are average design flows, peak hourly flows, and I&I contributions for new systems calculated.	V		
4	8.120(2)	Does the sewer exclude water from roofs, streets, groundwater from foundation drains, and combined wastewater?	V		
5	8.120(3)(C)	Is ASTM C969-17 leakage test specified to ensure water tight joint seals and appropriate exfiltration and infiltration rates?	V		
6	8.120(4)(A)	Are manholes located at all changes in grade, size or alignment, and all intersections?	1		
7	8.120(3)(A)1	Are all sewer pipes constructed with a slope to obtain mean velocities of not less than 2 feet per second?	V		
8	8.120(3)(A)2	Is the pipe covered with at least 36" of soil or sufficiently insulated to prevent freezing?	V		
9	8.120(3)(A)	Is the pipe installation, embedment, and backfill designed to prevent damage to the pipe and its joints?	V		
10	8.120(3)(B)	Is deflection testing specified to ensure no pipe exceeds a deflection of 5% of the inside diameter?			
11	8.120(4)(C)	Are manholes at least 42 inches in diameter with a clear opening of 22 inches on sewer line larger than 8"?	V		П
12	8.120(4)(C)	Where cleanouts are used at the end of a lateral instead of a manhole, are they a minimum diameter of 8 inches or larger and equal to the diameter for pipes < 8"?			V
13	8.120(4)(E)	Are the manholes specified to be watertight, constructed, installed in accordance with the manufacturer's recommendations and procedures?	1		
14	8.120(4)(F)	Do the specifications include a requirement for inspection and testing for manholes?	V		
15	8.120(5)(B)	Are sewers and manholes located at least 50 feet horizontally from any existing or proposed water supply well, sources, structures?	V		
16	8.120(5)(A)	Is the sewer free from physical connections to a potable water supply system with no water pipes coming in contact with a sewer manhole?	V		

REGULATION	10.0	PRESSURE SE	WERS, GRINDER PUMP, STEP AND STEG SEWER CHECKLIST			
18 8.125(5)(A)2. Is the diameter of the pressure sewer main pipe at least 1.5"?		REGULATION		YES	NO	N/A
19 8.125(5) Are appurtenances compatible with the piping system?	17	8.125(5)(A)1.	Does the cleaning velocity of ≥ 2 ft/s happen at least once per day?			V
20 8.125(5)(C) Do service line pipes have a minimum diameter of 1.25 in.? 21 8.125(5)(D)1 Do simplex grinder pump stations service only a single equivalent □ □ □ □ □ □ □ □ □	18	8.125(5)(A)2.	Is the diameter of the pressure sewer main pipe at least 1.5"?			✓
21 8.125(5)(D)1. Do simplex grinder pump stations service only a single equivalent dwelling unit (EDU)? i.e. 1 residence − 1 grinder pump station. 22 8.125(6)(D)1. Be multiple unit pump stations owned, operated, maintained by an approved continuing authority? 23 8.125(5)(D)3 Is there at least 70 gallons of storage in the grinder pump unit? 24 8.125(5)(D)4 Do grinder pump stations have shutoff valves, check valves, and antispithon valves (where siphoning could occur) that are accessible from the grinder pump unit? 25 8.125(5)(D)4 Are units serviceable and replaceable under wet conditions without electrical hazard and electrical equipment suitable for hazardous locations? 26 8.125(6)(D)8 Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity or interconnection with another disposal system? 27 8.125(6)(D) 8.180(2) gallon capacity with 20% of tank volume dedicated to freeboard and ventilation? 28 8.125(6)(F) Are pump vaults designed with duplex pumps for STEP sewer systems with design flow of 1,500 gallons per day or greater? 29 8.125(7)(A) Is the minimum STEG sewerservice line at least 4" in diameter? 30 8.130(2)(A) Is the minimum STEG sewerservice line at least 4" in diameter? 31 8.130(3)(A) Is the design flow is 1,500 gall or more, are at least 2 pumps or pneumatic ejectors provided? 31 8.130(3)(B) If the design flow is 1,500 gall or more, are at least 2 pumps or pneumatic ejectors provided? 32 8.130(3)(B) Is an alarm system provided with uninterrupted power? 33 8.130(3)(G) Does all potable water brought to the pump station comply with 8.140 Impact of the design flow	19	8.125(5)B	Are appurtenances compatible with the piping system?			V
dwelling unit (EDU)7 i.e. 1 residence — 1 grinder pump station. 22 8.125(5)(D)1. Are multiple unit pump stations owned, operated, maintained by an approved continuing authority? 23 8.125(5)(D)3 Is there at least 70 galions of storage in the grinder pump unit? 24 8.125(5)(D)4 Ogrinder pump stations have shutoff valves, check valves, and antisphon valves (where siphoning could occur) that are accessible from the ground surface? 25 8.125(5)(D)7 8.130(3)(B)2 Ogrinder pump stations have shutoff valves, check valves, and antisphon valves (where siphoning could occur) that are accessible from the ground surface? 26 8.125(5)(D)8 Are units serviceable and replaceable under wet conditions without electrical hazard and electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 locations)? 27 8.125(6)(D)8 Reprovisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity or interconnection with another disposal system? 28 8.125(6)(D) Reprovisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity or interconnection with another disposal system? 29 8.125(6)(D) Reprovisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage capacity or interconnection with another disposal system? 29 8.125(7)(A) Is the pump valutis designed with duplex pumps for STEP sewer systems with design flow of 1,500 gallons per day or greater? 29 8.125(7)(A) Is the minimum STEG sewerservice line at least 4" in diameter? 29 8.130(2)(A) Is the pump station designed to withstand the 100-year flood? 30 8.130(2)(A) Is the dry well completely separate from the well and is a suitable and safe means of access provided to each? 31 8.130(3)(B) If the design flow is 1,500 gpd or more, are at least 2 pumps or pneumatic ejectors provided? 32 8.130(3)(B) Ower and dry wells have separate ventilation syst	20	8.125(5)(C)	Do service line pipes have a minimum diameter of 1.25 in.?			1
B approved continuing authority? 28 8.125(5)(D)3 Is there at least 70 gallons of storage in the grinder pump unit? 29 8.125(5)(D)4 Do grinder pump stations have shutoff valves, check valves, and antisiphon valves (where siphoning could occur) that are accessible from the ground surface? 29 8.125(5)(D)7 Are units serviceable and replaceable under wet conditions without electrical hezard and electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 20 8.125(5)(D)8 Are provisions in place to avoid interruption of service due to mechanical or power fallure by providing standby power, storage apacity or interconnection with another disposal system? 21 8.125(6)(D) Bose each EDU have at least one septic tank with a minimum of 1,000 gallon capacity with 20% of tank volume dedicated to freeboard and ventilation? 22 8.125(7)(A) Is the minimum STEG sewerservice line at least 4" in diameter? 23 8.125(7)(A) Is the minimum STEG sewerservice line at least 4" in diameter? 24 8.130(3)(A) Is the pump station designed to withstand the 100-year flood? 25 8.130(3)(A) Is the dry well completely separate from the wet well and is a suitable and safe means of access provided to each? 26 8.130(3)(B) If the design flow is 1,500 gpd or more, are at least 2 pumps or pneumatic ejectors provided? 27 8.130(3)(G) Does all potable water brought to the pump station comply with 8.140 (7) D? 28 8.130(3)(G) Does all potable water brought to the pump station comply with 8.140 (7) D? 29 8.130(7)(A) Is the or a mindependent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? 29 8.130(8)(A) Is there a hours retention of the peak hourly flow for a design flow 20 100,000 gpd? 20 8.130(7)(B) Is the complete operation instructions for the pumping stations provided that include emergency procedures, maintenance schedules, Provided that include emergency procedures, maintenance schedules, Provided	21	Α				V
24 8.125(5)(D)4 Do grinder pump stations have shutoff valves, check valves, and antisphon valves (where siphoning could occur) that are accessible from the ground surface? 25 8.125(5)(D)7 Are units serviceable and replaceable under wet conditions without electrical hazard and electrical equipment suitable for hazardous locations (National Electrical code, Class I, Group D, Division 1 location)? 26 8.125(5)(D)8 Are provisions in place to avoid interruption of service due to mechanical or power failure by providing standby power, storage agacity or interconnection with another disposal system? 27 8.125(6)(D) Does each EDU have at least one septic tank with a minimum of 1,000 gallon capacity with 20% of tank volume dedicated to freeboard and ventilation? 28 8.125(6)(F) Are pump vaults designed with duplex pumps for STEP sewer systems with design flow of 1,500 gallons per day or greater? 29 8.125(7)(A) Is the minimum STEG sewerservice line at least 4" in diameter? 30 8.130(2)(A) Is the pump station designed to withstand the 100-year flood? 31 8.130(3)(A) Is the pump station designed to withstand the 100-year flood? 32 8.130(3)(B) Is the pump station designed to withstand the 100-year flood? 33 8.130(3)(B) If the design flow is 1,500 gpd or more, are at least 2 pumps or pum and safe means of access provided to each? 34 8.130(3)(F) Does all potable water brought to the pump station comply with 8.140 (7) D? 35 8.130(3)(G) Does all potable water brought to the pump station comply with 8.140 (7) D? 36 8.130(7)(A) Is there 2 hours retention of the peak hourly flow for a design flow < 100,000 gpd? 39 8.130(7)(A) Is there 2 hours retention of the peak hourly flow for a design flow < 100,000 gpd? 39 8.130(8)(A) Is the force main velocity of ≥ 2 ft/s maintained? 30 Provided that include emergency procedures, maintenance schedules, Provided the pumping stations provided the include emergency procedures, maintenance schedules, Provided that include emergency procedures, maintenance schedules, Provided tha		В	approved continuing authority?			V
siphon valves (where siphoning could occur) that are accessible from the ground surface? Are units serviceable and replaceable under wet conditions without electrical hazard and electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)? 26 8.125(6)(F)6 8.125(6)(F)7 8.125(6)(F)8 8.125(6)(F)8 8.125(6)(F)8 8.125(6)(F)8 8.125(6)(F)9 9.125(6)(F)9		, , , ,				✓
8.130(3)(B)2 electrical hazard and electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 locations)? 8.125(6)(F)8			siphon valves (where siphoning could occur) that are accessible from the ground surface?			V
8.125(6)(F)6 mechanical or power failure by providing standby power, storage capacity or interconnection with another disposal system? 27 8.125(6)(D) Does each EDU have at least one septic tank with a minimum of 1,000 gallon capacity with 20% of tank volume dedicated to freeboard and ventilation? 28 8.125(6)(F) Are pump vaults designed with duplex pumps for STEP sewer systems with design flow of 1,500 gallons per day or greater? 29 8.125(7)(A) 8.125(7)(C) Is the minimum STEG sewerservice line at least 4" in diameter? 29 8.125(7)(C) Is the minimum STEG sewerservice line at least 4" in diameter? 20 8.130(2)(A) Is the pump station designed to withstand the 100-year flood? 30 8.130(2)(A) Is the pump station designed to withstand the 100-year flood? 31 8.130(3)(A) Is the dry well completely separate from the wet well and is a suitable and safe means of access provided to each? 32 8.130(3)(B) If the design flow is 1,500 gpd or more, are at least 2 pumps or pneumatic ejectors provided? 33 8.130(3)(D) Are valves located outside well well unless integral to a pump or its housing? 34 8.130(3)(F) Do wet and dry wells have separate ventilation systems? 35 8.130(3)(G) Does all potable water brought to the pump station comply with 8.140 36 8.130(6) Is an alarm system provided with uninterrupted power? 37 8.130(7)(A) Is there 2 hours retention of the peak hourly flow for a design flow < 100,000 gpd? 38 8.130(7)(B) Is there an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? 39 8.130(8)(A) Is the force main velocity of ≥ 2 ft/s maintained? 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130 40 8.130	25	8.130(3)(B)2	electrical hazard and electrical equipment suitable for hazardous locations (National Electrical Code, Class I, Group D, Division 1 location)?			~
8.180(2) gallon capacity with 20% of tank volume dedicated to freeboard and ventilation? 8.125(6)(F) Are pump vaults designed with duplex pumps for STEP sewer systems with design flow of 1,500 gallons per day or greater? 9. 8.125(7)(A) 8.125(7)(C) Is the minimum STEG sewerservice line at least 4" in diameter? 11.0 PUMP STATION CHECKLIST REGULATION YES NO N/A 30. 8.130(2)(A) 8.140(2)(B) Is the pump station designed to withstand the 100-year flood? 31. 8.130(3)(A) Is the dry well completely separate from the wet well and is a suitable and safe means of access provided to each? 32. 8.130(3)(B) If the design flow is 1,500 gpd or more, are at least 2 pumps or pneumatic ejectors provided? 33. 8.130(3)(F) Are valves located outside wet well unless integral to a pump or its housing? 34. 8.130(3)(F) Bow and dry wells have separate ventilation systems? 35. 8.130(3)(G) Does all potable water brought to the pump station comply with 8.140 (7) D? 36. 8.130(6) Is an alarm system provided with uninterrupted power? 37. 8.130(7)(A) Is there 2 hours retention of the peak hourly flow for a design flow 100,000 gpd? 38. 8.130(7)(B) Is there 2 hours retention of the peak hourly flow for a design flow 2 100,000 gpd? 39. 8.130(8)(A) Is there an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? 39. 8.130(8)(A) Is the force main velocity of ≥ 2 ft/s maintained? 39. 8.130(8)(A) Is the complete operation instructions for the pumping stations provided that include emergency procedures, maintenance schedules, provided that include emergency procedures and the several substance is the pump station and the pump stations provided that include emergency procedures and the sex	26	8.125(6)(F)6	mechanical or power failure by providing standby power, storage capacity or interconnection with another disposal system?			V
with design flow of 1,500 gallons per day or greater?	27		gallon capacity with 20% of tank volume dedicated to freeboard and			V
8.125(7)(C)	28	8.125(6)(F)				V
REGULATION 8.130(2)(A) 8.130(2)(B) 8.130(2)(B) 8.130(3)(A) 8.130(3)(A) 8.130(3)(A) 8.130(3)(B) 8.130(B)		8.125(7)(C)				<u> </u>
30 8.130(2)(A) 8.140(2)(B) Is the pump station designed to withstand the 100-year flood? □ ✓ 31 8.130(3)(A) Is the dry well completely separate from the wet well and is a suitable and safe means of access provided to each? □ ✓ 32 8.130(3)(B) If the design flow is 1,500 gpd or more, are at least 2 pumps or pneumatic ejectors provided? □ ✓ 33 8.130(3)(D) Are valves located outside wet well unless integral to a pump or its housing? □ ✓ 34 8.130(3)(F) 8.140(B)(J) Do wet and dry wells have separate ventilation systems? □ ✓ 35 8.130(3)(G) Does all potable water brought to the pump station comply with 8.140 (7) D? ✓ 36 8.130(6) Is an alarm system provided with uninterrupted power? □ ✓ 37 8.130(7)(A) Is there 2 hours retention of the peak hourly flow for a design flow 100,000 gpd? □ ✓ 38 8.130(7)(B) Is there an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? □ ✓ 39 8.130(8)(A) Is the force main velocity of ≥ 2 ft/s maintained? □ ✓ 40 8.130 Are there complete operation instructions for the pumping stations provided that include emergency procedures, maintenance schedules, □ ✓	11.0	PUMP STATION	I CHECKLIST		100	
8.140(2)(B) 31 8.130(3)(A)		REGULATION		YES	NO	N/A
and safe means of access provided to each? 32 8.130(3)(B)		8.140(2)(B)				✓
pneumatic ejectors provided? 33 8.130(3)(D) Are valves located outside wet well unless integral to a pump or its housing? 34 8.130(3)(F)	31	8.130(3)(A)				V
housing?	32	. , , ,	pneumatic ejectors provided?			V
8.140(8)(J) 35 8.130(3)(G) Does all potable water brought to the pump station comply with 8.140 (7) D? 36 8.130(6) Is an alarm system provided with uninterrupted power? 37 8.130(7)(A) Is there 2 hours retention of the peak hourly flow for a design flow > 100,000 gpd or 4 hrs retention of the peak hourly flow for a design flow < 100,000 gpd? 38 8.130(7)(B) Is there an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? 39 8.130(8)(A) Is the force main velocity of ≥ 2 ft/s maintained? 40 8.130 Are there complete operation instructions for the pumping stations provided that include emergency procedures, maintenance schedules,	33	8.130(3)(D)	Are valves located outside wet well unless integral to a pump or its	_	l —	
(7) D?			housing?	Ш		
8.130(7)(A) Is there 2 hours retention of the peak hourly flow for a design flow > 100,000 gpd or 4 hrs retention of the peak hourly flow for a design flow < 100,000 gpd? Sthere an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? Sthere an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? Sthere an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? Sthere an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? Sthere an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? Sthere an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? Sthere an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? Sthere an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? Sthere an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? Sthere an independent utility substation provided for emergency power that is capacity? Sthere an independent utility substation provided for emergency power that is capacity? Sthere an independent utility substation provided for emergency power that is capacity at the pump station at its rated capacity? Sthere an independent utility substation provided for emergency power that its rated capacity at the pump station at its rated capacity at the pump station at it		8.140(8)(J)	housing? Do wet and dry wells have separate ventilation systems?			
100,000 gpd or 4 hrs retention of the peak hourly flow for a design flow < 100,000 gpd? 38 8.130(7)(B) Is there an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity? 39 8.130(8)(A) Is the force main velocity of ≥ 2 ft/s maintained? 40 8.130 Are there complete operation instructions for the pumping stations provided that include emergency procedures, maintenance schedules,		8.140(8)(J) 8.130(3)(G)	housing? Do wet and dry wells have separate ventilation systems? Does all potable water brought to the pump station comply with 8.140 (7) D?			V
that is capable of starting and operating the pump station at its rated capacity? 39 8.130(8)(A) Is the force main velocity of ≥ 2 ft/s maintained? 40 8.130 Are there complete operation instructions for the pumping stations provided that include emergency procedures, maintenance schedules,	35	8.140(8)(J) 8.130(3)(G)	housing? Do wet and dry wells have separate ventilation systems? Does all potable water brought to the pump station comply with 8.140 (7) D?			V
39 8.130(8)(A) Is the force main velocity of ≥ 2 ft/s maintained? 40 8.130 Are there complete operation instructions for the pumping stations provided that include emergency procedures, maintenance schedules,	35 36 37	8.140(8)(J) 8.130(3)(G) 8.130(6) 8.130(7)(A)	housing? Do wet and dry wells have separate ventilation systems? Does all potable water brought to the pump station comply with 8.140 (7) D? Is an alarm system provided with uninterrupted power? Is there 2 hours retention of the peak hourly flow for a design flow > 100,000 gpd or 4 hrs retention of the peak hourly flow for a design flow < 100,000 gpd?			\ \ \ \
provided that include emergency procedures, maintenance schedules,	35 36 37	8.140(8)(J) 8.130(3)(G) 8.130(6) 8.130(7)(A)	housing? Do wet and dry wells have separate ventilation systems? Does all potable water brought to the pump station comply with 8.140 (7) D? Is an alarm system provided with uninterrupted power? Is there 2 hours retention of the peak hourly flow for a design flow > 100,000 gpd or 4 hrs retention of the peak hourly flow for a design flow < 100,000 gpd? Is there an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated			V
	35 36 37 38	8.140(8)(J) 8.130(3)(G) 8.130(6) 8.130(7)(A) 8.130(7)(B)	housing? Do wet and dry wells have separate ventilation systems? Does all potable water brought to the pump station comply with 8.140 (7) D? Is an alarm system provided with uninterrupted power? Is there 2 hours retention of the peak hourly flow for a design flow > 100,000 gpd or 4 hrs retention of the peak hourly flow for a design flow < 100,000 gpd? Is there an independent utility substation provided for emergency power that is capable of starting and operating the pump station at its rated capacity?			\ \ \ \ \ \

12.0	SUCTION LIFT	PUMP AND SUBMERSIBL	E PUMP STATION	CHECKLIST				
	REGULATION		<u> 1987 (2001) B</u>			YES	NO	N/A
41	8.130(4)	Are the suction lift pumps	of the self priming o	r vacuum prim	ing type?			V
42	8.130(4)(A)	Is the combined total of dy and required net positive s less than or equal to twen	namic suction lift at suction head at desi ty-two feet (22')?	the "pump off gn operating c	elevation onditions			V
43	8.130(4)(B)	Are there dual vacuum pu lift pump?						V
44	8.130(5)(A)	Are submersible pumps re personel entering, or disco	eadily removable an onnecting any pipe i	d replaceable on the well?	without			V
13.0	CERTIFICATIO						·	
	the requirements including the pos	hat the design plans and sp s listed above. I am aware t ssibility of fine and imprison hat this plan, specification, Licensed Professional Engi	hat there are significe ment. and/or report was pi	eant penaities repared by me	or under my	taise in	rormatio	n,
For a	any guestion ansv	vered "NO" provide explana	ition. Provide any us	eful comment	s on design fo	r review	engine	er:
	· D. C. visual	Fusing and Cook of OF	M/o M					
Miss	souri Professional	SHAWN SHAWN ON ON ON ON ON ON ON ON ON	ABC 3006489 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					
Stre	ne: Shawn Duke, P et Address: 802 F : St. Joseph	E Snyder & Associates, Inc Francis Street	ate: MO	ZIP Code:	64501			
Pho	ne Number: 816-3	364-5222	Email: sduke@sny	der-associates.c	om			