

MiTek, Inc.
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200

Re: Avalon - Craftsman
Avalon - Craftsman
1908 SW Hightown Dr
Lees Summit MO, 64082

The truss drawing(s) referenced below have been prepared by MiTek USA, Inc. under my direct supervision based on the parameters provided by Wheeler - Waverly.

Pages or sheets covered by this seal: I65139922 thru I65139974

My license renewal date for the state of Kansas is April 30, 2024.

Kansas COA: E-943



April 25, 2024

Garcia, Juan

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

MiTek, Inc.
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200

Re: Avalon - Craftsman
Avalon - Craftsman

1908 SW Hightown Dr
Lees Summit MO, 64082

The truss drawing(s) referenced below have been prepared by MiTek USA, Inc. under my direct supervision based on the parameters provided by Wheeler - Waverly.

Pages or sheets covered by this seal: I65139922 thru I65139974

My license renewal date for the state of Missouri is December 31, 2024.

Missouri COA: Engineering 001193



April 25, 2024

Garcia, Juan ,Engineer

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	A1	Hip Girder	1	4	Job Reference (optional)

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139922
LEE'S SUMMIT, MISSOURI

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15,
Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-4=-70, 4-10=-70, 10-13=-70, 2-22=-20,
11-22=-20, 12-14=-20
Concentrated Loads (lb)
Vert: 18=-278 (B), 21=-785 (B), 15=-818 (B),
26=-278 (B), 27=-278 (B), 28=-278 (B), 29=-278 (B),
30=-278 (B), 31=-278 (B), 32=-278 (B), 33=-278 (B),
34=-278 (B), 35=-260 (B), 36=-278 (B), 37=-278 (B)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	A2	Hip	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 E Jan 4 2024 Print: 8.730 E Jan 4 2024 MiTek Industries, Inc. Thu Apr 25 14:28:30 Page: 1
ID: z5TmPe?5zI29cVg_rNJ0ddzNX_b_-fufWjdGUiwGJ9seNiejTsd?UG3i8kuc5dkCMEzN8?

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:77.4

Plate Offsets (X, Y): [2:0-4-0,0-1-0], [10:0-2-10,Edge], [11:0-2-2,0-0-9], [13:0-2-10,1-7-12], [21:0-5-12,0-4-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.56	Vert(LL)	-0.50	17-19	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.59	Vert(CT)	-0.90	17-19	>557	240	M18AHS	186/179
BCLL	0.0*	Rep Stress Incr	YES	WB	0.77	Horz(CT)	0.42	11	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.37	17-19	>999	240	Weight: 307 lb	FT = 10%

LUMBER

TOP CHORD	2x6 SP 2400F 2.0E *Except* 9-12:2x8 SP 2400F 2.0E
BOT CHORD	2x6 SP 2400F 2.0E *Except* 2-21,13-11:2x8 SP 2400F 2.0E, 22-23:2x4 SPF No.2
WEBS	2x4 SPF No.2 *Except* 10-13:2x6 SPF No.2
LBR SCAB	9-12 SP 2400F 2.0E one side

BRACING

TOP CHORD	Structural wood sheathing directly applied or 3-5-2 oc purlins, except
BOT CHORD	2-0-0 oc purlins (4-0-14 max.): 4-9. Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 11-13.

REACTIONS

Max Horiz 2=-74 (LC 13)
Max Uplift 2=-278 (LC 4), 11=-276 (LC 5)

FORCES

TOP CHORD Tension
1-2=0/3, 2-3=-7265/968, 3-4=-4811/726,
4-5=-5970/994, 5-6=-5968/993,
6-7=-5968/993, 7-8=-6012/998,
8-9=-6013/999, 9-26=-4611/707,
10-26=-4777/680, 10-11=-974/152,
11-12=0/11


BOT CHORD
2-21=-856/6544, 20-21=-786/5922,
19-20=-591/4434, 18-19=-991/6573,
17-18=-991/6573, 16-17=-991/6573,
15-16=-991/6573, 14-15=-573/4481,
10-14=-577/4471, 11-13=-41/2

WEBS
10-13=-11/195, 3-21=-173/1840, 4-20=0/490,
9-14=0/327, 4-19=-343/1868, 5-19=-454/183,
7-19=-768/130, 7-17=0/256, 7-15=-721/119,
8-15=-421/179, 9-15=-351/1846,
3-20=-1481/294

NOTES

- 1) Attached 10-11-6 scab 9 to 12, front face(s) 2x8 SP 2400F 2.0E with 2 row(s) of 10d (0.131"x3") nails spaced 9" o.c. except : starting at 0-3-14 from end at joint 9, nail 2 row(s) at 7" o.c. for 2-0-0; starting at 6-7-7 from end at joint 9, nail 2 row(s) at 4" o.c. for 3-11-7.
- 2) Unbalanced roof live loads have been considered for this design.
- 3) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 4) Provide adequate drainage to prevent water ponding.
- 5) All plates are MT20 plates unless otherwise indicated.
- 6) All plates are 2x4 MT20 unless otherwise indicated.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) All bearings are assumed to be SPF No.2 crushing capacity of 425 psi.
- 10) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 278 lb uplift at joint 2 and 276 lb uplift at joint 11.
- 12) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard




April 25, 2024



WARNING – Verify design parameters and READ NOTES on this and INCLUDED MITER KEEF ELEMENTS (see MIT-1473 Rev. 1/2/2023) BEFORE USE. Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.87	Vent(LL)	-0.51	20-22	>986	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.94	Vent(CT)	-0.91	20-22	>546	240	M18AHS	142/136
BCLL	0.0*	Rep Stress Incr	YES	WB	0.63	Horz(CT)	0.44	13	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.37	20-22	>999	240	Weight: 264 lb	FT = 10%

LOAD CASE(S) Standard

STATE OF MISSOURI

JUAN GARCIA

NUMBER E-2000162101

PROFESSIONAL ENGINEER

JUAN GARCIA

LICENSED

16952

KANSAS

PROFESSIONAL ENGINEER


WARNING – Verify design parameters and READ NOTES on this and INCLUDED MITER KEEF ELEMENT ASL (MKT) 1473 (REV. 1/2/2023) BEFORE USE. Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	A4	Hip	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 165139925 LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:30 Page: 1
ID:AMpSFYh9FvFj?ARzUQYstxZNWdl-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRcDof7423Cpf

09/15/2025
1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:77.7

Plate Offsets (X, Y): [12:Edge,0-6-8], [16:0-3-0,0-2-4], [22:0-8-0,0-3-7], [23:0-5-0,0-6-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.41	17-18	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.66	Vert(CT)	-0.77	17-18	>649	240	M18AHS	142/136
BCLL	0.0*	Rep Stress Incr	YES	WB	0.85	Horz(CT)	0.35	12	n/a	n/a	MT18HS	197/144
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.28	17-18	>999	240	Weight: 165 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF 2100F 1.8E *Except* 5-8:2x4 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 22-19,19-16:2x4 SPF 2100F 1.8E, 17-15:2x3 SPF No.2
WEBS 2x3 SPF No.2 *Except* 23-2,12-10:2x6 SPF No.2, 22-2:2x4 SPF 2100F 1.8E, 16-13:2x4 SPF No.2

WEBS
3-22=58/740, 4-20=1154/288,
5-20=68/1046, 14-16=0/440, 8-16=69/1031,
9-13=614/152, 2-22=496/4953,
10-13=242/2480, 4-21=0/390,
3-21=893/148, 6-18=14/203,
6-20=913/181, 7-18=6/207, 7-16=909/183,
9-16=24/510, 13-16=287/3029

BRACING
TOP CHORD Structural wood sheathing directly applied or 2-7-2 oc purlins, except end verticals, and 2-0-0 oc purlins (2-6-11 max.): 5-8.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
6-0-0 oc bracing: 14-15.
WEBS 1 Row at midpt 4-20, 6-20, 7-16
REACTIONS (size) 12=0-3-8, 23=0-3-8
Max Horiz 23=79 (LC 13)
Max Uplift 12=232 (LC 5), 23=232 (LC 4)
Max Grav 12=1947 (LC 1), 23=1947 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/30, 2-3=6014/628, 3-4=4880/566,
4-5=3794/505, 5-6=3410/489,
6-7=4020/580, 7-8=3410/488,
8-9=3761/502, 9-10=3482/408, 10-11=0/30,
2-23=-2023/259, 10-12=-1868/264
22-23=-150/553, 21-22=-536/5372,
20-21=-457/4517, 18-20=-447/3974,
17-18=-448/3971, 16-17=-407/3894,
15-17=-272/0, 14-15=-42/77, 13-14=-32/134,
12-13=-111/659

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) All plates are MT20 plates unless otherwise indicated.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 7) All bearings are assumed to be SPF No.2 .
 - 8) Bearing at joint(s) 23 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 232 lb uplift at joint 23 and 232 lb uplift at joint 12.
 - 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	A5	Hip	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 165139926 LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:30 Page: 1
ID:q5HqtzhfPb1JIXYhfa?Y3kzNWbA-RfC?PsB70Hq3NSgPqnL8w3ulTXbGK?VrCDoIZ-0-165139926
09/15/2025
008 SW Hightown Dr
Lees Summit MO, 64082




Scale = 1:77.8									
Plate Offsets (X, Y): [12:0-5-0,0-6-4], [13:0-8-0,0-3-7], [14:0-2-8,0-1-8], [20:0-2-8,0-1-8], [21:0-8-0,0-3-7], [22:0-5-0,0-6-4]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.93	Vert(LL)	-0.48	17	>999
TCDL	10.0	Lumber DOL	1.15	BC	0.79	Vert(CT)	-0.87	15-17	>570
BCLL	0.0*	Rep Stress Incr	YES	WB	0.55	Horz(CT)	0.54	12	n/a
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.32	17	>999
							L/d	360	
								240	
								n/a	
								240	
								Weight: 168 lb	FT = 10%

LUMBER	
TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2 *Except* 21-18,16-13:2x4 SPF 2100F 1.8E
WEBS	2x3 SPF No.2 *Except* 22-2,12-10:2x6 SPF No.2, 21-2,13-10:2x4 SPF 2100F 1.8E, 23-25,24-26:2x4 SPF No.2
BRACING	
TOP CHORD	Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (2-2-0 max.): 5-7.
BOT CHORD	Rigid ceiling directly applied or 9-6-15 oc bracing.
WEBS	1 Row at midpt 3-20, 4-19, 8-15, 9-14
REACTIONS	(size) 12=0-3-8, 22=0-3-8 Max Horiz 22=94 (LC 9) Max Uplift 12=213 (LC 9), 22=213 (LC 8) Max Grav 12=1947 (LC 1), 22=1947 (LC 1)
FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/30, 2-3=6154/685, 3-4=4412/463, 4-5=3482/436, 5-6=3479/486, 6-7=3479/486, 2-22=1982/263, 10-12=1982/232, 7-8=3482/436, 8-9=4412/463, 9-10=6154/580, 10-11=0/30
BOT CHORD	21-22=-138/430, 20-21=-680/5526, 19-20=-363/4040, 17-19=-238/3132, 15-17=-238/3132, 14-15=-337/4040, 13-14=-495/5526, 12-13=-37/430
WEBS	3-21=-49/761, 3-20=-1507/322, 4-20=0/431, 4-19=-1023/261, 5-19=-53/611, 5-17=-105/670, 6-17=-537/205, 7-17=-105/670, 7-15=-46/611, 8-15=-1023/246, 8-14=0/431, 9-14=-1507/259, 9-13=-7/761, 2-21=-560/5227, 10-13=-477/5227

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2 .
- Bearing at joint(s) 22, 12 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 213 lb uplift at joint 22 and 213 lb uplift at joint 12.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 25,2024


Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	A6	Hip	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 165139927 LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 E Jan 4 2024 Print: 8.730 E Jan 4 2024 MiTek Industries, Inc. Thu Apr 25 14:11:08 Page: 1

ID:GNEEB7nAflqmZ7HxHPc7aDzNWYT-QDMUOhwSI4sJ6M09Wc2GAWVVSXrrOfRMBfMdzN8s1

09/15/2025
1908 SW Hightown Dr
Lees Summit MO, 64082




Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	A7	Hip	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW
						DEVELOPMENT SERVICES
						165139928
						LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:33 PM Page: 1
ID:UqqDauCh0iUc?cPKMLBUyuzNWU2-RfC?PsB70Hq3NSgPqnL8w3uITX6GKwRCDa7J4JC?1

09/15/2025



Scale = 1:78.1									
Plate Offsets (X, Y): [15:0-5-0,0-6-0], [16:0-8-0,0-3-7], [21:0-2-8,0-1-8], [25:0-8-0,0-3-7], [26:0-5-0,0-6-0]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	l/defl	L/d
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.98	Vert(LL)	-0.44 21	>999	360
TCDL	10.0	Lumber DOL	1.15	BC	0.80	Vert(CT)	-0.80 21-23	>623	240
BCLL	0.0*	Rep Stress Incr	YES	WB	0.70	Horz(CT)	0.50 15	n/a	n/a
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.29 21-23	>999	240
								Weight: 176 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 25-22,19-16:2x4 SPF 2100F 1.8E
WEBS 2x3 SPF No.2 *Except* 26-2,15-13:2x6 SPF No.2, 25-2,16-13:2x4 SPF 2100F 1.8E, 27-29,28-17:2x4 SPF No.2

WEBS
3-25=-105/714, 7-21=-133/774,
7-20=-244/252, 8-20=-66/775,
12-16=-50/714, 2-25=-628/5010,
13-16=-502/5010, 6-21=-969/258,
9-20=-965/249, 4-24=0/438, 3-24=-896/205,
4-23=-1294/310, 6-23=-14/531, 9-18=-4/528,
11-18=-1295/277, 11-17=0/438,
12-17=-896/135

BRACING
TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (3-4-9 max.): 7-8.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. Except: 8-8-14 oc bracing: 24-25.
WEBS 1 Row at midpt 7-20, 6-21, 9-20, 4-23, 11-18
REACTIONS (size) 15=0-3-8, 26=0-3-8
Max Horiz 26=-123 (LC 13)
Max Uplift 15=-250 (LC 9), 26=-250 (LC 8)
Max Grav 15=1947 (LC 1), 26=1947 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/30, 2-3=-6023/808, 3-4=-4898/615, 4-6=-3668/416, 6-7=-2911/338, 7-8=-2612/320, 8-9=-2913/319, 9-11=-3667/390, 11-12=-4899/556, 12-13=-6023/669, 13-14=0/30, 2-26=-2003/325, 13-15=-2003/285
BOT CHORD 25-26=-209/508, 24-25=-809/5391, 23-24=-612/4532, 21-23=-317/3298, 20-21=-135/2609, 18-20=-170/3297, 17-18=-434/4532, 16-17=-564/5391, 15-16=-78/508

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - All plates are MT20 plates unless otherwise indicated.
 - All plates are 3x4 MT20 unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - All bearings are assumed to be SPF No.2 .
 - Bearing at joint(s) 26, 15 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 250 lb uplift at joint 26 and 250 lb uplift at joint 15.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	B1	Roof Special	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 165139929 LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:11:33 PM Page: 1
ID:OxhlzhDjOvrvLroOgWhezjzX478-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKvWvCDol7J4ZJC9F

09/15/2025




Plate Offsets (X, Y): [14:0-5-0,0-6-0], [15:0-8-0,0-3-7], [16:0-2-8,0-1-8], [22:0-2-8,0-1-8], [23:0-8-0,0-3-7], [24:0-5-0,0-6-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.97	Vert(LL)	-0.44	17-19	>999	360	MT20 197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.90	Vert(CT)	-0.82	17-19	>608	240	M18AHS 142/136
BCLL	0.0*	Rep Stress Incr	YES	WB	0.87	Horz(CT)	0.51	14	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.30	21	>999	240	Weight: 167 lb FT = 10%

LUMBER	
TOP CHORD	2x4 SPF 2100F 1.8E *Except* 1-5,9-13:2x4 SPF No.2
BOT CHORD	2x4 SPF No.2 *Except* 23-20,18-15:2x4 SPF 2100F 1.8E
WEBS	2x3 SPF No.2 *Except* 24-2,14-12:2x6 SPF No.2, 23-2,15-12:2x4 SPF 2100F 1.8E, 25-27,26-16:2x4 SPF No.2
BRACING	
TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 8-4-1 oc bracing.
WEBS	1 Row at midpt 8-19, 6-19, 4-21, 10-17
REACTIONS	
(size)	14=0-3-8, 24=0-3-8
Max Horiz	24=-139 (LC 9)
Max Uplift	14=-265 (LC 9), 24=-265 (LC 8)
Max Grav	14=1947 (LC 1), 24=1947 (LC 1)
FORCES	
(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/30, 2-3=-6030/882, 3-4=-4887/664, 4-6=-3682/466, 6-7=-2676/338, 7-8=-2676/356, 8-10=-3682/437, 10-11=-4887/598, 11-12=-6030/725, 12-13=0/30, 2-24=-2001/345, 12-14=-2001/300
BOT CHORD	23-24=-227/503, 22-23=-892/5399, 21-22=-672/4518, 19-21=-383/3317, 17-19=-217/3317, 16-17=-471/4518, 15-16=-616/5399, 14-15=-79/503
WEBS	7-19=-126/1520, 8-19=-1170/304, 11-15=-54/716, 6-19=-1170/316, 3-23=-116/716, 2-23=-696/5022, 12-15=-554/5022, 4-22=0/431, 3-22=-920/230, 4-21=-1258/303, 6-21=-1/556, 8-17=0/556, 10-17=-1258/266, 10-16=0/431, 11-16=-920/152

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2.
- Bearing at joint(s) 24, 14 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 265 lb uplift at joint 24 and 265 lb uplift at joint 14.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	B2	Roof Special	4	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:31 Page: 1
ID:s8F8B0EM9ozMz?NbEECTVxzX477-RfC?PsB70Hq3NSgPqnL8w3uITXbCKWrCDn7d42a07f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139930
LEE'S SUMMIT, MISSOURI

09/15/2025



1908 SW Hightown Dr
Lees Summit MO, 64082

Scale = 1:73.7

Plate Offsets (X, Y): [13:Edge,0-8-8], [14:0-2-8,0-3-0], [17:0-5-12,Edge], [21:0-2-8,0-3-0], [22:Edge,0-6-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.36	17-18	>999	360	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.98	Vert(CT)	-0.63	17-18	>788	240	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.97	Horz(CT)	0.17	13	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.14	17-18	>999	240	Weight: 184 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x3 SPF No.2 *Except* 22-19:2x4 SPF 2100F 1.8E, 18-17,16-13:2x4 SPF No.2
WEBS 2x3 SPF No.2 *Except* 22-2,13-12:2x6 SPF No.2, 18-20:2x4 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
6-0-0 oc bracing: 19-20
2-2-0 oc bracing: 14-15.

1 Row at midpt 8-17

REACTIONS (size) 13= Mechanical, 22=0-3-8
Max Horiz 22=87 (LC 8)
Max Uplift 13=26 (LC 9), 22=39 (LC 8)
Max Grav 13=1929 (LC 2), 22=1995 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/30, 2-3=-3598/58, 3-5=-3189/65, 5-6=-3289/82, 6-7=-3268/125, 7-8=-2807/96, 8-9=-2875/63, 9-11=-3162/63, 11-12=-3480/56, 2-22=-1874/71, 12-13=-1818/56
BOT CHORD 21-22=-127/652, 20-21=-86/3251, 19-20=-42/31, 18-19=0/8, 6-18=-166/59, 17-18=0/2427, 16-17=0/103, 8-17=-260/91, 15-16=-1/88, 14-15=-12/3153, 13-14=-19/367
WEBS 5-18=0/294, 7-18=-103/1195, 7-17=-91/1106, 9-17=-475/112, 2-21=0/2618, 12-14=0/2806, 3-21=-135/104, 3-20=-479/87, 5-20=-654/33, 18-20=0/3049, 9-15=-160/83, 11-15=-411/86, 15-17=0/2812, 11-14=-208/84

NOTES

- Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- All bearings are assumed to be SPF No.2 .
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 39 lb uplift at joint 22 and 26 lb uplift at joint 13.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	B3	Hip	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW
						DEVELOPMENT SERVICES
						165139931
						LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:32 Page: 1
ID:1FPIUnMFZBMoniJiN1vSSFzX46y-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwRCDoi7J4zJG47

09/15/2025



1908 SW Hightown Dr
Lees Summit MO, 64082

Scale = 1:78.4

Plate Offsets (X, Y): [13:Edge,0-8-8], [14:0-2-8,0-3-0], [22:0-2-8,0-3-0], [23:Edge,0-6-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.86	Vert(LL)	-0.29	18-19	>999	360	MT20 197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.88	Vert(CT)	-0.52	18-19	>958	240	M18AHS 142/136
BCLL	0.0*	Rep Stress Incr	YES	WB	0.96	Horz(CT)	0.18	13	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.14	19	>999	240	Weight: 188 lb FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2 *Except* 20-6-8-16:2x3 SPF No.2
WEBS	2x3 SPF No.2 *Except* 23-2,13-12:2x6 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (3-7-7 max.): 7-8.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	1 Row at midpt 6-18

REACTIONS

(size)	13= Mechanical, 23=0-3-8
Max Horiz	23=82 (LC 8)
Max Uplift	13=21 (LC 9), 23=-34 (LC 8)
Max Grav	13=1857 (LC 1), 23=1936 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/30, 2-3=-3473/50, 3-5=-3070/55, 5-6=-3136/72, 6-7=-2696/59, 7-8=-2467/67, 8-9=-2745/49, 9-11=-3051/53, 11-12=-3359/46, 2-23=-1862/67, 12-13=-1785/52
BOT CHORD	22-23=-120/600, 21-22=-73/3123, 20-21=-8/110, 19-20=0/14, 6-19=-53/770, 18-19=0/2831, 17-18=0/2439, 16-17=0/104, 8-17=-31/646, 15-16=0/179, 14-15=-3/3030, 13-14=-19/356
WEBS	5-19=-1/288, 9-17=-484/116, 2-22=0/2536, 12-14=0/2694, 6-18=-789/89, 8-18=-165/338, 9-15=-135/106, 11-15=-401/85, 15-17=0/2583, 11-14=-208/83, 3-22=-131/107, 3-21=-477/88, 5-21=-629/32, 19-21=0/2792, 7-18=-4/795

NOTES

- 1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) All plates are MT20 plates unless otherwise indicated.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) All bearings are assumed to be SPF No.2 .
- 8) Refer to girder(s) for truss to truss connections.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 34 lb uplift at joint 23 and 21 lb uplift at joint 13.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	B4	Hip	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:32 Page: 1
ID:dgk9sIKNGG_DwE_7ivMlqdzX47?-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCD0i7J4zJG7

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139932
LEE'S SUMMIT, MISSOURI

09/15/2025



1908 SW Hightown Dr
Lees Summit MO, 64082

Scale = 1:75.4

Plate Offsets (X, Y): [13:0-3-8,0-2-4], [21:0-2-8,0-1-8], [22:0-3-8,0-2-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	-0.10	20-21	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.57	Vert(CT)	-0.19	20-21	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.61	Horz(CT)	-0.04	16	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.04	20-21	>999	240	Weight: 186 lb FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 19-6:2x3 SPF No.2
WEBS 2x3 SPF No.2 *Except* 22-2,13-12:2x6 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 4-4-5 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 7-9.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
6-0-0 oc bracing: 19-20,15-16.
WEBS 1 Row at midpt 9-16, 7-17, 11-15, 3-20

REACTIONS (size) 13= Mechanical, 16=0-3-8, 22=0-3-8
Max Horiz 22=72 (LC 10)
Max Uplift 13=69 (LC 9), 22=61 (LC 8)
Max Grav 13=827 (LC 22), 16=2192 (LC 2), 22=1004 (LC 21)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/30, 2-3=-1535/104, 3-5=-868/117, 5-6=-561/140, 6-7=-472/142, 7-8=0/314, 8-9=0/298, 2-22=-932/93, 12-13=-744/101, 9-10=-595/231, 10-11=-621/163, 11-12=-1306/148
BOT CHORD 21-22=-118/412, 20-21=-114/1353, 19-20=-55/4, 18-19=0/7, 6-18=-12/80, 17-18=0/296, 16-17=-1253/17, 8-17=-297/66, 15-16=-96/32, 14-15=-93/1148, 13-14=-29/304
WEBS 5-18=-585/80, 9-16=-858/16, 2-21=0/961, 12-14=-64/848, 7-18=-34/812, 7-17=-1015/28, 10-15=-440/131, 11-15=-723/80, 11-14=0/229, 9-15=-91/1073, 3-21=0/228, 3-20=-690/80, 5-20=0/266, 18-20=-20/805

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- All bearings are assumed to be SPF No.2 .
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 61 lb uplift at joint 22 and 69 lb uplift at joint 13.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	B5	Hip	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW
						DEVELOPMENT SERVICES
						165139933
						LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:32 Page: 1
ID:9UAnfQJIVysMI4Px8CqWIPzX470-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zV6?
09/15/2025
1008 SW Hightown Dr
Lees Summit MO, 64082



16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-LLS.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	B8	Hip	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 165139936 LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:33 Page: 1
ID:lvUe0HsC1UoRdhMT3HpgnzX473-RfC?PsB70Hq3NSgPqnL8w3ulTXbCKWvCD0rJ42u0?f

09/15/2025
1908 SW Hightown Dr
Lees Summit MO, 64082




Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	C1	Common Supported Gable	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW
						DEVELOPMENT SERVICES
						165139937
						LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:33 Page: 1
ID:zEtypsiqUj_OeJcDyUWIEozX4oP-RfC?PsB70Hq3NSgPqnL8w3ulTXbGK1WrCDoi7J42JG41

09/15/2025



1908 SW Hightown Dr
Lees Summit MO, 64082

Scale = 1:29.5									
Plate Offsets (X, Y): [10:0-3-8,Edge]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.06	Vert(LL)	n/a	-	n/a
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(CT)	n/a	-	n/a
BCLL	0.0*	Rep Stress Incr	YES	WB	0.02	Horz(CT)	0.00	10	n/a
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R					
PLATES MT20 GRIP 197/144									
Weight: 40 lb FT = 10%									

LUMBER	
TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2
OTHERS	2x4 SPF No.2

BRACING	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (size)	
	10=11-7-0, 11=11-7-0, 12=11-7-0, 13=11-7-0, 14=11-7-0, 15=11-7-0, 16=11-7-0
Max Horiz	16=30 (LC 9)
Max Uplift	10=43 (LC 5), 11=51 (LC 9), 12=51 (LC 9), 14=51 (LC 8), 15=53 (LC 8), 16=43 (LC 4)
Max Grav	10=149 (LC 22), 11=156 (LC 1), 12=197 (LC 22), 13=169 (LC 1), 14=197 (LC 21), 15=156 (LC 1), 16=149 (LC 21)

FORCES (lb) - Maximum Compression/Maximum Tension	
TOP CHORD	2-16=-134/53, 1-2=0/26, 2-3=-29/42, 3-4=-21/57, 4-5=-28/78, 5-6=-28/74, 6-7=-21/53, 7-8=-26/39, 8-9=0/26, 8-10=-134/52
BOT CHORD	15-16=-10/25, 14-15=-10/25, 13-14=-10/25, 12-13=-10/25, 11-12=-10/25, 10-11=-10/25
WEBS	5-13=-129/0, 4-14=-156/76, 3-15=-117/70, 6-12=-156/77, 7-11=-117/69

NOTES
1) Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 43 lb uplift at joint 16, 43 lb uplift at joint 10, 51 lb uplift at joint 14, 53 lb uplift at joint 15, 51 lb uplift at joint 12 and 51 lb uplift at joint 11.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-UIS.com


Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	C3	Common	4	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:33 Page: 1
ID:w0foK9PmdPsEGJ1Tct_Oc5zX46u-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDol7s4ZJC7f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139939
LEE'S SUMMIT, MISSOURI

09/15/2025



1908 SW Hightown Dr
Lees Summit MO, 64082

Scale = 1:35.9

Plate Offsets (X, Y): [2:Edge,0-3-0], [6:Edge,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.29	Vert(LL)	-0.10	8-9	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.61	Vert(CT)	-0.20	8-9	>978	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.44	Horz(CT)	0.03	7	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.02	8	>999	240	Weight: 60 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2 *Except* 9-2,7-6:2x4 SPF No.2

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 119 lb uplift at joint 9 and 95 lb uplift at joint 7.
7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

BRACING
TOP CHORD Structural wood sheathing directly applied or 5-6-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS (size) 7=0-3-8, 9=0-3-8
Max Horiz 9=56 (LC 8)
Max Uplift 7=-95 (LC 9), 9=-119 (LC 8)
Max Grav 7=750 (LC 1), 9=826 (LC 1)

LOAD CASE(S) Standard

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/27, 2-3=-275/17, 3-4=-955/112, 4-5=-955/112, 5-6=-262/5, 2-9=-282/69, 6-7=-193/37
BOT CHORD 8-9=-191/1012, 7-8=-154/1026
WEBS 4-8=0/393, 5-8=-276/185, 3-8=-261/181, 3-9=-928/185, 5-7=-953/200

- NOTES**
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
5) All bearings are assumed to be SPF No.2 .



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	D1	Common Supported Gable	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 165139940 LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:33 Page: 1
ID:zEtypsiqUj_OeJcDyUWIEozX4oP-RfC?PsB70Hq3NSgPqnL8w3ulTXbGK1VrCDoi7J42JG41

09/15/2025



Scale = 1:39.1

Plate Offsets (X, Y): [14:0-5-8,0-1-8], [24:0-5-8,0-1-8]												
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.05	Horz(CT)	0.00	14	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R							Weight: 77 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (size)
14=20-0-0, 15=20-0-0, 16=20-0-0, 17=20-0-0, 18=20-0-0, 19=20-0-0, 20=20-0-0, 21=20-0-0, 22=20-0-0, 23=20-0-0, 24=20-0-0
Max Horiz 24=60 (LC 9)
Max Uplift 14=33 (LC 5), 15=66 (LC 9), 16=44 (LC 9), 17=49 (LC 9), 18=50 (LC 9), 20=50 (LC 8), 21=49 (LC 8), 22=42 (LC 8), 23=72 (LC 8), 24=34 (LC 4)
Max Grav 14=160 (LC 22), 15=166 (LC 1), 16=184 (LC 22), 17=177 (LC 1), 18=191 (LC 22), 19=169 (LC 1), 20=191 (LC 21), 21=177 (LC 1), 22=184 (LC 21), 23=166 (LC 1), 24=160 (LC 21)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 2-24=-142/45, 1-2=0/27, 2-3=-57/52, 3-4=-34/65, 4-5=-26/87, 5-6=-25/108, 6-7=-29/128, 7-8=-29/122, 8-9=-25/95, 9-10=-26/74, 10-11=-24/53, 11-12=-46/41, 12-13=0/27, 12-14=-142/45
BOT CHORD 23-24=-12/50, 22-23=-12/50, 21-22=-12/50, 20-21=-12/50, 19-20=-12/50, 18-19=-12/50, 17-18=-12/50, 16-17=-12/50, 15-16=-12/50, 14-15=-12/50

WEBS
7-19=-129/0, 6-20=-151/74, 5-21=-137/72, 4-22=-144/69, 3-23=-126/84, 8-18=-151/74, 9-17=-137/72, 10-16=-144/70, 11-15=-126/81

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - All bearings are assumed to be SPF No.2.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 34 lb uplift at joint 24, 33 lb uplift at joint 14, 50 lb uplift at joint 20, 49 lb uplift at joint 21, 42 lb uplift at joint 22, 72 lb uplift at joint 23, 50 lb uplift at joint 18, 49 lb uplift at joint 17, 44 lb uplift at joint 16 and 66 lb uplift at joint 15.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	D2	Common	5	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871.

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:33 Page: 1
ID: RQRL1CjSF16FGTBPWB1Xn?zX4oO-RfC?PsB70Hq3NSgPqnL8w3uITXGKWrCDj7342C?1

09/15/2025



Scale = 1:37.5

Plate Offsets (X, Y): [1:Edge,0-3-0], [5:Edge,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.30	Vert(LL)	-0.19	6-7	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.85	Vert(CT)	-0.38	6-7	>615	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.97	Horz(CT)	0.04	6	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.03	7	>999	240	Weight: 70 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 8-1,6-5:2x4 SPF No.2

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 113 lb uplift at joint 8 and 113 lb uplift at joint 6.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

BRACING

TOP CHORD	Structural wood sheathing directly applied or 5-3-11 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	6=0-3-8, 8=0-3-8
Max Horiz	8=-52 (LC 9)
Max Uplift	6=-113 (LC 9), 8=-113 (LC 8)
Max Grav	6=887 (LC 1), 8=887 (LC 1)

FORCES

Tension


TOP CHORD 1-2=-457/63, 2-3=-1132/133, 3-4=-1132/133,
4-5=-457/63, 1-8=-332/91, 5-6=-332/91

BOT CHORD 7-8=-203/1244, 6-7=-151/1244

WEBS 3-7=-18/552, 4-7=-348/209, 2-7=-348/209,
2-8=-1001/156, 4-6=-1001/157

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCFL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 5) All bearings are assumed to be SPF No.2 .



April 25, 2024



WARNING – Verify design parameters and READ NOTES on this and INCLUDED MITER KEEF ELEMENTS (see MIT-1473 Rev. 1/2/2023) BEFORE USE. Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	E1	Monopitch	3	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:33 Page: 1
ID:KKpWOME_w65Da9ynn628zX476-RfC?PsB70Hq3NSgPqnL8w3uITXb3KWrcD6wJ42JC?f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139942
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:34.2

Plate Offsets (X, Y): [7:0-5-0,0-0-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.32	Vert(LL)	-0.17	6-7	>569	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.56	Vert(CT)	-0.34	6-7	>291	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.23	Horz(CT)	0.00	6	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	-0.01	6-7	>999	240	Weight: 31 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2 *Except* 7-2:2x4 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (size) 6=0-3-8, 7=0-3-8
Max Horiz 7=209 (LC 5)
Max Uplift 6=142 (LC 8), 7=57 (LC 8)
Max Grav 6=491 (LC 1), 7=434 (LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension
TOP CHORD 1-2=0/27, 2-3=-413/84, 3-4=-136/54,
4-5=-44/0, 4-6=-287/123, 2-7=-343/107
BOT CHORD 6-7=-131/334
WEBS 3-6=-346/178

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 142 lb uplift at joint
6 and 57 lb uplift at joint 7.
- 6) This truss is designed in accordance with the 2018
International Residential Code sections R502.11.1 and
R802.10.2 and referenced standard ANSI/TPI 1.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	G1	Hip Girder	1	2	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871.

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:11:34 Page: 1
ID:00uJAWSGaeNakwKErj2KnxxX46q-RfC?PsB70Hq3NSqPanL8w3uITxbGKWrcDnJ4Z2Cpf

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:53.5

Plate Offsets (X, Y): [4:0-3-8.0-1-8], [9:0-1-4.0-2-8], [15:0-1-4.0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.62	Vert(LL)	-0.06	10-12	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.33	Vert(CT)	-0.12	10-12	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.44	Horz(CT)	0.01	9	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.05	10-12	>999	240	Weight: 260 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x6 SPF No.2
WEBS	2x4 SPF No.2 *Except* 15-2,9-7:2x6 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-6.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

Max Horiz 15=31 (LC 8)
Max Uplift 9=-303 (LC 9), 13=-659 (LC 4),
15=-225 (LC 27)
Max Grav 9=1465 (LC 1), 13=3211 (LC 1),
15=110 (LC 19)

FORCES

Tension

TOP CHORD
1-2=0/30, 2-3=-145/715, 3-4=-232/1269,
4-5=-2065/489, 5-6=-2069/491,
6-7=-2566/537, 7-8=0/30, 2-15=-79/262,
7-9=-1392/322

BOT CHORD
14-15=-184/257, 13-14=-671/178,
12-13=-1272/315, 10-12=-443/2279,
9-10=-186/627

WEBS
3-14=-75/457, 6-10=0/503, 2-14=-817/232,
7-10=-332/1760, 4-13=-1988/543,
3-13=-1144/255, 6-12=-236/88,
5-12=-985/472, 4-12=-81/3595



NOTES

- 1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc, 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.

- 5) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- 3) Unbalanced roof live loads have been considered for this design.
- 4) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; $h=25$ ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) All bearings are assumed to be SPF No.2 .
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 225 lb uplift at joint 15, 303 lb uplift at joint 9 and 659 lb uplift at joint 13.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 12) "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
- 13) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 419 lb down and 91 lb up at 6-0-0, and 419 lb down and 91 lb up at 21-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15,
Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-3=-70, 3-6=-70, 6-7=-70, 7-8=-70,
9-15=-20
Concentrated Loads (lb)
Vert: 3=-112 (B), 6=-112 (B), 11=-52 (B), 14=-419
(B), 10=-449 (B), 4=-38 (B), 16=-112 (B), 17=-112
(B), 18=-112 (B), 19=-112 (B), 20=-112 (B), 21=-112
(B), 22=-52 (B), 23=-52 (B), 24=-52 (B), 25=-52 (B),
26=-52 (B)



April 25, 2024



Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcscomponents.com)

MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-IJS.com


Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	G2	Hip	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:11:34 PM 2025
ID: sPmZlqR0916yVdAsjl0siWzX46s-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKw/rCDoi7J4ZJOC

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139944
LEE'S SUMMIT, MISSOURI

09/15/2025
1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:53.6

Plate Offsets (X, Y): [3:0-4-2,Edge], [5:0-4-2,Edge], [8:0-3-4,0-2-4], [9:0-2-8,Edge], [12:0-2-8,Edge], [13:0-3-4,0-2-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.09	8-9	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.47	Vert(CT)	-0.18	8-9	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.98	Horz(CT)	0.03	8	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.04	9-11	>999	240	Weight: 101 lb FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2 *Except* 13-2,8-6:2x6 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 3-7-0 oc purlins, except end verticals, and 2-0-0 oc purlins (5-6-1 max.): 3-5.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 11-12.

REACTIONS (size) 8=0-3-8, 12=0-3-8, 13=0-3-8
Max Horiz 13=43 (LC 13)
Max Uplift 8=134 (LC 9), 12=153 (LC 4), 13=134 (LC 8)
Max Grav 8=944 (LC 1), 12=1339 (LC 1), 13=359 (LC 21)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/30, 2-3=-36/258, 3-4=-967/238, 4-5=-967/238, 5-6=-1316/193, 6-7=0/30, 2-13=-295/178, 6-8=-872/179
BOT CHORD 12-13=-287/590, 11-12=-183/35, 9-11=-105/1106, 8-9=-247/718
WEBS 3-12=-1118/229, 3-11=-204/1279, 4-11=-481/194, 5-11=-199/38, 5-9=0/274, 2-12=-677/219, 6-9=0/569

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 134 lb uplift at joint 13, 153 lb uplift at joint 12 and 134 lb uplift at joint 8.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	1908 SW Hightown Dr Lee's Summit, MO 64082 66139945 LEE'S SUMMIT, MISSOURI
Avalon - Craftsman	G3	Hip Girder	1	2	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:34 PM
ID:0hIod5rQsMHx345fsG3xMezNVpv-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4z3G?



Scale = 1:41.7									
Plate Offsets (X, Y): [1:Edge,0-5-8], [5:0-4-2,Edge], [8:0-2-0,0-4-4], [9:0-3-8,0-4-0]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	l/defl	L/d
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.59	Vert(LL)	-0.12 9-10	>999	360
TCDL	10.0	Lumber DOL	1.15	BC	0.44	Vert(CT)	-0.21 9-10	>999	240
BCLL	0.0*	Rep Stress Incr	NO	WB	0.67	Horz(CT)	0.03 7	n/a	n/a
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.08 9-10	>999	240
							PLATES	GRIP	
							MT20	197/144	
							Weight: 231 lb FT = 10%		

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x6 SP 2400F 2.0E
WEBS 2x4 SPF No.2 *Except* 11-1:2x6 SP 2400F 2.0E

BRACING
TOP CHORD Structural wood sheathing directly applied or 4-1-1 oc purlins, except end verticals, and 2-0-0 oc purlins (5-6-0 max.): 3-5.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS (size) 7=0-3-8, (req. 0-3-9), 11=0-3-8, (req. 0-3-11)
Max Horiz 11=163 (LC 26)
Max Uplift 7=489 (LC 5), 11=567 (LC 8)
Max Grav 7=4580 (LC 1), 11=4704 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-8073/957, 2-3=-6276/692, 3-4=-4888/555, 4-5=-4889/555, 5-6=-144/62, 6-7=-3936/493, 7-8=-114/34
BOT CHORD 10-11=-365/1999, 9-10=-933/7390, 8-9=-653/5661, 7-8=-198/1401
WEBS 2-10=-162/1272, 2-9=-1799/400, 3-9=-302/2871, 3-8=-1125/207, 4-8=-456/152, 5-7=-3949/473, 1-10=-606/5434, 5-8=-507/5041

NOTES
1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-6-0 oc, 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.

- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- WARNING:** Required bearing size at joint(s) 11, 7 greater than input bearing size.
- All bearings are assumed to be SPF No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 567 lb uplift at joint 11 and 489 lb uplift at joint 7.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 867 lb down and 125 lb up at 2-0-12, 867 lb down and 125 lb up at 4-0-12, 867 lb down and 125 lb up at 6-0-12, 867 lb down and 125 lb up at 8-0-12, 828 lb down and 39 lb up at 10-0-12, 826 lb down and 48 lb up at 12-0-12, 897 lb down and 70 lb up at 14-0-12, and 892 lb down and 78 lb up at 16-0-12, and 876 lb down and 81 lb up at 18-0-12 on bottom chord. The design selection of such connection device(s) is the responsibility of others.
- LOAD CASE(S)** Standard
- Dead + Roof Live (balanced), Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-3=-70, 3-5=-70, 5-6=-70, 7-11=-20
Concentrated Loads (lb)
Vert: 8=-806 (B), 12=-867 (B), 13=-867 (B), 14=-867 (B), 15=-867 (B), 16=-828 (B), 17=-820 (B), 18=-809 (B), 19=-787 (B)



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	G4	Monopitch Girder	1	2	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:34 PM 2025 Page: 1
ID:BAIOWZlLIPrF5eA1excASzNVrK-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4ZJC9f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139946
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:40.2

Plate Offsets (X, Y): [1:0-3-4,0-1-12], [5:0-3-8,0-4-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.30	Vert(LL)	-0.05	5-6	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.46	Vert(CT)	-0.08	5-6	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	NO	WB	0.62	Horz(CT)	0.01	4	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P		Wind(LL)	0.02	5-6	>999	240	Weight: 90 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x6 SP 2400F 2.0E
WEBS 2x4 SPF No.2 *Except* 6-1:2x6 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-2-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 4=0-3-8, (req. 0-4-2), 6=0-3-8, (req. 0-4-0)
Max Horiz 6=165 (LC 5)
Max Uplift 4=-175 (LC 8), 6=-135 (LC 8)
Max Grav 4=5289 (LC 15), 6=5107 (LC 18)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-5770/158, 2-3=-89/40, 3-4=-127/43, 1-6=-3035/115
BOT CHORD 5-6=-162/15, 4-5=-175/5233
WEBS 2-5=-41/4853, 2-4=-5959/235, 1-5=-115/5353

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc, 2x6 - 2 rows staggered at 0-4-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-5-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- WARNING: Required bearing size at joint(s) 4, 6 greater than input bearing size.
- All bearings are assumed to be SPF No.2.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 175 lb uplift at joint 4 and 135 lb uplift at joint 6.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 2037 lb down and 36 lb up at 0-10-12, 2033 lb down and 38 lb up at 2-10-12, 2033 lb down and 38 lb up at 3-11-4, and 2033 lb down and 38 lb up at 5-11-4, and 1845 lb down and 28 lb up at 8-1-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-3=-70, 4-6=-20
Concentrated Loads (lb)
Vert: 4=-1845 (F), 5=-1837 (F), 7=-1840 (F), 8=-1837 (F), 9=-1837 (F)



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J1	Diagonal Hip Girder	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,


Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:35 Page: 1

ID: ?ZIMXg1MuezcxpwEfN9kHZNxbI-RfC?PsB70Hq3NSgPqnL8w3uITxbGhWrCDoin34Z0C7

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139947
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:40.3

Plate Offsets (X, Y): [2:0-2-12,0-2-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.62	Vert(LL)	-0.08	6	>999	360	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.65	Vert(CT)	-0.15	5-6	>744	240	
BCLL	0.0*	Rep Stress Incr	NO	WB	0.92	Horz(CT)	0.05	5	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.07	6	>999	240	
										Weight: 35 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 7-2:2x4 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 4-6-3 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 8-11-7 oc bracing.


REACTIONS

(size)	5= Mechanical, 7=0-3-7
Max Horiz	7=138 (LC 5)
Max Uplift	5=-130 (LC 8), 7=-147 (LC 4)
Max Grav	5=535 (LC 1), 7=578 (LC 1)
(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	2-7=-571/184, 1-2=0/27, 2-3=-1565/360, 3-4=-151/32, 4-5=-199/94
BOT CHORD	6-7=-148/237, 5-6=-417/1425
WEBS	2-6=-286/1238, 3-6=0/337, 3-5=-1395/404

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 130 lb uplift at joint 5 and 147 lb uplift at joint 7.
 - 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 9) "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - 10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-4=-70, 6-7=-20, 5-6=-20
Concentrated Loads (lb)
Vert: 9=-97 (F=-48, B=-48), 10=-5 (F=-3, B=-3), 11=-56 (F=-28, B=-28)



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J2	Jack-Open	2	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:35 Page: 1
ID:hskECvFZNNgvnFrLja0tzNXck-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWCD0i7J42C4

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139948
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:26.6

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	-0.01	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 9 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-10-15 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical, 5=0-3-8
Max Horiz 5=53 (LC 5)
Max Uplift 3=-45 (LC 8), 5=-29 (LC 8)
Max Grav 3=80 (LC 1), 4=50 (LC 3), 5=207 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-181/56, 1-2=0/27, 2-3=-46/23
BOT CHORD 4-5=-18/12

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 29 lb uplift at joint 5 and 45 lb uplift at joint 3.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J3	Jack-Open	2	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,


Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:35 Page: 1

ID:6RQisEyXslmFm9VqWTHHdWzNXch-RfC?PsB70Hq3NSgPqnL8w3uITXhGKwRCda7342JC?fi

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139949
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:28.4

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.34	Vert(LL)	-0.02	5-6	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.19	Vert(CT)	-0.05	5-6	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.03	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.03	5-6	>999	240	Weight: 14 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-10-15 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical, 6=0-3-8
Max Horiz 6=86 (LC 8)
Max Uplift 3=-77 (LC 8), 6=-37 (LC 8)
Max Grav 3=147 (LC 1), 4=88 (LC 3), 6=291 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-6=-253/82, 1-2=0/27, 2-3=-78/44
BOT CHORD 5-6=-31/6, 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 37 lb uplift at joint 6 and 77 lb uplift at joint 3.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J4	Jack-Closed	11	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:35 Page: 1
ID: _CfDic?2wXGgEmpblJLDmZNXcd-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcDm7442u0C7f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139950
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:36.6

Plate Offsets (X, Y): [5:Edge,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	-0.15	6	>536	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.38	Vert(CT)	-0.27	6	>302	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.09	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.11	6	>737	240	Weight: 21 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 7-2:2x4 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10'-0" oc bracing.

REACTIONS	(size)	5= Mechanical, 7=0-3-8
	Max Horiz	7=107 (LC 5)
	Max Uplift	5=-26 (LC 8), 7=-14 (LC 8)
	Max Grav	5=298 (LC 1), 7=381 (LC 1)

FORCES	(lb) - Maximum Compression/Maximum Tension
---------------	--

TOP CHORD	2-7=-324/26, 1-2=0/27, 2-3=-175/0, 3-4=-101/17, 4-5=-190/36
BOT CHORD	6-7=-27/82, 5-6=-24/87
WEBS	3-6=-31/83

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0" tall by 2'-0" wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 14 lb uplift at joint 7 and 26 lb uplift at joint 5.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J5	Jack-Closed	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:35 Page: 1
ID:6iy8Q29BsXvqlmI50X4Gp5zNXcQ-RfC?PsB70Hq3NSgPqnL8w3uITXbGHWrCDoi734z3C7?

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139951
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:35.5

Plate Offsets (X, Y): [4:Edge,0-2-8], [5:0-5-8,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.53	Vert(LL)	-0.05	4-5	>999	360	M18AHS 142/136
TCDL	10.0	Lumber DOL	1.15	BC	0.29	Vert(CT)	-0.11	4-5	>752	240	MT20 197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.01	7	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.02	4-5	>999	240	Weight: 22 lb FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x4 SPF No.2 *Except* 3-4:2x3 SPF No.2
OTHERS	2x3 SPF No.2

8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(size) 5=0-3-8, 7= Mechanical
Max Horiz	5=85 (LC 5)
Max Uplift	5=-4 (LC 8), 7=-35 (LC 8)
Max Grav	5=380 (LC 1), 7=280 (LC 1)

FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	2-5=-338/56, 1-2=0/27, 2-3=-211/0, 4-6=0/137, 3-6=-256/137
BOT CHORD	4-5=-18/118
WEBS	3-7=-96/60

NOTES

- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 4 lb uplift at joint 5 and 35 lb uplift at joint 7.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J6	Jack-Closed	3	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:35 Page: 1
ID:6iy8Q29BsXvqlm150X4Gp5zNXcQ-RfC?PsB70Hq3NSgPqnL8w3uITXbGHWrCDoi734z3C7?

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139952
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:31.4

Plate Offsets (X, Y): [5:Edge,0-2-8], [6:0-3-0,0-0-8], [8:0-5-8,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	-0.10	5-6	>809	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.55	Vert(CT)	-0.20	5-6	>399	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.09	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.07	5-6	>999	240	Weight: 22 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 7-6:2x3 SPF No.2
WEBS 2x4 SPF No.2 *Except* 4-5:2x3 SPF No.2

7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6'-0" oc bracing.

REACTIONS (size) 5= Mechanical, 8=0-3-8
Max Horiz 8=106 (LC 5)
Max Uplift 5=26 (LC 8), 8=14 (LC 8)
Max Grav 5=298 (LC 1), 8=381 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-8=-375/37, 1-2=0/27, 2-3=-233/11, 3-4=-131/12, 4-5=-187/45
BOT CHORD 7-8=-45/129, 6-7=-5/48, 3-6=-64/50, 5-6=-19/65

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0" tall by 2'-0" wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 14 lb uplift at joint 8 and 26 lb uplift at joint 5.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J7	Jack-Open	2	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:35 Page: 1
ID: ?ZIMXg1MuezcxqpwEfN9kHZNxbI-RfC?PsB70Hq3NSgPqnL8w3uITXbGhWrCDoin34Z0C77

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139953
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:26.6

Plate Offsets (X, Y): [6:0-2-0,0-0-8], [8:0-5-8,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.26	Vert(LL)	-0.03	5-6	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.28	Vert(CT)	-0.06	5-6	>984	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.03	5	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.03	5-6	>999	240	Weight: 15 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 7-6:2x3 SPF No.2
WEBS 2x4 SPF No.2

7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-10-15 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (size) 4= Mechanical, 5= Mechanical, 8=0-3-8
Max Horiz 8=87 (LC 8)
Max Uplift 4=-61 (LC 8), 8=-30 (LC 8)
Max Grav 4=133 (LC 1), 5=97 (LC 3), 8=305 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-8=-293/58, 1-2=0/27, 2-3=-153/0, 3-4=-49/41
BOT CHORD 7-8=-46/76, 6-7=-4/46, 3-6=-76/46, 5-6=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 30 lb uplift at joint 8 and 61 lb uplift at joint 4.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J8	Jack-Open	2	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:35 Page: 1
ID: ?ZIMXg1MuezcxpwEfN9kHZNxbI-RfC?PsB70Hq3NSgPqnL8w3uITXbGhWrCDoin34Z0C77

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139954
LEE'S SUMMIT, MISSOURI

09/15/2025
1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:32.1

Plate Offsets (X, Y): [8:0-5-8,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.08	Vert(LL)	0.00	3	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.07	Vert(CT)	0.00	3-6	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	5	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	3	>999	240	Weight: 10 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 7-6:2x3 SPF No.2
WEBS 2x4 SPF No.2

7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-10-15 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

(size) 4= Mechanical, 5= Mechanical, 8=0-3-8
Max Horiz 8=53 (LC 8)
Max Uplift 4=30 (LC 8), 5=2 (LC 8), 8=24 (LC 8)
Max Grav 4=66 (LC 1), 5=72 (LC 3), 8=216 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-8=-196/45, 1-2=0/27, 2-3=-69/0, 3-4=-21/21
BOT CHORD 7-8=-16/25, 6-7=0/42, 3-6=-25/16, 5-6=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 24 lb uplift at joint 8, 30 lb uplift at joint 4 and 2 lb uplift at joint 5.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J9	Diagonal Hip Girder	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:35 Page: 1
ID: Tlskl01_fy5TZ_O7oNuOHVzNXbH-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCD0i734z307

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139955
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:38.4

Plate Offsets (X, Y): [3:0-3-7,0-1-14], [5:0-3-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.60	Vert(LL)	-0.21	6	>552	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.51	Vert(CT)	-0.44	3-5	>261	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.15	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.20	6	>558	240	Weight: 42 lb	FT = 10%

LUMBER

TOP CHORD	2x6 SP 2400F 2.0E
BOT CHORD	2x4 SPF 2100F 1.8E *Except* 6-3:2x4 SPF No.2
WEBS	2x4 SPF No.2 *Except* 4-5:2x3 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS	(size) 5= Mechanical, 7=0-4-9
	Max Horiz 7=134 (LC 5)
	Max Uplift 5=-111 (LC 8), 7=-148 (LC 4)
	Max Grav 5=568 (LC 1), 7=621 (LC 1)

FORCES	(lb) - Maximum Compression/Maximum Tension
--------	--

TOP CHORD	2-7=-603/170, 1-2=0/27, 2-3=-187/16,
	3-4=-184/25, 4-5=-397/156

BOT CHORD	6-7=-37/0, 3-6=0/76, 3-5=-26/108
-----------	----------------------------------

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 148 lb uplift at joint 7 and 111 lb uplift at joint 5.

- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 8) "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - 9) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-3=-70, 3-4=-70, 6-7=-20, 3-5=-20
Concentrated Loads (lb)
Vert: 9=-68 (F=-34, B=-34), 10=-50 (F=-25, B=-25), 11=-99 (F=-49, B=-49)



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J10	Diagonal Hip Girder	2	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:36 PM Page: 1
ID:WRzgi7NtKUUFPrIuxlQh?TzX46x-RfC?PsB70Hq3NSgPqnL8w3uITXbGKw/rCDoi7J4zJC2

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139956
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:39.3

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.46	Vert(LL)	-0.03	5-6	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.32	Vert(CT)	-0.06	5-6	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.24	Horz(CT)	0.01	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.02	5-6	>999	240	Weight: 28 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2 *Except* 7-2:2x4 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 5= Mechanical, 7=0-4-9
Max Horiz 7=135 (LC 5)
Max Uplift 5=-97 (LC 8), 7=-131 (LC 4)
Max Grav 5=396 (LC 1), 7=487 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-7=-417/144, 1-2=0/27, 2-3=-549/103,
3-4=-107/29, 4-5=-142/61
BOT CHORD 6-7=-131/462, 5-6=-131/462
WEBS 3-6=0/173, 3-5=-484/144

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 131 lb uplift at joint 7 and 97 lb uplift at joint 5.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

- 8) "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - 9) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-4=-70, 5-7=-20
Concentrated Loads (lb)
Vert: 9=-30 (F=-15, B=-15), 10=3 (F=1, B=1), 11=-29 (F=-15, B=-15)



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J11	Jack-Open	4	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:36 PM Page: 1
ID:KKpWOME_w65Da9ynnrxk628zX476-RfC?PsB70Hq3NSgPqnL8w3uITXb3KWrcD6WJ42JC?f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139957
LEE'S SUMMIT, MISSOURI

1908 SW Hightown Dr
Lees Summit MO, 64082

-0-10-8	1-10-15
0-10-8	1-10-15



Scale = 1:23.1

Plate Offsets (X, Y): [5:0-5-8,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	4-5	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(CT)	0.00	4-5	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 6 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 1-10-15 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical, 5=0-3-8
Max Horiz 5=41 (LC 5)
Max Uplift 3=-29 (LC 8), 5=-32 (LC 4)
Max Grav 3=44 (LC 1), 4=32 (LC 3), 5=171 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-150/47, 1-2=0/27, 2-3=-32/12
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 32 lb uplift at joint 5 and 29 lb uplift at joint 3.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J12	Jack-Open	4	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:36 Page: 1
ID:KKpWOME_w65Da9ynn628zX476-RfC?PsB70Hq3NSgPqnL8w3uITXb3KWrcD6WJ42JC?i

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139958
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:24.8

Plate Offsets (X, Y): [5:0-5-8,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.19	Vert(LL)	-0.01	4-5	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.12	Vert(CT)	-0.02	4-5	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.01	3	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.01	4-5	>999	240	Weight: 11 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-10-15 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical, 5=0-3-8
Max Horiz 5=70 (LC 8)
Max Uplift 3=-61 (LC 8), 5=-34 (LC 8)
Max Grav 3=114 (LC 1), 4=70 (LC 3), 5=248 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-217/69, 1-2=0/27, 2-3=-62/34
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 34 lb uplift at joint 5 and 61 lb uplift at joint 3.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	J13	Jack-Open	9	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:36 PM 2025
ID:KbKxyASevKEp7ml2H?X5EkzX46r-RfC?PsB70Hq3NSgPqnL8w3ulTXbGLWwCDon74429C7f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139959
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:26.7

Plate Offsets (X, Y): [5:0-5-8,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	-0.05	4-5	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.32	Vert(CT)	-0.12	4-5	>593	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.05	3	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.06	4-5	>999	240	Weight: 16 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 6'-0'-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10'-0'-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical, 5=0-3-8
Max Horiz 5=105 (LC 8)
Max Uplift 3=92 (LC 8), 5=43 (LC 8)
Max Grav 3=182 (LC 1), 4=109 (LC 3), 5=338 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-295/98, 1-2=0/27, 2-3=-96/55
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0"-0 tall by 2'-0"-0 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 43 lb uplift at joint 5 and 92 lb uplift at joint 3.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	LAY1	Lay-In Gable	2	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:36 Page: 1
ID:vc?jEYk40KE6tdmb4uYmKDzX4oN-RFC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoh7423C#f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139960
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:79.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.12	Horiz(TL)	0.00	9	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 103 lb FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x4 SPF No.2
OTHERS	2x4 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

WEBS 1 Row at midpt 8-9, 5-12, 6-11, 7-10

REACTIONS	(size)	1=13-10-9, 9=13-10-9, 10=13-10-9, 11=13-10-9, 12=13-10-9, 13=13-10-9, 14=13-10-9, 15=13-10-9
Max Horiz		1=593 (LC 8)
Max Uplift		1=-195 (LC 6), 9=-48 (LC 8), 10=-133 (LC 8), 11=-131 (LC 8), 12=-122 (LC 8), 13=-131 (LC 8), 14=-129 (LC 8), 15=-131 (LC 8)
Max Grav		1=600 (LC 8), 9=73 (LC 15), 10=214 (LC 15), 11=206 (LC 15), 12=198 (LC 15), 13=207 (LC 15), 14=205 (LC 15), 15=208 (LC 15)

FORCES

	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	8-9=-59/55, 1-2=-832/326, 2-3=-709/278, 3-4=-578/228, 4-5=-447/179, 5-7=-321/131, 7-8=-70/36
BOT CHORD	1-15=-2/2, 14-15=-2/2, 13-14=-2/2, 12-13=-2/2, 11-12=-2/2, 10-11=0/0, 9-10=0/0
WEBS	2-15=-163/148, 3-14=-166/155, 4-13=-166/155, 5-12=-158/146, 6-11=-166/155, 7-10=-173/160

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) All plates are 2x4 MT20 unless otherwise indicated.
- 4) Gable requires continuous bottom chord bearing.
- 5) Gable studs spaced at 2-0-0 oc.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) All bearings are assumed to be SPF No.2.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 48 lb uplift at joint 9, 195 lb uplift at joint 1, 131 lb uplift at joint 15, 129 lb uplift at joint 14, 131 lb uplift at joint 13, 122 lb uplift at joint 12, 131 lb uplift at joint 11 and 133 lb uplift at joint 10.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	LAY2	Lay-In Gable	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,


Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:36 Page: 1

ID: oWMuciFchQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3ulTXbCkKWrdDn7J4zG0?f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139961
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:52.3

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.06	Vert(LL)	n/a	-	n/a	999	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(TL)	n/a	-	n/a	999	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.11	Horiz(TL)	0.01	9	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							
										Weight: 78 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x4 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	1 Row at midpt 5-13

REACTIONS

(size)	1=15-9-11, 9=15-9-11, 10=15-9-11, 11=15-9-11, 12=15-9-11, 13=15-9-11, 14=15-9-11, 15=15-9-11, 16=15-9-11
Max Horiz	1=-220 (LC 4)
Max Uplift	1=-94 (LC 6), 9=-58 (LC 7), 10=-130 (LC 9), 11=-132 (LC 9), 12=-127 (LC 9), 14=-129 (LC 8), 15=-132 (LC 8), 16=-131 (LC 8)
Max Grav	1=203 (LC 8), 9=179 (LC 9), 10=208 (LC 16), 11=205 (LC 16), 12=210 (LC 16), 13=196 (LC 9), 14=212 (LC 15), 15=204 (LC 15), 16=209 (LC 15)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-293/188, 2-3=-169/140, 3-4=-136/102, 4-5=-108/164, 5-6=-86/142, 6-7=-99/65, 7-8=-141/91, 8-9=-260/139
BOT CHORD	1-16=-96/203, 15-16=-96/203, 14-15=-96/203, 13-14=-96/203, 12-13=-96/203, 11-12=-96/203, 10-11=-96/203, 9-10=-96/203
WEBS	2-16=-163/149, 3-15=-165/157, 4-14=-173/152, 8-10=-163/149, 7-11=-166/158, 6-12=-171/150, 5-13=-173/21

NOTES

- 1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) All bearings are assumed to be SPF No.2.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 94 lb uplift at joint 1, 58 lb uplift at joint 9, 131 lb uplift at joint 16, 132 lb uplift at joint 15, 129 lb uplift at joint 14, 130 lb uplift at joint 10, 132 lb uplift at joint 11 and 127 lb uplift at joint 12.
- 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	LAY3	Lay-In Gable	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:36 PM
ID:oWMuciFchQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3uITXbCkWrCDorJ42u0?ft

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139962
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:71.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.10	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.07	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.15	0.01	11	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							
										Weight: 127 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

WEBS

6-17=-260/38, 5-18=-175/148,
4-19=-167/161, 3-20=-150/139,
2-21=-214/196, 7-16=-171/145,
8-15=-169/162, 9-13=-150/139,
10-12=-215/196

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 6-17, 5-18, 7-16


REACTIONS (size)
1=21-9-11, 11=21-9-11,
12=21-9-11, 13=21-9-11,
15=21-9-11, 16=21-9-11,
17=21-9-11, 18=21-9-11,
19=21-9-11, 20=21-9-11,
21=21-9-11
Max Horiz 1=-307 (LC 4)
Max Uplift 1=-121 (LC 6), 11=-70 (LC 7),
12=-176 (LC 9), 13=-114 (LC 9),
15=-139 (LC 9), 16=-121 (LC 9),
18=-124 (LC 8), 19=-137 (LC 8),
20=-114 (LC 8), 21=-176 (LC 8)
Max Grav 1=278 (LC 8), 11=245 (LC 9),
12=279 (LC 16), 13=182 (LC 16),
15=211 (LC 16), 16=211 (LC 16),
17=284 (LC 9), 18=214 (LC 15),
19=209 (LC 15), 20=182 (LC 15),
21=279 (LC 15)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-406/263, 2-3=-239/190, 3-4=-174/148,
4-5=-149/166, 5-6=-120/228, 6-7=-94/205,
7-8=-96/120, 8-9=-123/79, 9-10=-193/121,
10-11=-360/194
BOT CHORD 1-21=-136/289, 20-21=-136/289,
19-20=-136/289, 18-19=-136/289,
17-18=-136/289, 16-17=-136/289,
15-16=-136/289, 13-15=-136/289,
12-13=-136/289, 11-12=-136/289

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 121 lb uplift at joint 1, 70 lb uplift at joint 11, 124 lb uplift at joint 18, 137 lb uplift at joint 19, 114 lb uplift at joint 20, 176 lb uplift at joint 21, 121 lb uplift at joint 16, 139 lb uplift at joint 15, 114 lb uplift at joint 13 and 176 lb uplift at joint 12.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	V1	Valley	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:36 Page: 1
ID:oWMuciFchQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3uITXbCKWwCD0rJ42u0?r

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139963
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:28.9

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.26	Vert(LL)	n/a	-	n/a	999	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.14	Vert(TL)	n/a	-	n/a	999	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.07	Horiz(TL)	0.00	4	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							
										Weight: 24 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2
OTHERS	2x3 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6'-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10'-0-0 oc bracing.

REACTIONS

(size)	1=8-11-4, 4=8-11-4, 5=8-11-4
Max Horiz	1=148 (LC 7)
Max Uplift	4=-23 (LC 5), 5=-121 (LC 8)
Max Grav	1=144 (LC 1), 4=128 (LC 1), 5=455 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD	1-2=-115/70, 2-3=-101/28, 3-4=-100/40
BOT CHORD	1-5=-48/36, 4-5=-48/36
WEBS	2-5=-353/181

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 4'-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06-00 tall by 2'-00-00 wide will fit between the bottom chord and any other members.
- 7) All bearings are assumed to be SPF No.2.

- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 23 lb uplift at joint 4 and 121 lb uplift at joint 5.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	V2	Valley	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:37 Page: 1
ID:oWMuciFchQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3ulTXbCKWwCDorJ42zG?f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139964
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:24.5

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.74	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.40	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 17 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=6-11-4, 3=6-11-4


Max Horiz 1=111 (LC 5)
Max Uplift 1=40 (LC 8), 3=62 (LC 8)
Max Grav 1=274 (LC 1), 3=274 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-99/66, 2-3=-213/99
BOT CHORD 1-3=-36/27

NOTES

- Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 40 lb uplift at joint 1 and 62 lb uplift at joint 3.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	V3	Valley	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:37 Page: 1
ID:oWMucifChQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3ulTXbCKWwCD0rJ42dC?f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139965
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:21.3

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.31	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 12 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=4-11-4, 3=4-11-4

Max Horiz 1=75 (LC 5)
Max Uplift 1=-27 (LC 8), 3=-42 (LC 8)
Max Grav 1=184 (LC 1), 3=184 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-67/44, 2-3=-143/66
BOT CHORD 1-3=-24/18

NOTES

- Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 27 lb uplift at joint 1 and 42 lb uplift at joint 3.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	V4	Valley	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:37 Page: 1
ID:oWMuciFchQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3uITXbCKWwCDorJ42dC?f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139966
LEE'S SUMMIT, MISSOURI

1908 SW Hightown Dr
Lees Summit MO, 64082

09/15/2025



Scale = 1:18

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 7 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=2-11-4, 3=2-11-4

Max Horiz 1=38 (LC 5)
Max Uplift 1=-14 (LC 8), 3=-21 (LC 8)
Max Grav 1=94 (LC 1), 3=94 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-34/23, 2-3=-73/34
BOT CHORD 1-3=-12/9

NOTES

- Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 14 lb uplift at joint 1 and 21 lb uplift at joint 3.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	V5	Valley	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:37 Page: 1
ID:oWMuciFchQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3ulTXbCCKWwCDorJ4z2C?f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139967
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:27.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.21	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.11	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.06	Horiz(TL)	0.00	4	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P						Weight: 21 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2
OTHERS	2x3 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	1=7-11-4, 4=7-11-4, 5=7-11-4
Max Horiz	1=129 (LC 5)
Max Uplift	4=-24 (LC 8), 5=-107 (LC 8)
Max Grav	1=98 (LC 1), 4=138 (LC 1), 5=401 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD	1-2=-104/57, 2-3=-94/31, 3-4=-108/43
BOT CHORD	1-5=-42/32, 4-5=-42/32
WEBS	2-5=-312/160

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 4-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) All bearings are assumed to be SPF No.2 .

- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 24 lb uplift at joint 4 and 107 lb uplift at joint 5.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	V7	Valley	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:37 Page: 1
ID:oWMuciFchQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3uITXbCKWwCDorJ4z2C?f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139969
LEE'S SUMMIT, MISSOURI

09/15/2025
1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:19.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.17	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.09	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 9 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=3-11-4, 3=3-11-4

Max Horiz 1=57 (LC 5)
Max Uplift 1=-20 (LC 8), 3=-32 (LC 8)
Max Grav 1=139 (LC 1), 3=139 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-50/33, 2-3=-108/50
BOT CHORD 1-3=-18/14

NOTES

- Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 20 lb uplift at joint 1 and 32 lb uplift at joint 3.



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	V8	Valley	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:37 Page: 1

ID:GjwGp2GESjMxqT69vMma7ZzX474-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDomJ42JC?f

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:44.4

[illegible]

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x3 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.); 3-4.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	1=23-7-13, 6=23-7-13, 7=23-7-13, 9=23-7-13, 10=23-7-13, 11=23-7-13
Max Horiz	1=66 (LC 12)
Max Uplift	1=-12 (LC 8), 6=-27 (LC 9), 7=-139 (LC 9), 9=-15 (LC 5), 10=-18 (LC 4), 11=-138 (LC 8)
Max Grav	1=190 (LC 1), 6=199 (LC 1), 7=498 (LC 1), 9=307 (LC 22), 10=327 (LC 21), 11=490 (LC 1)

FORCES

Tension

TOP CHORD 1-2=-89/77, 2-3=-86/98, 3-4=-27/99,
4-5=-86/87, 5-6=-69/63

BOT CHORD 1-11=-1/54, 10-11=-1/54, 9-10=0/54,
7-9=-2/55, 6-7=-2/55


WEBS 3-10=-253/66, 2-11=-374/191, 4-9=-240/60,
5-7=-378/192

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- 4) Provide adequate drainage to prevent water ponding.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 4-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) All bearings are assumed to be SPF No.2 .
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 12 lb uplift at joint 1, 27 lb uplift at joint 6, 18 lb uplift at joint 10, 138 lb uplift at joint 11, 15 lb uplift at joint 9 and 139 lb uplift at joint 7.
- 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 25, 2024

 WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

WARNING – Verify design parameters and READ NOTES on this and INCLUDED WITH REFERENCE ASCE MIP 473 Rev. 1/2/2023 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinet.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman	RELEASE FOR CONSTRUCTION
Avalon - Craftsman	V9	Valley	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW
						DEVELOPMENT SERVICES
						165139971
						LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:37 Page: 1

ID:oWMuciFchQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3uITXb6KvW6C000Jm430Pr

09/15/2025
908 SW Hightown Dr
Lees Summit MO, 64082



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.31	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.08	Horiz(TL)	0.00	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 51 lb	FT = 10%

LUMBER		
TOP CHORD	2x4 SPF No.2	
BOT CHORD	2x4 SPF No.2	
OTHERS	2x3 SPF No.2	
BRACING		
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.	
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	
REACTIONS	(size)	1=19-7-13, 5=19-7-13, 6=19-7-13, 7=19-7-13, 8=19-7-13
	Max Horiz	1=67 (LC 12)
	Max Uplift	1=-15 (LC 8), 5=-26 (LC 9), 6=-138 (LC 9), 8=-138 (LC 8)
	Max Grav	1=193 (LC 1), 5=193 (LC 1), 6=508 (LC 22), 7=245 (LC 1), 8=508 (LC 21)
FORCES	(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-87/79, 2-3=-90/100, 3-4=-90/90, 4-5=-67/66	
BOT CHORD	1-8=-2/54, 7-8=-2/54, 6-7=-2/54, 5-6=-2/54	
WEBS	3-7=-191/16, 2-8=-386/193, 4-6=-386/193	

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) Gable requires continuous bottom chord bearing.
 - 5) Gable studs spaced at 4-0-0 oc.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) All bearings are assumed to be SPF No.2 .
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 15 lb uplift at joint 1, 26 lb uplift at joint 5, 138 lb uplift at joint 8 and 138 lb uplift at joint 6.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	V10	Valley	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:37
ID: oWMuciFchQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3uITXb0KWwCD0rJ42z0C?ft

RELEASE FOR CONSTRUCTION

AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139972
LEE'S SUMMIT, MISSOURI

09/15/2025



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.09	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.06	Horiz(TL)	0.00	5	n/a	n/a	Weight: 39 lb
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							FT = 10%

LUMBER	
TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x3 SPF No.2
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS (size)	
	1=15-7-13, 5=15-7-13, 6=15-7-13, 7=15-7-13, 8=15-7-13
Max Horiz	1=52 (LC 12)
Max Uplift	1=-10 (LC 9), 5=-9 (LC 9), 6=-107 (LC 9), 8=-107 (LC 8)
Max Grav	1=111 (LC 1), 5=111 (LC 1), 6=381 (LC 22), 7=313 (LC 1), 8=381 (LC 21)
FORCES (lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-70/46, 2-3=-87/78, 3-4=-87/66, 4-5=-53/36
BOT CHORD	1-8=0/42, 7-8=0/42, 6-7=0/42, 5-6=0/42
WEBS	3-7=-234/42, 2-8=-298/150, 4-6=-298/150

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) Gable requires continuous bottom chord bearing.
 - 5) Gable studs spaced at 4-0-0 oc.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) All bearings are assumed to be SPF No.2 .
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 1, 9 lb uplift at joint 5, 107 lb uplift at joint 8 and 107 lb uplift at joint 6.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	V11	Valley	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:38 Page: 1
ID:oWMucifChQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3uITXbC6KWwCD0rJ42z0C?r

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
165139973
LEE'S SUMMIT, MISSOURI

09/15/2025

1908 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:27.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.37	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.22	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.07	Horiz(TL)	0.00	3	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S						Weight: 27 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x3 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(size)	1=11-7-13, 3=11-7-13, 4=11-7-13
	Max Horiz	1=-38 (LC 13)
	Max Uplift	1=-44 (LC 8), 3=-50 (LC 9), 4=-32 (LC 8)
	Max Grav	1=211 (LC 21), 3=211 (LC 22), 4=507 (LC 1)

FORCES

	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=-108/56, 2-3=-108/42
BOT CHORD	1-4=-2/43, 3-4=-2/43
WEBS	2-4=-353/93

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 44 lb uplift at joint 1, 50 lb uplift at joint 3 and 32 lb uplift at joint 4.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Avalon - Craftsman
Avalon - Craftsman	V12	Valley	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Apr 3 2024 Print: 8.730 S Apr 3 2024 MiTek Industries, Inc. Wed Apr 24 12:41:38 Page: 1

ID:oWMuciFchQD4CJXzLeFLbMzX475-RfC?PsB70Hq3NSgPqnL8w3ulTXb0KWrcDofJ4zJc?f

Wed Apr 24 12:11:38 PM CDT Page: 1
00KWRCD00142JC?f
1008 SW Hightown Dr
Lees Summit MO, 64082



Scale = 1:23.2

[illegible]

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x3 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size) 1=7-7-13, 3=7-7-13, 4=7-7-13
 Max Horiz 1=23 (LC 13)
 Max Uplift 1=33 (LC 8), 3=37 (LC 9), 4=7 (LC 8)
 Max Grav 1=142 (LC 1), 3=142 (LC 1), 4=278 (LC 1)

FORCES

FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=-57/33, 2-3=-57/23
BOT CHORD	1-4=-1/24, 3-4=-1/24
WEBS	2-4=-200/54

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) Gable requires continuous bottom chord bearing.
- 5) Gable studs spaced at 4-0-0 oc.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) All bearings are assumed to be SPF No.2 .
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 33 lb uplift at joint 1, 37 lb uplift at joint 3 and 7 lb uplift at joint 4.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



April 25, 2024



WARNING – Verify design parameters and READ NOTES ON THIS and INCLUDED MITER KNOT REFERENCE ASSEMBLY DRAWINGS BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinet.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcscomponents.com)


MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-UIS.com

Symbols

PLATE LOCATION AND ORIENTATION

Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



This symbol indicates the required direction of slots in connector plates.


* Plate location details available in MITek software or upon request.

PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.

Industry Standards:
ANSI/TP11: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-22: Design Standard for Bracing.
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

Numbering System

6-4-8 dimensions shown in ft-in-sixteenths (Drawings not to scale)



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

Product Code Approvals

ICC-ES Reports:

ESR-1988, ESR-2362, ESR-2685, ESR-3282
ESR-4722, ESL-1388

Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 1 section 6.3. These truss designs rely on lumber values established by others.

© 2023 MITek® All Rights Reserved



MITek Engineering Reference Sheet: MII-7473 rev. 1/2/2023

General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.