LEE'S SUMMIT FIRE DEPARTMENT

FIRE HEADQUARTERS 207 SE DOUGLAS STREET LEE'S SUMMIT, MISSOURI 64063-2372 (816) 969-1300 FAX (816) 969-1313 TDU (816) 969-7407

PLAN REVIEW CONDITIONS

April 23, 2013

BRR ARCHITECTURE 6700 ANTIOCH PLAZA SUITE 300 MERRIAM KS, KS 66204

Permit No:	PRCOM20130393
Project Title:	FREDDY'S STEAKBURGERS
Project Address:	194 NW OLDHAM PKWY, LEES SUMMIT, MO 64081
Parcel Number:	62140031600000000
Location:	SUMMIT SHOPPING CENTER LOT 1
Type of Work:	NEW COMMERCIAL
Occupancy Group:	ASSEMBLY FOR FOOD AND DRINK INC BARS, RESTAURANTS, BANQUET HALLS
Description:	RESTAURANT

The following is a list of requirements from the City of Lee's Summit that have not been satisfactorily addressed in the plans and specifications. Please contact the appropriate department regarding clarification of comments.

Codes Administration (816) 969-1200

Fire Department (816) 969-1300

Building Plan Review Reviewed By: Michael Weisenborn Pending

1. Per the Lee's Summit Water Utilities Department, the existing water meter at this location is a one inch. I have included in the permit fee the cost of a new meter setup as they will not allow the existing setup to be reused. The tap fee is not being charged. The fittings provided are one inch and the service line coming out of the meter will need to one inch for a minimum of ten feet. At that time the service can transition to a larger size.

Action required - This comment is for information purposes.

2. 2006 IPC 608.3 - Devices, appurtenances, appliances and apparatus. All devices, appurtenances, appliances and apparatus intended to serve some special function, such as sterilization, distillation, processing, cooling, or storage of ice or foods, and that connect to the water supply system, shall be provided with protection against backflow and contamination of the water supply system. Water pumps, filters, softeners, tanks and all other appliances and devices that handle or treat potable water shall be protected against contamination.

Action required - Note 15 on Sheet P102 indicates a backflow preventer is to be installed on the tea brewer but not the ice machine. Make needed corrections.

3. The Lee's Summit Water Department requires a dougle check valve assembly on irrigation systems.

Action required - Make needed corrections.

Fire Plan Review Reviewed By: Brian Austerman Approved with Conditions

1. 2006 IFC 609.2- Where required. A Type I hood shall be installed at or above all commercial cooking appliances and domestic cooking appliances used for commercial purposes that produce grease vapors.

Fryer #34 needs a type 1 protected hood, not shown on plans. Per a phone conversation with Bill (Hockenbergs Design) this hood is part of a 6 gallon shared system, both hoods are activated with the manual pull. Verified on inspection

4/23/2013- PROVIDE PLANS FOR BOTH TYPE 1 HOODS

2. 2006 IFC 904.11.5- Portable fire extinguishers for commercial cooking equipment. Portable fire extinguishers shall be provided within a 30-foot (9144 mm) travel distance of commercial-type cooking equipment. Cooking equipment involving vegetable or animal oils and fats shall be protected by a Class K rated portable extinguisher.

Place K class under the manual release for the hood systems along with instructions. Verified at inspection ADDRESSED IN RESUB

3. 2006 IFC 506.1- Where required. Where access to or within a structure or an area is restricted because of secured openings or where immediate access is necessary for life-saving or fire-fighting purposes, the fire code official is authorized to require a key box to be installed in an approved location. The key box shall be of an approved type and shall contain keys to gain necessary access as required by the fire code official.

Call 816.969.1316 to obtain a knox box application. Knox box is to be located underneath the outside horn strobe

ADDRESSED IN RESUB

4. 2006 IFC 901.2- Construction documents. The fire code official shall have the authority to require construction documents and calculations for all fire protection systems and to require permits be issued for the installation, rehabilitation or modification of any fire protection system. Construction documents for fire protection systems shall be submitted for review and approval prior to system installation.

Provide sprinkler plans for approval

5. 2006 IFC 907.1.1- Construction documents. Construction documents for fire alarm systems shall be submitted for review and approval prior to system installation. Construction documents shall include, but not be limited to, all of the following: 1. A floor plan which indicates the use of all rooms. 2. Locations of alarm-initiating and notification appliances. 3. Alarm control and trouble signaling equipment. 4. Annunciation. 5. Power connection. 6. Battery calculations. 7. Conductor type and sizes. 8. Voltage drop calculations. 9. Manufacturers, model numbers and listing information for equipment, devices and materials. 10. Details of ceiling height and construction. 11. The interface of fire safety control functions.

Provide alarm plans for approval

6. 904.11.1 Manual system operation.

A manual actuation device shall be located at or near a means of egress from the cooking area a minimum of 10 feet (3048 mm) and a maximum of 20 feet (6096 mm) from the kitchen exhaust system. The manual actuation device shall be installed not more than 48 inches (1200 mm) nor less than 42 inches (1067 mm) above the floor and shall clearly identify the hazard protected. The manual actuation shall require a maximum force of 40 pounds (178 N) and a maximum movement of 14 inches (356 mm) to actuate the fire suppression system.

SHOW LOCATION FOR MANUAL PULL FOR KITCHEN HOODS. THIS IS A SHARED SYSTEM, LOCATE MANUAL PULL ACCORDING TO DISTANCE REQUIREMENTS LISTED ABOVE

The approval of plans and specifications does not permit the violation of any section of the Building Codes or other City Ordinances or State Law.

The review conducted by the City of Lee's Summit Codes Administration Department shall not be construed as a structural review of the project.