



Kansas City Testing Engineering, LLC
1308 Adams Street
Kansas City, Kansas 66103
Telephone: (913) 321-8100
Fax: (913) 321-8181

REPORT OF BITUMINOUS MIXTURE PROPERTIES

CLIENT: SILVERSTONE DEVELOPMENT, LLC

PROJECT NO.: R20-16-061

SAMPLE DATE: 11.17.2016

SAMPLE LOC.: Cul-de-sac @ Pocand
Circle Drive

PROJECT: MONTICELLO SUBDIVISION
BOWLIN ROAD
LEE'S SUMMIT, MO

REPORT DATE: 11.23.2016

REPORT NO.: K14690

PROJECT DATA

MIX TYPE: APWA TYPE 2
SUPPLIER: Superior Bowen
Marshall (lb/ft³): 151.1

PLANT:

ASTM D5444 Extraction Gradation			
Sieve Size	% Retained	% Passing	APWA Spec % Passing
37.5 mm (1 1/2")	0.0	100.0	
25mm (1")	0.0	100	100
19mm (3/4")	0.0	100	80-100
12.5mm (1/2")	17.0	83	
9.5mm (3/8")	23.9	76	60-80
4.75 mm (No. 4)	42.0	58	48-65
2.36 mm (No. 8)	58.3	42	35-47
1.18mm (No. 16)	67.2	33	25-36
600um (No. 30)	74.1	26	18-30
300um (No. 50)	86.1	14	12-22
150um (No. 100)	92.1	8	6-14
75um (No. 200)	93.7	6.3	3-10

	Test Result	Spec.	Test Designation
% AC by Ignition	4.8%	4-7	ASTM D6307
Gmm (Field)	2.546		ASTM D2726
Gmb (Field)	2.427		ASTM D2726
Gse (Calculated)	2.751		ASTM D2726
VMA	11.8		ASTM D3203
VTM	4.7	3-5	ASTM D3203
VFA	60.5		ASTM D3203
Stability, lbs	5336.3	1500 min	ASTM D6927
Flow, 1/100 in.	10.9	8-16	ASTM D6927

Reviewed By: 



KANSAS CITY
TESTING & ENGINEERING, LLC

Kansas City Testing & Engineering, LLC
1308 Adams Street
Kansas City, KS 66103
Phone 913.321.8100
Fax 913.321.8181

REPORT OF RELATIVE IN-PLACE DENSITY OF COMPACTED BITUMINOUS CONCRETE

CLIENT: SILVERSTONE DEVELOPMENT, LLC
ATTN: TROY BELLAH
P O BOX 346
LEE'S SUMMIT MO 64063

PAGE 1 OF 1

PROJECT: MONTICELLO SUBDIVISION
BOWLIN ROAD
LEE'S SUMMIT MO

PROJECT NO.: R20-16-061
REPORT NO.: K14691
DATE OF SERVICE: 11/17/2016
AUTHORIZATION: TROY BELLAH
REPORT DATE: 11/30/2016

SERVICES: Perform density determinations on the compacted asphaltic concrete mixture using the nuclear gauge.

PROJECT DATA

CONTRACTOR: Superior Bowen
SUPPLIER: Superior Bowen
MIXTURE TYPE: APWA 2R
METHOD: ASTM D 2726
SPECIFICATIONS: Not provided

AMBIENT TEMPERATURE (deg F): 67 **TO:** 76
RAW MATERIALS:
SURFACE TEXTURE:
STANDARDIZATION COUNT RATE: 1856
DEPTH OF PROBE: Backscatter

REPORT OF TESTS

TEST NUMBER	LOCATION	COURSE THICKNESS (IN.)	NUCLEAR DENSITY (PCF)	REFERENCE DENSITY (PCF)	IN-PLACE DENSITY (%)
1.	Gateway @ Sta. 3+75, 10' R of CL	4.00	150.4	151.1	99.5
2.	Gateway @ Sta. 29+00	4.00	156.0	151.1	103.2
3.	Goshen @ Sta. 2+60 10' L of CL	4.00	154.2	151.1	102.1
4.	Goshen @ Sta. 3+95	4.00	151.8	151.1	100.5
5.	Goshen @ Sta. 4+45, 12' R of CL	4.00	154.8	151.1	102.4
6.	Goshen @ Sta. 5+50, 7' L of CL	4.00	149.2	151.1	98.7
7.	Goshen @ Sta. 5+00 10' R of CL	4.00	148.9	151.1	98.5
8.	Pocano @ Sta. 2+00, 6' L of CL	4.00	155.1	151.1	102.6
9.	Pocano @ Sta. 3+10, 10' R of CL	4.00	157.2	151.1	104.0
10.	Pocano @ Sta. 4+00	4.00	159.6	151.1	105.6


Note: The density results obtained by this method are relative. If actual density results are required, a conversion factor can be developed to convert nuclear density to actual density by taking nuclear density measurements and core densities at the same randomly selected locations.

ADDITIONAL COMMENTS:

Technician: ERIC HOWARD, CME TECHNICIAN III
Report Distribution:

(1) barton.reese@cityofks.net
(1) TROY@BELLAHOMES.COM

KANSAS CITY TESTING & ENGINEERING,


JIM BYRNES, R.G.
PROJECT MANAGER

Our letters and reports are for the exclusive use of the client to whom they are addressed and shall not be reproduced except in full without the approval of the testing laboratory. The use of our name must receive our written approval. Our letters and reports apply only to the sample tested and/or inspected, and are not indicative of the quantities of apparently identical or similar products.



KANSAS CITY
TESTING & ENGINEERING, LLC

Kansas City Testing Engineering, LLC
1308 Adams Street
Kansas City, Kansas 66103
Telephone: (913) 321-8100
Fax: (913) 321-8181

REPORT OF BITUMINOUS MIXTURE PROPERTIES

CLIENT: SILVERSTONE DEVELOPMENT, LLC

PROJECT NO.: R20-16-061

SAMPLE DATE: 11.23.2016

SAMPLE LOC.: Cul-de-sac @ Pocano Rd.

PROJECT: MONTICELLO SUBDIVISION
BOWLIN ROAD
LEE'S SUMMIT, MO

REPORT DATE: 12.1.2016

REPORT NO.: K14858

PROJECT DATA

MIX TYPE: APWA TYPE 3V
SUPPLIER: Superior Bowen
Marshall (lb/ft³): 148.2

PLANT: Manchester

ASTM D5444 Extraction Gradation			
Sieve Size	% Retained	% Passing	APWA Spec % Passing
37.5 mm (1 1/2")	0.0	100.0	
25mm (1")	0.0	100	
19mm (3/4")	0.0	100	100
12.5mm (1/2")	15.0	85	85-100
9.5mm (3/8")	22.5	78	70-90
4.75 mm (No. 4)	35.6	64	50-70
2.36 mm (No. 8)	53.6	46	37-47
1.18mm (No. 16)	65.1	35	26-36
600um (No. 30)	73.7	26	18-30
300um (No. 50)	86.9	13	12-22
150um (No. 100)	93.1	7	6-15
75um (No. 200)	94.0	6.0	4-10

	Test Result	Spec.	Test Designation
% AC by Ignition	4.8%	4-6	ASTM D6307
Gmm (Field)	2.508		ASTM D2726
Gmb (Field)	2.381		ASTM D2726
Gse (Calculated)	2.704		ASTM D2726
VMA	12.0		ASTM D3203
VTM	5.1	3-5	ASTM D3203
VFA	57.6		ASTM D3203
Stability, lbs	3951.5	1500 min	ASTM D6927
Flow, 1/100 in.	9.5	8-16	ASTM D6927

Reviewed By: 



KANSAS CITY
TESTING & ENGINEERING, LLC

Kansas City Testing & Engineering, LLC
1308 Adams Street
Kansas City, KS 66103
Phone 913.321.8100
Fax 913.321.8181

REPORT OF RELATIVE IN-PLACE DENSITY OF COMPACTED BITUMINOUS CONCRETE

CLIENT: SILVERSTONE DEVELOPMENT, LLC
ATTN: TROY BELLAH
P O BOX 346
LEE'S SUMMIT MO 64063

PAGE 1 OF 1

PROJECT: MONTICELLO SUBDIVISION
BOWLIN ROAD
LEE'S SUMMIT MO

PROJECT NO.: R20-16-061
REPORT NO.: K14859
DATE OF SERVICE: 11/23/2016
AUTHORIZATION: TROY BELLAH
REPORT DATE: 11/30/2016

SERVICES: Perform density determinations on the compacted asphaltic concrete mixture using the nuclear gauge.

PROJECT DATA

CONTRACTOR: Superior Bowen
SUPPLIER: Superior Bowen
MIXTURE TYPE: 3V
METHOD: ASTM D 2726
SPECIFICATIONS: Not provided

AMBIENT TEMPERATURE (deg F): 46 **TO:** 51
RAW MATERIALS:
SURFACE TEXTURE:
STANDARDIZATION COUNT RATE: 1851
DEPTH OF PROBE: Backscatter

REPORT OF TESTS

TEST NUMBER	LOCATION	COURSE THICKNESS (IN.)	NUCLEAR DENSITY (PCF)	REFERENCE DENSITY (PCF)	IN-PLACE DENSITY (%)
1.	Pocano @ Sta. 4+25, 5' L of CL	2.00	158.1	148.2	106.7
2.	Pocano @ Sta. 2+75, 10' L of CL	2.00	155.8	148.2	105.1
3.	Pocano @ Sta. 1+65, 12' L of CL	2.00	158.7	148.2	107.1
4.	Goshen @ Sta. 1+75, 5' R of CL	2.00	158.5	148.2	107.0
5.	Goshen @ Sta. 2+80, 10' L of CL	2.00	156.9	148.2	105.9
6.	Goshen @ Sta. 4+00, 5' R of CL	2.00	154.7	148.2	104.4
7.	Gateway @ Sta. 2+50, 2' L of CL	2.00	150.8	148.2	101.8
8.	Gateway @ Sta. 3+50, 4' R of CL	2.00	150.0	148.2	101.2
9.	Gateway @ Sta. 5+60, 10' L of CL	2.00	152.6	148.2	103.0
10.	Gateway @ Sta. 7+40, 8' R of CL	2.00	151.4	148.2	102.2

Note: The density results obtained by this method are relative. If actual density results are required, a conversion factor can be developed to convert nuclear density to actual density by taking nuclear density measurements and core densities at the same randomly selected locations.

ADDITIONAL COMMENTS:

Technician: ERIC HOWARD, CME TECHNICIAN III
Report Distribution:

(1) barton.reese@cityofks.net
(1) TROY@BELLAHOMES.COM

KANSAS CITY TESTING & ENGINEERING,

JIM BYRNES, R.G.
PROJECT MANAGER

Our letters and reports are for the exclusive use of the client to whom they are addressed and shall not be reproduced except in full without the approval of the testing laboratory. The use of our name must receive our written approval. Our letters and reports apply only to the sample tested and/or inspected, and are not indicative of the quantities of apparently identical or similar products.



KANSAS CITY
TESTING & ENGINEERING, LLC

Kansas City Testing & Engineering, LLC
1308 Adams Street
Kansas City, KS 66103
Phone 913.321.8100
Fax 913.321.8181

REPORT OF RELATIVE IN-PLACE DENSITY OF COMPACTED BITUMINOUS CONCRETE

CLIENT: SILVERSTONE DEVELOPMENT, LLC
ATTN: TROY BELLAH
P O BOX 346
LEE'S SUMMIT MO 64063

PAGE 1 OF 1

PROJECT: MONTICELLO SUBDIVISION
BOWLIN ROAD
LEE'S SUMMIT MO

PROJECT NO.: R20-16-061
REPORT NO.: K14859
DATE OF SERVICE: 11/23/2016
AUTHORIZATION: TROY BELLAH
REPORT DATE: 11/30/2016

SERVICES: Perform density determinations on the compacted asphaltic concrete mixture using the nuclear gauge.

PROJECT DATA

CONTRACTOR: Superior Bowen
SUPPLIER: Superior Bowen
MIXTURE TYPE: 3V
METHOD: ASTM D 2726
SPECIFICATIONS: Not provided

AMBIENT TEMPERATURE (deg F): 46 **TO:** 51
RAW MATERIALS:
SURFACE TEXTURE:
STANDARDIZATION COUNT RATE: 1851
DEPTH OF PROBE: Backscatter

REPORT OF TESTS

TEST NUMBER	LOCATION	COURSE THICKNESS (IN.)	NUCLEAR DENSITY (PCF)	REFERENCE DENSITY (PCF)	IN-PLACE DENSITY (%)
1.	Pocano @ Sta. 4+25, 5' L of CL	2.00	158.1	148.2	106.7
2.	Pocano @ Sta. 2+75, 10' L of CL	2.00	155.8	148.2	105.1
3.	Pocano @ Sta. 1+65, 12' L of CL	2.00	158.7	148.2	107.1
4.	Goshen @ Sta. 1+75, 5' R of CL	2.00	158.5	148.2	107.0
5.	Goshen @ Sta. 2+80, 10' L of CL	2.00	156.9	148.2	105.9
6.	Goshen @ Sta. 4+00, 5' R of CL	2.00	154.7	148.2	104.4
7.	Gateway @ Sta. 2+50, 2' L of CL	2.00	150.8	148.2	101.8
8.	Gateway @ Sta. 3+50, 4' R of CL	2.00	150.0	148.2	101.2
9.	Gateway @ Sta. 5+60, 10' L of CL	2.00	152.6	148.2	103.0
10.	Gateway @ Sta. 7+40, 8' R of CL	2.00	151.4	148.2	102.2


Note: The density results obtained by this method are relative. If actual density results are required, a conversion factor can be developed to convert nuclear density to actual density by taking nuclear density measurements and core densities at the same randomly selected locations.

ADDITIONAL COMMENTS:

Technician: ERIC HOWARD, CME TECHNICIAN III
Report Distribution:

(1) barton.reese@cityofks.net
(1) TROY@BELLAHOMES.COM

KANSAS CITY TESTING & ENGINEERING,


JIM BYRNES, R.G.
PROJECT MANAGER

Our letters and reports are for the exclusive use of the client to whom they are addressed and shall not be reproduced except in full without the approval of the testing laboratory. The use of our name must receive our written approval. Our letters and reports apply only to the sample tested and/or inspected, and are not indicative of the quantities of apparently identical or similar products.