CENTURY CONCRETE CONDITION OF SALE: All accounts payable C.O.D. There will be a \$20.00 service charge on returned checks.

11011 CODY STREET, SUITE 150 OVERLAND PARK, KANSAS 66210 PHONE: 913-345-2030 FAX: 913-345-8027

SOLD TO:

SHIP TO: 621708281996

REDFORD CONSTRUCTION INC STONEY CREEK DR & GEORGETOWN DR

WARD RD & 150 HWY WEST - STONEYCREEK DR SOUTH TO SW GEORGETOWNDR

Customer Signature X

| TIME OUT | CUSTOMER ID | 4 80L | ORDER # | SLUMP | TRUC | K TICKET | con | CHECK |
|----------|-------------|----------|---------|------------|--------|----------|---------|-------------|
| 8:34 | 00015320 | | 681 | - <u> </u> | in 284 | | | |
| DATE | PLANT | P O. NUM | IBER | LOT | ZON | USE | YDS DEL | YDS ORDERED |
| 08/31/17 | 62 | 3743 | | | | FILL | 2.00 | 2.00 |

WARNING: INJURIOUS TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are light at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, where knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1% Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline Silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear an appropriate NIOSH-approved respirator during these activities.

QUANTITY CODE DESCRIPTION UNITPRICE **EXTENDED PRICE**

| 2.00 FF29 | 50+75 CASH FF |
|--------------|---------------------------|
| 2.00 ME23 | DELIVERY CHARGE |
| 1.00 NOCHILL | NO CHILLED WATER CUSTOMER |

Flowfill for the trench checks for the sewer stubs for lots 66,67,88

| UNUSUAL INCIDENT OF NOTE ON T | | Gallons Added | inches |
|-------------------------------|--|---------------------------------|------------------------------|
| LEFT PLANT AHRIVED STARTED | RINISHED LEFT JOB RETURNED UNLOAD PLANT | WATER ADDED AT CUSTOMER REQUEST | ESTIMATED SLUMP AT UNLOADING |

SEE REVERSE SIDE FOR CONDITIONS OF SALE

| Truck | Driver | User | Dis | p Ticket | Num | Ticket | ID I | Time | Date | | |
|-------------|----------|----------|--------|----------|-------|---------|------|-------|-----------|----------|-----|
| 284 | 0693 | user | 281 | 996 | | 86818 | | 8:34 | 8/31/17 | | |
| Load Size | Mix Code | Retur | ned | Qty | Mix | Age | Seq | | d ID | | |
| 2.00 CY | FF29 | | | | | - | р - | 883 | 06 | | |
| Material | Design | Qty | Requi | red | Bat | ched | | % Var | * Moistur | e Actual | Wot |
| SAND-9 | 2500 | 1b | 5250 | lb | 52 | 60 lb | c |).19% | 5.00% M | | gl |
| TYPE I/II | 50 | lb | 100 | lb | 1 | 04 lb | | .00% | ii | 30 | 91 |
| C-ASH JEF | 75.0 | 1b | 150.0 | 1b | 144 | .0 lb | -4 | .00% | | | |
| AEA-92S | 6.00 | /c | 15.00 | oz | 14. | 00 oz | -6 | .67% | | | |
| WATER | 44.00 | gl | 55.04 | gl | 55. | 00 gl | -0 | .08% | | 55.00 | al |
| Actual | Num | Batches: | 1 | | | | | | | | 91 |
| Load Total: | 5968 | lb | Design | 2.937 W | ater. | /Cement | 2.86 | 1 A | Design | 88.0 gl | |
| Slump 5. | 00 in | # Water | | | | | | | - | 5 | |

Actual 85.0 gl To Add: 3.0 ql Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -1.0 gl/ CY 5.00 in

CENTURY CONCRETE CONDITION OF SALE: All accounts payable C.O.D. There will be a \$20.00 service charge on returned checks.

SHIP TO:

11011 CODY STREET, SUITE 150 OVERLAND PARK, KANSAS 66210 PHONE: 913-345-2030 FAX: 913-345-8027

SOLD TO:

REDFORD CONSTRUCTION INC STONEY CREEK DR & GEORGETOWN DR WARD RD & 150 HWY WEST - STONEYCREEK DR SOUTH TO SW GEORGETOWNDR

621708282024

Customer Signature X

| TIME OUT | CUSTOMER ID | JOB # | ORDER # | SLUMP | TRUCK | TICKET | COD | CHECK |
|----------|-------------|-----------|---------|---------|-------|--------|----------|-------------|
| 14:33 | 00015320 | JOB | 638 | 4.00 in | | 282024 | | |
| DATE | PLANT | P.O. NUMB | EA | LOT | ZONE | USE | YDS DEL. | YDS ORDERED |
| 08/31/17 | 62 | 3743 | | | | FILL | 3.00 | 3.00 |

WARNING: INJURIOUS TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are light at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, where knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE. USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1% Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear an appropriate NIOSH-approved respirator during these activities.

QUANTITY CODE DESCRIPTION UNIT PRICE EXTENDED PRICE

| 3.00 | FF29 | 50+75 CASH FF |
|------|---------|---------------------------|
| 3.00 | ME23 | DELIVERY CHARGE |
| 1.00 | NOCHILL | NO CHILLED WATER CUSTOMER |

Flow fill for tots the trench checks on lots 68,69,70,89 & 90.

| LEFT PLANT ARRIVED | STARTED | PINISHED | WATER ADDED AT CUSTOMER REQUEST | ESTIMATED SLUMP AT UNLOADING | | |
|--------------------|---------|----------|---------------------------------|------------------------------|---------------|--------|
| | | | | | Gallons Added | inches |

UNUSUAL INCIDENT OF NOTE ON THIS DELIVERY:

SEE REVERSE SIDE FOR CONDITIONS OF SALE

| Truck | Driver | User | Disp | o Ticket | Num | Ticket | ID. | Time | Date | ÷ | | | | | | | | |
|-------------|----------|------------|--------|----------|--------|---------|-----|--------|-------|--------|--------|---------|--------|--------------|----|---------|------|----|
| 249 | | user | 2820 | 024 | | 86846 | | 14:33 | 8/31 | /17 | | | | | | | | |
| Load Size | Mix Code | Returned | a ç | Qty | Mix . | Age | Seq | . Loa | d ID | | | | | | | | | |
| 3.00 CY | FF29 | | | | | | D | 883 | 34 | | | | | | | | | |
| Material | Design Ç | ity 1 | Requir | red | Bat | ched | | ∛ Var | | % Mois | ture | Actu | al Wat | | | | | |
| SAND-9 | 2500 | 1b · | 7856 | 1b | 78 | 00 1Ь | - | 0.72% | | 4.75% | м | 4: | 2 gl | | | | | |
| TYPE I/II | 50 | lb | 150 | lb | 1. | 50 lb | | 6.67% | | | | | | | | | | |
| C-ASH JEF | 75.0 | lb 22 | 25.0 | 1b | 232 | .0 lb | | 3.11% | | | | | | | | | | |
| AEA-92S | 6.00 | /c 22 | 2.50 | oz | 21.0 | 00 oz | - | 6.67% | | | | | | | | | | |
| WATER | 44.00 | gl 73 | 3.31 | gl | 73.0 | 00 gl | - | 0.42% | | | | 73.00 |) gl | | | | | |
| Actual | Num | Batches: | l | | | | | | | | | | | | | | | |
| Load Total: | 8802 | lb De | esign | 2.937 | Water, | /Cement | 2.4 | 56 A | | Des | ign 13 | 2.0 gl | | Actual 115.4 | gl | To Add: | 16.6 | gl |
| Slump: 4. | 00 in | # Water in | n Truc | ck: 0.0 | gl | Adjust | Wa | ter: 0 | .0 gl | / LO | ad T | rim Wat | er: -4 | 4.0 gl/ CY | | | | |