

11011 CODY STREET, SUITE 150
OVERLAND PARK, KANSAS 66210
PHONE: 913-345-2030 FAX: 913-345-8027



SOLD TO:

SHIP TO:

621709282220

REDFORD CONSTRUCTION INC
STONE CREEK DR & GEORGETOWN DR

WARD RD & 150 HWY WEST - STONEYCREEK DR
SOUTH TO SW GEORGETOWNDR

Customer Signature X _____

TIME OUT	CUSTOMER ID	JOB #	ORDER #	SLUMP	TRUCK	TICKET	COD	CHECK
13:51	00015320	JOB	263	3.00 in	249	282220		
DATE	PLANT	P.O. NUMBER	LOT	ZONE	USE	YDS DEL	YDS ORDERED	
09/07/17	62	3743			FILL	7.00	7.00	

WARNING: INJURIOUS TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are light at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, where knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1% Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear an appropriate NIOSH-approved respirator during these activities.

QUANTITY	CODE	DESCRIPTION	UNIT PRICE	EXTENDED PRICE
7.00	FF29	50+75 CASH FF		
7.00	ME23	DELIVERY CHARGE		
1.00	NOCHILL	NO CHILLED WATER CUSTOMER		

For trench checks on the sewer service stubs

LEFT PLANT	ARRIVED JOB	STARTED UNLOAD	FINISHED UNLOAD	LEFT JOB	RETURNED PLANT	WATER ADDED AT CUSTOMER REQUEST	ESTIMATED SLUMP AT UNLOADING
						Gallons Added	Inches

UNUSUAL INCIDENT OF NOTE ON THIS DELIVERY:

SEE REVERSE SIDE FOR CONDITIONS OF SALE

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
249		user		282220	87037	13:51	9/7/17
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
7.00	CY	FF29			D	88527	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	
SAND-9	2500 lb	18200 lb	18240 lb	0.22%	4.00% M	84 gl	
TYPE I/II	50 lb	350 lb	440 lb	+ 25.71%			
C-ASH JEF	75.0 lb	525.0 lb	528.0 lb	0.57%			
AEA-92S	6.00 /C	52.50 oz	51.00 oz	-2.86%			
WATER	44.00 gl	184.12 gl	184.00 gl	-0.06%		184.00 gl	
Actual	Num Batches:	1					
Load Total:	20747 lb	Design 2.937	Water/Cement 2.311	A	Design 308.0 gl	Actual 268.1 gl	To Add: 39.9 gl
Slump:	3.00 in	#	Water in Truck: 0.0 gl	Adjust Water: 0.0 gl	/ Load	Trim Water: -5.0 gl/	CY