11011 CODY STREET, SUITE 150 OVERLAND PARK, KANSAS 66210 PHONE: 913-345-2030 FAX: 913-345-8027

SHIP TO:

621710283189

SOLD TO:

REDFORD CONSTRUCTION INC STONEY CREEK DR & GEORGETOWN DR 150 HWY AND WARD W TO STONEY CREEK DR S TO WHISTLE E TO FLINTLOCK DR S TO 44TH ST W TO STONEY CREEK DR GO W

## Customer Signature X

TIME OUT	CUSTOMER ID	JOB# ORDER#	SLUMP	TRUCK	TICKET	COD	CHECK
8:45	00015320	001041 436	3.00 in	238	283189		
DATE	PLANT	P.O. NUMBER	LOT	ZONE	USE	YOS DEL	YOS ORDERED
10/04/17	62	JEREMY			<unknown></unknown>	2.00	2.00

## WARNING: INJURIOUS TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. if you have to stand in wet concrete, use waterproof boots that are light at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, where knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1% Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear an appropriate NIOSH-approved respirator during these activities.

QUANTITY	CODE	DESCRIPTION UNIT PRICE EXTENDED PRICE
2.00	FF29	50+75 CASH FF
2 00	ME23	DELIVERY CHARGE

For trench checks on sewer stubs for lots 42,43,48 & 66.

LEFT PLANT	ARRIVED JOB	STARTED UNLOAD	FINISHED UNLOAD	LEFT JOS	RETURNED PLANT	WATER ADDED AT CUSTOMER REQUEST	ESTIMATED SLUMP AT UNLOADING
						Gallons Added	Inches

UNUSUAL INCIDENT OF NOTE ON THIS DELIVERY:

User

Truck

Driver

SEE REVERSE SIDE FOR CONDITIONS OF SALE

uch	Dilver Oser	DISP IICA	ec Num 11cket	ID IIMC Da	LG				
238	user	283189	87993	8:45 10	/4/17				
Load Size	Mix Code Retu	rned Qty	Mix Age	Seq Load I	D				
2.00 CY	FF29		]	D 89491					
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat			
SAND-9	2500 lb	5250 lb	5240 lb	-0.19%	5.00% M	30 gl			
TYPE I/II	50 lb	100 lb	104 lb	4.00%					
C-ASH JEF	75.0 lb	150.0 lb	136.0 lb	-9.33%					
AEA-92S	6.00 /C	15.00 oz	16.00 oz	6.67%					
WATER	44.00 gl	43.04 gl	43.00 gl	-0.10%		<b>4</b> 3.00 gl			
Actual	Num Batches	: 1							
Load Total:	5840 lb	Design 2.937	Water/Cement	2.535 A	Design :	88.0 gl	Actual 72.9 g	gl To Add: 15.1 gl	
Slump: 3.	00 in # Water	r in Truck: 0.	0 gl Adjust	Water: 0.0	gl / Load S	Trim Water: -5.	0 gl/ CY		

Disp Ticket Num Ticket ID Time Date