

VIEWPOINT
 RESIDENTIAL DESIGN LLC
 1550 SW Market St., Ste. 230A ▼ Louds Summit, MD 20638-3313 ▼ Office: (301) 564-0400 Ext. 101
 www.viewpointdesignllc.com ▼ Email: Planinfo@viewpointdesignllc.com

THIS PLAN AND SPECIFICATIONS ARE PREPARED BY THE ARCHITECT FOR THE CLIENT. THE CLIENT IS RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR THE ACCURACY OF THE INFORMATION PROVIDED TO THE ARCHITECT. THE ARCHITECT'S RESPONSIBILITY IS LIMITED TO THE DESIGN OF THE FOUNDATION SYSTEM AS SHOWN ON THIS PLAN. THE ARCHITECT DOES NOT WARRANT THE SUITABILITY OF THE FOUNDATION SYSTEM FOR THE SITE OR THE SOIL CONDITIONS. THE CLIENT SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR THE ACCURACY OF THE INFORMATION PROVIDED TO THE ARCHITECT. THE ARCHITECT'S RESPONSIBILITY IS LIMITED TO THE DESIGN OF THE FOUNDATION SYSTEM AS SHOWN ON THIS PLAN. THE ARCHITECT DOES NOT WARRANT THE SUITABILITY OF THE FOUNDATION SYSTEM FOR THE SITE OR THE SOIL CONDITIONS.

UNFINISHED: 10.99 SQ. FT.
 SCALE: 1/4" = 1'-0"
 FOUNDATION
 2" X 10" FLOOR SYSTEM
 9'-0" FOUNDATION WALLS
 ON 16" X 8" STRIP FOOTINGS
 (UNLESS NOTED OTHERWISE)
 (STEP WHERE GRADE REQUIRES)

FOUND. NOTES:
 1. FOUND. WALLS SHALL BE 9'-0" HIGH ABOVE FIN. GRADE.
 2. FOUND. WALLS SHALL BE 2'-0" THICK.
 3. FOUND. WALLS SHALL BE 1'-0" THICK AT TOP.
 4. FOUND. WALLS SHALL BE 1'-0" THICK AT BOTTOM.
 5. FOUND. WALLS SHALL BE 1'-0" THICK AT CORNERS.
 6. FOUND. WALLS SHALL BE 1'-0" THICK AT JOINTS.
 7. FOUND. WALLS SHALL BE 1'-0" THICK AT CHASES.
 8. FOUND. WALLS SHALL BE 1'-0" THICK AT PENETRATIONS.
 9. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 10. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 11. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 12. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 13. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 14. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 15. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 16. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 17. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 18. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 19. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.
 20. FOUND. WALLS SHALL BE 1'-0" THICK AT REINFORCING.

