

## CENTURY CONCRETE

CONDITION OF SALE: All accounts payable C.O.D. There will be a \$20.00 service charge on returned checks.

11011 CODY STREET, SUITE 150  
OVERLAND PARK, KANSAS 66210  
PHONE: 913-345-2030 FAX: 913-345-8027

SOLD TO:

SHIP TO:

69180397494

KAT EXCAVATION INC - 1070  
150 HWY AND CHEDDINGTON / LEE'S

50 HWY AND 291 HWY S TO 150 HWY TO  
CHEDDINGTON GO N

Customer Signature X

TIME OUT	CUSTOMER ID	JOB #	ORDER #	SLUMP	TRUCK	TICKET	COD	CHECK
8:37	00010159	JOB	218	1.99 in	258	97494		
DATE	PLANT	P.O. NUMBER	LOT	ZONE	USE	YDS DEL	YDS ORDERED	
03/15/18	69				COLLARS	5.00	5.00	

WARNING: INJURIOUS TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are tight at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, where knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1%. Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear an appropriate NIOSH-approved respirator during these activities.

QUANTITY	CODE	DESCRIPTION	UNIT PRICE	EXTENDED PRICE
----------	------	-------------	------------	----------------

5.00 KCMMB4KF2 KCMMB 4K 2" MC GRANITE/F  
5.00 NCA1.5 ACCELGAURD NCA 1.5%  
5.00 ME08 WINTER SERVICE (CY)  
5.00 ME23 DELIVERY CHARGE

**CERTIFICATION**  
I hereby certify that City of MO  
inspected and approved materials have  
been proportioned and mixed in  
accordance with contract requirements.

*Eric Behrens*  
Skiles Plant  
Century Concrete  
Eric Behrens  
Quality Control Technician

LEFT PLANT	ARRIVED JOB	STARTED UNLOAD	FINISHED UNLOAD	LEFT JOB	RETURNED PLANT	WATER ADDED AT CUSTOMER REQUEST	ESTIMATED SLUMP AT UNLOADING
						Gallons Added	Inches

UNUSUAL INCIDENT OF NOTE ON THIS DELIVERY:

SEE REVERSE SIDE FOR CONDITIONS OF SALE

Truck	Driver	User	Disp Ticket Num	Ticket ID	Time	Date	
258	0705	user	97494	57440	8:37	3/15/18	
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
5.00 CY	KCMMB4KF2				DE	52214	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	
3/4MC GRAN	1669 lb	8387 lb	8420 lb	> 0.10%	0.50% M	5 gl	
SAND-9	1335 lb	7009 lb	6980 lb	-0.11%	5.00% M	40 gl	
DURAPOZ F	150.0 lb	750.0 lb	740.0 lb	-1.33%			
TYPE I/II	450 lb	2250 lb	2315 lb	> 3.69%			
AEA-92S	2.60 /C	78.00 oz	78.00 oz	0.00%			
NCA	18.00 /C	# 540.00 OZ	536.00 OZ	-0.74%		3.14 gl	
WR-91	3.00 /C	90.00 oz	89.00 oz	-1.11%			
WATER	29.0 gl	86.8 gl	87.0 gl	0.18%		87.0 gl	
Actual	Num Batches:	1					
Load Total:	19225 lb	Design 0.403	Water/Cement 0.396	T	Design 145.0 gl	Actual 135.0 gl	To Add: 10.0 gl
Slump:	1.99 in	#	Water in Truck: 0.0 gl	Adjust Water: 0.0 gl	/ Load	Trim Water: -2.0 gl/	CY