11011 CODY STREET, SUITE 150 OVERLAND PARK, KANSAS 66210 PHONE: 913-345-2030 FAX: 913-345-4251

SOLD TO:



SHIP TO:

RAY COCHRAN AND COMPANY, LLC ((BOB))1700 SW MERRYMAN/ STONEYC 150 AND WARD S TO COUNTY LINE WTO STONEY CREEK DR N TO MERRYMANDR GO W

Customer Signature X__

TIME OUT	CUSTOMERIO	JOB#	oriorisc	SLUMP	TRUCK	TICKET	COD	CHECK
9:37	00004440	JOB	407	5.00 in	221	291569		
DATE	PLANT	P.O. NUMI	SER .	LOT	ZONE	USE	YOS DEL	YOS ORDERED
08/28/18	62	4 - BOB	ı			APPROACH	16.00	16.00

WARNING: INJURIOUS TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING, Contains Portland Cement,

Contact with wet (unhardened) concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are light at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, where knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1% Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear an appropriate NIOSH-approved respirator during these activities.

QUANTITY	CODE	DESCRIPTION UNIT PRICE EXTENDED PRICE
8.00	KCMMB4KF4	KCMMB 4K 4" MC GRANITE/F
8.00	ME23	DELIVERY CHARGE
1.00	NOCHILL	NO CHILLED WATER CUSTOMER

LEFT PLANT JOB STARTED FINISHED LEFT JOB RETURN UNLOAD UNLOAD PLAN	WATER ADDED AT CUSTOMER REQUEST	ESTIMATED SLUMP AT UNLOADING
	Gallons Added	Inches

UNUSUAL INCIDENT OF NOTE ON THIS DELIVERY:

SEE REVERSE SIDE FOR CONDITIONS OF SALE

g1

Truck	Driver	User	Disp Ticks	et Num Ticket	ID Time Da	ite		
221	539	user	291569	96258	9:37 8/	28/18		
Load Size	Mix Code	Retu	ırned Qty	Mix Age S	Seq Load I	מו		
8.00 CY	KCMMB4KF4			I	D 97926			
Material	Design (Qty	Required	Batched	% Var	% Moisture	Actual	Wat
3/4MC GRAN	J 1676	1b	13442 lb	13460 lb	0.14%	0.25% M	4	gl
SAND-9	1317	1b	10900 lb	10860 lb	-0.37%	3.45% A	43	gl
TYPE I/II	510	1b	4080 lb	4080 lb	0.00%			
DURAPOZ F	90.0	1b	720.0 lb	712.0 lb	-1.11%			
AEA-92S	.60	/c #	28.80 oz	29.00 oz	0.69%			
WATER	30.20	gl	189.48 gl	189.00 gl	-0.25%		189.00	gl
P-6420	6.0	/c #	288.0 oz	280.0 oz	-2.78%			
Actual	Num	Batches	s: 1					
Load Total	: 30709	lb	Design 0.420	Water/Cement	0.412 A	Design 24	1.6 gl	Actual 236.5 gl To Add: 5.1
Slump 5	ni 00	# Wate	er in Truck · 0	0 al Adiust	Water: 0.0	gl / Load T	rim Wate:	r: -0.5 gl/ CY