CENTURY CONCRETE CONDITION OF SALE: All accounts payable C.O.D. There will be a \$20.00 service charge on returned checks.												
11011 C	ODY STREET, SUITE 150 ND PARK, KANSAS 66210 -345-2030 FAX: 913-345-424		SHIP TO: 621808291569									
	RAY COCHRAN ((BOB))170 5	AND COMPANY, LLC SW MERRYMAN/ STONE	C 150 AND WARD S TO COUNTY LINE WTO ONEYC STONEY CREEK DR N TO MERRYMANDR GO W									
ADA RAMP for 1621 SW MERRYMAN AS We !!												
Customer Signature X												
TIME OUT	CUSTOMER ID	JOB # ORDER #	SLUMP	TRUCK	TICKET	COD	CHECK					
9:37	00004440	JOB 407	5.00 in	221	291569							
DATE	PLANT	P.O. NUMBER	LOT	ZONE	USE	YDS DEL	YDS ORDERED					
08/28/3	L8 62	4 - BOB			APPROACH	16.00	16.00					
WARNING: INJURIOUS TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement. Contact with wet (unhardened) concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-steeved shin, full length trousers, and light fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are light at lops and high enough to keep concrete from flowing into them. If you are finishing concrete, where knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately. KEEP OUT OF REACH OF CHILDREN USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1% Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear an appropriate NIOSH-approved respirator during these activities.												
QUANTITY	CODE	<u> </u>	ESCRIPTION		UNIT PRICE	EXTEND	ED PRICE					
	KCMMB4KF4		IC GRANI	FE/F								
	ME23	DELIVERY CHAP										
1.00	NOCHILL	NO CHILLED WA	ATER CUST	FOMER								

LEFT PLANT	ARRIVED JOB	STARTED UNLOAD	FINISHED UNLOAD	LEFT JOB	RETURNED PLANT	WATER ADDED AT CUSTOMER REQUEST	ESTIMATED SLUMP AT UNLOADING
						Gallons Added	Inches

UNUSUAL INCIDENT OF NOTE ON THIS DELIVERY:

Truck	Driver	Us	er	Dis	sp Ticke	t Num	Ticke	t ID	Time	D	Date										
221	539	us	er	293	1569		96258	÷	9:37	8	3/28	/18									
Load Size	Mix Code		Retur	ned	Qty	Mix	Age	Seq	Loa	ad	ID										
8.00 CY	KCMMB4KF4							D	979	926	5										
Material	Design (Qty		Requi	ired	Bat	ched		∛ Var	r		% Moi	sture	Actua	Wat						
3/4MC GRAN	1676	lb		13442	lb	134	60 lb		0.14%			0.25%	м	4	gl						
SAND-9	1317	lb		10900	1b	108	60 lb	-	0.37%			3.45%	A	43	gl						
TYPE I/II	510	lb		4080	1b	40	80 lb		0.00%												
DURAPOZ F	90.0	1b		720.0	lb	712	.0 lb	-	1.11%												
AEA-92S	.60	/c	#	28.80	oz	29.	00 oz		0.69%												
WATER	30.20	gl		189.48	gl	189.	00 gl	-	0.25%					189.00	gl						
P-6420	6.0	/c	#	288.0	oz	280	.0 oz	-	2.78%												
Actual	Num	Bat	ches:	1																	
Load Total:	30709	lb		Design	1 0.420	Water	/Cemen	t 0.4	12 A			Des	sign	241.6 gl		Actual 23	6.5	gl	To Add:	5.1	gl
Slump: 5.	.00 in	#	Water	in Tru	ack: 0.0) gl	Adjus	t Wa	ter: 0	0.0) gl	/ Lo	ad	Trim Wate	er: -0.	5 gl/ CY					

SEE REVERSE SIDE FOR CONDITIONS OF SALE