



11011 Cody St Suite 150
Overland Park, KS 66210

Phone: 913.780.4605

A CRH COMPANY

Customer Signature X _____

CONDITION OF SALE: All accounts payable C.O.D. There will be a \$25.00 service charge on returned checks.

CUSTOMER # 238567	CUSTOMER Freedom Concrete LLC				PROJECT # 87518	PROJECT OAKVIEW STREETS - NW VICTORIA &	
PLANT 372	DATE 6/12/19 11:02	TIME 10:59	ORDER 367	TRUCK 268	DRIVER 751	REQUESTED TIME 6/12/19 11:24	PREVIOUS TRUCK 221
DELIVERY ADDRESS ((DONNIE))NW VICTORIA and NE D OUGLAS LSMO				DIRECTIONS COLBERN TO DOUGLAS S TO VICTORIADR W TO JOB SITE			
SLUMP 1.99		USAGE DESCRIPTION CURBHAND					
PO NUMBER		JOB NUMBER					

LOAD QUANTITY	CUMULATIVE QUANTITY	ORDERED QUANTITY	PROD ID	PRODUCT DESCRIPTION	UNIT	\$/UNIT	EXTENDED
9.00	21.00	21.00	340D4E02	KCMMB GR 4K F 2"	yd		
9.00		0.00	DELIVERY	DELIVERY CHARGE	/y		
9.00		0.00	998200	ENVIRONMENTAL FEE	/l		
9.00		0.00	NONTAXDE	NON TAXABLE DELIVERY CHARGE	/y		

TICKET NUMBER 37202371	WATER ADDED:					Sub-Total Sales Tax Total \$ Balance Due	
	_____ GALLONS TO _____ YARDS X _____						
	_____ GALLONS TO _____ YARDS X _____						
	_____ GALLONS TO _____ YARDS X _____						
LEAVE PLANT	ARRIVE JOB	START POUR	FINISH POUR	LEAVE JOB	ARRIVE PLANT	QUALITY / TESTING	
						SLUMP AIR CYLINDERS TAKEN	

DRIVER COMMENTS:

WARNING: INJURIES TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement, or cement mixture can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are tight at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, wear knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1%. Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear and appropriate NIOSH approved respirator during these activities.

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	Trim
3/4GRANITE	1695 lb	15408 lb	15340 lb	-0.44%	1.00% M	18 gl	
SAND-9	1295 lb	11946 lb	11900 lb	-0.39%	2.50% M	35 gl	
AG-I/II	510 lb	4590 lb	4616 lb	+ 0.57%			
DURAPOZF	90.0 lb	810.0 lb	800.0 lb	-1.23%			
H2OGL	29.50 gl	187.30 gl	187.00 gl	-0.16%		187.00 gl	-2.50 gl
WR-91	1.00 /C	54.00 oz	55.00 oz	1.85%			
AEA-92S	2.00 /C	108.00 oz	107.00 oz	-0.93%			

Actual	Num Batches: 1									
Load	34227 lb	Design W/C: 0.410	Water/Cement: 0.370	A	Design	265.5 gl	Actual	240.0 gl	To Add:	25.5 gl
Slump:	1.99 in	#	Water in Truck: 0.0 gl	Adjust Water:	0.0 gl / Load	Trim Water:	-2.5 gl /	CYT		



11011 Cody St Suite 150
Overland Park, KS 66210

Phone: 913.780.4605

A CRH COMPANY

Customer Signature X _____

CONDITION OF SALE: All accounts payable C.O.D. There will be a \$25.00 service charge on returned checks.

CUSTOMER # 238567	CUSTOMER Freedom Concrete LLC				PROJECT # 87518	PROJECT OAKVIEW STREETS - NW VICTORIA &	
PLANT 372	DATE 6/12/19 10:05	TIME 10:03	ORDER 367	TRUCK 221	DRIVER 607	REQUESTED TIME 6/12/19 10:23	PREVIOUS TRUCK 247
DELIVERY ADDRESS ((DONNIE))NW VICTORIA and NE D OUGLAS LSMO				DIRECTIONS COLBERN TO DOUGLAS S TO VICTORIADR W TO JOB SITE			
SLUMP 1.99		USAGE DESCRIPTION CURBHAND					
PO NUMBER		JOB NUMBER					

LOAD QUANTITY	CUMULATIVE QUANTITY	ORDERED QUANTITY	PROD ID	PRODUCT DESCRIPTION	UNIT	\$/UNIT	EXTENDED
6.00	12.00	12.00	340D4E02	KCMMB GR 4K F 2"	yd		
6.00		0.00	DELIVERY	DELIVERY CHARGE	/y		
6.00		0.00	998200	ENVIRONMENTAL FEE	/l		
6.00		0.00	NONTAXDE	NON TAXABLE DELIVERY CHARGE	/y		

TICKET NUMBER  37202364
--

WATER ADDED:

_____ GALLONS TO _____ YARDS X _____
_____ GALLONS TO _____ YARDS X _____
_____ GALLONS TO _____ YARDS X _____

Sub-Total
Sales Tax
Total \$
Balance Due

LEAVE PLANT	ARRIVE JOB	START POUR	FINISH POUR	LEAVE JOB	ARRIVE PLANT	QUALITY / TESTING
						SLUMP AIR CYLINDERS TAKEN

DRIVER COMMENTS:

WARNING: INJURIES TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement, or cement mixture can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are tight at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, wear knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1%. Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear and appropriate NIOSH approved respirator during these activities.

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	Trim
3/4GRANITE	1695 lb	10272 lb	10240 lb	-0.31%	1.00% M	12 gl	
SAND-9	1295 lb	7964 lb	7960 lb	-0.05%	2.50% M	23 gl	
AG-I/II	510 lb	3060 lb	3048 lb	-0.39%			
DURAPOZF	90.0 lb	540.0 lb	536.0 lb	-0.74%			
H2OGL	29.50 gl	124.04 gl	124.00 gl	-0.03%		124.00 gl	-2.50 gl
WR-91	1.00 /C	36.00 oz	36.00 oz	0.00%			
AEA-92S	2.00 /C	72.00 oz	71.00 oz	-1.39%			

Actual Load: 22825 lb Num Batches: 1 Design W/C: 0.410 Water/Cement: 0.371 A Design: 177.0 gl Actual: 159.4 gl To Add: 17.6 gl
Slump: 1.99 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.5 gl / CYC



11011 Cody St Suite 150
Overland Park, KS 66210

Phone: 913.780.4605

A CRH COMPANY

Customer Signature X _____

CONDITION OF SALE: All accounts payable C.O.D. There will be a \$25.00 service charge on returned checks.

CUSTOMER # 238567	CUSTOMER Freedom Concrete LLC				PROJECT # 87518	PROJECT OAKVIEW STREETS - NW VICTORIA &	
PLANT 372	DATE 6/12/19 8:43	TIME 8:40	ORDER 367	TRUCK 247	DRIVER 865	REQUESTED TIME 6/12/19 9:04	PREVIOUS TRUCK
DELIVERY ADDRESS ((DONNIE))NW VICTORIA and NE D OUGLAS LSMO				DIRECTIONS COLBERN TO DOUGLAS S TO VICTORIADR W TO JOB SITE			
SLUMP 1.99		USAGE DESCRIPTION CURBHAND					
PO NUMBER		JOB NUMBER					

LOAD QUANTITY	CUMULATIVE QUANTITY	ORDERED QUANTITY	PROD ID	PRODUCT DESCRIPTION	UNIT	\$/UNIT	EXTENDED
6.00	6.00	6.00	340D4E02	KCMMB GR 4K F 2"	yd		
6.00		0.00	DELIVERY	DELIVERY CHARGE	/y		
6.00		0.00	998200	ENVIRONMENTAL FEE	/l		
6.00		0.00	NONTAXDE	NON TAXABLE DELIVERY CHARGE	/y		

TICKET NUMBER  37202361
--

WATER ADDED:

_____ GALLONS TO _____ YARDS X _____
_____ GALLONS TO _____ YARDS X _____
_____ GALLONS TO _____ YARDS X _____

Sub-Total
Sales Tax
Total \$
Balance Due

LEAVE PLANT	ARRIVE JOB	START POUR	FINISH POUR	LEAVE JOB	ARRIVE PLANT	QUALITY / TESTING	
						SLUMP AIR	CYLINDERS TAKEN

DRIVER COMMENTS:

WARNING: INJURIES TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement, or cement mixture can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are tight at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, wear knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1%. Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear and appropriate NIOSH approved respirator during these activities.

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	Trim
3/4GRANITE	1695 lb	10272 lb	10260 lb	-0.11%	1.00% M	12 gl	
SAND-9	1295 lb	7964 lb	7940 lb	-0.30%	2.50% M	23 gl	
AG-I/II	510 lb	3060 lb	3064 lb	0.13%			
DURAPOZF	90.0 lb	540.0 lb	528.0 lb	-2.22%			
H2OGL	29.50 gl	124.04 gl	124.00 gl	-0.03%		124.00 gl	-2.50 gl
WR-91	1.00 /C	36.00 oz	35.00 oz	-2.78%			
AEA-92S	2.00 /C	72.00 oz	72.00 oz	0.00%			

Actual Load 22833 lb Slump: 1.99 in #
Num Batches: 1
Design W/C: 0.410
Water/Cement: 0.370 A
Water in Truck: 0.0 gl
Adjust Water: 0.0 gl / Load
Design 177.0 gl
Actual 159.4 gl
To Add: 17.6 gl
CYL