

Flying Biscuit

Summit Orchard
460 NW Chipman Rd.
Lee's Summit, MO 64086

RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
05/06/2020

Landlord's Tenant Improvements

Construction Documents

04-24-20



DRAWING INDEX

ARCHITECTURAL	
A-100	FIRST FLOOR CONSTRUCTION PLAN
A-101a	DL ASSEMBLY CASE




MECHANICAL AND ELECTRICAL	
ME-101	SYMBOLS AND ABBREVIATIONS - MECH AND ELEC.
ME-201	SPECIFICATIONS - MECHANICAL AND ELECTRICAL
ME-202	SPECIFICATIONS - MECHANICAL AND ELECTRICAL
ME-301	SPECIFICATIONS AND DETAILS - MECHANICAL AND ELECTRICAL
ME-302	SCHEDULES AND DETAILS - MECHANICAL AND ELECTRICAL
ME-401	FIRST FLOOR PLAN - MECHANICAL AND ELECTRICAL

ARCHITECT


SLAGGIE ARCHITECTS, INC.
4600 MADISON AVENUE, SUITE 350
KANSAS CITY, MO 64112
PHONE: (888) 756-1958

MEP ENGINEER

SMITH & BOUCHER ENGINEERS
25501 WEST VALLEY PARKWAY, SUITE 200
OLATHE, KS 66061
PHONE: (913) 345-0617




STOREFRONT GENERAL NOTES: <ol style="list-style-type: none"> SEE FLOOR PLANS FOR DOOR SWING DIRECTIONS. MANUFACTURER / FABRICATOR TO FIELD VERIFY ALL ALL DIMENSIONS / OPENINGS PRIOR TO GLASS FABRICATION. ALL DOORS TO RECEIVE 1/4" GLASS IN COLOR TO MATCH OTHER GLASS IN RESPECTIVE STOREFRONT UNLESS OTHERWISE NOTED. MANUFACTURER / FABRICATOR TO DETERMINE FINAL LOCATION OF HEAT-STRENGTHENED AND TEMPERED GLASS AS REQUIRED BY LOCAL CODE. PROVIDE HEAD AND SILL FLASHING AS REQUIRED PER STOREFRONT MANUFACTURER'S RECOMMENDATIONS. 	FRAME TYPES: <p>EXTERIOR STOREFRONT (SF): KAWNEER TRIPAB VERSAGLAZE 451-T 2" x 4 1/2" FRAME DIMENSION - 4 1/2" x 4 1/2" FRAME DIMENSION - FINISH: CLEAR ANODIZED</p>	GLASS TYPES: <p>GL-1 INSULATED LOW-E GLASS COLOR / FINISH: CLEAR NON-REFLECTIVE GLASS: AGC ENERGY SELECT 40</p> <p>T PROVIDE TEMPERED GLASS WHERE INDICATED. MANUFACTURER / FABRICATOR TO DETERMINE FINAL LOCATION OF HEAT-STRENGTHENED AND TEMPERED GLASS AS REQUIRED BY LOCAL CODE.</p> <p>NOTE: ALL STOREFRONT GLASS UNITS TO BE TYPE GL-1 UNLESS NOTED OTHERWISE</p>
---	---	---



DRAWING SYMBOL LEGEND		
SYMBOL	NAME	DESCRIPTION
	NEW DOOR IN NEW WALL	NEW DOOR (XXXX) AND FRAME IN NEW WALL. SEE DOOR SCHEDULE FOR DOOR INFORMATION.
	STOREFRONT	EXTERIOR ALUMINUM STOREFRONT. SEE FRAME TYPE ELEVATIONS FOR DETAILS. SFR INDICATES FRAME # ON FRAME TYPES SHEET.
	DOWNSPOUT	6"x6" PREFINISHED (KYNAR 500) ALUMINUM SHOP-FABRICATED BOX DOWNSPOUT FROM GUTTER OR SLOPPER ABOVE. CONTINUE TO UNDERGROUND STORM DRAIN SYSTEM PER CIVIL DRAWINGS U.N.O. SEE EXTERIOR ELEVATIONS FOR EXTERIOR FINISHES. HIDDEN SEAM - TYPICAL.
	ELEVATION	HEIGHT ABOVE FINISH FLOOR ELEVATION.
	WALL TYPE TAG	WALL TYPE SYMBOL INDICATES TYPE OF WALL CONSTRUCTION WITH FIRE RATING AND HEIGHT WHERE APPLICABLE. REFER TO WALL TYPES (SHEET A-002) FOR DETAILS.
	ENLARGED PLAN OR DETAIL TAG	ENLARGED DETAIL SYMBOL. INDICATES A PORTION OF THE DRAWING WHICH IS ENLARGED OR DETAILED. REFER TO SHEET AND DRAWING # INDICATED FOR ASSOCIATED DRAWING.
	WALL SECTION TAG	SECTION SYMBOL. INDICATES LOCATION OF SECTION CUT AND DIRECTION VIEWED. REFER TO SHEET AND DRAWING # INDICATED FOR ASSOCIATED SECTION.
	GRID LINE MARKER	STRUCTURAL GRID MARKER. REFERS TO STRUCTURAL ENGINEERING DRAWINGS' GRID LINE NUMBERING SYSTEM.

GENERAL NOTES	
<ol style="list-style-type: none"> ALL NEW CONSTRUCTION SHALL MEET LATEST EDITIONS OF ALL APPLICABLE NATIONAL, STATE, AND LOCAL BUILDING CODES. BUILDING PERMIT WILL BE REQUIRED FOR THE PROJECT. PERMIT SHALL BE OBTAINED AND PAID FOR BY THE GENERAL CONTRACTOR. CONTRACTOR SHALL VISIT THE JOB SITE AND SHALL REVIEW THE CONTRACT DOCUMENTS TO FAMILIARIZE HIMSELF WITH THE REQUIREMENTS AND INTENT OF THE SCOPE OF WORK PRIOR TO BID. ANY DEFICIENCIES OR DISCREPANCIES DISCOVERED SHALL BE REPORTED TO THE PROJECT MANAGER OR THE ARCHITECT FOR REVIEW AND CLARIFICATION PRIOR TO COMMENCING ANY WORK. EACH CONTRACTOR AND SUB-CONTRACTOR SHALL BE RESPONSIBLE FOR THE COORDINATION OF HIS WORK WITH THE WORK OF SUB-CONTRACTORS OR OTHER CONTRACTORS. WORKMANSHIP SHALL BE OF THE HIGHEST QUALITY. QUALITY MATERIALS SHALL BE USED THROUGHOUT. ALL WORK SHALL BE DONE IN A MANNER SO AS TO MATCH ADJACENT WORK AND FINISHES AND AS APPROVED BY OWNER. CONTRACTORS SHALL BE RESPONSIBLE FOR CONTAINING THEIR WORK WITHIN THE WORK AREA AND PROTECTING THE PUBLIC FROM INJURIES AT ALL TIMES. CONTRACTOR SHALL SECURE THE WORK AT THE END OF EACH WORK DAY. KEEP PREMISES BROOMED CLEAN AT ALL TIMES FROM FOREIGN MATERIAL CREATED UNDER THE CONTRACT. PROVIDE TARPULINS TO PROTECT ALL FINISHES, SURFACES, AND EQUIPMENT. AREAS FOR MATERIAL STORAGE, TRASH DISPOSAL, WORKMEN'S PARKING, ETC., SHALL BE COORDINATED WITH THE OWNER'S REPRESENTATIVE. ALL WOOD BLOCKING AND PLYWOOD BACKING SHALL BE FIRE RETARDANT TREATED. ALL DIMENSIONS SHALL BE VERIFIED BY CONTRACTOR. 	

CODE REVIEW	
ALL WORK UNDER THIS CONTRACT SHALL COMPLY WITH THE PROVISIONS OF THE SPECIFICATIONS AND DRAWINGS, AND SHALL SATISFY ALL APPLICABLE CODES, ORDINANCES AND REGULATIONS OF ALL GOVERNING BODIES INVOLVED.	
PROJECT INFORMATION SUMMARY:	
BUILDING OCCUPANCY:	GROUP A2
BUILDING CONSTRUCTION CLASS:	TYPE IIB
TENANT SPACE AREA:	3080.06 S.F.
BUILDING PROTECTED BY AUTOMATIC SPRINKLER SYSTEM:	YES
BUILDING IS PROTECTED BY AUTOMATIC FIRE ALARM SYSTEM (NFPA 70 AND NFPA 72):	YES
APPLICABLE CODES:	
BUILDING CODE:	INTERNATIONAL BUILDING CODE 2018 EDITION
MECHANICAL CODE:	INTERNATIONAL MECHANICAL CODE 2018 EDITION
PLUMBING CODE:	NATIONAL PLUMBING CODE 2018 EDITION
ELECTRICAL CODE:	NATIONAL ELECTRIC CODE 2017 EDITION
FIRE CODE:	INTERNATIONAL FIRE CODE 2018 EDITION
GAS CODE:	INTERNATIONAL FUEL GAS CODE 2018 EDITION
ANSI A117.1:	ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES 2017 EDITION
FIRE-RESISTANCE - BUILDING ELEMENTS (TABLE 601):	
FOR TYPE IIB CONSTRUCTION:	0 HRS
PRIMARY STRUCTURAL FRAME:	0 HRS
BEARING WALLS (EXTERIOR AND INTERIOR):	PER TABLE 602
NONBEARING WALLS - EXTERIOR:	0 HRS
NONBEARING WALLS - INTERIOR:	0 HRS
FLOOR CONSTRUCTION:	0 HRS
ROOF CONSTRUCTION:	0 HRS
FIRE-RESISTANCE FOR EXTERIOR WALLS - FIRE SEPARATION DISTANCE (TABLE 602):	
OCCUPANCY GROUP B	1 HR
X < 6	1 HR
6 < X < 10'	0 HR
10' < X < 30'	0 HR
X > 30'	0 HRS
NOTE: OCCUPANCY LOAD AND EXITING WILL BE PROVIDED IN THE TENANT FINISH PLANS SUBMITTED FOR EACH INDIVIDUAL TENANT	



DOOR #	ROOM #	WIDTH	HEIGHT	TYPE	FRAME TYPE	HEAD DETAIL	JAMB DETAIL	HWDR. GROUP #	COMMENTS
E001	AREA E	3'-0"	8'-0"	1GWA	AL			1	
E002	AREA E	3'-0"	8'-0"	1GWA	AL			1	



DOOR HARDWARE									
Hardware Set No. 1 (Single Storefront Aluminum/Glass Door)									
Qty:	1	Continuous Hinge	CFM-HD1		628	Pemko			
1	Morris Deadlock	MS1850SN		130	Adams Rite	Adams Rite			
1	Thumb Turn	4085-01		US302	Sargent	Sargent			
1	Cylinder, Mortise	DC1141101		AL	US302	Adams Rite			
1	Status Indicator	4089-00		130	Adams Rite	Adams Rite			
1	Push Bar & Pull	BF 15847		US302	Adams Rite	Adams Rite			
1	Concealed Closer	2033 H-Bumper		AL	Adams Rite	Adams Rite			
1	Threshold	2535SFG 36"		Aluminum Pan	Adams Rite	Adams Rite			
1	Adhesive Header Sign	"This Door to Remain Unlocked During Business Hours"		By Door Manuf.	Adams Rite	Adams Rite			
1	Set Weatherstrip			By Door Manuf.					
1	Door Sweep								

NOTE:	PROVIDE CONCEALED CLOSER (TYPICAL)
	1/4" CLEAR TEMPERED GLASS AT INTERIOR AND EXTERIOR DOORS
	DOOR FINISH TO MATCH STOREFRONT
	1" DIAMETER FULL ALUMINUM BENT PUSH AND PULL BARS (NO PLASTIC TRIM)

WIDE STILE ALUMINUM STOREFRONT DOOR	1GWA
	1/4" = 1'-0"

DOOR TYPE LEGEND	
Door Type:	Material:
1 = Single	A = Aluminum
2 = Double	F = Fiberglass
B = Bold	P = Plastic
O = Overhead	S = Steel
P = Pocket	W = Wood
S = Sliding	
Door Type Code: (Per Door Schedule)	
1	F S W
Defining Feature:	
B = Fabric	C = Coiling
E = Embossed	G = Grille
F = Flush	H = Hollow Core
G = Glass	M = Medium Stile
L = Louver	N = Narrow Stile
N = Narrow Lite	P = Panel (Sectional)
S = Security	R = Shutter
T = Traffic	S = Solid Core
V = View Lite(s)	W = Wide Stile
Example Shown = Single Flush Solid Core Wood	

RELEASE FOR CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
05/04/2020



UL Product iQ™

BXUVU425

- Design/System/Construction/Assembly Usage Disclaimer
- Authorities Having Jurisdiction should be consulted in all cases as to the particular requirements covering the installation and use of UL Certified products, equipment, system, devices, and materials.
 - Authorities Having Jurisdiction should be consulted before construction.
 - Fire resistance assemblies and products are developed by the design submitter and have been investigated by UL for compliance with applicable requirements. The published information cannot always address every construction nuance encountered in the field.
 - When field issues arise, it is recommended the first contact for assistance be the technical service staff provided by the product manufacturer noted for the design. Users of fire resistance assemblies are advised to consult the general Guide Information for each product category and each group of assemblies. The Guide Information includes specifics concerning alternate materials and alternate methods of construction.
 - Only products which bear UL's Mark are considered Certified.

BXUV - Fire Resistance Ratings - ANSI/UL 263 Certified for United States
BXUV7 - Fire Resistance Ratings - CAN/ULC-S101 Certified for Canada

See General Information for Fire-resistance Ratings - ANSI/UL 263 Certified for United States Design Criteria and Allowable Variances

See General Information for Fire Resistance Ratings - CAN/ULC-S101 Certified for Canada Design Criteria and Allowable Variances

Design No. U425


March 05, 2020

Bearing Wall Rating — 3/4 Hr., 1, 1-1/2 or 2 Hr.
(See Items 2, 4 and 5)


This design was evaluated using a load design method other than the Limit States Design Method (e.g., Working Stress Design Method). For jurisdictions employing the Limit States Design Method, such as Canada, a load restriction factor shall be used — See Guide BXUV or BXUV7

* Indicates such products shall bear the UL or cUL Certification Mark for jurisdictions employing the UL or cUL Certification (such as Canada), respectively.

INTERIOR OR EXTERIOR WALL (FIRE FROM EITHER SIDE), SEE TABLE I



EXTERIOR WALL (FIRE FROM INTERIOR SIDE ONLY), SEE TABLE II



1. **Steel Floor and Ceiling Tracks** — (Not Shown) — Top and bottom tracks of wall assemblies shall consist of steel members, min No. 20 MSG (0.0329 in., min bare metal thickness) steel or min No. 20 MSG (0.036 in. thick) galv steel or No. 20 MSG (0.033 in. thick) primed steel, that provide a sound structural connection between steel studs, and to adjacent assemblies such as a floor, ceiling, and/or other walls. Attached to floor and ceiling assemblies with steel fasteners spaced not greater than 24 in. OC.

2. **Steel Studs** — Min 3-1/2 in. wide, No. 20 MSG (0.0329 in., min bare metal thickness) corrosion protected cold formed steel studs designed in accordance with the current edition of the Specification for the Design of Cold-Formed Steel Structural Members by the American Iron and Steel Institute. All design details enhancing the structural integrity of the wall assembly, including the axial design load of the studs, shall be as specified by the steel stud designer and/or producer, and shall meet the requirements of all applicable local code agencies. The max stud spacing of wall assemblies shall not exceed 24 in. OC or 16 in. OC when Item 5b is used. Studs attached to floor and ceiling tracks with 1/2 in. long Type S-12 steel screws on both sides of studs or by welded or bolted connections designed in accordance with the AISI specifications.

2A. **Steel Studs — Framing Members*** — In lieu of Item 2 — Min 3-1/2 in. wide, No. 20 MSG (0.0329 in., min bare metal thickness) corrosion protected cold formed steel studs designed in accordance with the current edition of the Specification for the Design of Cold-Formed Steel Structural Members by the American Iron and Steel Institute. All design details enhancing the structural integrity of the wall assembly, including the axial design load of the studs, shall be as specified by the steel stud designer and/or producer, and shall meet the requirements of all applicable local code agencies. The max stud spacing of wall assemblies shall not exceed 24 in. OC or 16 in. OC when Item 5b is used. Studs attached to floor and ceiling tracks with 1/2 in. long Type S-12

steel screws on both sides of studs or by welded or bolted connections designed in accordance with the AISI specifications.
IB METAL INC — NITROSTUD

2B. **Steel Studs — Framing Members*** — In lieu of Item 2 — Min 3-5/8 in. wide, No. 20 MSG (0.036 in. min. thickness) corrosion protected cold formed steel studs designed in accordance with the current edition of the Specification for the Design of Cold-Formed Steel Structural Members by the American Iron and Steel Institute. All design details enhancing the structural integrity of the wall assembly, including the axial design load of the studs, shall be as specified by the steel stud designer and/or producer, and shall meet the requirements of all applicable local code agencies. The max stud spacing of wall assemblies shall not exceed 24 in. OC or 16 in. OC when Item 5b is used. Studs attached to floor and ceiling tracks with 1/2 in. long Type S-12 steel screws on both sides of studs or by welded or bolted connections designed in accordance with the AISI specifications.

BAILEY METAL PRODUCTS LTD

3. **Lateral Support Members** — (Not Shown) — Where required for lateral support of studs, support may be provided by means of steel straps, channels or other similar means as specified in the design of a particular steel stud wall system.

4. **Gypsum Board*** — Any 1/2 in. thick UL Classified Gypsum Board that is eligible for use in Design No. J515. Any 5/8 in. thick UL Classified Gypsum Board that is eligible for use in Design Nos. L501, G512 or U505. Gypsum board bearing the UL Classification Marking as to Fire Resistance. Applied vertically with joints between layers staggered. Outer layer of 3 layer construction may be applied horizontally unless specified below. The thickness and number of layers and percent of design load for the 45 min, 1 hr., 1-1/2 hr and 2 hr ratings are as follows:

TABLE I Interior or Exterior Walls (Fire From Either Side)			
Wallboard Protection Both Sides of Wall - No. of Layers & Thickness of Board in. Each Layer			
Rating			% of Design Load
45 min	1 layer, 1/2 in. thick		100
1 hr	1 layer, 5/8 in. thick		100
1-1/2 hr	2 layers, 1/2 in. thick		100
2 hr	2 layers, 5/8 in. thick or		80
2 hr	3 layers, 1/2 in. thick		100
2 hr	2 layers, 3/4 in. thick		100

Note: Exterior facings allowed for use with Item 5 are also allowed to be installed on one side of the above walls.

TABLE II
Exterior Walls (Fire From Interior Side Only)

Wallboard Protection on Interior Side of Wall - No. of Layers & Thickness of Board in. Each Layer			
Rating			% of Design Load
45 min	1 layer, 5/8 in. thick		100
1 hr	2 layers, 1/2 in. thick		100
1-1/2 hr	2 layers, 5/8 in. thick		100
2 hr	3 layers, 1/2 in. thick		100
2 hr	2 layers, 3/4 in. thick		100

AMERICAN GYPSUM CO (View Classification) — CNXK.R14196

BEIJING NEW BUILDING MATERIALS PUBLIC LTD CO (View Classification) — CNXK.R19374

CABOT MANUFACTURING ULC (View Classification) — CNXK.R23730

CERTAINTED GYPSUM INC (View Classification) — CNXK.R3660

CGC INC (View Classification) — CNXK.R19751

CONTINENTAL BUILDING PRODUCTS OPERATING CO. L L C (View Classification) — CNXK.R18482

GEORGIA-PACIFIC GYPSUM L L C (View Classification) — CNXK.R2717

LOADMASTER SYSTEMS INC (View Classification) — CNXK.R11809

NATIONAL GYPSUM CO (View Classification) — Riyadh, Saudi Arabia — CNXK.R15208

NATIONAL GYPSUM CO (View Classification) — CNXK.R3501

PARCO BUILDING PRODUCTS L L C, DBA PARCO GYPSUM (View Classification) — CNXK.R7904

PANEL REY S A (View Classification) — CNXK.R21796

SIAM GYPSUM INDUSTRY (SARABURI) CO LTD (View Classification) — CNXK.R19262

THAI GYPSUM PRODUCTS PCL (View Classification) — CNXK.R27517

UNITED STATES GYPSUM CO (View Classification) — CNXK.R1319

USG BORAL DRYWALL SFZ LLC (View Classification) — CNXK.R38438

USG MEXICO S A DE CV (View Classification) — CNXK.R16089

4A. **Gypsum Board** — Nom. 3/4 in. gypsum board applied vertically with joints between layers staggered. The thickness and number of layers and percent of design load for the 2 hr ratings are shown in the table above.
CGC INC — Types AR, IP-AR, IP-X3, or ULTRACODE

UNITED STATES GYPSUM CO — Types AR, IP-AR, IP-X3, or ULTRACODE

USG BORAL DRYWALL SFZ LLC — Type ULTRACODE

USG MEXICO S A DE CV — Types AR, IP-AR, IP-X3, or ULTRACODE

4B. **Gypsum Board*** — (As an alternate to Item 4) — Nom. 5/8 in. thick gypsum panels, with square edges, applied horizontally. Gypsum panels fastened to framing with 1 in. long bugle head steel screws spaced a max 8 in. OC, with last 2 screws 3/4 in. and 4 in. from each edge of board. Horizontal joints need not be backed by steel framing. Horizontal edge joints and horizontal butt joints on opposite sides of studs on interior walls need not be staggered. Horizontal edge joints and horizontal butt joints in adjacent layers on interior walls (multilayer systems) staggered a min of 12 in.
GEORGIA-PACIFIC GYPSUM L L C — GreenGloss Type X, Type DGG

NATIONAL GYPSUM CO — Type PSW-6.

CERTAINTED GYPSUM INC — GlasRoc

4C. **Gypsum Board*** — (As an alternate to Item 4) — 5/8 in. thick, 4 ft. wide, paper surfaced applied vertically only and secured as described in Item 6.
GEORGIA-PACIFIC GYPSUM L L C — Type X ComfortGuard Sound Deadening Gypsum Board.

NATIONAL GYPSUM CO — Type SBWB

4D. **Wall and Partition Facings and Accessories*** — (As an alternate to Item 4) — Nominal 5/8 in. thick, 4 ft wide panels, applied vertically and secured as described in Item 4.
PARCO BUILDING PRODUCTS L L C, DBA PARCO GYPSUM — Type QuietRock ES.

4E. **Wall and Partition Facings and Accessories*** — (As an alternate to Item 4) — Nominal 5/8 in. thick, 4 ft wide panels, applied vertically and secured as described in Item 4.
PARCO BUILDING PRODUCTS L L C, DBA PARCO GYPSUM — Type QuietRock S27.

4F. **Gypsum Board*** — (As an alternate to 5/8 in. Type PSW in Item 4) — Nom. 5/16 in. thick gypsum panels applied vertically. Two layers of 5/16 in. for every single layer of 5/8 in. gypsum board described in Item 4. Horizontal joints on the same side need not be staggered. Inner layer of each double 5/16 in. layer attached with fasteners, as described in Item 4, spaced 24 in. OC. Outer layer of each double 5/16 in. layer attached per Item 4.
NATIONAL GYPSUM CO — Type PSW.

4G. **Wall and Partition Facings and Accessories*** — (As an alternate to 5/8 in. thick board as outlined in Item 4) — Nominal 1-3/8 in. thick, 4 ft wide panels, applied vertically or horizontally. Fastened to studs as described in Item 6.
PARCO BUILDING PRODUCTS L L C, DBA PARCO GYPSUM — Type QuietRock S45

5. **Gypsum Boards** — For exterior walls, Rating from Interior Side Only - 1/2 or 5/8 in. thick. Classified or unclassified gypsum boards applied vertically and attached to studs and runner tracks with 1 in. long Type S-12 bugle head screws spaced 12 in. OC, along studs and tracks. One of the following exterior facings are to be applied over the gypsum board.

a. **Siding, Brick, or Stucco** — Aluminum siding, steel siding, brick veneer, or stucco attached to studs over gypsum sheathing and meeting the requirements of local code agencies. When a min 3-3/4 in. thick brick veneer facing is used, the Exterior Wall Rating is applicable with exposure on either face. Brick veneer wall attached to studs with corrugated metal wall ties attached to each stud with steel screws, not more than each sixth course of brick. When a min 3-3/4 in. thick brick veneer facing is used, Foamed Plastic (Item 10) may be used.

b. **Cementitious Backer Units*** — 1/2 or 5/8 in. thick, attached vertically or horizontally to steel studs over gypsum sheathing with 1-5/8 in. long, Type S-12, corrosion resistant, waffle head steel screws, spaced 8 in. OC. Studs spaced a max of 16 in. OC. Joints covered with glass fiber mesh tape.
UNITED STATES GYPSUM CO — Type DCB

NATIONAL GYPSUM CO — Type PermBase, or DuraBacker

c. **Fiber-Cement Siding** — Fiber-cement exterior sidings including smooth and patterned panel or lap siding.

d. **Molded Plastic*** — Solid vinyl siding mechanically secured to framing members in accordance with manufacturer's recommended installation details.
ALSID, DIV OF ASSOCIATED MATERIALS INC

e. **Wood Structural Panel or Lap Siding** — APA Rated Siding, Exterior, plywood, OSB or composite panels with veneer faces and structural wood core, per PS 1 or APA Standard PRP-108, including textured, rough sawn, medium density overlay, brushed, grooved and lap siding.

f. **Building Units*** — (Not Shown) — 3 in. thick 18 x 24 in. cellular glass blocks, applied to the gypsum board (Item 5) with PC B8 adhesive or fastened with anchors spaced a maximum 24 in. OC. F anchors fastened to framing members with 1-1/4 in. long #6 drywall screws.
PITTSBURGH CORNING CORP — Type Fawdium

6. **Fasteners** — (Not Shown) — Screws used to attach wallboard to studs; self-tapping bugle head sheet steel type, spaced 12 in. OC. First layer Type S-12 by 1 in. long for 1/2 and 5/8 in. thick wallboards and 1-1/4 in. long for 3/4 in. thick wallboard. Second layer Type S-12 by 1-1/2 in. long for 1/2 and 5/8 in. thick wallboards and 2-1/4 in. long for 3/4 in. thick wallboard. Third layer Type S-12 by 1-7/8 in. long. Fasteners when Item 4G is used: First layer #6 x 2 in. long drywall screw spaced 8 in. OC along the perimeter and 12 in. OC in the field. Second layer #6 x 4 in. long drywall screw spaced 8 in. OC along the perimeter and 12 in. OC in the field. Horizontal joints to be staggered 12 in. between layers.

7. **Batts and Blankets*** — Placed in stud cavities of all exterior walls. May or may not be used in interior walls. Any glass fiber or mineral wool batt material bearing the UL Classification Marking as to Fire Resistance, of a thickness to completely fill stud cavity. See **Batts and Blankets** (B2JZ) Category for names of Classified companies.

7A. **Fiber, Sprayed*** — As an alternate to Batts and Blankets (Item 7) — (100% Borate Formulation) — Spray applied cellulose material. The fiber is applied with water to completely fill the enclosed cavity in accordance with the application instructions supplied with the product with a nominal dry density of 2.7 lb/ft³. Alternate Application Method: The fiber is applied without water or adhesive at a nominal dry density of 3.5 lb/ft³, in accordance with the application instructions supplied with the product.
U S GRENFIBER, L L C — IN5731, IN5745, IN5750LD for use with wet or dry application. IN5750SD and IN5730LD are to be used for dry application only.

7B. **Fiber, Sprayed*** — As an alternate to Item 7 — Spray applied cellulose material. The fiber is applied with water to completely fill the enclosed cavity in accordance with the application instructions supplied with the product. Nominal dry density of 4.58 lb/ft³.
NU-WOOD CO INC — Cellulose Insulation

7C. **Fiber, Sprayed*** — As an alternate to Batts and Blankets (Item 7) — Spray applied cellulose fiber. The fiber is applied with water to completely fill the enclosed cavity in accordance with the application instructions supplied with the product. The minimum dry density shall be 4.30 lb/ft³.
INTERNATIONAL CELLULOSE CORP — Celbar-RL

7D. **Fiber, Sprayed*** — (Optional) — As an alternate to Batts and Blankets (Item 7) — Spray applied mineral wool insulation. The fiber is applied with adhesive, at a minimum density of 4.0 gsf, to completely fill the enclosed cavity in accordance with the application instructions supplied with the product. See Fiber, Sprayed (CCA2).
AMERICAN ROCKWOOL MANUFACTURING, LLC — Type Rockwool Premium Plus

8. **Joint Tape and Compound** — (Not Shown) — Vinyl or casin, dry or premixed joint compound applied in two coats to joints and screw heads of outer layer. Perforated paper tape, 2 in. wide, embedded in first layer of compound over all joints of outer layer.

9. **Furring Channels** — (Optional, Not Shown, for single or double layer systems) — Resilient furring channels fabricated from min 25 MSG corrosion-protected steel, spaced vertically a max of 24 in. OC. Flange portion attached to each intersecting stud with 1/2 in. long Type S-12 steel screws.

10. **Foamed Plastic*** — (Optional, Not Shown) For use with brick veneer as outlined in Item 5a - Maximum 2 in. thick rigid polystyrene insulation attached to studs with fasteners of sufficient length to penetrate the foam and 3/16 in. into the stud. A minimum 1 in. air space is to be maintained between the outer surface of the foamed plastic and the inner surface of the brick veneer.
ATLAS MOLDED PRODUCTS, A DIVISION OF ATLAS ROOFING CORPORATION — Type ThermaStar

OWENS CORNING SCIENCE AND TECHNOLOGY, LLC

10A. **Foamed Plastic*** — (Optional, Not shown) — For use with brick veneer as outlined in Item 5a - Mortar drop protection - Foamed plastic with mortar control device attached, continuous, with drainage holes at bottom of air space behind brick veneer.
OWENS CORNING SCIENCE AND TECHNOLOGY, LLC — WeggGuard

10B. **Foamed Plastic*** — Polysocyanurate foamed plastic insulation boards, any thickness. Classified in accordance with B7XX and / or CCRW. May be used with any exterior facing shown under Items 5a, 5c, 5d and 5e.
ATLAS ROOFING CORP — EnergyShield Pro Wall Insulation*, EnergyShield Pro 3 Wall Insulation*, EnergyShield GSF Pro and EnergyShield Pfy Pro

CARLISLE COATINGS & WATERPROOFING INC — Type R2+ SHEATHE

DUPONT DE NEMOURS, INC. — Type Therma Sheathing, Therma Light Duty Insulation, Therma Heavy Duty Insulation, Therma Metal Building Board, Therma White Finish Insulation, Therma c Exterior Insulation, Therma XAARMOR c Exterior Insulation, Therma HI Insulation, Therma Plus Liner Panel, Therma Heavy Duty Plus (HDP), TUFF-8™ c Insulation, Therma ButylShield Insulation Board and Therma Morton Heavy Duty Insulation Board

FIRESTONE BUILDING PRODUCTS CO L L C — "Energizer" c Foil Exterior Wall Insulation" and "Energizer" c Glass Exterior Wall Insulation"

HUNTER PANELS, A DIVISION OF CARLISLE CONSTRUCTION MATERIALS, LLC — Type "Xci Class A"; "Xci 286"; "Xci Foil (Class A)"; "Xci CG"; "Xci Foil"; "Xci CG NF"; "Xci Foil NF"; "Xci Foil NF"

RMAX OPERATING L L C — Types "TSX-8500"; "ECOMAXI FR"; "TSX-8510"; "ECOMAXI FR White"; "ECOMAXI"; "ECOMAXI FR Air Barrier"; "Thermasheath-XP"; "Thermasheath"; "Durasheath"; "Thermasheath-3"; "Durasheath-3".

10C. **Building Unit*** — Polysocyanurate foamed plastic composite insulation boards, any thickness. Classified in accordance with B2XX. May be used with any exterior facing shown under Items 5a, 5c, 5d and 5e.
HUNTER PANELS, A DIVISION OF CARLISLE CONSTRUCTION MATERIALS, LLC — Type "Xci NF" and "Xci Pfy"

LAMINATIONS INC — Type "Omega c"

RMAX OPERATING L L C — Types ThermaSheath-SI, ECOMAXI, ECOMAXI FR Pfy, ThermaBase c, "ECOMAXI Pfy"; attached to studs with Type S screws long enough to penetrate the studs a minimum of three threads.

10D. **Foamed Plastic*** — (As an alternate to Item 10 - Not Shown) — Expanded polystyrene insulation installed to a maximum nominal density of 2.0 lb/ft³.

BASF CORP STYRENIC FOAMS DIV — Type Neopor "N" Series

11. **Cementitious Backer Units*** — (Optional, Not Shown - For Use as an additional layer over required gypsum boards) - 7/16 in., 1/2 in., 5/8 in., 3/4 in., or 1 in. thick, min. 32 in. wide - Applied vertically or horizontally with vertical joints centered over studs. Fastened to studs and runners with cement board screws of adequate length to penetrate stud by a minimum of 3/8 in. spaced a max of 8 in. OC. When 4 ft. wide boards are used, horizontal joints need not be backed by framing.
NATIONAL GYPSUM CO — Type DuraBacker, PermBase, DuraBacker Plus, or PermBase Plus

12. **Wall and Partition Facings and Accessories*** — (Optional, Not Shown) — For use with Item 1, Items 2 and 2A, Item 3, Item 4 to 4B, Item 6, Item 7, Item 8 and Item 9. For maximum fire rating of 1 hour. On one side of the wall, over the first layer of Gypsum Board (Item 4 to 4B), install Reflector membrane with the gold side facing outwards. Membrane installed with 150 staples spaced 12 inches on center in both directions as per manufacturer's instructions, seams in membrane to be overlapped by 2 inches. When Reflector membrane is used an additional layer of Gypsum Board that is identical to the one used in the first layer and as specified in Item 4 to 4B shall be installed over the membrane. The additional layer of Gypsum Board to be installed through the membrane to the stud as specified in Item 4 to 4B except the fastener length shall be increased by a minimum of 5/8 inch. Install Batts and Blankets in the stud cavity as per Item 7. On the other side of the wall prior to the installation of the Gypsum Board install Resilient Channels, 25 MSG galv-steel, spaced vertically 24 in. OC. Large portion screw attached to one side of studs with 1-1/4 in. long diamond shaped point, double lead Phillips head steel screws. Over the Resilient Channels install 3/4 inch thick SONOpan panel secured to the Resilient Channels with drywall screws and washers spaced at 16 in. OC on the perimeter of the panel and 8 in. OC in the field of the panel. Over the SONOpan panel install the same Gypsum Board as specified in Item 4 (and 4 alternates) with the fastener length increased by minimum 3/4 inch. Not evaluated or intended as a substitute for the required layer(s) of UL Classified Gypsum Board.
MSL — Reflector membrane, SONOpan panel.

13. **Wall and Partition Facings and Accessories*** — (Optional, Not Shown) - **When the Wall Assembly is used as an External Wall, on the External side of the wall one of the following Wall and Partition and Facing Accessories may be used, refer to Items (A) to (C) below.**

A. **Non Insulated System with Metal Channels** — Install moisture barrier over the Gypsum Board Item 4 and install Acrytec Panels on Acry Metal Channels vertically at a horizontal spacing not greater than 24 inches OC over the moisture barrier. Any Metal Channels attached through the moisture barrier and the Gypsum Board to the Steel Studs Item 2 using fasteners specified by the manufacturer and fasteners spaced max. 24 in. OC. Install Acrytec Panels on Acry Metal Channels using 1-1/4" long corrosion coated stainless steel screws spaced at a max spacing of 24 inches OC, along with manufacturer's approved adhesive (3M 540 or Tremco Vulcum 116). Adhesive to be applied in a zigzag pattern along every channel. Joint treatment in between panels shall be Tremco Ilmod 600 pre compressed polyurethane foam sealant.

B. **Insulated System with Metal Channels** — Install moisture barrier over the Gypsum Board Item 4. Install galvanized Z girt channels specified by the manufacturer over the moisture barrier and the Gypsum Board Item 4. Z girt channels to be installed horizontally at a max. spacing of 24" OC. Z girt channels attached through the Gypsum Board and the moisture barrier to the Steel Studs Item 2, with screws provided by the manufacturer at a max spacing of 24 inches OC. Install mineral wool insulation between the Z girts. Maximum thickness of mineral wool insulation not to exceed 6 in. As per manufacturer's instructions install Acry Metal Channels vertically over the Z girts at a max horizontal spacing of 24 in. OC. Acrytec Panels installed on Acry channel with 1-1/4" long corrosion coated stainless steel screws at a max spacing of 24 in. OC, along with manufacturer's approved adhesive (3M 540 or Tremco Vulcum 116).

Adhesive to be applied in a zigzag pattern along every channel. Joint treatment in between panels to be Tremco Ilmod 600 pre compressed polyurethane foam sealant.

C. **Non Insulated Wood Strapping System** — Install moisture barrier over the Gypsum Board Item 4 and install 1" x 3" wood strapping vertically at a horizontal spacing not greater than 24 inches OC, over the moisture barrier. 1" x 3" wood strapping attached through the moisture barrier and the Gypsum Board to the Steel Studs Item 2, using fasteners specified by the manufacturer and fasteners spaced max. 24 in. OC. Acrytec Panels to be installed on the 1" x 3" wood strapping using manufacturer's approved stainless steel fasteners spaced at maximum 24 inches OC along with Tremco Vulcum 116 adhesive applied in a zigzag pattern along every wood strap. Joint treatment in between panels to be Tremco Ilmod 600 pre compressed polyurethane foam sealant.

D. **Insulated Wood Strapping System** — Install moisture barrier over the Gypsum Board Item 4. Install Extruded Polystyrene Insulation over moisture barrier, max thickness of insulation not to exceed 4 inches. Install 1" x 3" wood strapping vertically at a horizontal spacing not greater than 24 inches OC. Wood strapping attached through the insulation, the Gypsum Board and moisture barrier to the Steel Studs Item 2 using fasteners specified by the manufacturer and fasteners spaced max. 24 in. OC. Acrytec Panels to be installed over the wood strapping using manufacturer's approved stainless steel fasteners at a max spacing of 24 in. OC, and Tremco Vulcum 116 adhesive applied in a zigzag pattern along every wood strap. Joint treatment in between panels to be Tremco Ilmod 600 pre compressed polyurethane foam sealant.
ACRYTEC PANEL INDUSTRIES — Nominal 5/8 inch thick Acrytec Panel.

* Indicates such products shall bear the UL or cUL Certification Mark for jurisdictions employing the UL or cUL Certification (such as Canada), respectively.


Last Updated on 2020-09-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data or drawings; 2. The statements "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

RELEASE FOR CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
05/06/2020

SAI
Kamen City, Missouri • Omaha, Nebraska
888.756.1958
slaggle.com



Flying Biscuit
Landlord's Tenant Improvements

Summit Orchard
460 NW Chipman Rd.
Lee's Summit, MO 64086

Revisions:		
1	Add City Councils	05-01-2020






Project #: 180902-04

Construction Documents
04-24-20

















UL ASSEMBLY U425

A-101a















CONDUIT AND WIRE

	ARROWS INDICATE CONDUIT AND WIRE HOME RUN(S) TO PANEL WITH 2-#12 AWG CONDUCTORS UNLESS NOTED OR OTHERWISE REQUIRED.
	CONDUIT RUN CONCEALED IN WALL OR ABOVE CEILING.
	CONDUIT RUN UNDERGROUND OR CONCEALED IN FLOOR SLAB.
	TELEPHONE CONDUIT
	LOW VOLTAGE CONDUIT AND WIRING








LIGHTING

	BATTERY OPERATED EMERGENCY LIGHT (WALL MOUNTED)
	BATTERY OPERATED EMERGENCY LIGHT (CEILING MOUNTED)
	SURFACE/RECESSED LIGHT FIXTURE
	FLUORESCENT LIGHT FIXTURE
	FLUORESCENT STRIP FIXTURE
	SHADING DENOTES EMERGENCY FIXTURE
	POLE MOUNTED LIGHT FIXTURE
	EXIT LIGHT - DOUBLE FACE - ARROWS AS SHOWN
	EXIT LIGHT - SINGLE FACE - ARROWS AS SHOWN
	LIGHTING SWITCHES-SINGLE POLE, 3-WAY, 4-WAY, KEY, LOW VOLTAGE, PILOT LIGHT
	DIMMER WITH SINGLE POLE SWITCH
	DIMMER WITH THREE WAY SWITCH (WATTAGE NOTED)
	WALL MOUNTED MOTION SENSOR
	CEILING MOUNTED MOTION SENSOR (LETTER DENOTES TYPE)
	SWITCH AND DUPLEX RECEPTACLE
	DENOTES A WALL MOUNTED FIXTURE









WIRING DEVICES

	DUPLEX RECEPTACLE.
	LINE THRU DEVICE INDICATES ABOVE COUNTER
	DUPLEX RECEPTACLE WITH ISOLATED GROUND (SINGLE AND FOURPLEX SIMILAR)
	DUPLEX RECEPTACLE - TOP HALF SWITCHED - BOTTOM HALF TO HAVE POWER AT ALL TIMES
	DUPLEX RECEPTACLE ON EMERGENCY POWER (SINGLE AND FOURPLEX SIMILAR)
	FOURPLEX RECEPTACLE
	SINGLE RECEPTACLE
	CEILING MOUNTED RECEPTACLE
	MULTI-SERVICE FLOOR BOX
	DIVIDED POWER POLE
	FLOOR BOX W/DUPLEX RECEPTACLE
	SPECIAL RECEPTACLE W/NEMA CONFIGURATION AS NOTED
	CLOCK RECEPTACLE
	MULTI-OUTLET ASSEMBLY









COMMUNICATIONS

	TELEPHONE OUTLET
	LINE THRU DEVICE INDICATES ABOVE COUNTER
	DATA OUTLET
	TELEPHONE/DATA OUTLET
	FLOOR BOX WITH COMMUNICATIONS OUTLET
	TELEVISION ANTENNA OUTLET
	TELEPHONE CABINET OR PLYWOOD BOARD















SECURITY

	CLOSED CIRCUIT TV CAMERA
	CARD READER
	DOOR LOCK
	SECURITY MONITOR
	WATCH TOUR
	ELECTRIC DOOR LOCK
	MOTION SENSOR - SECURITY
	MOTION SENSOR (WALL MOUNTED) - SECURITY

















PUBLIC ADDRESS

	MICROPHONE OUTLET
	SPEAKER. ('H' DENOTES HORN TYPE)
	SPEAKER VOLUME CONTROL
	SPEAKER VOLUME CONTROL
	BELL
	INTERCOM OUTLET
	INTERCOM OUTLET - MASTER
	CLOCK SYSTEM RECEPTACLE WITH SINGLE FACE ('D' DENOTES DOUBLE FACE)













POWER DEVICE AND CONTROLS

	THERMOSTAT
	DISCONNECT SWITCH. 30A-3P, NON-FUSED EXCEPT AS NOTED
	MANUAL MOTOR STARTER
	MAGNETIC MOTOR STARTER
	COMBINATION MOTOR STARTER AND DISCONNECT SWITCH
	MOTOR
	PANELBOARD (SEE ONE-LINE)
	DISTRIBUTION PANELBOARD
	CONTACTOR
	AUTOMATIC TRANSFER SWITCH
	PHOTOCELL
	JUNCTION BOX
	PUSHBUTTON
	TRANSFORMER











FIRE ALARM

	MANUAL PULL STATION
	PHOTOELECTRIC DETECTOR ('D' DENOTES IN DUCT) ('B' DENOTES BEAM-TYPE) ('R' DENOTES IN RETURN AIR PLENUM)
	IONIZATION DETECTOR ('D' DENOTES IN DUCT) ('P' DENOTES PLENUM-TYPE)
	INFRARED DETECTOR ('D' DENOTES IN DUCT) ('F' DENOTES IN FLOOR)
	THERMODEETECTOR ('D' DENOTES IN DUCT) ('F' DENOTES IN FLOOR)
	DOOR HOLDER
	CHIME
	BELL
	FIRE ALARM STROBE LIGHT
	FIRE ALARM SPEAKER - ARROWS DENOTE PROJECTORS IF ANY. ('L' DENOTES COMBINATION SPEAKER AND VISUAL FIRE LIGHT)
	FIRE HORN. ('L' DENOTES COMBINATION HORN AND VISUAL FIRE LIGHT)
	REMOTE ALARM LAMP
	POST INDICATOR SWITCH
	FLOW SWITCH
	GATE SWITCH
	FIREMAN'S PHONE JACK































FIRE PROTECTION

	FIRE PROTECTION PIPING
	FIRE HOSE CABINET
	FIRE DEPARTMENT VALVE
	UPRIGHT SPRINKLER HEAD
	PENDENT SPRINKLER
	RECESSED SPRINKLER
	RECESSED SPRINKLER WITH CLOSURE PLATE
	SIDEWALL SPRINKLER.
	DOUBLE CHECK DETECTOR BACKFLOW PREVENTER
	FIRE PROTECTION SIAMESE CONNECTION
	FIRE PROTECTION SIDEWALK SIAMESE CONNECTION
	POST INDICATOR VALVE













MEDICAL GAS

	MEDICAL VACUUM
	OXYGEN
	NITROUS OXIDE
	MEDICAL COMPRESSED AIR
	NITROGEN
	OXYGEN OUTLET
	VACUUM OUTLET
	MEDICAL AIR OUTLET
	NITROUS OXIDE OUTLET
	NITROGEN OUTLET




























HVAC

	CHILLED WATER SUPPLY
	CHILLED WATER RETURN
	CHILLED/HOT WATER SUPPLY
	CHILLED/HOT WATER RETURN
	HEATING HOT WATER SUPPLY
	HEATING HOT WATER RETURN
	COOLING TOWER SUPPLY
	COOLING TOWER RETURN
	LOW PRESSURE STEAM
	LOW PRESSURE CONDENSATE RETURN
	HIGH PRESSURE STEAM - NO'S GIVE GAUGE PRESSURE IN P.S.I.
	HIGH PRESSURE RETURN - NO'S GIVE GAUGE PRESSURE IN P.S.I.
	REFRIGERANT DISCHARGE
	REFRIGERANT LIQUID
	REFRIGERANT SUCTION
	FUEL OIL SUPPLY
	FUEL OIL RETURN
	COMPRESSED AIR
	DRAIN (CONDENSATE)
	THERMOSTAT - ('S' DENOTES SENSOR)
	HUMIDISTAT - ('S' DENOTES SENSOR)
	THERMOSTAT/HUMIDITY SENSOR
	CARBON DIOXIDE SENSOR
	THERMOSTAT/HUMIDITY SENSOR/CO2 SENSOR
	HUMIDIFIER
	SUPPLY AIR FLOW INDICATOR
	RETURN AND EXHAUST AIR FLOW INDICATOR
	SUPPLY DIFFUSER
	SUPPLY STRIP DIFFUSER
	RETURN GRILLE OR EXHAUST REGISTER








HOSPITAL

	NURSE CALL CONDUIT AND WIRING
	MONITOR CONDUIT AND WIRING
	NURSE CALL MASTER STATION
	NURSE CALL BEDSIDE STATION - SINGLE PATIENT
	NURSE CALL BEDSIDE STATION - DOUBLE PATIENT
	EMERGENCY PUSHBUTTON STATION ('P' DENOTES PULL CORD)
	DUTY STATION
	STAFF STATION
	DOME LIGHT - CEILING MOUNTED ('B' DENOTES WITH BUZZER)
	DOME LIGHT - WALL MOUNTED ('B' DENOTES WITH BUZZER)
	ZONE DOMELIGHT
	CODE BLUE PUSHBUTTON


PLUMBING

	DOMESTIC COLD WATER
	DOMESTIC HOT WATER
	RECIRCULATING DOMESTIC HOT WATER
	DOMESTIC TEMPERED WATER
	SOFT DOMESTIC COLD WATER
	SOFT DOMESTIC HOT WATER
	SOFT RECIRCULATING HOT WATER
	SOIL OR WASTE ABOVE GRADE OR FLOOR
	SOIL OR WASTE BELOW GRADE OR FLOOR
	STORM ABOVE GRADE OR FLOOR
	STORM BELOW GRADE OR FLOOR
	STORM OVERFLOW ABOVE GRADE OR FLOOR
	STORM OVERFLOW BELOW GRADE OR FLOOR
	PLUMBING VENT
	GAS (NATURAL)
	LIQUIFIED PETROLEUM
	PUMP DISCHARGE
	HOSE BIBB
	WALL HYDRANT
	WALL CLEAN OUT
	CLEAN OUT
	FLOOR CLEAN OUT
	FLOOR DRAIN, AREA DRAIN, FLOOR SINK
	ROOF DRAIN, OVERFLOW ROOF DRAIN
	SHOWER HEAD.
	REDUCED PRESSURE BACKFLOW PREVENTER
	PLUMBING VENT RISER CALL-OUT NUMBER

GENERAL

	MECHANICAL NOTE REFERENCE
	ELECTRICAL NOTE REFERENCE
	DEMOLITION NOTE REFERENCE
	REVISION NOTE REFERENCE
	CONNECT TO EXISTING WORK
	DETAIL REFERENCE - NO./SHEET NO.
	SECTION CUT - SECTION/SHEET NO.

DUCTWORK



MECHANICAL AND ELECTRICAL SYMBOLS AND ABBREVIATIONS

"SOME SYMBOLS AND ABBREVIATIONS ON THIS LEGEND MAY NOT BE USED. REFER TO FLOOR PLANS FOR ALL SYMBOLS AND ABBREVIATIONS."

AMPS, AIR (COMPRESSED)	DX	DIRECT EXPANSION	HTG	HEATING
AIR CONDITIONING	EA	EXHAUST AIR	HTR	HEATER
AREA DRAIN, ACCESS DOOR	EAT	ENTERING AIR TEMPERATURE	HVU	HEATING AND VENTILATING UNIT
ABOVE FINISH CEILING	EC	ELECTRICAL CONTRACTOR, EMPTY CONDUIT	HW	DOMESTIC HOT WATER
ABOVE FINISH GRADE	EF	EXHAUST FAN	HWR	HOT WATER RETURN
AIR HANDLING UNIT	EM	INDICATES EMERGENCY CIRCUIT	HWS	HOT WATER SUPPLY
ABOVE FINISHED FLOOR	EPO	EMERGENCY POWER OFF	IE	INVERT ELEVATION
BACKDRAFT DAMPER, BLOWDOWN	ER	EXHAUST REGISTER	IG	ISOLATED GROUND
BACKFLOW PREVENTER	ETR	EXISTING TO REMAIN	KCMIL	1000 CIRCULAR MILS
BREAKER	EWB	ENTERING WET BULB	KV	KILOVOLT
BOTTOM OF DUCT	EW	ELECTRIC WATER COOLER	KVA	KILOVOLT AMPS
BOTTOM OF PIPE	EW	ELECTRIC WATER HEATER, ELEC. WALL HTR.	KW	KILOWATT
BOTTOM OF STRUCTURE	EXH	EXHAUST	KWH	KILOWATT HOUR
BRITISH THERMAL UNIT	F/S	COMBINATION FIRE AND SMOKE DAMPER	LAT	LEAVING AIR TEMPERATURE
CONDUIT	FACP	FIRE ALARM CONTROL PANEL	LDB	LEAVING DRY BULB
CABLE TELEVISION SYSTEM	FAACP	FIRE ALARM ANNUNCIATOR CONTROL PANEL	LP	LIQUIFIED PETROLEUM
CIRCUIT BREAKER	FCO	FLOOR CLEANOUT	LRA	LOCKED ROTOR AMPS
CLOSED CIRCUIT TELEVISION	FCU	FAN COIL UNIT	LV	LOW VOLTAGE
CUBIC FEET PER MINUTE	FD	FIRE DAMPER, FLOOR DRAIN	LWB	LEAVING WET BULB
CHILLED/HOT WATER RETURN	FLA	FULL LOAD AMPS	LWT	LEAVING WATER TEMPERATURE
CHILLED/HOT WATER SUPPLY	FLR	FLOOR	MA	MEDICAL AIR
CIRCUIT	FOR	FUEL OIL RETURN	MAU	MAKE UP AIR UNIT
CLEANOUT, CARBON MONOXIDE	FOS	FUEL OIL SUPPLY	MBH	1000 BTU PER HOUR
CARBON DIOXIDE	FP	FIRE PROTECTION	MC	MECHANICAL CONTROLS
COOLING TOWER RETURN	FPB	FAN POWERED TERMINAL UNIT	MCA	MINIMUM CIRCUIT AMPERES
COOLING TOWER SUPPLY	FPVAV	FAN POWERED TERMINAL UNIT	MCC	MOTOR CONTROL
COPPER, CONDENSING UNIT	FS	FLOOR SINK	MD	MOTORIZED DAMPER
CABINET UNIT HEATER	GS	GAS (NATURAL), GROUND	MDP	MAIN DISTRIBUTION PANEL
DOMESTIC COLD WATER	G	GRADE CLEANOUT	MFR	MANUFACTURER
CHILLED WATER RETURN	GFI/GFCI	GROUND FAULT CIRCUIT INTERRUPTER	MH	MANHOLE
CHILLED WATER SUPPLY	GND	GROUND	MLO	MAIN LUGS ONLY
DIRECT DIGITAL CONTROL	GP	GALLONS PER MINUTE	MTD	MOUNTED
DECK DRAIN	HB	HOSE BIBB	MU	MAKE UP
DOWN	HOA	HAND OFF AUTOMATIC		

PROJECT NAME: Smith Orchard Flying Biscuit Landlord Scope of Work
LAST CORRECTION NAME: JCampbell
LAST CORRECTION DATE: Thursday, April 23, 2020 1:32:06 PM
PLOTTED BY: Charles Booy
DATE: Friday, April 24, 2020 1:32:03 PM

PART 1 - GENERAL REQUIREMENTS - ELECTRICAL

1.1 SUMMARY OF WORK

- A. THE CONTRACT DOCUMENTS REQUIRE THE FURNISHING AND INSTALLING OF COMPLETE FUNCTIONING ELECTRICAL SYSTEMS, AND EACH ELEMENT THEREOF, AS SPECIFIED OR INDICATED IN THE CONTRACT DOCUMENTS OR REASONABLY INFERRED, TO COMPLETELY CONSTRUCT AND LEAVE READY FOR OPERATION THE SYSTEMS AS SHOWN ON THE DRAWINGS AND HEREIN DESCRIBED, INCLUDING EVERY ARTICLE, DEVICE OR ACCESSORY, WHETHER OR NOT SPECIFICALLY CALLED FOR BY ITEM. ELEMENTS OF THE WORK INCLUDE MATERIALS, LABOR, SUPERVISION, SUPPLIES, EQUIPMENT, TRANSPORTATION, AND UTILITIES.
- B. SPECIFICATIONS AND DRAWINGS ARE COMPLEMENTARY AND WHAT IS CALLED FOR IN ONE SHALL BE AS BINDING AS IF CALLED FOR BY BOTH.
- C. ALL WORK PERFORMED UNDER THIS SECTION SHALL BE DONE IN A NEAT AND WORKMANLIKE MANNER BY EXPERIENCED MECHANICS OF THE PROPER TRADE.

1.2 COORDINATION, MEASUREMENTS AND LAYOUTS

- A. THE CONTRACTOR SHALL INSPECT THE SITE WHERE THIS WORK IS TO BE PERFORMED AND FULLY FAMILIARIZE HIMSELF WITH ALL CONDITIONS RELATED TO THIS PROJECT.
- B. THE CONTRACTOR SHALL EMPLOY A COMPETENT FOREMAN ON THE JOB TO SEE THAT WORK IS DONE IN ACCORDANCE WITH THE BEST PRACTICES AND IN A SATISFACTORY AND WORKMANLIKE MANNER. THE FOREMAN SHALL KEEP INFORMED AS TO THE WORK OF OTHER TRADES ENGAGED IN THE CONSTRUCTION OF THE PROJECT, AND SHALL EXECUTE HIS WORK IN SUCH A MANNER AS NOT TO INTERFERE WITH OR DELAY THE WORK OF OTHER TRADES.
- C. DRAWINGS SHOW THE GENERAL ARRANGEMENT OF ALL SYSTEMS AND COMPONENTS COVERED UNDER THIS SECTION. WHERE LOCAL CONDITIONS NECESSITATE A REARRANGEMENT, THE CONTRACTOR SHALL PREPARE, AND SUBMIT FOR APPROVAL, DRAWINGS OF THE PROPOSED REARRANGEMENT. BECAUSE OF THE SMALL SCALE OF THE DRAWINGS, IT IS NOT POSSIBLE TO INDICATE ALL OFFSETS, FITTINGS, AND ACCESSORIES THAT MAY BE REQUIRED. THE CONTRACTOR SHALL CAREFULLY INVESTIGATE THE STRUCTURAL AND FINISH CONDITIONS AFFECTING ALL OF HIS WORK AND SHALL ARRANGE SUCH WORK ACCORDINGLY, FURNISHING SUCH OFFSETS, FITTINGS AND ACCESSORIES AS MAY BE REQUIRED TO MEET SUCH CONDITIONS AT NO ADDITIONAL COST TO THE OWNER. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS. DRAWINGS SHALL NOT BE SCALED TO DETERMINE DIMENSION.

1.3 PERMITS AND FEES

- A. THE CONTRACTOR SHALL OBTAIN AND PAY FOR ALL REQUIRED PERMITS AND LICENSES AND SHALL MAKE ALL DEPOSITS AND PAY ALL FEES REQUIRED FOR THE PERFORMANCE OF WORK UNDER THIS SECTION, OTHER THAN THOSE DEPOSITS OR FEES WHICH ARE FULLY REFUNDABLE TO THE OWNER.

1.4 SUBMITTALS, MATERIALS AND EQUIPMENT

- A. ALL ITEMS OF MATERIALS AND EQUIPMENT SHALL BE NEW UNLESS OTHERWISE SPECIFIED HEREIN, FREE FROM DEFECTS AND OF THE BEST QUALITY NORMALLY USED FOR THE PURPOSE IN GOOD COMMERCIAL PRACTICE.
- B. AS SOON AS POSSIBLE AFTER THE AWARD OF THE CONTRACT, THE CONTRACTOR SHALL SUBMIT FOR REVIEW SIX COPIES OF SHOP DRAWINGS FOR ALL EQUIPMENT TO BE FURNISHED FOR THIS PROJECT. SUBMITTALS SHALL INCLUDE MANUFACTURER'S NAME, MODEL NUMBER, DESCRIPTIVE ENGINEERING DATA AND ALL NECESSARY INFORMATION AS TO FINISH, MATERIAL GAUGES AND ACCESSORIES. AFTER SUCH SHOP DRAWINGS ARE PROCESSED, THREE COPIES WILL BE RETURNED TO THE CONTRACTOR. THE CONTRACTOR SHALL, UPON RECEIPT OF REVIEWED SHOP DRAWINGS PROCEED WITH THE PROCUREMENT AND INSTALLATION OF SUCH EQUIPMENT.

1.5 CODES, LAWS, AND STANDARDS

- A. ALL WORK SHALL BE INSTALLED IN COMPLIANCE WITH THE NATIONAL ELECTRICAL CODE, THE NATIONAL BOARD OF FIRE UNDERWRITERS, THE NATIONAL ELECTRICAL SAFETY CODE, AND ALL GOVERNING CODES, APPLICABLE LOCAL LAWS, REGULATIONS, ORDINANCES OR STATUTES OF REGULATORY BODIES HAVING JURISDICTION. THE WORK SHALL BE EXECUTED IN ACCORDANCE WITH SAID LAWS, REGULATIONS, ORDINANCES, STATUTES OR CODES, WITHOUT INCREASED COST TO THE OWNER. ANY POINT IN QUESTION SHALL BE REFERRED TO THE ENGINEER FOR APPROVAL. WORK INDICATED ON THE DOCUMENTS THAT IS IN EXCESS OF CODE REQUIREMENTS SHALL NOT BE REDUCED IN QUALITY AND/OR QUANTITY.
- B. COMPLY WITH RULES AND REGULATIONS OF PUBLIC UTILITIES AND MUNICIPAL DEPARTMENTS AFFECTED BY CONNECTIONS OF SERVICES.

1.6 RECORD DOCUMENTS

- A. THIS CONTRACTOR SHALL PREPARE A COMPLETE "AS-BUILT" SET OF DRAWINGS INCORPORATING ALL CHANGES MADE DURING CONSTRUCTION. LOCATION OF UNDERGROUND CONDUIT SHALL BE LOCATED BY DIMENSION FROM COLUMN LINES.
- B. THIS CONTRACTOR SHALL PREPARE AND SUBMIT TO THE OWNER'S REPRESENTATIVE FIVE BOUND SETS OF OPERATING AND MAINTENANCE MANUALS INCLUDING FINAL COPIES OF EQUIPMENT SHOP DRAWINGS, MANUFACTURER'S LITERATURE FOR ALL EQUIPMENT INSTALLED ON THE PROJECT SHOWING ALL DETAILS OF EQUIPMENT, REPLACEMENT PART DATA AND MAINTENANCE AND OPERATING INSTRUCTIONS. MANUALS SHALL INCLUDE COPIES OF ALL EQUIPMENT WARRANTIES.

1.7 GUARANTEES AND WARRANTIES

- A. THE CONTRACTOR SHALL GUARANTEE COMPLETE SYSTEM OPERATION AND THAT THE MATERIAL AND EQUIPMENT FURNISHED AND INSTALLED WILL BE FREE FROM DEFECTS IN WORKMANSHIP AND MATERIALS AND WILL GIVE SATISFACTORY SERVICE UNDER THE SPECIFIED OPERATING CONDITIONS. THE CONTRACTOR AGREES TO REPLACE, WITHOUT EXPENSE TO THE OWNER, ANY PART OF THE APPARATUS WHICH PROVES OR BECOMES DEFECTIVE WITHIN ONE YEAR AFTER THE SYSTEM IS ACCEPTED. NO EQUIPMENT WARRANTY OR GUARANTEE SHALL START UNTIL THE TIME OF BUILDING ACCEPTANCE.
- B. ALL WARRANTIES ISSUED BY EQUIPMENT MANUFACTURERS SHALL BE FILLED OUT IN THE OWNER'S NAME AND GIVEN TO THE OWNER PRIOR TO FINAL ACCEPTANCE OF WORK PERFORMED UNDER THIS SECTION.

1.8 FINAL INSPECTION

- A. AFTER COMPLETION OF THE ENTIRE PROJECT THE CONTRACTOR SHALL REQUEST FINAL INSPECTION OF THIS PROJECT IN WRITTEN FORM ADDRESSED TO THE ARCHITECT ALONG WITH A STATEMENT TO THE EFFECT THAT ALL INSTALLATIONS HAVE BEEN COMPLETED, CHECKED, ADJUSTED AND BALANCED IN ACCORDANCE WITH REQUIREMENTS OF THIS PROJECT. UPON RECEIPT OF WRITTEN NOTIFICATION OF COMPLETION AND REQUEST FOR FINAL INSPECTION THE ENGINEER WILL PERFORM A FINAL INSPECTION OF THIS WORK AND, IF ALL INSTALLATIONS ARE AS REPRESENTED BY THE CONTRACTOR, THE ENGINEER WILL SUBMIT WRITTEN RECOMMENDATION OF ACCEPTANCE.

1.9 CLEANING

- A. DIRT AND REFUSE RESULTING FROM THE PERFORMANCE OF THE WORK SHALL BE REMOVED TO KEEP THE PREMISES REASONABLY CLEAN AT ALL TIMES.
- B. AFTER COMPLETION OF THE WORK DESCRIBED IN THIS SPECIFICATION AND SHOWN ON THE DRAWINGS, THE CONTRACTOR SHALL THOROUGHLY CLEAN ALL EXPOSED SURFACES AND EQUIPMENT, REMOVE ALL DIRT, DEBRIS, CRATING, CARTONS, ETC., AND LEAVE ALL INSTALLATIONS FINISHED AND READY FOR OPERATION.

1.10 OPENINGS AND SLEEVES

- A. ALL PIPING THROUGH EXTERIOR OR FOUNDATION WALLS SHALL PASS THROUGH SCHEDULE 40 GALVANIZED STEEL SLEEVES WHICH SHALL BE LARGE ENOUGH TO ALLOW FOR PIPE SEAL MATERIAL. SLEEVES IN NEW CONSTRUCTION SHALL HAVE A MINIMUM 2 INCH WATERSTOP IN THE CENTER OF THE SLEEVE. NO SLEEVES ARE PERMITTED THROUGH CONCRETE STRUCTURAL MEMBERS.
1. SPACE BETWEEN PIPE AND SLEEVE IN EXTERIOR UNDERGROUND WALLS SHALL BE SEALED WITH LINK-SEAL, FLEXICRAFT OR METRAFLEX LINK STYLE PIPE SEALS.
2. IN ABOVE GRADE EXTERIOR WALLS PACK THE SPACE BETWEEN PIPE AND SLEEVE WITH MINERAL WOOL AND THEN COMPLETE SEAL WITH APPROVED CAULKING COMPOUND FLUSH WITH FINISHED SURFACE. PROVIDE PIPE COLLAR ON INTERIOR SIDE OF WALL.
- B. ALL PIPING THROUGH FLOORS SHALL BE PROVIDED WITH SCHEDULE 40 GALVANIZED STEEL PIPE SLEEVES, EXTENDING 1 INCH ABOVE THE FLOOR.
- C. IN FIRE RATED WALLS: CAULKING SHALL BE A PURE CERAMIC FIBER MADE OF ALUMINA-SILICA, "CERAFIBER-FS" BY JOHNS-MANVILLE. SEALANT SHALL BE GUN GRADE. AN ACRYLIC 2-PART GUN APPLIED, FIRE RETARDANT ELASTIC SEALANT, "DYMERIC" BY TREMCO OR EQUAL BY PERMATITE NO. 1113FR.
1. LIMIT THE SIZE OF THE SPACE BETWEEN THE WALL OR FLOOR AND THE OUTSIDE OF THE PIPE OR DUCT TO 1 INCH MAXIMUM. THIS SPACE IS SUFFICIENT TO ALLOW SOME MOVEMENT OF THE PIPES OR DUCT WITHOUT CRACKING THE CAULKING OR SEALANT.
2. FOR OPENINGS IN WALLS, THE CAULKING SHALL BE APPLIED TO A MINIMUM OF 3 INCH TOTAL DEPTH. SEALANT SHALL THEN BE APPLIED ON BOTH SIDES OF THE WALL OPENING A MINIMUM OF 1/2 INCH IN DEPTH, FINISHED FLUSH WITH THE WALL. D.
- D. FOR OPENINGS IN FLOORS, THE CAULKING SHALL BE APPLIED FROM THE UPPER SIDE TO A MINIMUM OF 3 INCH TOTAL DEPTH RECESSED 1/2 INCH BELOW THE FINISHED FLOOR. THIS 1/2 INCH RECESS SHALL THEN BE FILLED WITH SEALANT TO FLUSH WITH FINISHED FLOOR.

1.11 CUTTING AND PATCHING

- A. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY CUTTING OF WALLS, FLOORS, CEILINGS AND ROOFS REQUIRED FOR PERFORMANCE OF HIS WORK.
- B. NO STRUCTURAL MEMBER SHALL BE CUT WITHOUT PERMISSION FROM THE ARCHITECT.
- C. PATCH ALL OPENINGS TO MATCH ADJACENT CONSTRUCTION IN BOTH MATERIAL AND FINISH.
- D. ALL CUTTING OF EXISTING CONCRETE FLOORS/SLABS ON GRADE IN THE INTERIOR OF THE BUILDING SHALL BE PERFORMED BY "SAW CUTTING" AND SHALL BE PERFORMED BY THIS CONTRACTOR.

1.12 TEMPORARY HEAT

- A. THE CONTRACTOR SHALL COOPERATE WITH THE GENERAL CONTRACTOR TO PROVIDE TEMPORARY HEAT AS SOON AS POSSIBLE FOR USE DURING CONSTRUCTION IF TEMPORARY HEAT IS REQUIRED. AIR HANDLING EQUIPMENT SHALL NOT BE OPERATED AT ANY TIME WITHOUT FILTERS IN PLACE AND ALL EQUIPMENT SHALL BE PROTECTED FROM DAMAGE. OPERATING THE EQUIPMENT FOR TEMPORARY HEAT SHALL NOT START THE WARRANTY PERIOD OF THE EQUIPMENT USED.

1.13 INTERRUPTION OF SERVICES

- A. THE CONTRACTOR SHALL SCHEDULE ANY SERVICE INTERRUPTIONS TO THE EXISTING BUILDING WITH THE OWNER'S REPRESENTATIVE. SUCH INTERRUPTIONS SHALL BE PLANNED SO AS TO BE AT TIMES TO CAUSE THE LEAST INCONVENIENCE AND INTERRUPTION TO THE FACILITY'S SCHEDULE.

1.14 EXISTING CONDITIONS

- A. ALL EXISTING CONDITIONS SHOWN ON THE DRAWINGS AND DESCRIBED IN THE SPECIFICATIONS FOR THIS PROJECT HAVE BEEN DETERMINED FROM AVAILABLE DRAWINGS AND FIELD INVESTIGATIONS. CONTRACTORS MAKING PROPOSALS FOR THIS WORK SHALL INVESTIGATE ALL EXISTING CONDITIONS AND BASE THEIR PROPOSALS ON THEIR OBSERVATIONS TO PROVIDE COMPLETE AND FUNCTIONING INSTALLATIONS IN ACCORDANCE WITH THE INTENT OF THE DRAWINGS AND SPECIFICATIONS FOR THIS PROJECT AND ALL APPLICABLE GOVERNING CODES, RULES, REGULATIONS AND ORDINANCES. FAILURE TO DETERMINE EXISTING CONDITIONS WHICH CAUSE ADDITIONAL WORK WILL NOT CONSTITUTE GROUNDS FOR ADDITIONAL COMPENSATION.

PART 2 - ELECTRICAL

2.1 GENERAL REQUIREMENTS

- A. SEE PART 1 FOR GENERAL REQUIREMENTS.

2.2 IDENTIFICATION OF SWITCHES AND APPARATUS

- A. ALL CABINETS, SAFETY SWITCHES, AND OTHER APPARATUS USED FOR OPERATION AND CONTROL OF CIRCUITS, APPLIANCES, AND EQUIPMENT UNDER THIS CONTRACT SHALL BE PROPERLY IDENTIFIED BY MEANS OF ENGRAVED PLASTIC PLATES EITHER BLACK WITH WHITE LETTERS OR WHITE WITH BLACK LETTERS.

2.3 GROUNDING

- A. ALL CONDUCTORS, MOTOR FRAMES, RACEWAYS, CABINETS, ETC., THAT REQUIRE GROUNDING SHALL BE GROUNDED IN ACCORDANCE WITH THE REQUIREMENTS OF ARTICLE 250 OF THE NATIONAL ELECTRICAL CODE, THOSE OF THE SERVING UTILITY AND LOCAL AUTHORITIES HAVING JURISDICTION.

2.4 SAFETY SWITCHES

- A. SAFETY SWITCHES, AS MANUFACTURED BY GENERAL ELECTRIC, CROUSE-HINDS, CUTLER-HAMMER, SQUARE D, SIEMENS, OR APPROVED EQUAL, SHALL BE FURNISHED AND INSTALLED (WHERE NOT FURNISHED BY OTHERS) WHEREVER SHOWN ON THE DRAWINGS SPECIFIED, OR REQUIRED BY THE NATIONAL ELECTRICAL CODE.
- B. SAFETY SWITCHES SHALL BE HEAVY DUTY TYPE, UNDERWRITERS' LABORATORIES SHORT CIRCUIT LABELED FOR AT LEAST 100,000 AMPERES WITH CLASS R REJECTION FUSEHOLDERS SO AS TO COMPLY WITH NEC 100-9. SWITCHES INSIDE OF BUILDING SHALL BE FURNISHED IN NEMA 1 GENERAL PURPOSE ENCLOSURES. SWITCHES OUTSIDE OF BUILDING SHALL BE FURNISHED IN NEMA 3R ENCLOSURES UNLESS OTHERWISE SPECIFIED.
- C. EACH MOTOR SHALL BE PROVIDED WITH A DISCONNECTING MEANS IN ACCORDANCE WITH REQUIREMENTS OF THE NATIONAL ELECTRICAL CODE.

2.5 CONDUIT

- A. ALL ELECTRICAL WIRING, INCLUDING LOW VOLTAGE WIRING, SHALL BE INSTALLED IN CONDUIT AS HEREIN SPECIFIED. NO CONDUIT OR TUBING OF LESS THAN 3/4 INCH NOMINAL SIZE SHALL BE USED BELOW GRADE; NO LESS THAN 1/2 INCH NOMINAL SIZE SHALL BE USED ABOVE GRADE.
- B. UNDERGROUND CONDUIT SHALL BE SCHEDULE 40 EPC-40-PVC. ALL CONDUITS SHALL BE INSTALLED WITH MINIMUM 24 INCH COVER.
- C. CONDUIT INSTALLED IN CONCRETE SLABS OR ABOVE GROUND SHALL BE GALVANIZED RIGID STEEL OR EPC-40-PVC.
- D. WHEN PVC CONDUITS PENETRATE CONCRETE FLOOR CONSTRUCTION, CONTRACTOR SHALL USE RIGID STEEL OR IMC ELBOWS AND EXTENSION. PVC CONDUIT/FITTINGS SHALL NOT BE PERMITTED TO BE EXPOSED ABOVE THE FLOOR.
- E. THINWALL TUBING SHALL BE E.M.T.
- F. ALL FITTINGS SHALL BE OF THE COMPRESSION TYPE AND WATERTIGHT FOR UNDERGROUND AND IN SLAB LOCATIONS. COMPRESSION OR SCREWED FITTINGS FOR INDOOR.
- G. CONDUIT FOR INTERIOR WIRING, IN GENERAL, SHALL BE THINWALL TUBING UNLESS OTHERWISE NOTED.

- H. RACEWAYS SHALL BE CONTINUOUS FROM OUTLET TO OUTLET AND FITTING TO FITTING. A RUN OF CONDUIT BETWEEN OUTLETS OR FITTINGS SHALL NOT CONTAIN MORE THAN THE EQUIVALENT OF FOUR QUARTER-BENDS INCLUDING THOSE BENDS LOCATED IMMEDIATELY AT THE OUTLET OR FITTING. THE RADIUS OF BENDS SHALL NEVER BE SHORTER THAN THAT OF THE CORRESPONDING TRADE ELBOW. THE SYSTEM SHALL BE COMPLETE WITH OUTLETS, DISTRIBUTION BOXES, ETC., SMOOTH INSIDE AND MECHANICALLY SECURE IN PLACE. APPROVED STRAPS, HANGERS, OR SUPPORTS SHALL BE USED TO SECURE CONDUITS IN PLACE. CONDUITS SHALL, IN GENERAL, BE SUPPORTED AT INTERVALS NOT EXCEEDING 10'-0" AND WITHIN 3'-0" OF EACH OUTLET BOX, JUNCTION BOX, CABINET OR FITTING.

- I. CONDUITS SHALL BE PROTECTED DURING CONSTRUCTION; PLUG AND KEEP CLEAN AND DRY. CONDUIT ENDS SHALL BE BUTTED IN CENTERS OF COUPLINGS. NO CRACKS OR FLATTENED SECTIONS WILL BE PERMITTED AT BENDS OR ELSEWHERE. ALL ENDS OF CONDUIT SHALL BE REAMED TO REMOVE ROUGH EDGES. RUNNING THREADS WILL NOT BE PERMITTED.


- J. CONDUITS SHALL BE CONCEALED WITHIN THE WALLS, CEILINGS, AND FLOORS WHERE POSSIBLE AND UNLESS OTHERWISE NOTED. EXPOSED CONDUIT SHALL BE RUN PARALLEL TO OR AT RIGHT ANGLES WITH THE BUILDING LINES.

2.6 WIRE AND CABLE

- A. WIRE AND CABLE SHALL BE COPPER.
- B. ALL CONDUCTORS SHALL BE COPPER.
- C. NO. 10 AWG AND SMALLER CONDUCTORS SHALL BE SOLID WITH TYPE THHN INSULATION AND NO. 8 AWG AND LARGER CONDUCTORS SHALL BE STRANDED WITH TYPE THHN INSULATION EXCEPT THAT CONDUCTORS WITHIN 3 INCHES OF LIGHT FIXTURE BALLASTS SHALL HAVE RHH, THHN, OR EQUAL INSULATION RATED FOR 90 DEGREES C. APPLICATION.

2.7 IDENTIFICATION OF EQUIPMENT

- A. ALL SERVICE ENTRANCE EQUIPMENT, DISCONNECT SWITCHES, PANELBOARDS, RELAYS, MOTOR STARTERS, CONTACTORS, TELEPHONE TERMINAL CABINETS, TV EQUIPMENT AND RISER JUNCTION BOXES, AND OTHER ELECTRICAL EQUIPMENT UNDER THIS CONTRACT, SHALL BE PROVIDED WITH PROPER IDENTIFICATION. IDENTIFICATION SHALL BE BY THE USE OF ENGRAVED COLOR CODED PLASTIC NAMEPLATES WITH WHITE LETTERING SCREWED TO THE COVER OF THE EQUIPMENT. USE OF EMBOSSED PLASTIC "TAP" LABELS AS PREPARED BY "TYPEWRITER" TYPE EQUIPMENT SHALL NOT BE USED. COLOR CODING SHALL BE AS FOLLOWS:
1. EQUIPMENT CONNECTED TO A NORMAL POWER SOURCE SHALL BE BLACK WITH WHITE LETTERS.



RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
05/06/2020

Flying Biscuit
Tenant Improvements

Client Name
Summit Orchard
460 NW Chipman Rd.
Lee's Summit, MO 64086

Revisions:
Project #: #####

Construction
Documents
04-24-20

SPECIFICATIONS -
MECHANICAL AND
ELECTRICAL

ME202

PROJECT NAME: Smith Architects Flying Biscuit Landlord Scope of Work
LAST CORRECTION: 11/23/2020 11:34:27 AM
DRAWN BY: Charles Boody
CHECKED BY: Charles Boody
DATE: 11/23/2020 11:34:27 AM
TIME: 11:34:27 AM
PROJECT NUMBER: 1923001

ROOFTOP UNIT SCHEDULE - GAS HEAT				
DESIGNATION	RTU-1	RTU-2	RTU-3	RTU-4
MANUFACTURER	YORK	YORK	YORK	YORK
MODEL NO.	ZJ078	ZJ078	ZJ078	ZJ078
NOMINAL TONNAGE	6.5	6.5	6.5	6.5
CAPACITY	CFM	2600	2600	2600
	TOTAL COOLING CAPACITY (MBH)	80.4	80.4	80.4
	SENSIBLE COOLING CAPACITY (MBH)	58.8	58.8	58.8
	ENT. AIR (DBWB)	80/67	80/67	80/67
	L.V.G. AIR (DBWB)	59.1/57.2	59.1/57.2	59.1/57.2
	MINIMUM E.E.R.	11.8	11.8	11.8
	HEATING INPUT (MBH)	120	120	120
	HEATING OUTPUT (MBH)	96	96	96
	STAGES OF HEATING	2	2	2
	EFFICIENCY	80%	80%	80%
UNIT DATA	OUTSIDE AIR CFM	SET BY TENANT	SET BY TENANT	SET BY TENANT
	TOTAL S.P. (IN. W.C.)	1.0	1.0	1.0
	FAN BRAKE HP	1.97	1.97	1.97
	FAN MOTOR HP	2.0	2.0	2.0
	NO. OF COMPRESSORS	2	2	2
	STAGES OF COOLING	2	2	2
	SMOKE DETECTORS	YES, NOTE 3	YES, NOTE 3	YES, NOTE 3
	RECEPTACLE	NOTE 4	NOTE 4	NOTE 4
	RELIEF	BAROMETRIC	BAROMETRIC	BAROMETRIC
	ECONOMIZER	DIFF. ENTHALPY	DIFF. ENTHALPY	DIFF. ENTHALPY
FILTER	TYPE	2"	2"	2"
	EFFICIENCY	MERV 8	MERV 8	MERV 8
	VOLTAGE/PHASE	208/3	208/3	208/3
	MINIMUM CIRCUIT AMPACITY	36.2	36.2	36.2
	MAXIMUM OVERCURRENT PROTECTION	45	45	45
	PANEL & CIRCUIT	EL-2,4,6	EL-8,10,12	EL-14,16,18
	WIRE & CONDUIT	(3)#8, #10G, 3/4"C.	(3)#8, #10G, 3/4"C.	(3)#8, #10G, 3/4"C.
	OVERCURRENT DEVICE	45A/3P CB	45A/3P CB	45A/3P CB
	DISCONNECT	60A-3P NF NEMA 3R	60A-3P NF NEMA 3R	60A-3P NF NEMA 3R
	CONTROL SEQUENCE	NOTE 5	NOTE 5	NOTE 5
REFERENCE DRAWING/DETAIL				
REMARKS				


- NOTES:
- FURNISH WITH ALUMINIZED FURNACE, INTELLISPEED FAN, STANDARD DRAIN PAN, ROOF CURB, AND HAIL GUARD KIT. PROVIDE MODULATING OUTDOOR AIR DAMPER CAPABLE OF DEMAND CONTROL VENTILATION WITH CO2 SENSOR LOCATED IN UNIT OR DUCTWORK.
 - ROUTE DUCTWORK DOWN FROM UNIT TO THE BOTTOM OF STRUCTURE. REFER TO DETAIL AND INSULATION/LINER REQUIREMENTS.
 - FURNISH WITH FACTORY INSTALLED SMOKE DETECTOR IN RETURN AIR DUCT SECTION. FIRE ALARM CONTRACTOR TO CONNECT TO FIRE ALARM CONTROL PANEL AS REQUIRED.
 - FACTORY PROVIDED GFI / WP RECEPTACLE, UNPOWERED. CONTRACTOR TO FIELD WIRE PER PLANS.
 - PROVIDE FACTORY CONTROLLER FOR STAND-ALONE OPERATION. PROVIDE 7-DAY PROGRAMMABLE THERMOSTAT IN LOCKBOX TEMPORARILY MOUNT IN SPACE, TENANT TO RELOCATE TO ITS FINAL LOCATION.

DUCTWORK SCHEDULE					
SERVICE	DUCT MATERIAL	DUCT SHAPE	SMACNA REQUIREMENTS		
			CLASSIFICATION	SEAL CLASS	LEAKAGE CLASS
SUPPLY AIR DUCTS CONNECTED TO RTU	GALVANIZED STEEL	RECTANGULAR	2" WG POSITIVE	B	12
	GALVANIZED STEEL	ROUND/FLAT OVAL (EXPOSED)	4" WG POSITIVE SPIRAL SEAM/FLAT OVAL	B	3
RETURN AIR AND TRANSFER AIR DUCTWORK	GALVANIZED STEEL	RECTANGULAR	2" WG NEGATIVE	B	12
GENERAL EXHAUST DUCTS TO THE INLET OF THE FAN	GALVANIZED STEEL	RECTANGULAR OR ROUND	2" WG NEGATIVE	B - RECTANGULAR A - ROUND	12 - RECTANGULAR 3 - ROUND

- NOTES:
- SEE DUCTWORK INSULATION SCHEDULE FOR REQUIREMENTS ON DUCT INSULATION


DUCTWORK INSULATION SCHEDULE	
SERVICE	INSULATION
CASINGS, HOUSINGS AND PLENUMS	2", 6 LB. FIBERGLASS BOARD, GCVB
CONCEALED DUCTWORK AS FOLLOWS:	1-1/2", 1.5 LB. RIGID FIBERGLASS BLANKET, VAPOR BARRIER FACED, WITH HEAVY DUTY FOIL-SCRM-KRAFT FACING.
ALL ROUND SUPPLY AIR AND UNLINED BRANCH TAKE-OFFS FOR ROUND DUCTS AND IN-LINE TRANSITIONS.	
EXHAUST AIR BETWEEN ISOLATION DAMPER AND PENETRATION OF BUILDING EXTERIOR	
RELIEF AIR	

- NOTES:
- SEE DUCTWORK SCHEDULE FOR ITEMS THAT ARE TO BE LINED.
 - EXPOSED, LOW PRESSURE, ROUND AND FLAT OVAL SUPPLY AIR DUCTWORK IS NOT INSULATED.




CONDENSATE DRAIN TRAP DETAIL

NOT TO SCALE




GREASE INTERCEPTOR

NOT TO SCALE



ROOFTOP UNIT AND CURB DETAIL

NOT TO SCALE




WALL MOUNTED DEVICES: MOUNTING HEIGHTS

NO SCALE


PANEL		EXISTING EL									
MAIN BUS AMPS: 400 A		AIC:		22,000 A						EQUIPMENT GROUND BUS	
MAIN BREAKER: 400 A		SECTIONS:		2 - 42 SPACE							
VOLTAGE: 208Y/120 V		MOUNTING:		SURFACE							
PHASES/WIRES: 3 PH / 4 W		LOCATION:								SERVICE ENTRANCE	
CIRCUIT DESCRIPTION		POLES	AMPS	CKT	NO	CKT	NO	AMPS	POLES	CIRCUIT DESCRIPTION	
EXISTING LTO - EMERGENCY		1	20	1	2	45	3		RTU-1		
PREPARED SPACE				3	4						
PREPARED SPACE				5	6						
PREPARED SPACE				7	8	45	3		RTU-2		
PREPARED SPACE				9	10						
PREPARED SPACE				11	12						
PREPARED SPACE				13	14	45	3		RTU-3		
PREPARED SPACE				15	16						
PREPARED SPACE				17	18						
PREPARED SPACE				19	20	45	3		RTU-4		
PREPARED SPACE				21	22						
PREPARED SPACE				23	24						
PREPARED SPACE				25	26	20	1		RTU-RECEPTACLES ROOF		
PREPARED SPACE				27	28				1	PREPARED SPACE	
PREPARED SPACE				29	30				1	PREPARED SPACE	
PREPARED SPACE				31	32				1	PREPARED SPACE	
PREPARED SPACE				33	34				1	PREPARED SPACE	
PREPARED SPACE				35	36				1	PREPARED SPACE	
PREPARED SPACE				37	38				1	PREPARED SPACE	
PREPARED SPACE				39	40				1	PREPARED SPACE	
PREPARED SPACE				41	42				1	PREPARED SPACE	
PREPARED SPACE		1		43	44				1	PREPARED SPACE	
PREPARED SPACE		1		45	46				1	PREPARED SPACE	
PREPARED SPACE		1		47	48				1	PREPARED SPACE	
PREPARED SPACE		1		49	50				1	PREPARED SPACE	
PREPARED SPACE		1		51	52				1	PREPARED SPACE	
PREPARED SPACE		1		53	54				1	PREPARED SPACE	
PREPARED SPACE		1		55	56				1	PREPARED SPACE	
PREPARED SPACE		1		57	58				1	PREPARED SPACE	
PREPARED SPACE		1		59	60				1	PREPARED SPACE	
PREPARED SPACE		1		61	62				1	PREPARED SPACE	
PREPARED SPACE		1		63	64				1	PREPARED SPACE	
PREPARED SPACE		1		65	66				1	PREPARED SPACE	
PREPARED SPACE		1		67	68				1	PREPARED SPACE	
PREPARED SPACE		1		69	70				1	PREPARED SPACE	
PREPARED SPACE		1		71	72				1	PREPARED SPACE	
PREPARED SPACE		1		73	74				1	PREPARED SPACE	
PREPARED SPACE		1		75	76				1	PREPARED SPACE	
PREPARED SPACE		1		77	78				1	PREPARED SPACE	
PREPARED SPACE		1		79	80				1	PREPARED SPACE	
PREPARED SPACE		1		81	82				1	PREPARED SPACE	
PREPARED SPACE		1		83	84				1	PREPARED SPACE	


ITALIC - EXISTING

BOLD - NEW



**RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
05/06/2020**

	Revisions:
Project #:	#####




ELECTRICAL GENERAL NOTES:

1. REFER TO M/E SCHEDULES AND DETAILS FOR MECHANICAL EQUIPMENT CIRCUITING INFORMATION.
2. FIRESTOP ALL CONDUIT PENETRATIONS THROUGH FIRE ROUTED WALLS AND FLOORS AFTER INSTALLATION IS COMPLETE.
3. 120V BRANCH CIRCUITING SHALL BE AS FOLLOWS: (UNLESS NOTED OTHERWISE)

0'-100' = 12 AWG.
101'-150' = 10AWG.
151'-250' = 8AWG.

ELECTRICAL PLAN NOTES


- 1 WEATHER PROOF GFI RECEPTACLE FACTORY PROVIDED WITH EQUIPMENT. PROVIDE ELECTRIC CONNECTION AS NECESSARY. MANUFACTURER'S RECOMMENDATIONS. REFER TO MANUFACTURER'S SCHEDULE FOR ADDITIONAL DETAIL.
- 2 FACTORY PROVIDED AND INSTALLED DUCT AND SMOKE DETECTOR FOR SHUTDOWN OF OUTSIDE AIR INTAKE. LOG IN SUPPLY AND RETURN DUCT. MAKE CONNECTIONS TO UNIT AS REQUIRED FOR CORRECT OPERATION AS NOTED IN THE SPECIFICATIONS AND TO THE FIRE ALARM PANEL. UNIT TO ALSO SHUTDOWN UPON DETECTION OF SMOKE. AT ANY OF THE FIRE/SMOKE DAMPERS ASSOCIATED WITH THIS EQUIPMENT, DEMONSTRATION WILL BE REQUIRED TO PROVIDE EVIDENCE OF ALARM OR MECHANICAL CONTRACTOR, INCLUDING FIRE MARSHAL ACCEPTANCE TESTS.
- 2 (1) "CONDUIT SLEEVES, ONE FOR PHONE AND ONE FOR DATA. COORDINATE EXACT LOCATION WITH ARCHITECT/OWNER PRIOR TO ROUGH-IN.



**RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
05/06/2020**

Flying Biscuit Tenant Improvements

Client Name
Summit Urchard
460 NW Chipman Rd.
Lee's Summit, MO 64086

 Revisions:

Construction Documents

04-24-20

**FIRST FLOOR PLAN -
MECHANICAL AND
ELECTRICAL**

ME401