

# CO2 MK9 DETECTOR SET 4 A

## CO2 Safety System SET 4 A with amber Horn/Strobe



### TECHNICAL DATA

<b>Power supply:</b>	12-24V DC
<b>Number of sensors:</b>	1-8
<b>Communication:</b>	RS485 Modbus
<b>Automatic calibration:</b>	Several times a year

For further data see separate data sheets for the specific components.

### ORDERING EXAMPLE

Description	Item code
CO2 Mk9 Detector SET 4 A	2049

### CO2 Mk9 Detector SET 4 A consists of:

CO2 Central Unit Mk9  
Cable red 5m  
CO2 Sensor Mk9  
Cable red 10m  
Cable blue 5m  
Horn/Strobe LED amber with 1m cable  
RJ45 1-1 split  
RJ45 1-2 split  
Transformer 1A  
Plug-UL for transformer  
Plug-CE for transformer  
Plug-AU for transformer  
Plug-UK for transformer  
Plug-lock  
Bag with 6 screws and plug  
Sign CO2 Safety System Mk9  
Sign Horn/strobe Mk9/10  
Installation manual Mk9  
Quick-guide Mk9

### FUNCTION

The Carbon Dioxide (CO<sub>2</sub>) Safety System is designed to measure CO<sub>2</sub> concentration in a confined space environment. It provides an alarm in the event that a CO<sub>2</sub> level considered unhealthy/dangerous in accordance with existing safety codes, in the area being monitored.

The basic CO<sub>2</sub> Safety System is a precision instrument comprising one central unit (with a digital display), one (up to eight) sensor unit, one horn/strobe. A separate electronic transformer supplies power to the system. The sensor unit uses infrared analysis for detecting CO<sub>2</sub>. The System monitors STEL as well as TWA levels of CO<sub>2</sub>. The system also provides visible indication of CO<sub>2</sub> levels and temperature in the area where the remote sensor is located. It is displayed on a screen of the Central Unit in most languages. Explaining what to do in different Alarm situations. The CO<sub>2</sub> Safety System performs a self-calibration at regular intervals insuring calibration under normal circumstances. This eliminates the need of manual service calibration in a normal environment.

When installed properly, the CO<sub>2</sub> Safety System will continuously monitor the CO<sub>2</sub> concentration and temperature wherever a sensor unit is located. A green light emitting diode (LED) on the central unit indicates normal safe conditions. If ambient conditions at the CO<sub>2</sub> Sensor reach a CO<sub>2</sub> concentration level of 1.5% (preset low alarm), the central unit will emit an intermittent audible tone and the « low alarm » red LED will blink. A remote Horn/Strobe will flash. This will also happen if the TWA for 8 hours also surpasses 5000 ppm. The difference can be acknowledged on the display. If ambient conditions at the CO<sub>2</sub> Sensor reach a CO<sub>2</sub> concentration level of 3.0% (preset high alarm), the central unit will emit a constant audible tone and the « high alarm » red LED lights. A remote Horn/Strobe will flash and sound.


### APPROVALS

CE, EN55022 :2006/A1 :2007, EN55024/A2 :2003, EN61000-3-2 : 2006, EN61000-3-3/A2 :2006, AS/NZS CISPR 22 :2006, IEC/EN :IT55022/55024, LNE Règle de certification NF 128 rev 12 Nov 2007 (§2.1.2.4.3.) for the S8 CO<sub>2</sub> Sensor Module. UL Certified. DIN6653-2:2015-06.

In the United States, the Mk9 system is in compliance with International Fire Code (IFC) 2015 Edition Section 5307.5.2.2, CGA G-6.5 2013, NFPA 55 2013 Edition 13.2.2 and NBIC Part 1 Supplement 3 S 3.4.

In compliance with EU Commission Directive 2006/15/EC of 7 Feb 2006 as well as OSHA – PEL (Permissible Exposure Limit) of TWA for CO<sub>2</sub>.

## C E

[illegible]

Cut off the prolongations of the lock-release on the RJ45 connectors to secure unauthorized disconnection of the CO2 Safety System.



Use a small screwdriver to disconnect the RJ45 plugs.

# CO2 Mk9 Detector Base SET

Art no: 2049

## MK9 CO<sub>2</sub> Safety system

The MK9 CO<sub>2</sub> sensor is the latest generation of CO<sub>2</sub> Safety Systems and has replaced the Logico2 MKVII CO<sub>2</sub> Sensor System. A large display, functional design and revolutionary language functionalities are some of the new features of the MK9 CO<sub>2</sub> Safety System. The display alternates between actual CO<sub>2</sub> concentration (0.0%- 6,7%), TWA (ppm) and temperature (°C or °F), (if temperature alarm is activated for cold room applications).

This complete plug and play SET contains a Mk9 CO<sub>2</sub> Sensor with display, a Mk9 Central Unit to display the measured values, a Horn/strobe, cabling and signage. Up to eight sensors can be connected to the Mk9 CO<sub>2</sub> Safety Detector SET, providing a sophisticated and powerful CO<sub>2</sub> Safety System while still being the most economical and easiest system on the market. All Logico2 sensors have automatic calibration as standard. The alarm levels can be changed to any level to comply with all local Safety Codes and legislation.

### The default alarm levels are:

- 5.000 ppm Awareness Alert
- 5000 ppm TWA 8Hr (PEL)
- 1,5% (15.000 ppm) ½ STEL
- 3,0% (30.000 ppm) STEL

### The CO<sub>2</sub> Mk9 Detector SET is available in the following languages:

Chinese Simplified  
 Danish  
 Dutch / Netherlands  
 English  
 Filipino  
 Finnish  
 French  
 German  
 Hebrew  
 Indonesian  
 Italian  
 Japanese  
 Korean  
 Norwegian  
 Polish



## What is in the package:



### CO2 Sensor

Art no: 1134



### Central Unit

Art no: 1148



### Horn/Strobe amber glass

Art no: 0440



### Power Supply

Art no: 0021

Swedish

Thai

**The Asian version also has:**

- Chinese Simplified
- Thai
- Japanese
- Korean

**What is in the package?**

CO<sub>2</sub> Mk9 detector + Central Unit Mk9 + Horn/Strobe LED incl. cable + 10 m power/communication cable + power supply incl. cable + plug lock + 5m signalization cable + 1 J45 1-1 connector + 1 RJ45 1-2 connector + manual + Central Unit sign+ H/S sign and collar seals.

## Specifications

## Manuals & instructions

**Data Sheet** English**Manual** English**Quick Guide** English[Other languages](#)

## Mk9 tutorial (English)