

Page 1 of 2 Report: K37876

## **IN-PLACE DENSITY: K37876**

CLIENT:	CHOYCE, LLC	<b>REPORT NO:</b>	K37876
	PO BOX 847	REPORT DATE:	10/9/2020
	LEE'S SUMMIT, MO 64063	SERVICE DATE:	10/7/2020
PROJECT:	R20-20-096 NAPA VALLEY 4TH PLAT	AUTHORIZATION: CONTRACTOR:	

**SERVICES:** Perform in-place density and moisture content tests to determine the degree of field compaction.

Gauge													
Se	rial No.	Test Mod	e	Density	Current	Density Previo	us Moi	sture Curr	ent l	Moisture F	Previous		
TROXLER 3440 21653 Di		irect Transmi	mission 1740			1748		644		651			
				R	equiremer	nts							
. Density Method			nsity Specification			Moisture Method		Moisture Specification					
ASTM D6938			95% MIN			ASTM D3017		N/A					
				Т	est Procto	rs							
Test Type			Material O		Optir	timum Moisture		Max Density		Reference			
STANDARD PROCTOR			AB3			8%		136 pcf		Client1			
					Results								
Locatio	on	Probe Depth	Lift/Elev	Proctor	Field Moisture %	Optimum Moisture %	Moisture Result	Dry Density	Max Density	Density %	Density Result		
W RD FROM BENZ ·00, 4' LCL	INGER, STA	4	FG	1	5.9	8.0	Pass	132.0	136.0	97.0	Pass		
W RD FROM BENZ 20,4' RCL	ZINGER, STA	4	FG	1	5.4	8.0	Pass	129.8	136.0	95.0	Pass		
W RD FROM BENZ 20, 4' LCL	ZINGER, STA	4	FG	1	5.8	8.0	Pass	131.0	136.0	96.0	Pass		
,	ZINGER, STA	4	FG	1	5.2	8.0	Pass	129.4	136.0	95.0	Pass		
,	ZINGER, STA	4	FG	1	5.8	8.0	Pass	131.8	136.0	97.0	Pass		
,	ZINGER, STA	4	FG	1	5.5	8.0	Pass	130.2	136.0	96.0	Pass		
,	INGER, STA	4	FG	1	5.6	8.0	Pass	130.8	136.0	96.0	Pass		
	Density Me ASTM D6 Test Type STANDARD PRO STANDARD PRO STANDARD PRO UNCL W RD FROM BENZ 20,4' LCL W RD FROM BENZ 20,4' RCL W RD FROM BENZ 25, 6' RCL W RD FROM BENZ 25, 6' RCL W RD FROM BENZ 25, 4' LCL W RD FROM BENZ 230, 4' RCL W RD FROM BENZ	Density Method ASTM D6938 Test Type STANDARD PROCTOR UDENTIFY TO A CONTRIBUTION OF THE TYPE STANDARD PROCTOR UNDERTOR DENZINGER, STA 20, 4' LCL W RD FROM BENZINGER, STA 20, 4' LCL W RD FROM BENZINGER, STA 20, 4' LCL W RD FROM BENZINGER, STA 25, 4' LCL W RD FROM BENZINGER, STA 25, 4' LCL W RD FROM BENZINGER, STA 20, 4' RCL W RD FROM BENZINGER, STA 30, 4' RCL W RD FROM BENZINGER, STA	LER 3440 21653 Direct Transmi   Density Method Density   ASTM D6938 ASTM D6938   Test Type STANDARD PROCTOR   STANDARD PROCTOR Probe Depth   W RD FROM BENZINGER, STA 400, 4' LCL 4   W RD FROM BENZINGER, STA 20, 4' LCL 4   W RD FROM BENZINGER, STA 25, 6' RCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4   W RD FROM BENZINGER, STA 40, 4' LCL 4' LCL   W RD FROM BENZINGER, STA 40, 4' LCL 4' LCL   W RD FROM BENZINGER, STA 40, 4' LCL 4' LCL   W RD FROM BENZINGER, STA 40, 4' LCL 4' LCL	LER 3440   21653   Direct Transmission     Density Method   Density Specifi     ASTM D6938   95% MIN     Test Type   Mate     STANDARD PROCTOR   AB     Location   Probe Depth   Lift/Elev     W RD FROM BENZINGER, STA   4   FG     W RD FROM BENZINGER, STA	LER 3440   21653   Direct Transmission   17     Density Method   Density Specification   Red     ASTM D6938   95% MIN   Test Type   Material     STANDARD PROCTOR   AB3   Material   Test Type   Material     Version of the test of the test of te	Serial No.   Test Mode   Density Current     LER 3440   21653   Direct Transmission   1740     Requirement     Density Method   Density Specification     ASTM D6938   95% MIN     Test Type   Material   Optin     STANDARD PROCTOR   AB3     Location   Probe Depth   Lift/Elev Proctor   Field Moisture %     W RD FROM BENZINGER, STA -00, 4' LCL   4   FG   1   5.9     W RD FROM BENZINGER, STA -20, 4' LCL   4   FG   1   5.4     W RD FROM BENZINGER, STA -20, 4' LCL   4   FG   1   5.4     W RD FROM BENZINGER, STA -20, 4' LCL   4   FG   1   5.8     W RD FROM BENZINGER, STA -20, 4' LCL   4   FG   1   5.8     W RD FROM BENZINGER, STA -25, 6' RCL   4   FG   1   5.8     W RD FROM BENZINGER, STA -25, 6' RCL   4   FG   1   5.8     W RD FROM BENZINGER, STA -25, 6' RCL   4   FG   1   5.5     W RD FROM BENZINGER, STA -25, 6' RCL   4   FG   1   5.5     W RD FROM B	Serial No.     Test Mode     Density Current     Density Previo       LER 3440     21653     Direct Transmission     1740     1748       Requirements       Density Method     Density Specification     Moisture Method       ASTM D6938     95% MIN     ASTM D301       Test Proctors       Test Type     Material     Optimum Moisture       STANDARD PROCTOR     AB3     8%       Location     Probe Depth     Lift/Elev Proctor     Field Moisture %     Optimum Moisture %       W RD FROM BENZINGER, STA 00, 4' LCL     4     FG     1     5.9     8.0       W RD FROM BENZINGER, STA 20,4' RCL     4     FG     1     5.4     8.0       W RD FROM BENZINGER, STA 20, 4' LCL     4     FG     1     5.8     8.0       W RD FROM BENZINGER, STA 25, 6' RCL     4     FG     1     5.8     8.0       W RD FROM BENZINGER, STA 25, 4' LCL     4     FG     1     5.8     8.0       W RD FROM BENZINGER, STA 25, 6' RCL     4     FG     1     5.8     8.0	Serial No.     Test Mode     Density Current     Density Previous     Moi       LER 3440     21653     Direct Transmission     1740     1748     Requirements       Requirements       Density Method     Density Specification     Moisture Method       ASTM D6938     95% MIN     ASTM D3017       Test Type     Material     Optimum Moisture       STANDARD PROCTOR     AB3     8%       Eventual Moisture Method       Uocation     Probe Depth     Lift/Elev Proctor     Field Moisture Moisture       W RD FROM BENZINGER, STA 4     4     FG     1     5.9     8.0     Pass 20.4 RCL       W RD FROM BENZINGER, STA 20.4 LCL     4     FG     1     5.8     8.0     Pass 20.4 RCL       W RD FROM BENZINGER, STA 4     FG     1     5.8     8.0     Pass 20.4 RCL       W RD FROM BENZINGER, STA 4     FG     1     5.8     8.0     Pass 20.4 RCL       W RD FROM BENZINGER, STA 4     FG     1     5.8     8.0     Pass 20.4 RCL       W RD FROM BENZINGER, STA 4 <td< td=""><td>Serial No.     Test Mode     Density Current     Density Previous     Moisture Current       LER 3440     21653     Direct Transmission     1740     1748     644       Requirements     Requirements     Moisture Method     M       Density Method     Density Specification     Moisture Method     M       ASTM D6938     95% MIN     ASTM D3017     Max Den       Test Proctors       Test Type     Material     Optimum Moisture     Max Den       STANDARD PROCTOR     AB3     8%     136 pc       Lift/Elev Proctor     Field Moisture %     Optimum Moisture %     Moisture Moisture Pry Density       W RD FROM BENZINGER, STA 00, 4 LCL     4     FG     1     5.4     8.0     Pass     132.0       W RD FROM BENZINGER, STA 20, 4 LCL     4     FG     1     5.8     8.0     Pass     132.0       W RD FROM BENZINGER, STA 25, 6 (RCL     4     FG     1     5.8     8.0     Pass     132.0       W RD FROM BENZINGER, STA 25, 4 LCL     4     FG     1     5.8     8.0<td>Serial No.     Test Mode     Density Current     Density Previous     Moisture Current     M       LER 3440     21653     Direct Transmission     1740     1748     644       Requirements       Density Method     Density Specification     Moisture Method     Moisture Specification       ASTM D6938     95% MIN     ASTM D3017     N       Test Proctors       Test Type     Material     Optimum Moisture     Max Density       Second PROCTOR     AB3     8%     136 pcf       Lift//Elev Proctor     Field Moisture %     Optimum Moisture %     Moisture Dry Result     Max Density Density Density       W RD FROM BENZINGER, STA 40, 4 FG     1     5.9     8.0     Pass     136.0       W RD FROM BENZINGER, STA 40, 4 FG     1     5.4     8.0     Pass     131.0     136.0       W RD FROM BENZINGER, STA 40, 4 FG     1     5.8     8.0     Pass     131.0     136.0       W RD FROM BENZINGER, STA 40, 4 FG     5.8     8.0     Pass     131.0     136.0       W RD FROM BENZING</td><td>Serial No.     Test Mode     Density Current     Density Previous     Moisture Current     Moisture F       LER 3440     21653     Direct Transmission     1740     1748     644     653       Requirements     Requirements     Moisture Method     Moisture Specification     Moisture Method     Moisture Specification       ASTM D6938     95% MIN     ASTM D3017     N/A       Test Proctors       Test Type     Material     Optimum Moisture     Max Density     Reference       STANDARD PROCTOR     AB3     8%     136 pcf     Cli       W RD FROM BENZINGER, STA     4     FG     1     5.9     8.0     Pass     132.0     136.0     97.0       W RD FROM BENZINGER, STA     4     FG     1     5.4     8.0     Pass     132.0     136.0     97.0       W RD FROM BENZINGER, STA     4     FG     1     5.4     8.0     Pass     132.0     136.0     95.0       VR D FROM BENZINGER, STA     4     FG     1     5.4     8.0     Pass     13</td></td></td<>	Serial No.     Test Mode     Density Current     Density Previous     Moisture Current       LER 3440     21653     Direct Transmission     1740     1748     644       Requirements     Requirements     Moisture Method     M       Density Method     Density Specification     Moisture Method     M       ASTM D6938     95% MIN     ASTM D3017     Max Den       Test Proctors       Test Type     Material     Optimum Moisture     Max Den       STANDARD PROCTOR     AB3     8%     136 pc       Lift/Elev Proctor     Field Moisture %     Optimum Moisture %     Moisture Moisture Pry Density       W RD FROM BENZINGER, STA 00, 4 LCL     4     FG     1     5.4     8.0     Pass     132.0       W RD FROM BENZINGER, STA 20, 4 LCL     4     FG     1     5.8     8.0     Pass     132.0       W RD FROM BENZINGER, STA 25, 6 (RCL     4     FG     1     5.8     8.0     Pass     132.0       W RD FROM BENZINGER, STA 25, 4 LCL     4     FG     1     5.8     8.0 <td>Serial No.     Test Mode     Density Current     Density Previous     Moisture Current     M       LER 3440     21653     Direct Transmission     1740     1748     644       Requirements       Density Method     Density Specification     Moisture Method     Moisture Specification       ASTM D6938     95% MIN     ASTM D3017     N       Test Proctors       Test Type     Material     Optimum Moisture     Max Density       Second PROCTOR     AB3     8%     136 pcf       Lift//Elev Proctor     Field Moisture %     Optimum Moisture %     Moisture Dry Result     Max Density Density Density       W RD FROM BENZINGER, STA 40, 4 FG     1     5.9     8.0     Pass     136.0       W RD FROM BENZINGER, STA 40, 4 FG     1     5.4     8.0     Pass     131.0     136.0       W RD FROM BENZINGER, STA 40, 4 FG     1     5.8     8.0     Pass     131.0     136.0       W RD FROM BENZINGER, STA 40, 4 FG     5.8     8.0     Pass     131.0     136.0       W RD FROM BENZING</td> <td>Serial No.     Test Mode     Density Current     Density Previous     Moisture Current     Moisture F       LER 3440     21653     Direct Transmission     1740     1748     644     653       Requirements     Requirements     Moisture Method     Moisture Specification     Moisture Method     Moisture Specification       ASTM D6938     95% MIN     ASTM D3017     N/A       Test Proctors       Test Type     Material     Optimum Moisture     Max Density     Reference       STANDARD PROCTOR     AB3     8%     136 pcf     Cli       W RD FROM BENZINGER, STA     4     FG     1     5.9     8.0     Pass     132.0     136.0     97.0       W RD FROM BENZINGER, STA     4     FG     1     5.4     8.0     Pass     132.0     136.0     97.0       W RD FROM BENZINGER, STA     4     FG     1     5.4     8.0     Pass     132.0     136.0     95.0       VR D FROM BENZINGER, STA     4     FG     1     5.4     8.0     Pass     13</td>	Serial No.     Test Mode     Density Current     Density Previous     Moisture Current     M       LER 3440     21653     Direct Transmission     1740     1748     644       Requirements       Density Method     Density Specification     Moisture Method     Moisture Specification       ASTM D6938     95% MIN     ASTM D3017     N       Test Proctors       Test Type     Material     Optimum Moisture     Max Density       Second PROCTOR     AB3     8%     136 pcf       Lift//Elev Proctor     Field Moisture %     Optimum Moisture %     Moisture Dry Result     Max Density Density Density       W RD FROM BENZINGER, STA 40, 4 FG     1     5.9     8.0     Pass     136.0       W RD FROM BENZINGER, STA 40, 4 FG     1     5.4     8.0     Pass     131.0     136.0       W RD FROM BENZINGER, STA 40, 4 FG     1     5.8     8.0     Pass     131.0     136.0       W RD FROM BENZINGER, STA 40, 4 FG     5.8     8.0     Pass     131.0     136.0       W RD FROM BENZING	Serial No.     Test Mode     Density Current     Density Previous     Moisture Current     Moisture F       LER 3440     21653     Direct Transmission     1740     1748     644     653       Requirements     Requirements     Moisture Method     Moisture Specification     Moisture Method     Moisture Specification       ASTM D6938     95% MIN     ASTM D3017     N/A       Test Proctors       Test Type     Material     Optimum Moisture     Max Density     Reference       STANDARD PROCTOR     AB3     8%     136 pcf     Cli       W RD FROM BENZINGER, STA     4     FG     1     5.9     8.0     Pass     132.0     136.0     97.0       W RD FROM BENZINGER, STA     4     FG     1     5.4     8.0     Pass     132.0     136.0     97.0       W RD FROM BENZINGER, STA     4     FG     1     5.4     8.0     Pass     132.0     136.0     95.0       VR D FROM BENZINGER, STA     4     FG     1     5.4     8.0     Pass     13		

Kansas City Testing & Engineering, LLC 1141 Southwest Blvd. Kansas City, KS 66103 Phone: 913-321-8100 https://www.kctesting.com

TECHNICIAN: ERIC HOWARD CME TECHNICIAN III

## REPORT DISTRIBUTION:

KEVIN HIGDON CHAD SIPES MATT SCHLICHT MARC COOK STEVEN ROBBINS JOHN JACKSON JOHN DIMAURO



Page 2 of 2 Report: K37876

KANSAS CITY TESTING & ENGINEERING, LLC,

JIM BYRNES, R.G. PROJECT MANAGER