



04/06/2021

RE: 210322
Lot 89 MN

MiTek USA, Inc.

16023 Swingley Ridge Rd
Chesterfield, MO 63017
314-434-1200

Site Information:

Customer: Project Name: 210322
Lot/Block:
Address:
City:

Model:
Subdivision:
State:

General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):

Design Code: IRC2018/TPI2014
Wind Code: N/A
Roof Load: 45.0 psf


Design Program: MiTek 20/20 8.4
Wind Speed: 115 mph
Floor Load: N/A psf

This package includes 62 individual, dated Truss Design Drawings and 0 Additional Drawings.

No.	Seal#	Truss Name	Date	No.	Seal#	Truss Name	Date
1	I45104177	A1	3/9/2021	21	I45104197	C4	3/9/2021
2	I45104178	A2	3/9/2021	22	I45104198	C5	3/9/2021
3	I45104179	A3	3/9/2021	23	I45104199	C6	3/9/2021
4	I45104180	A4	3/9/2021	24	I45104200	D1	3/9/2021
5	I45104181	A5	3/9/2021	25	I45104201	D2	3/9/2021
6	I45104182	B1	3/9/2021	26	I45104202	D3	3/9/2021
7	I45104183	B2	3/9/2021	27	I45104203	D4	3/9/2021
8	I45104184	B3	3/9/2021	28	I45104204	D5	3/9/2021
9	I45104185	B4	3/9/2021	29	I45104205	D6	3/9/2021
10	I45104186	B5	3/9/2021	30	I45104206	D8	3/9/2021
11	I45104187	B6	3/9/2021	31	I45104207	E1	3/9/2021
12	I45104188	B7	3/9/2021	32	I45104208	E2	3/9/2021
13	I45104189	B8	3/9/2021	33	I45104209	E3	3/9/2021
14	I45104190	B9	3/9/2021	34	I45104210	J1	3/9/2021
15	I45104191	B10	3/9/2021	35	I45104211	J2	3/9/2021
16	I45104192	B11	3/9/2021	36	I45104212	J3	3/9/2021
17	I45104193	B12	3/9/2021	37	I45104213	J4	3/9/2021
18	I45104194	C1	3/9/2021	38	I45104214	LAY1	3/9/2021
19	I45104195	C2	3/9/2021	39	I45104215	LAY2	3/9/2021
20	I45104196	C3	3/9/2021	40	I45104216	LAY3	3/9/2021

The truss drawing(s) referenced above have been prepared by
MiTek USA, Inc. under my direct supervision
based on the parameters provided by Wheeler - Waverly.
Truss Design Engineer's Name: Garcia, Juan
My license renewal date for the state of Kansas is April 30, 2022.
Kansas COA: E-943

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek. Any project specific information included is for MiTek customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.



March 09, 2021



04/06/2021

RE: 210322 - Lot 89 MN

MiTek USA, Inc.

16023 Swingley Ridge Rd
Chesterfield, MO 63017
314-434-1200

Site Information:

Project Customer: Project Name: 210322

Lot/Block:

Subdivision:

Address:

City, County:

State:

No.	Seal#	Truss Name	Date
41	I45104217	LAY4	3/9/2021
42	I45104218	V1	3/9/2021
43	I45104219	V2	3/9/2021
44	I45104220	V3	3/9/2021
45	I45104221	V4	3/9/2021
46	I45104222	V4A	3/9/2021
47	I45104223	V5	3/9/2021
48	I45104224	V6	3/9/2021
49	I45104225	V7	3/9/2021
50	I45104226	V8	3/9/2021
51	I45104227	V9	3/9/2021
52	I45104228	V10	3/9/2021
53	I45104229	V11	3/9/2021
54	I45104230	V12	3/9/2021
55	I45104231	V13	3/9/2021
56	I45104232	V14	3/9/2021
57	I45104233	V15	3/9/2021
58	I45104234	V16	3/9/2021
59	I45104235	V17	3/9/2021
60	I45104236	V18	3/9/2021
61	I45104237	V19	3/9/2021
62	I45104238	V20	3/9/2021



04/06/2021

RE: 210322
Lot 89 MN

MiTek USA, Inc.

16023 Swingley Ridge Rd
Chesterfield, MO 63017
314-434-1200

Site Information:

Customer: Project Name: 210322
Lot/Block:
Address:
City:

Model:
Subdivision:
State:

General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):

Design Code: IRC2018/TPI2014
Wind Code: N/A
Roof Load: 45.0 psf

Design Program: MiTek 20/20 8.4
Wind Speed: 115 mph
Floor Load: N/A psf

This package includes 62 individual, dated Truss Design Drawings and 0 Additional Drawings.

No.	Seal#	Truss Name	Date	No.	Seal#	Truss Name	Date
1	I45104177	A1	3/9/2021	21	I45104197	C4	3/9/2021
2	I45104178	A2	3/9/2021	22	I45104198	C5	3/9/2021
3	I45104179	A3	3/9/2021	23	I45104199	C6	3/9/2021
4	I45104180	A4	3/9/2021	24	I45104200	D1	3/9/2021
5	I45104181	A5	3/9/2021	25	I45104201	D2	3/9/2021
6	I45104182	B1	3/9/2021	26	I45104202	D3	3/9/2021
7	I45104183	B2	3/9/2021	27	I45104203	D4	3/9/2021
8	I45104184	B3	3/9/2021	28	I45104204	D5	3/9/2021
9	I45104185	B4	3/9/2021	29	I45104205	D6	3/9/2021
10	I45104186	B5	3/9/2021	30	I45104206	D8	3/9/2021
11	I45104187	B6	3/9/2021	31	I45104207	E1	3/9/2021
12	I45104188	B7	3/9/2021	32	I45104208	E2	3/9/2021
13	I45104189	B8	3/9/2021	33	I45104209	E3	3/9/2021
14	I45104190	B9	3/9/2021	34	I45104210	J1	3/9/2021
15	I45104191	B10	3/9/2021	35	I45104211	J2	3/9/2021
16	I45104192	B11	3/9/2021	36	I45104212	J3	3/9/2021
17	I45104193	B12	3/9/2021	37	I45104213	J4	3/9/2021
18	I45104194	C1	3/9/2021	38	I45104214	LAY1	3/9/2021
19	I45104195	C2	3/9/2021	39	I45104215	LAY2	3/9/2021
20	I45104196	C3	3/9/2021	40	I45104216	LAY3	3/9/2021


The truss drawing(s) referenced above have been prepared by
MiTek USA, Inc. under my direct supervision
based on the parameters provided by Wheeler - Waverly.

Truss Design Engineer's Name: Garcia, Juan

My license renewal date for the state of Missouri is December 31, 2022.

Missouri COA: 001193

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek. Any project specific information included is for MiTek customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.



March 09, 2021



04/06/2021

RE: 210322 - Lot 89 MN

MiTek USA, Inc.

16023 Swingley Ridge Rd
Chesterfield, MO 63017
314-434-1200

Site Information:

Project Customer: Project Name: 210322

Lot/Block:

Subdivision:

Address:

City, County:

State:

No.	Seal#	Truss Name	Date
41	I45104217	LAY4	3/9/2021
42	I45104218	V1	3/9/2021
43	I45104219	V2	3/9/2021
44	I45104220	V3	3/9/2021
45	I45104221	V4	3/9/2021
46	I45104222	V4A	3/9/2021
47	I45104223	V5	3/9/2021
48	I45104224	V6	3/9/2021
49	I45104225	V7	3/9/2021
50	I45104226	V8	3/9/2021
51	I45104227	V9	3/9/2021
52	I45104228	V10	3/9/2021
53	I45104229	V11	3/9/2021
54	I45104230	V12	3/9/2021
55	I45104231	V13	3/9/2021
56	I45104232	V14	3/9/2021
57	I45104233	V15	3/9/2021
58	I45104234	V16	3/9/2021
59	I45104235	V17	3/9/2021
60	I45104236	V18	3/9/2021
61	I45104237	V19	3/9/2021
62	I45104238	V20	3/9/2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN
210322	A1	Hip Girder	1	1	

Wheeler Lumber, Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-GWMwCOTIVAn8StAD4vbZkjudr76I67GoTsgRPaAzcxlK

RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
04/06/2021

LOAD CASE(S) Standard

Uniform Loads (plf)

Vert: 1-2=-70, 2-3=-70, 3-4=-70, 4-5=-70, 5-6=-70, 7-10=-20

Concentrated Loads (lb)

Vert: 3=-12(F) 4=-12(F) 9=-10(F) 8=-10(F) 11=-12(F) 12=-12(F) 13=-12(F) 14=-10(F) 15=-10(F) 16=-10(F)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
 Chesterfield, MO 63017

Job

210322

Truss

A2

Truss Type

Hip

Qty

1

Ply

1

Lot 89 MN

Job Reference (optional)

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-kjwlcpm8x5GJVJoGSi4zF5A7UWWhdskVd5KAy6czcxIJ

13-11-8

4-11-8

RELEASE FOR

CONSTRUCTION

AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

LEES SUMMIT, MISSOURI

04/06/2021

Scale = 1:25.0




Plate Offsets (X,Y)--		[5:0-3-8,Edge]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	25.0	Plate Grip DOL	1.15	TC	0.48	Vert(LL)	-0.05	MT20		197/144	
TCDL	10.0	Lumber DOL	1.15	BC	0.41	Vert(CT)	-0.10				
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.01				
BCDL	10.0	Code IRC2018/TPI2014		Matrix-S		Wind(LL)	0.03	Weight: 44 lb		FT = 10%	

LUMBER-		BRACING-	
TOP CHORD	2x4 SPF No.2	TOP CHORD	Structural wood sheathing directly applied or 5-8-5 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-4.
BOT CHORD	2x4 SPF No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x3 SPF No.2 *Except*		
	2-9.5-6: 2x6 SPF No.2		

REACTIONS.	
(size)	9=0-3-8, 6=0-3-8
Max Horz	9=59(LC 5)
Max Uplift	9=-85(LC 8), 6=-58(LC 9)
Max Grav	9=688(LC 1), 6=604(LC 1)

FORCES.	
(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	2-3=-849/64, 3-4=-672/95, 4-5=-835/63, 2-9=-623/120, 5-6=-523/90
BOT CHORD	8-9=-53/679, 7-8=-55/676, 6-7=-23/674

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-6.0" tall by 2'-0.0" wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 6.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



March 9,2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN
210322	A3	Roof Special Girder	1	1	

Wheeler Lumber, Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-CvUhp9nmOOA7TNS00cCoJjFMwzlb38mK_wWe2zcxlI

RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
04/06/2021

J45104179
Page 2

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)
- Vert: 1-2=-70, 2-3=-70, 3-4=-70, 4-7=-70, 7-9=-70, 13-16=-20, 12-13=-20, 10-12=-20, 8-10=-20
- Concentrated Loads (lb)
- Vert: 7=-13(F) 17=-13(F) 18=-13(F) 19=-13(F) 20=-13(F) 21=-10(F) 23=-10(F) 24=-10(F) 25=-10(F) 26=-10(F)

 WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
Chesterfield, MO 63017

Job

210322

Truss

A4

Truss Type

Roof Special

Qty

1

Ply

1

Lot 89 MN

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

ID:dwZTNcNXrfJm8tRCSIY7DzSTnz-g5231VoOSiW1kdyfaj7RKWFQIKMaKTowYef3AUzcxIH

04/08/2021

0-10-8

7-0-0

9-0-0

13-11-8

20-8-0

22-11-11

25-8-0

26-6-8

0-10-8

7-0-0

2-0-0

4-11-8


6-8-8

2-3-11

2-8-5

0-10-8

Scale = 1:46.1



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.65	Vert(LL)	-0.08 10-11	>999	360	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.51	Vert(CT)	-0.16 10-11	>845	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.71	Horz(CT)	0.05 8	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S	Wind(LL)	0.03 10-11	>999	240	Weight: 88 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2 *Except* 3-4: 2x6 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 5-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 4-6.
BOT CHORD 2x4 SPF No.2 *Except* 8-10: 2x6 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS 2x3 SPF No.2 *Except* 2-14: 2x6 SPF No.2	6-0-0 oc bracing: 11-12.

REACTIONS.	(size) 14=0-3-8, 12=0-3-8, 8=0-3-8 Max Horz 14=-62(LC 13) Max Uplift 14=-128(LC 8), 12=-187(LC 9), 8=-114(LC 9) Max Grav 14=581(LC 1), 12=1388(LC 1), 8=456(LC 1)
FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-572/129, 3-4=-461/160, 4-5=0/521, 5-6=0/307, 6-7=-1007/221, 7-8=-1201/182, 2-14=-533/172
BOT CHORD	13-14=-78/413, 12-13=-123/334, 11-12=-600/71, 10-11=-101/478, 8-10=-115/1032
WEBS	4-12=-907/54, 5-12=-667/192, 5-11=0/311, 6-11=-801/177, 6-10=-29/549

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

3) Provide adequate drainage to prevent water ponding.

4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.


5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.

6) Bearing at joint(s) 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 14=128, 12=187, 8=114.

8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



March 9,2021

Job

210322

Truss

A5

Truss Type

HALF HIP GIRDER

Qty

1

Ply

2

Lot 89 MN

Job Reference (optional)

8.430 e Nov 30 2020 MiTek Industries, Inc. 11/30/2020 11:11 AM

RELEASE FOR

CONSTRUCTION

AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

USE'S SUMMARY MISSOURI

45104181

Wheeler Lumber, Waverly, KS 66871, Mitek

ID:dwZTNcNXrqfJm8tRCSIY7DzSTnz-TTqb80mTNf_Yfa1OZZUDm1IFMrCF2TEe0?aqyZcgL5

2-8-5

2-8-5

6-3-2

3-6-13

9-3-11

3-0-9

12-0-0

2-8-5

04/06/2021

Scale = 1"=22.5'

Plate Offsets (X,Y)--		[2:0-4-10,Edge], [4:0-4-3,0-1-5], [5:0-8-0,0-4-0], [6:0-3-8,0-6-4], [8:0-8-8,0-2-8]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.83
TCDL 10.0	Lumber DOL	1.15	BC 0.63
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.59
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S
			DEFL.
			in (loc) l/defl L/d
			Vert(LL) -0.13 5-6 >999 360
			Vert(CT) -0.23 5-6 >622 240
			Horz(CT) 0.18 4 n/a n/a
			Wind(LL) 0.08 5-6 >999 240
			PLATES
			MT20 197/144
			M18SHS 197/144
			Weight: 147 lb FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2 *Except* 2-4: 2x4 SPF 2400F 2.0E	TOP CHORD Structural wood sheathing directly applied or 4-7-5 oc purlins, except[PSA] end verticals, and 2-0-0 oc purlins (6-0-0 max.): 1-2.
BOT CHORD 2x8 SP DSS *Except* 7-9: 2x6 SP 2400F 2.0E	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SPF No.2	WEBS 1 Row at midpt 2-8

REACTIONS. (lb/size)	9=3571/0-3-8, 4=3571/0-3-8
Max Horz	9=-125(LC 6)
Max Uplift	9=-283(LC 4), 4=-401(LC 9)
Max Grav	9=3571(LC 1), 4=3581(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	8-9=-3200/256, 1-2=-420/67, 2-3=-7491/553, 3-4=-11431/1174
BOT CHORD	7-10=-41/535, 8-11=-524/6259, 7-11=-524/6259, 7-12=-458/6443, 12-13=-458/6443, 6-13=-458/6443, 6-14=-853/8830, 5-14=-854/8836, 5-15=-1046/10392, 4-15=-980/9910
WEBS	2-8=-6355/486, 2-6=-299/4827, 3-6=-2108/466, 3-5=-437/3419

NOTES-

- 1) N/A
- 2) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-4-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-2-0 oc, 2x8 - 4 rows staggered at 0-2-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- 3) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- 4) Unbalanced roof live loads have been considered for this design.
- 5) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 6) Provide adequate drainage to prevent water ponding.
- 7) All plates are MT20 plates unless otherwise indicated.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 10) Bearing at joint(s) 9, 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 283 lb uplift at joint 9 and 401 lb uplift at joint 4.
- 12) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

STATE OF MISSOURI

JUAN GARCIA

NUMBER E-2000162101

PROFESSIONAL ENGINEER

JUAN GARCIA

LICENSED

16952

PROFESSIONAL ENGINEER

March 9,2021

MiTek

16023 Swingley Ridge Rd

Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES USE'S SUMMIT, MISSOURI 04/06/2021
210322	A5	HALF HIP GIRDER	1	2	Job Reference (optional)	
Wheeler Lumber, Waverly, KS 66871, Mitek						8.430 e Nov 30 2020 MiTek Industries, Inc. Page 2
ID:dwZTNcNXrfJm8tRCSiY7DzSTnz-TTqb80mTNf_Yfa1OZZUDm1IFMrCF2TEe0?a9qyzcgL5						


NOTES-

14) Use Simpson Strong-Tie HUS26 (14-10d Girder, 4-10d Truss) or equivalent spaced at 2'-0" oc max. starting at 2'-0" from the left end to 10'-0" to connect truss(es) to back face of bottom chord.

15) Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)
- Vert: 1-2=-70, 2-4=-70, 7-9=-20, 5-7=-20, 4-5=-20
- Concentrated Loads (lb)
- Vert: 10=-1218(B) 12=-1217(B) 13=-1217(B) 14=-1219(B) 15=-1217(B)




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.15	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.09	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.13	Horz(CT)	-0.00	17	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-R						
								Weight: 173 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x3 SPF No.2 *Except* 16-17: 2x4 SPF No.2	WEBS 1 Row at midpt 12-21, 11-22, 10-23, 13-20, 14-19
OTHERS 2x4 SPF No.2	


REACTIONS. All bearings 27-8-14.
(lb) - Max Horz 31=323(LC 5)
Max Uplift All uplift 100 lb or less at joint(s) 31, 17, 21, 22, 23, 24, 25, 26, 27, 28, 29, 20, 19, 18 except 30=143(LC 8)
Max Grav All reactions 250 lb or less at joint(s) 31, 17, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 20, 19, 18

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-296/102

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 2x4 MT20 unless otherwise indicated.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 7) Gable studs spaced at 2-0-0 oc.
 - 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 31, 17, 21, 22, 23, 24, 25, 26, 27, 28, 29, 20, 19, 18 except (jt=lb) 30=143.
 - 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	25.0	Plate Grip DOL	1.15	TC	0.60	Vert(LL)	-0.17 11-12 >999 360	MT20		197/144	
TCDL	10.0	Lumber DOL	1.15	BC	0.60	Vert(CT)	-0.32 11-12 >999 240				
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.72	Horz(CT)	0.07 8 n/a n/a				
BCDL	10.0	Code IRC2018/TPI2014		Matrix-S		Wind(LL)	0.12 12-13 >999 240			Weight: 131 lb	FT = 10%

LUMBER-		BRACING-	
TOP CHORD	2x4 SPF No.2 *Except* 6-7: 2x4 SPF 2100F 1.8E	TOP CHORD	Structural wood sheathing directly applied or 3-1-5 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 1-2.
BOT CHORD	2x3 SPF No.2 *Except* 11-14: 2x4 SPF 2100F 1.8E, 8-10: 2x4 SPF No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 9-10.
WEBS	2x3 SPF No.2 *Except* 6-11,6-9,7-8: 2x4 SPF No.2	WEBS	1 Row at midpt 3-11, 6-9, 7-8

REACTIONS.	
(size)	14=Mechanical, 8=Mechanical
Max Horz	14=310(LC 7)
Max Uplift	14=-181(LC 8), 8=-147(LC 8)
Max Grav	14=1274(LC 2), 8=1316(LC 2)
FORCES.	
(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	1-2=-273/35, 2-3=-2495/347, 3-5=-1563/254, 5-6=-1535/401, 6-7=-892/221, 7-8=-1167/190
BOT CHORD	13-14=-589/3197, 12-13=-575/3180, 11-12=-403/2222, 5-11=-474/265
WEBS	2-14=-3079/426, 2-12=-978/173, 3-12=0/424, 3-11=-981/249, 9-11=-41/726, 6-11=-345/1199, 6-9=-500/145, 7-9=-89/910

- NOTES-**
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 14=181, 8=147.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- STATE OF MISSOURI

JUAN GARCIA

NUMBER E-2000162101


PROFESSIONAL ENGINEER

JUAN GARCIA

LICENSED

16952

PROFESSIONAL ENGINEER
- March 9,2021



REACTIONS. (size) 12=Mechanical, 6=Mechanical
Max Horz 12=304(LC 7)
Max Uplift 12=-184(LC 8), 6=-143(LC 8)
Max Grav 12=1293(LC 2), 6=1291(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2075/287, 3-4=-1036/198, 4-5=-975/227, 5-6=-1163/185
BOT CHORD 11-12=-557/3352, 10-11=-550/3364, 9-10=-278/1808, 8-9=-572/0
WEBS 2-12=-3430/460, 2-10=-1587/275, 3-10=0/616, 3-9=-1181/319, 7-9=0/780, 4-9=-26/434,
5-9=-93/971

-
- STATE OF MISSOURI
- JUAN GARCIA
- NUMBER E-2000162101
- PROFESSIONAL ENGINEER




WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MI-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTEK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601.

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEES SUMMIT, MISSOURI J45104185
210322	B4	Roof Special	1	1	Job Reference (optional)	8.430 s Feb 12 2021 MiTek Industries, Inc. Not for construction
Wheeler Lumber,	Waverly, KS - 66871,					04/06/2021
ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-ReX4iEuPa9XuisZB2PGJfCpmY1mC1f5OubUT1zcxI9						Scale = 1:71.0




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.56	Vert(LL)	-0.14 11-12	>999	360	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.74	Vert(CT)	-0.26 10-11	>999	240	M18SHS	197/144
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.91	Horz(CT)	0.09 6	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S	Wind(LL)	0.08 11-12	>999	240		
								Weight: 139 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2 *Except*	TOP CHORD Structural wood sheathing directly applied or 4-11-7 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 1-2.
2-4: 2x6 SPF No.2, 4-5: 2x4 SPF 2100F 1.8E	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
BOT CHORD 2x4 SPF No.2 *Except*	WEBS 1 Row at midpt 2-13, 3-9, 5-6
8-10: 2x3 SPF No.2	
WEBS 2x3 SPF No.2 *Except*	
2-13,3-9,4-7,5-6: 2x4 SPF No.2	

REACTIONS.	(size) 13=Mechanical, 6=Mechanical
	Max Horz 13=244(LC 7)
	Max Uplift 13=-34(LC 8), 6=-7(LC 8)
	Max Grav 13=1237(LC 1), 6=1237(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-1970/65, 3-4=-998/73, 4-5=-968/93, 5-6=-1173/41
BOT CHORD	12-13=-81/2600, 11-12=-78/2605, 10-11=-43/1696, 9-10=-14/1736, 8-10=-496/0
WEBS	2-13=-2718/56, 2-11=-972/37, 3-11=0/522, 3-9=-1112/132, 7-9=0/700, 4-9=0/362, 5-9=0/923

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - All plates are MT20 plates unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 13, 6.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



March 9,2021

Job

210322

Truss

B5

Truss Type

Roof Special

Qty

1

Ply

1

Lot 89 MN

Job Reference (optional)

Wheeler Lumber,

Waverly, KS - 66871,


8.430 s Feb 12 2021 MiTek Industries, Inc.

145104186

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-N0er7wvf6nncx9ja9qlnkdg5IMiUg_LOrC4bXvzcxl7

04/06/2021

Scale = 1:72.3



										1-11-4		7-11-4		13-9-9		19-6-0		20-0-0		27-8-14	
										1-11-4		6-0-0		5-10-5		5-8-7		0-6-0		7-8-14	
Plate Offsets (X,Y)--										[6:Edge,0-2-4], [10:0-3-8,0-2-0], [12:0-2-8,0-1-8], [13:0-2-8,0-1-8]											
LOADING (psf)		SPACING-		2-0-0		CSI.		DEFL.		in (loc)		l/defl		L/d		PLATES		GRIP			
TCLL	25.0	Plate Grip DOL		1.15		TC 0.78		Vert(LL)		-0.15 13-14		>999		360		MT20		197/144			
TCDL	10.0	Lumber DOL		1.15		BC 0.79		Vert(CT)		-0.30 13-14		>999		240							
BCLL	0.0 *	Rep Stress Incr		YES		WB 0.71		Horz(CT)		0.06 7		n/a		n/a							
BCDL	10.0	Code IRC2018/TPI2014				Matrix-S		Wind(LL)		0.06 12-13		>999		240		Weight: 138 lb		FT = 10%			

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*
3-5: 2x6 SPF No.2, 5-6: 2x4 SPF 2100F 1.8E
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2 *Except*
5-8,6-7: 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-5-5 oc purlins, except end verticals, and 2-0-0 oc purlins (2-8-12 max.): 2-3.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 3-12, 4-10, 6-7

REACTIONS.

(size) 7=Mechanical, 14=Mechanical
Max Horz 14=244(LC 7)
Max Uplift 7=-7(LC 8), 14=-35(LC 8)
Max Grav 7=1295(LC 2), 14=1289(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-2306/47, 3-4=-1748/67, 4-5=-983/84, 5-6=-989/96, 6-7=-1176/44
BOT CHORD 13-14=-159/713, 12-13=-54/2325, 11-12=-26/1524, 10-11=-26/1524
WEBS 9-11=-417/0, 2-13=0/1864, 3-13=-696/92, 3-12=-941/47, 4-12=0/677, 4-10=-998/112, 8-10=0/618, 5-10=0/470, 2-14=-1313/92, 6-10=0/977

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 14.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



March 9,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
Chesterfield, MO 63017





Plate Offsets (X,Y)-- [4:0-2-12,0-2-11], [5:0-2-12,0-2-0], [9:0-6-0,0-2-8], [10:0-2-8,0-1-8]											
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d		PLATES GRIP			
TCLL	25.0	Plate Grip DOL	1.15	TC	0.89	Vert(LL)	-0.21 10-11	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.99	Vert(CT)	-0.46 9-10	>725	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.72	Horz(CT)	0.06 6	n/a	n/a		
BCDL	10.0	Code IRC2018/TPI2014		Matrix-S		Wind(LL)	0.05 9-10	>999	240	Weight: 135 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2 *Except* 3-4: 2x6 SPF No.2	TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (3-7-2 max.): 2-3.
BOT CHORD 2x4 SPF No.2 *Except* 8-9: 2x3 SPF No.2	BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 2x3 SPF No.2 *Except* 3-9,4-7,5-6: 2x4 SPF No.2	WEBS 1 Row at midpt 3-9, 2-11, 5-6


REACTIONS. (size) 6=Mechanical, 11=Mechanical
Max Horz 11=244(LC 7)
Max Uplift 6=-5(LC 8), 11=-35(LC 8)
Max Grav 6=1239(LC 1), 11=1238(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1938/53, 3-4=-1039/62, 4-5=-981/98, 5-6=-1167/45
BOT CHORD 10-11=-125/952, 9-10=-31/1949, 8-9=-405/0
WEBS 2-10=0/1215, 3-10=-491/116, 3-9=-1270/105, 7-9=0/600, 4-9=0/340, 2-11=-1367/71, 5-9=0/930

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 11.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



March 9,2021



LUMBER-		BRACING-	
TOP CHORD	2x4 SPF No.2 *Except* 3-4,4-5: 2x6 SPF No.2	TOP CHORD	Structural wood sheathing directly applied or 4-9-6 oc purlins, except end verticals, and 2-0-0 oc purlins (3-8-6 max.): 2-3.
BOT CHORD	2x4 SPF No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x3 SPF No.2	WEBS	1 Row at midpt 3-7, 5-6

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD	1-2=-992/42, 2-3=-1741/71, 3-4=-1009/72, 4-5=-978/96, 1-11=-1309/48, 5-6=-1174/48
BOT CHORD	9-10=-119/1146, 7-9=-34/1744
WEBS	2-10=-641/69, 2-9=0/835, 3-9=-316/84, 3-7=-1113/98, 4-7=0/392, 1-10=0/1103, 5-7=0/983

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCFL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Bearing at joint(s) 11 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11, 6.
 - 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



March 9, 2021




Plate Offsets (X,Y)--		[1:0-2-0,0-1-8], [4:0-3-14,0-3-0], [5:0-2-8,Edge], [6:Edge,0-2-8], [9:0-2-8,0-1-8]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.97
TCDL 10.0	Lumber DOL	1.15	BC 0.95
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.80
BCDL 10.0	Code	IRC2018/TPI2014	Matrix-S
			DEFL.
			in (loc) l/defl L/d
			Vert(LL) -0.25 7-9 >999 360
			Vert(CT) -0.53 7-9 >620 240
			Horz(CT) 0.07 6 n/a n/a
			Wind(LL) 0.06 9 >999 240
			PLATES GRIP
			MT20 197/144
			Weight: 124 lb FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2 *Except* 3-4: 2x6 SPF No.2	TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (3-7-1 max.): 2-3.
BOT CHORD 2x4 SPF No.2 *Except* 6-8: 2x4 SPF 2100F 1.8E	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 2-2-0 oc bracing: 7-9.
WEBS 2x3 SPF No.2 *Except* 3-7: 2x4 SPF No.2	WEBS 1 Row at midpt 3-7, 5-6

REACTIONS.	(size) 11=0-3-8, 6=Mechanical Max Horz 11=238(LC 5) Max Uplift 11=34(LC 8), 6=-7(LC 8) Max Grav 11=1275(LC 2), 6=1308(LC 2)
FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-952/43, 2-3=-2052/65, 3-4=-1044/57, 4-5=-997/91, 1-11=-1241/57, 5-6=-1185/41
BOT CHORD	9-10=-155/1006, 7-9=-64/2062
WEBS	2-10=-667/56, 2-9=0/1326, 3-9=-533/113, 3-7=-1343/125, 4-7=0/348, 1-10=-27/1119, 5-7=0/1000

- NOTES-
- 1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

3) Provide adequate drainage to prevent water ponding.

4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

6) Refer to girder(s) for truss to truss connections.

7) Bearing at joint(s) 11 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11, 6.

9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- STATE OF MISSOURI

JUAN GARCIA

NUMBER E-2000162101

PROFESSIONAL ENGINEER

JUAN GARCIA

LICENSED

16952

PROFESSIONAL ENGINEER

March 9,2021
- WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see


Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

MiTek

16023 Swingley Ridge Rd
Chesterfield, MO 63017

04/06/2021




TOP CHORD	Structural wood sheathing directly applied or 4-11-11 oc purlins, except end verticals, and 2-0-0 oc purlins (4-9-13 max.): 2-3.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	1 Row at midpt 3-11, 4-8, 6-7

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDF=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Bearing at joint(s) 12 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 12, 7.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



WARNING – verify design parameters and READ NOTES ON THIS AND INCLUDED WELDER REFERENCE PAGE MH-1413 (Rev. 3/25/2020) BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for the building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2671 Crain Highway, Suite 203 Waldorf, MD 20601.





LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	25.0	Plate Grip DOL	1.15	TC	0.81	Vert(LL)	-0.25 14-15 >999 360	MT20		197/144	
TCDL	10.0	Lumber DOL	1.15	BC	0.69	Vert(CT)	-0.44 14-15 >747 240	M18SHS		197/144	
BCLL	0.0 *	Rep Stress Incr	YES	WB	1.00	Horz(CT)	0.22 8 n/a n/a	MT18HS		197/144	
BCDL	10.0	Code IRC2018/TPI2014		Matrix-S		Wind(LL)	0.19 14-15 >999 240	Weight: 127 lb		FT = 10%	

LUMBER-		BRACING-	
TOP CHORD	2x4 SPF No.2 *Except* 6-7: 2x4 SPF 2100F 1.8E	TOP CHORD	Structural wood sheathing directly applied or 2-1-10 oc purlins, except end verticals.
BOT CHORD	2x4 SPF No.2 *Except* 1-15: 2x8 SP DSS, 12-15: 2x4 SPF 2100F 1.8E, 9-11: 2x6 SPF No.2	BOT CHORD	Rigid ceiling directly applied or 8-3-6 oc bracing.
WEBS	2x3 SPF No.2 *Except* 2-15: 2x6 SPF No.2	WEBS	1 Row at midpt 3-13, 5-11, 7-8

REACTIONS.	
(size)	1=0-3-8, 8=0-3-8
Max Horz	1=321(LC 7)
Max Uplift	1=-176(LC 8), 8=-152(LC 8)
Max Grav	1=1300(LC 2), 8=1449(LC 2)
FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	1-2=-5408/987, 2-3=-2615/399, 3-5=-1760/281, 5-6=-957/199, 6-7=-968/220, 8-10=-1299/193, 7-10=-1224/195
BOT CHORD	1-15=-1066/4952, 14-15=-898/4059, 13-14=-433/2357, 11-13=-208/1539
WEBS	2-15=-337/1923, 2-14=-1725/471, 3-14=-8/478, 3-13=-930/255, 5-13=-40/690, 5-11=-1003/282, 7-11=-107/1005, 6-11=-47/459

- NOTES-

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

3) All plates are MT20 plates unless otherwise indicated.


4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

6) Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.


7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=176, 8=152.

8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

**RELEASE FOR
CONSTRUCTION**
145104193
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LET'S SUMMIT MISSOURI
Page 1
4CsXHE8KrQocNGic1ayFrL0I?99fiwNqsizxcXC
6-0 27-7-8
1-0 0-2-8
04/06/2021



REACTIONS. (size) 1=0-3-8, 8=0-3-8
 Max Horz 1=321(LC 7)
 Max Uplift 1=-176(LC 8), 8=-152(LC 8)
 Max Grav 1=1232(LC 1), 8=1232(LC 1)

The seal is circular with a double-lined border. The outer ring contains the text "STATE OF MISSOURI" at the top and "PROFESSIONAL ENGINEER" at the bottom, separated by two stars. The center of the seal contains the name "JUAN GARCIA" and the number "E-2000162101".

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Components**.
Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601.






Plate Offsets (X,Y)-- [6:0-2-11,Edge], [7:0-2-8,Edge], [8:Edge,0-2-8], [17:0-2-4,Edge]									
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d		PLATES GRIP	
TCLL	25.0	Plate Grip DOL	1.15	TC	0.71	Vert(LL)	-0.09 15-17 >999	360	MT20 197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.49	Vert(CT)	-0.19 15-17 >999	240	
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.73	Horz(CT)	-0.10 8 n/a	n/a	
BCDL	10.0	Code IRC2018/TPI2014		Matrix-S		Wind(LL)	0.05 14-15 >999	240	Weight: 133 lb FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2 *Except* 6-7: 2x4 SPF 2100F 1.8E	TOP CHORD Structural wood sheathing directly applied or 3-5-1 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2 *Except* 9-11: 2x3 SPF No.2	BOT CHORD Rigid ceiling directly applied or 9-0-13 oc bracing.
WEBS 2x3 SPF No.2 *Except* 2-17: 2x8 SP DSS	WEBS 1 Row at midpt 7-8

REACTIONS. (size) 17=0-3-8, 8=0-3-8
Max Horz 17=332(LC 5)
Max Uplift 17=-201(LC 8), 8=-151(LC 8)
Max Grav 17=1309(LC 1), 8=1223(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1946/273, 3-5=-1420/251, 5-6=-1143/213, 6-7=-1162/229, 2-17=-1234/245,
8-10=-1162/183, 7-10=-1146/184
BOT CHORD 15-17=-414/786, 14-15=-332/1629, 6-12=-53/506
WEBS 3-14=-548/189, 12-14=-193/1302, 5-12=-367/195, 7-12=-123/998, 2-15=0/844

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 17=201, 8=151.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021




Plate Offsets (X, Y)--		[2:0-0-0,0-0-7], [3:0-7-0,0-1-8], [3:0-4-0,0-1-8], [6:0-4-8,Edge], [9:0-2-12,0-2-0]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.97
TCDL 10.0	Lumber DOL	1.15	BC 0.62
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.70
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S
		DEFL.	in (loc)
		Vert(LL)	-0.25 11-12 >999 360
		Vert(CT)	-0.53 11-12 >623 240
		Horz(CT)	0.25 10 n/a n/a
		Wind(LL)	0.18 15 >999 240
		PLATES	MT20
		GRIP	197/144
		Weight:	147 lb
		FT =	10%

LUMBER-

TOP CHORD 2x4 SPF No.2 *Except*
1-6: 2x6 SP DSS

BOT CHORD 2x4 SPF No.2 *Except*
3-13: 2x4 SPF 2100F 1.8E, 5-12: 2x3 SPF No.2

WEBS 2x3 SPF No.2 *Except*
8-11,9-10: 2x4 SPF No.2

WEDGE
Left: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied, except end verticals.


BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
6-0-0 oc bracing: 2-15.

WEBS 1 Row at midpt 7-11, 9-10

REACTIONS. (size) 2=0-3-8, 10=0-3-8
Max Horz 2=327(LC 5)
Max Uplift 2=-192(LC 8), 10=-152(LC 8)
Max Grav 2=1346(LC 2), 10=1309(LC 2)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-865/33, 3-4=-2944/461, 4-5=-2075/341, 5-7=-2016/437, 7-8=-853/209,
8-9=-890/220, 9-10=-1169/189
BOT CHORD 3-14=-558/2797, 13-14=-558/2797
WEBS 4-13=-1119/283, 11-13=-177/970, 7-13=-270/1162, 7-11=-848/306, 8-11=-72/428,
9-11=-88/923

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=192, 10=152.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-CA06Oz_QhdXmf5AjW4PB_uw5xnpK4kDGE8XvlZzcxl1



Weight: 154 lb FT = 10%

16023 Swingley Ridge Rd
Chesterfield, MO 63017

Job

210322

Truss

C4

Truss Type

Roof Special

Qty

2

Ply

1

Lot 89 MN

Job Reference (optional)

8.430 s Feb 12 2021 MiTek Industries, Inc. 145104197

Wheeler Lumber,

Waverly, KS - 66871,

ID:dwZTNcNXrfJm8tRCSiY7DzSTnz-gNaUbJ72SwfHElw4owQW5SJD4BpALQT0HSH?zcxI0

04/06/2021

Scale = 1:64.8




Plate Offsets (X,Y)--	[2:0-0-0,0-0-7], [3:0-0-13,0-1-8], [5:0-4-4,Edge], [8:0-2-8,Edge], [9:0-3-8,Edge], [12:0-3-0,0-0-0], [14:0-2-8,0-1-8]									
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.76	Vert(LL)	-0.28	3-16	>999	360	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.79	Vert(CT)	-0.49	3-16	>668	240	MT18HS	197/144
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.69	Horz(CT)	0.30	9	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S	Wind(LL)	0.22	17	>999	240	Weight: 140 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2 *Except* 7-8: 2x4 SPF 2100F 1.8E, 1-5: 2x6 SP DSS	TOP CHORD Structural wood sheathing directly applied or 2-11-6 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2 *Except* 3-15: 2x4 SPF 2100F 1.8E, 10-12: 2x3 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-17. 8-7-0 oc bracing: 14-16
WEBS 2x3 SPF No.2 *Except* 18-20,19-21: 2x4 SPF No.2	WEBS 1 Row at midpt 4-14, 6-13, 8-9

REACTIONS.	(size) 2=0-3-8, 9=0-3-8 Max Horz 2=326(LC 5) Max Uplift 2=192(LC 8), 9=152(LC 8) Max Grav 2=1376(LC 2), 9=1438(LC 2)
FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-882/33, 3-4=-2713/399, 4-6=-1780/290, 6-7=-992/207, 7-8=-986/226, 9-11=-1297/190, 8-11=-1208/197
BOT CHORD	3-16=-474/2532, 14-16=-473/2531, 13-14=-207/1523
WEBS	4-16=0/280, 4-14=-1140/301, 6-14=-65/750, 6-13=-963/279, 7-13=-50/476, 8-13=-110/1005

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - All plates are MT20 plates unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=192, 9=152.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




March 9,2021

8.430 s Feb 12 2021 MiTek Industries, Inc. Mon Mar 8 15:51:58 2021 Page 1

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-8Z7sof0gDnUuOK6dVRf3J?UDaQhYayZhS00pSzcxl?

~~Scale = 1:65.7~~



REACTIONS. (size) 16=0-3-8, 8=0-3-8
 Max Horz 16=332(LC 5)
 Max Uplift 16=-200(LC 8), 8=-152(LC 8)
 Max Grav 16=1359(LC 2), 8=1431(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-2057/270, 3-4=-1909/320, 4-6=-1013/197, 6-7=-987/225, 2-16=-1232/244,
8-10=-1292/190, 7-10=-1207/195

BOT CHORD 15-16=-451/948, 4-13=-65/716, 12-13=-262/1708

WEBS 3-15=-298/150, 13-15=-304/1813, 4-12=-1078/316, 6-12=-26/447, 2-15=0/867,
7-12=-111/1008

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) All plates are MT20 plates unless otherwise indicated.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 16=200, 8=152.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021




WARNING – verify design parameters and READ NOTES ON THIS AND INCLUDED WELDER REFERENCE PAGE MH-1413 (Rev. 3/25/2020) BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for the building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2671 Crain Highway, Suite 203 Waldorf, MD 20601.



16023 Swingley Ridge Rd
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021
210322	C6	Common Supported Gable	1	1		
Wheeler Lumber, Waverly, KS - 66871,						8.430 s Feb 12 2021 MiTek Industries, Inc. 145104199
ID:dwZTNcNXrqJm8tRCSiY7DzSTnz-5xFdDL1xlr1B8iUVlwU78k4yCOHu0fos9IV7tKzcHz						Job Reference (optional)



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.21	Vert(LL)	-0.00	1	n/r	120	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.08	Vert(CT)	-0.00	1	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.13	Horz(CT)	-0.00	18	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-R						Weight: 167 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
 BOT CHORD 2x4 SPF No.2
 WEBS 2x4 SPF No.2
 OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 13-22, 12-23, 11-24, 14-21, 15-20

REACTIONS.

All bearings 27-7-8.
 (lb) - Max Horz 32=332(LC 5)
 Max Uplift All uplift 100 lb or less at joint(s) 32, 18, 22, 23, 24, 25, 26, 27, 28, 29, 30, 21, 20, 19 except 31=-140(LC 8)
 Max Grav All reactions 250 lb or less at joint(s) 32, 18, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 21, 20, 19

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-299/102

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 32, 18, 22, 23, 24, 25, 26, 27, 28, 29, 30, 21, 20, 19 except (jt=lb) 31=140.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
 Chesterfield, MO 63017

RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LET'S SUMMER MISSOURI
04-06-2021
0-10-8



REACTIONS. All bearings 20-0-0.
(lb) - Max Horz 24=-186(LC 6)
Max Uplift All uplift 100 lb or less at joint(s) 24, 14, 20, 21, 22, 23, 18, 17, 16, 15
Max Grav All reactions 250 lb or less at joint(s) 24, 14, 19, 20, 21, 22, 23, 18, 17, 16, 15

NOTES-

- 
- A circular professional engineer seal for the State of Missouri. The outer ring contains the text "STATE OF MISSOURI" at the top and "PROFESSIONAL ENGINEER" at the bottom, separated by two stars. The center of the seal contains the name "JUAN GARCIA" and the license number "NUMBER E-2000162101". There are two horizontal lines above and below the name.

A circular blue seal for a Professional Engineer in the State of Kansas. The outer ring contains the text "JUAN GARCIA" at the top and "PROFESSIONAL ENGINEER" at the bottom. Inside this ring, the word "LICENSED" is at the top and "KANSAS" is at the bottom. The center of the seal features the license number "16952" in a large, bold font. A red ink signature is written across the bottom half of the seal, overlapping the "KANSAS" text and the license number.

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

MiTek
16023 Swingley Ridge Rd
Chesterfield, MO 63017

Job

210322

Truss

D2

Truss Type

Common

Qty

5

Ply

1

Lot 89 MN

Job Reference (optional)

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

ID:dwZTNcNXrqfJm8tRCSIY7DzSTnz-1KNNe03BHSHvN0etsLWbD99AxBp6UX?9c3_DxDzcxHx

145104201

20-0-0

4-8-4

04/06/2021

Scale = 1:40.2





Plate Offsets (X,Y)--		[6:Edge,0-6-10], [9:0-1-11,0-2-15]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.77
TCDL 10.0	Lumber DOL	1.15	BC 0.74
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.28
BCDL 10.0	Code	IRC2018/TPI2014	Matrix-S
		DEFL.	in (loc)
		Vert(LL)	-0.17 8-9 >999 360
		Vert(CT)	-0.36 8-9 >649 240
		Horz(CT)	0.03 7 n/a n/a
		Wind(LL)	0.07 8 >999 240
		PLATES	GRIP
		MT20	197/144
		Weight: 68 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 3-7-5 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x3 SPF No.2 *Except* 2-9,6-7: 2x8 SP DSS	

REACTIONS.	(size) 9=0-3-8, 7=0-3-8
Max Horz	9=183(LC 5)
Max Uplift	9=-130(LC 8), 7=-103(LC 9)
Max Grav	9=958(LC 1), 7=870(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-1177/186, 3-4=-911/140, 4-5=-911/140, 5-6=-1188/189, 2-9=-854/178, 6-7=-762/149
BOT CHORD	8-9=-185/920, 7-8=-111/931
WEBS	4-8=-4/472, 5-8=-292/215, 3-8=-273/210

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 9=130, 7=103.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

Job 210322	Truss D3	Truss Type GABLE	Qty 1	Ply 1	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021 J45104202 8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN ID:dwZTNcNXrqfJm8trCSIY7DzSTnz-VWxIsM3p2mPm79D4Q21qmMiLNb9RD74lrjknUfzcxHw 0-10-8
Wheeler Lumber, Waverly, KS - 66871,						Job Reference (optional)




Plate Offsets (X,Y)--		[1:Edge,0-4-2], [3:0-1-4,0-1-8], [7:0-3-8,0-4-15], [12:0-1-4,0-1-0], [19:0-1-4,0-1-0]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.72
TCDL 10.0	Lumber DOL	1.15	BC 0.67
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.16
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S
		DEFL.	in (loc) l/defl L/d
		Vert(LL)	-0.12 8-9 >999 360
		Vert(CT)	-0.29 8-9 >475 240
		Horz(CT)	0.14 7 n/a n/a
		Wind(LL)	0.08 8-9 >999 240
		PLATES	MT20
		GRIP	197/144
		Weight:	49 lb
		FT =	10%

LUMBER-

TOP CHORD 2x4 SPF No.2
 BOT CHORD 2x4 SPF No.2
 WEBS 2x3 SPF No.2 *Except*
 1-10,5-7: 2x6 SPF No.2
 OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-1-14 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 10=0-3-8, 7=0-3-8
 Max Horz 10=-121(LC 4)
 Max Uplift 10=-60(LC 8), 7=-86(LC 9)
 Max Grav 10=516(LC 1), 7=600(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-1094/129, 2-3=-976/224, 3-4=-969/175, 4-5=-1111/75, 1-10=-733/100,
 5-7=-847/94
 BOT CHORD 9-10=-117/927, 8-9=-13/494, 7-8=-15/886
 WEBS 3-8=-113/466, 3-9=-146/525

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 10, 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10, 7.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
 Chesterfield, MO 63017

Job

210322

Truss

D4

Truss Type

GABLE

Qty

1

Ply

1

Lot 89 MN

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

Job Reference (optional)

145104203

RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES

LEE'S SUMMIT, MISSOURI

04/06/2021

ID:dwZTNcNXrfJm8tRCSIY7DzSTnz-Rv2WG253aNgUETMSYT3lrmnjePpghjqbl1DuYzcxHu

25-4-0 29-4-0 34-7-12 4-8-4

2-8-5 9-3-11 11-10-8 15-8-0 19-5-8 25-4-0 29-4-0 34-7-12 4-8-4

2-8-5 6-7-6 2-6-13 3-9-8 3-9-8 5-10-8 4-0-0 5-3-12 4-8-4

Scale = 1:75.4




Plate Offsets (X,Y)--		[1:0-4-8,Edge], [5:0-3-0,0-0-11], [10:Edge,0-5-8], [16:0-7-8,Edge]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.54
TCDL 10.0	Lumber DOL	1.15	BC 0.81
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.91
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S
			DEFL. in (loc) l/defl L/d
			Vert(LL) -0.23 12-13 >999 360
			Vert(CT) -0.48 12-13 >485 240
			Horz(CT) -0.09 13 n/a n/a
			Wind(LL) 0.10 12-13 >999 240
			PLATES GRIP
			MT20 197/144
			MT18HS 197/144
			Weight: 203 lb FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 4-7-12 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2 *Except* 4-16,6-13: 2x3 SPF No.2	BOT CHORD Rigid ceiling directly applied or 4-2-11 oc bracing.
WEBS 2x3 SPF No.2 *Except* 1-19: 2x6 SPF No.2, 10-11: 2x6 SP DSS	WEBS 1 Row at midpt 5-15, 5-14, 7-13
OTHERS 2x4 SPF No.2	

REACTIONS. All bearings 0-2-0 except (jt=length) 13=0-2-4 (input: 0-2-0), 16=0-2-4 (input: 0-2-0), 19=0-3-8, 11=Mechanical.

(lb) - Max Horz 19=-257(LC 6)

Max Uplift All uplift 100 lb or less at joint(s) except 19=-115(LC 9), 13=-246(LC 9), 11=-176(LC 9), 16=-210(LC 8)

Max Grav All reactions 250 lb or less at joint(s) except 19=399(LC 16), 13=1426(LC 16), 11=943(LC 16), 16=1445(LC 15)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-841/264, 2-3=-178/334, 3-4=-93/515, 4-5=-58/557, 5-6=-69/359, 6-7=-17/326, 7-8=-948/257, 8-9=-965/244, 9-10=-1239/313, 1-19=-520/156, 10-11=-779/221

BOT CHORD 18-19=-359/903, 17-18=-341/812, 15-16=-832/43, 13-14=-655/121, 6-14=-416/240, 12-13=-181/748, 11-12=-211/968

WEBS 2-18=-35/408, 2-17=-877/313, 3-17=-25/379, 3-16=-692/226, 5-15=-531/31, 7-13=-1137/313, 8-12=-103/563, 9-12=-297/201

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) Provide adequate drainage to prevent water ponding.
 - 5) All plates are MT20 plates unless otherwise indicated.
 - 6) All plates are 2x4 MT20 unless otherwise indicated.
 - 7) Gable studs spaced at 2-0-0 oc.
 - 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 10) WARNING: Required bearing size at joint(s) 13, 16 greater than input bearing size.
 - 11) Refer to girder(s) for truss to truss connections.
 - 12) Bearing at joint(s) 19, 16 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify compatibility of bearing surface.



March 9,2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN
210322	D4	GABLE	1	1	

Wheeler Lumber, Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

ID:dwZTNcNXrfJm8tRCSiY7DzSTnz-Rv2WG253aNgUETMSYT3lrmnjePpghjqbl1DuYzcXHu

Job Reference (optional)

RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
04/06/2021

45104203

NOTES-

- 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 115 lb uplift at joint 19, 246 lb uplift at joint 13, 176 lb uplift at joint 11 and 210 lb uplift at joint 16.
- 14) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

 **WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
Chesterfield, MO 63017

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-v5cuU06iLhoLsdxe5BbXO?Krrp7SQA5IXhyR4_zcxHt

04/06/2021


~~Scale = 1:72.6~~

Plate Offsets (X,Y)-- [1:0-4-8,Edge], [16:0-1-4,Edge]									
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d		PLATES	GRIP
TCLL 25.0		Plate Grip DOL 1.15		TC 0.71		Vert(LL) -0.22 11-12 >999 360		MT20	197/144
TCDL 10.0		Lumber DOL 1.15		BC 0.90		Vert(CT) -0.45 11-12 >530 240		M18SHS	197/144
BCLL 0.0 *		Rep Stress Incr YES		WB 0.91		Horz(CT) 0.08 16 n/a n/a			
BCDL 10.0		Code IRC2018/TPI2014		Matrix-S		Wind(LL) 0.09 17-18 >999 240		Weight: 167 lb	FT = 10%

LUMBER-		BRACING-	
TOP CHORD	2x4 SPF No.2	TOP CHORD	Structural wood sheathing directly applied or 5-11-8 oc purlins, except end verticals.
BOT CHORD	2x4 SPF No.2 *Except* 4-16, 6-13; 2x3 SPF No.2	BOT CHORD	Rigid ceiling directly applied or 4-2-13 oc bracing.
WEBS	2x3 SPF No.2 *Except* 1-19: 2x6 SPF No.2	WEBS	1 Row at midpt 5-15, 5-14, 7-13, 9-11

REACTIONS. All bearings 0-2-0 except (jt=length) 13=0-2-1 (input: 0-2-0), 16=0-2-5 (input: 0-2-0), 19=0-3-8, 11=Mechanical.

(lb) - Max Horz 19=255(LC 6)

Max Uplift All uplift 100 lb or less at joint(s) 19 except 13=-253(LC 9), 11=-151(LC 9), 16=-223(LC 8)

Max Grav All reactions 250 lb or less at joint(s) except 19=395(LC 16), 13=1314(LC 16), 11=854(LC 24), 16=1474(LC 15)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 1-2=-845/261, 2-3=-168/330, 3-4=-82/510, 4-5=-48/536, 5-6=-103/252, 6-7=-49/266,
7-8=-918/154, 8-9=-904/170, 1-19=-522/154

BOT CHORD 18-19=-367/904, 17-18=-347/812, 15-16=-861/55, 13-14=-573/163, 6-14=-414/239,
12-13=-172/778, 11-12=-185/823

WEBS 2-18=-38/408, 2-17=-876/318, 3-17=-26/379, 3-16=-692/227, 5-15=-561/4,
7-13=-1100/247, 8-12=-72/645, 9-11=-930/187, 9-12=-305/163

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) All plates are MT20 plates unless otherwise indicated.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) WARNING: Required bearing size at joint(s) 13, 16 greater than input bearing size.
- 8) Refer to girder(s) for truss to truss connections.
- 9) Bearing at joint(s) 19, 16 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 19 except (jt=lb) 13=253, 11=151, 16=223.
- 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021



WARNING – verify design parameters and READ NOTES ON THIS AND INCLUDED WELDER REFERENCE PAGE MH-1413 (Rev. 3/25/2020) BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for the building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2671 Crain Highway, Suite 203 Waldorf, MD 20601.



16023 Swingley Ridge Rd
Chesterfield, MO 63017




Plate Offsets (X,Y)--		[1:0-1-2,0-1-11], [8:0-5-4,0-3-4], [9:Edge,0-3-8], [10:0-3-8,0-6-0]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.71
TCDL 10.0	Lumber DOL	1.15	BC 0.79
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.98
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S
		DEFL.	in (loc) l/defl L/d
		Vert(LL)	-0.22 6-8 >999 360
		Vert(CT)	-0.38 6-8 >616 240
		Horz(CT)	0.05 6 n/a n/a
		Wind(LL)	0.10 6-8 >999 240
		PLATES	MT20
		GRIP	197/144
		Weight:	300 lb
		FT =	10%

LUMBER-		BRACING-	
TOP CHORD	2x4 SPF 2100F 1.8E *Except* 4-5: 2x4 SPF No.2	TOP CHORD	Structural wood sheathing directly applied or 4-10-2 oc purlins, except end verticals.
BOT CHORD	2x8 SP DSS *Except* 3-9: 2x4 SPF No.2, 6-8: 2x8 SP 2400F 2.0E	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS	2x4 SPF No.2	WEBS	6-0-0 oc bracing: 9-10. 1 Row at midpt 4-6
WEDGE			
Left: 2x4 SP No.3			

REACTIONS. (size) 1=(0-3-8 + bearing block) (req. 0-5-0), 6=(0-3-8 + bearing block) (req. 0-5-3)
Max Horz 1=328(LC 26)
Max Uplift 1=-429(LC 8), 6=-273(LC 8)
Max Grav 1=6386(LC 2), 6=6649(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-9131/460, 2-3=-6352/311, 3-4=-6363/430
BOT CHORD 1-10=-502/7638, 8-9=0/979, 3-8=-315/191, 6-8=-134/1962
WEBS 2-10=-188/2776, 8-10=-451/7957, 2-8=-2627/319, 4-8=-449/7992, 4-6=-4596/235

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-7-0 oc.
Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-5-0 oc, 2x4 - 1 row at 0-9-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - 2x8 SP DSS bearing block 12" long at jt. 1 attached to each face with 4 rows of 10d (0.131"x3") nails spaced 3" o.c. 16 Total fasteners per block. Bearing is assumed to be SPF No.2.
 - 2x8 SP 2400F 2.0E bearing block 12" long at jt. 6 attached to each face with 4 rows of 10d (0.131"x3") nails spaced 3" o.c. 16 Total fasteners per block. Bearing is assumed to be SPF No.2.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=429, 6=273.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEES SUMMIT, MISSOURI 04/06/2021
210322	D6	ROOF SPECIAL GIRDER	1	2	Job Reference (optional)	
Wheeler Lumber, Waverly, KS - 66871,						8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN
NOTES-						ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-NIAGhk7K6?wCUnWrfu6mwCt0XCvV9clumLi_dQzcxHs
11) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1281 lb down and 167 lb up at 2-0-0, 1256 lb down and 163 lb up at 4-0-0, 1255 lb down and 27 lb up at 6-0-0, 1260 lb down and 27 lb up at 8-0-0, 1219 lb down and 25 lb up at 10-0-0, 1279 lb down and 27 lb up at 12-0-0, 1267 lb down and 27 lb up at 14-0-0, and 1258 lb down and 27 lb up at 16-0-0, and 1283 lb down and 27 lb up at 18-0-0 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.						

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-70, 4-5=-70, 1-9=-20, 6-8=-20

Concentrated Loads (lb)

Vert: 12=-1217(B) 13=-1220(B) 14=-1217(B) 15=-1217(B) 16=-1219(B) 17=-1219(B) 19=-1219(B) 20=-1219(B) 22=-1219(B)





Plate Offsets (X,Y)--		[1:0-5-8,Edge], [2:0-4-1,0-2-0]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.77
TCDL 10.0	Lumber DOL	1.15	BC 0.87
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.67
BCDL 10.0	Code	IRC2018/TPI2014	Matrix-S
			DEFL. in (loc) l/defl L/d
			Vert(LL) -0.23 6-7 >999 360
			Vert(CT) -0.46 6-7 >513 240
			Horz(CT) 0.41 6 n/a n/a
			Wind(LL) 0.08 7-8 >999 240
			PLATES MT20 GRIP 197/144
			Weight: 87 lb FT = 10%

LUMBER-		BRACING-	
TOP CHORD	2x4 SPF No.2	TOP CHORD	Structural wood sheathing directly applied or 5-9-9 oc purlins, except end verticals.
BOT CHORD	2x4 SPF No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x3 SPF No.2	WEBS	1 Row at midpt 2-8, 4-6
OTHERS	2x4 SPF No.2		

REACTIONS. (size) 6=Mechanical, 10=0-3-0
Max Horz 10=-210(LC 4)
Max Uplift 6=-140(LC 9), 10=-187(LC 9)
Max Grav 6=888(LC 1), 10=864(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 8-9=-89/706, 1-9=-89/706, 2-3=-929/135, 3-4=-920/151
BOT CHORD 7-8=-131/931, 6-7=-168/895
WEBS 2-8=-1080/240, 2-7=-277/71, 3-7=-53/668, 4-6=-1015/168, 4-7=-300/165, 1-10=-866/188

- NOTES-**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Provide adequate drainage to prevent water ponding.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Refer to girder(s) for truss to truss connections.
 - 6) Bearing at joint(s) 10 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 6=140, 10=187.
 - 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




March 9,2021

**RELEASE FOR
CONSTRUCTION**
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEADS SUMMARY SHEET

04/06/2021


21-6-8
0-10-8



REACTIONS. All bearings 20-8-0.
(lb) - Max Horz 2=-82(LC 13)
Max Uplift All uplift 100 lb or less at joint(s) 2, 20, 21, 22, 23, 18, 16, 15, 14, 12
Max Grav All reactions 250 lb or less at joint(s) 2, 19, 20, 21, 22, 23, 18, 16, 15, 14, 12

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCFL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 20, 21, 22, 23, 18, 16, 15, 14, 12.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601.



Job 210322	Truss E2	Truss Type Common	Qty 4	Ply 1	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021
Wheeler Lumber, Waverly, KS - 66871,		8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN ID:dwZTNcNXrqfJm8trCSIY7DzStnz-otsPKI9COWnLEFQK0fTYrVanQZ7MAeKSJwfDlzcXHp				
0-10-8 0-10-8		6-3-3 6-3-3		10-4-0 4-0-13		14-4-13 4-0-13
						20-8-0 6-3-3
						21-6-8 0-10-8
						Scale = 1:35.9



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	25.0	Plate Grip DOL	1.15	TC	0.52	Vert(LL)	-0.11 6-9 >999 360	MT20		197/144	
TCDL	10.0	Lumber DOL	1.15	BC	0.60	Vert(CT)	-0.25 6-9 >977 240				
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.17	Horz(CT)	0.04 6 n/a n/a				
BCDL	10.0	Code IRC2018/TPI2014		Matrix-S		Wind(LL)	0.06 2-10 >999 240				
								Weight: 65 lb		FT = 10%	

LUMBER-
 TOP CHORD 2x4 SPF No.2
 BOT CHORD 2x4 SPF No.2
 WEBS 2x3 SPF No.2
 WEDGE
 Left: 2x3 SPF No.2 , Right: 2x3 SPF No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 3-8-13 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 2=0-3-8, 6=0-3-8
 Max Horz 2=-82(LC 9)
 Max Uplift 2=-141(LC 8), 6=-141(LC 9)
 Max Grav 2=988(LC 1), 6=988(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1643/210, 3-4=-1437/214, 4-5=-1437/214, 5-6=-1643/211
 BOT CHORD 2-10=-199/1413, 9-10=-56/1021, 6-9=-117/1413
 WEBS 4-9=-107/507, 5-9=-339/190, 4-10=-107/507, 3-10=-339/190

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=141, 6=141.
 - 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021

Job

210322

Truss

E3

Truss Type

COMMON GIRDER

Qty

1

Ply

3

Lot 89 MN

Job Reference (optional)

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

Wheeler Lumber,

Waverly, KS - 66871,

ID:dwZTNcNXrqlJm8tRCSiY7DzSTnz-G3QnX5Aq9DQeyQgcukAi521kcqws5b?UhzgCmBzcXHo

14-4-13

4-0-13

20-8-0

6-3-3

21-6-8

0-10-8

0-10-8

6-3-3

10-4-0

4-0-13

14-4-13

4-0-13

20-8-0

6-3-3

21-6-8

0-10-8

RELEASE FOR CONSTRUCTION


AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

LEE'S SUMMIT, MISSOURI

04/06/2021

Scale = 1:35.9



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.58	Vert(LL)	-0.14	6-9	>999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.57	Vert(CT)	-0.26	6-9	>949		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.29	Horz(CT)	0.04	6	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S	Wind(LL)	0.11	2-10	>999	Weight: 282 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2

BOT CHORD 2x6 SP 2400F 2.0E

WEBS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 2=0-3-8, 6=0-3-8
Max Horz 2=-49(LC 28)
Max Uplift 2=-849(LC 8), 6=-647(LC 9)
Max Grav 2=5446(LC 1), 6=4872(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-8457/1312, 3-4=-8286/1323, 4-5=-8330/1215, 5-6=-8500/1204
BOT CHORD 2-10=-1188/7646, 9-10=-817/5846, 6-9=-1039/7684
WEBS 4-9=-470/3594, 4-10=-670/3569

- NOTES-**
- 3-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-7-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-5-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=849, 6=647.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 873 lb down and 154 lb up at 0-7-4, 834 lb down and 171 lb up at 2-7-4, 834 lb down and 171 lb up at 4-7-4, 834 lb down and 171 lb up at 6-7-4, 834 lb down and 171 lb up at 8-7-4, 812 lb down and 196 lb up at 10-7-4, 850 lb down and 123 lb up at 12-7-4, 850 lb down and 123 lb up at 14-7-4, and 850 lb down and 123 lb up at 16-7-4, and 850 lb down and 123 lb up at 18-7-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

Continued on page 2



March 9,2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN
210322	E3	COMMON GIRDER	1	3	

Wheeler Lumber, Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-G3QnX5Aq9DQeyOqcukAi521kcqws5b?UhzgCmBzcXHo

RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
04/06/2021

J45104209

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-70, 4-7=-70, 2-6=-20

Concentrated Loads (lb)

Vert: 11=-873(F) 12=-819(F) 13=-819(F) 14=-819(F) 15=-819(F) 16=-793(F) 17=-850(F) 18=-850(F) 19=-850(F) 20=-850(F)

 **WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
Chesterfield, MO 63017

**RELEASE FOR
CONSTRUCTION**
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
J45104210
LBN'S SUBM21 MISS GRI
wXYVaYPoSrhxdGa02DNMq6rdvdPllczcxHn
04/06/2021
Scale = 1:12



Weight: 11 lb FT = 10%

TOP CHORD	Structural wood sheathing directly applied or 4-1-7 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

WARNING: Velly design parameters are READ NOTES ON THIS AND INCLUDED WITH REFERENCE PAGE MM-1475 (Rev. 3/25/2020) BEFORE USE. Design valid for use only with MITEK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



Job

210322

Truss

J2

Truss Type

Jack-Open

Qty

5

Ply

1

Lot 89 MN

Job Reference (optional)

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

04/06/2021

Scale = 1:13.7

0-10-8

0-10-8

3-0-0

3-0-0

6.00

12

2-2-0

0-8-0

1-9-5

2-2-0

3-0-0

3-0-0

3x6

II

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.10	Vert(LL)	-0.00	4-5	>999	360	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.06	Vert(CT)	-0.01	4-5	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-R	Wind(LL)	0.00	4-5	>999	240	Weight: 9 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 3-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SPF No.2	

REACTIONS. (size) 5=0-3-8, 3=Mechanical, 4=Mechanical
 Max Horz 5=69(LC 8)
 Max Uplift 5=-27(LC 8), 3=-49(LC 8)
 Max Grav 5=210(LC 1), 3=82(LC 1), 4=52(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 4) Refer to girder(s) for truss to truss connections.
 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 3.
 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

Job

210322

Truss

J3

Truss Type

Jack-Open Girder

Qty

1

Ply

1

Lot 89 MN

Job Reference (optional)

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-CSXXynB5hrgLCiz?09DAAT7BodjdZZ5n8H9Jq4zcXhm

4-1-7

4-1-7

RELEASE FOR CONSTRUCTION


AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

LEE'S SUMMIT, MISSOURI

04/06/2021

Scale = 1:13.4



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.15	Vert(LL)	-0.01	5-6	>999	360	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.10	Vert(CT)	-0.02	5-6	>999	240		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-R	Wind(LL)	0.01	5-6	>999	240	Weight: 12 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 4-1-7 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SPF No.2	

REACTIONS. (size) 6=0-3-7, 3=Mechanical, 4=Mechanical
Max Horz 6=80(LC 12)
Max Uplift 6=90(LC 6), 3=51(LC 12)
Max Grav 6=144(LC 1), 3=80(LC 1), 4=60(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Bearing at joint(s) 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 3.
 - 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 8) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 30 lb down and 11 lb up at -1-2-14, and 30 lb down and 11 lb up at -1-2-14 on top chord. The design/selection of such connection device(s) is the responsibility of others.
 - 9) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Concentrated Loads (lb)

Vert: 1=-46(F=-23, B=23)

Trapezoidal Loads (plf)

Vert: 1=0(F=35, B=35)-to-2=-24(F=23, B=23), 2=-3(F=34, B=34)-to-3=-72(F=-1, B=-1), 6=0(F=10, B=10)-to-5=-19(F=1, B=1), 5=-19(F=1, B=1)-to-4=-21(F=-0, B=-0)



March 9, 2021

Job

210322

Truss

J4

Truss Type

Jack-Open

Qty

5

Ply

1

Lot 89 MN

Job Reference (optional)

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

ID:dwZTNcNXrqlJm8tRCSiY7DzSTnz-ge5w97CjS8oCpsYBZskPjhNL14UI0LwNxusMWzcXHI

45104213

RELEASE FOR

CONSTRUCTION


AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

LEE'S SUMMIT, MISSOURI

04/06/2021

Scale = 1:13.7




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.10	Vert(LL)	-0.00	5-6	>999	360	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.06	Vert(CT)	-0.01	5-6	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-R	Wind(LL)	0.00	5-6	>999	240	Weight: 9 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 3-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SPF No.2	

REACTIONS. (size) 6=0-3-8, 3=Mechanical, 4=Mechanical
Max Horz 6=68(LC 8)
Max Uplift 6=26(LC 8), 3=50(LC 8)
Max Grav 6=210(LC 1), 3=83(LC 1), 4=52(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Bearing at joint(s) 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 3.
 - 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021

Job

210322

Truss

LAY1

Truss Type

GABLE

Qty

1

Ply

1

Lot 89 MN

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

Page 1

ID:dwZTNcNXrqlJm8tRCSiY7DzSTnz-ge5w97CjS8oCpsYBZskPjhfO0145I0swNxusMWzcXHI

7-9-15


3-11-0

Job Reference (optional)

LEE'S SUMMER MISSOURI

04/06/2021

Scale = 1:29.3



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.06	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.02	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P						Weight: 29 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SPF No.2	

REACTIONS. All bearings 7-9-15.
 (lb) - Max Horz 1=-108(LC 4)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 8=-154(LC 8), 6=-154(LC 9)
 Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7, 8, 6

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=154, 6=154.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




March 9,2021

RELEASE FOR CONSTRUCTION

AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

J45104215
RE: S.W. 8TH ST. & MISSION BLVD.
D/SW3R?7N7AFeFuCYJRQ?7T93bbePvzcZxHk
04/06/2021




BRACING-	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 2-8.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCFL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8, 10, 15, 14, 13, 12, 11, 9.
- 8) Non Standard bearing condition. Review required.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



March 9, 2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN
210322	LAY3	GABLE	1	1	

Wheeler Lumber, Waverly, KS - 66871,

Job Reference (optional)

8.430 s Feb 12 2021 MiTek Industries, Inc. For M... 165501

ID:dwZTNcNXrqfJm8tRCSIY7DzSTnz-d0DgapEz_m2w39iahHmto6ljvql6mvsDqFNzRPzcxHj

RELEASE FOR

CONSTRUCTION

AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

LEE'S SUMMIT, MISSOURI

04/06/2021

145104216

Page 1

Scale = 1:56.0




Plate Offsets (X,Y)--		[5:0-2-10,Edge], [9:0-0-10,0-1-8]							
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL	25.0	Plate Grip DOL	1.15	TC	0.09	in (loc)	l/defl	MT20	GRIP
TCDL	10.0	Lumber DOL	1.15	BC	0.05	n/a	-		197/144
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.13	Vert(CT)	n/a		
BCDL	10.0	Code IRC2018/TPI2014		Matrix-S		Horz(CT)	-0.01 9	Weight: 67 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals, and 2'-0" oc purlins (6'-0" max.): 5-9.
BOT CHORD Rigid ceiling directly applied or 6'-0" oc bracing.

REACTIONS.

All bearings 12-7-13.
(lb) - Max Horz 17=281(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 17, 12, 11, 10 except 9=280(LC 8), 14=-136(LC 6), 16=-197(LC 8), 15=-139(LC 8), 13=-136(LC 8)
Max Grav All reactions 250 lb or less at joint(s) 17, 9, 16, 15, 13, 12, 11, 10 except 14=306(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 4-5=-186/337, 5-6=-129/261, 6-7=-129/261, 7-8=-129/261, 8-9=-129/263
BOT CHORD 16-17=-263/127, 15-16=-263/127, 14-15=-263/127, 13-14=-407/208, 12-13=-403/207, 11-12=-403/206, 10-11=-404/206, 9-10=-401/196

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-6" tall by 2'-0" wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 17, 12, 11, 10 except (jt=lb) 9=280, 14=136, 16=197, 15=139, 13=136.
- Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 9, 13, 12, 11, 10.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



March 9,2021



16023 Swingley Ridge Rd
Chesterfield, MO 63017





Plate Offsets (X,Y)--		[4:0-2-10,Edge], [8:0-0-10,0-1-8]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.05
TCDL 10.0	Lumber DOL	1.15	BC 0.03
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.06
BCDL 10.0	Code	IRC2018/TPI2014	Matrix-S
			DEFL.
			in (loc) l/defl L/d
			Vert(LL) n/a - n/a 999
			Vert(CT) n/a - n/a 999
			Horz(CT) -0.00 8 n/a n/a
			PLATES GRIP
			MT20 197/144
			Weight: 46 lb FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except
BOT CHORD 2x4 SPF No.2	2-0-0 oc purlins (6-0-0 max.): 4-8.
OTHERS 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 10-11-8.
(lb) - Max Horz 1=225(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 1, 8, 11, 12, 10, 9 except 14=-117(LC 8), 13=-142(LC 8)
Max Grav All reactions 250 lb or less at joint(s) 1, 8, 11, 14, 13, 12, 10, 9

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 8, 11, 12, 10, 9 except (jt=lb) 14=117, 13=142.
 - Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 8, 10, 9.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



March 9,2021

Job

210322

Truss

V1

Truss Type

Valley

Qty

1

Ply

1

Lot 89 MN

Job Reference (optional)

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

ID:dwZTNcNXrqfJm8tRCSiy7DzSTnz-ZPLQ?UFDWNlelTsyoiolTq4zeRvEqKWIZs4VHzcxHh

45104218

RELEASE FOR

CONSTRUCTION


AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

LEE'S SUMMIT, MISSOURI

04/06/2021

Scale = 1:9.3



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.06	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.03	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P						Weight: 6 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
 BOT CHORD 2x4 SPF No.2
 WEBS 2x3 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-7-4 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 1=2-6-12, 3=2-6-12
 Max Horz 1=39(LC 5)
 Max Uplift 1=11(LC 8), 3=21(LC 8)
 Max Grav 1=84(LC 1), 3=84(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd
 Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021
210322	V3	Valley	1	1		
Wheeler Lumber, Waverly, KS - 66871,					Job Reference (optional)	

8.430 s Feb 12 2021 MiTek Industries, Inc. Not for construction

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-KyqSgEEdqJVFiTVGNxDCD9Nps846Rjh7ooVoqzcxHZ

Scale = 1:14.0



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.26	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.14	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P						Weight: 11 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2

BOT CHORD 2x4 SPF No.2

WEBS 2x3 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-5-12 oc purlins, except end verticals.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=4-5-4, 3=4-5-4

Max Horz 1=78(LC 5)


Max Uplift 1=22(LC 8), 3=41(LC 8)

Max Grav 1=169(LC 1), 3=169(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN
210322	V4	Valley	1	1	


Wheeler Lumber, Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

ID:dwZTNcNXrfJm8tRCSiY7DzSTnz-KyqSgELEdqJVfITVGNxDCD9R4sAr6Rjh7ooVoqzcXHZ

**RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES**
J45104221
LEE'S SUMMIT, MISSOURI
04/06/2021

Scale = 1:9.0



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.05	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.03	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P					Weight: 6 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-5-12 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

(size) 1=2-5-4, 3=2-5-4
Max Horz 1=37(LC 5)
Max Uplift 1=10(LC 8), 3=19(LC 8)
Max Grav 1=79(LC 1), 3=79(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**
Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
Chesterfield, MO 63017

Job

210322

Truss

V4A

Truss Type

GABLE

Qty

1

Ply

1

Lot 89 MN

Job Reference (optional)

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

RELEASE FOR

CONSTRUCTION

AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

LEES SUMMIT, MISSOURI

04/06/2021


J45104222

Wheeler Lumber,

Waverly, KS - 66871,

ID:dwZTNcNXrQJm8tRCSiY7DzSTnz-o8OquZMt08RMtr2hq5TSkQiaRGWbrugqMSY2KGzcxHY

Scale = 1:30.0



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.14	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.06	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.06	Horz(CT)	-0.00	7	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S						Weight: 47 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2

BOT CHORD 2x4 SPF No.2

WEBS 2x4 SPF No.2

OTHERS 2x4 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 11-11-6.

(lb) - Max Horz 1=233(LC 5)

Max Uplift All uplift 100 lb or less at joint(s) 7, 11, 10, 9, 8

Max Grav All reactions 250 lb or less at joint(s) 1, 7, 10, 9, 8 except 11=283(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 11, 10, 9, 8.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021
210322	V5	Valley	1	1		
Wheeler Lumber, Waverly, KS - 66871,					Job Reference (optional)	

8.430 s Feb 12 2021 MiTek Industries, Inc. Not for construction

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-GKx5vNV9SZDV?dtOo_hHeEiFgq1aKU_b6HbsizcxHX

Scale = 1:28.8



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.33	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.17	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.09	Horz(CT)	-0.00	4	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S					Weight: 28 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
 BOT CHORD 2x4 SPF No.2
 WEBS 2x3 SPF No.2
 OTHERS 2x3 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 1=9-7-12, 4=9-7-12, 5=9-7-12
 Max Horz 1=187(LC 5)
 Max Uplift 4=-28(LC 5), 5=-152(LC 8)
 Max Grav 1=183(LC 1), 4=117(LC 1), 5=506(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-5=-383/203

NOTES-

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4 except (jt=lb) 5=152.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
 Chesterfield, MO 63017

Job

210322

Truss

V6

Truss Type

Valley

Qty

1

Ply

1

Lot 89 MN

Job Reference (optional)

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

ID:dwZTNcNXrfJm8tRCSiY7DzSTnz-GKxC5vNV9SZDV?dtOo_hHeEkJgr8aL__b6HbsizcxHX

45104224

RELEASE FOR

CONSTRUCTION


AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

LEE'S SUMMIT, MISSOURI

04/06/2021

Scale = 1:22.4




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.19	Vert(LL)	n/a	-	n/a	999	MT20
BCDL 10.0	Lumber DOL	1.15	BC 0.10	Vert(CT)	n/a	-	n/a	999	197/144
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.05	Horz(CT)	-0.00	4	n/a	n/a	
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P						
								Weight: 20 lb	FT = 10%

LUMBER-		BRACING-	
TOP CHORD	2x4 SPF No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SPF No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x3 SPF No.2		
OTHERS	2x3 SPF No.2		

REACTIONS. (size) 1=7-3-12, 4=7-3-12, 5=7-3-12
Max Horz 1=138(LC 5)
Max Uplift 4=-26(LC 8), 5=-115(LC 8)
Max Grav 1=87(LC 16), 4=141(LC 1), 5=382(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-5=-297/165


- NOTES-**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Gable requires continuous bottom chord bearing.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4 except (jt=lb) 5=115.
 - 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021
210322	V7	Valley	1	1		
Wheeler Lumber, Waverly, KS - 66871,					Job Reference (optional)	

8.430 s Feb 12 2021 MiTek Industries, Inc. 16023 Swingley Ridge Rd Chesterfield, MO 63017
 ID: dwZTNcNXrqJm8tRCSiY7DzSTnz-kXVaJFO7wlh469C3yVWwprmtg491Jo37pm19O9zcxHW




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.35	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.19	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P					Weight: 13 lb	FT = 10%

LUMBER-		BRACING-	
TOP CHORD 2x4 SPF No.2		TOP CHORD	Structural wood sheathing directly applied or 5-0-4 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2		BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x3 SPF No.2			

REACTIONS.	(size) 1=4-11-12, 3=4-11-12
	Max Horz 1=89(LC 7)
	Max Uplift 1=25(LC 8), 3=47(LC 8)
	Max Grav 1=193(LC 1), 3=193(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
----------------	--

- NOTES-**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Gable requires continuous bottom chord bearing.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN
210322	V8	Valley	1	1	


Wheeler Lumber, Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

ID:dwZTNcNXrqiJm8tRCSIY7DzSTnz-kXVaJFO7vH469C3yWVwpmY54BQJo37pm19O9zcXHW

RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI
04/06/2021

Scale = 1:9.5



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.03	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P					Weight: 6 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
 BOT CHORD 2x4 SPF No.2
 WEBS 2x3 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-8-4 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 1=2-7-12, 3=2-7-12
 Max Horz 1=41(LC 5)
 Max Uplift 1=11(LC 8), 3=22(LC 8)
 Max Grav 1=88(LC 1), 3=88(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**
Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
 Chesterfield, MO 63017

Job

210322

Truss

V9

Truss Type

Valley

Qty

1

Ply

1

Lot 89 MN

Job Reference (optional)

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-Cj3zWbOlh3pxkJnGVD09M3K50UWs2FmH2QmixbzcxHV

7-4-14

3-8-7

RELEASE FOR CONSTRUCTION


AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

LEE'S SUMMIT, MISSOURI

04/06/2021

Scale = 1:15.4



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.18	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.09	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P						Weight: 18 lb	FT = 10%

LUMBER-		BRACING-	
TOP CHORD 2x4 SPF No.2		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SPF No.2		BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x3 SPF No.2			

REACTIONS. (size) 1=7-4-0, 3=7-4-0, 4=7-4-0
Max Horz 1=-48(LC 6)
Max Uplift 1=-35(LC 8), 3=-41(LC 9)
Max Grav 1=154(LC 1), 3=154(LC 1), 4=261(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021

Job 210322	Truss V10	Truss Type Valley	Qty 1	Ply 1	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021
Wheeler Lumber, Waverly, KS - 66871,		8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN ID:dwZTNcNXrfJm8tRCSIY7DzSTnz-ZPLQ?UFDWNleTsyoiLtXq4LeQ3EqKWIZs4VHzcxHh				




Plate Offsets (X,Y)-- [2:0-2-0,Edge]		3-11-11		3-11-5	
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	PLATES
TCLL 25.0	Plate Grip DOL	1.15	TC 0.03	in (loc) l/defl L/d	MT20
TCDL 10.0	Lumber DOL	1.15	BC 0.08	Vert(LL) n/a - n/a 999	GRIP 197/144
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Vert(CT) n/a - n/a 999	
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P	Horz(CT) 0.00 3 n/a n/a	Weight: 8 lb FT = 10%

LUMBER-
 TOP CHORD 2x4 SPF No.2
 BOT CHORD 2x4 SPF No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 3-11-11 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=3-10-14, 3=3-10-14
 Max Horz 1=-22(LC 4)
 Max Uplift 1=-16(LC 8), 3=-16(LC 9)
 Max Grav 1=130(LC 1), 3=130(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

MiTek
 16023 Swingley Ridge Rd
 Chesterfield, MO 63017

Job

210322

Truss

V11

Truss Type

Valley

Qty

1

Ply

1

Lot 89 MN

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

ID:dwZTNcNXrqfJm8tRCSIY7DzSTnz-1bvoCqGrHhRVwdR8MPJaQkN7V2jzfzHaFWDcd2kzcXHg

7-7-2021

Job Reference (optional)

Lee's Summit, Missouri

RELEASE FOR CONSTRUCTION

AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

04/06/2021

Scale = 1:14.1





Plate Offsets (X,Y)--		[3:0-3-3,Edge], [4:Edge,0-2-8]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.52
TCDL 10.0	Lumber DOL	1.15	BC 0.32
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00
BCDL 10.0	Code	IRC2018/TPI2014	Matrix-R
			DEFL.
			in (loc) l/defl L/d
			Vert(LL) n/a - n/a 999
			Vert(CT) n/a - n/a 999
			Horz(CT) 0.00 4 n/a n/a
			PLATES GRIP
			MT20 197/144
			Weight: 17 lb FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x3 SPF No.2	

REACTIONS.	(size) 1=7-6-0, 4=7-6-0
	Max Horz 1=60(LC 5)
	Max Uplift 1=-48(LC 4), 4=-54(LC 8)
	Max Grav 1=272(LC 1), 4=272(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Gable requires continuous bottom chord bearing.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 4.
 - 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021 Scale = 1:17.3
210322	V12	Valley	1	1		
Wheeler Lumber, Waverly, KS - 66871,						

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

ID:dwZTNcNXrqfJm8tRCSiy7DzSTnz-1bvoCqGrHhRVwdR8MPJaQkN2E2FfzHaFWDcd2kzcxHg

04/06/2021





Plate Offsets (X,Y)--		[2:0-6-2,Edge], [4:Edge,0-1-8]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 25.0	Plate Grip DOL	1.15	TC 0.86
TCDL 10.0	Lumber DOL	1.15	BC 0.52
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00
BCDL 10.0	Code	IRC2018/TPI2014	Matrix-R
DEFL.	in (loc)	l/defl	L/d
Vert(LL)	n/a	-	n/a 999
Vert(CT)	n/a	-	n/a 999
Horz(CT)	0.00	4	n/a n/a
PLATES	GRIP		
MT20	197/144		
M18SHS	197/144		
Weight: 22 lb	FT = 10%		

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 2-4-4 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SPF No.2	

REACTIONS.	(size) 1=9-3-10, 4=9-3-10
	Max Horz 1=76(LC 5)
	Max Uplift 1=-62(LC 4), 4=-70(LC 8)
	Max Grav 1=351(LC 1), 4=351(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-269/43

- NOTES-**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 4.
 - 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




March 9,2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES
210322	V13	Valley	1	1		145104231

Wheeler Lumber, Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc. Job Reference (optional) LEE'S SUMMIT, MISSOURI
ID:dwZTNcNXrqJm8tRCSIY7DzSTnz-VoSBQAHU2_ZMXn0Lw7rpyyvO9S75ikoplLAAzcHf



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.08	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.05	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	4	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-R					Weight: 8 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-11-13 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 1=3-10-10, 4=3-10-10
Max Horz 1=27(LC 5)
Max Uplift 1=19(LC 4), 4=22(LC 8)
Max Grav 1=109(LC 1), 4=109(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 4.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**
Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
Chesterfield, MO 63017


Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021
210322	V14	Valley	1	1		
Wheeler Lumber, Waverly, KS - 66871,					Job Reference (optional)	

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN 8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN 8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

ID:dwZTNcNXrfJm8tRCSiY7DzSTnz-z_OZdWH6plhD9wbXUqM2V9SYurSuRA4y_X5k6czcxHe

3-6-15
3-6-15

Scale = 1:11.8



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.14	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.08	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P					Weight: 9 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-6-15 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 1=3-6-7, 3=3-6-7
Max Horz 1=59(LC 5)
Max Uplift 1=-16(LC 8), 3=-31(LC 8)
Max Grav 1=128(LC 1), 3=128(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**
Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
Chesterfield, MO 63017

**RELEASE FOR
CONSTRUCTION**
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEF'S 50102233
Missouri
s, Inc. 50102233 Missouri page 1
wxbUqM2V9SW?rRsRA4y_X5k6czcxHe
04/06/2021



A circular blue seal for a Professional Engineer in the State of Kansas. The outer ring contains the text "JUAN GARCIA" at the top and "PROFESSIONAL ENGINEER" at the bottom. Inside this ring, the word "LICENSED" is at the top and "KANSAS" is at the bottom. In the center of the seal, the license number "16952" is printed in blue. A red ink signature is written over the license number and the word "KANSAS".

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Components**.

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601.



16023 Swingley Ridge Rd
Chesterfield, MO 63017

Job

210322

Truss

V16

Truss Type

Valley

Qty

1

Ply

1

Lot 89 MN

Job Reference (optional)

Wheeler Lumber,

Waverly, KS - 66871,

8.430 s Feb 12 2021 MiTek Industries, Inc.

Lot 89 MN

ID:dwZTNcNXrqJm8tRCSiY7DzSTnz-RAaxrsIkZcp4n4Aj1YtH1N_gxFl7AdK5CAqHe3zcxHd

Lee's Summit, Missouri

04/06/2021


Scale = 1:16.3

RELEASE FOR CONSTRUCTION

AS NOTED ON PLANS REVIEW

DEVELOPMENT SERVICES

04/06/2021




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.38	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.20	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P					Weight: 13 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 5-2-6 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x3 SPF No.2	

REACTIONS.	(size) 1=5-1-14, 3=5-1-14
Max Horz	1=93(LC 5)
Max Uplift	1=-26(LC 8), 3=-49(LC 8)
Max Grav	1=201(LC 1), 3=201(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
---------	--


- NOTES-**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Gable requires continuous bottom chord bearing.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021
210322	V17	Valley	1	1		
Wheeler Lumber, Waverly, KS - 66871,					Job Reference (optional)	

8.430 s Feb 12 2021 MiTek Industries, Inc. 145104235
ID:dwZTNcNXrfJm8tRCSIY7DzSTnz-RAaxrskZcp4n4Aj1YtH1N_dnFkzAdK5CAqHe3zcXhd




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.52	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.28	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P					Weight: 15 lb	FT = 10%

LUMBER-		BRACING-	
TOP CHORD	2x4 SPF No.2	TOP CHORD	Structural wood sheathing directly applied or 5-10-10 oc purlins, except end verticals.
BOT CHORD	2x4 SPF No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x3 SPF No.2		

REACTIONS.	(size) 1=5-10-2, 3=5-10-2
	Max Horz 1=107(LC 5)
	Max Uplift 1=30(LC 8), 3=57(LC 8)
	Max Grav 1=232(LC 1), 3=232(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
----------------	--

- NOTES-**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Gable requires continuous bottom chord bearing.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

Job

210322

Truss

V18

Truss Type

GABLE

Qty

1

Ply

1

Lot 89 MN

Job Reference (optional)

8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

Wheeler Lumber,

Waverly, KS - 66871,

ID:dwZTNcNXrqfJm8tRCSiY7DzSTnz-vN8J2CJMkvxxOEkwbfOWaaXujf7Rv44FRqarBVzcxHc

6-3-14

6-3-14

RELEASE FOR

CONSTRUCTION

AS NOTED ON PLANS REVIEW


DEVELOPMENT SERVICES

LEES SUMMIT, MISSOURI

04/06/2021

145104236

Scale = 1:20.4




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.15	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.07	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.03	Horz(CT)	-0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P						Weight: 21 lb	FT = 10%

LUMBER-		BRACING-	
TOP CHORD 2x4 SPF No.2		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2		BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x3 SPF No.2			
OTHERS 2x4 SPF No.2			

REACTIONS.	(size) 1=6-3-14, 5=6-3-14, 6=6-3-14
	Max Horz 1=117(LC 5)
	Max Uplift 5=-23(LC 5), 6=-94(LC 8)
	Max Grav 1=122(LC 1), 5=62(LC 1), 6=316(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 6.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9,2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021
210322	V19	Valley	1	1		
Wheeler Lumber, Waverly, KS - 66871,					Job Reference (optional)	

8.430 s Feb 12 2021 MiTek Industries, Inc. 16023 Swingley Ridge Rd Chesterfield, MO 63017
ID:dwZTNcNXrfJm8tRCSiY7DzSTnz-OZihGYK_5D3o0OJ69zvi7o43S3TDeX00gUJOjxcxHb



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.19	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.10	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.05	Horz(CT)	-0.00	4	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P						Weight: 18 lb	FT = 10%

LUMBER-	BRACING-
TOP CHORD 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x3 SPF No.2	
OTHERS 2x3 SPF No.2	

REACTIONS. (size) 1=7-1-0, 4=7-1-0, 5=7-1-0
Max Horz 1=115(LC 5)
Max Uplift 4=-27(LC 8), 5=-98(LC 8)
Max Grav 1=62(LC 16), 4=142(LC 1), 5=370(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-5=-288/148

- NOTES-**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Gable requires continuous bottom chord bearing.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 5.
 - 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




March 9,2021

Job	Truss	Truss Type	Qty	Ply	Lot 89 MN	RELEASE FOR CONSTRUCTION AS NOTED ON PLANS REVIEW DEVELOPMENT SERVICES LEE'S SUMMIT, MISSOURI 04/06/2021
210322	V20	Valley	1	1		

Wheeler Lumber, Waverly, KS - 66871, 8.430 s Feb 12 2021 MiTek Industries, Inc. Lot 89 MN

ID:dwZTNcNXrqJm8tRCSIY7DzSTnz-sIG4TulcsXBeeYuljgQ_f?cDhTpAN_3Yv83xFOzcHa

Scale = 1:11.8



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 25.0	Plate Grip DOL	1.15	TC 0.22	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.12	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	3	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-P					Weight: 10 lb	FT = 10%

LUMBER-

TOP CHORD 2x4 SPF No.2
 BOT CHORD 2x4 SPF No.2
 WEBS 2x3 SPF No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-4-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

(size) 1=4-3-6, 3=4-3-6
 Max Horz 1=64(LC 5)
 Max Uplift 1=23(LC 8), 3=36(LC 8)
 Max Grav 1=156(LC 1), 3=156(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



March 9, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**
Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd
 Chesterfield, MO 63017

Symbols

RELEASE FOR
CONSTRUCTION
AS NOTED ON PLANS REVIEW
DEVELOPMENT SERVICES
LEE'S SUMMIT, MISSOURI



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.

For 4 x 2 orientation, locate plates 0- 3/8" from outside edge of truss.

This symbol indicates the required direction of slots in connector plates.

* Plate location details available in MitTek 20120 software or upon request.

PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

Industry Standards:

ANSI/TP1.1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-89: Design Standard for Bracing.
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses.

Numbering System

6-4-8 dimensions shown in ft-in-sixteenths (Drawings not to scale)



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MitTek® All Rights Reserved



MitTek Engineering Reference Sheet: MII-7473 rev. 5/19/2020



General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.