

VAN DEURZEN AND ASSOCIATES, P.A.

CONSULTING STRUCTURAL ENGINEERS 11011 KING STREET, SUITE 130 COMMERCE TERRACE BUILDING D OVERLAND PARK, KANSAS 66210 (913) 451 - 6305 FAX (913) 451 - 1021

Address or Project Na	ime	City	Inspector		Date		Time	
1000 CM/ Div.o	» Dum D»	Laala Cumamait	Dah Dawa		7/0/20	21	11.16	
1808 SW River Run Dr Lee's Summit			Bob Rowe Contractor		7/8/2021 11:10 General/Owner			
PRRES 2021 2025			PTM JFE					
Inspection Type	023	Bill Topp						
Pier		JFE						
Areas Inspected			Current Temp	nt Temp 24 hr High 24 hr Low				
			00					
			80					
Site Conditions	(all must comply if a	pplicable)	Slab (Basement	or Garage A	s Marke	d)		
_	ved plot plan and buil	Formed & Reinforced Per City Approved Dwgs						
plans on si	•	Suspended floor slab (over usable space)						
_ '	ntrol is in place and fu	Garage structural slab per approved plan						
	e performed if erosior	Basement structural slab per approved plan.						
	y in compliance with t	-	6 mil vapor barrier installed – not required for garage					
requireme	•	= -	slab					
	tbacks per approved ¡		Isolation rings or block-outs are provided over pier pads					
	ring capacity as deter	for columns						
	= : :	<u> </u>	-		alled wh	ara rani	uired metal	
Bearing on undisturbed soil @ 1,500 psfSoils report (comment or attach report)Footings							anca metai	
=	er engineering report		Reinforced	oor city ann	round al	anc		
_	of organic material	<u> </u>	•		-	a115.		
Cold weath	•	Deck/porch/balcony piers Footing – width, depth and location						
	·		Solid jumps					
	on Certification	•						
_	levation Certification"		Frost depth (min. 36 inches)					
contractor has been reviewed for completeness and allowable tolerances.				Column pads – basement				
			Column pads – basement structural slab					
	efer to footings for de	_	Column pads – garage steel column					
Pier foundation per approved plan			_	Column/pad at garage structural slab				
Quantity: 44 - addition of 2 Size: 18"			•	Undermined fdn elements (recommendation in				
Size:	,	comments and/or attached report) Ufer Ground attachment rod provided						
Depth:	5-9'		•	d attachmer	it rod pro	ovided		
Bearing:	sandstone shale		Location:					
C								
Comments							1	
Approved	house piers.							
				-managanana-]	
This is to certif	fy that I, or qualified individua	als working under my directio	n, milital	OF MIS	100000000			
•		litems in accordance with the		Toonsononsonoo				
	r approved building and site park is complete and to the be		dto LA	CHAD	VOR BER STOP			
	•	st of my knowledge was foun oved plans and specifications	E Ji			1		
				ankenie	TA Ame	The state of the s		

Signed

Date 7/8/2021

ad M. Streeter