



RELEASE FOR  
CONSTRUCTION  
AS NOTED ON PLANS REVIEW  
Development Services  
LEE'S SUMMIT, MISSOURI

RE: 210529  
Lot 71 RR

MiTek USA, Inc.  
16023 Swingley Ridge Rd  
Chesterfield, MO 63017  
314-434-1200

**Site Information:**

Customer: Project Name: 210529  
Lot/Block:  
Address:  
City:

Model:  
Subdivision:  
State:

**General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):**

Design Code: IRC2018/TPI2014  
Wind Code: ASCE 7 - 16[Low Rise]  
Roof Load: 45.0 psf


Design Program: MiTek 20/20 8.4  
Wind Speed: 115 mph  
Floor Load: N/A psf

This package includes 81 individual, dated Truss Design Drawings and 0 Additional Drawings.

No.	Seal#	Truss Name	Date	No.	Seal#	Truss Name	Date
1	I47674077	A3	8/30/2021	21	I47674097	E3	8/30/2021
2	I47674078	A4	8/30/2021	22	I47674098	E4	8/30/2021
3	I47674079	A5	8/30/2021	23	I47674099	E5	8/30/2021
4	I47674080	B1	8/30/2021	24	I47674100	G1	8/30/2021
5	I47674081	B2	8/30/2021	25	I47674101	G2	8/30/2021
6	I47674082	B3	8/30/2021	26	I47674102	G3	8/30/2021
7	I47674083	C1	8/30/2021	27	I47674103	G4	8/30/2021
8	I47674084	C2	8/30/2021	28	I47674104	G5	8/30/2021
9	I47674085	C3	8/30/2021	29	I47674105	G6	8/30/2021
10	I47674086	C4	8/30/2021	30	I47674106	G7	8/30/2021
11	I47674087	C5	8/30/2021	31	I47674107	G8	8/30/2021
12	I47674088	C6	8/30/2021	32	I47674108	H1	8/30/2021
13	I47674089	C7	8/30/2021	33	I47674109	H2	8/30/2021
14	I47674090	D1	8/30/2021	34	I47674110	H3	8/30/2021
15	I47674091	D2	8/30/2021	35	I47674111	H4	8/30/2021
16	I47674092	D3	8/30/2021	36	I47674112	H5	8/30/2021
17	I47674093	D4	8/30/2021	37	I47674113	J4	8/30/2021
18	I47674094	D5	8/30/2021	38	I47674114	J5	8/30/2021
19	I47674095	E1	8/30/2021	39	I47674115	J6	8/30/2021
20	I47674096	E2	8/30/2021	40	I47674116	J7	8/30/2021

The truss drawing(s) referenced above have been prepared by  
MiTek USA, Inc. under my direct supervision  
based on the parameters provided by Wheeler - Waverly.  
Truss Design Engineer's Name: Garcia, Juan  
My license renewal date for the state of Kansas is April 30, 2022.  
Kansas COA: E-943

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek. Any project specific information included is for MiTek customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.





RE: 210529 - Lot 71 RR

MiTek USA, Inc.  
16023 Swingley Ridge Rd  
Chesterfield, MO 63017  
314-434-1200

**Site Information:**

Project Customer:      Project Name: 210529

Lot/Block:

Subdivision:

Address:

City, County:

State:

No.	Seal#	Truss Name	Date
41	I47674117	J8	8/30/2021
42	I47674118	J9	8/30/2021
43	I47674119	J10	8/30/2021
44	I47674120	J11	8/30/2021
45	I47674121	J12	8/30/2021
46	I47674122	J13	8/30/2021
47	I47674123	J14	8/30/2021
48	I47674124	J15	8/30/2021
49	I47674125	J16	8/30/2021
50	I47674126	J17	8/30/2021
51	I47674127	J18	8/30/2021
52	I47674128	J19	8/30/2021
53	I47674129	J20	8/30/2021
54	I47674130	J21	8/30/2021
55	I47674131	J22	8/30/2021
56	I47674132	J23	8/30/2021
57	I47674133	J24	8/30/2021
58	I47674134	J25	8/30/2021
59	I47674135	J26	8/30/2021
60	I47674136	J27	8/30/2021
61	I47674137	J28	8/30/2021
62	I47674138	J29	8/30/2021
63	I47674139	J30	8/30/2021
64	I47674140	J31	8/30/2021
65	I47674141	J32	8/30/2021
66	I47674142	J33	8/30/2021
67	I47674143	J34	8/30/2021
68	I47674144	J35	8/30/2021
69	I47674145	J36	8/30/2021
70	I47674146	J37	8/30/2021
71	I47674147	J38	8/30/2021
72	I47674148	K1	8/30/2021
73	I47674149	LAY1	8/30/2021
74	I47674150	LAY2	8/30/2021
75	I47674151	LAY3	8/30/2021
76	I47674152	LAY4	8/30/2021
77	I47674153	LAY5	8/30/2021
78	I47674154	LAY6	8/30/2021
79	I47674155	LAY7	8/30/2021
80	I47674156	LAY8	8/30/2021
81	I47674157	LAY9	8/30/2021



RE: 210529  
Lot 71 RR

MiTek USA, Inc.  
16023 Swingley Ridge Rd  
Chesterfield, MO 63017  
314-434-1200

**Site Information:**

Customer: Project Name: 210529  
Lot/Block:  
Address:  
City:

Model:  
Subdivision:  
State:

**General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):**

Design Code: IRC2018/TPI2014  
Wind Code: ASCE 7 - 16[Low Rise]  
Roof Load: 45.0 psf

Design Program: MiTek 20/20 8.4  
Wind Speed: 115 mph  
Floor Load: N/A psf

This package includes 81 individual, dated Truss Design Drawings and 0 Additional Drawings.

No.	Seal#	Truss Name	Date	No.	Seal#	Truss Name	Date
1	I47674077	A3	8/30/2021	21	I47674097	E3	8/30/2021
2	I47674078	A4	8/30/2021	22	I47674098	E4	8/30/2021
3	I47674079	A5	8/30/2021	23	I47674099	E5	8/30/2021
4	I47674080	B1	8/30/2021	24	I47674100	G1	8/30/2021
5	I47674081	B2	8/30/2021	25	I47674101	G2	8/30/2021
6	I47674082	B3	8/30/2021	26	I47674102	G3	8/30/2021
7	I47674083	C1	8/30/2021	27	I47674103	G4	8/30/2021
8	I47674084	C2	8/30/2021	28	I47674104	G5	8/30/2021
9	I47674085	C3	8/30/2021	29	I47674105	G6	8/30/2021
10	I47674086	C4	8/30/2021	30	I47674106	G7	8/30/2021
11	I47674087	C5	8/30/2021	31	I47674107	G8	8/30/2021
12	I47674088	C6	8/30/2021	32	I47674108	H1	8/30/2021
13	I47674089	C7	8/30/2021	33	I47674109	H2	8/30/2021
14	I47674090	D1	8/30/2021	34	I47674110	H3	8/30/2021
15	I47674091	D2	8/30/2021	35	I47674111	H4	8/30/2021
16	I47674092	D3	8/30/2021	36	I47674112	H5	8/30/2021
17	I47674093	D4	8/30/2021	37	I47674113	J4	8/30/2021
18	I47674094	D5	8/30/2021	38	I47674114	J5	8/30/2021
19	I47674095	E1	8/30/2021	39	I47674115	J6	8/30/2021
20	I47674096	E2	8/30/2021	40	I47674116	J7	8/30/2021


The truss drawing(s) referenced above have been prepared by  
MiTek USA, Inc. under my direct supervision  
based on the parameters provided by Wheeler - Waverly.

Truss Design Engineer's Name: Garcia, Juan


My license renewal date for the state of Missouri is December 31, 2022.

Missouri COA: 001193

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek. Any project specific information included is for MiTek customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.



August 30, 2021



RE: 210529 - Lot 71 RR

MiTek USA, Inc.  
16023 Swingley Ridge Rd  
Chesterfield, MO 63017  
314-434-1200

**Site Information:**

Project Customer:      Project Name: 210529

Lot/Block:

Subdivision:

Address:

City, County:

State:


No.	Seal#	Truss Name	Date
41	I47674117	J8	8/30/2021
42	I47674118	J9	8/30/2021
43	I47674119	J10	8/30/2021
44	I47674120	J11	8/30/2021
45	I47674121	J12	8/30/2021
46	I47674122	J13	8/30/2021
47	I47674123	J14	8/30/2021
48	I47674124	J15	8/30/2021
49	I47674125	J16	8/30/2021
50	I47674126	J17	8/30/2021
51	I47674127	J18	8/30/2021
52	I47674128	J19	8/30/2021
53	I47674129	J20	8/30/2021
54	I47674130	J21	8/30/2021
55	I47674131	J22	8/30/2021
56	I47674132	J23	8/30/2021
57	I47674133	J24	8/30/2021
58	I47674134	J25	8/30/2021
59	I47674135	J26	8/30/2021
60	I47674136	J27	8/30/2021
61	I47674137	J28	8/30/2021
62	I47674138	J29	8/30/2021
63	I47674139	J30	8/30/2021
64	I47674140	J31	8/30/2021
65	I47674141	J32	8/30/2021
66	I47674142	J33	8/30/2021
67	I47674143	J34	8/30/2021
68	I47674144	J35	8/30/2021
69	I47674145	J36	8/30/2021
70	I47674146	J37	8/30/2021
71	I47674147	J38	8/30/2021
72	I47674148	K1	8/30/2021
73	I47674149	LAY1	8/30/2021
74	I47674150	LAY2	8/30/2021
75	I47674151	LAY3	8/30/2021
76	I47674152	LAY4	8/30/2021
77	I47674153	LAY5	8/30/2021
78	I47674154	LAY6	8/30/2021
79	I47674155	LAY7	8/30/2021
80	I47674156	LAY8	8/30/2021
81	I47674157	LAY9	8/30/2021

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	A3	Hip Girder	1	1	Job Reference (optional)	I47674077

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:14  
ID: 94jkrHqc3i50wMLL9rDh1yjc5-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRCDoi7J4zJC7f

Page: 1



Scale = 1:36

Plate Offsets (X, Y): [8:Edge,0-5-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.83	Vert(LL)	-0.16	9-10	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.73	Vert(CT)	-0.36	9-10	>452	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.29	Horz(CT)	0.03	8	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.10	9-10	>999	240	Weight: 46 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 11-2,8-6:2x6 SP DSS

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 4-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (5-10-9 max.): 3-5.
BOT CHORD	Rigid ceiling directly applied or 8-11-14 oc bracing.

REACTIONS	(lb/size) 8=743/0-3-8, 11=743/0-3-8
	Max Horiz 11=17 (LC 7)
	Max Uplift 8=199 (LC 5), 11=199 (LC 4)

FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/30, 2-3=-1064/250, 3-4=-892/235, 4-5=-892/236, 5-6=-1064/250, 6-7=0/30, 2-11=-674/167, 6-8=-674/167
BOT CHORD	10-11=-191/908, 9-10=-421/1414, 8-9=-186/908

WEBS	3-10=0/354, 5-9=0/354, 4-9=-576/251, 4-10=-576/251
------	--

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 199 lb uplift at joint 11 and 199 lb uplift at joint 8.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 89 lb down and 138 lb up at 3-0-0, and 89 lb down and 138 lb up at 11-0-0 on top chord, and 30 lb down at 3-0-0, and 30 lb down at 10-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 3-5=-70, 5-6=-70, 6-7=-70, 8-11=-20  
Concentrated Loads (lb)  
Vert: 3=-13 (F), 5=-13 (F), 10=-10 (F), 9=-10 (F), 4=-13 (F), 12=-13 (F), 13=-13 (F), 14=-10 (F), 15=-10 (F), 16=-10 (F)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	A4	Hip	1	1	Job Reference (optional)	I47674078

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:16  
ID:wdCmWaOrWly\_9zupq\_60jyjhcz-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:31.7

Plate Offsets (X, Y): [7:Edge,0-5-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.57	Vert(LL)	-0.06	8-9	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.40	Vert(CT)	-0.12	8-9	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.02	7	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.04	8-9	>999	240	Weight: 44 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x3 SPF No.2 \*Except\* 10-2,7-5:2x6 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 5-3-6 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-4.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** (lb/size) 7=687/0-3-8, 10=687/0-3-8  
Max Horiz 10=-24 (LC 13)  
Max Uplift 7=-92 (LC 5), 10=-92 (LC 4)

**FORCES** (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/30, 2-3=-897/106, 3-4=-750/116, 4-5=-898/105, 5-6=0/30, 2-10=-610/119, 5-7=-610/119

BOT CHORD 9-10=-45/753, 8-9=-47/750, 7-8=-46/753  
WEBS 3-9=0/159, 3-8=-98/98, 4-8=0/159

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 92 lb uplift at joint 10 and 92 lb uplift at joint 7.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	147674079
210529	A5	Common	4	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:17  
ID:ChMD7ciAHfkObA4nesPoDyz1ktF-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?fi

Page: 1



Scale = 1:32.7

Plate Offsets (X, Y): [6:Edge,0-5-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.61	Vert(LL)	-0.05	6-7	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.36	Vert(CT)	-0.10	6-7	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.09	Horz(CT)	0.01	6	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.02	7-8	>999	240	Weight: 39 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x6 SPF No.2 \*Except\* 7-3:2x3 SPF No.2

6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 5-8-5 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 6=687/0-3-8, 8=687/0-3-8  
Max Horiz 8=-39 (LC 9)  
Max Uplift 6=-103 (LC 9), 8=-103 (LC 8)

#### FORCES

(lb) - Maximum Compression/Maximum Tension  
TOP CHORD 1-2=0/30, 2-3=-819/104, 3-4=-819/104, 4-5=0/30, 2-8=-622/150, 4-6=-622/150  
BOT CHORD 7-8=-31/660, 6-7=-31/660  
WEBS 3-7=0/284

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0"-0" tall by 2'-0"-0" wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 103 lb uplift at joint 8 and 103 lb uplift at joint 6.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Page: 1

16023 Swingley Ridge Rd  
Chesterfield, MO 63017



Wheeler Lumber, Waverly, KS - 66871, Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:17 Page: 1  
ID:5k79XnyLK6NPdPBpNmHiaNz1ksw-RfC?PsB70Hg3NSqPanL8w3uITXbGKWrCDoi7J4zJC?f



<b>LUMBER</b>			
TOP CHORD	2x4 SPF No.2		6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 202 lb uplift at joint 10 and 202 lb uplift at joint 7.
BOT CHORD	2x4 SPF No.2		7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
WEBS	2x3 SPF No.2 *Except* 10-2,7-5:2x6 SPF No.2		8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
<b>BRACING</b>			
TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (5-8-5 max.): 3-4		


**REACTIONS** (lb/size) 7=802/0-3-8, 10=802/0-3-8  
 Max Horiz 10=-17 (LC 19)  
 Max Uplift 7=-202 (LC 5), 10=-202 (LC 4)

FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/47, 2-3=-930/139, 3-4=-802/153, 4-5=-930/139, 5-6=0/47, 2-10=-690/222, 5-7=-690/222

BOT CHORD 9-10=-73/803, 8-9=-76/802, 7-8=-58/803  
WEBS 3-9=0/153, 3-8=-87/87, 4-8=-5/153

## NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.



August 30, 2021



**WARNING:** - verify design parameters and READ NOTES ON THIS AND INCLUDED MITER REFERENCE PAGE MM1/473 (rev. 3/19/2020) BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674082
210529	B3	Common	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:18  
ID:N42o?A2khGGQyUD9HkvMMsz1ksp-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:32

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.83	Vert(LL)	-0.17	6-7	>972	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.69	Vert(CT)	-0.35	6-7	>474	240	M18SHS	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.07	Horz(CT)	0.01	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.10	6-7	>999	240	Weight: 39 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF 2100F 1.8E \*Except\* 6-3:2x3 SPF No.2

8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 5-2-7 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 5=606/ Mechanical, 7=769/0-3-8  
Max Horiz 7=42 (LC 8)  
Max Uplift 5=-86 (LC 5), 7=-183 (LC 4)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/45, 2-3=-767/107, 3-4=-754/108, 4-5=-483/118, 2-7=-666/226  
BOT CHORD 6-7=-53/633, 5-6=-53/633  
WEBS 3-6=0/230

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 183 lb uplift at joint 7 and 86 lb uplift at joint 5.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	C1	Hip Girder	1	1	Job Reference (optional)	I47674083

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:18  
ID:nUWW5iRJ?OVHV2Yb?J1ATpz1kuu-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRCDoi7J4zJC?f

Page: 1



Scale = 1:43.5

Plate Offsets (X, Y): [2:0-2-15,0-2-0], [8:0-2-8,0-2-0], [10:0-2-8,0-2-0]												
<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.55	Vert(LL)	-0.11	9	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.67	Vert(CT)	-0.22	8-9	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.64	Horz(CT)	0.04	7	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.10	9	>999	240	Weight: 74 lb	FT = 10%

<b>LUMBER</b>	
TOP CHORD	2x4 SPF No.2 *Except* 3-5:2x4 SPF 2100F 1.8E
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 11-2,7-6:2x4 SPF No.2
<b>BRACING</b>	
TOP CHORD	Structural wood sheathing directly applied or 4-0-2 oc purlins, except end verticals, and 2-0-0 oc purlins (3-11-13 max.): 3-5.
BOT CHORD	Rigid ceiling directly applied or 8-10-12 oc bracing.
<b>REACTIONS</b> (lb/size)	
	7=1452/ Mechanical, 11=1608/0-3-8
	Max Horiz 11=62 (LC 7)
	Max Uplift 7=321 (LC 5), 11=385 (LC 4)
<b>FORCES</b> (lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/54, 2-3=1952/469, 3-4=2911/727, 4-5=2911/727, 5-6=1981/467, 2-11=1583/395, 6-7=1425/330
BOT CHORD	10-11=50/31, 9-10=431/1770, 8-9=430/1804, 7-8=31/62
WEBS	3-10=249/159, 3-9=307/1284, 4-9=808/390, 5-9=301/1261, 5-8=244/163, 2-10=412/1849, 6-8=421/1828

- NOTES**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 385 lb uplift at joint 11 and 321 lb uplift at joint 7.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 201 lb down and 55 lb up at 4-0-0, and 201 lb down and 55 lb up at 15-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 3-5=-70, 5-6=-70, 7-11=-20  
Concentrated Loads (lb)  
Vert: 3=-80 (F), 5=-80 (F), 10=-197 (F), 9=-38 (F), 4=-80 (F), 8=-197 (F), 12=-80 (F), 13=-80 (F), 14=-80 (F), 15=-80 (F), 16=-38 (F), 17=-38 (F), 18=-38 (F), 19=-38 (F)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	C2	Roof Special Girder	1	2	Job Reference (optional)	I47674084

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:18  
ID:krRzmKjsVTJtG5VwZVwVdgz1krx-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:62.1

Plate Offsets (X, Y): [4:0-4-8,0-1-15], [5:0-6-0,0-2-4], [10:Edge,0-6-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.65	Vert(LL)	-0.32	11-12	>999	360	MT20 197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.98	Vert(CT)	-0.58	11-12	>617	240	M18SHS 197/144
BCLL	0.0*	Rep Stress Incr	NO	WB	0.56	Horz(CT)	0.06	10	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.26	11-12	>999	240	Weight: 281 lb FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2 \*Except\* 3-4,5-7:2x4 SPF

2100F 1.8E

BOT CHORD 2x6 SPF No.2 \*Except\* 13-10:2x6 SPF

1650F 1.4E

WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 5-3-6 oc purlins, except end verticals, and 2-0-0 oc purlins (5-2-5 max.): 3-4, 5-7.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 10=2623/0-3-8, 16=1923/0-3-8

Max Horiz 16=39 (LC 9)

Max Uplift 10=581 (LC 5), 16=303 (LC 4)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/54, 2-3=-2805/472, 3-4=-4536/862,

4-5=-4995/916, 5-6=-9472/1776,

6-7=-4734/914, 7-8=-5127/958, 8-9=0/45,

2-16=-1871/327, 8-10=-2680/594

BOT CHORD 15-16=-74/143, 14-15=-341/2538,

12-14=-1708/9503, 11-12=-1534/7822,

10-11=-67/323

WEBS 3-15=-322/163, 3-14=-441/2252,

4-14=-180/1429, 5-14=-5469/1083,

5-12=-210/575, 7-11=-152/1288,

2-15=-349/2439, 8-11=-841/4579,

6-12=-183/1802, 6-11=-3382/760


#### NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-7-0 oc.  
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.

- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 303 lb uplift at joint 16 and 581 lb uplift at joint 10.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Use Simpson Strong-Tie HUS26 (14-10d Girder, 4-10d Truss) or equivalent at 20-0-12 from the left end to connect truss(es) to front face of bottom chord.
- Use Simpson Strong-Tie LTHJA26 (LTHJA26 on 2 ply, Right Hand Hip) or equivalent at 25-11-10 from the left end to connect truss(es) to front face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.
- "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.

#### LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 3-4=-70, 4-5=-70, 5-7=-70, 7-8=-70, 8-9=-70, 10-16=-20  
Concentrated Loads (lb)  
Vert: 7=-80 (F), 11=-197 (F), 6=-80 (F), 17=-80 (F), 18=-1077 (F), 19=-38 (F), 20=-38 (F)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	C3	Roof Special	1	1	Job Reference (optional)	I47674085

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:19  
ID: \_Cex3H3UMZljV8UGZJPWd4z1kqC-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1






Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	C4	Roof Special	1	1	Job Reference (optional)	I47674086

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:19  
ID:jlPHZaQk\_\_PqxM2n7qQnAhz1koS-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:63

Plate Offsets (X, Y): [2:0-3-0,0-1-12], [5:0-6-0,0-2-3], [9:Edge,0-7-8], [10:0-2-8,0-2-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.87	Vert(LL)	-0.22	10-11	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.70	Vert(CT)	-0.42	10-11	>850	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.71	Horz(CT)	0.06	9	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.16	10-11	>999	240	Weight: 114 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2 *Except* 5-6,6-8:2x4 SPF 2100F 1.8E
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 14-2,9-7:2x4 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 2-8-9 oc purlins, except end verticals, and 2-0-0 oc purlins (2-2-0 max.): 5-6.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS

(lb/size) 9=1478/0-3-8, 14=1478/0-3-8  
Max Horiz 14=67 (LC 13)  
Max Uplift 9=290 (LC 5), 14=172 (LC 8)

#### FORCES

TOP CHORD	(lb) - Maximum Compression/Maximum Tension 1-2=0/54, 2-3=-1996/239, 3-4=-1947/282, 4-5=-3305/541, 5-6=-3025/455, 6-7=-2591/392, 7-8=0/45, 2-14=-1409/210, 7-9=-1400/330
BOT CHORD	13-14=-107/211, 11-13=-81/1617, 10-11=-294/2374, 9-10=-145/544
WEBS	5-11=-1702/384, 6-11=-80/715, 6-10=-23/196, 7-10=-146/1838, 4-11=-371/2055, 4-13=-135/423, 3-13=-402/216, 2-13=-122/1561

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 172 lb uplift at joint 14 and 290 lb uplift at joint 9.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674087
210529	C5	Roof Special	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:20  
ID:0Sz2t1XSJF?nzV4TW93Mu5z1kn0-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRcDoi7J4zJC?i

Page: 1



Scale = 1:63

Plate Offsets (X, Y): [2:0-2-15,0-2-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.69	Vert(LL)	-0.25	13-14	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.83	Vert(CT)	-0.45	10-11	>788	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.61	Horz(CT)	0.07	10	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.12	11-13	>999	240	Weight: 115 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2 *Except* 5-6:2x4 SPF 2100F 1.8E
BOT CHORD	2x4 SPF No.2 *Except* 12-10:2x4 SPF 2100F 1.8E
WEBS	2x3 SPF No.2 *Except* 15-2,10-8:2x4 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 2-7-11 oc purlins, except end verticals, and 2-0-0 oc purlins (3-10-7 max.): 5-6.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	1 Row at midpt 7-10
REACTIONS	(lb/size) 10=1478/0-3-8, 15=1478/0-3-8 Max Horiz 15=67 (LC 9) Max Uplift 10=297 (LC 5), 15=172 (LC 8) Max Grav 10=1501 (LC 2), 15=1512 (LC 2)

#### FORCES

	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/54, 2-3=-1984/199, 3-4=-1985/257, 4-5=-2842/446, 5-6=-2608/378, 6-7=-2540/377, 7-8=-336/0, 8-9=0/45, 2-15=-1458/189, 8-10=-347/118
BOT CHORD	14-15=-56/99, 13-14=-83/1686, 11-13=-245/2363, 10-11=-367/2175
WEBS	4-13=-284/1771, 5-13=-1409/324, 6-13=-75/287, 6-11=0/289, 7-11=0/241, 2-14=-119/1790, 7-10=-2219/500, 3-14=-357/192, 4-14=-115/271

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 172 lb uplift at joint 15 and 297 lb uplift at joint 10.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674088
210529	C6	Roof Special	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:20  
ID: VS6jnp933DYOCU3SZ4?Z?3z1kmC-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:59.6

Plate Offsets (X, Y): [9:Edge,0-7-8], [10:0-2-8,0-2-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.93	Vert(LL)	-0.14	10-11	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.64	Vert(CT)	-0.28	11-13	>999	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.71	Horz(CT)	0.06	9	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.11	10-11	>999	240	Weight: 115 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x3 SPF No.2 \*Except\* 15-1,9-7:2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 3-2-12 oc purlins, except end verticals, and 2-0-0 oc purlins (2-2-0 max.): 4-5.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** (lb/size) 9=1468/0-3-8, 15=1317/  
Mechanical  
Max Horiz 15=-82 (LC 9)  
Max Uplift 9=-302 (LC 5), 15=-128 (LC 5)

**FORCES** (lb) - Maximum Compression/Maximum Tension  
TOP CHORD 1-2=-1773/209, 2-3=-1793/273,  
3-4=-2186/372, 4-5=-1992/324,  
5-6=-2216/372, 6-7=-2519/402, 7-8=0/45,  
1-15=-1274/147, 7-9=-1397/332  
BOT CHORD 14-15=-33/114, 13-14=-72/1590,  
11-13=-207/2041, 10-11=-317/2322,  
9-10=-49/284  
WEBS 2-14=-369/196, 3-14=-197/196,  
3-13=-251/1397, 4-13=-1175/280,  
5-13=-192/106, 5-11=0/336, 6-11=-339/122,  
6-10=-159/115, 1-14=-144/1591,  
7-10=-297/2054

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 128 lb uplift at joint 15 and 302 lb uplift at joint 9.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



16023 Swingley Ridge Rd  
Chesterfield, MO 63017






Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674090
210529	D1	Hip Girder	1	2	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:21  
ID:qT5\_qmX7sIdqJERIU9Exmz1jql-RfC?PsB70Hq3NSgPqnL8w3uTXbGKWrCDoi7J4zJC7f

Page: 1



Scale = 1:62.7

Plate Offsets (X, Y): [3:0-3-2,Edge], [8:0-3-2,Edge], [9:0-1-12,0-1-12], [17:0-3-8,0-2-0], [18:Edge,0-5-5]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.91	Vert(LL)	-0.30	14	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.51	Vert(CT)	-0.55	14-16	>687	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.52	Horz(CT)	0.08	11	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.27	14	>999	240	Weight: 253 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2 *Except* 3-6:2x4 SPF 2100F 1.8E
BOT CHORD	2x4 SPF 2100F 1.8E
WEBS	2x4 SPF No.2 *Except* 11-9,18-2:2x3 SPF No.2
OTHERS	2x3 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (3-10-14 max.): 3-8.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 11-12.

REACTIONS	(lb/size) 11=2293/0-5-8, 18=2384/0-3-8
	Max Horiz 18=64 (LC 7)
	Max Uplift 11=509 (LC 4), 18=454 (LC 5)

FORCES	(lb) - Maximum Compression/Maximum Tension
--------	--

TOP CHORD	1-2=0/31, 2-3=-3842/783, 3-4=-6848/1474, 4-5=-6845/1472, 5-7=-6299/1400, 7-8=-6302/1402, 8-9=-2644/643, 9-10=0/62, 9-11=-2302/508, 2-18=-2349/459
BOT CHORD	17-18=-87/259, 16-17=-705/3408, 14-16=-1649/7749, 13-14=-1649/7749, 12-13=-543/2392, 11-12=-26/20
WEBS	3-17=-110/125, 3-16=-827/3739, 4-16=-799/361, 5-16=-996/235, 5-14=0/419, 5-13=-1564/309, 7-13=-785/356, 8-13=-881/4219, 8-12=-765/184, 9-12=-579/2550, 2-17=-636/3186

#### NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc, 2x3 - 1 row at 0-9-0 oc.  
Bottom chords connected as follows: 2x4 - 1 row at 0-9-0 oc.  
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 454 lb uplift at joint 18 and 509 lb uplift at joint 11.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Use Simpson Strong-Tie TJC37 (4 nail, 30-90) or equivalent at 3-11-8 from the left end to connect truss (es) to front face of bottom chord, skewed 33.7 deg.to the left, sloping 0.0 deg. down.
- Use Simpson Strong-Tie TJC37 (4 nail 90-150) or equivalent at 28-7-8 from the left end to connect truss (es) to front face of bottom chord, skewed 33.7 deg.to the right, sloping 0.0 deg. down.
- Fill all nail holes where hanger is in contact with lumber.
- "NAILED" indicates 3x10d (0.148"x3") or 3-12d (0.148"x3.25") toe nails per NDS guidelines.

#### LOAD CASE(S) - Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 3-8=-70, 8-9=-70, 9-10=-70, 11-18=-20  
Concentrated Loads (lb)  
Vert: 17=-224 (F), 7-8-83 (F), 13=85 (F), 12=7 (F), 19=83 (F), 20=83 (F), 21=83 (F), 22=83 (F), 23=83 (F), 24=83 (F), 25=83 (F), 26=83 (F), 27=83 (F), 28=83 (F), 29=83 (F), 30=35 (F), 31=35 (F), 32=35 (F), 33=35 (F), 34=35 (F), 35=35 (F), 36=35 (F), 37=35 (F), 38=35 (F), 39=35 (F), 40=35 (F)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	D2	Hip	1	1	Job Reference (optional)	I47674091

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:22  
ID:UsxEd7Vl0tITvWY7AygI0pz1jp5-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?i

Page: 1



Scale = 1:62.7

Plate Offsets (X, Y): [7:0-4-13,Edge], [8:0-2-15,0-2-0], [11:0-2-8,0-1-8], [12:0-2-8,0-1-8], [15:0-2-8,0-1-8], [16:Edge,0-5-13]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.77	Vert(LL)	-0.27	12-14	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.93	Vert(CT)	-0.52	12-14	>722	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.68	Horz(CT)	0.09	10	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.21	12-14	>999	240	Weight: 114 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2 \*Except\* 3-6-6-7:2x4 SPF 2100F 1.8E  
BOT CHORD 2x4 SPF No.2  
WEBS 2x3 SPF No.2 \*Except\* 10-8,16-2:2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 3-6-6 oc purlins, except end verticals, and 2-0-0 oc purlins (3-1-13 max.): 3-7.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 2-2-0 oc bracing: 12-14.

**REACTIONS** (lb/size) 10=1553/0-5-8, 16=1476/0-3-8  
Max Horiz 16=73 (LC 7)  
Max Uplift 10=202 (LC 4), 16=185 (LC 5)

**FORCES** (lb) - Maximum Compression/Maximum Tension  
TOP CHORD 1-2=0/32, 2-3=-2292/340, 3-4=-3559/624, 4-5=-3557/622, 5-7=-3444/607, 7-8=-1882/295, 8-9=0/63, 8-10=-1524/215, 2-16=-1427/206  
BOT CHORD 15-16=-128/371, 14-15=-297/1984, 12-14=-564/3444, 11-12=-208/1644, 10-11=-8/30  
WEBS 3-15=-67/127, 3-14=-361/1772, 4-14=-573/231, 5-14=-31/148, 5-12=-633/244, 7-12=-386/1988, 7-11=-313/137, 8-11=-234/1677, 2-15=-241/1622

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 185 lb uplift at joint 16 and 202 lb uplift at joint 10.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	D3	Hip	1	1	Job Reference (optional)	I47674092

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:22  
ID:jtV340pcutan1WX7IQ8o3lz1joh-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:62.8

Plate Offsets (X, Y): [3:0-4-8,0-1-11], [7:0-3-0,0-1-12], [14:Edge,0-5-13]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.73	Vert(LL)	-0.21	10-11	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.99	Vert(CT)	-0.49	11-13	>766	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.68	Horz(CT)	0.10	9	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.15	11-13	>999	240	Weight: 113 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x3 SPF No.2 \*Except\* 9-7:2x4 SPF No.2,  
14-2:2x4 SPF 2100F 1.8E

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
3-0-7 oc purlins, except end verticals, and  
2-0-0 oc purlins (2-7-11 max.): 3-6.

BOT CHORD Rigid ceiling directly applied or 2-2-0 oc  
bracing.

WEBS 1 Row at midpt 4-13, 5-10

REACTIONS (lb/size) 9=1553/0-5-8, 14=1476/0-3-8  
Max Horiz 14=82 (LC 7)  
Max Uplift 9=176 (LC 4), 14=161 (LC 5)

FORCES (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 1-2=0/32, 2-3=-2292/301, 3-4=-1940/292,  
4-5=-2929/431, 5-6=-1685/263,  
6-7=-1984/272, 7-8=0/63, 7-9=-1513/194,  
2-14=-1420/188

BOT CHORD 13-14=-227/573, 11-13=-466/2876,  
10-11=-439/2784, 9-10=-47/107

WEBS 3-13=-31/631, 4-13=-1173/298, 4-11=0/243,  
5-11=0/329, 5-10=-1334/314, 6-10=-23/541,  
7-10=-191/1622, 2-13=-184/1452

#### NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 161 lb uplift at joint 14 and 176 lb uplift at joint 9.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see


ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Wheeler Lumber, Waverly, KS - 66871, Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:22 Page: 1  
ID:UqWWWKZ6l0YjEXMxwfA4faZz1jol-RfC?PsB70Hg3NSqPqnL8w3ulTXbGKWrCDoi7J4zJC?f



<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	-0.15	11	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.76	Vert(CT)	-0.31	10-11	>999	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.51	Horz(CT)	0.08	9	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.11	11	>999	240	Weight: 117 lb	FT = 10%

TOP CHORD	2x4 SPF 2100F 1.8E *Except* 3-6:2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 9-7:2x4 SPF No.2, 14-2:2x6 SPF No.2

TOP CHORD	Structural wood sheathing directly applied or 4-5-15 oc purlins, except end verticals, and 2-0-0 oc purlins (3-6-0 max.): 3-6.	
BOT CHORD	Rigid ceiling directly applied or 9-11-7 oc bracing.	
WEBS	1 Row at midbt	4-13. 5-10

Max Horiz 14=91 (LC 7)  
Max Uplift 9=-149 (LC 4), 14=-137 (LC 5)


TOP CHORD      Tension  
1-2=0/35, 2-3=-2229/267, 3-4=-1865/265,  
4-5=-2481/348, 5-6=-1690/248,  
6-7=-2012/250, 7-8=0/63, 7-9=-1487/181,  
2-14=-1407/177

WEBS 10-11=-323/2402, 9-10=-81/223  
3-13=-16/568, 4-13=-844/219, 4-11=0/166,  
5-11=0/234, 5-10=-969/228, 6-10=-13/514,  
7-10=-170/1495, 2-13=-161/1258

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 137 lb uplift at joint 14 and 149 lb uplift at joint 9.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021




**WARNING -** Velly design parameters and READ NOTES ON THIS AND INCLUDED WITHIN KEY EXERCISE 1 AGE MH-475 (Rev. 3/19/2020) BEFORE USE. Design valid for use only with MITEK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Wheeler Lumber, Waverly, KS - 66871, Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:23 Page: 1  
ID:cjsHBdmz eZqa1ywXQH Tz1jnZ-RfC?PsB70Hg3NSaPqnL8w3uLTxbGKWrCDoi7J4zJC?f



**LUMBER**  
TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x3 SPF No.2 \*Except\* 10-8,15-2:2x4 SPF No.2

**BRACING**  
TOP CHORD Structural wood sheathing directly applied or 3-10-3 oc purlins, except end verticals, and 2-0-0 oc purlins (2-2-0 max.): 4-6.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS 1 Row at midpt 7-10, 3-15

**REACTIONS** (lb/size) 10=1553/0-5-8, 15=1476/0-3-8  
Max Horiz 15=99 (LC 7)  
Max Uplift 10=-153 (LC 9), 15=-141 (LC 8)

**FORCES** (lb) - Maximum Compression/Maximum Tension  
TOP CHORD 1-2=0/32, 2-3=-588/84, 3-4=-2087/236,  
4-5=-2242/312, 5-6=-2242/312,  
6-7=-1932/225, 7-8=-171/39, 8-9=0/63,  
8-10=-334/103, 2-15=-487/120  
BOT CHORD 14-15=-224/1883, 12-14=-176/1813,  
11-12=-112/1679, 10-11=-101/1503  
WEBS 3-14=-105/181, 4-14=0/324, 4-12=-173/642,  
5-12=-597/239, 6-12=-179/782,  
6-11=-16/210, 7-11=-42/325,  
7-10=-1830/181, 3-15=-1693/192

- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 153 lb uplift at joint 10 and 141 lb uplift at joint 15.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

- ## NOTES
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

 **WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

**WARNING:** - verify design parameters and READ NOTES ON THIS AND INCLUDED MITER REFERENCE PAGE MM1/473 (rev. 3/19/2020) BEFORE USE.


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017



Wheeler Lumber, Waverly, KS - 66871, Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:23 Page: 1  
ID:K?5B76gMZAcSZBoD dyKWz1jm4-RfC?PsB70Hg3NSqPqnL8w3ulTXbGKWkRCDoi7J4zJC?f



<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.67	Vert(LL)	-0.20	16-17	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.70	Vert(CT)	-0.45	16-17	>826	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.87	Horz(CT)	0.10	12	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.10	14-15	>999	240	Weight: 137 lb	FT = 10%

LOAD CASE(S) Standard



**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITER REFERENCE PAGE MH-747.5 (REV. 3/19/2020) BEFORE USE.**


Design valid for use only with MiTEK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Code**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601





Wheeler Lumber, Waverly, KS - 66871, Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:24 Page: 1  
ID:4i4yAwawANSuJlmtW446Opz1jiC-RfC?PsB70Hq3NSaPanL8w3uITxBGKWRCDoi7J4zJC?f



<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.95	Vert(LL)	-0.14	12-13	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.67	Vert(CT)	-0.30	14-15	>999	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.89	Horz(CT)	0.10	11	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.07	12-13	>999	240	Weight: 135 lb	FT = 10%

**FORCES** (lb) - Maximum Compression/Maximum Tension

**TOP CHORD**  
1-2=0/32, 2-3=-2262/12, 3-4=-1914/11,  
4-5=-1948/18, 5-6=-1946/17, 6-7=-2129/0,  
7-8=-2136/0, 8-9=-2408/0, 9-10=-61/7,  
2-17=-1407/38, 10-11=-134/25


**BOT CHORD**  
16-17=-108/359, 15-16=-37/1950,  
14-15=0/95, 13-14=0/134, 5-13=-446/163,  
12-13=0/2334, 11-12=-17/2230

**WEBS**  
3-16=-82/102, 3-15=-390/106, 4-15=0/275,  
13-15=-10/1547, 4-13=-46/527,  
7-13=-528/50, 8-12=0/912, 9-12=-150/61,  
9-11=-2485/20, 2-16=0/1602, 6-13=-74/760,  
7-12=-732/16

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCdL=6.0psf; BCdL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.

- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 17 and 2 lb uplift at joint 11.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021



**WARNING – Velly design parameters are listed below and included with the key reference to AISC M14-15 16f, 3f, 9f, 10f, 11f, 12f, 13f, 14f, 15f, 16f, 17f, 18f, 19f, 20f, 21f, 22f, 23f, 24f, 25f, 26f, 27f, 28f, 29f, 30f, 31f, 32f, 33f, 34f, 35f, 36f, 37f, 38f, 39f, 40f, 41f, 42f, 43f, 44f, 45f, 46f, 47f, 48f, 49f, 50f, 51f, 52f, 53f, 54f, 55f, 56f, 57f, 58f, 59f, 60f, 61f, 62f, 63f, 64f, 65f, 66f, 67f, 68f, 69f, 70f, 71f, 72f, 73f, 74f, 75f, 76f, 77f, 78f, 79f, 80f, 81f, 82f, 83f, 84f, 85f, 86f, 87f, 88f, 89f, 90f, 91f, 92f, 93f, 94f, 95f, 96f, 97f, 98f, 99f, 100f, 101f, 102f, 103f, 104f, 105f, 106f, 107f, 108f, 109f, 110f, 111f, 112f, 113f, 114f, 115f, 116f, 117f, 118f, 119f, 120f, 121f, 122f, 123f, 124f, 125f, 126f, 127f, 128f, 129f, 130f, 131f, 132f, 133f, 134f, 135f, 136f, 137f, 138f, 139f, 140f, 141f, 142f, 143f, 144f, 145f, 146f, 147f, 148f, 149f, 150f, 151f, 152f, 153f, 154f, 155f, 156f, 157f, 158f, 159f, 160f, 161f, 162f, 163f, 164f, 165f, 166f, 167f, 168f, 169f, 170f, 171f, 172f, 173f, 174f, 175f, 176f, 177f, 178f, 179f, 180f, 181f, 182f, 183f, 184f, 185f, 186f, 187f, 188f, 189f, 190f, 191f, 192f, 193f, 194f, 195f, 196f, 197f, 198f, 199f, 200f, 201f, 202f, 203f, 204f, 205f, 206f, 207f, 208f, 209f, 210f, 211f, 212f, 213f, 214f, 215f, 216f, 217f, 218f, 219f, 220f, 221f, 222f, 223f, 224f, 225f, 226f, 227f, 228f, 229f, 230f, 231f, 232f, 233f, 234f, 235f, 236f, 237f, 238f, 239f, 240f, 241f, 242f, 243f, 244f, 245f, 246f, 247f, 248f, 249f, 250f, 251f, 252f, 253f, 254f, 255f, 256f, 257f, 258f, 259f, 260f, 261f, 262f, 263f, 264f, 265f, 266f, 267f, 268f, 269f, 270f, 271f, 272f, 273f, 274f, 275f, 276f, 277f, 278f, 279f, 280f, 281f, 282f, 283f, 284f, 285f, 286f, 287f, 288f, 289f, 290f, 291f, 292f, 293f, 294f, 295f, 296f, 297f, 298f, 299f, 300f, 301f, 302f, 303f, 304f, 305f, 306f, 307f, 308f, 309f, 310f, 311f, 312f, 313f, 314f, 315f, 316f, 317f, 318f, 319f, 320f, 321f, 322f, 323f, 324f, 325f, 326f, 327f, 328f, 329f, 330f, 331f, 332f, 333f, 334f, 335f, 336f, 337f, 338f, 339f, 340f, 341f, 342f, 343f, 344f, 345f, 346f, 347f, 348f, 349f, 350f, 351f, 352f, 353f, 354f, 355f, 356f, 357f, 358f, 359f, 360f, 361f, 362f, 363f, 364f, 365f, 366f, 367f, 368f, 369f, 370f, 371f, 372f, 373f, 374f, 375f, 376f, 377f, 378f, 379f, 380f, 381f, 382f, 383f, 384f, 385f, 386f, 387f, 388f, 389f, 390f, 391f, 392f, 393f, 394f, 395f, 396f, 397f, 398f, 399f, 400f, 401f, 402f, 403f, 404f, 405f, 406f, 407f, 408f, 409f, 410f, 411f, 412f, 413f, 414f, 415f, 416f, 417f, 418f, 419f, 420f, 421f, 422f, 423f, 424f, 425f, 426f, 427f, 428f, 429f, 430f, 431f, 432f, 433f, 434f, 435f, 436f, 437f, 438f, 439f, 440f, 441f, 442f, 443f, 444f, 445f, 446f, 447f, 448f, 449f, 450f, 451f, 452f, 453f, 454f, 455f, 456f, 457f, 458f, 459f, 460f, 461f, 462f, 463f, 464f, 465f, 466f, 467f, 468f, 469f, 470f, 471f, 472f, 473f, 474f, 475f, 476f, 477f, 478f, 479f, 480f, 481f, 482f, 483f, 484f, 485f, 486f, 487f, 488f, 489f, 490f, 491f, 492f, 493f, 494f, 495f, 496f, 497f, 498f, 499f, 500f, 501f, 502f, 503f, 504f, 505f, 506f, 507f, 508f, 509f, 510f, 511f, 512f, 513f, 514f, 515f, 516f, 517f, 518f, 519f, 520f, 521f, 522f, 523f, 524f, 525f, 526f, 527f, 528f, 529f, 530f, 531f, 532f, 533f, 534f, 535f, 536f, 537f, 538f, 539f, 540f, 541f, 542f, 543f, 544f, 545f, 546f, 547f, 548f, 549f, 550f, 551f, 552f, 553f, 554f, 555f, 556f, 557f, 558f, 559f, 560f, 561f, 562f, 563f, 564f, 565f, 566f, 567f, 568f, 569f, 570f, 571f, 572f, 573f, 574f, 575f, 576f, 577f, 578f, 579f, 580f, 581f, 582f, 583f, 584f, 585f, 586f, 587f, 588f, 589f, 590f, 591f, 592f, 593f, 594f, 595f, 596f, 597f, 598f, 599f, 600f, 601f, 602f, 603f, 604f, 605f, 606f, 607f, 608f, 609f, 610f, 611f, 612f, 613f, 614f, 615f, 616f, 617f, 618f, 619f, 620f, 621f, 622f, 623f, 624f, 625f, 626f, 627f, 628f, 629f, 630f, 631f, 632f, 633f, 634f, 635f, 636f, 637f, 638f, 639f, 640f, 641f, 642f, 643f, 644f, 645f, 646f, 647f, 648f, 649f, 650f, 651f, 652f, 653f, 654f, 655f, 656f, 657f, 658f, 659f, 660f, 661f, 662f, 663f, 664f, 665f, 666f, 667f, 668f, 669f, 670f, 671f, 672f, 673f, 674f, 675f, 676f, 677f, 678f, 679f, 680f, 681f, 682f, 683f, 684f, 685f, 686f, 687f, 688f, 689f, 690f, 691f, 692f, 693f, 694f, 695f, 696f, 697f, 698f, 699f, 700f**



16023 Swingley Ridge Rd  
Chesterfield, MO 63017


Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	E3	Roof Special	1	1	Job Reference (optional)	I47674097

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:24

Page: 1

ID:ocUQWHDVmgYsajkYy6JtLz1jf7-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCdoi7J4zJC?fi



Scale = 1:60.8

Plate Offsets (X, Y): [7:0-4-0,0-2-12], [9:0-4-13,Edge], [14:Edge,0-2-8], [16:0-2-8,0-1-8], [17:Edge,0-5-13]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.67	Vert(LL)	-0.14	12-13	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.79	Vert(CT)	-0.31	12-13	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.87	Horz(CT)	0.09	11	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.07	12-13	>999	240	Weight: 138 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2 \*Except\* 7-8:2x8 SP DSS,  
8-9:2x6 SPF No.2  
BOT CHORD 2x4 SPF No.2 \*Except\* 14-6:2x3 SPF No.2  
WEBS 2x3 SPF No.2 \*Except\* 17-2:2x4 SPF 2400F  
2.0E, 11-10:2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
3-0-8 oc purlins, except end verticals, and  
2-0-0 oc purlins (4-3-8 max.): 4-5, 7-9.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.  
WEBS 1 Row at midpt 5-15

**REACTIONS** (lb/size) 11=1395/ Mechanical,  
17=1469/0-3-8  
Max Horiz 17=132 (LC 5)  
Max Uplift 11=8 (LC 9), 17=16 (LC 8)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension  
TOP CHORD 1-2=0/32, 2-3=-2246/20, 3-4=-1782/37,  
4-5=-1509/56, 5-6=-2094/86, 6-7=-2148/13,  
7-9=-2296/0, 9-10=-67/27, 2-17=-1392/59,  
10-11=-69/16  
BOT CHORD 16-17=-161/660, 15-16=-29/1901,  
14-15=-6/67, 13-14=0/109, 6-13=-338/152,  
12-13=-8/2555, 11-12=-13/810  
WEBS 3-16=0/199, 3-15=-511/99, 4-15=0/382,  
7-13=-774/70, 9-12=0/1886, 2-16=0/1246,  
9-11=-1505/16, 5-15=-402/35, 7-12=-728/52,  
8-12=-359/38, 5-13=-96/1039, 13-15=0/1619

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- Provide adequate drainage to prevent water ponding.
- The Fabrication Tolerance at joint 2 = 6%
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 16 lb uplift at joint 17 and 8 lb uplift at joint 11.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	E4	Roof Special	1	1	Job Reference (optional)	I47674098

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:24  
ID:IVJ3PIHIVSDhTruc3MhPIPz1jcS-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1




Scale = 1:64.4									
Plate Offsets (X, Y): [4:0-6-0,0-1-15], [9:0-6-0,0-2-3], [10:0-4-13,Edge], [13:0-2-8,0-2-0], [16:0-6-0,0-2-4], [18:0-2-8,0-1-8], [19:Edge,0-5-13]									
<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in (loc)	l/defl	L/d
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.19 13-14	>999	360
TCDL	10.0	Lumber DOL	1.15	BC	0.90	Vert(CT)	-0.42 13-14	>886	240
BCLL	0.0*	Rep Stress Incr	YES	WB	0.98	Horz(CT)	0.09 12	n/a	n/a
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.10 13-14	>999	240
							Weight: 148 lb FT = 10%		

<b>LUMBER</b>	
TOP CHORD	2x4 SPF No.2 *Except* 7-9:2x4 SPF 2100F 1.8E
BOT CHORD	2x4 SPF No.2 *Except* 15-8:2x3 SPF No.2
WEBS	2x3 SPF No.2 *Except* 19-2:2x4 SPF 2100F 1.8E
<b>BRACING</b>	
TOP CHORD	Structural wood sheathing directly applied or 3-2-6 oc purlins, except end verticals, and 2-0-0 oc purlins (3-2-11 max.): 4-5, 6-7, 9-10.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 15-16.
WEBS	1 Row at midpt 3-17, 9-14
<b>REACTIONS</b>	(lb/size) 12=1397/ Mechanical, 19=1471/0-3-8
	Max Horiz 19=142 (LC 5)
<b>FORCES</b>	(lb) - Maximum Compression/Maximum Tension
	TOP CHORD 1-2=0/32, 2-3=-2265/32, 3-4=-1705/62, 4-5=-1454/80, 5-6=-1675/85, 6-7=-1513/67, 7-8=-2191/151, 8-9=-2205/51, 9-10=-2962/33, 10-11=-47/18, 2-19=-1396/62, 11-12=-42/23
BOT CHORD	18-19=-159/609, 17-18=-48/1924, 16-17=0/1403, 15-16=-32/28, 14-15=0/63, 8-14=-541/213, 13-14=-34/2903, 12-13=-18/383
WEBS	3-18=0/230, 3-17=-631/109, 4-17=0/241, 5-17=-65/396, 6-16=-764/53, 9-14=-1063/51, 9-13=-1073/98, 10-13=-23/2840, 2-18=0/1320, 7-16=-496/27, 5-16=-88/698, 7-14=-150/1454, 14-16=0/1691, 10-12=-1415/52

**NOTES**  
1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 22 lb uplift at joint 19 and 25 lb uplift at joint 12.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see


**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Wheeler Lumber, Waverly, KS - 66871, Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:25 Page: 1  
ID:8Hu4qbV3dgMQS9MO2dkqBz1jam-RfC?PsB70Hq3NSqPanL8w3uITXbGKWKRcDoi7J4zJC?f




<b>LUMBER</b>		2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
TOP CHORD	2x4 SPF No.2	3) Provide adequate drainage to prevent water ponding.
BOT CHORD	2x4 SPF No.2	4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
WEBS	2x3 SPF No.2 *Except* 18-2:2x4 SPF 2100F 1.8E	5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
<b>BRACING</b>		6) Refer to girder(s) for truss to truss connections.
TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (4-1-7 max.): 5-6, 8-9.	7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 186 lb uplift at joint 10 and 190 lb uplift at joint 18.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 8-7-14 oc bracing: 10-11.	8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
WEBS	1 Row at midpt 5-15, 8-10, 3-16	9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
<b>REACTIONS</b> (lb/size)		<b>LOAD CASE(S)</b> Standard
	10=1397/ Mechanical, 18=1471/0-3-8	
	Max Horiz 18=154 (LC 5) Max Uplift 10=186 (LC 9), 18=190 (LC 8)	
<b>FORCES</b> (lb) - Maximum Compression/Maximum Tension		
TOP CHORD	1-2=0/32, 2-3=2268/264, 3-4=1684/251, 4-5=2204/352, 5-6=1955/281, 6-7=2748/436, 7-8=2737/331, 8-9=85/0, 9-10=136/44, 2-18=1397/229	
BOT CHORD	17-18=304/599, 16-17=290/1928, 15-16=0/23, 14-15=0/0, 12-13=145/1865, 11-12=145/1865, 10-11=457/3135	
WEBS	12-14=2/7, 13-15=0/99, 5-13=1057/204, 6-11=188/847, 8-10=3280/488, 2-17=34/1333, 3-17=0/237, 4-16=118/104, 13-16=96/1453, 3-16=659/234, 7-11=288/181, 8-11=765/201, 4-13=247/1472, 6-13=47/308	

1) Unbalanced roof live loads have been considered for this design.




August 30, 2021





Wheeler Lumber, Waverly, KS - 66871, Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:25 Page: 1  
ID:8eT1wkdp2lXl7W8itOead6z1iZR-RfC?PsB70Hq3NSaPanL8w3ulTXbGKWrcDOI7J4zJC?f




<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.75	Vert(LL)	-0.12	14-15	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.59	Vert(CT)	-0.26	14-15	>999	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.89	Horz(CT)	0.07	10	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.08	14-15	>999	240	Weight: 127 lb	FT = 10%

- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 191 lb uplift at joint 16 and 209 lb uplift at joint 10.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.



August 30, 2021



**WARNING:** - verify design parameters and READ NOTES ON THIS AND INCLUDED MITER REFERENCE PAGE MMF/473 Rev. 3/19/2020 BEFORE USE.

Design valid for use only with MITek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	G2	Roof Special	1	1	Job Reference (optional)	I47674101

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:26

Page: 1

ID:CoP7dh?uWaamzQbrl6DAwsz1jYx-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRCDoi7J4zJC?i



Scale = 1:59.8

Plate Offsets (X, Y): [5:0-3-3,Edge], [8:Edge,0-2-0], [14:0-2-8,0-1-8], [15:Edge,0-5-13]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.74	Vert(LL)	-0.17	10-11	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.74	Vert(CT)	-0.37	10-11	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.55	Horz(CT)	0.08	10	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.08	11-13	>999	240	Weight: 124 lb FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 15-2,10-8:2x4 SPF 2100F 1.8E

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (4-3-9 max.): 5-6.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

WEBS	1 Row at midpt 3-13, 5-13, 7-10
REACTIONS	(lb/size) 10=1480/0-3-8, 15=1480/0-3-8
	Max Horiz 15=124 (LC 7)
	Max Uplift 10=209 (LC 9), 15=191 (LC 8)

#### FORCES

TOP CHORD	(lb) - Maximum Compression/Maximum Tension
	1-2=0/32, 2-3=-2284/267, 3-4=-1703/260, 4-5=-1664/249, 5-6=-1799/283, 6-7=-2088/282, 7-8=-592/104, 8-9=0/32, 2-15=-1405/230, 8-10=-487/131
BOT CHORD	14-15=-271/605, 13-14=-259/1941, 11-13=-116/1979, 10-11=-228/1892
WEBS	3-14=0/230, 3-13=-659/237, 4-13=-91/984, 5-13=-775/230, 5-11=-474/120, 6-11=-47/663, 7-11=-140/166, 2-14=-32/1340, 7-10=-1698/239

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 191 lb uplift at joint 15 and 209 lb uplift at joint 10.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	G3	Roof Special	1	1	Job Reference (optional)	I47674102

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:26  
ID:9jakB?RT1e6fHylmsgsdNSz1jYN-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:59.8

Plate Offsets (X, Y): [5:0-5-10,0-2-4], [6:0-4-8,0-1-11], [9:0-4-12,0-2-12], [13:0-2-8,0-1-8], [14:Edge,0-6-13]																		
Loading		(psf)	Spacing		2-0-0		CSI		DEFL		in	(loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)		25.0	Plate Grip DOL		1.15		TC		0.94		Vert(LL)		-0.15	10-12	>999	360	MT20	197/144
TCDL		10.0	Lumber DOL		1.15		BC		0.73		Vert(CT)		-0.36	10-12	>999	240		
BCLL		0.0*	Rep Stress Incr		YES		WB		0.54		Horz(CT)		0.07	9	n/a	n/a		
BCDL		10.0	Code		IRC2018/TPI2014		Matrix-S				Wind(LL)		0.08	12-13	>999	240	Weight: 122 lb	FT = 10%

<b>LUMBER</b>	
TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 14-2,9-7:2x6 SPF No.2
<b>BRACING</b>	
TOP CHORD	Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (4-0-2 max.): 5-6.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	1 Row at midpt 3-12, 5-12
<b>REACTIONS</b>	
(lb/size)	9=1478/0-3-8, 14=1478/0-3-8
Max Horiz	14=125 (LC 7)
Max Uplift	9=-210 (LC 9), 14=-192 (LC 8)
<b>FORCES</b>	
(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/35, 2-3=-2245/265, 3-4=-1692/257, 4-5=-1679/241, 5-6=-1859/293, 6-7=-2228/269, 7-8=0/35, 2-14=-1403/232, 7-9=-1407/249
BOT CHORD	13-14=-261/574, 12-13=-255/1906, 10-12=-166/2117, 9-10=-277/767
WEBS	3-13=0/207, 3-12=-635/237, 4-12=-61/928, 5-12=-851/261, 5-10=-603/121, 6-10=-6/623, 2-13=-32/1338, 7-10=0/1111

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 192 lb uplift at joint 14 and 210 lb uplift at joint 9.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	G4	Roof Special	1	1	Job Reference (optional)	I47674103

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:26  
ID: djjO6n45ncfGWyKmvbopUQz1jXZ-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwRCDoi7J4zJC7f

Page: 1



Scale = 1:59.8

Plate Offsets (X, Y): [6:0-4-0,0-2-4], [10:Edge,0-5-13], [15:0-2-8,0-1-8], [16:Edge,0-5-13]												
<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.73	Vert(LL)	-0.14	12-14	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.70	Vert(CT)	-0.30	12-14	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.64	Horz(CT)	0.07	10	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.09	12-14	>999	240	Weight: 125 lb	FT = 10%


<b>LUMBER</b>		
TOP CHORD	2x4 SPF No.2	
BOT CHORD	2x4 SPF No.2	
WEBS	2x3 SPF No.2 *Except* 16-2:2x4 SPF 2400F	
	2.0E, 10-8:2x4 SPF 2100F 1.8E	
<b>BRACING</b>		
TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (4-0-11 max.): 6-7.	
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	
WEBS	1 Row at midpt 3-14, 5-14	
<b>REACTIONS</b>		
(lb/size)	10=1480/0-3-8, 16=1480/0-3-8	
Max Horiz	16=125 (LC 7)	
Max Uplift	10=209 (LC 9), 16=191 (LC 8)	
<b>FORCES</b>		
(lb) - Maximum Compression/Maximum Tension		
TOP CHORD	1-2=0/32, 2-3=-2282/268, 3-4=-1707/260, 4-5=-1708/245, 5-6=-2415/268, 6-7=-1917/302, 7-8=-2271/289, 8-9=0/32, 2-16=-1404/231, 8-10=-1407/246	
BOT CHORD	15-16=-272/613, 14-15=-259/1939, 12-14=-197/2242, 11-12=-181/2311, 10-11=-185/610	
WEBS	3-15=0/223, 3-14=-655/239, 4-14=-71/946, 5-14=-957/287, 6-11=-801/69, 7-11=-5/651, 2-15=-30/1330, 8-11=-6/1330, 5-12=0/515, 6-12=-318/3	

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 191 lb uplift at joint 16 and 209 lb uplift at joint 10.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017


Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	G5	Roof Special	1	1	Job Reference (optional)	I47674104

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:27

Page: 1

ID:M440JW2KPiB8a?H5yKD1boz1jV0-RfC?PsB70Hq3NSgPqnL8w3uTXbGKWrCDoi7J4zJC?i



Scale = 1:59.8

Plate Offsets (X, Y): [3:0-0-11,0-1-12], [6:0-4-12,0-3-12], [13:Edge,0-5-13]


Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.52	Vert(LL)	-0.19	18-19	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.85	Vert(CT)	-0.35	18-19	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.99	Horz(CT)	0.25	13	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.14	18-19	>999	240	Weight: 169 lb	FT = 10%

<b>LUMBER</b>	
TOP CHORD	2x4 SPF No.2 *Except* 1-6:2x8 SP DSS, 6-7:2x6 SPF No.2
BOT CHORD	2x4 SPF No.2 *Except* 5-17:2x3 SPF No.2
WEBS	2x3 SPF No.2 *Except* 13-11:2x4 SPF No.2
<b>BRACING</b>	
TOP CHORD	Structural wood sheathing directly applied or 3-6-1 oc purlins, except end verticals, and 2-0-0 oc purlins (4-2-3 max.): 6-7, 9-10.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
<b>REACTIONS</b>	
(lb/size)	2=1492/0-3-8, 13=1480/0-3-8
Max Horiz	2=131 (LC 8)
Max Uplift	2=-183 (LC 8), 13=-208 (LC 9)
<b>FORCES</b>	
(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/6, 2-3=-863/164, 3-4=-2978/349, 4-5=-2223/272, 5-6=-2089/329, 6-7=-1286/251, 7-8=-1668/245, 8-9=-2250/298, 9-10=-1931/288, 10-11=-2270/282, 11-12=0/32, 11-13=-1423/231
BOT CHORD	2-20=-27/0, 3-19=-351/2737, 18-19=-350/2737, 17-18=0/28, 5-18=-109/97, 16-17=-12/46, 15-16=-107/1968, 14-15=-240/2470, 13-14=-121/421
WEBS	3-20=0/55, 4-18=-1032/259, 6-18=-233/1273, 7-16=-53/189, 8-16=-763/215, 9-14=-962/114, 10-14=-13/719, 11-14=-56/1545, 8-15=-27/493, 9-15=-626/166, 4-19=0/221, 16-18=-43/1488, 6-16=-167/51

**NOTES**  
1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 183 lb uplift at joint 2 and 208 lb uplift at joint 13.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	G6	Roof Special	1	1	Job Reference (optional)	I47674105

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:27  
ID:WSrcGbvRHIOtL1AP8qR03z1jQ1-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?i

Page: 1



Scale = 1:62.6

Plate Offsets (X, Y): [3:0-0-11,0-1-12], [9:0-5-10,0-2-4], [13:Edge,0-5-13], [14:0-4-12,0-2-4], [18:0-1-8,0-1-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.31	16-17	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.94	Vert(CT)	-0.56	16-17	>671	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.88	Horz(CT)	0.38	13	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.19	16-17	>999	240	Weight: 175 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2 *Except* 1-5:2x8 SP DSS
BOT CHORD	2x4 SPF No.2 *Except* 18-7,8-15:2x3 SPF No.2
WEBS	2x3 SPF No.2 *Except* 22-23,14-16,13-11,18-24,25-26:2x4 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (4-1-8 max.): 5-6, 9-10.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-21 2-2-0 oc bracing: 16-17.
WEBS	1 Row at midpt 4-19

REACTIONS	(lb/size) 2=1492/0-3-8, 13=1480/0-3-8
	Max Horiz 2=120 (LC 8)
	Max Uplift 2=173 (LC 8), 13=198 (LC 9)

FORCES	(lb) - Maximum Compression/Maximum Tension
--------	--

TOP CHORD	1-2=0/6, 2-3=-863/147, 3-4=-2957/318, 4-5=-2107/216, 5-6=-1803/233, 6-7=-2592/297, 7-8=-2695/262, 8-9=-4022/380, 9-10=-2024/260, 10-11=-2241/257, 11-12=0/32, 11-13=-1430/209
BOT CHORD	2-21=-27/0, 3-20=-311/2713, 19-20=-309/2713, 18-19=-4/81, 17-18=0/58, 7-17=-38/62, 16-17=-190/3543, 15-16=0/126, 8-16=-78/1339, 14-15=0/66, 13-14=-73/297, 3-21=0/55, 4-19=-1051/279, 5-19=-31/557, 6-19=-596/78, 17-19=-34/1994, 6-17=-182/1548, 8-17=-1593/255, 14-16=-377/3596, 9-16=-55/174, 9-14=-2503/311, 10-14=-37/780, 11-14=-99/1671, 4-20=0/231
WEBS	

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 173 lb uplift at joint 2 and 198 lb uplift at joint 13.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674106
210529	G7	Roof Special	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:28  
ID: Vz\_TTjrkZKmrzWsgan3hbz1jKy-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:62.9												
Plate Offsets (X, Y): [3:0-0-11,0-1-12], [5:0-6-0,0-2-1], [9:0-5-10,0-2-4], [13:Edge,0-5-13], [15:0-2-8,0-3-0], [19:0-2-8,0-2-8], [20:0-1-8,0-1-0], [21:0-2-0,0-2-12]												
<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.68	Vert(LL)	-0.28	17-18	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.93	Vert(CT)	-0.50	17-18	>747	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.77	Horz(CT)	0.36	13	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.16	17-18	>999	240	Weight: 170 lb	FT = 10%

<b>LUMBER</b>	
TOP CHORD	2x4 SPF No.2 *Except* 1-5:2x8 SP DSS, 7-9:2x4 SPF 2100F 1.8E
BOT CHORD	2x4 SPF No.2 *Except* 20-6,8-16:2x3 SPF No.2
WEBS	2x3 SPF No.2 *Except* 21-24:2x6 SPF No.2, 15-17,13-11,20-25,26-27:2x4 SPF No.2
<b>BRACING</b>	
TOP CHORD	Structural wood sheathing directly applied or 2-10-6 oc purlins, except end verticals, and 2-0-0 oc purlins (2-11-10 max.): 5-7, 9-10.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-23 2-2-0 oc bracing: 17-18.
<b>REACTIONS</b>	
(lb/size)	2=1492/0-3-8, 13=1480/0-3-8
Max Horiz	2=108 (LC 12)
Max Uplift	2=161 (LC 8), 13=189 (LC 9)
<b>FORCES</b>	
(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/6, 2-3=-863/129, 3-4=-2953/281, 4-5=-2282/218, 5-6=-2473/230, 6-7=-2423/230, 7-8=-2812/246, 8-9=-4095/345, 9-10=-1700/222, 10-11=-1986/234, 11-12=0/32, 11-13=-1420/202
BOT CHORD	2-23=-27/0, 3-22=-263/2711, 21-22=-261/2710, 20-21=-8/135, 19-20=0/101, 6-19=-334/127, 18-19=-17/2466, 17-18=-166/3559, 16-17=0/115, 8-17=-54/1324, 15-16=0/53, 14-15=-295/3068, 13-14=-25/184
WEBS	3-23=0/55, 4-21=-916/236, 19-21=-67/1849, 8-18=-1488/252, 15-17=-306/3138, 9-17=-15/555, 9-15=-941/178, 9-14=-1791/171, 10-14=-67/752, 11-14=-148/1609, 5-21=-55/314, 4-22=0/194, 5-19=-85/736, 7-18=-109/1200

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Provide adequate drainage to prevent water ponding.
  - 4) All plates are 2x4 MT20 unless otherwise indicated.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 161 lb uplift at joint 2 and 189 lb uplift at joint 13.
  - 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674107
210529	G8	Roof Special Girder	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:28  
ID:Pj1gZ196lFOgFKcZNbirtx1jHz-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDdi7J4zJC?f

Page: 1



Scale = 1:59.8

Plate Offsets (X, Y): [3:0-0-11,0-1-12], [5:0-6-0,0-2-1], [9:0-2-14,Edge], [13:Edge,0-5-13], [15:0-2-8,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.97	Vert(LL)	-0.21	6	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.92	Vert(CT)	-0.39	16-17	>974	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.63	Horz(CT)	0.26	13	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.13	18-19	>999	240	Weight: 150 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2 \*Except\* 1-5:2x8 SP DSS  
BOT CHORD 2x4 SPF No.2 \*Except\* 6-17:2x3 SPF No.2,  
17-13:2x4 SPF 2100F 1.8E  
WEBS 2x3 SPF No.2 \*Except\* 13-11:2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
3-2-10 oc purlins, except end verticals, and  
2-0-0 oc purlins (2-7-11 max.): 5-7, 9-10.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing, Except:  
6-0-0 oc bracing: 2-20.

REACTIONS (lb/size) 2=1489/0-3-8, 13=1399/0-3-8  
Max Horiz 2=97 (LC 8)  
Max Uplift 2=150 (LC 8), 13=205 (LC 9)

#### FORCES

(lb) - Maximum Compression/Maximum  
Tension  
TOP CHORD 1-2=0/6, 2-3=-861/113, 3-4=-2954/239,  
4-5=-3141/375, 5-6=-2243/203,  
6-7=-2245/209, 7-8=-2145/211,  
8-9=-2784/285, 9-10=-1192/137,  
10-11=-1383/145, 11-12=0/32,  
11-13=-1350/157  
BOT CHORD 2-20=-27/0, 3-19=-210/2711,  
18-19=-112/2067, 17-18=0/127,  
6-18=-458/202, 16-17=0/118,  
15-16=-178/2447, 14-15=-380/3364,  
13-14=-15/85  
WEBS 3-20=0/55, 4-19=-844/273, 16-18=-61/1749,  
7-18=-122/605, 7-16=-32/339,  
8-16=-706/208, 8-15=0/362, 9-15=-949/209,  
9-14=-2472/319, 10-14=-69/581,  
11-14=-106/1330, 5-19=-238/1135,  
5-18=-154/638


#### NOTES

1) Unbalanced roof live loads have been considered for  
this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 5) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 6) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 150 lb uplift at  
joint 2 and 205 lb uplift at joint 13.
- 7) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size  
or the orientation of the purlin along the top and/or  
bottom chord.
- 9) Hanger(s) or other connection device(s) shall be  
provided sufficient to support concentrated load(s) 126  
lb down and 235 lb up at 30-3-8 on top chord, and 17 lb  
down and 65 lb up at 30-2-6 on bottom chord. The  
design/selection of such connection device(s) is the  
responsibility of others.
- 10) In the LOAD CASE(S) section, loads applied to the face  
of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15,  
Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-5=-70, 5-7=-70, 7-9=-70, 9-10=-70,  
10-11=-70, 11-12=-70, 2-20=-20, 3-18=-20,  
13-17=-20  
Concentrated Loads (lb)  
Vert: 10=58 (B), 14=26 (B)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see


ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Wheeler Lumber, Waverly, KS - 66871, Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:29 Page: 1  
ID:?DSFCfXSDaRYJ43qLN53az1iGv-RfC?PsB70Hq3NSqPqnL8w3uITxbGKWrCdoi7J4zJC?f



<b>LUMBER</b>	
TOP CHORD	2x8 SP DSS *Except* 4-7:2x4 SPF No.2, 7-8:2x4 SPF 2400F 2.0E
BOT CHORD	2x4 SPF No.2 *Except* 5-11:2x3 SPF No.2
WEBS	2x3 SPF No.2 *Except* 9-8:2x6 SPF No.2
<b>BRACING</b>	
TOP CHORD	Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (3-7-4 max.): 4-7.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-14.
<b>REACTIONS</b>	(lb/size) 2=1399/0-3-8, 9=1314/0-3-8 Max Horiz 2=94 (LC 12) Max Uplift 2=-133 (LC 8), 9=-115 (LC 9)
<b>FORCES</b>	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/6, 2-3=-805/75, 3-4=-2375/206, 4-5=-2284/266, 5-6=-2276/266, 6-7=-1680/185, 7-8=-2014/172, 8-9=-1227/165
BOT CHORD	2-14=-26/0, 3-13=-187/2122, 12-13=-184/2125, 11-12=0/133, 5-12=-210/106, 10-11=0/194, 9-10=-200/704
WEBS	3-14=0/54, 4-13=0/319, 4-12=-149/399, 10-12=-216/1884, 6-12=-33/345, 6-10=-727/195, 7-10=0/475, 8-10=-111/1025

## NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 133 lb uplift at joint 2 and 115 lb uplift at joint 9.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

 **WARNING** - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

**WARNING:** - verify design parameters and READ NOTES ON THIS AND INCLUDED MITER REFERENCE PAGE MM1/473 (rev. 3/19/2020) BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674109
210529	H2	Hip	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:29  
ID:0mW6LlCRgtddXhbgU\_3Slz1jGQ-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:56.2

Plate Offsets (X, Y): [8:0-4-6,Edge], [9:0-2-8,0-1-8], [12:0-2-8,0-1-8], [13:0-4-6,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.12	11	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.56	Vert(CT)	-0.23	9-11	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.39	Horz(CT)	0.06	8	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.09	11	>999	240	Weight: 109 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x3 SPF No.2 \*Except\* 13-2,8-6:2x6 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (2-10-6 max.): 3-5.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** (lb/size) 8=1388/0-3-8, 13=1388/0-3-8  
Max Horiz 13=80 (LC 7)  
Max Uplift 8=126 (LC 9), 13=126 (LC 8)

#### FORCES

(lb) - Maximum Compression/Maximum Tension  
TOP CHORD 1-2=0/35, 2-3=-2053/224, 3-4=-2251/317, 4-5=-2251/317, 5-6=-2053/224, 6-7=0/35, 2-13=-1314/170, 6-8=-1314/170  
BOT CHORD 12-13=-315/745, 11-12=-180/1717, 9-11=-119/1717, 8-9=-263/745  
WEBS 3-12=0/245, 3-11=-178/749, 4-11=-576/233, 5-11=-177/749, 5-9=0/245, 2-12=-145/1138, 6-9=-149/1138

#### NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 126 lb uplift at joint 13 and 126 lb uplift at joint 8.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674110
210529	H3	Hip	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:29  
ID:jyeJ?6g84zGoNhFnlfzQ2Rz1jG?-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:56.1

Plate Offsets (X, Y): [9:Edge,0-5-13], [14:Edge,0-5-13]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.62	Vert(LL)	-0.16	12	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.77	Vert(CT)	-0.33	10-12	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.95	Horz(CT)	0.08	9	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.12	12	>999	240	Weight: 106 lb FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x3 SPF No.2 \*Except\* 14-2,9-7:2x4 SPF  
2100F 1.8E

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 3-2-15 oc purlins, except end verticals, and 2-0-0 oc purlins (3-0-4 max.): 3-6.  
BOT CHORD Rigid ceiling directly applied or 9-7-4 oc bracing.

**REACTIONS** (lb/size) 9=1390/0-3-8, 14=1390/0-3-8  
Max Horiz 14=70 (LC 7)  
Max Uplift 9=138 (LC 4), 14=138 (LC 5)

**FORCES** (lb) - Maximum Compression/Maximum Tension  
TOP CHORD 1-2=0/32, 2-3=-2115/261, 3-4=-1781/255, 4-5=-2569/354, 5-6=-1781/255, 6-7=-2115/261, 7-8=0/32, 2-14=-1329/169, 7-9=-1329/169  
BOT CHORD 13-14=-227/580, 12-13=-370/2494, 10-12=-349/2494, 9-10=-186/580  
WEBS 3-13=-35/602, 4-13=-967/243, 4-12=0/227, 5-12=0/227, 5-10=-967/243, 6-10=-35/602, 2-13=-156/1283, 7-10=-161/1283

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 138 lb uplift at joint 14 and 138 lb uplift at joint 9.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021


**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017





Scale = 1:56

Plate Offsets (X, Y): [3:0-0-11,0-1-12], [4:0-6-0,0-2-1], [10:Edge,0-5-13], [11:0-2-8,0-1-8]

<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.84	Vert(LL)	-0.27	5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.86	Vert(CT)	-0.54	12-14	>651	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.75	Horz(CT)	0.22	10	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.20	5	>999	240	Weight: 124 lb	FT = 10%

**LUMBER**

TOP CHORD 2x8 SP DSS \*Except\* 4-7:2x4 SPF 2100F  
1.8E, 7-9:2x4 SPF No.2

BOT CHORD 2x4 SPF No.2 \*Except\* 5-14:2x3 SPF No.2

WEBS 2x3 SPF No.2 \*Except\* 12-15,10-8:2x4 SPF  
No.2

## BRACING

TOP CHORD	Structural wood sheathing directly applied or 3-8-6 oc purlins, except end verticals, and 2-0-0 oc purlins (2-4-4 max.): 4-7.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

## REACTIONS

(lb/size) 2=1402/0-3-8, 10=1390/0-3-8  
Max Horiz 2=57 (LC 7)  
Max Uplift 2=-156 (LC 5), 10=-164 (LC 4)

## FORCES

	Tension
TOP CHORD	1-2=0/6, 2-3=-806/121, 3-4=-2992/431, 4-5=-3855/644, 5-6=-3836/651, 6-7=-3287/549, 7-8=-2141/302, 8-9=0/32, 8-10=-1345/185
BOT CHORD	2-17=-26/0, 3-16=-396/2799, 15-16=-392/2801, 14-15=0/141, 5-15=-372/169, 12-14=-9/259, 11-12=-210/1850, 10-11=-104/346
WEBS	3-17=0/54, 4-16=0/152, 4-15=-299/1299, 12-15=-503/3050, 6-15=-115/596, 6-12=-798/289, 7-12=-322/1610, 7-11=-45/148, 8-11=-220/1513

## NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDF=6.0psf; BCDF=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone: cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.

- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 156 lb uplift at joint 2 and 164 lb uplift at joint 10.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021



Design valid for use only with MiTEK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personnel injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Code**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	147674112
210529	H5	Hip Girder	1	2	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:31  
ID:yZSiXNzPi3L84nJo9\_fWoz1j9S-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWRCDoi7J4zJC?#

Page: 1



Scale = 1:56.4

Plate Offsets (X, Y): [2:Edge,0-0-15], [3:0-11-3,0-0-5-0], [4:0-7-4,0-2-8], [9:0-3-2,Edge], [12:0-2-12,0-4-8], [16:0-3-8,0-3-0], [18:0-3-12,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.95	Vert(LL)	-0.36	18	>973	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.39	Vert(CT)	-0.66	18	>529	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.80	Horz(CT)	0.21	12	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.32	18	>999	240	Weight: 321 lb	FT = 10%

**LUMBER**  
TOP CHORD 2x4 SPF No.2 \*Except\* 1-4:2x6 SP DSS, 4-6:2x4 SPF 2100F 1.8E  
BOT CHORD 2x6 SP 2400F 2.0E \*Except\* 20-3:2x4 SPF No.2  
WEBS 2x4 SPF No.2

**BRACING**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (2-10-9 max.): 4-9.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-20.

**REACTIONS** (lb/size) 2=2300/0-3-8, 12=2268/0-3-8  
Max Horiz 2=45 (LC 7)  
Max Uplift 2=394 (LC 5), 12=416 (LC 4)

**FORCES** (lb) - Maximum Compression/Maximum Tension  
TOP CHORD 1-2=0/6, 2-3=-1448/281, 3-4=-6550/1252, 4-5=-10211/2072, 5-7=-9682/1980, 7-8=-6264/1290, 8-9=-6268/1292, 9-10=-3723/736, 10-11=0/32, 10-12=-2192/415  
BOT CHORD 2-20=-165/20, 3-20=-33/273, 3-19=-1157/6085, 18-19=-1164/6173, 16-17=-152/779, 14-16=-1435/7224, 13-14=-617/3293, 12-13=-127/594  
WEBS 17-18=0/214, 5-18=-412/235, 4-19=-65/806, 4-18=-954/4257, 16-18=-1302/6544, 7-18=-534/2525, 7-16=-885/351, 7-14=-1060/203, 8-14=-724/332, 9-14=-684/3252, 9-13=0/163, 10-13=-547/2725

**NOTES**

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc.  
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 394 lb uplift at joint 2 and 416 lb uplift at joint 12.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Use Simpson Strong-Tie TJC37 (6 nail 90-150) or equivalent at 3-11-8 from the left end to connect truss (es) to back face of bottom chord, skewed 33.7 deg.to the right, sloping 0.0 deg. down.

- Use Simpson Strong-Tie TJC37 (4 nail, 30-90) or equivalent at 25-7-8 from the left end to connect truss (es) to back face of bottom chord, skewed 33.7 deg.to the left, sloping 0.0 deg. down.
  - Fill all nail holes where hanger is in contact with lumber.
  - "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe nails per NDS guidelines.
- LOAD CASE(S)** Standard  
1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-3=-70, 3-4=-70, 4-9=-70, 9-10=-70, 10-11=-70, 2-20=-20, 3-18=-20, 12-19=-20  
Concentrated Loads (lb)  
Vert: 18=-35 (B), 5=-83 (B), 19=-240 (B), 13=-224 (B), 21=-76 (B), 22=-76 (B), 23=-83 (B), 24=-83 (B), 25=-83 (B), 26=-83 (B), 27=-83 (B), 28=-83 (B), 29=-83 (B), 30=-83 (B), 31=-49 (B), 32=-49 (B), 33=-35 (B), 34=-35 (B), 35=-35 (B), 36=-35 (B), 37=-35 (B), 38=-35 (B), 39=-35 (B), 40=-35 (B)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J4	Jack-Closed Supported Gable	2	1	Job Reference (optional)	I47674113

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:31  
ID:cF8hBeJsXlzbRZ0yGz\_j7qz1leq-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?i

Page: 1



Scale = 1:27.1

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.03	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(CT)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	4	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 5 lb FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x3 SPF No.2

8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 1-6-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=93/1-6-0, 4=59/1-6-0  
Max Horiz 2=39 (LC 5)  
Max Uplift 2=14 (LC 8), 4=18 (LC 8)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-6/0, 2-3=-43/21, 3-4=-45/26  
BOT CHORD 2-4=-14/10

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 2-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 18 lb uplift at joint 4 and 14 lb uplift at joint 2.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J5	Jack-Closed	2	1	Job Reference (optional)	I47674114

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:31  
ID:RyYpaKoy62?wEi3ecNi5IGz1leC-RfC?PsB70Hq3NSgPqnL8w3uTXbGKWrCDoi7J4zJC?f

Page: 1



<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.02	Vert(LL)	0.00	2-4	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	0.00	2-4	>999	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 5 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x3 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
1-6-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 2=94/0-3-8, 4=57/ Mechanical  
Max Horiz 2=39 (LC 5)  
Max Uplift 2=-15 (LC 8), 4=-17 (LC 8)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 1-2=-6/0, 2-3=-43/21, 3-4=-44/25  
BOT CHORD 2-4=-14/10

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 17 lb uplift at joint  
4 and 15 lb uplift at joint 2.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J6	Jack-Open Girder	2	1	Job Reference (optional)	I47674115

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:31  
ID:romNn91VOBX5dnbUna3nZUz1Idu-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?i

Page: 1



Scale = 1:30.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.49	Vert(LL)	-0.01	4-5	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.11	Vert(CT)	-0.01	4-5	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.01	3	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	-0.01	4-5	>999	240	Weight: 12 lb FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 4-1-6 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS

(lb/size) 3=67/ Mechanical, 4=15/  
Mechanical, 5=386/0-4-8  
Max Horiz 5=58 (LC 4)  
Max Uplift 3=-37 (LC 8), 5=-157 (LC 4)  
Max Grav 3=67 (LC 1), 4=56 (LC 3), 5=386 (LC 1)

#### FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-337/174, 1-2=0/44, 2-3=-44/11  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 157 lb uplift at joint 5 and 37 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

- 7) "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
  - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 4-5=-20  
Concentrated Loads (lb)  
Vert: 7=2 (F)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Page: 1

**LUMBER**


## BRACING

<b>REACTIONS</b>	(lb/size)	3=78/ Mechanical, 4=28/ Mechanical, 5=205/0-3-8
Max Horiz		5=53 (LC 8)
Max Uplift		3=-43 (LC 8), 5=-31 (LC 8)
Max Grav		3=78 (LC 1), 4=49 (LC 3), 5=205 (LC 1)

TOP CHORD 2-5=-180/57, 1-2=0/27, 2-3=-46/23  
BOT CHORD 4-5=0/0

## NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 31 lb uplift at joint 5 and 43 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

A circular professional engineer seal for the State of Missouri. The outer ring contains the text "STATE OF MISSOURI" at the top and "PROFESSIONAL ENGINEER" at the bottom, separated by two stars. In the center, the name "JUAN GARCIA" is displayed above the number "E-2000162101". The seal is blue and white.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Code**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J8	Jack-Open	2	1	Job Reference (optional)	I47674117

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:32  
ID:z1Wsxo\_Ky0f99ljYk\_rOez1dy-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:28.1

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 5 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 1-8-1 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS

(lb/size) 3=34/ Mechanical, 4=10/  
Mechanical, 5=164/0-3-8  
Max Horiz 5=37 (LC 5)  
Max Uplift 3=24 (LC 8), 5=34 (LC 4)  
Max Grav 3=34 (LC 1), 4=27 (LC 3), 5=164 (LC 1)

#### FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-143/46, 1-2=0/27, 2-3=-28/9  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 34 lb uplift at joint 5 and 24 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J9	Diagonal Hip Girder	2	1	Job Reference (optional)	I47674118

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:32  
ID:?swo8jWev2w3OMI?YlLOnz1kw4-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:35.7

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.03	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.24	Vert(CT)	-0.06	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.02	4-5	>999	240	Weight: 19 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x4 SPF No.2 *Except* 3-4:2x3 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(lb/size) 4=187/ Mechanical, 5=487/0-3-8
	Max Horiz 5=133 (LC 5)
	Max Uplift 4=-54 (LC 5), 5=-190 (LC 4)

FORCES	(lb) - Maximum Compression/Maximum Tension
--------	--

TOP CHORD	2-5=-429/217, 1-2=0/55, 2-3=-116/19, 3-4=-137/68
BOT CHORD	4-5=-39/50

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 190 lb uplift at joint 5 and 54 lb uplift at joint 4.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 7) "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.

- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 4-5=-20  
Concentrated Loads (lb)  
Vert: 7=-3 (F)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J10	Jack-Open	7	1	Job Reference (optional)	I47674119

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:32  
ID:XMp160e\_XYkRYz6?RxxRJ1z1laW-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRCDoi7J4zJC?f

Page: 1



Scale = 1:26.7

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.35	Vert(LL)	-0.02	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.21	Vert(CT)	-0.06	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.04	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.03	4-5	>999	240	Weight: 14 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
5-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=150/ Mechanical, 4=58/  
Mechanical, 5=295/0-3-8  
Max Horiz 5=85 (LC 8)  
Max Uplift 3=80 (LC 8), 5=34 (LC 8)  
Max Grav 3=150 (LC 1), 4=91 (LC 3), 5=295  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-256/81, 1-2=0/27, 2-3=-80/45  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 34 lb uplift at joint  
5 and 80 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J11	Jack-Open	2	1	Job Reference (optional)	I47674120

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:32  
ID:P73YyOhVanFt0aQmgn?NTtz1laS-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:24.8

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	-0.01	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 9 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF 2400F 2.0E

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
2-10-15 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=80/ Mechanical, 4=29/  
Mechanical, 5=207/0-3-8  
Max Horiz 5=58 (LC 5)  
Max Uplift 3=-47 (LC 8), 5=-26 (LC 4)  
Max Grav 3=80 (LC 1), 4=50 (LC 3), 5=207  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-181/54, 1-2=0/27, 2-3=-47/23  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 26 lb uplift at joint  
5 and 47 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
T210529	J12	Jack-Open	1	1	Job Reference (optional)	I47674121

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:33  
ID:LVAIN4j16OVbGuZ9nC2rY1z1aQ-RfC?PsB70Hq3NSgPqnL8w3u1TXbGKWrCDoi7J4zJC?f

Page: 1



<b>Loading</b>	(psf)	<b>Spacing</b>	2'-0'-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.07	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 8 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF 2400F 2.0E

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
1'-10'-15 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10'-0'-0 oc  
bracing.

**REACTIONS** (lb/size) 3=1/ Mechanical, 4=-4/ Mechanical,  
5=302/0-3-8  
Max Horiz 5=65 (LC 5)  
Max Uplift 3=-23 (LC 8), 4=-6 (LC 5), 5=-74  
(LC 4)  
Max Grav 3=8 (LC 19), 4=27 (LC 3), 5=302  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-263/90, 1-2=0/54, 2-3=-47/2  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3'-06'-00 tall by 2'-00'-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 74 lb uplift at joint  
5, 6 lb uplift at joint 4 and 23 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674122
210529	J13	Jack-Open	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:33  
ID:pgfwZi4WmzHPDCpPFIqh7z1kxJ-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:22.9

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	0.00	3-4	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	0.00	3-4	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.01	2	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	3-4	>999	240	Weight: 6 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
1-10-15 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 2=59/ Mechanical, 3=20/  
Mechanical, 4=79/ Mechanical  
Max Horiz 4=47 (LC 5)  
Max Uplift 2=-37 (LC 8), 3=-4 (LC 5)  
Max Grav 2=59 (LC 1), 3=34 (LC 3), 4=79  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 1-4=-64/14, 1-2=-29/18  
BOT CHORD 3-4=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 37 lb uplift at joint  
2 and 4 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J14	Jack-Closed Girder	1	1	Job Reference (optional)	I47674123

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:33  
ID:0mcn7PyHtcwB9fLs0rlFitz1kuD-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKwRCDoi7J4zJC?f

Page: 1



Scale = 1:28.4

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.57	Vert(LL)	-0.08	2-4	>750	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.86	Vert(CT)	-0.14	2-4	>409	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P		Wind(LL)	0.06	2-4	>886	240	Weight: 20 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x6 SP DSS  
WEBS 2x3 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 4-10-2 oc bracing.

**REACTIONS** (lb/size) 2=894/0-3-8, 4=1097/ Mechanical  
Max Horiz 2=85 (LC 5)  
Max Uplift 2=-201 (LC 4), 4=-248 (LC 8)

**FORCES** (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/1, 2-3=-77/47, 3-4=-159/74  
BOT CHORD 2-4=-27/21

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 248 lb uplift at joint 4 and 201 lb uplift at joint 2.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

- 7) Use Simpson Strong-Tie HUS26 (14-10d Girder, 6-10d Truss, Single Ply Girder) or equivalent at 3-0-12 from the left end to connect truss(es) to back face of bottom chord, skewed 0.0 deg.to the right, sloping 0.0 deg. down.
- 8) Fill all nail holes where hanger is in contact with lumber.
- 9) "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
- 10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-3=-70, 2-4=-20  
Concentrated Loads (lb)  
Vert: 5=-60 (B), 6=-1432 (B)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J15	Diagonal Hip Girder	1	1	Job Reference (optional)	I47674124

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:33  
ID:11QjYD0FsErLHA8xXiyk0z1kvA-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:33.2

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.63	Vert(LL)	-0.03	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.23	Vert(CT)	-0.06	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	-0.02	4-5	>999	240	Weight: 18 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x4 SPF No.2 *Except* 3-4:2x3 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(lb/size) 4=187/ Mechanical, 5=487/0-3-8
	Max Horiz 5=95 (LC 5)
	Max Uplift 4=-34 (LC 8), 5=-187 (LC 4)

FORCES	(lb) - Maximum Compression/Maximum Tension
--------	--

TOP CHORD	2-5=-428/217, 1-2=0/45, 2-3=-107/11, 3-4=-137/63
BOT CHORD	4-5=-26/58


#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 187 lb uplift at joint 5 and 34 lb uplift at joint 4.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 7) "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.

- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 4-5=-20  
Concentrated Loads (lb)  
Vert: 7=-3 (B)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J16	Jack-Open	1	1	Job Reference (optional)	I47674125

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:33  
ID:i33?pyraYLKE7WJBdWeh\_Tz1kvf-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRCDoi7J4zJC?f

Page: 1



Scale = 1:22.6

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	-0.01	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 8 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
2-10-15 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=80/ Mechanical, 4=29/  
Mechanical, 5=207/0-3-8  
Max Horiz 5=48 (LC 4)  
Max Uplift 3=39 (LC 8), 5=61 (LC 4)  
Max Grav 3=80 (LC 1), 4=50 (LC 3), 5=207  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=181/84, 1-2=0/23, 2-3=37/19  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 61 lb uplift at joint  
5 and 39 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
T210529	J17	Jack-Open	1	1	Job Reference (optional)	I47674126

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:33  
ID:bqlWfJu4cZqgc7cysMjd8Jz1kvb-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?i

Page: 1



Scale = 1:21.4

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.08	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 7 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### LOAD CASE(S) Standard

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
1-10-15 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=2/ Mechanical, 4=-5/ Mechanical,  
5=302/0-3-8  
Max Horiz 5=48 (LC 4)  
Max Uplift 3=-14 (LC 8), 4=-5 (LC 1), 5=-130  
(LC 4)  
Max Grav 3=5 (LC 19), 4=26 (LC 3), 5=302  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-262/137, 1-2=0/45, 2-3=-38/1  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 130 lb uplift at  
joint 5, 5 lb uplift at joint 4 and 14 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J18	Jack-Open	3	1	Job Reference (optional)	I47674127

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:34  
ID:XDQG3?vK7B4OrRmLznI5Dkz1kvZ-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWRCDoi7J4zJC?f

Page: 1



Scale = 1:24.1

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.35	Vert(LL)	-0.02	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.21	Vert(CT)	-0.05	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.02	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.02	4-5	>999	240	Weight: 13 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
5-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=150/ Mechanical, 4=58/  
Mechanical, 5=295/0-3-8  
Max Horiz 5=77 (LC 4)  
Max Uplift 3=69 (LC 8), 5=71 (LC 4)  
Max Grav 3=150 (LC 1), 4=90 (LC 3), 5=295  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-257/113, 1-2=0/23, 2-3=-64/37  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 71 lb uplift at joint  
5 and 69 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
T210529	J19	Diagonal Hip Girder	2	1	Job Reference (optional)	I47674128

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:34  
ID:CuoGng7SmlVYYX8fZ0lpe4z1kD-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:44.1

Plate Offsets (X, Y): [4:Edge,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.50	Vert(LL)	-0.06	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.34	Vert(CT)	-0.12	4-5	>630	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.02	4-5	>999	240	Weight: 20 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x4 SPF No.2 *Except* 3-4:2x3 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(lb/size) 4=248/ Mechanical, 5=463/0-3-11
	Max Horiz 5=116 (LC 7)
	Max Uplift 4=58 (LC 8), 5=164 (LC 4)

#### FORCES

	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	2-5=-412/202, 1-2=0/43, 2-3=-147/17, 3-4=-181/85
BOT CHORD	4-5=-36/59

#### NOTES

- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 164 lb uplift at joint 5 and 58 lb uplift at joint 4.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- "NAILED" indicates 2-12d (0.148"x3.25") toe-nails per NDS guidelines.

- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 4-5=-20  
Concentrated Loads (lb)  
Vert: 8=4 (B), 9=2 (F=3, B=-1)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674129
210529	J20	Diagonal Hip Girder	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:34  
ID:9u4acEOhHico0W5ees9Cs?z1lib-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:33.5

Plate Offsets (X, Y): [2:0-2-8,0-1-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.65	Vert(LL)	0.02	4-5	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.11	Vert(CT)	-0.03	4-5	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.00	4	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	-0.01	4-5	>999	240	Weight: 29 lb FT = 10%

#### LUMBER

TOP CHORD 2x6 SP DSS  
BOT CHORD 2x4 SPF 2400F 2.0E  
WEBS 2x4 SPF No.2 \*Except\* 3-4:2x3 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS** (lb/size) 4=31/ Mechanical, 5=964/0-3-8  
Max Horiz 5=118 (LC 7)  
Max Uplift 4=108 (LC 21), 5=330 (LC 4)  
Max Grav 4=224 (LC 24), 5=964 (LC 1)

**FORCES** (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-897/351, 1-2=-11/133, 2-3=-105/21, 3-4=-145/123

BOT CHORD 4-5=-54/44

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 330 lb uplift at joint 5 and 108 lb uplift at joint 4.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

- 7) "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
  - 8) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 260 lb down and 47 lb up at -2-1-8 on top chord. The design/selection of such connection device(s) is the responsibility of others.
  - 9) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 4-5=-20  
Concentrated Loads (lb)  
Vert: 1=-250, 3=-65 (B), 4=-27 (B), 7=29 (F), 8=11 (B)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J21	Jack-Open	21	1	Job Reference (optional)	I47674130

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:34  
ID: C4C\_4EWTn44nwkr3ptr4Kz1IIO-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcDoi7J4zJC?fi

Page: 1



Scale = 1:23.9

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.37	Vert(LL)	-0.03	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.24	Vert(CT)	-0.07	4-5	>863	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.03	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.03	4-5	>999	240	Weight: 16 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
5-5-4 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=153/ Mechanical, 4=55/  
Mechanical, 5=404/0-3-8  
Max Horiz 5=95 (LC 4)  
Max Uplift 3=75 (LC 8), 5=122 (LC 4)  
Max Grav 3=153 (LC 1), 4=96 (LC 3), 5=404  
(LC 1)


**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-354/165, 1-2=0/45, 2-3=-72/37  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 122 lb uplift at  
joint 5 and 75 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674131
210529	J22	Jack-Open	2	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:35  
ID:ceu7iGYL4?SMn9TQlxRZhyz1lkz-RfC?PsB70Hq3NsgPqnL8w3ulTXbGKWRCDoi7J4zJC?f

Page: 1



Scale = 1:22.5

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	-0.01	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.08	Vert(CT)	-0.01	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 11 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 3-5-12 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** (lb/size) 3=80/ Mechanical, 4=24/ Mechanical, 5=332/0-3-8  
Max Horiz 5=69 (LC 4)  
Max Uplift 3=44 (LC 8), 5=119 (LC 4)  
Max Grav 3=80 (LC 1), 4=58 (LC 3), 5=332 (LC 1)

**FORCES** (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-291/142, 1-2=0/45, 2-3=-48/18  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 119 lb uplift at joint 5 and 44 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
T210529	J23	Jack-Open	2	1	Job Reference (optional)	I47674132

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:35  
ID:1DaFKlaDNwqxdC?Q3\_GJbz1lkW-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?i

Page: 1



Scale = 1:24.1

Plate Offsets (X, Y): [5:0-5-9,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 8 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
2-6-10 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=67/ Mechanical, 4=23/  
Mechanical, 5=192/0-3-8  
Max Horiz 5=57 (LC 8)  
Max Uplift 3=-43 (LC 8), 5=-23 (LC 8)  
Max Grav 3=67 (LC 1), 4=43 (LC 3), 5=192  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-169/48, 1-2=0/32, 2-3=-48/22  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 23 lb uplift at joint  
5 and 43 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017


Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J24	Jack-Open	4	1	Job Reference (optional)	I47674133

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:35  
ID:RoFOzJd6frCWV4wa5BYzxZz1kt-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1

-0-10-8	1-2-10
0-10-8	1-2-10



Scale = 1:27.1

Plate Offsets (X, Y): [5:0-5-9,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	5	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(CT)	0.00	5	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 5 lb FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 1-2-10 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS

(lb/size) 3=11/ Mechanical, 4=2/ Mechanical, 5=154/0-3-8  
Max Horiz 5=36 (LC 5)  
Max Uplift 3=-18 (LC 8), 4=-2 (LC 5), 5=-23 (LC 8)  
Max Grav 3=12 (LC 15), 4=18 (LC 3), 5=154 (LC 1)

#### FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-134/36, 1-2=0/32, 2-3=-28/3  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 23 lb uplift at joint 5, 2 lb uplift at joint 4 and 18 lb uplift at joint 3.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see


ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Wheeler Lumber, Waverly, KS - 66871, Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:35 Page: 1  
ID:nNxWbLf ymb4MYf9mK5aZsz1lka-RfC?PsB70Hg3NSaPnL8w3ulTXbGKWRcDoi7J4zJC?f




## LUMBER


## BRACING

## NOTES

- LOAD CASE(S) Standard



August 30, 2021






Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
T210529	J26	Jack-Open	1	1	Job Reference (optional)	I47674135

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:35  
ID:GycfDNhtFhzfD?OkSSfNBuZ1lkn-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



<b>Loading</b>	(psf)	<b>Spacing</b>	2-0-0	<b>CSI</b>		<b>DEFL</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.08	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 8 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 1-11-12 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** (lb/size) 3=7/ Mechanical, 4=-3/ Mechanical, 5=302/0-5-8  
Max Horiz 5=49 (LC 4)  
Max Uplift 3=-16 (LC 8), 4=-3 (LC 1), 5=-128 (LC 4)  
Max Grav 3=7 (LC 1), 4=28 (LC 3), 5=302 (LC 1)

**FORCES** (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-262/136, 1-2=0/45, 2-3=-38/1  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 128 lb uplift at joint 5, 3 lb uplift at joint 4 and 16 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017


Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J27	Jack-Open	1	1	Job Reference (optional)	I47674136

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:35

Page: 1

ID:gXlosOkYcLE4T6J7aC4o6z1lkk-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f



Scale = 1:23

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.29	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 7 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 1-6-10 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS

(lb/size) 3=-30/ Mechanical, 4=-10/ Mechanical, 5=307/0-5-8  
Max Horiz 5=60 (LC 5)  
Max Uplift 3=-30 (LC 1), 4=-10 (LC 16), 5=-53 (LC 8)  
Max Grav 3=10 (LC 4), 4=20 (LC 3), 5=307 (LC 1)

#### FORCES

(lb) - Maximum Compression/Maximum Tension  
TOP CHORD 2-5=-269/74, 1-2=0/63, 2-3=-57/4  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 53 lb uplift at joint 5, 10 lb uplift at joint 4 and 30 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
T210529	J28	Diagonal Hip Girder	1	1	Job Reference (optional)	I47674137

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:36  
ID:xzcSQbu1Ocuq3zli6gv2Zsz1lhx-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:40

Plate Offsets (X, Y): [5:Edge,0-2-8], [6:0-2-0,0-0-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.43	Vert(LL)	-0.05	5-6	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.38	Vert(CT)	-0.11	5-6	>708	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.03	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.05	5-6	>999	240	Weight: 22 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2 \*Except\* 7-6:2x3 SPF No.2  
WEBS 2x4 SPF No.2 \*Except\* 4-5:2x3 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** (lb/size) 5=264/ Mechanical, 8=473/0-3-11  
Max Horiz 8=99 (LC 5)  
Max Uplift 5=66 (LC 8), 8=166 (LC 4)

#### FORCES

(lb) - Maximum Compression/Maximum Tension  
TOP CHORD 2-8=-440/184, 1-2=0/43, 2-3=-182/24,  
3-4=-168/20, 4-5=-159/68  
BOT CHORD 7-8=-50/92, 6-7=0/60, 3-6=-8/29, 5-6=-31/99

#### NOTES

- Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 166 lb uplift at joint 8 and 66 lb uplift at joint 5.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.

- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-4=-70, 7-8=-20, 5-6=-20  
Concentrated Loads (lb)  
Vert: 11=4 (F), 13=-23 (F=-24, B=1)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J29	Jack-Open	2	1	Job Reference (optional)	I47674138

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:36  
ID:NeJIFNE1C0A2fAUQDTzSeTz1IIN-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:24.8

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	-0.03	5-6	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.26	Vert(CT)	-0.08	5-6	>821	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.03	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.04	5-6	>999	240	Weight: 18 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2 \*Except\* 7-6:2x3 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 5-5-4 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** (lb/size) 4=146/ Mechanical, 5=69/ Mechanical, 8=423/0-3-8  
Max Horiz 8=95 (LC 4)  
Max Uplift 4=63 (LC 8), 8=111 (LC 4)  
Max Grav 4=146 (LC 1), 5=104 (LC 3), 8=423 (LC 1)

**FORCES** (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-8=-396/134, 1-2=0/45, 2-3=-115/0, 3-4=-53/36  
BOT CHORD 7-8=-39/39, 6-7=-1/39, 3-6=-39/39, 5-6=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 111 lb uplift at joint 8 and 63 lb uplift at joint 4.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J30	Jack-Open	1	1	Job Reference (optional)	I47674139

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:36  
ID:UcYMRB\_s8ZX1exNOUZ5Xl2z1lli-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:28.6

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	0.00	7	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	-0.01	7	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	5	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	3-6	>999	240	Weight: 13 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2 \*Except\* 7-6:2x3 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
3-5-12 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc  
bracing.

**REACTIONS** (lb/size) 4=80/ Mechanical, 5=35/  
Mechanical, 8=347/0-3-8  
Max Horiz 8=69 (LC 4)  
Max Uplift 4=-35 (LC 8), 8=-110 (LC 4)  
Max Grav 4=80 (LC 1), 5=73 (LC 3), 8=347  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-8=-315/126, 1-2=0/45, 2-3=-51/0,  
3-4=-30/20  
BOT CHORD 7-8=-10/20, 6-7=0/38, 3-6=-20/10, 5-6=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 110 lb uplift at joint  
8 and 35 lb uplift at joint 4.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017



Wheeler Lumber, Waverly, KS - 66871, Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:36 Page: 1  
ID:cZnPR0jh56u0dIGMmfDcxzc1m1-RfC?PsB70Hq3NSaPanL8w3u1tXhGKWRCDoi7J4zJC?f




Plate Offsets (X, Y): [8:0-5-9.0-1-8]

**LUMBER**

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2 *Except* 7-6:2x3 SPF No.2
WEBS	2x4 SPF No.2

6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

## BRACING

TOP CHORD	Structural wood sheathing directly applied or 2-6-10 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

## REACTIONS

(lb/size)	4=56/ Mechanical, 5=48/ Mechanical, 8=202/0-3-8
Max Horiz	8=57 (LC 8)
Max Uplift	4=29 (LC 8), 5=2 (LC 8), 8=17 (LC 8)
Max Grav	4=56 (LC 1), 5=73 (LC 3), 8=202 (LC 1)


## FORCES

(Ib) - Maximum Compression/Maximum Tension

TOP CHORD 2-8=-181/38, 1-2=0/32, 2-3=-61/0, 3-4=-24/21  
BOT CHORD 7-8=-14/19, 6-7=0/41, 3-6=-19/14, 5-6=0/0

## NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate girf DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 17 lb uplift at joint 8, 29 lb uplift at joint 4 and 2 lb uplift at joint 5.



August 30, 2021



**WARNING – Velly design parameters are listed below and included with the key reference to AISC M14-15 16f, 17f, 18f, 19f, 20f, 21f, 22f, 23f, 24f, 25f, 26f, 27f, 28f, 29f, 30f, 31f, 32f, 33f, 34f, 35f, 36f, 37f, 38f, 39f, 40f, 41f, 42f, 43f, 44f, 45f, 46f, 47f, 48f, 49f, 50f, 51f, 52f, 53f, 54f, 55f, 56f, 57f, 58f, 59f, 60f, 61f, 62f, 63f, 64f, 65f, 66f, 67f, 68f, 69f, 70f, 71f, 72f, 73f, 74f, 75f, 76f, 77f, 78f, 79f, 80f, 81f, 82f, 83f, 84f, 85f, 86f, 87f, 88f, 89f, 90f, 91f, 92f, 93f, 94f, 95f, 96f, 97f, 98f, 99f, 100f, 101f, 102f, 103f, 104f, 105f, 106f, 107f, 108f, 109f, 110f, 111f, 112f, 113f, 114f, 115f, 116f, 117f, 118f, 119f, 120f, 121f, 122f, 123f, 124f, 125f, 126f, 127f, 128f, 129f, 130f, 131f, 132f, 133f, 134f, 135f, 136f, 137f, 138f, 139f, 140f, 141f, 142f, 143f, 144f, 145f, 146f, 147f, 148f, 149f, 150f, 151f, 152f, 153f, 154f, 155f, 156f, 157f, 158f, 159f, 160f, 161f, 162f, 163f, 164f, 165f, 166f, 167f, 168f, 169f, 170f, 171f, 172f, 173f, 174f, 175f, 176f, 177f, 178f, 179f, 180f, 181f, 182f, 183f, 184f, 185f, 186f, 187f, 188f, 189f, 190f, 191f, 192f, 193f, 194f, 195f, 196f, 197f, 198f, 199f, 200f, 201f, 202f, 203f, 204f, 205f, 206f, 207f, 208f, 209f, 210f, 211f, 212f, 213f, 214f, 215f, 216f, 217f, 218f, 219f, 220f, 221f, 222f, 223f, 224f, 225f, 226f, 227f, 228f, 229f, 230f, 231f, 232f, 233f, 234f, 235f, 236f, 237f, 238f, 239f, 240f, 241f, 242f, 243f, 244f, 245f, 246f, 247f, 248f, 249f, 250f, 251f, 252f, 253f, 254f, 255f, 256f, 257f, 258f, 259f, 260f, 261f, 262f, 263f, 264f, 265f, 266f, 267f, 268f, 269f, 270f, 271f, 272f, 273f, 274f, 275f, 276f, 277f, 278f, 279f, 280f, 281f, 282f, 283f, 284f, 285f, 286f, 287f, 288f, 289f, 290f, 291f, 292f, 293f, 294f, 295f, 296f, 297f, 298f, 299f, 300f, 301f, 302f, 303f, 304f, 305f, 306f, 307f, 308f, 309f, 310f, 311f, 312f, 313f, 314f, 315f, 316f, 317f, 318f, 319f, 320f, 321f, 322f, 323f, 324f, 325f, 326f, 327f, 328f, 329f, 330f, 331f, 332f, 333f, 334f, 335f, 336f, 337f, 338f, 339f, 340f, 341f, 342f, 343f, 344f, 345f, 346f, 347f, 348f, 349f, 350f, 351f, 352f, 353f, 354f, 355f, 356f, 357f, 358f, 359f, 360f, 361f, 362f, 363f, 364f, 365f, 366f, 367f, 368f, 369f, 370f, 371f, 372f, 373f, 374f, 375f, 376f, 377f, 378f, 379f, 380f, 381f, 382f, 383f, 384f, 385f, 386f, 387f, 388f, 389f, 390f, 391f, 392f, 393f, 394f, 395f, 396f, 397f, 398f, 399f, 400f, 401f, 402f, 403f, 404f, 405f, 406f, 407f, 408f, 409f, 410f, 411f, 412f, 413f, 414f, 415f, 416f, 417f, 418f, 419f, 420f, 421f, 422f, 423f, 424f, 425f, 426f, 427f, 428f, 429f, 430f, 431f, 432f, 433f, 434f, 435f, 436f, 437f, 438f, 439f, 440f, 441f, 442f, 443f, 444f, 445f, 446f, 447f, 448f, 449f, 450f, 451f, 452f, 453f, 454f, 455f, 456f, 457f, 458f, 459f, 460f, 461f, 462f, 463f, 464f, 465f, 466f, 467f, 468f, 469f, 470f, 471f, 472f, 473f, 474f, 475f, 476f, 477f, 478f, 479f, 480f, 481f, 482f, 483f, 484f, 485f, 486f, 487f, 488f, 489f, 490f, 491f, 492f, 493f, 494f, 495f, 496f, 497f, 498f, 499f, 500f, 501f, 502f, 503f, 504f, 505f, 506f, 507f, 508f, 509f, 510f, 511f, 512f, 513f, 514f, 515f, 516f, 517f, 518f, 519f, 520f, 521f, 522f, 523f, 524f, 525f, 526f, 527f, 528f, 529f, 530f, 531f, 532f, 533f, 534f, 535f, 536f, 537f, 538f, 539f, 540f, 541f, 542f, 543f, 544f, 545f, 546f, 547f, 548f, 549f, 550f, 551f, 552f, 553f, 554f, 555f, 556f, 557f, 558f, 559f, 560f, 561f, 562f, 563f, 564f, 565f, 566f, 567f, 568f, 569f, 570f, 571f, 572f, 573f, 574f, 575f, 576f, 577f, 578f, 579f, 580f, 581f, 582f, 583f, 584f, 585f, 586f, 587f, 588f, 589f, 590f, 591f, 592f, 593f, 594f, 595f, 596f, 597f, 598f, 599f, 600f, 601f, 602f, 603f, 604f, 605f, 606f, 607f, 608f, 609f, 610f, 611f, 612f, 613f, 614f, 615f, 616f, 617f, 618f, 619f, 620f, 621f, 622f, 623f, 624f, 625f, 626f, 627f, 628f, 629f, 630f, 631f, 632f, 633f, 634f, 635f, 636f, 637f, 638f, 639f, 640f, 641f, 642f, 643f, 644f, 645f, 646f, 647f, 648f, 649f, 650f, 651f, 652f, 653f, 654f, 655f, 656f, 657f, 658f, 659f, 660f, 661f, 662f, 663f, 664f, 665f, 666f, 667f, 668f, 669f, 670f, 671f, 672f, 673f, 674f, 675f, 676f, 677f, 678f, 679f, 680f, 681f, 682f, 683f, 684f, 685f, 686f, 687f, 688f, 689f, 690f, 691f, 692f, 693f, 694f, 695f, 696f, 697f, 698f, 699f, 700f, 701f, 702f, 703f, 704f, 705f, 706f, 707f,**




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674141
210529	J32	Jack-Open Girder	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:36  
ID:M09krV?2DgKXQUhQF28XVzz1lmz-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:26.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.27	Vert(LL)	0.00	4-5	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.07	Vert(CT)	0.00	4-5	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 7 lb FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 1-7-12 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS

(lb/size) 3=-43/ Mechanical, 4=-20/ Mechanical, 5=175/0-3-11  
Max Horiz 5=51 (LC 7)  
Max Uplift 3=-43 (LC 1), 4=-20 (LC 1), 5=-146 (LC 6)  
Max Grav 3=33 (LC 4), 4=17 (LC 4), 5=175 (LC 1)

#### FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-149/147, 1-2=-5/23, 2-3=-18/9  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 146 lb uplift at joint 5, 20 lb uplift at joint 4 and 43 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

- 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 25 lb down and 9 lb up at -2-1-8, and 25 lb down and 9 lb up at -2-1-8 on top chord. The design/selection of such connection device(s) is the responsibility of others.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Concentrated Loads (lb)  
Vert: 1=-38 (F=-19, B=-19)  
Trapezoidal Loads (lb/ft)  
Vert: 1=0 (F=35, B=35)-to-2=-40 (F=15, B=15), 2=-3 (F=34, B=34)-to-3=-29 (F=21, B=21), 5=0 (F=10, B=10)-to-4=-8 (F=6, B=6)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674142
210529	J33	Jack-Open	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:37  
ID:QNVYs?m8hrxDeZkAdZi4Eyz1lnG-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:21

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.07	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 6 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
1-5-4 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=-38/ Mechanical, 4=-16/  
Mechanical, 5=311/0-3-8  
Max Horiz 5=43 (LC 5)  
Max Uplift 3=-38 (LC 1), 4=-16 (LC 1), 5=-143  
(LC 4)  
Max Grav 3=22 (LC 4), 4=16 (LC 3), 5=311  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-269/145, 1-2=0/45, 2-3=-40/7  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 143 lb uplift at  
joint 5, 16 lb uplift at joint 4 and 38 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J34	Jack-Open Girder	2	1	Job Reference (optional)	I47674143

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:37  
ID:u4p7U73lUKxV2MG50XodzAyy7Pq-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwRCDoi7J4zJC?f

Page: 1



Scale = 1:27.8

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	0.00	4-5	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	0.00	4-5	>999	240	197/144
BCLL	0.0 *	Rep Stress Incr	NO	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 10 lb FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 3-5-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS

(lb/size) 3=44/ Mechanical, 4=6/ Mechanical, 5=345/0-3-8  
Max Horiz 5=52 (LC 4)  
Max Uplift 3=28 (LC 8), 5=146 (LC 4)  
Max Grav 3=44 (LC 1), 4=44 (LC 3), 5=345 (LC 1)

#### FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-302/156, 1-2=0/43, 2-3=-39/7  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 146 lb uplift at joint 5 and 28 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

- 7) "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
  - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 4-5=-20  
Concentrated Loads (lb)  
Vert: 7=4 (F)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017


Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674144
T210529	J35	Jack-Open	3	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:37  
ID:3ewQfGnKvF2mnp0gACtDYJyy7QB-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRCDoi7J4zJC?f

Page: 1

-0-10-8	2-0-0
0-10-8	2-0-0



Scale = 1:23.5

Plate Offsets (X, Y): [5:0-5-9,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 7 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
2-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=48/ Mechanical, 4=15/  
Mechanical, 5=174/0-3-8  
Max Horiz 5=47 (LC 8)  
Max Uplift 3=-34 (LC 8), 5=-22 (LC 8)  
Max Grav 3=48 (LC 1), 4=33 (LC 3), 5=174  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-153/42, 1-2=0/32, 2-3=-39/16  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 22 lb uplift at joint  
5 and 34 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J36	Jack-Open	1	1	Job Reference (optional)	I47674145

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:37  
ID:?mWmW8cwRe9uUWNooZ6iR9yy7QQ-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:22.9

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.01	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 5 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x3 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
1-5-4 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=24/ Mechanical, 4=10/  
Mechanical, 5=153/0-3-8  
Max Horiz 5=38 (LC 5)  
Max Uplift 3=24 (LC 8), 5=21 (LC 8)  
Max Grav 3=24 (LC 1), 4=24 (LC 3), 5=153  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-137/37, 1-2=0/31, 2-3=-31/7  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 21 lb uplift at joint  
5 and 24 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017


Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J37	Diagonal Hip Girder	2	1	Job Reference (optional)	I47674146

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:37

Page: 1

ID:zi19zGyGCSD3fcDziGLfY7jciX-RfC?PsB70Hq3NSgPqnL8w3uTXbGKwRCDoi7J4zJC?f



Scale = 1:23.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	-0.01	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	-0.02	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.01	4-5	>999	240	Weight: 11 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 4-1-7 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS

(lb/size) 3=80/ Mechanical, 4=24/ Mechanical, 5=144/0-4-9  
Max Horiz 5=63 (LC 12)  
Max Uplift 3=-48 (LC 12), 5=-92 (LC 6)  
Max Grav 3=80 (LC 1), 4=60 (LC 3), 5=144 (LC 1)

#### FORCES

(lb) - Maximum Compression/Maximum Tension  
TOP CHORD 2-5=-128/119, 1-2=-6/21, 2-3=-30/15  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 92 lb uplift at joint 5 and 48 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

- 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 30 lb down and 11 lb up at -1-2-14, and 30 lb down and 11 lb up at -1-2-14 on top chord. The design/selection of such connection device(s) is the responsibility of others.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

#### LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Concentrated Loads (lb)  
Vert: 1=-46 (F=-23, B=-23)  
Trapezoidal Loads (lb/ft)  
Vert: 1=0 (F=35, B=35)-to-2=-24 (F=23, B=23), 2=-3 (F=34, B=34)-to-3=-72 (F=-1, B=-1), 5=0 (F=10, B=10)-to-4=-21 (F=0, B=0)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	J38	Jack-Open	5	1	Job Reference (optional)	I47674147

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:38  
ID:8G8S8PgrcOJKP4zYsxQG6Hyjciu-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:23.7

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.10	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	-0.01	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 9 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or  
3-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc  
bracing.

**REACTIONS** (lb/size) 3=83/ Mechanical, 4=30/  
Mechanical, 5=210/0-3-8  
Max Horiz 5=55 (LC 8)  
Max Uplift 3=-45 (LC 8), 5=-32 (LC 8)  
Max Grav 3=83 (LC 1), 4=52 (LC 3), 5=210  
(LC 1)

**FORCES** (lb) - Maximum Compression/Maximum  
Tension

TOP CHORD 2-5=-184/58, 1-2=0/27, 2-3=-48/24  
BOT CHORD 4-5=0/0

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed; end vertical left and  
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom  
chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf  
on the bottom chord in all areas where a rectangle  
3-06-00 tall by 2-00-00 wide will fit between the bottom  
chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to  
bearing plate capable of withstanding 32 lb uplift at joint  
5 and 45 lb uplift at joint 3.
- 6) This truss is designed in accordance with the 2018  
International Residential Code sections R502.11.1 and  
R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	I47674148
210529	K1	Hip Girder	1	2	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:38  
ID: \_muX547n7qBzJofskZAvNyy77k-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?i

Page: 1



Scale = 1:39.5

Plate Offsets (X, Y): [3:0-6-0,0-2-0], [5:0-5-12,0-2-0], [8:Edge,0-5-12], [12:0-3-4,0-2-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.46	Vert(LL)	-0.08	9-10	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.38	Vert(CT)	-0.14	9-10	>925	240	M18SHS	197/144
BCLL	0.0*	Rep Stress Incr	NO	WB	0.66	Horz(CT)	0.01	8	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S		Wind(LL)	0.05	9-10	>999	240	Weight: 122 lb	FT = 10%

#### LUMBER

TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x6 SP 2400F 2.0E  
WEBS 2x4 SPF No.2 \*Except\* 12-2:2x6 SPF No.2, 8-6:2x3 SPF No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 4-9-10 oc purlins, except end verticals, and 2-0-0 oc purlins (4-1-8 max.): 3-5.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** (lb/size) 8=3939/0-3-8, 12=4195/0-3-8  
Max Horiz 12=13 (LC 31)  
Max Uplift 8=404 (LC 5), 12=379 (LC 4)

**FORCES** (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-5743/325, 3-4=-7780/426, 4-5=-7780/426, 5-6=-5993/407, 6-7=0/44, 2-12=-3435/312, 6-8=-3546/358

BOT CHORD 11-12=-36/917, 10-11=-255/5456, 9-10=-346/5711, 8-9=-20/431

WEBS 3-11=-7/652, 5-9=-75/833, 2-11=-291/4747, 6-9=-356/5415, 5-10=-39/2284, 4-10=-171/108, 3-10=-135/2558

#### NOTES


- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc, 2x6 - 2 rows staggered at 0-9-0 oc, 2x3 - 1 row at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-8-0 oc.  
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 379 lb uplift at joint 12 and 404 lb uplift at joint 8.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Use Simpson Strong-Tie HUS26 (14-10d Girder, 4-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-6-0 from the left end to 9-6-0 to connect truss(es) to back face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.
- "NAILED" indicates 2-12d (0.148"x3.25") toe-nails per NDS guidelines.

#### LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
Uniform Loads (lb/ft)  
Vert: 1-2=-70, 2-3=-70, 3-5=-70, 5-6=-70, 6-7=-70, 8-12=-20  
Concentrated Loads (lb)

Vert: 11=10 (F), 9=10 (F), 10=-1374 (F=1, B=-1375), 15=-1377 (B), 16=-1374 (F=1, B=-1375), 17=-1376 (F=1, B=-1377), 18=-1377 (B)



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	LAY1	Lay-In Gable	1	1	Job Reference (optional)	I47674149

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:38  
ID:lvLwo6q9Kz4uE6hpNx\_xrPz1lux-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwvCD0i7J4zJC?f

Page: 1



Scale = 1:32.7

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.06	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.02	Horiz(TL)	0.00	5	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 31 lb FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x4 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS

(lb/size)	1=94/9-0-15, 5=94/9-0-15, 6=224/9-0-15, 7=116/9-0-15, 8=224/9-0-15
Max Horiz	1=-94 (LC 4)
Max Uplift	1=-10 (LC 4), 6=-119 (LC 9), 8=-120 (LC 8)
Max Grav	1=103 (LC 16), 5=94 (LC 1), 6=242 (LC 16), 7=124 (LC 18), 8=242 (LC 15)

#### FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-93/74, 2-3=-86/80, 3-4=-79/64, 4-5=-77/54
BOT CHORD	1-8=-34/74, 7-8=-34/74, 6-7=-34/74, 5-6=-34/74
WEBS	3-7=-89/0, 2-8=-188/142, 4-6=-187/141

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 1, 120 lb uplift at joint 8 and 119 lb uplift at joint 6.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see



ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Page: 1LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	LAY3	Lay-In Gable	1	1	Job Reference (optional)	I47674151

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:39  
ID:E62zwETorGIM5FF?zaRNubz1lu6-RfC?PsB70Hq3NSgPqnL8w3uTXbGKWRcD0i7J4zJC?f

Page: 1



Scale = 1:61.2

Plate Offsets (X, Y): [10:0-0-12,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.06	Vert(LL)	n/a	-	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(TL)	n/a	-	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.17	Horiz(TL)	-0.01	10	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S						Weight: 79 lb	FT = 10%

**LUMBER**  
TOP CHORD 2x4 SPF No.2  
BOT CHORD 2x4 SPF No.2  
WEBS 2x4 SPF No.2  
OTHERS 2x4 SPF No.2

**BRACING**  
TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals, and 2'-0" oc purlins (6'-0" max.): 7-13, 7-10. Except:  
1 Row at midpt 7-13  
BOT CHORD Rigid ceiling directly applied or 10'-0" oc bracing, Except:  
6'-0" oc bracing: 10-11.

**REACTIONS** (lb/size)  
1=62/14-10-11, 10=30/14-10-11, 11=145/14-10-11, 12=219/14-10-11, 13=141/14-10-11, 14=172/14-10-11, 15=182/14-10-11, 16=179/14-10-11, 17=183/14-10-11  
Max Horiz 1=433 (LC 8)  
Max Uplift 1=102 (LC 6), 10=78 (LC 8), 11=29 (LC 9), 12=83 (LC 9), 14=113 (LC 8), 15=126 (LC 8), 16=123 (LC 8), 17=126 (LC 8)  
Max Grav 1=353 (LC 8), 10=48 (LC 15), 11=145 (LC 1), 12=219 (LC 1), 13=176 (LC 17), 14=191 (LC 15), 15=206 (LC 15), 16=202 (LC 15), 17=207 (LC 15)

**FORCES** (lb) - Maximum Compression/Maximum Tension  
TOP CHORD 1-2=503/202, 2-3=384/156, 3-4=259/110, 4-5=131/72, 5-6=63/29, 7-13=115/39, 6-7=51/28, 7-8=30/61, 8-9=30/61, 9-10=31/63

**BOT CHORD** 1-17=61/27, 16-17=61/27, 15-16=61/27, 14-15=61/28, 13-14=65/32, 12-13=173/94, 11-12=116/63, 10-11=111/49  
**WEBS** 2-17=161/144, 3-16=163/149, 4-15=165/152, 5-14=161/139, 8-12=168/73, 9-11=111/47

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2'-0" oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0" tall by 2'-0" wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 102 lb uplift at joint 1, 78 lb uplift at joint 10, 113 lb uplift at joint 14, 126 lb uplift at joint 17, 123 lb uplift at joint 16, 126 lb uplift at joint 15, 83 lb uplift at joint 12 and 29 lb uplift at joint 11.
- Non Standard bearing condition. Review required.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

**LOAD CASE(S)** Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

**ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component**




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	LAY4	Lay-In Gable	3	1	Job Reference (optional)	I47674152

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:39  
ID:M8Nkol1tnigiEUL1EynOuVz1ItN-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrcDoi7J4zJC?i

Page: 1



Scale = 1:84.1

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.17	Horiz(TL)	0.00	7	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 103 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x6 SPF No.2
OTHERS	2x4 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 5-6-9 oc purlins, except end verticals.		
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.		
WEBS	1 Row at midpt	4-9, 5-8	
WEBS	2 Rows at 1/3 pts	6-7	

REACTIONS	(lb/size)	1=93/10-9-0, 7=67/10-9-0,	
		8=177/10-9-0, 9=187/10-9-0,	
		10=161/10-9-0, 11=240/10-9-0	
	Max Horiz	1=662 (LC 8)	
	Max Uplift	1=-367 (LC 6), 7=-94 (LC 8),	
		8=-224 (LC 8), 9=-249 (LC 8),	
		10=-213 (LC 8), 11=-316 (LC 8)	
	Max Grav	1=923 (LC 8), 7=95 (LC 15), 8=245	
		(LC 15), 9=262 (LC 15), 10=226	
		(LC 15), 11=337 (LC 15)	

#### FORCES

	(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-1109/524, 2-3=-808/376, 3-4=-584/278,	
	4-5=-335/164, 5-6=-100/66, 6-7=-79/99	
BOT CHORD	1-11=-1/1, 10-11=-1/1, 9-10=-1/1, 8-9=-1/1,	
	7-8=-1/1	
WEBS	2-11=-268/326, 3-10=-195/242,	
	4-9=-219/270, 5-8=-207/254	

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)  
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.  
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;  
cantilever left and right exposed ; end vertical left  
exposed; Lumber DOL=1.60 plate grip DOL=1.60

- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) All plates are 2x4 MT20 unless otherwise indicated.
- 4) Gable requires continuous bottom chord bearing.
- 5) Gable studs spaced at 2-0-0 oc.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 367 lb uplift at joint 1, 94 lb uplift at joint 7, 316 lb uplift at joint 11, 213 lb uplift at joint 10, 249 lb uplift at joint 9 and 224 lb uplift at joint 8.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR
210529	LAY5	Lay-In Gable	1	1	Job Reference (optional)


I47674153

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:39

Page: 1

ID:JccCUEunICUmeEhUke1pkGz1IsH-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f



Scale = 1:93.6

Plate Offsets (X, Y): [4:0-2-5,Edge], [8:0-1-5,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	n/a	-	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(TL)	n/a	-	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.18	Horiz(TL)	0.00	12	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							
Weight: 134 lb FT = 10%											

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x6 SPF No.2
OTHERS	2x4 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 5-6-14 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5, 8-10.		
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.		
WEBS	1 Row at midpt	4-16, 6-15, 7-14, 9-13	
WEBS	2 Rows at 1/3 pts	11-12	

#### REACTIONS

(lb/size)	1=52/13-9-0, 12=66/13-9-0, 13=181/13-9-0, 14=178/13-9-0, 15=188/13-9-0, 16=169/13-9-0, 17=186/13-9-0, 18=175/13-9-0
Max Horiz	1=650 (LC 8)
Max Uplift	1=-410 (LC 6), 13=-51 (LC 8), 14=-285 (LC 8), 16=-354 (LC 8), 17=-294 (LC 8), 18=-215 (LC 8)
Max Grav	1=955 (LC 8), 12=66 (LC 1), 13=181 (LC 1), 14=268 (LC 15), 15=188 (LC 1), 16=255 (LC 15), 17=279 (LC 15), 18=240 (LC 15)


#### FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-1138/535, 2-3=-933/442, 3-4=-641/302, 4-5=-301/142, 5-6=-330/165, 6-7=-348/184, 7-8=-77/39, 8-9=-16/13, 9-10=-16/13, 10-11=-9/40, 11-12=-51/5
BOT CHORD	1-18=-1/1, 17-18=-1/1, 16-17=-1/1, 15-16=-1/1, 14-15=-1/1, 13-14=-1/1, 12-13=-1/1
WEBS	2-18=-192/224, 3-17=-240/321, 4-16=-214/377, 6-15=-148/0, 7-14=-227/308, 9-13=-141/82

#### NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Provide adequate drainage to prevent water ponding.
- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 410 lb uplift at joint 1, 215 lb uplift at joint 18, 294 lb uplift at joint 17, 354 lb uplift at joint 16, 285 lb uplift at joint 14 and 51 lb uplift at joint 13.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	LAY6	Lay-In Gable	1	1	Job Reference (optional)	I47674154

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:40  
ID:1plP9TDjxVuxNOFGp08Kyz1lrs-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?i

Page: 1



Scale = 1:36

Plate Offsets (X, Y): [2:0-2-15,Edge], [6:0-3-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	0.00	4	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 22 lb FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x4 SPF No.2
OTHERS	2x4 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 4-8-14 oc purlins, except end verticals, and 2-0-0 oc purlins: 2-4.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 4-5.

#### REACTIONS

(lb/size)	4=17/4-6-6, 5=158/4-6-6, 6=22/4-6-6, 7=164/4-6-6, 8=72/4-6-6
Max Horiz	8=95 (LC 8)
Max Uplift	4=165 (LC 8), 5=32 (LC 5), 6=130 (LC 6), 7=2 (LC 4), 8=93 (LC 8)
Max Grav	4=109 (LC 6), 5=158 (LC 1), 6=161 (LC 8), 7=164 (LC 1), 8=126 (LC 15)

#### FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-8=-114/100, 1-2=-96/96, 2-3=-68/103, 3-4=-67/104
BOT CHORD	7-8=-104/67, 6-7=-104/67, 5-6=-206/146, 4-5=-202/127
WEBS	2-7=-109/42, 3-5=-124/52

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-9-6 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 93 lb uplift at joint 8, 165 lb uplift at joint 4, 130 lb uplift at joint 6, 2 lb uplift at joint 7 and 32 lb uplift at joint 5.
- Non Standard bearing condition. Review required.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



16023 Swingley Ridge Rd  
Chesterfield, MO 63017




Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	LAY7	Lay-In Gable	1	1	Job Reference (optional)	I47674155

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:40  
ID:zBs9Z9EzS78fchP2XE3cPNz1lrq-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCdoi7J4zJC?f

Page: 1



Scale = 1:34.6

Plate Offsets (X, Y): [2:0-2-15,Edge], [6:0-3-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	n/a	-	n/a	999	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(TL)	n/a	-	n/a	999	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	0.00	4	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							
										Weight: 25 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x4 SPF No.2
OTHERS	2x4 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 5-8-14 oc purlins, except end verticals, and 2-0-0 oc purlins: 2-4.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 4-5.

#### REACTIONS

(lb/size)	4=59/5-6-6, 5=193/5-6-6, 6=4/5-6-6, 7=151/5-6-6, 8=72/5-6-6
Max Horiz	8=100 (LC 8)
Max Uplift	4=167 (LC 8), 5=56 (LC 5), 6=104 (LC 6), 7=10 (LC 4), 8=97 (LC 8)
Max Grav	4=111 (LC 15), 5=193 (LC 1), 6=194 (LC 8), 7=151 (LC 1), 8=120 (LC 15)

#### FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-8=-108/104, 1-2=-89/101, 2-3=-63/106, 3-4=-62/106
BOT CHORD	7-8=-107/62, 6-7=-106/62, 5-6=-215/140, 4-5=-209/125
WEBS	2-7=-113/35, 3-5=-158/66

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 97 lb uplift at joint 8, 167 lb uplift at joint 4, 104 lb uplift at joint 6, 10 lb uplift at joint 7 and 56 lb uplift at joint 5.
- Non Standard bearing condition. Review required.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	LAY8	Lay-In Gable	1	1	Job Reference (optional)	I47674156

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:40  
ID:CwwZSEldLuHNB4bnYdjjGHZ1lrh-RfC?PsB70Hq3NSgPqnL8w3uTXbGKWrCDoi7J4zJC?

Page: 1



Scale = 1:118.2

Plate Offsets (X, Y): [8:0-2-15,Edge], [17:0-3-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.13	Vert(LL)	n/a	-	n/a	999	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.16	Vert(TL)	n/a	-	n/a	999	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.06	Horiz(TL)	-0.03	9	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							
										Weight: 74 lb	FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x4 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 5-9-8 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 8-9.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

#### REACTIONS

(lb/size)	1=81/14-4-2, 9=35/14-4-2, 10=294/14-4-2, 13=325/14-4-2, 14=120/14-4-2, 15=191/14-4-2, 16=186/14-4-2, 17=30/14-4-2
Max Horiz	1=804 (LC 8)
Max Uplift	1=-348 (LC 6), 9=-223 (LC 8), 10=-17 (LC 8), 13=-439 (LC 8), 14=-155 (LC 8), 15=-249 (LC 8), 16=-299 (LC 8), 17=-110 (LC 6)
Max Grav	1=861 (LC 8), 9=83 (LC 6), 10=294 (LC 1), 13=460 (LC 15), 14=167 (LC 15), 15=267 (LC 15), 16=275 (LC 15), 17=313 (LC 8)

#### FORCES


(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-1028/483, 2-3=-751/351, 3-4=-511/241, 4-5=-300/162, 5-7=-100/36, 7-8=-89/206, 8-9=-89/190
BOT CHORD	1-17=-192/86, 16-17=-378/176, 15-16=-372/181, 14-15=-359/167, 13-14=-400/204, 11-13=-307/124, 10-11=-433/231, 9-10=-332/146
WEBS	8-10=-180/8, 7-11=-112/173, 5-13=-307/353, 4-14=-174/225, 3-15=-212/260, 2-16=-246/301

#### NOTES

- Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 9, 10 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 223 lb uplift at joint 9, 348 lb uplift at joint 1, 110 lb uplift at joint 17, 17 lb uplift at joint 10, 439 lb uplift at joint 13, 155 lb uplift at joint 14, 249 lb uplift at joint 15 and 299 lb uplift at joint 16.
- Non Standard bearing condition. Review required.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

Job	Truss	Truss Type	Qty	Ply	Lot 71 RR	
210529	LAY9	Lay-In Gable	1	1	Job Reference (optional)	I47674157

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.43 S Aug 16 2021 Print: 8.430 S Aug 16 2021 MiTek Industries, Inc. Fri Aug 27 15:04:40  
ID:ZOIRv362vm\_4LmIfWDbx64yjiJ-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:33.9

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	0.00	5	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-P							Weight: 29 lb FT = 10%

#### LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x4 SPF No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS

(lb/size)	1=71/7-9-11, 5=71/7-9-11, 6=198/7-9-11, 7=110/7-9-11, 8=198/7-9-11
Max Horiz	1=-104 (LC 4)
Max Uplift	1=-25 (LC 4), 5=-8 (LC 5), 6=-147 (LC 9), 8=-147 (LC 8)
Max Grav	1=96 (LC 16), 5=87 (LC 18), 6=226 (LC 16), 7=122 (LC 18), 8=226 (LC 15)

#### FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-115/87, 2-3=-98/77, 3-4=-90/62, 4-5=-99/64
BOT CHORD	1-8=-42/89, 7-8=-42/89, 6-7=-42/89, 5-6=-42/89
WEBS	3-7=-82/0, 2-8=-186/171, 4-6=-186/171

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 25 lb uplift at joint 1, 8 lb uplift at joint 5, 147 lb uplift at joint 8 and 147 lb uplift at joint 6.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



August 30, 2021

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601


ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component




16023 Swingley Ridge Rd  
Chesterfield, MO 63017

# Symbols

## PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.


\* Plate location details available in **MiTek 20/20 software** or upon request.

## PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

## LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

## BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

## Industry Standards:

ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.  
DSB-89: Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses.

# Numbering System

6-4-8 dimensions shown in ft-in-sixteenths (Drawings not to scale)



**JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.**

**CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.**

## PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988  
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MiTek® All Rights Reserved



MiTek Engineering Reference Sheet: MII-7473 rev. 5/19/2020



# General Safety Notes

**Failure to Follow Could Cause Property Damage or Personal Injury**

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.