

2 OFFICE INTERIOR ELEVATION
1/4" = 1'-0"

ELECTRICAL SYMBOL LEGEND		
SYMBOL	DESCRIPTION	MTG. HGT. (U.N.O.)
\$	LIGHT SWITCH	48"
\$ ^{OS}	OCCUPANCY SENSOR	48"
OS	OCCUPANCY SENSOR	CEILING
⌀ / ⌀ / ⌀	SINGLE / DUPLEX / DOUBLE DUPLEX RECEPTACLE	18"
⌀ ^{GF} / ⌀ ^{GF} / ⌀ ^{GF}	RECEPTACLE WITH GROUND FAULT PROTECTION	18"
⌀ ^{WR} / ⌀ ^{WR} / ⌀ ^{WR}	WEATHER RESISTANT RECEPTACLE WITH WEATHERPROOF IN-USE COVER	18"
⌀ ^{WR} / ⌀ ^{WR} / ⌀ ^{WR}	WEATHER RESISTANT RECEPTACLE	
Ⓜ	JUNCTION BOX	60"
Ⓜ	THERMOSTAT LOCATION, PROVIDE BOX WITH 1/2" CONDUIT TO CEILING SPACE	
Ⓜ	DATA ACCESS POINT	
▼	TELEPHONE JACK, PROVIDE BOX WITH 1/2" CONDUIT TO CEILING SPACE	18"
▼	DATA JACK, PROVIDE BOX WITH 3/4" CONDUIT TO CEILING SPACE	18"
▼	COMBO DATA/TELE JACK, PROVIDE BOX WITH 3/4" CONDUIT TO CEILING SPACE	
■	BUTTON	
■	BELL/BUZZER	
TC	TIME CLOCK	
■	PANELBOARD	
■	MOTOR	
■	NON-FUSED DISCONNECT	

EQUIPMENT SCHEDULE					
MARK	DESCRIPTION	FEEDER	DISCONNECT	CIRCUIT	REMARKS
AHU-1	AIR HANDLING UNIT	2#4 + 1#8 GND. - 1"	100A N.F.	A-74,76	1,5,6,8,9
AHU-2	AIR HANDLING UNIT	2#4 + 1#8 GND. - 1"	100A N.F.	A-78,80	1,5,6,8,9
AHU-3	AIR HANDLING UNIT	2#4 + 1#8 GND. - 1"	100A N.F.	A-82,84	1,5,6,8,9
CU-1	CONDENSING UNIT	2#4 + 1#8 GND. - 1"	100A N.F.	A-74,76	1,3,5,6,8,9
CU-2	CONDENSING UNIT	2#4 + 1#8 GND. - 1"	100A N.F.	A-78,80	1,3,5,6,8,9
CU-3	CONDENSING UNIT	2#4 + 1#8 GND. - 1"	100A N.F.	A-82,84	1,3,5,6,8,9
DH-1	DUCT HEATER	3#8 + 1#10 GND. - 3/4"	60A N.F.	A-56,58,60	1,2,6
DH-2	DUCT HEATER	3#8 + 1#10 GND. - 3/4"	60A N.F.	A-61,63,65	1,2,6
DH-3	DUCT HEATER	3#8 + 1#10 GND. - 3/4"	60A N.F.	A-67,69,71	1,2,6
HAC-1	HEATED AIR CURTAIN	2#6 + 1#10 GND. - 3/4"	60A N.F.	A-55,57	1,2,6
EF-1	EXHAUST FAN	2#12 + 1#12 GND. - 3/4"	TOGGLE	A-11	1,5,6,7
EF-2	EXHAUST FAN	2#12 + 1#12 GND. - 3/4"	TOGGLE	A-9	1,5,6,7
EF-3	EXHAUST FAN	2#12 + 1#12 GND. - 3/4"	TOGGLE	A-72	1,6,7,10
IWH-1	INSTANT WATER HEATER	2#12 + 1#12 GND. - 3/4"	PLUG	A-77	1,6,7
NOTES: 1. THE E.C. SHALL VERIFY ALL EQUIPMENT SPECIFICATIONS (VOLTAGE, OVERCURRENT PROTECTION, FUSE SIZES, ETC.) WITH M.C. PRIOR TO PLACING PURCHASE ORDER FOR DISTRIBUTION EQUIPMENT AND ROUGH-IN. THE E.C. SHALL ALSO BE RESPONSIBLE FOR PROVIDING ALL CONNECTIONS, DEVICES, SAFETY SWITCHES, ETC. LISTED ON THIS SCHEDULE UNLESS NOTED ON THIS SCHEDULE AS BEING PROVIDED BY OTHERS. 2. UNIT PROVIDED WITH INTEGRAL STARTER AND/OR DISCONNECT SWITCH. E.C. SHALL BRANCH TO FINAL CONNECTION VIA LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT. 3. ROUTE CONDUIT THRU EQUIPMENT CURB OR PROVIDE SEPARATE ROOT CONDUIT BOOT. COORDINATE WITH M.C. 4. CONNECT TO LOCAL LIGHTING CIRCUIT FOR FAN SERVICE. 5. MULTIPLE ITEMS ARE CONNECTED TO THE SAME CIRCUIT. 6. ALL CONDUIT PENETRATIONS THROUGH FIRE RATED WALLS, FLOORS, OR SHAFTS SHALL BE SEALED IN ACCORDANCE WITH WALL TYPE AS SHOWN ON SHEET A1.0. 7. EQUIPMENT MUST BE HARD WIRED THRU JUNCTION BOX 8. EQUIPMENT LOCATED ON ROOF, REFER TO MECHANICAL ROOF PLAN FOR EXACT LOCATION. 9. EQUIPMENT UTILIZES A SINGLE POINT CONNECTION FOR AIR HANDLING UNIT AND CONDENSING UNIT. 10. EXHAUST FAN TO BE WIRED THROUGH TIMECLOCK FOR CONSTANT OPERATION DURING OCCUPIED HOURS.					


Design and construction documents are instruments of service and are given in confidence and remain the property of Onyx Creative. The use of this design and these construction documents for purposes other than the specific project named herein is strictly prohibited without expressed written consent of Onyx Creative.

PetPeople
SUMMIT AT WEST PRYOR
940 NW PRYOR RD, UNIT J
LEES SUMMIT (KANSAS CITY), MO

Project No: 18804
Drawn By: TWK
Date: 07/16/2021
Issue: Etk/ Permit
08/27/2021 Revision: 2

E2.1

FLOOR PLAN



onyx | creative
25001 Emery Road, Suite 400
Cleveland, Ohio 44128
216.223.3200 onyxcreative.com