JOB # 211286 CHIPOTLE - LEES SUMMIT, MO HEARTLAND TRUSS, INC. 500 MID AMERICA DR. PLATTSBURG, MO 64477 PH. 816-930-3177 DESIGN BY: SEAN FEEHAN SIMPSON H10A-2 BY OTHERS SEAN@HEARTLANDTRUSS.COM 29-01-12 DIMENSIONS TO RTUs ARE FROM INSIDE FACE OF COPING 11-07-02 A01 2-06-00 14-01-1 6-04-10 2-0\$-00 3-11-00₁4-06-10 80-6 A03 2-08-00 100# 250# 24-01-00 1350# A03 3-10-08 2-08-00 30-07-12 A04 2-0\$-00 12-01-06 37-07-04 A05 6-04-10 2-08-00 1-05-08 100# 2-08-00 1150# 3-10-08 A04 2-0\$-00 52-01-12 A04 2-08-00 56-09-14 A06 2-08-00 A07 2-0\$-00 7-04-00 HOOD = 1200# A07 2-0\$-00 A07 2-05-12 5-03-00 A08 300# 2-07-08 2-0\$-12 A08 2-0\$-12 A07 2-07-06 A09 2-07-06 JGA Project No.: 21.34.059 Jezerinac Geers A10 650# 2-07-06 ed: 11/08/2021 A10 2-07-06 NO EXCEPTIONS TAKEN A10 2-11-08 REVISE AND RESUBMIT A02 10-10-06 100# 2-11-08 REJECTED A01 THD26-2 TYP. JEZERINAC GEERS COMMENTS ON THIS SUBMITTAL ARE POSTED IN RED 4-00-00 REFER TO PROVIDED BSCI-B1 **UPLIFT RESISTANCE:**

REFER TO PROVIDED BSCI-B1 BRACING SUMMARY SHEET FOR TEMPORARY, PERMANENT AND GABLE END BRACING

All trusses are to be held down with (1) TLOK06 screw or (1) RT clip per ply, at each bearing location unless noted otherwise on this diagram