



SOUTHSIDE RETAIL




COPYRIGHT © 2022.
HIVE DESIGN COLLABORATIVE, INC.

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT ST., KANSAS CITY, MO 64108
816.581.6363

SECTION 07 46 60 - FIBER CEMENT SIDING			SECTION 09 21 16 - GYPSUM BOARD ASSEMBLIES				
PART 1 - GENERAL	1.1	Section Includes	PART 1 GENERAL	1.1	Section Includes		
	A.	Siding panels.		1.2	Interior Partitions Indicated as Sound-Rated: STC as indicated calculated in accordance with ASTM E413, based on tests conducted in accordance with ASTM E90.		
	B.	Soffit panels.		3.	Fire Rated Assemblies: Comply with applicable requirements of ICC IBC or GA-600 for the particular assembly. Provide construction equivalent to that listed for the particular assembly in the current UL Fire Resistance Directory.		
	C.	Accessories and trim.		4.	Manufacturers - Metal Framing, Connectors, and Accessories: ClarkDietrich, Scafo, or equal.		
	1.2	Related Sections		5.	Non-Loadbearing Framing System Components: ASTM C645; galvanized steel sheet, of size and properties necessary to comply with ASTM C754 for the spacing indicated, with maximum deflection of wall framing of L/240 at 5 psf.		
	D.	Section 061000 - Rough Carpentry: Framing and Sheathing.		6.	Studs: "C" shaped with flat or formed webs .		
	E.	Section 079005 - Joint Sealers.		7.	Runners: U shaped, sized to match studs.		
	F.	Section 099000 - Paints and Coatings: Field painting.		8.	Celling Channels: C shaped.		
	1.3	References		9.	Celling Hangers: Type and size as specified in ASTM C754 for spacing required.		
	A.	ASTM C 920 - Standard Specification for Elastomeric Joint Sealants		10.	Partition Head to Structure Connections: Provide mechanical anchorage devices that accommodate deflection using slotted holes, screws and anti-friction bushings, preventing rotation of studs while maintaining structural performance of partition. Maintain lateral load resistance and vertical movement capacity required by applicable code, when evaluated in accordance with AISI North American Specification for the Design of Cold-Formed Steel Structural Members.		
1.4	Submittals	A.	PART 1 GENERAL	1.1	Material: ASTM A653/A653M steel sheet, SS Grade 50/340, with G60/Z180 hot dipped galvanized coating. Provide components UL-listed for use in UL-listed fire-rated head of partition joint systems indicated on drawings. Deflection within 6 months after installation as described above that accommodate deflection while maintaining the fire-rating of the wall assembly.		
		B.			12.	Manufacturers - Gypsum-Based Board: National Gypsum Company, USG Corporation or equal.	
		C.			13.	Gypsum Wallboard: Paper-faced gypsum panels as defined in ASTM C1396/C1396M; sizes to minimize joints in place; ends square cut.	
		D.			14.	Application: Use for vertical surfaces and ceilings, unless otherwise indicated. At Assemblies indicated with Fire-Rating: Use type required by indicated tested assembly, if no tested assembly is indicated, use Type X board, UL or WH listed.	
		E.			15.	Thickness: Vertical Surfaces: 5/8 inch.	
		F.			16.	Ceilings: 1/2 inch.	
		G.			17.	Multi-Layer Assemblies: Thicknesses as indicated on drawings.	
		H.			18.	Impact-Rated Wallboard: Tested to Level 3 soft-body and hard-body impact in accordance with ASTM C1629.	
		I.			19.	Application: High-traffic areas indicated. Mold Resistance: Score of 10, when tested in accordance with ASTM D3273.	
		J.			20.	Type: Fire-resistance rated Type X, UL or WH listed.	
1.5	Quality Assurance	A.	PART 1 GENERAL	1.2	Edges: Tapered.		
		B.			21.	Soffit Board for Exterior Areas; ends square cut:	
		C.			22.	Application: Protected exterior ceilings and soffits unless otherwise indicated.	
		D.			23.	Type: Sag and warp-resistant Type X.	
		E.			24.	Thickness: 5/8 inch.	
		F.			25.	Long Edges: Tapered.	
		G.			26.	Backing Board For Wet Areas:	
		H.			27.	Application: Surfaces behind tile in wet areas including tub and shower surrounds and shower ceiling.	
		I.			28.	Type: Glass-Mat-Faced Board: Coated glass mat water-resistant gypsum backing panel as defined in ASTM C1178.	
		J.			29.	Backing Board For Non-Wet Areas: Water-resistant gypsum backing board as defined in ASTM C1396/C1396M; sizes to minimum joints in place; ends square cut.	
1.6	Delivery, Storage, and Handling	A.	PART 1 GENERAL	1.3	Application: Vertical surfaces behind toilet stalls, except in wet areas.		
		B.			30.	Type: Regular and Type X, in locations indicated.	
		C.			31.	Type X Thickness: 5/8 inch.	
		D.			32.	Regular Board Thickness: 5/8 inch.	
		E.			33.	Edges: Tapered.	
		F.			34.	Ceiling Board: Special water-resistant gypsum ceiling board as defined in ASTM C1396/C1396M; sizes to minimize joints in place; ends square cut.	
		G.			35.	Application: Ceilings, unless otherwise indicated.	
		H.			36.	Thickness: 1/2 inch.	
		I.			37.	Edges: Tapered.	
		J.			38.	Acoustical Sound Dampening Wall and Ceiling Board: Two layers of heavy paper faced, high density gypsum board separated by a viscoelastic polymer layer and capable of achieving STC rating of 50 or more in typical stud wall assemblies as calculated in accordance with ASTM E413 and when tested in accordance with ASTM E90.	
1.7	WARRANTY	A.	PART 1 GENERAL	1.4	Thickness: 1/2 inch.		
		B.			19.	Long Edges: Tapered.	
		C.			20.	Mold Resistance: Score of 10, when tested in accordance with ASTM D3273.	
		D.			21.	Thickness: 3 1/2 inch. (if/where applicable)	
		E.			22.	Acoustic Insulation: ASTM C665; preformed glass fiber, friction fit type, unfaced.	
		F.			23.	Thickness: 3 1/2 inch. (if/where applicable)	
		G.			24.	Acoustic Sealant: Non-hardening, non-skinning, for use in conjunction with gypsum board.	
		H.			25.	Joint Materials: ASTM C475; as recommended by gypsum board manufacturer for project conditions.	
		I.			26.	High Build Drywall Surface: Vinyl acrylic latex-based coating for spray application, designed to take the place of skim coating and separate paint primer in achieving Level 5 finish.	
		J.			27.	Screws for Attachment to Steel Members Less Than 0.03 inch in Thickness, to Wood Members, and to Gypsum Board: ASTM C1002; self-piercing tapping type.	
PART 2 - PRODUCTS	2.1	Manufacturer	PART 2 - PRODUCTS	2.01	SHEET MATERIALS		
						A.	Pre-Finished Aluminum: ASTM B209 (ASTM B209M); 20 gauge, (0.032 inch) thick; plain finish shop pre-coated with modified silicone coating.
						1.	Fluoropolymer Coating: High Performance Organic Finish, AAMA 2604; multiple coat, thermally cured fluoropolymer finish system.
						2.	Color: As indicated on drawings.
						2.02	FABRICATION
						A.	Form sections true to shape, accurate in size, square, and free from distortion or defects.
						B.	Form pieces in longest possible lengths.
						C.	Hem exposed edges on underside 1/2 inch; miter and seam corners.
						D.	Form material with flat lock seams, except where otherwise indicated; at moving joints, use sealed lapped, bayonet-type or interlocking hooked seams.
						E.	Fabricate corners from one piece with minimum 18 inch long legs; seam for rigidity, seal with sealant.
F.	Fabricate flashings to allow toe to extend 2 inches over roofing gravel. Return and brake edges.						
2.03	ACCESSORIES						
A.	Fasteners: Galvanized steel, with soft neoprene washers.						
B.	Primer: Zinc chromate type.						
C.	Concealed Sealants: Non-curing butyl sealant.						
D.	Exposed Sealants: ASTM C920; elastomeric sealant, with minimum movement capability as recommended by manufacturer for substrates to be sealed; color to match adjacent material.						
E.	Plastic Cement: ASTM D4586/D4586M, Type 1.						
F.	Reglets: Surface mounted type, galvanized steel.						
2.04	INSULATION						
A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.						
B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.						
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION
						A.	Insert flashings into reglets to form tight fit; secure in place with plastic wedges ; seal flashings into reglets with sealant.
						B.	Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted.
C.	Apply plastic cement compound between metal flashings and felt flashings.						
D.	Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines acceptable to profiles.						
E.	Seal metal joints watertight.						
F.	Slope gutters 1/4 inch per 10 feet, minimum.						
G.	Connect downspouts to storm sewer system , and grout connection watertight.						
PART 3 - EXECUTION	3.1	EXAMINATION	PART 3 - EXECUTION	3.01	EXAMINATION		
						A.	Verify roof openings, curbs, pipes, sleeves, ducts, and vents through roof are solidly set, reglets in place, and nailing strips are installed.
						B.	Verify roofing termination and base flashings are in place, sealed, and secure.
						3.02	PREPARATION
						A.	Install starter and edge strips, and cleats before starting installation.
						B.	Install starter mounted reglets true to lines and levels, and seal top of reglets with sealant.
						C.	Back paint concealed metal surfaces with protective backing paint to a minimum dry film thickness of 15 mil.
						3.03	INSTALLATION

	
<hr/>	
<p style="font-size: 2em; font-weight: bold; margin: 0;">SOUTHSIDE RETAIL</p>	<p style="margin: 0;">HIVE DESIGN COLLABORATIVE, INC. 1617 WALNUT STREET, KANSAS CITY, MO 64108 816.581.6363</p>
<hr/>	
<p>COPYRIGHT © 2022 HIVE DESIGN COLLABORATIVE, INC.</p>	
<hr/>	
<p>seal/signature</p> <div style="text-align: center;">  </div>	<p>02/24/22</p>
<hr/>	
project number	2021-045
<hr/>	
date	02.24.22
<hr/>	
issued for	PERMIT/BID
<hr/>	
rev date	description
<hr/>	
<hr/>	



DEMOLITION PLAN GENERAL NOTES:

- a. REMOVE ALL EXISTING SOFFIT LIGHTING, TO BE REPLACED W/ LED EQUIVALENT LIGHT FIXTURE OF SIMILAR TYPE.

DEMOLITION PLAN KEY NOTES:

- 1 EXISTING COLUMN WRAP TO BE REMOVED. PATCH AND REPAIR EXISTING ADJACENT CONSTRUCTION TO REMAIN TO MATCH EXISTING ADJACENT CONDITIONS.
- 2 EXISTING PILASTER TO REMAIN. PREPARE FOR NEW COLUMN FINISH. REMOVE EXISTING WALL SCONCES @ EXISTING LARGE & MEDIUM PILASTERS.
- 3 REMOVE EXISTING EIFS DECORATIVE ARCH & DIAMOND SHAPED BUMP-OUTS @ TOWER ELEMENT ABOVE. PATCH & REPAIR EIFS AS REQ'D TO RECEIVE NEW FACADE FINISH.



SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature



02/24/22

project number 2021-045

date 02.24.22

issued for PERMIT/BID

rev date description

DEMO - SITE
PLAN

sheet number


D001

1 SITE / ROOF PLAN - DEMO

1" = 30'-0"

DEMO PLAN NOTES

1/8" = 1'-0"



- DEMOLITION PLAN GENERAL NOTES:**
- a. REMOVE ALL EXISTING SOFFIT LIGHTING, TO BE REPLACED W/ LED EQUIVALENT LIGHT FIXTURE OF SIMILAR TYPE.
- DEMOLITION PLAN KEY NOTES:**
- 1 EXISTING COLUMN WRAP TO BE REMOVED. PATCH AND REPAIR EXISTING ADJACENT CONSTRUCTION TO REMAIN TO MATCH EXISTING ADJACENT CONDITIONS.
- 2 EXISTING PILASTER TO REMAIN. PREPARE FOR NEW COLUMN FINISH. REMOVE EXISTING WALL SCONCES @ EXISTING LARGE & MEDIUM PILASTERS.
- 3 REMOVE EXISTING EIFS DECORATIVE ARCH & DIAMOND SHAPED BUMP-OUTS @ TOWER ELEMENT ABOVE. PATCH & REPAIR EIFS AS REQ'D TO RECEIVE NEW FACADE FINISH.



SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature



02/24/22

project number 2021-045

date 02.24.22

issued for PERMIT/BID

rev date description

DEMO -
ENLARGED
PLAN

sheet number

D002

DEMO PLAN NOTES

1/8" = 1'-0"

APPLICABLE CODES JURISDICTION :
THE CITY OF LEE'S SUMMIT, MISSOURI
2018 INTERNATIONAL BUILDING CODE
2018 INTERNATIONAL EXISTING BUILDING CODE
2018 INTERNATIONAL FUEL GAS CODE
2018 INTERNATIONAL MECHANICAL CODE
2018 INTERNATIONAL PLUMBING CODE
2017 NATIONAL ELECTRICAL CODE
ICC/ANSI A117.1-2009 STANDARDS FOR ACCESSIBLE DESIGN

PROJECT DESCRIPTION
EXISTING RETAIL SHOPPING CENTER CONSISTING OF TWO BUILDINGS. THE SCOPE OF THE PROJECT INCLUDES THE RENOVATION OF THE EXISTING EXTERIOR FACADES ONLY.

CODE INFORMATION


N.T.S.

SITE AND ROOF PLAN GENERAL NOTES:

- a. PATCH AND REPAIR EXISTING CONCRETE WHERE EFFECTED BY DEMOLITION.
b. PROVIDE NEW TPO ROOFING @ BACK SIDE OF PARAPETS & TOWERS. REMOVE EXISTING EIFS/STUCCO FINISHES AS REQ'D PRIOR TO INSTALLATION OF NEW TPO ROOFING. PROVIDE NEW COUNTER-FLASHING AT EXISTING ROOF COPINGS (AND AT DIFFERING MATERIAL TRANSITIONS) FOR TPO TERMINATION. COORDINATE EXACT LOCATIONS W/ GC. MATCH EXISTING TPO COLOR.

SITE PLAN KEY NOTES:

- 1 NEW TPO ROOFING @ BACK SIDE OF PARAPETS & TOWERS, COORDINATE EXACT LOCATIONS W/ GC. RE: GENERAL NOTES ABOVE.



SITE PLAN NOTES

N.T.S.

1 SITE / ROOF PLAN

1" = 30'-0"



SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature



02/24/22

project number 2021-045

date 02.24.22


issued for PERMIT/BID

rev date description

SITE / ROOF PLAN

sheet number

A100



- FLOOR PLAN GENERAL NOTES:**
- CONTRACTOR TO FIELD VERIFY ALL DIMENSIONS AND EXISTING CONDITIONS.
 - PATCH ALL EXISTING WALLS WHERE ADJACENT WALLS AND/OR CASEWORK, EQUIPMENT, ETC. WERE REMOVED. PREPARE FOR PAINT FINISH.
 - CLEAN ALL EXISTING WINDOW SILLS. PROTECT FROM DAMANGE DURING DEMOLITION & CONSTRUCTION.
 - CAULK ALL JOINTS BETWEEN DISSIMILAR MATERIALS FOR WEATHER TIGHT, WATERTIGHT, AIRTIGHT, ETC. PERFORMANCE.
 - ALL PENETRATIONS INTO FIRE-RATED ASSEMBLIES ARE TO BE FIRESTOPPED WITH UL APPROVED FIRESTOPPING ASSEMBLIES. UL INFORMATION SHALL BE PROVIDED BY TRADE RESPONSIBLE FOR PENETRATION.
 - PATCH AND REPAIR EXISTING CONCRETE WHERE EFFECTED BY DEMOLITION.

- FLOOR PLAN KEY NOTES:**
- EXISTING CONCRETE SIDEWALK. PATCH AND REPAIR AS NEEDED.
 - FIBER CEMENT PANEL WRAPPED PILASTER (SMALL PILASTER, TYP.).
 - FIBER CEMENT LAP SIDING WRAPPED PILASTER (LARGE PILASTER, TYP.).
 - FIBER CEMENT LAP SIDING WRAPPED PILASTER (MEDIUM PILASTER, TYP.).



SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature



02/24/22

project number 2021-045

date 02.24.22

issued for PERMIT/BID

rev	date	description
-----	------	-------------

ENLARGED PLANS

sheet number


A101

1 ENLARGED PLAN

1/16" = 1'-0"


PLAN NOTES

1/8" = 1'-0"



2 ENLARGED PLAN

1/16" = 1'-0"



3 ENLARGED PLAN

1/16" = 1'-0"

FLOOR PLAN GENERAL NOTES:

- CONTRACTOR TO FIELD VERIFY ALL DIMENSIONS AND EXISTING CONDITIONS.
- PATCH ALL EXISTING WALLS WHERE ADJACENT WALLS AND/OR CASEWORK, EQUIPMENT, ETC. WERE REMOVED. PREPARE FOR PAINT FINISH.
- CLEAN ALL EXISTING WINDOW SILLS. PROTECT FROM DAMAGE DURING DEMOLITION & CONSTRUCTION.
- CAULK ALL JOINTS BETWEEN DISSIMILAR MATERIALS FOR WEATHER TIGHT, WATERTIGHT, AIRTIGHT, ETC. PERFORMANCE.
- ALL PENETRATIONS INTO FIRE-RATED ASSEMBLIES ARE TO BE FIRESTOPPED WITH UL APPROVED FIRESTOPPING ASSEMBLIES. UL INFORMATION SHALL BE PROVIDED BY TRADE RESPONSIBLE FOR PENETRATION.
- PATCH AND REPAIR EXISTING CONCRETE WHERE EFFECTED BY DEMOLITION.

FLOOR PLAN KEY NOTES:

- EXISTING CONCRETE SIDEWALK. PATCH AND REPAIR AS NEEDED.
- FIBER CEMENT PANEL WRAPPED PILASTER (SMALL PILASTER, TYP.).
- FIBER CEMENT LAP SIDING WRAPPED PILASTER (LARGE PILASTER, TYP.).
- FIBER CEMENT LAP SIDING WRAPPED PILASTER (MEDIUM PILASTER, TYP.).



SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature



02/24/22

project number 2021-045

date 02.24.22

issued for PERMIT/BID

rev date description





ENLARGED PLANS

sheet number

A102

PLAN NOTES

1/8" = 1'-0"

				<div>EXTERIOR ELEVATION GENERAL NOTES:</div> <div><div>a.</div><div>EXISTING STANDING SEAM ROOFING TO REMAIN.</div></div> <div><div>b.</div><div>ALL EXISTING EIFS / STUCCO AND STOREFRONT TO BE REPAIRED AS NEEDED. NEW SEALANT IN ALL CASES.</div></div> <div><div>c.</div><div>REFER TO DETAILS 7/A500 & 8/A500 FOR TYPICAL FIBER CEMENT JOINT DETAILS (FOR @ LOCATIONS NOT INDICATED IN EXTERIOR ELEVATIONS).</div></div> <div><div>d.</div><div>EXIST. MASONRY WALLS @ SIDES & REARS OF EXISTING BUILDINGS TO BE PAINTED.</div></div> <div><div>e.</div><div>PROVIDE MOCK-UP FOR PAINT COLOR SELECTIONS BY OWNER. PRELIMINARY PAINT FINISH COLORS AS FOLLOWS:</div><div><div><div></div>SW2861 - EXIST. EIFS, STUCCO, & MASONRY, DOWNSPOUTS (WHERE APPLICABLE)</div><div><div></div>SW2803 - LAP & PANEL SIDING, GUTTERS & DOWNSPOUTS</div></div></div> <div><div>f.</div><div>THIN STONE VENEER:</div><div><div></div>CANYON STONE "CHALK TIMBER LEDGE" BY ENVIRONMENTAL STONE WORKS</div></div>			
				<div>EXTERIOR ELEVATION KEY NOTES:</div> <div><div>1</div><div>FIBER CEMENT LAP SIDING, PAINTED. REMOVE EXISTING EIFS DECORATIVE BUMP-OUTS & PATCH/REPAIR PRIOR TO FURRING & SIDING INSTALLATION.</div></div> <div><div>2</div><div>WOOD TEXTURED PANELED FIBER CEMENT SIDING, PAINTED, W/ ALUMINUM TRIM, JOINTS & TRANSITIONS.</div></div> <div><div>3</div><div>WOOD TEXTURED PANELED FIBER CEMENT SIDING CLADDING, PAINTED, @ EXISTING COLUMNS, W/ ALUMINUM TRIM CORNERS</div></div> <div><div>4</div><div>PATCH & REPAIR EXISTING EIFS AS REQ'D & PREPARE FOR NEW PAINT FINISH.</div></div> <div><div>5</div><div>PAINT EXISTING EIFS DROP SOFFIT & EXISTING SOFFIT BEYOND.</div></div> <div><div>6</div><div>EXTEND SOFFIT EIFS FINISH AT TOPS OF PILASTERS WHERE PREVIOUS PILASTER MATERIAL WAS REMOVED. PROVIDE SEAMLESS FINISH.</div></div> <div><div>7</div><div>REMOVE & SALVAGE FOR RE-USE EXISTING GUTTERS & DOWNSPOUTS. PROVIDE NEW FLASHING EXTENSIONS OVER NEW CLADDING MATERIALS. PAINTED TO MATCH PAINTED LAP & PANEL SIDING TYPICAL. EXCEPT WHERE DOWNSPOUTS OCCUR UP AGAINST EXISTING EIFS, PAINT TO MATCH EIFS PAINT COLOR.</div></div> <div><div>8</div><div>SIGNAGE SHOWN AS GENERIC, COORDINATE W/ CURRENT TENANTS & ACTUAL SIGNAGE. REMOVE & SALVAGE FOR RE-USE ALL EXISTING SIGNAGE. PROVIDE FOR ELECTRICAL AS NEEDED TO ALL EXISTING & POTENTIAL SIGNAGE LOCATIONS.</div></div> <div><div>9</div><div>VERTICAL ALUMINUM PANEL JOINT (TYP.), RE: DETAILS.</div></div> <div><div>10</div><div>EXIST. EIFS TO BE PAINTED.</div></div> <div><div>11</div><div>FIBER CEMENT TRIM.</div></div> <div><div>12</div><div>TURBO 18 OUTDOOR WALL SCONCE BY TECH LIGHTING. COORDINATE APPROVAL WITH OWNER.</div></div>			
							
3	EAST ELEVATION	4	WEST ELEVATION (OUTBUILDING)				
1/16" = 1'-0"		1/16" = 1'-0"					
							
2	SOUTH ELEVATION (EAST)						
1/16" = 1'-0"							
							
1	SOUTH ELEVATION (WEST)						
1/16" = 1'-0"							
				ELEVATION NOTES			
/				N.T.S.			

HIVE

SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature

STATE OF MISSOURI
LOGAN HAYES
NUMBER
A-2015040635
ARCHITECT

02/24/22

project number

2021-045

date

02.24.22

issued for

PERMIT/BID

rev

date

description

sheet number

A200

EXTERIOR ELEVATIONS



SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature



02/24/22

project number 2021-045

date 02.24.22

issued for PERMIT/BID

rev date description

EXTERIOR
ELEVATIONS

sheet number

A200

	<div>4</div> <div>CANOPY #2 & #3</div> <div>1/2" = 1'-0"</div>
	<div>3</div> <div>TOWER #2 & #3</div> <div>1/2" = 1'-0"</div>
	<div>2</div> <div>CANOPY #1</div> <div>1/2" = 1'-0"</div>
	<div>1</div> <div>TOWER #1</div> <div>1/2" = 1'-0"</div>



SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature



02/24/22

project number 2021-045

date 02.24.22

issued for PERMIT/BID

rev date description

WALL
SECTIONS

sheet number

A300



SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature



02/24/22

project number 2021-045

date 02.24.22


issued for PERMIT/BID

rev date description

WALL
SECTIONS


sheet number

A301




4 PILASTER - LARGE

1/2" = 1'-0"




3 CANOPY #4 / PILASTER - SMALL

1/2" = 1'-0"

















2 TOWER #4 - SOLID

1/2" = 1'-0"



1 CORNER TOWER

1/2" = 1'-0"

				<div><p>PLAN VIEW:</p><p>1. INTERMEDIATE TRIM @ PANEL SIDING: • @ PANEL BAND</p><p>EZ-7 2-PIECE VERTICAL U 5/16" PANEL TRIM, PRIMED, PAINTED TO MATCH SIDING</p><p>PLAN VIEW:</p><p>2. END / CORNER @ PANEL SIDING TO EXIST. EIFS SIDING TRANSITION: • @ PANEL BAND TO EXIST. EIFS • @ TOPS OF SMALL PILASTERS (HORIZONTAL)</p><p>EZ-8 GENERAL J 5/16" PANEL TRIM, PRIMED, PAINTED TO MATCH SIDING</p><p>BACKER ROD & SEALANT</p><p>SECTION VIEW:</p><p>3. HORIZONTAL TRIM TRANSITION: • @ SMALL PILASTERS</p><p>EZ-22 HORIZONTAL SLT Z 5/16" PANEL TRIM</p></div>		<div><p>PLAN VIEW:</p><p>EZ-33 ARROW OUTSIDE CORNER 3/4" LAP TRIM, PRIMED, PAINTED TO MATCH SIDING</p><p>PLAN VIEW:</p><p>EZ-13 ARROW OUTSIDE CORNER 5/16" LAP TRIM, PRIMED, PAINTED TO MATCH SIDING</p><p>PLAN VIEW:</p><p>EZ-17 INSIDE CORNER 5/16" TO 3/4" TRANSITION TRIM, PRIMED, PAINTED TO MATCH SIDING</p><p>PLAN VIEW:</p><p>EZ-18 MULTI-ANGLE INSIDE CORNER 5/16" PANEL TRIM, PRIMED, PAINTED TO MATCH SIDING</p><p>VARIES F.V.</p></div> <div><p>1. OUTSIDE CORNER @ LAP SIDING: • @ TOWERS • @ TOWER LARGE & MEDIUM PILASTERS</p><p>2. OUTSIDE CORNER @ PANEL SIDING: • @ PANEL BAND • @ SMALL PILASTERS, SIM., RE: DETAIL 5/A501</p><p>3. INSIDE CORNER @ PANEL SIDING TO LAP SIDING TRANSITION: • @ PANEL BAND TO TOWER</p><p>4. INSIDE CORNER @ ANGLED PANEL SIDING TRANSITION: • @ PANEL BAND</p></div>		
	9	DETAIL		8	DETAIL		7	DETAIL
		1 1/2" = 1'-0"			3" = 1'-0"			3" = 1'-0"
								
	6	DETAIL		5	DETAIL		4	DETAIL
		1 1/2" = 1'-0"			1 1/2" = 1'-0"			1 1/2" = 1'-0"
								
	3	DETAIL		2	DETAIL		1	DETAIL
		1 1/2" = 1'-0"			1 1/2" = 1'-0"			1 1/2" = 1'-0"



SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature



02/24/22

project number 2021-045

date 02.24.22





issued for PERMIT/BID

rev date description

DETAILS

sheet number

A500

			
		5	COLUMN PLAN DETAIL @ WOOD - TYP.
			3" = 1'-0"
			
		3	COLUMN PLAN DETAIL @ STONE - TYP.
			3" = 1'-0"
			
	2	DETAIL	1
		1 1/2" = 1'-0"	3" = 1'-0"



SOUTHSIDE RETAIL

840 SW BLUE PKWY
LEE'S SUMMIT, MO

HIVE DESIGN COLLABORATIVE, INC.
1617 WALNUT STREET, KANSAS CITY, MO 64108
816.581.6363

COPYRIGHT © 2022
HIVE DESIGN COLLABORATIVE, INC.

seal/signature



02/24/22

project number2021-045

date02.24.22

issued forPERMIT/BID

rev	date	description
-----	------	-------------

DETAILS

sheet number

A501