

CITY OF LEE'S SUMMIT

CODES ADMINISTRATION DEPARTMENT

220 SE Green Street

Lee's Summit, MO 64063

(816) 969-1200

Fax (816) 969-1201

PLANS REVIEW CONDITIONS

Permit No:	PRCOM20100308	Date:	December 30, 2010
Project Title:	The Silver Source	Applicant:	
Project Address:	880 NW BLUE PKWY, Unit:I		
Location:	SUMMIT FAIR LOTS 22A & 24A---LOT 22A	LYTLE CONSTRUCTION INC	
Type of Work:	New Tenant Finish	1100 SE HAMBLEN RD	
Occupancy Group:	Mercantile	LEES SUMMIT, MO 64081	
Description:	Complete tenant finish		

The following is a list of requirements from the City of Lee's Summit that have not been satisfactorily addressed in the plans and specifications. Please contact the appropriate department regarding clarification of comments.

Codes Administration (816) 969-1200

Fire Department (816) 969-1300

Building Plan Review

Reviewed By: Michael Weisenborn

Rejected

1. 2006 IPC 403.4 - Required public toilet facilities. Customers, patrons and visitors shall be provided with public toilet facilities in structures and tenant spaces intended for public utilization. The accessible route to public facilities shall not pass through kitchens, storage rooms, closets or similar spaces. Employees shall be provided with toilet facilities in all occupancies. Employee toilet facilities shall be either separate or combined employee and public toilet facilities.

Action required - Provide documentation from the tenant that the restroom will be available to the customers.

2. 2006 IBC 1109.4 - Kitchens and kitchenettes. Where kitchens and kitchenettes are provided in accessible spaces or rooms, they shall be accessible in accordance with ICC A117.1.

Action required - Show how this requirement will be met for the breakroom sink.,

3. 2006 IBC 1210.1 - Floors. In other than dwelling units, toilet and bathing room floors shall have a smooth, hard, nonabsorbent surface that extends upward onto the walls at least 6 inches.

Action required - Show how this requirement will be met.,

4. 2006 IBC 1210.2 - Walls. Walls within 2 feet of urinals and water closets shall have a smooth, hard, nonabsorbent surface, to a height of 4 feet above the floor, and except for structural elements, the materials used in such walls shall be of a type that is not adversely affected by moisture. Exceptions: 1. Dwelling units and sleeping units. 2. Toilet rooms that are not accessible to the public and which have not more than one water closet. Accessories such as grab bars, towel bars, paper dispensers and soap dishes, provided on or within walls, shall be installed and sealed to protect structural elements from moisture.

Action required - Show how this requirement will be met.,

5. 2006 IBC 1109.12.3 - Point of sale and service counters. Where counters are provided for sales or distribution of goods or services, at least one of each type provided shall be accessible. Where such counters are dispersed throughout the building or facility, accessible counters shall also be dispersed.

Action required - Show how this requirement will be met.,

6. 2006 IBC 1008.1.8.1 - Hardware. Door handles, pulls, latches, locks and other operating devices on doors required to be accessible by Chapter 11 shall not require tight grasping, tight pinching or twisting of the wrist to operate.

Action required - Provide information on the door hardware to be used.

,

7. The rear wall of this space is the only rated assembly. The demising walls are not.

Action required - Make needed corrections to the plans.

,

8. Details and specifications for the alteration to the plumbing system have not been provided.

Action required - Provide additional information.,

Fire Plan Review

Reviewed By: Brian Austerman

Rejected

1. 2006 IFC 505.1- Address numbers. New and existing buildings shall have approved address numbers, building numbers or approved building identification placed in a position that is plainly legible and visible from the street or road fronting the property. These numbers shall contrast with their background. In Multi-tenant commercial building where tenants have multiple entrances located on different sides of the building , each door shall be addressed. Address numbers shall be Arabic numerals or alphabet letters. Numbers shall be a minimum of 4 inches (102 mm) high with a minimum stroke width of 0.5 inch (12.7 mm).

ACTION REQUIRED- PROVIDE ADDRESS ON ALL EXTERIOR DOORS, VERIFIED AT INSPECTION,

2. 2006 IFC 901.2- Construction documents. The fire code official shall have the authority to require construction documents and calculations for all fire protection systems and to require permits be issued for the installation, rehabilitation or modification of any fire protection system. Construction documents for fire protection systems shall be submitted for review and approval prior to system installation.

ACTION REQUIRED- PROVIDE DRAWINGS FOR SPRINKLER MODIFICATIONS,

3. 2006 IFC 901.5- Installation acceptance testing. Fire detection and alarm systems, fire-extinguishing systems, fire hydrant systems, fire standpipe systems, fire pump systems, private fire service mains and all other fire protection systems and appurtenances thereto shall be subject to acceptance tests as contained in the installation standards and as approved by the fire code official. The fire code official shall be notified before any required acceptance testing. The fire code official shall be notified 48 hours before any required acceptance test.

ACTION REQUIRED- CALL 969-1316 TO SCHEDULE ALARM TESTING PRIOR TO THE FINAL,

4. Fire Department 2006 IFC- 1008.1.8.4 Bolt locks.
Manually operated flush bolts or surface bolts are not permitted.

ACTION REQUIRED- VERIFIED AT INSPECTION,

The approval of plans and specifications does not permit the violation of any section of the Building Codes or other City Ordinances or State Law.

The review conducted by the City of Lee's Summit Codes Administration Department shall not be construed as a structural review of the project.