

GENERAL NOTES

- 1.1.1 PROJECT NOTES:
- 1.1.2 THIS PHOTOVOLTAIC (PV) SYSTEM SHALL COMPLY WITH THE NATIONAL ELECTRIC CODE (NEC) ARTICLE 690, ALL MANUFACTURERS'S LISTING AND INSTALLATION INSTRUCTIONS, AND THE RELEVANT CODES AS SPECIFIED BY THE AUTHORITY HAVING JURISDICTION'S (AHJ) APPLICABLE CODES.
- 1.1.3 THE UTILITY INTERCONNECTION APPLICATION MUST BE APPROVED AND PV SYSTEM INSPECTED PRIOR TO PARALLEL OPERATION
- 1.1.4 GROUND FAULT DETECTION AND INTERRUPTION (GFDI) DEVICE IS INTEGRATED WITH THE MICROINVERTER IN ACCORDANCE WITH NEC 690.41(B)
- 1.1.5 ALL PV SYSTEM COMPONENTS; MODULES, UTILITY-INTERACTIVE INVERTERS, AND SOURCE CIRCUIT COMBINER BOXES ARE IDENTIFIED AND LISTED FOR USE IN PHOTOVOLTAIC SYSTEMS AS REQUIRED BY NEC 690.4:
PV MODULES: UL1703, IEC61730, AND IEC61215, AND NFPA 70 CLASS C FIRE
INVERTERS: UL 1741 CERTIFIED, IEEE 1547, 929, 519
COMBINER BOX(ES): UL 1703 OR UL 1741 ACCESSORY
- 1.1.6 MAX DC VOLTAGE CALCULATED USING MANUFACTURER PROVIDED TEMP COEFFICIENT FOR VOC. IF UNAVAILABLE, MAX DC VOLTAGE CALCULATED ACCORDING TO NEC 690.7.
- 1.1.7 ALL INVERTERS, PHOTOVOLTAIC MODULES, PHOTOVOLTAIC PANELS, AND SOURCE CIRCUIT COMBINERS INTENDED FOR USE IN A PHOTOVOLTAIC POWER SYSTEM WILL BE IDENTIFIED AND LISTED FOR THE APPLICATION PER 690.4 (D). SHALL BE INSTALLED ACCORDING TO ANY INSTRUCTIONS FROM LISTING OR LABELING [NEC 110.3].
- 1.1.8 ALL SIGNAGE TO BE PLACED IN ACCORDANCE WITH LOCAL BUILDING CODE. IF EXPOSED TO SUNLIGHT, IT SHALL BE UV RESISTANT. ALL PLAQUES AND SIGNAGE WILL BE INSTALLED AS REQUIRED BY THE NEC AND AHJ.
- 1.2.1 SCOPE OF WORK:
- 1.2.2 PRIME CONTRACTOR IS RESPONSIBLE FOR THE DESIGN AND SPECIFICATIONS OF THE GRID-TIED PHOTOVOLTAIC SYSTEM RETROFIT. PRIME CONTRACTOR WILL BE RESPONSIBLE FOR COLLECTING EXISTING ONSITE REQUIREMENTS TO DESIGN, SPECIFY, AND INSTALL THE EXTERIOR ROOF-MOUNTED PORTION OF THE PHOTOVOLTAIC SYSTEMS DETAILED IN THIS DOCUMENT.
- 1.3.1 WORK INCLUDES:
- 1.3.2 PV ROOF ATTACHMENTS - SUNMODO NANOMOUNT
- 1.3.3 PV RACKING SYSTEM INSTALLATION - IRONRIDGE XR-10
- 1.3.4 PV MODULE AND INVERTER INSTALLATION - SILFAB SIL-370 HC / ENPHASE IQ8PLUS-72-2-US
- 1.3.5 PV EQUIPMENT GROUNDING
- 1.3.6 PV SYSTEM WIRING TO A ROOF-MOUNTED JUNCTION BOX
- 1.3.7 PV LOAD CENTERS (IF INCLUDED)
- 1.3.8 PV METERING/MONITORING (IF INCLUDED)
- 1.3.9 PV DISCONNECTS
- 1.3.10 PV GROUNDING ELECTRODE & BONDING TO (E) GEC
- 1.3.11 PV FINAL COMMISSIONING
- 1.3.12 (E) ELECTRICAL EQUIPMENT RETROFIT FOR PV
- 1.3.13 SIGNAGE PLACED IN ACCORDANCE WITH LOCAL BUILDING CODE

SCOPE OF WORK

SYSTEM SIZE: STC: 17 X 370W = 6.290KW
PTC: 17 X 344.4W = 5.855KW
(17) SILFAB SIL-370 HC
(17) ENPHASE IQ8PLUS-72-2-US

ATTACHMENT TYPE: SUNMODO NANOMOUNT

MSP UPGRADE: NO

NEW PV SYSTEM: 6.290 kWp

JONES RESIDENCE

4427 SOUTHWEST AMETHYST DRIVE,
LEES SUMMIT, MO 64082



ASSESSOR'S #: 697000708000000000



01

AERIAL PHOTO

NOT TO SCALE



SHEET LIST TABLE

SHEET NUMBER	SHEET TITLE
T-001	COVER PAGE
G-001	NOTES
A-101	SITE PLAN
A-102	ELECTRICAL PLAN
A-103	SOLAR ATTACHMENT PLAN
E-601	LINE DIAGRAM
E-602	DESIGN TABLES
E-603	PLACARDS
S-501	ASSEMBLY DETAILS
R-001	RESOURCE DOCUMENT
R-002	RESOURCE DOCUMENT
R-003	RESOURCE DOCUMENT
R-004	RESOURCE DOCUMENT
R-005	RESOURCE DOCUMENT

PROJECT INFORMATION

OWNER

NAME: ALAINA JONES

PROJECT MANAGER

NAME: TYLER BLANCHARD
PHONE: 816-433-8025

CONTRACTOR

NAME: BARRETT SOLAR
PHONE: 816-433-8025

AUTHORITIES HAVING JURISDICTION

BUILDING: LEES SUMMIT MO
ZONING: LEES SUMMIT MO
UTILITY: EVERGY

DESIGN SPECIFICATIONS

OCCUPANCY: II
CONSTRUCTION: SINGLE-FAMILY
ZONING: RESIDENTIAL
GROUND SNOW LOAD: 20 PSF
WIND EXPOSURE: C
WIND SPEED: 115 MPH

APPLICABLE CODES & STANDARDS

BUILDING: IBC 2018
MECHANICAL: IMC 2018
PLUMBING: IPC 2018
FUEL GAS: IFGC 2018
ELECTRICAL: NEC 2017
FIRE: IFC 2018
ICC/ANSI A117.1-2009



CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025
ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067
HIC. NO.:
ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES
RESIDENCE

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

COVER PAGE

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

T-001.00

(SHEET 1)

	A	B	C	D	E	F	G	H
1	2.1.1	SITE NOTES:		4.5.1	GROUNDING NOTES:			
	2.1.2	A LADDER WILL BE IN PLACE FOR INSPECTION IN COMPLIANCE WITH OSHA REGULATIONS.		2.5.2	GROUNDING SYSTEM COMPONENTS SHALL BE LISTED FOR THEIR PURPOSE, AND GROUNDING DEVICES EXPOSED TO THE ELEMENTS SHALL BE RATED FOR SUCH USE.			
	2.1.3	THE PV MODULES ARE CONSIDERED NON-COMBUSTIBLE AND THIS SYSTEM IS A UTILITY INTERACTIVE SYSTEM WITH STORAGE BATTERIES.		2.5.3	PV EQUIPMENT SHALL BE GROUNDED ACCORDING TO NEC 690.43 AND MINIMUM NEC TABLE 250.122.			
	2.1.4	THE SOLAR PV INSTALLATION WILL NOT OBSTRUCT ANY PLUMBING, MECHANICAL, OR BUILDING ROOF VENTS.		2.5.4	METAL PARTS OF MODULE FRAMES, MODULE RACKING, AND ENCLOSURES CONSIDERED GROUNDED IN ACCORD WITH 250.134 AND 250.136(A).			
	2.1.5	PROPER ACCESS AND WORKING CLEARANCE AROUND EXISTING AND PROPOSED ELECTRICAL EQUIPMENT WILL BE PROVIDED AS PER SECTION NEC 110.26.		2.5.5	EQUIPMENT GROUNDING CONDUCTORS SHALL BE SIZED ACCORDING TO NEC 690.45 AND MICROINVERTER MANUFACTURERS' INSTRUCTIONS.			
2	2.1.6	ROOF COVERINGS SHALL BE DESIGNED, INSTALLED, AND MAINTAINED IN ACCORDANCE WITH THIS CODE AND THE APPROVED MANUFACTURER'S INSTRUCTIONS SUCH THAT THE ROOF COVERING SERVES TO PROTECT THE BUILDING OR STRUCTURE.		2.5.6	EACH MODULE WILL BE GROUNDED USING WEEB GROUNDING CLIPS AS SHOWN IN MANUFACTURER DOCUMENTATION AND APPROVED BY THE AHJ. IF WEEBS ARE NOT USED, MODULE GROUNDING LUGS MUST BE INSTALLED AT THE SPECIFIED GROUNDING LUG HOLES PER THE MANUFACTURERS' INSTALLATION REQUIREMENTS.			
	2.2.1	EQUIPMENT LOCATIONS:		2.5.7	THE GROUNDING CONNECTION TO A MODULE SHALL BE ARRANGED SUCH THAT THE REMOVAL OF A MODULE DOES NOT INTERRUPT A GROUNDING CONDUCTOR TO ANOTHER MODULE.			
	2.2.2	ALL EQUIPMENT SHALL MEET MINIMUM SETBACKS AS REQUIRED BY NEC 110.26.		2.5.8	GROUNDING AND BONDING CONDUCTORS, IF INSULATED, SHALL BE COLORED GREEN OR MARKED GREEN IF #4 AWG OR LARGER [NEC 250.119]			
	2.2.3	WIRING SYSTEMS INSTALLED IN DIRECT SUNLIGHT MUST BE RATED FOR EXPECTED OPERATING TEMPERATURE AS SPECIFIED BY NEC 690.31 (A),(C) AND NEC TABLES 310.15 (B)(2)(A) AND 310.15 (B)(3)(C).		2.5.9	THE GROUNDING ELECTRODE SYSTEM COMPLIES WITH NEC 690.47 AND NEC 250.50 THROUGH 250.106. IF EXISTING SYSTEM IS INACCESSIBLE, OR INADEQUATE, A GROUNDING ELECTRODE SYSTEM PROVIDED ACCORDING TO NEC 250, NEC 690.47 AND AHJ.			
	2.2.4	JUNCTION AND PULL BOXES PERMITTED INSTALLED UNDER PV MODULES ACCORDING TO NEC 690.34.		2.5.10	GROUND-FAULT DETECTION SHALL COMPLY WITH NEC 690.41(B)(1) AND (2) TO REDUCE FIRE HAZARDS			
3	2.2.5	ADDITIONAL AC DISCONNECT(S) SHALL BE PROVIDED WHERE THE INVERTER IS NOT WITHIN SIGHT OF THE AC SERVICING DISCONNECT.						
	2.2.6	ALL EQUIPMENT SHALL BE INSTALLED ACCESSIBLE TO QUALIFIED PERSONNEL ACCORDING TO NEC APPLICABLE CODES.						
	2.2.7	ALL COMPONENTS ARE LISTED FOR THEIR PURPOSE AND RATED FOR OUTDOOR USAGE WHEN APPROPRIATE.		2.6.1	DISCONNECTION AND OVER-CURRENT PROTECTION NOTES:			
				2.6.2	DISCONNECTING SWITCHES SHALL BE WIRED SUCH THAT WHEN THE SWITCH IS OPENED THE CONDUCTORS REMAINING ENERGIZED ARE CONNECTED TO THE TERMINALS MARKED "LINE SIDE" (TYPICALLY THE UPPER TERMINALS).			
	2.3.1	STRUCTURAL NOTES:			DISCONNECTS TO BE ACCESSIBLE TO QUALIFIED UTILITY PERSONNEL, BE LOCKABLE, AND BE A VISIBLE-BREAK SWITCH			
4	2.3.2	RACKING SYSTEM & PV ARRAY WILL BE INSTALLED ACCORDING TO CODE-COMPLIANT INSTALLATION MANUAL. TOP CLAMPS REQUIRE A DESIGNATED SPACE BETWEEN MODULES, AND RAILS MUST ALSO EXTEND A MINIMUM DISTANCE BEYOND EITHER EDGE OF THE ARRAY/SUBARRAY, ACCORDING TO RAI MANUFACTURER'S INSTRUCTIONS.		2.6.3	PV SYSTEM CIRCUITS INSTALLED ON OR IN BUILDINGS SHALL INCLUDE A RAPID SHUTDOWN FUNCTION TO REDUCE SHOCK HAZARD FOR EMERGENCY RESPONDERS IN ACCORDANCE WITH 690.12(A) THROUGH (D).			
	2.3.3	JUNCTION BOX WILL BE INSTALLED PER MANUFACTURERS' SPECIFICATIONS. IF ROOF-PENETRATING TYPE, IT SHALL BE FLASHED & SEALED PER LOCAL REQUIREMENTS.		2.6.4	ALL OCPD RATINGS AND TYPES SPECIFIED ACCORDING TO NEC 690.8, 690.9, AND 240.			
	2.3.4	ROOFTOP PENETRATIONS FOR PV RACEWAY WILL BE COMPLETED AND SEALED W/ APPROVED CHEMICAL SEALANT PER CODE BY A LICENSED CONTRACTOR.		2.6.5	MICROINVERTER BRANCHES CONNECTED TO A SINGLE BREAKER OR GROUPED FUSES IN ACCORDANCE WITH NEC 110.3(B).			
	2.3.5	ALL PV RELATED ROOF ATTACHMENTS TO BE SPACED NO GREATER THAN THE SPAN DISTANCE SPECIFIED BY THE RACKING MANUFACTURER.		2.6.6	IF REQUIRED BY AHJ, SYSTEM WILL INCLUDE ARC-FAULT CIRCUIT PROTECTION ACCORDING TO NEC 690.11 AND UL1699B.			
	2.3.6	WHEN POSSIBLE, ALL PV RELATED RACKING ATTACHMENTS WILL BE STAGGERED AMONGST THE ROOF FRAMING MEMBERS.		2.6.7				
5	2.4.1	WIRING & CONDUIT NOTES:		2.7.1	INTERCONNECTION NOTES:			
	2.4.2	ALL CONDUIT AND WIRE WILL BE LISTED AND APPROVED FOR THEIR PURPOSE. CONDUIT AND WIRE SPECIFICATIONS ARE BASED ON MINIMUM CODE REQUIREMENTS AND ARE NOT MEANT TO LIMIT UP-SIZING.		2.7.2	LOAD-SIDE INTERCONNECTION SHALL BE IN ACCORDANCE WITH [NEC 705.12 (B)]			
	2.4.3	CONDUCTORS SIZED ACCORDING TO NEC 690.8, NEC 690.7.		2.7.3	THE SUM OF THE UTILITY OCPD AND INVERTER CONTINUOUS OUTPUT MAY NOT EXCEED 120% OF BUSBAR RATING [NEC 705.12(D)(2)(3)].			
	2.4.4	VOLTAGE DROP LIMITED TO 1.5%.		2.7.4	THE SUM OF 125 PERCENT OF THE POWER SOURCE(S) OUTPUT CIRCUIT CURRENT AND THE RATING OF THE OVERCURRENT DEVICE PROTECTING THE BUSBAR SHALL NOT EXCEED 120 PERCENT OF THE AMPACITY OF THE BUSBAR, PV DEDICATED BACKFEED BREAKERS MUST BE LOCATED OPPOSITE END OF THE BUS FROM THE UTILITY SOURCE OCPD [NEC 705.12(B)(2)(3)].			
	2.4.5	DC WIRING LIMITED TO MODULE FOOTPRINT. MICROINVERTER WIRING SYSTEMS SHALL BE LOCATED AND SECURED UNDER THE ARRAY W/ SUITABLE WIRING CLIPS.		2.7.5	AT MULTIPLE ELECTRIC POWER SOURCES OUTPUT COMBINER PANEL, TOTAL RATING OF ALL OVERCURRENT DEVICES SHALL NOT EXCEED AMPACITY OF BUSBAR. HOWEVER, THE COMBINED OVERCURRENT DEVICE MAY BE EXCLUDED ACCORDING TO NEC 705.12 (B)(2)(3)(C).			
6	2.4.6	AC CONDUCTORS COLORED OR MARKED AS FOLLOWS:		2.7.6	FEEDER TAP INTERCONNECTION (LOAD SIDE) ACCORDING TO NEC 705.12 (B)(2)(1)			
		PHASE A OR L1- BLACK		2.7.7	SUPPLY SIDE TAP INTERCONNECTION ACCORDING TO NEC 705.12 (A) WITH SERVICE ENTRANCE CONDUCTORS IN ACCORDANCE WITH NEC 230.42			
		PHASE B OR L2- RED, OR OTHER CONVENTION IF THREE PHASE		2.7.8	BACKFEEDING BREAKER FOR ELECTRIC POWER SOURCES OUTPUT IS EXEMPT FROM ADDITIONAL FASTENING [NEC 705.12 (B)(5)].			
		PHASE C OR L3- BLUE, YELLOW, ORANGE**, OR OTHER CONVENTION						
		NEUTRAL- WHITE OR GRAY						
		IN 4-WIRE DELTA CONNECTED SYSTEMS THE PHASE WITH HIGHER VOLTAGE TO BE MARKED ORANGE [NEC 110.15].						

RELEASED FOR
CONSTRUCTION
As Noted on Plans Review

Development Services Department
Lee's Summit, Missouri
04/03/2022



CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025
ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067
HIC. NO.:
ELE. NO.:
UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES
RESIDENCE
4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 69700070800000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

NOTES

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

G-001.00
(SHEET 2)

GENERAL NOTES

1. FIELD VERIFY ALL MEASUREMENTS
2. ITEMS BELOW MAY NOT BE ON THIS PAGE

----- PROPERTY LINE

NOTE: FUSED DISCONNECT
WITHIN 4 FEET OF THE METER

SOUTHWEST AMETHYST DRIVE

ENTRANCE

20'-3"

38'-7"

12'-0"

UTILITY METER
AC DISCONNECT
AC COMBINER BOX

AREA OF WORK


43'-0"

01

SITE PLAN

1/16" = 1'-0"

0 8' 16'



Wyssling Consulting, PLLC
76 N Meadowbrook Drive Alpine UT 84004
Missouri COA # 2020037943
Signed 5/9/2022

CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025
ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161
LIC. NO.: 2101209067
HIC. NO.:
ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES RESIDENCE

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

SITE PLAN

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

A-101.00

(SHEET 3)

GENERAL NOTES

1. FIELD VERIFY ALL MEASUREMENTS
2. ITEMS BELOW MAY NOT BE ON THIS PAGE

- (A) MODULE STRINGING
- (B) MODULE STRINGING



NOTE: FUSED DISCONNECT
WITHIN 4 FEET OF THE METER

CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025

ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067

HIC. NO.:

ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES RESIDENCE

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD



Wyssling Consulting, PLLC
76 N Meadowbrook Drive Alpine UT 84004
Missouri COA # 2020037943

Signed 5/9/2022

PAPER SIZE: 11" x 17" (ANSI B)

ELECTRICAL PLAN


DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

A-102.00
(SHEET 4)



GENERAL NOTES

1. FIELD VERIFY ALL MEASUREMENTS
2. ITEMS BELOW MAY NOT BE ON THIS PAGE

--- ROOF RAFTERS




ROOF MATERIAL IS ASPHALT SHINGLE

FLUSH MOUNT SOLAR MODULES
ATTACHED TO ROOF SURFACE (SEE
SHEET S-501 FOR MOUNTING DETAILS)

01

SOLAR ATTACHMENT PLAN

1/8" = 1'-0"



MODULE:
SILFAB
SIL-370 HC
370 WATTS

CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025

ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067

HIC. NO.:

ELE. NO.:


UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES RESIDENCE

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD



Wyssling Consulting, PLLC
76 N Meadowbrook Drive Alpine UT 84004
Missouri COA # 2020037943

Signed 5/9/2022

PAPER SIZE: 11" x 17" (ANSI B)

SOLAR ATTACHMENT PLAN

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

A-103.00

(SHEET 5)

CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025
ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067
HIC. NO.:
ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

**JONES
RESIDENCE**

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

LINE DIAGRAM

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

E-601.00
(SHEET 6)

CONDUCTOR AND CONDUIT SCHEDULE W/ELECTRICAL CALCULATIONS

ID	TYPICAL	CONDUCTOR	CONDUIT	CURRENT-CARRYING CONDUCTORS IN CONDUIT	OCPD	EGC	TEMP. CORR. FACTOR	CONDUIT FILL FACTOR	CONT. CURRENT	MAX. CURRENT (125%)	BASE AMP.	DERATED AMP.	TERM. TEMP. RATING	AMP. @ TERMINAL
1	1	10 AWG THWN-2, COPPER	0.5" DIA EMT	4	20A	8 AWG THWN-2, COPPER	0.91 (36.2 °C)	0.8	10.89A	13.61A	40A	29.12A	75°C	35A
2	1	10 AWG THWN-2, COPPER	0.5" DIA EMT	2	30A	8 AWG THWN-2, COPPER	0.91 (36.2 °C)	1	20.57A	25.71A	40A	36.4A	75°C	35A
3	1	6 AWG THWN-2, COPPER	0.75" DIA EMT	2	N/A	8 AWG THWN-2, COPPER	0.91 (36.2 °C)	1	20.57A	25.71A	75A	68.25A	75°C	65A

- A MODULE STRINGING
- B MODULE STRINGING

SYSTEM EQUIPPED WITH RAPID SHUTDOWN
DISCONNECT PER NEC 690.12
SYSTEM COMPLIANT WITH NEC 690.13

MAX. CONTINUOUS CURRENT: 65A
MAX. OCPD: 90A
125A AC COMBINER BOX
(X-IQ-AM1-240-4)
120/240V, 1Ø, 3W

NOTE: FUSED DISCONNECT
WITHIN 4FT OF THE METER

TO UTILITY
GRID (UG)

(E)
UTILITY
METER


GROUND
ROD
(E) GROUNDING
ELECTRODE

TO (E)
LOADS

(E) MAIN ELECTRICAL PANEL
240/120 V 1Ø, 3W
MAIN BUSS: 200A

EQUIPMENT LEFT
OF LINE IS (N) NEW

EQUIPMENT RIGHT OF
LINE IS (E) EXISTING
UNLESS OTHERWISE NOTED.



CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025
ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067
HIC. NO.:
ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES
RESIDENCE

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

DESIGN TABLES

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

E-602.00

(SHEET 7)

SYSTEM SUMMARY		
	BRANCH #1	BRANCH #2
INVERTERS PER BRANCH	8	9
MAX AC CURRENT	9.68A	10.89A
MAX AC OUTPUT POWER	2,400W	2,700W
ARRAY STC POWER	6,290W	
ARRAY PTC POWER	5,855W	
MAX AC CURRENT	20.57A	
MAX AC POWER	5,100W	
DERATED (CEC) AC POWER	5,100W	

MODULES											
REF.	QTY.	MAKE AND MODEL	PMAX	PTC	ISC	IMP	VOC	VMP	TEMP. COEFF. OF VOC	FUSE RATING	
PM1-17	17	SILFAB SIL-370 HB	370W	344.4W	11.25A	10.6A	41.75V	34.95V	-0.117V/°C (-0.28%/°C)	20A	

INVERTERS											
REF.	QTY.	MAKE AND MODEL	AC VOLTAGE	GROUND	OCPD RATING	RATED POWER	MAX OUTPUT CURRENT	MAX INPUT CURRENT	MAX INPUT VOLTAGE	CEC WEIGHTED EFFICIENCY	
I1-17	17	ENPHASE IQ8PLUS-72-2-US	240V	FLOATING	20A	290W	1.21A	15A	60V	97.0%	

DISCONNECTS				
REF.	QTY.	MAKE AND MODEL	RATED CURRENT	MAX RATED VOLTAGE
SW1	1	CUTLER HAMMER DG222NRB OR EQUIV.	60A	240VAC

OCPDS			
REF.	QTY.	RATED CURRENT	MAX VOLTAGE
CB1-2	2	20A	240VAC
CB3	1	10A	240VAC
F1-2	2	30A	240VAC

ASHRAE EXTREME LOW	-22.6°C (-8.7°F), SOURCE: CHARLES B WHEELER D (39.12°; -94.59°)
ASHRAE 2% HIGH	36.2°C (97.2°F), SOURCE: CHARLES B WHEELER D (39.12°; -94.59°)

BILL OF MATERIALS							
CATEGORY	MAKE	MODEL NUMBER	REF	QTY	UNIT	QTY/UNIT	DESCRIPTION
MODULE	SILFAB	SIL-370 HB	PM1-17	17	PIECES	1	SILFAB SIL-370 HB 370W 120 HALF-CUT CELLS, MONOCRYSTALLINE SILICON
INVERTER	ENPHASE	IQ8PLUS-72-2-US	I1-17	17	PIECES	1	ENPHASE IQ8PLUS-72-2-US 290W INVERTER
DISCONNECT	CUTLER HAMMER	DG222NRB	SW1	1	PIECE	1	CUTLER HAMMER DG222NRB, FUSED, 2-POLE, 60A, 240VAC OR EQUIVALENT
MISC ELECTRICAL EQUIPMENT		GEN-CABLE-CLIP	HDWR20-105	85	PIECES	1	GENERIC CABLE CLIP
AC COMBINER PANEL		ENPHASE-IQ4-PANEL	EP1	1	PIECE	1	ENPHASE IQ COMBINER 4 (X-IQ-AM1-240-4)
MONITORING		ENPHASE-ENVOY	ENV1	1	PIECE	1	ENPHASE ENVOY
WIRING	ENPHASE	Q-12-17-240	EN1-17	17	PIECES	1	ENPHASE ENGAGE (TM) TRUNK CABLE
WIRING	ENPHASE	Q-TERM-10	EN18	1	BUNDLE	10	ENPHASE ENGAGE (TM) BRANCH TERMINATOR
WIRING	ENPHASE	Q-SEAL-10	EN19	1	BUNDLE	10	ENPHASE ENGAGE (TM) WATERTIGHT SEALING CAP
WIRING		GEN-10-AWG-THWN-2-CU-RD	WR1-2	100	FEET	1	10 AWG THWN-2, COPPER, RED (LINE 1)
WIRING		GEN-10-AWG-THWN-2-CU-BLK	WR1-2	100	FEET	1	10 AWG THWN-2, COPPER, BLACK (LINE 2)
WIRING		GEN-10-AWG-THWN-2-CU-WH	WR2	10	FEET	1	10 AWG THWN-2, COPPER, WHITE (NEUTRAL)
WIRING		GEN-8-AWG-THWN-2-CU-GR	WR1-3	65	FEET	1	8 AWG THWN-2, COPPER, GREEN (GROUND)
WIRING		GEN-6-AWG-THWN-2-CU-RD	WR3	10	FEET	1	6 AWG THWN-2, COPPER, RED (LINE 1)
WIRING		GEN-6-AWG-THWN-2-CU-BLK	WR3	10	FEET	1	6 AWG THWN-2, COPPER, BLACK (LINE 2)
WIRING		GEN-6-AWG-THWN-2-CU-WH	WR3	10	FEET	1	6 AWG THWN-2, COPPER, WHITE (NEUTRAL)
WIREWAY	ENPHASE	ET-SPLK-05	EN5	1	BUNDLE	5	ENPHASE ENGAGE (TM) ENGAGE COUPLER
WIREWAY		GEN-EMT-0.5" DIA	WW1-2	55	FEET	1	EMT CONDUIT, 0.5" DIA
WIREWAY		GEN-EMT-0.75" DIA	WW3	10	FEET	1	EMT CONDUIT, 0.75" DIA
OCPD	GENERIC MANUFACTURER	GEN-CB-20A-240VAC	CB1-2	2	PIECES	1	CIRCUIT BREAKER, 20A, 240VAC
OCPD	GENERIC MANUFACTURER	GEN-CB-10A-240VAC	CB3	1	PIECE	1	CIRCUIT BREAKER, 10A, 240VAC
OCPD	GENERIC MANUFACTURER	GEN-FU-30A-240VAC	F1-2	2	PIECES	1	FUSE, 30A, 240VAC
TRANSITION BOX	GENERIC MANUFACTURER	GEN-AWB-TB-4-4X	JB1	1	PIECE	1	TRANSITION/PASS-THROUGH BOX, WITH 4 TERMINAL BLOCKS

CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025
ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067
HIC. NO.:
ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

**JONES
RESIDENCE**

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

ASSEMBLY DETAILS

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

S-501.00
(SHEET 9)

GENERAL NOTES

1. FIELD VERIFY ALL MEASUREMENTS


SHEET KEYNOTES

1. ROOF MATERIAL: ASPHALT SHINGLE
2. ROOF STRUCTURE: KNEE WALL & COLLAR TIE
3. ATTACHMENT TYPE: SUNMODO NANOMOUNT
4. MODULE MANUFACTURER: SILFAB
5. MODULE MODEL: SIL-370 HC
6. MODULE LENGTH: 69.4"
7. MODULE WIDTH: 40.8"
8. MODULE WEIGHT: 43.4 LBS
9. SEE SHEET A-103 FOR DIMENSION(S)
10. MIN. FIRE OFFSET: 3' FROM RIDGE/RAKE, 18" FROM HIPS/VALLEYS
11. RAFTER SPACING: 24" IN. O.C.
12. RAFTER SIZE: 2X6" NOMINAL
13. LAG BOLT DIAMETER: 5/16 IN.
14. LAG BOLT EMBEDMENT: 2 1/2 IN. MIN.
15. TOTAL # OF ATTACHMENTS: 63
16. TOTAL AREA: 4334.28 SQ.FT.
17. TOTAL WEIGHT: 857.76 LBS
18. WEIGHT PER ATTACHMENT: 13.62 LBS
19. DISTRIBUTED LOAD: 2.57 PSF
20. MAX. HORIZONTAL STANDOFF: 48 IN.
21. MAX. VERTICAL STANDOFF: IN ACCORDANCE WITH MODULE MANUFACTURER'S INSTRUCTIONS.
22. STANDOFF STAGGERING: YES
23. RAIL MANUFACTURER (OR EQUIV.): IRONRIDGE
24. RAIL MODEL (OR EQUIVALENT): XR-10
25. RAIL WEIGHT: 0.436 PLF
26. MAX. RAFTER SPAN: 7 FT.
27. MODULE CLEARANCE: 3 IN. MIN., 6 IN. MAX.




Wyssling Consulting, PLLC
76 N Meadowbrook Drive Alpine UT 84004
Missouri CQA # 2020037943


Signed 5/9/2022




D2 RACKING DETAIL (LONGITUDINAL)
NOT TO SCALE




D1 RACKING DETAIL (TRANSVERSE)
NOT TO SCALE



D3 RACKING DETAIL (TOP)
NOT TO SCALE




D4 DETAIL (TRANSVERSE)
NOT TO SCALE



D5 DETAIL (LONGITUDINAL)
NOT TO SCALE

SILFAB PRIME

SIL-370 HC



RELIABLE ENERGY.
DIRECT FROM THE SOURCE.

Introducing Silfab Prime.

Designed to outperform.

Dependable, durable, high-performance solar panels
engineered for North American homeowners.

SILFABSOLAR.COM



CHUBB

* Chubb provides error and omission insurance to Silfab Solar Inc.

ELECTRICAL SPECIFICATIONS		370	
Test Conditions		STC	NOCT
Module Power (Pmax)	Wp	370	276
Maximum power voltage (Vpmax)	V	34.95	32.48
Maximum power current (Ipmax)	A	10.60	8.50
Open circuit voltage (Voc)	V	41.75	39.16
Short circuit current (Isc)	A	11.25	9.07
Module efficiency	%	20.2%	18.9%
Maximum system voltage (VDC)	V	1000	
Series fuse rating	A	20	
Power Tolerance	Wp	0 to +10	


Measurement conditions: STC 1000 W/m² • AM 1.5 • Temperature 25 °C • NOCT 800 W/m² • AM 1.5 • Measurement uncertainty ≤ 3%
Sun simulator calibration reference modules from Fraunhofer Institute. Electrical characteristics may vary by ±5% and power by 0 to +10W.

MECHANICAL PROPERTIES / COMPONENTS	METRIC	IMPERIAL
Module weight	19.5kg ±0.2kg	43lbs ±0.4lbs
Dimensions (H x L x D)	1762 mm x 1037 mm x 35 mm	69.4 in x 40.8 in x 1.37 in
Maximum surface load (wind/snow)*	5400 Pa rear load / 5400 Pa front load	112.8 lb/ft ² rear load / 112.8 lb/ft ² front load
Hail impact resistance	ø 25 mm at 83 km/h	ø 1 in at 51.6 mph
Cells	120 Half cells - Si mono PERC 9 busbar - 83 x 166 mm	120 Half cells - Si mono PERC 9 busbar - 3.26 x 6.53 in
Glass	3.2 mm high transmittance, tempered, DSM antireflective coating	0.126 in high transmittance, tempered, DSM antireflective coating
Cables and connectors (refer to installation manual)	1350 mm, ø 5.7 mm, MC4 from Staubli	53.15 in, ø 0.22 in (12AWG), MC4 from Staubli
Backsheet	High durability, superior hydrolysis and UV resistance, multi-layer dielectric film, fluorine-free PV backsheet	
Frame	Anodized Aluminum (Black)	
Bypass diodes	3 diodes-30SQ045T (45V max DC blocking voltage, 30A max forward rectified current)	
Junction Box	UL 3730 Certified, IEC 62790 Certified, IP68 rated	

TEMPERATURE RATINGS		WARRANTIES	
Temperature Coefficient Isc	+0.064 %/°C	Module product workmanship warranty	25 years**
Temperature Coefficient Voc	-0.28 %/°C	Linear power performance guarantee	30 years
Temperature Coefficient Pmax	-0.36 %/°C		≥ 97.1% end 1st yr ≥ 91.6% end 12th yr ≥ 85.1% end 25th yr ≥ 82.6% end 30th yr
NOCT (± 2°C)	45 °C		
Operating temperature	-40/+85 °C		

CERTIFICATIONS		SHIPPING SPECS	
Product	ULC ORD C1703, UL1703, CEC listed, UL 61215-1/-2, UL 61730-1/-2, IEC 61215-1/-2, IEC 61730-1/-2, CSA C22.2#61730-1/-2, IEC 62716 Ammonia Corrosion; IEC61701:2011 Salt Mist Corrosion Certified, UL Fire Rating: Type 2	Modules Per Pallet:	26 or 26 (California)
Factory	ISO9001:2015	Pallets Per Truck	34 or 32 (California)
		Modules Per Truck	884 or 832 (California)

* ⚠ Warning. Read the Safety and Installation Manual for mounting specifications and before handling, installing and operating modules.
** 12 year extendable to 25 years subject to registration and conditions outlined under "Warranty" at silfabsolar.com
PAN files generated from 3rd party performance data are available for download at: silfabsolar.com/downloads



SILFAB SOLAR INC.

800 Cornwall Ave
Bellingham WA 98225 USA
T +1 360.569.4733
info@silfabsolar.com

SILFABSOLAR.COM

1770 Port Drive
Burlington WA 98233 USA
T +1 360.569.4733

240 Courtneypark Drive East
Mississauga ON L5T 2Y3 Canada
T +1 905.255.2501
F +1 905.696.0267

Silfab - SIL-370-HC-20220216

No reproduction of any kind is allowed without permission. Data and information is subject to modifications without notice. © Silfab Solar Inc., 2021. Silfab Solar™ is a trademark of Silfab Solar Inc.

RELEASED FOR
CONSTRUCTION
As Noted on Plans Review

Development Services Department
Lee's Summit, Missouri
04/03/2022



CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025

ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067

HIC. NO.:

ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES
RESIDENCE

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

RESOURCE DOCUMENT

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

R-001.00

(SHEET 10)



DATA SHEET



IQ8 Series Microinverters

Our newest IQ8 Microinverters are the industry's first microgrid-forming, software-defined microinverters with split-phase power conversion capability to convert DC power to AC power efficiently. The brain of the semiconductor-based microinverter is our proprietary application-specific integrated circuit (ASIC) which enables the microinverter to operate in grid-tied or off-grid modes. This chip is built in advanced 55nm technology with high speed digital logic and has super-fast response times to changing loads and grid events, alleviating constraints on battery sizing for home energy systems.



Part of the Enphase Energy System, IQ8 Series Microinverters integrate with the Enphase IQ Battery, Enphase IQ Gateway, and the Enphase App monitoring and analysis software.



IQ8 Series Microinverters redefine reliability standards with more than one million cumulative hours of power-on testing, enabling an industry-leading limited warranty of up to 25 years.



Connect PV modules quickly and easily to IQ8 Series Microinverters using the included Q-DCC-2 adapter cable with plug-n-play MC4 connectors.



IQ8 Series Microinverters are UL Listed as PV Rapid Shut Down Equipment and conform with various regulations, when installed according to manufacturer's instructions.

© 2022 Enphase Energy. All rights reserved. Enphase, the Enphase logo, IQ8 microinverters, and other names are trademarks of Enphase Energy, Inc. Data subject to change.

IQ8SE-DS-0001-01-EN-US-2022-03-01

Easy to install

- Lightweight and compact with plug-n-play connectors
- Power Line Communication (PLC) between components
- Faster installation with simple two-wire cabling

High productivity and reliability

- Produce power even when the grid is down
- More than one million cumulative hours of testing
- Class II double-insulated enclosure
- Optimized for the latest high-powered PV modules

Microgrid-forming

- Complies with the latest advanced grid support
- Remote automatic updates for the latest grid requirements
- Configurable to support a wide range of grid profiles
- Meets CA Rule 21 (UL 1741-SA) requirements

IQ8 Series Microinverters

INPUT DATA (DC)		IQ8-60-2-US	IQ8PLUS-72-2-US	IQ8M-72-2-US	IQ8A-72-2-US	IQ8H-240-72-2-US	IQ8H-208-72-2-US ¹
Commonly used module pairings ²	W	235 – 350	235 – 440	260 – 460	295 – 500	320 – 540+	295 – 500+
Module compatibility		60-cell/120 half-cell		60-cell/120 half-cell, 66-cell/132 half-cell and 72-cell/144 half-cell			
MPPT voltage range	V	27 – 37	29 – 45	33 – 45	36 – 45	38 – 45	38 – 45
Operating range	V	25 – 48			25 – 58		
Min/max start voltage	V	30 / 48			30 / 58		
Max input DC voltage	V	50			60		
Max DC current ³ [module Isc]	A			15			
Overvoltage class DC port				II			
DC port backfeed current	mA			0			
PV array configuration		1x1 Ungrounded array; No additional DC side protection required; AC side protection requires max 20A per branch circuit					
OUTPUT DATA (AC)		IQ8-60-2-US	IQ8PLUS-72-2-US	IQ8M-72-2-US	IQ8A-72-2-US	IQ8H-240-72-2-US	IQ8H-208-72-2-US
Peak output power	VA	245	300	330	366	384	366
Max continuous output power	VA	240	290	325	349	380	360
Nominal (L-L) voltage/range ⁴	V			240 / 211 – 264			208 / 183 – 250
Max continuous output current	A	1.0	1.21	1.35	1.45	1.58	1.73
Nominal frequency	Hz			60			
Extended frequency range	Hz			50 – 68			
Max units per 20 A (L-L) branch circuit ⁵		16	13	11	11	10	9
Total harmonic distortion				<5%			
Overvoltage class AC port				III			
AC port backfeed current	mA			30			
Power factor setting				1.0			
Grid-tied power factor (adjustable)				0.85 leading – 0.85 lagging			
Peak efficiency	%	97.5	97.6	97.6	97.6	97.6	97.4
CEC weighted efficiency	%	97	97	97	97.5	97	97
Night-time power consumption	mW			60			
MECHANICAL DATA							
Ambient temperature range				-40°C to +60°C (-40°F to +140°F)			
Relative humidity range				4% to 100% (condensing)			
DC Connector type				MC4			
Dimensions (HxWxD)				212 mm (8.3") x 175 mm (6.9") x 30.2 mm (1.2")			
Weight				1.08 kg (2.38 lbs)			
Cooling				Natural convection – no fans			
Approved for wet locations				Yes			
Acoustic noise at 1 m				<60 dBA			
Pollution degree				PD3			
Enclosure				Class II double-insulated, corrosion resistant polymeric enclosure			
Environ. category / UV exposure rating				NEMA Type 6 / outdoor			
COMPLIANCE							
		CA Rule 21 (UL 1741-SA), UL 62109-1, UL1741/IEEE1547, FCC Part 15 Class B, ICES-0003 Class B, CAN/CSA-C22.2 NO. 107.1-01					
Certifications		This product is UL Listed as PV Rapid Shut Down Equipment and conforms with NEC 2014, NEC 2017, and NEC 2020 section 690.12 and C22.1-2018 Rule 64-218 Rapid Shutdown of PV Systems, for AC and DC conductors, when installed according to manufacturer's instructions.					

(1) The IQ8H-208 variant will be operating in grid-tied mode only at 208V AC. (2) No enforced DC/AC ratio. See the compatibility calculator at <https://link.enphase.com/module-compatibility> (3) Maximum continuous input DC current is 10.6A (4) Nominal voltage range can be extended beyond nominal if required by the utility. (5) Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area.

IQ8SE-DS-0001-01-EN-US-2022-03-01

CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025
ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067

HIC. NO.:

ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES RESIDENCE

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

RESOURCE DOCUMENT

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

R-002.00

(SHEET 11)

Enphase IQ Combiner 4/4C

X-IQ-AM1-240-4

X-IQ-AM1-240-4C



X-IQ-AM1-240-4C

X-IQ-AM1-240-4



To learn more about Enphase offerings, visit enphase.com

The **Enphase IQ Combiner 4/4C** with Enphase IQ Gateway and integrated LTE-M1 cell modem (included only with IQ Combiner 4C) consolidates interconnection equipment into a single enclosure and streamlines IQ microinverters and storage installations by providing a consistent, pre-wired solution for residential applications. It offers up to four 2-pole input circuits and Eaton BR series busbar assembly.

Smart

- Includes IQ Gateway for communication and control
- Includes Enphase Mobile Connect cellular modem (CELLMODEM-M1-06-SP-05), included only with IQ Combiner 4C
- Includes solar shield to match Enphase IQ Battery aesthetics and deflect heat
- Flexible networking supports Wi-Fi, Ethernet, or cellular
- Optional AC receptacle available for PLC bridge
- Provides production metering and consumption monitoring

Simple

- Centered mounting brackets support single stud mounting
- Supports bottom, back and side conduit entry
- Up to four 2-pole branch circuits for 240 VAC plug-in breakers (not included)
- 80A total PV or storage branch circuits

Reliable

- Durable NRTL-certified NEMA type 3R enclosure
- Five-year limited warranty
- Two years labor reimbursement program coverage included for both the IQ Combiner SKU's
- UL listed



Enphase IQ Combiner 4/4C

MODEL NUMBER

IQ Combiner 4 (X-IQ-AM1-240-4)

IQ Combiner 4 with Enphase IQ Gateway printed circuit board for integrated revenue grade PV production metering (ANSI C12.20 +/- 0.5%) and consumption monitoring (+/- 2.5%). Includes a silver solar shield to match the IQ Battery system and IQ System Controller 2 and to deflect heat.

IQ Combiner 4C (X-IQ-AM1-240-4C)

IQ Combiner 4C with Enphase IQ Gateway printed circuit board for integrated revenue grade PV production metering (ANSI C12.20 +/- 0.5%) and consumption monitoring (+/- 2.5%). Includes Enphase Mobile Connect cellular modem (CELLMODEM-M1-06-SP-05), a plug-and-play industrial-grade cell modem for systems up to 60 microinverters. (Available in the US, Canada, Mexico, Puerto Rico, and the US Virgin Islands, where there is adequate cellular service in the installation area.) Includes a silver solar shield to match the IQ Battery and IQ System Controller and to deflect heat.

ACCESSORIES AND REPLACEMENT PARTS

(not included, order separately)

Ensemble Communications Kit
COMMS-CELLMODEM-M1-06
CELLMODEM-M1-06-SP-05
CELLMODEM-M1-06-AT-05

- Includes COMMS-KIT-01 and CELLMODEM-M1-06-SP-05 with 5-year Sprint data plan for Ensemble sites
- 4G based LTE-M1 cellular modem with 5-year Sprint data plan
- 4G based LTE-M1 cellular modem with 5-year AT&T data plan

Circuit Breakers

BRK-10A-2-240V
BRK-15A-2-240V
BRK-20A-2P-240V
BRK-15A-2P-240V-B
BRK-20A-2P-240V-B

Supports Eaton BR210, BR215, BR220, BR230, BR240, BR250, and BR260 circuit breakers.
Circuit breaker, 2 pole, 10A, Eaton BR210
Circuit breaker, 2 pole, 15A, Eaton BR215
Circuit breaker, 2 pole, 20A, Eaton BR220
Circuit breaker, 2 pole, 15A, Eaton BR215B with hold down kit support
Circuit breaker, 2 pole, 20A, Eaton BR220B with hold down kit support

EPLC-01

Power line carrier (communication bridge pair), quantity - one pair

XA-SOLARSHIELD-ES

Replacement solar shield for IQ Combiner 4/4C

XA-PLUG-120-3

Accessory receptacle for Power Line Carrier in IQ Combiner 4/4C (required for EPLC-01)

XA-ENV-PCBA-3

Replacement IQ Gateway printed circuit board (PCB) for Combiner 4/4C

X-IQ-NA-HD-125A

Hold down kit for Eaton circuit breaker with screws.

ELECTRICAL SPECIFICATIONS

Rating

Continuous duty

System voltage

120/240 VAC, 60 Hz

Eaton BR series busbar rating

125 A

Max. continuous current rating

65 A

Max. continuous current rating (input from PV/storage)

64 A

Max. fuse/circuit rating (output)

90 A

Branch circuits (solar and/or storage)

Up to four 2-pole Eaton BR series Distributed Generation (DG) breakers only (not included)

Max. total branch circuit breaker rating (input)

80A of distributed generation / 95A with IQ Gateway breaker included

Production metering CT

200 A solid core pre-installed and wired to IQ Gateway

Consumption monitoring CT (CT-200-SPLIT)

A pair of 200 A split core current transformers

MECHANICAL DATA

Dimensions (WxHxD)

37.5 x 49.5 x 16.8 cm (14.75" x 19.5" x 6.63"). Height is 21.06" (53.5 cm) with mounting brackets.

Weight

7.5 kg (16.5 lbs)

Ambient temperature range

-40° C to +46° C (-40° to 115° F)

Cooling

Natural convection, plus heat shield

Enclosure environmental rating

Outdoor, NRTL-certified, NEMA type 3R, polycarbonate construction

Wire sizes

• 20 A to 50 A breaker inputs: 14 to 4 AWG copper conductors
• 60 A breaker branch input: 4 to 1/0 AWG copper conductors
• Main lug combined output: 10 to 2/0 AWG copper conductors
• Neutral and ground: 14 to 1/0 copper conductors
Always follow local code requirements for conductor sizing.

Altitude

To 2000 meters (6,560 feet)

INTERNET CONNECTION OPTIONS

Integrated Wi-Fi

802.11b/g/n

Cellular

CELLMODEM-M1-06-SP-05, CELLMODEM-M1-06-AT-05 (4G based LTE-M1 cellular modem). Note that an Enphase Mobile Connect cellular modem is required for all Ensemble installations.

Ethernet

Optional, 802.3, Cat5E (or Cat 6) UTP Ethernet cable (not included)

COMPLIANCE

Compliance, IQ Combiner

UL 1741, CAN/CSA C22.2 No. 107.1, 47 CFR, Part 15, Class B, ICES 003
Production metering: ANSI C12.20 accuracy class 0.5 (PV production)
Consumption metering: accuracy class 2.5

Compliance, IQ Gateway

UL 60601-1/CANCSA 22.2 No. 61010-1

To learn more about Enphase offerings, visit enphase.com

© 2021 Enphase Energy. All rights reserved. Enphase, the Enphase logo, IQ Combiner 4/4C, and other names are trademarks of Enphase Energy, Inc. Data subject to change. 10-21-2021



CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025

ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067

HIC. NO.:

ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES RESIDENCE

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 69700070800000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

RESOURCE DOCUMENT

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

R-003.00

(SHEET 12)





XR Rail Family

Tech Brief

Solar Is Not Always Sunny

Over their lifetime, solar panels experience countless extreme weather events. Not just the worst storms in years, but the worst storms in 40 years. High winds capable of ripping panels from a roof, and snowfalls weighing enough to buckle a panel frame.

XR Rails are the structural backbone preventing these results. They resist uplift, protect against buckling and safely and efficiently transfer loads into the building structure. Their superior spanning capability requires fewer roof attachments, reducing the number of roof penetrations and the amount of installation time.



Force-Stabilizing Curve

Sloped roofs generate both vertical and lateral forces on mounting rails which can cause them to bend and twist. The curved shape of XR Rails is specially designed to increase strength in both directions while resisting the twisting. This unique feature ensures greater security during extreme weather and a longer system lifetime.

Compatible with Flat & Pitched Roofs



XR Rails are compatible with FlashFoot and other pitched roof attachments.



IronRidge offers a range of tilt leg options for flat roof mounting applications.

Corrosion-Resistant Materials

All XR Rails are made of 6000-series aluminum alloy, then protected with an anodized finish. Anodizing prevents surface and structural corrosion, while also providing a more attractive appearance.



XR Rail Family

The XR Rail Family offers the strength of a curved rail in three targeted sizes. Each size supports specific design loads, while minimizing material costs. Depending on your location, there is an XR Rail to match.



XR10

XR10 is a sleek, low-profile mounting rail, designed for regions with light or no snow. It achieves spans up to 6 feet, while remaining light and economical.

- 6' spanning capability
- Moderate load capability
- Clear & black anodized finish
- Internal splices available



XR100

XR100 is the ultimate residential mounting rail. It supports a range of wind and snow conditions, while also maximizing spans up to 10 feet.

- 10' spanning capability
- Heavy load capability
- Clear & black anodized finish
- Internal splices available



XR1000

XR1000 is a heavyweight among solar mounting rails. It's built to handle extreme climates and spans up to 12 feet for commercial applications.

- 12' spanning capability
- Extreme load capability
- Clear anodized finish
- Internal splices available

Rail Selection

The table below was prepared in compliance with applicable engineering codes and standards.* Values are based on the following criteria: ASCE 7-16, Gable Roof Flush Mount, Roof Zones 1 & 2e, Exposure B, Roof Slope of 8 to 20 degrees and Mean Building Height of 30 ft. Visit IronRidge.com for detailed certification letters.

Load		Rail Span					
Snow (PSF)	Wind (MPH)	4'	5' 4"	6'	8'	10'	12'
None	90	XR10		XR100		XR1000	
	120						
	140						
	160						
20	90						
	120						
	140						
	160						
30	90						
	160						
40	90						
	160						
80	160						
120	160						

*Table is meant to be a simplified span chart for conveying general rail capabilities. Use approved certification letters for actual design guidance.

CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025

ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067

HIC. NO.:

ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES RESIDENCE

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

RESOURCE DOCUMENT

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

R-004.00

(SHEET 13)



NanoMount™ (Rafter)




Part Description: Nano Rafter Mount, Black
Part No.: K50044-BK1

Item No.	Description	Qty in Kit
1	Nano Rafter Mount Assembly <ul style="list-style-type: none">Nano Rafter MountNano Gasket	1
2	Lat Bolt Assembly <ul style="list-style-type: none">Hex Lag Bolt M8X115, DIN 571, 304SSealing Washer .33 ID X .75 X .157	1

Cut Sheet


1. Nano Mount




2. Nano Gasket



3. Hex Lag Bolt M8X115, DIN 571, 304SS



4. Sealing Washer .33ID X.75X.157



D10213-V001
Dimensions shown are inches (and millimeters)
Details are subject to change without notice



NanoMount™ (Decking)




Part Description: Nano Deck Mount, Black
Part No.: K50044-BK2


Item No.	Description	Qty in Kit
1	Nano Deck Mount Assembly <ul style="list-style-type: none">Nano Deck MountNano Gasket	1
2	Decking Screw Assembly <ul style="list-style-type: none">Self-Drilling Screw, #6.3 X 76Sealing Washer .26ID X .50X .125	4

Cut Sheet


1. Nano Mount




2. Nano Gasket



3. Self-Drilling Screw, #6.3 X 76



4. Sealing Washer .26ID X .50X .125



D10214-V001
Dimensions shown are inches (and millimeters)
Details are subject to change without notice

CONTRACTOR

BARRETT SOLAR

PHONE: 816-433-8025

ADDRESS: 3603 N KIMBALL DR,
KANSAS CITY, MO 64161

LIC. NO.: 2101209067

HIC. NO.:

ELE. NO.:

UNAUTHORIZED USE OF THIS
DRAWING SET WITHOUT WRITTEN
PERMISSION FROM CONTRACTOR IS IN
VIOLATION OF U.S. COPYRIGHT LAWS
AND WILL BE SUBJECT TO CIVIL
DAMAGES AND PROSECUTIONS.

NEW PV SYSTEM: 6.290 kWp

JONES RESIDENCE

4427 SOUTHWEST
AMETHYST DRIVE,
LEES SUMMIT, MO 64082
APN: 697000708000000000

ENGINEER OF RECORD

PAPER SIZE: 11" x 17" (ANSI B)

RESOURCE DOCUMENT

DATE: 05.07.2022

DESIGN BY: P.M.

CHECKED BY: M.M.

REVISIONS

R-005.00

(SHEET 14)