

June 17, 2022

Summit Homes 120 SE 30th St. Lee's Summit, MO 64082

RE: Field Issue of holes within 2 inches for Lot #106 Hawthorne Ridge -3121 SW Arbortree Drive, Lee's Summit, MO 64082 - Permit # PRRES20214340

Findings:

Holes were drilled within 2" of each other in floor joist to allow for pex lines. Floor joists are located in the great room/dining area and support the second level floor system. Floor joists span approximately 15' 5" and have standard loading of Dead=10 PSF and Live = 40 PSF.

Recommended modifications:

Install 2' length of CS-16 centered under the holes per manufacturer's spec's.

ſ	Martin	Total L	Ga.	DF/SP		SPF/HF		Allowable	0-4-
	Model No.			Fasteners	End Length	Fasteners	End Length	Tension Loads (160)	Code Ref.
ľ	CMST12	40'	12	(74) 16d	33"	(84) 16d	38"	9,215	14, L3, FL
				(86) 10d	39"	(98) 10d	44"	9,215	
ľ	CMST14	5216	14	(56) 16d	26"	(66) 16d	30"	6,490	
Э				(66) 10d	30"	(76) 10d	34"	6,490	
	CMSTC16	54'	16	(50) 16d sinker	20"	(58) 16d sinker	25"	4,585	
	CS14	100'	14	(26) 10d	15"	(30) 10d	16"	2,490	
				(30) 8d	16"	(36) 8d	19"	2,490	
	CS16	150'	16	(20) 10d	11"	(22) 10d	13"	1,705	
				(22) 8d	13"	(26) 8d	14"	1,705	
	CS18	200'	18	(16) 10d	9"	(18) 10d	11"	1,370	
				(18) 8d	11"	(22) 8d	12"	1,370	
	CS20	250'	20	(12) 10d	6"	(14) 10d	g"	1,030	
				(14) 8d	9"	(16) 8d	g"	1,030	
	CS22	300'	22	(10) 10d	7"	(12) 10d	7"	845	
ı				(12) 8d	7"	(14) 8d	8"	845	

[.] Fastener quantities and end lengths are calculated using an increase for wind or seismic loading. . Use half of the required nails in each member being connected to achieve the listed loads.

Allowable Load = $\frac{\text{No. of Nalls Used}}{\text{No. of Nalls In Table}} \times \text{Table Load}$

example: CMSTC16 in DF/SP with 40 nails total. Haif of the nails in each member being connected)

rable Load = 40 Nalls (Used) x 4,585 lb. = 3,668 lb.

Tension loads apply for uplift when installed vertically.

Nalls: f6d = 0.162* dia. x 31/5* long, f6d sinker = 0.148* dia. x 31/5* long, 10d = 0.148* dia. x 3* long. See pp. 26-27 for other nall sizes and information.

Sincerely,

Bradley Huxol, PE



^{3.} Calculate the connector value for a reduced number of nalls as follows: