

## FIRE DEPARTMENT

Prevention Division (816)969-1300

## **PLAN REVIEW CONDITIONS**

June 22, 2022

red architecture + planning 589 W Nationwide Blvd, suite b columbus, OH 43215

Permit No: PRCOM20222664

Project Title: CAVA

Project Address: 904 NW PRYOR RD, LEES SUMMIT, MO 64081

Parcel Number: 258401

Location:

Type of Work: NEW TENANT FINISH

Occupancy Group: ASSEMBLY FOR FOOD AND DRINK INC BARS, RESTAURANTS, BANQUET HALLS

Description: TENANT FINISH FOR NEW RESTAURANT

\*\*no fire sprinker on fdp or shell??\*\*

\*\*g.i. scheduled at min. 1250 gal - shell installs 1000

The following is a list of requirements from the City of Lee's Summit that have not been satisfactorily addressed in the plans and specifications. Please contact the appropriate department regarding clarification of comments.

Development Services Department (816) 969-1200

Fire Department (816) 969-1300

Fire Plan Review

Reviewed By: Jim Eden

**Approved with Conditions** 

- 1. 2018 IFC 1008.3.1 & 3.2 Emergency power for illumination. The power supply for means of egress illumination shall normally be provided by the premises' electrical supply. In the event of power supply failure, an emergency electrical system shall automatically illuminate all of the following:
- 1. Aisles and unenclosed egress stairways in rooms and spaces that require two or mor means of egress.
- 2. Corridors, interior exit stairways and ramps and exit passageways in buildings required to have two or more exits.
- 3. Exterior egress components at other than their levels of exit discharge until exit discharge is accomplished for buildings required to have two or more exits.

Action required- Provide emergency exterior illumination at both exits.

2. 2018 IFC 904.11.5- Portable fire extinguishers for commercial cooking equipment. Portable fire extinguishers shall be provided within a 30-foot (9144 mm) travel distance of commercial-type cooking equipment. Cooking equipment involving vegetable or animal oils and fats shall be protected by a Class K rated portable extinguisher.

Action required- Place the K class extinguisher under the manual pull for the ansul system.

3. 2018 IFC 901.5- Installation acceptance testing. Fire detection and alarm systems, fire-extinguishing systems, fire hydrant systems, fire standpipe systems, fire pump systems, private fire service mains and all other fire protection systems and appurtenances thereto shall be subject to acceptance tests as contained in the installation standards and as approved by the fire code official. The fire code official shall be notified before any required acceptance testing. The fire code official shall be notified 48 hours before any required acceptance test.

Action required- Call (816) 969-1300 to schedule a hood trip test.

4. 5307.2.1 Gas detection system. In rooms or areas not provided with ventilation in accordance with Section 5307.2, a gas detection system complying with Section 916 or, where approved, an oxygen depletion alarm system, either of which initiates audible and visible alarm signals in the room or area where sensors are installed, shall be provided.

Action required- Provide detection or ventilation for the carbon dioxide beverage system provided.

Building Plan Review Reviewed By: Joe Frogge Pending

The approval of plans and specifications does not permit the violation of any section of the Building Codes or other City Ordinances or State Law.

The review conducted by the City of Lee's Summit Development Services Department shall not be construed as a structural review of the project.