



SAINT LUKE'S EAST HOSPITAL
PULMONARY CLINIC - PHASE 1
20 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

RELEASED FOR CONSTRUCTION
NOT FOR PERMITTING

STATE OF MISSOURI
Professional Services Department
Samuel K. Beckman
A-20110-0001
ARCHITECT

8/15/2022 11:01:34 AM
Samuel K. Beckman - Architect
License - Missouri WA-2011012130

ACI
BOLAND
ARCHITECTS

ACI/Boland, Inc.
Kansas City | St. Louis
1710 Wyandotte
Kansas City, MO 64108
T: 816.763.9600
Licensee's Certificate of Authority Number:
Missouri: #000958

MEP ENGINEER
Branch Pattern
1508 Grand Boulevard
Kansas City, MO 64108
816.531.2121
Mike Galyardt: 316.207.7939

P R O J E C T T E A M

ARCHITECT ACI BOLAND, INC.	MEP ENGINEER BRANCH PATTERN
1710 WYANDOTTE STREET KANSAS CITY, MO 64108	1508 GRAND BOULEVARD KANSAS CITY, MO 64108
PHONE 816.763.9600 FAX 816.763.9757	PHONE 816.531.2121

ABBREVIATIONS

AC. ACOUSTIC/ACOUSTICAL	FLOR. FLUORESCENT	PTD. PAINTED
ADD. ADDENDUM	FTG. FOOTING	PG. PAGE
ADDN. ADDITION	FND. FOUNDATION	PLAM. PLASTIC LAMINATE
ABC. AGGREGATE BASE COURSE	FR. FRAME	PR. PAIR
AFF. ABOVE FINISH FLOOR	F.H.C. FIRE HOSE CAB.	PNL. PANEL
AGG. AGGREGATE	FV. FIELD VERIFY	PTN. PARTITION
ANC. AIR CONDITIONING		PENNY
AL. ALUMINUM	GA. GAUGE	PL. PLATE
ALT. ALTERNATE	GL. GLASS / GLAZING	PLBG. PLUMBING
A.B. ANCHOR BOLT	GD. GRADE	PLYWD. PLYWOOD
& AND	G. GRAM	PT. POINT
ARCH. ARCHITECT	GRL. GRILLE	P.S.I. POUNDS PER SQ. IN.
ASP. ASPHALT	GRD. GRID	P.S.F. POUNDS PER SQ. FT.
@ AT	GND. GROUND	P.C. PRECAST
ACT. ACOUSTIC CEILING TILE/PANEL	G.S. GALVANIZED STEEL	P.L. PROPERTY LINE
<L. ANGLE	GYP. GYPSUM	
	GWB/G.B. GYPSUM BOARD	
BLKG. BLOCKING	H.R. HAND RAIL	R. RISER, RISERS
BSMT. BASEMENT	HDN. HARDENER	RAD. RADIUS
BM. BEAM	HDW. HARDWARE	R.D. ROOF DRAIN
B.M. BENCHMARK	HDWD. HARDWOOD	RB. RESILIENT BASE
BD. BOARD	HTR. HEATER	RE. REFER TO
B.O. BOTTOM OF BLDG.	HT. HEIGHT	REG. REGISTER
	H.P. HIGH POINT	REQD. REQUIRED
CABT. CABINET	H.M. HOLLOW METAL	REV. REVISION
C.I.P. CAST IN PLACE	HORIZ. HORIZONTAL	RFG. ROOFING
C.B. CATCH BASIN	H.B. HOSE BIB	RGL. ROUGH
C.C. CEILING	H.W. HOT WATER	RM. ROOM
CEM. CEMENT/CEMENTITIOUS		RND. ROUND
CG. CENTIGRAM	IN. INCH / INCHES	R.O. ROUGH OPENING
CM. CENTIMETER	INSUL. INSULATION	
CL. CENTER LINE	INT. INTERIOR	SCHED. SCHEDULE
CER. CERAMIC	INV. INVERT	S.C. SEALED CONCRETE
C.T. CERAMIC TILE		SCR. SCREW
CHAN. CHANNEL	JAN. JANITOR	SECT. SECTION
CLR. CLEAR	JT. JOINT	SEL. SELECT
C.O. CLEAN OUT	JST. JOIST	SHG. SHEATHING
CLOS. CLOSET	K.P. KICK PLATE	SHT. SHEET
COL. COLUMN	LAM. LAMINATED	SDG. SIDING
CONC. CONCRETE	LB. POUND	SIM. SIMILAR
CONN. CONNECTION	LDG. LANDING	SLDG. SLIDING
CONST. CONSTRUCTION	LTH. LATH	SM. SMOOTH
C.J. CONTROL JOINT	LAV. LAVATORY	SPEC. SPECIFICATION
CONT. CONTINUOUS	LG. LENGTH	SQ. SQUARE
CONTR. CONTRACTOR	LOC. LOCATION	ST. STAINED
CORR. CORRUGATED	LT. LIGHT	STD. STANDARD
CTR. COUNTER	L.W.C. LIGHT WEIGHT CONCRETE	S.S. / ST.STL. STAINLESS STEEL
CTS/K. COUNTERSUNK	LVR. LOUVER	STRUC. STRUCTURE
C.M.U. CONCRETE MASONRY UNIT	LOC. LOCATION	SUSP. SUSPENDED
		SW BD. SWITCHBOARD
D.P. DAMP PROOFING	M.O. MASONRY OPENING	SYS. SYSTEM
DB. DECIBEL	MATL.. MATERIAL	T. TREAD
DIAG. DIAGONAL	MFR. MANUFACTURER	T.C. TOP OF CURB
DIAM. DIAMETER	MB. MARKER BOARD	T.G. TEMPERED GLASS
DM. DIMENSION	MAX. MAXIMUM	T.O. TOP OF
DISP. DISPENSER	MECH. MECHANICAL	T.S.D. TOP OF STEEL DECK
DWL. DOWEL	MTL. METAL	T.W. TEACHERS WARDROBE
DOWN. DOWN	M.L. METAL LATH	TYP. TYPICAL
D.S. DOWNSPOUT	M. METER	
DWG. DRAWING	MIN. MINIMUM	U.O.N. UNLESS OTHERWISE NOTED
	MLDG. MOLDING	
EA. EACH	MULL. MULLION	V. VENT
ELEC. ELECTRIC		VERT. VERTICAL
E.W.C. ELECTRIC WATER COOLER	N.G. NATURAL GRADE	V.G. VERTICAL GRAIN
EL. ELEVATION	NOM. NOMINAL	VEST. VESTIBULE
ELEV. ELEVATOR	N.L.C. NOT IN CONTRACT	V.C.T. VINYL COMPOSITION TILE
EQ. EQUAL	N.T.S. NOT TO SCALE	VCP. VITREOUS CLAY PIPE
EQUIP. EQUIPMENT	NO. / # NUMBER	
EXH. EXHAUST		W.W.M. WELDED WIRE MESH
EXPAN. EXPANSION	OBS. OBSCURE	W.C. WATER CLOSET
E.J. EXPANSION JOINT	O.C. ON CENTER	W.H. WATER HEATER
EXST. EXISTING	OPNG. OPENING	W.F. WIDE FLANGE
EXT. EXTERIOR	O.A. OVERALL	W. WITH
	O.D. OUTSIDE DIAMETER	W/O. WITHOUT
FT. FEET / FOOT	O.F.S. OVERFLOW SCUPPER	WD. WOOD
FIN. FINISH	O.F.D. OVERFLOW DRAIN	WDW. WINDOW
FIKT. FIXTURE	O.H.D. OVERHEAD DOOR	W.W. WINDOW WALL
FL. FLASHING		
FUR. FLOOR		
F.D. FLOOR DRAIN		

LOCATION PLAN

KEY PLAN

KEY PLAN
1" = 100'-0"

SHEET INDEX

SHEET NUMBER	SHEET NAME
GENERAL	
A0.1	COVER SHEET
A0.2	CODE FOOTPRINT PLAN
A0.3	PARTITION TYPES, DETAILS, & SYMBOLS
A0.4	U.L. DESIGN ASSEMBLIES
DEMOLITION	
AD2.1	DEMOLITION PLAN
AD3.1	DEMOLITION REFLECTED CEILING PLAN
ARCHITECTURE	
A2.1	FIRST FLOOR DIMENSION AND ANNOTATION PLAN - AREA A
A2.2	FIRST FLOOR DIMENSION AND ANNOTATION PLAN - AREA B
A3.1	FIRST FLOOR REFLECTED CEILING PLAN - PHASE 1
A3.2	REFLECTED CEILING PLAN - AREA B
A4.1	DOOR AND FRAME SCHEDULE AND DETAILS
A4.2	ROOM FINISH SCHEDULE & FINISH LEGEND
A7.2	INTERIOR ELEVATIONS
A7.3	INTERIOR DETAILS
ELECTRICAL	
E0.1	ELECTRICAL LEGEND
E0.2	ELECTRICAL NOTES
E1.1	PHASE 1 - FIRST FLOOR POWER PLAN
E2.1	PHASE 1 - FIRST FLOOR LIGHTING PLAN
E3.1	PHASE 1 - FIRST FLOOR FIRE ALARM PLAN
E4.0	ELECTRICAL DETAILS
E5.0	ELECTRICAL SCHEDULES
ED1.0	FIRST FLOOR ELECTRICAL PLAN - DEMOLITION
MECHANICAL	
M0.1	MECHANICAL LEGEND & NOTES
M1.0	FIRST FLOOR HVAC PLAN
M1.1	FIRST FLOOR HYDRONIC PLAN
M4.0	MECHANICAL DETAILS
M5.0	MECHANICAL SCHEDULES
MD1.0	FIRST FLOOR HVAC DEMOLITION PLAN
MD1.1	FIRST FLOOR HYDRONIC DEMOLITION PLAN
MD3.0	THIRD FLOOR MECHANICAL & ELECTRICAL DEMOLITION PLAN
PLUMBING	
P0.1	PLUMBING LEGEND & NOTES
P1.0	UNDERFLOOR WASTEVENT PLAN
P1.1	FIRST FLOOR WASTEVENT PLAN
P2.1	FIRST FLOOR DOMESTIC WATER PLAN
P3.1	FIRST FLOOR MED GAS PLAN
P4.0	PLUMBING DETAILS
P5.0	PLUMBING SCHEDULES
PD1.0	UNDERFLOOR WASTEVENT DEMOLITION PLAN
PD1.1	FIRST FLOOR WASTEVENT DEMOLITION PLAN
PD2.1	FIRST FLOOR DOMESTIC WATER DEMOLITION PLAN
TECHNOLOGY	
T0.1	TECHNOLOGY LEGEND
T0.2	TECHNOLOGY NOTES
T1.0	FIRST FLOOR TECHNOLOGY PLAN
T3.0	TECHNOLOGY DIAGRAMS
T4.0	TECHNOLOGY DETAILS
TD1.0	TECHNOLOGY DEMOLITION PLAN

PULMONARY CLINIC - PHASE 1
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
20 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086


Date	8/15/22
Job Number	3-22015
Drawn By	KDS
Checked By	ABD

Revision	Date	Description

A0.1

© 2022 ACI/BOLAND, Inc.

COVER SHEET



A1 CODE FOOTPRINT PLAN - PHASE 1
1/8" = 1'-0"



*THIS DRAWING IS INTENDED TO BE PRINTED IN COLOR. USE BLACK AND WHITE COPIES AT YOUR OWN RISK.

CODE SUMMARY

Project Construction Purpose: Renovation of existing therapy department into new pulmonary clinic

Project Address:
Saint Luke's Lee's Summit
20 NE Saint Luke's Blvd
Lee's Summit, MO 64083

Code Information:
2018 International Building Code
2018 International Plumbing Code
2018 International Mechanical Code
2018 International Fuel Gas Code
2018 International Fire Code
2017 National Electrical Code
2009 ICC/ANSI A117.1 as amended and adopted by the City of Lee's Summit

State of Missouri Dept. of Health & Environment references the following codes:
2012 NFPA 101 Life Safety Code (LSC)
2018 FGI Guidelines for Design & Construction of Hospitals & Outpatient Facilities

Note: If code requirements overlap, the most stringent shall apply.

Designer Information:
ACI/Boland Architects
1710 Wyandotte St.
Kansas City, MO 64108
Phone: (816) 763-9600
Fax: (816) 763-9757

Local Authority:
Responsible Fire Service: Lee's Summit Fire Department
Local Building Inspection: Lee's Summit, MO, Codes Administration Department

Type of Construction: 1-A

Area of Renovation: PHASE A: 4,145 SF
PHASE B: 3,895 SF
TOTAL: 8040 +/- SF

Occupancy Group: B

Occupant Load:
Total Square Footage: SF / I = 8040
Total Number of Occupants = 81 occupants

Required Fire Resistance Ratings (in hours)
Per NFPA 101 A.8.2.1.2:

Exterior Bearing Walls	3 HR
Interior Bearing Walls	3 HR
Primary Structural Frame	3 HR
Floor Construction	2 HR
Roof Construction	1 1/2 HR
Interior non-bearing walls	0 HR
Shaft Enclosure	2 HR
Stair Enclosure	2 HR provided

Active Fire Safety Features:

- Fire Alarm System - The fire alarm system is specified as an addressable type system. The device type and locations are per the applicable codes as well as ADA requirements.
- Smoke Control System - All ductwork penetrating smoke rated walls will have a smoke or combination fire/smoke damper as indicated on construction documents. These dampers will close upon detection of smoke by the area smoke detectors or duct smoke detectors in the air handling units.
- Fire Sprinkler System - Specified to be per NFPA 13. The sprinkler heads are specified to be quick response type.
- Emergency Lighting and Power - Emergency lighting, life safety and critical loads will receive power from a backup generator located outside the main electrical room.
- Illuminated Exit Signs

Passive Fire Safety Features:

- Smoke Compartments no greater than 22,500 SF.

CODE FOOTPRINT LEGEND

PARTITION TYPES

- 0 HR SMOKE PARTITION (SMOKE RESISTIVE)
- 1 HR SMOKE BARRIER
- 1 HR FIRE BARRIER
- 2 HR FIRE BARRIER
- 2 HR FIRE SMOKE BARRIER
- 3 HR FIRE BARRIER

AREA DESIGNATIONS

- EXIT ENCLOSURE
- SHAFT

BOUNDARY DESIGNATIONS

- NOT IN ARCHITECTURAL SCOPE

SYMBOLS

- FIRE EXIT
- OCCUPANT LOAD
- EXIT WIDTH PROVIDED
- EXIT WIDTH REQUIRED
- NEW FIRE EXTINGUISHER CABINET
- EXISTING FIRE EXTINGUISHER CABINET
- EXIT SIGN
- FIRE DOOR RATING
- TRAVEL DISTANCE

PULMONARY CLINIC - PHASE 1
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
20 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

Date 8/15/22
Job Number 3-22015
Drawn By Author
Checked By Checker

Revision
Number Date Description

RELEASED FOR CONSTRUCTION
NOT FOR PERMITTING

8/15/2022 4:37:49 PM
Samuel A. Beckman - Architect
License - Missouri WA-2011012130

ACI BOLAND ARCHITECTS

ACI/Boland, Inc.
Kansas City | St. Louis
1710 Wyandotte
Kansas City, MO 64108
T: 816.763.9600

Licensee's Certificate of Authority Number:
Missouri: #000958

CIVIL CONSULTANT

Company Title
Address Line 1
City, State, Zip
Phone Number: 000.000.0000
Licensee's Certificate of Authority:

STRUCTURAL CONSULTANT




Company Title
Address Line 1
City, State, Zip
Phone Number: 000.000.0000
Licensee's Certificate of Authority

MEP CONSULTANT

Company Title
Address Line 1
City, State, Zip
Phone Number: 000.000.0000
Licensee's Certificate of Authority:

CONSULTANT

Company Title
Address Line 1
City, State, Zip
Phone Number: 000.000.0000
Licensee's Certificate of Authority:



RELEASED FOR CONSTRUCTION

8/15/2022 11:01:44 AM

Samuel K. Beckman - Architect

License - Missouri WA-2011012130

ACI

BOLAND

ARCHITECTS

ACI/Boland, Inc.
Kansas City | St. Louis
1710 Wyandotte
Kansas City, MO 64108
T: 816.763.9600

Licensee's Certificate of Authority Number:
Missouri: #000958

PULMONARY CLINIC - PHASE 1

SAINT LUKE'S EAST HOSPITAL

FIRST FLOOR MOB

20 NE SAINT LUKE'S BLVD.

LEE'S SUMMIT, MO 64086

Date8/15/22

Job Number3-22015

Drawn ByKDS

Checked ByABD

Revision

NumberDateDescription

A0.3

© 2022 ACI/BOLAND, Inc.

PARTITION TYPES, DETAILS, & SYMBOLS

ONLINE CERTIFICATIONS DIRECTORY

Design No. U465
BXUV,U465
Fire-resistance Ratings - ANSI/UL 263

Page History

Design/System/Construction/Assembly Usage Disclaimer

- Authorities having jurisdiction should be consulted in all cases as to the particular requirements covering the installation and use of UL Classified products, equipment, systems, devices and materials.
- Fire resistance assemblies and products are developed by the design submitter and have been investigated by UL for compliance with applicable requirements. The submitted information cannot address every construction nuance encountered in the field.
- When field details arise, it is recommended the first contact for assistance be the technical service staff provided by the product manufacturer noted for the design. Users of fire resistance assemblies are advised to consult the general Guide Information for each product category and the design. Users of fire resistance assemblies are advised to consult the general Guide Information for each product category and the design.
- Only products which bear UL's Mark are considered Certified.

BXUV - Fire Resistance Ratings - ANSI/UL 263

BXUV7 - Fire Resistance Ratings - CAN/ULC-S101 Certified for Canada


See General Information for Fire Resistance Ratings - ANSI/UL 263

See General Information for Fire Resistance Ratings - CAN/ULC-S101 Certified for Canada

Design No. U465

Nonbearing Wall Rating - 1 HR

* Indicates such products shall bear the UL or cUL Certification Mark for jurisdictions employing the UL or cUL Certification (see in Canada), respectively.



- Floor and Ceiling Runners - (Not Shown) - Channel shaped runners, 3-5/8 in. deep (min), 1-1/4 in. high, formed from min. 25 M50 galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max.
- Floor and Ceiling Members - (Not Shown) - As an alternate to Item 1 - Channel shaped, min. 5-5/8 in. deep, attached to floor and ceiling with fasteners 24 in. OC, max.
- Wall and Ceiling Members - (Not Shown) - As an alternate to Item 1 - Channel shaped, min. 5-5/8 in. deep, attached to floor and ceiling with fasteners 24 in. OC, max.
- ALSTET & GYPSUM PRODUCTS INC. - Type SUPRME Framing System

CONSOLIDATED FABRICATORS CORP, BUILDING PRODUCTS DIV. - Type SUPRME Framing System

QUAL RUN BUILDING MATERIALS INC. - Type SUPRME Framing System

SCAFCO STEEL STUD MANUFACTURING CO. - Type SUPRME Framing System

STEEL STRUCTURE SYSTEMS INC. - Type SUPRME Framing System

UNITED METAL PRODUCTS INC. - Type SUPRME Framing System

18. Framing Members* - Floor and Ceiling Runners - (Not Shown) - In lieu of Item 1 - For use with Item 20, proprietary channel shaped runners, 1-1/4 in. wide by min 3-5/8 in. deep fabricated from min 0.020 in. thick galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max.

CALIFORNIA EXPANDED METAL PRODUCTS CO. - Viper200™

CRACKO MFG INC. - SmartTrack200™

HAZINO/WARE, DIV OF WARE INDUSTRIES INC. - Viper200™ Track

- Floor and Ceiling Runners - (Not Shown) - For use with Item 20 - Channel shaped, fabricated from min 25 M50 galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max.
- Floor and Ceiling Members - (Not Shown) - As an alternate to Item 1 - Channel shaped, min. 5-5/8 in. deep, attached to floor and ceiling with fasteners spaced 24 in. OC, max.
- CLARKDIERICH BUILDING SYSTEMS - CD INFRAC

DMFCWS L L C - INFRAC

HEA METAL FRAMING - INFRAC

RAN SALES L L C - Rann INFRAC

STEEL STRUCTURAL PRODUCTS L L C - TR-1 INFRAC

19. Framing Members* - Floor and Ceiling Runners - (Not Shown) - In lieu of Item 1 through 10 - For use with Item 20, proprietary channel shaped runners, 1-1/4 in. wide by min 3-5/8 in. deep fabricated from min 0.020 in. thick galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max.

TELLING INDUSTRIES L L C - TRUE-TRACK™

- Framing Members* - Floor and Ceiling Runners - (Not Shown) - In lieu of Item 1 through 10 - For use with Item 20, proprietary channel shaped runners, 1-1/4 in. wide by min 3-5/8 in. deep fabricated from min 25 M50 galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max.
- KIIZII (JONG KONG) LTD. - Type K030

- Framing Members* - Floor and Ceiling Runners - (Not Shown) - In lieu of Item 1 through 10 - For use with Item 20, proprietary channel shaped runners, 1-1/4 in. wide by min 3-5/8 in. deep fabricated from min 0.020 in. thick galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max.
- STUCCO BUILDING SYSTEMS - CRCCSTUD

- Floor and Ceiling Runners - (Not Shown) - Channel shaped, fabricated from min 0.020 in. galv steel, min 1/4 in. wide by min 3-5/8 in. deep, attached to floor and ceiling with fasteners spaced 24 in. OC, max.
- HAZINO/WARE, DIV OF WARE INDUSTRIES INC. - Viper200™ Track V100

- Framing Members* - Floor and Ceiling Runners - (Not Shown) - In lieu of Item 1 - For use with Item 20, proprietary channel shaped runners, 1-1/4 in. wide by min 3-5/8 in. deep fabricated from min 0.020 in. thick galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max.
- TELLING INDUSTRIES L L C - Viper200™ Track

- Steel Studs - Channel shaped, 3-5/8 in. deep (min), formed from min 25 M50 galv steel spaced 24 in. OC, max. Studs to be cut 1/2 in. less than assembly height.
- Framing Members* - Steel Studs - (As an alternate to Item 2) - Channel shaped studs, min 5-5/8 in. deep, spaced a max of 24 in. OC. Studs to be cut 1/2 in. less than assembly height.
- ALSTET & GYPSUM PRODUCTS INC. - Type SUPRME Framing System

CONSOLIDATED FABRICATORS CORP, BUILDING PRODUCTS DIV. - Type SUPRME Framing System

QUAL RUN BUILDING MATERIALS INC. - Type SUPRME Framing System

SCAFCO STEEL STUD MANUFACTURING CO. - Type SUPRME Framing System

STEEL STRUCTURE SYSTEMS INC. - Type SUPRME Framing System

UNITED METAL PRODUCTS INC. - Type SUPRME Framing System

- Framing Members* - Steel Studs - (Not Shown) - In lieu of Item 2 - For use with Item 10, proprietary channel shaped studs, min 5-5/8 in. wide fabricated from min 0.020 in. thick galv steel. Studs to be cut 1/4 in. less than assembly height.
- CALIFORNIA EXPANDED METAL PRODUCTS CO. - Viper200™

CRACKO MFG INC. - SmartTrack200™

HAZINO/WARE, DIV OF WARE INDUSTRIES INC. - Viper200™

- Steel Studs - (As an alternate to Item 2) - For use with Item 40 - Channel shaped, fabricated from min 25 M50 galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max. Studs to be cut 1/2 in. less than assembly height.
- TELLING INDUSTRIES L L C - TRUE-TRACK™

- Framing Members* - Steel Studs - (As an alternate to Item 2) - For use with Item 10, proprietary channel shaped studs, min 5-5/8 in. wide fabricated from min 0.020 in. thick galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max. Studs to be cut 1/2 in. less than assembly height.
- KIIZII (JONG KONG) LTD. - Type K030

- Framing Members* - Steel Studs - (Not Shown) - In lieu of Item 2 through 10 - For use with Item 10, proprietary channel shaped studs, min 5-5/8 in. wide fabricated from min 0.020 in. thick galv steel. Studs to be cut 1/4 in. less than assembly height.
- STUCCO BUILDING SYSTEMS - CRCCSTUD

- Framing Members* - Steel Studs - (Not Shown) - In lieu of Item 2 - For use with Item 1, channel shaped studs, fabricated from min 25 M50 galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max. Studs to be cut 1/4 in. less than assembly height.
- TELLING INDUSTRIES L L C - Viper200™

- Framing Members* - Steel Studs - (Not Shown) - In lieu of Item 2 - For use with Item 1, channel shaped studs, fabricated from min 25 M50 galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max. Studs to be cut 1/4 in. less than assembly height.
- EB RETAIL INC. - EB Stud

- Framing Members* - Steel Studs - (Not Shown) - In lieu of Item 2 - For use with Item 1, channel shaped studs, fabricated from min 25 M50 galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max. Studs to be cut 1/4 in. less than assembly height.
- OLMAR SUPPLY INC. - PRISMSTUD

- Framing Members* - Steel Studs - (Not Shown) - In lieu of Item 2 - For use with Item 10, proprietary channel shaped studs, min 5-5/8 in. wide fabricated from min 25 M50 galv steel, attached to floor and ceiling with fasteners spaced 24 in. OC, max. Studs to be cut 1/2 in. less than assembly height.
- HAZINO/WARE, DIV OF WARE INDUSTRIES INC. - Viper200™

- Batts and Blankets* - (Optional) - Mineral wool or glass fiber batts partially or completely filling stud cavity.
- Batts and Blankets (R202) category for names of Classified companies.
- Fiber, Spray* - (As an alternate to Batts and Blankets (Item 3) - (100% Fiberglass) - Spray applied cellulose material. The fiber is applied with water to completely fill the enclosed cavity in accordance with the application instructions supplied with the product with a nominal dry density of 2.7 lb/ft³. Alternate Application Method: The fiber is applied without water or adhesive at a nominal dry density of 3.0 lb/ft³, in accordance with the application instructions supplied with the product.
- INTERNATIONAL CELLULOSE CORP. - Cellulose

- Batts and Blankets* - For use with Item 8, Nom 3 in. thick, minimum 3.4 pcf mineral wool batts, friction fit between the studs and floor and ceiling runners.
- Batts and Blankets (R202) category for names of manufacturers.
- Batts and Blankets* - For use with Item 40, Fiberglass stud cavity batts, min 3-1/2 in. thick glass fiber insulation bearing the UL Classification Marking in its Rating and Characteristics section for Fire Resistance.
- Batts and Blankets (R202) category for names of Classified companies.

- Gypsum Board* - 5/8 in. thick, 4 ft wide, attached to steel studs and floor and ceiling track with 1 in. long, Type 5 steel screws spaced 8 in. OC, along edges of board and 12 in. OC in the field of the board. Joints between panels with beveled, square or tapered edges, applied vertically. Vertical joints centered over studs and staggered min 1 stud cavity on opposite side of stud. Gypsum board secured to studs with 1-1/4 in. long Type 5-1/2 steel screws spaced 8 in. OC, along perimeter and 12 in. OC in the field. To be used with Lead Board Strips (see Item 9A) or Lead Dots (see Item 9A).
- US GREENGLASS L L C - INFRAC INFRAC for use with wet or dry application, INFRAC and INFRAC2 are to be used for dry application only.

- Fiber, Spray* - As an alternate to Batts and Blankets (Item 3) and Item 1A - Spray applied cellulose insulation material. The fiber is applied with water to completely fill the enclosed cavity in accordance with the application instructions supplied with the product with a nominal dry density of 2.7 lb/ft³. Alternate Application Method: The fiber is applied without water or adhesive at a nominal dry density of 3.0 lb/ft³, in accordance with the application instructions supplied with the product.
- NO-WOOL CO INC. - Cellulose Insulation


- Batts and Blankets* - For use with Item 8, Nom 3 in. thick, minimum 3.4 pcf mineral wool batts, friction fit between the studs and floor and ceiling runners.
- Batts and Blankets (R202) category for names of manufacturers.
- Batts and Blankets* - For use with Item 40, Fiberglass stud cavity batts, min 3-1/2 in. thick glass fiber insulation bearing the UL Classification Marking in its Rating and Characteristics section for Fire Resistance.
- Batts and Blankets (R202) category for names of Classified companies.

- Gypsum Board* - 5/8 in. thick, 4 ft wide, attached to steel studs and floor and ceiling track with 1 in. long, Type 5 steel screws spaced 8 in. OC, along edges of board and 12 in. OC in the field of the board. Joints between panels with beveled, square or tapered edges, applied vertically. Vertical joints centered over studs and staggered min 1 stud cavity on opposite side of stud. Gypsum board secured to studs with 1-1/4 in. long Type 5-1/2 steel screws spaced 8 in. OC, along perimeter and 12 in. OC in the field. To be used with Lead Board Strips (see Item 9A) or Lead Dots (see Item 9A).
- ACADA DRYWALL SUPPLIES LTD. - Type X, 5/8 Type X, Type Blueboard Exterior Sheathing
- AMERICAN GYPSUM CO. - Types GPC-F, FSK, FSC, FSG, G, FPMR-C, FPM, FSW, FSW-3, FSW-4, FSW-5, FSW-6, FSW-7, FSW-8

- Batts and Blankets* - For use with Item 8, Nom 3 in. thick, minimum 3.4 pcf mineral wool batts, friction fit between the studs and floor and ceiling runners.
- Batts and Blankets (R202) category for names of manufacturers.
- Batts and Blankets* - For use with Item 40, Fiberglass stud cavity batts, min 3-1/2 in. thick glass fiber insulation bearing the UL Classification Marking in its Rating and Characteristics section for Fire Resistance.
- Batts and Blankets (R202) category for names of Classified companies.

- Gypsum Board* - 5/8 in. thick, 4 ft wide, attached to steel studs and floor and ceiling track with 1 in. long, Type 5 steel screws spaced 8 in. OC, along edges of board and 12 in. OC in the field of the board. Joints between panels with beveled, square or tapered edges, applied vertically. Vertical joints centered over studs and staggered min 1 stud cavity on opposite side of stud. Gypsum board secured to studs with 1-1/4 in. long Type 5-1/2 steel screws spaced 8 in. OC, along perimeter and 12 in. OC in the field. To be used with Lead Board Strips (see Item 9A) or Lead Dots (see Item 9A).
- BEIJING NEW BUILDING MATERIALS PUBLIC LTD CO. - Type OBR-K

- CRC INC. - Types AR, C, IP-AR, IP-K1, IP-K2, IP-K3, IP-K4, IP-K5, IP-K6, IP-K7, IP-K8, IP-K9, IP-K10, IP-K11, IP-K12, IP-K13, IP-K14, IP-K15, IP-K16, IP-K17, IP-K18, IP-K19, IP-K20, IP-K21, IP-K22, IP-K23, IP-K24, IP-K25, IP-K26, IP-K27, IP-K28, IP-K29, IP-K30, IP-K31, IP-K32, IP-K33, IP-K34, IP-K35, IP-K36, IP-K37, IP-K38, IP-K39, IP-K40, IP-K41, IP-K42, IP-K43, IP-K44, IP-K45, IP-K46, IP-K47, IP-K48, IP-K49, IP-K50, IP-K51, IP-K52, IP-K53, IP-K54, IP-K55, IP-K56, IP-K57, IP-K58, IP-K59, IP-K60, IP-K61, IP-K62, IP-K63, IP-K64, IP-K65, IP-K66, IP-K67, IP-K68, IP-K69, IP-K70, IP-K71, IP-K72, IP-K73, IP-K74, IP-K75, IP-K76, IP-K77, IP-K78, IP-K79, IP-K80, IP-K81, IP-K82, IP-K83, IP-K84, IP-K85, IP-K86, IP-K87, IP-K88, IP-K89, IP-K90, IP-K91, IP-K92, IP-K93, IP-K94, IP-K95, IP-K96, IP-K97, IP-K98, IP-K99, IP-K100, IP-K101, IP-K102, IP-K103, IP-K104, IP-K105, IP-K106, IP-K107, IP-K108, IP-K109, IP-K110, IP-K111, IP-K112, IP-K113, IP-K114, IP-K115, IP-K116, IP-K117, IP-K118, IP-K119, IP-K120, IP-K121, IP-K122, IP-K123, IP-K124, IP-K125, IP-K126, IP-K127, IP-K128, IP-K129, IP-K130, IP-K131, IP-K132, IP-K133, IP-K134, IP-K135, IP-K136, IP-K137, IP-K138, IP-K139, IP-K140, IP-K141, IP-K142, IP-K143, IP-K144, IP-K145, IP-K146, IP-K147, IP-K148, IP-K149, IP-K150, IP-K151, IP-K152, IP-K153, IP-K154, IP-K155, IP-K156, IP-K157, IP-K158, IP-K159, IP-K160, IP-K161, IP-K162, IP-K163, IP-K164, IP-K165, IP-K166, IP-K167, IP-K168, IP-K169, IP-K170, IP-K171, IP-K172, IP-K173, IP-K174, IP-K175, IP-K176, IP-K177, IP-K178, IP-K179, IP-K180, IP-K181, IP-K182, IP-K183, IP-K184, IP-K185, IP-K186, IP-K187, IP-K188, IP-K189, IP-K190, IP-K191, IP-K192, IP-K193, IP-K194, IP-K195, IP-K196, IP-K197, IP-K198, IP-K199, IP-K200, IP-K201, IP-K202, IP-K203, IP-K204, IP-K205, IP-K206, IP-K207, IP-K208, IP-K209, IP-K210, IP-K211, IP-K212, IP-K213, IP-K214, IP-K215, IP-K216, IP-K217, IP-K218, IP-K219, IP-K220, IP-K221, IP-K222, IP-K223, IP-K224, IP-K225, IP-K226, IP-K227, IP-K228, IP-K229, IP-K230, IP-K231, IP-K232, IP-K233, IP-K234, IP-K235, IP-K236, IP-K237, IP-K238, IP-K239, IP-K240, IP-K241, IP-K242, IP-K243, IP-K244, IP-K245, IP-K246, IP-K247, IP-K248, IP-K249, IP-K250, IP-K251, IP-K252, IP-K253, IP-K254, IP-K255, IP-K256, IP-K257, IP-K258, IP-K259, IP-K260, IP-K261, IP-K262, IP-K263, IP-K264, IP-K265, IP-K266, IP-K267, IP-K268, IP-K269, IP-K270, IP-K271, IP-K272, IP-K273, IP-K274, IP-K275, IP-K276, IP-K277, IP-K278, IP-K279, IP-K280, IP-K281, IP-K282, IP-K283, IP-K284, IP-K285, IP-K286, IP-K287, IP-K288, IP-K289, IP-K290, IP-K291, IP-K292, IP-K293, IP-K294, IP-K295, IP-K296, IP-K297, IP-K298, IP-K299, IP-K300, IP-K301, IP-K302, IP-K303, IP-K304, IP-K305, IP-K306, IP-K307, IP-K308, IP-K309, IP-K310, IP-K311, IP-K312, IP-K313, IP-K314, IP-K315, IP-K316, IP-K317, IP-K318, IP-K319, IP-K320, IP-K321, IP-K322, IP-K323, IP-K324, IP-K325, IP-K326, IP-K327, IP-K328, IP-K329, IP-K330, IP-K331, IP-K332, IP-K333, IP-K334, IP-K335, IP-K336, IP-K337, IP-K338, IP-K339, IP-K340, IP-K341, IP-K342, IP-K343, IP-K344, IP-K345, IP-K346, IP-K347, IP-K348, IP-K349, IP-K350, IP-K351, IP-K352, IP-K353, IP-K354, IP-K355, IP-K356, IP-K357, IP-K358, IP-K359, IP-K360, IP-K361, IP-K362, IP-K363, IP-K364, IP-K365, IP-K366, IP-K367, IP-K368, IP-K369, IP-K370, IP-K371, IP-K372, IP-K373, IP-K374, IP-K375, IP-K376, IP-K377, IP-K378, IP-K379, IP-K380, IP-K381, IP-K382, IP-K383, IP-K384, IP-K385, IP-K386, IP-K387, IP-K388, IP-K389, IP-K390, IP-K391, IP-K392, IP-K393, IP-K394, IP-K395, IP-K396, IP-K397, IP-K398, IP-K399, IP-K400, IP-K401, IP-K402, IP-K403, IP-K404, IP-K405, IP-K406, IP-K407, IP-K408, IP-K409, IP-K410, IP-K411, IP-K412, IP-K413, IP-K414, IP-K415, IP-K416, IP-K417, IP-K418, IP-K419, IP-K420, IP-K421, IP-K422, IP-K423, IP-K424, IP-K425, IP-K426, IP-K427, IP-K428, IP-K429, IP-K430, IP-K431, IP-K432, IP-K433, IP-K434, IP-K435, IP-K436, IP-K437, IP-K438, IP-K439, IP-K440, IP-K441, IP-K442, IP-K443, IP-K444, IP-K445, IP-K446, IP-K447, IP-K448, IP-K449, IP-K450, IP-K451, IP-K452, IP-K453, IP-K454, IP-K455, IP-K456, IP-K457, IP-K458, IP-K459, IP-K460, IP-K461, IP-K462, IP-K463, IP-K464, IP-K465, IP-K466, IP-K467, IP-K468, IP-K469, IP-K470, IP-K471, IP-K472, IP-K473, IP-K474, IP-K475, IP-K476, IP-K477, IP-K478, IP-K479, IP-K480, IP-K481, IP-K482, IP-K483, IP-K484, IP-K485, IP-K486, IP-K487, IP-K488, IP-K489, IP-K490, IP-K491, IP-K492, IP-K493, IP-K494, IP-K495, IP-K496, IP-K497, IP-K498, IP-K499, IP-K500, IP-K501, IP-K502, IP-K503, IP-K504, IP-K505, IP-K506, IP-K507, IP-K508, IP-K509, IP-K510, IP-K511, IP-K512, IP-K513, IP-K514, IP-K515, IP-K516, IP-K517, IP-K518, IP-K519, IP-K520, IP-K521, IP-K522, IP-K523, IP-K524, IP-K525, IP-K526, IP-K527, IP-K528, IP-K529, IP-K530, IP-K531, IP-K532, IP-K533, IP-K534, IP-K535, IP-K536, IP-K537, IP-K538, IP-K539, IP-K540, IP-K541, IP-K542, IP-K543, IP-K544, IP-K545, IP-K546, IP-K547, IP-K548, IP-K549, IP-K550, IP-K551, IP-K552, IP-K553, IP-K554, IP-K555, IP-K556, IP-K557, IP-K558, IP-K559, IP-K560, IP-K561, IP-K562, IP-K563, IP-K564, IP-K565, IP-K566, IP-K567, IP-K568, IP-K569, IP-K570, IP-K571, IP-K572, IP-K573, IP-K574, IP-K575, IP-K576, IP-K577, IP-K578, IP-K579, IP-K580, IP-K581, IP-K582, IP-K583, IP-K584, IP-K585, IP-K586, IP-K587, IP-K588, IP-K589, IP-K590, IP-K591, IP-K592, IP-K593, IP-K594, IP-K595, IP-K596, IP-K597, IP-K598, IP-K599, IP-K600, IP-K601, IP-K602, IP-K603, IP-K604, IP-K605, IP-K606, IP-K607, IP-K608, IP-K609, IP-K610, IP-K611, IP-K612, IP-K613, IP-K614, IP-K615, IP-K616, IP-K617, IP-K618, IP-K619, IP-K620, IP-K621, IP-K622, IP-K623, IP-K624, IP-K625, IP-K626, IP-K627, IP-K628, IP-K629, IP-K630, IP-K631, IP-K632, IP-K633, IP-K634, IP-K635, IP-K636, IP-K637, IP-K638, IP-K639, IP-K640, IP-K641, IP-K642, IP-K643, IP-K644, IP-K645, IP-K646, IP-K647, IP-K648, IP-K649, IP-K650, IP-K651, IP-K652, IP-K653, IP-K654, IP-K655, IP-K656, IP-K657, IP-K658, IP-K659, IP-K660, IP-K661, IP-K662, IP-K663, IP-K664, IP-K665, IP-K666, IP-K667, IP-K668, IP-K669, IP-K670, IP-K671, IP-K672, IP-K673, IP-K674, IP-K675, IP-K676, IP-K677, IP-K678, IP-K679, IP-K680, IP-K681, IP-K682, IP-K683, IP-K684, IP-K685, IP-K686, IP-K687, IP-K688, IP-K689, IP-K690, IP-K691, IP-K692, IP-K693, IP-K694, IP-K695, IP-K696, IP-K697, IP-K698, IP-K699, IP-K700, IP-K701, IP-K702, IP-K703, IP-K704, IP-K705, IP-K706, IP-K707, IP-K708, IP-K709, IP-K710, IP-K711, IP-K712, IP-K713, IP-K714, IP-K715, IP-K716, IP-K717, IP-K718, IP-K719, IP-K720, IP-K721, IP-K722, IP-K723, IP-K724, IP-K725, IP-K726, IP-K727, IP-K728, IP-K729, IP-K730, IP-K731, IP-K732, IP-K733, IP-K734, IP-K735, IP-K736, IP-K737, IP-K738, IP-K739, IP-K740, IP-K741, IP-K742, IP-K743, IP-K744, IP-K745, IP-K746, IP-K747, IP-K748, IP-K749, IP-K750, IP-K751, IP-K752, IP-K753, IP-K754, IP-K755, IP-K756, IP-K757, IP-K758, IP-K759, IP-K760, IP-K761, IP-K762, IP-K763, IP-K764, IP-K765, IP-K766, IP-K767, IP-K768, IP-K769, IP-K770, IP-K771, IP-K772, IP-K773, IP-K774, IP-K775, IP-K776, IP-K777, IP-K778, IP-K779, IP-K780, IP-K781, IP-K782, IP-K783, IP-K784, IP-K785, IP-K786, IP-K787, IP-K788, IP-K789, IP-K790, IP-K791, IP-K792, IP-K793, IP-K794, IP-K795, IP-K796, IP-K797, IP-K798, IP-K799, IP-K800, IP-K801, IP-K802, IP-K803, IP-K804, IP-K805, IP-K806, IP-K807, IP-K808, IP-K809, IP-K810, IP-K811, IP-K812, IP-K813, IP-K814, IP-K815, IP-K816, IP-K817, IP-K818, IP-K819, IP-K820, IP-K821, IP-K822, IP-K823, IP-K824, IP-K825, IP-K826, IP-K827, IP-K828, IP-K829, IP-K830, IP-K831, IP-K832, IP-K833, IP-K834, IP-K835, IP-K836, IP-K837, IP-K838, IP-K839, IP-K840, IP-K841, IP-K842, IP-K843, IP-K844, IP-K845, IP-K846, IP-K847, IP-K848, IP-K849, IP-K850, IP-K851, IP-K852, IP-K853, IP-K854, IP-K855, IP-K856, IP-K857, IP-K858, IP-K859, IP-K860, IP-K861, IP-K862, IP-K863, IP-K864, IP-K865, IP-K866, IP-K867, IP-K868, IP-K869, IP-K870, IP-K871, IP-K872, IP-K873, IP-K874, IP-K875, IP-K876, IP-K877, IP-K878, IP-K879, IP-K880, IP-K881, IP-K882, IP-K883, IP-K884, IP-K885, IP-K886, IP-K887, IP-K888, IP-K889, IP-K890, IP-K891, IP-K892, IP-K893, IP-K894, IP-K895, IP-K896, IP-K897, IP-K898, IP-K899, IP-K900, IP-K901, IP-K902, IP-K903, IP-K904, IP-K905, IP-K906, IP-K907, IP-K908, IP-K909, IP-K910, IP-K911, IP-K912, IP-K913, IP-K914, IP-K915, IP-K916, IP-K917, IP-K918, IP-K919, IP-K920, IP-K921, IP-K922, IP-K923, IP-K924, IP-K925, IP-K926, IP-K927, IP-K928, IP-K929, IP-K930, IP-K931, IP-K932, IP-K933, IP-K934, IP-K935, IP-K936, IP-K937, IP-K938, IP-K939, IP-K940, IP-K941, IP-K942, IP-K943, IP-K944, IP-K945, IP-K946, IP-K947, IP-K948, IP-K949, IP-K950, IP-K951, IP-K952, IP-K953, IP-K954, IP-K955, IP-K956, IP-K957, IP-K958, IP-K959, IP-K960, IP-K961, IP-K962, IP-K963, IP-K964, IP-K965, IP-K966, IP-K967, IP-K968, IP-K969, IP-K970, IP-K971, IP-K972, IP-K973, IP-K974, IP-K975, IP-K976, IP-K977, IP-K978, IP-K979, IP-K980, IP-K981, IP-K982, IP-K983, IP-K984, IP-K985, IP-K986, IP-K987, IP-K988, IP-K989, IP-K990, IP-K991, IP-K992, IP-K993, IP-K994, IP-K995, IP-K996, IP-K997, IP-K998, IP-K999, IP-K1000, IP-K1001, IP-K1002, IP-K1003, IP-K1004, IP-K1005, IP-K1006, IP-K1007, IP-K1008, IP-K1009, IP-K1010, IP-K1011, IP-K1012, IP-K1013, IP-K1014, IP-K1015, IP-K1016, IP-K1017, IP-K1018, IP-K1019, IP-K1020, IP-K1021, IP-K1022, IP-K1023, IP-K1024, IP-K1025, IP-K1026, IP-K1027, IP-K1028, IP-K1029, IP-K1030, IP-K1031, IP-K1032, IP-K1033, IP-K1034, IP-K1035, IP-K1036, IP-K1037, IP-K1038, IP-K1039, IP-K1040, IP-K1041, IP-K1042, IP-K1043, IP-K1044, IP-K1045, IP-K1046, IP-K1047, IP-K1048, IP-K104



A3 DEMO PLAN
1/8" = 1'-0"




KEYNOTES - DEMO PLAN	
NUMBER	COMMENTS
1	DEMO EXISTING FLOORING AND BASE, TYPICAL THROUGHOUT, PREP FOR NEW FINISHES.
2	DEMO PLUMBING FIXTURES AND CAP PLUMBING, REMEP.
3	DEMO EXISTING LOCKERS, PATCH AND REPAIR AREA FOR NEW CONSTRUCTION, SALVAGE TO OWNER.
4	DEMO POOL, EQUIPMENT AND ASSOCIATED EQUIPMENT IN ITS ENTIRETY, PREP TO BE FILLED.
5	DEMO EXISTING CASEWORK, PREP AREA FOR NEW CONSTRUCTION.
6	DEMO TOILET PARTITION.
8	COORDINATE EQUIPMENT RELOCATION WITH OWNER.
9	DEMO EXISTING FIXTURE, REMEP, PREP FOR NEW FIXTURE.
11	DEMO EXISTING GRID AND CEILING TILES.
12	REMOVE LIGHTS AND DIFFUSERS, REMEP, SALVAGE TO OWNER.
13	DEMO GYP SUFFIT AS REQUIRED.
14	DEMO GYP CEILING AS REQUIRED.

GENERAL DEMOLITION NOTES

- THE OWNER SHALL VACATE THE EXISTING ROOMS AS INDICATED ON THE PLAN AND BE RESPONSIBLE FOR THE REMOVAL OF ANY EQUIPMENT WHICH IS TO REMAIN THE PROPERTY OF THE OWNER PRIOR TO ANY WORK DONE BY THE CONTRACTOR FOR THIS PORTION OF THE SEQUENCE.
- INSTALL TEMPORARY DUST PARTITION AND/OR BARRIERS AND OTHER METHODS AS MAY BE REQUIRED/NECESSARY AS INDICATED ON THE PLAN AND AS NECESSARY TO CONTAIN DEMOLITION CONSTRUCTION DUST AND DEBRIS WITHIN THE AREA OF CONSTRUCTION. REFER TO DUST PARTITION "DP" ON THIS SHEET AND THE SPECIFICATIONS FOR ADDITIONAL INFORMATION.
- IT IS THE INTENT OF THIS DEMOLITION TO REMOVE ALL EXISTING CONSTRUCTION WHICH CONFLICTS WITH THE INTENT OF THE NEW CONSTRUCTION. EVERY DEMOLITION DETAIL MAY NOT NECESSARILY BE COVERED ON THESE DRAWINGS. FIELD VERIFY THE EXTENT OF ALL DEMOLITION.
- THE CONTRACTOR SHALL USE EXTREME CARE IN THE PROTECTION OF ALL ADJACENT AREAS FOR IT IS IMPERATIVE TO PROVIDE CONTINUOUS OPERATION OF ALL OCCUPIED AREAS DURING THE DEMOLITION, CONSTRUCTION AND RENOVATION.
- ALL DEMOLITION DESCRIBED IN THESE DOCUMENTS SHALL BE COORDINATED WITH PHASING WORK REQUIRED TO COMPLETE THE WORK.
- THE CONTRACTOR SHALL COORDINATE ALL DEMOLITION WORK WITHIN OCCUPIED SPACES ABOVE, BELOW AND ADJACENT TO THE WORK. THE CONTRACTOR SHALL NOTIFY THE OWNER AND THE MANAGEMENT OF THE OCCUPIED SPACES ABOVE, BELOW, AND ADJACENT TO THE WORK, TWO WEEKS PRIOR TO COMMENCING WORK. SUCH SPACES ARE TO REMAIN OCCUPIED DURING DEMOLITION AND ALL WORK SHALL BE PERFORMED IN SUCH A MANNER TO MINIMIZE DISRUPTION TO OCCUPIED SPACES. EXISTING FLOOR, WALL AND CEILING FINISHES TO REMAIN SHALL BE PROTECTED AND ANY DAMAGE DONE AS A RESULT OF DEMOLITION WORK SHALL BE REPAIRED.
- IN AREAS SCHEDULED FOR DEMOLITION, THE CONTRACTOR SHALL REMOVE ALL ACCESSORIES, GRAB BARS, MIRRORS, SOAP AND PAPER TOWEL DISPENSERS, SHELVES, BULLETIN BOARDS, ETC., SHALL BE TURNED OVER TO THE OWNER, EXCEPT FOR RELOCATED ITEMS.
- WHERE NEW FINISHES ARE CALLED FOR, REMOVE AND DISCARD EXISTING FLOORING, CEILINGS AND WALL COVERING THROUGH-OUT AREA DESIGNATED FOR NEW CONSTRUCTION AND PREP EXISTING FLOOR AND WALL SUBSTRATE TO RECEIVE THE INSTALLATION OF NEW FINISH AS SCHEDULED.
- SEE NEW WORK PLAN FOR REPAIR AND PREPARATION OF ADJACENT SURFACES.
- WHERE CEILING IS TO REMAIN, REMOVE ALL DAMAGED CEILING PANELS/ TILES AND REPLACE WITH NEW TO MATCH EXISTING.
- REMOVE AND RETURN TO THE OWNER ALL EXISTING PLUMBING FIXTURES. CAP ALL SUPPLY AND WASTE LINES AS REQUIRED. REFER TO PLUMBING DRAWINGS FOR ADDITIONAL INFORMATION.
- THE CONTRACTOR SHALL PATCH TO MATCH ADJACENT SURFACES OF EXISTING WALLS, FLOOR, AND CEILINGS IN ALL AREAS THAT REQUIRE THE REMOVAL OF GENERAL MECHANICAL, ELECTRICAL, PLUMBING, AND FIRE PROTECTION WORK AND OF EQUIPMENT AND FIXTURES.
- THE CONTRACTOR SHALL PROVIDE FOR ALL NECESSARY TEMPORARY RELOCATION AND MAINTENANCE OF ALL EXISTING UTILITIES WHICH ARE CURRENTLY IN USE AND WHICH MUST BE TEMPORARILY RELOCATED DURING CONSTRUCTION OF NEW AREAS AND RENOVATION OF EXISTING AREAS.
- REFER TO MECHANICAL, ELECTRICAL, PLUMBING, AND FIRE PROTECTION DRAWINGS FOR WORK REQUIRED FOR NEW CONSTRUCTION.
- WHERE REMOVAL OF EXISTING PARTITIONS, EQUIPMENT, ETC. DISTURBS EXISTING MECHANICAL, PLUMBING OR ELECTRICAL SERVICES, THE CONTRACTOR SHALL MAKE PERMANENT REVISIONS/PROVISIONS AS REQUIRED TO MAINTAIN SERVICES AND IF NECESSARY, PROVIDE TEMPORARY SERVICES TO AREAS NOT SCHEDULED FOR DEMOLITION, RENOVATION, AND/OR NEW CONSTRUCTION.
- WHERE EXISTING WALLS, CEILINGS, OR FLOORS ARE DAMAGED BY THE CONTRACTOR FOR ACCESS TO SERVICES AND NEW CONSTRUCTION WHICH MAY NOT BE INDICATED IN THE CONTRACT DOCUMENTS, THE CONTRACTOR SHALL BE RESPONSIBLE TO PATCH TO MATCH MATERIAL, AND FINISHES TO ORIGINAL CONDITIONS. IF EXISTING FINISHES CANNOT BE MATCHED, THE ENTIRE WALL, CEILING, OR FLOOR SHALL BE REFINISHED TO THE NEAREST CORNER OR POSITIVE BREAKING POINT.
- WHEN DEMOLITION CAUSES DAMAGE TO FLOOR SLAB, WALL, OR CEILING SURFACES WHICH WILL REMAIN EXPOSED IN THE FINISHED WORK, SUCH CONDITIONS SHALL BE REPAIRED AND LEVELED AS REQUIRED TO RECEIVE NEW FINISHES.
- WHEN DEMOLITION EXPOSES DAMAGE TO FLOOR SLAB, WALL, OR CEILING SURFACES WHICH WILL REMAIN EXPOSED IN THE FINISHED WORK, SUCH CONDITIONS SHALL BE REPORTED TO THE ARCHITECT AND OWNER WITH A RECOMMENDATION FOR RESOLUTION OF THE CONDITIONS.
- CLEAN AIR GRILLES AND LIGHT FIXTURES THROUGHOUT PROJECT AREA UPON COMPLETION OF WORK.
- WHERE EXISTING PHONE, DATA, OR PHONE/DATA OUTLETS ARE REMOVED, THE CONTRACTOR SHALL USE EXTREME CARE IN PULLING WIRE THROUGH THE EXISTING CONDUITS, COIL AND WRAP ABOVE EXISTING CEILING FOR REUSE.
- WHERE EXISTING WALLS, WINDOWS, AND/OR DOORS ARE BEING REMOVED, THE CONTRACTOR WILL BE RESPONSIBLE TO CONSTRUCT TEMPORARY PARTITIONS AS REQUIRED TO ENSURE THAT THE EXISTING BUILDINGS REMAIN WATERTIGHT, SECURE, AND WITHOUT DRAFTS DURING DEMOLITION WORK. THESE PARTITIONS SHALL REMAIN IN PLACE DURING THE NEW CONSTRUCTION WORK, OR AS REQUIRED TO MAINTAIN THIS SEPARATION.
- PROVIDE SHORING AND BRACING AS REQUIRED DURING DEMOLITION AND NEW CONSTRUCTION.

DEMOLITION LEGEND

- NOT IN SCOPE
- EXISTING WALL, DOOR, FRAME AND HARDWARE TO REMAIN
- WALLS, DOORS, DOOR/WINDOW FRAMES, EQUIPMENT, FIXTURES, ETC. INDICATED BY DASHED LINES WITHIN THE AREA OF CONSTRUCTION SHALL BE REMOVED. REFER TO THIS SHEET FOR ARCHITECTURAL DEMOLITION NOTES.
- DUST PARTITIONS - THE CONTRACTOR SHALL MAKE EVERY EFFORT TO ENSURE THE EXISTING BUILDING TO BE COMPLETELY PROTECTED AGAINST INFILTRATION OF DUST AND MOISTURE DURING THE COURSE OF DEMOLITION CONSTRUCTION WITH DUST PARTITIONS ACROSS CORRIDORS AND OPENINGS THRU EXISTING WALLS. ALL CONSTRUCTION WORK CREATING ANY TYPE OF DUST THROUGHOUT THE BUILDING SHALL BE SHIELDED BY DUST PROTECTION. PROVIDE DOOR OPENINGS AS REQUIRED FOR EMERGENCY EGRESS.
- DUST BARRIERS - (2) LAYERS 6 MIL PVC W/ STUDS @ 4'-0" O.C. DUST BARRIER. THE CONTRACTOR SHALL MAKE EVERY EFFORT TO ENSURE THE EXISTING BUILDING TO BE COMPLETELY PROTECTED AGAINST THE INFILTRATION OF DUST & MOISTURE DURING THE COURSE OF DEMOLITION/ CONSTRUCTION. PROVIDE DOOR OPENINGS AS REQUIRED FOR EMERGENCY EGRESS.



WHERE DUST PARTITIONS ARE TO REMAIN THROUGH CONSTRUCTION, THEY SHALL BE CONSTRUCTED OF 3-5/8" METAL STUDS WITH CONTINUOUS TOP AND BOTTOM RUNNERS. PARTITIONS SHALL EXTEND TIGHT FROM FLOOR TO THE EXISTING CEILING OR STRUCTURE ABOVE, AND COPED AROUND DUCTS, PIPES, ETC. THAT PENETRATE THE PARTITION. THE ENTIRE PARTITION SHALL BE COVERED WITH 5/8" FIRE RATED GYP. BOARD SCREWED TO STUDS. ALL JOINTS BETWEEN SHEATHING, AT WALLS, AT FLOORS, CEILINGS, AROUND PIPES, ETC., TAPED AND SEALED TIGHT TO ENSURE DUST-PROOFING.

THE CONTRACTOR SHALL COVER AND SEAL IN A DUST-TIGHT MANNER ALL EXISTING OPENINGS, GRILLES, JOINTS AROUND DOORS AND FRAMES, ETC., WITH FIRE RETARDANT SHEET AND/OR TAPE AS APPROPRIATE WHERE SUCH OPENINGS, ETC., OCCUR IN EXISTING PARTITIONS SEPARATING EXISTING AREAS FROM CONSTRUCTION AREAS. THE CONTRACTOR SHALL MAINTAIN AND REPAIR ANY DUST BARRIERS AS DETERMINED BY, AND TO THE SATISFACTION OF, THE OWNER.

SMOKE TIGHT (NON-COMBUSTIBLE CONSTRUCTION)
DP
1 1/2" = 1'-0"

PULMONARY CLINIC - PHASE 1
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
20 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

Date 8/15/22
Job Number 3-22015
Drawn By Author
Checked By Checker

Revision
Number Date Description

AD2.1
© 2022 ACI/BOLAND, Inc.
DEMOLITION PLAN

RELEASED FOR CONSTRUCTION
8/15/2022 11:02:37 AM
License - Missouri WA-2011012130


ACI
BOLAND
ARCHITECTS

ACI/Boland, Inc.
Kansas City | St. Louis
1710 Wyandotte
Kansas City, MO 64108
T: 816.763.9600

Licensee's Certificate of Authority Number:
Missouri: #000958



A1 DEMOLITION RCP
1/8" = 1'-0"



KEY PLAN AREAS
1" = 50'-0"



KEYNOTES - DEMO RCP	
NUMBER	COMMENTS
11	DEMO EXISTING GRID AND CEILING TILES.
12	REMOVE LIGHTS AND DIFFUSERS. RE MEP. SALVAGE TO OWNER.
13	DEMO GYP SOFFIT AS REQUIRED.
14	DEMO GYP CEILING AS REQUIRED.

RELEASED FOR CONSTRUCTION
NOT TO BE REPRODUCED
WITHOUT THE WRITTEN PERMISSION OF THE ARCHITECT

SAMUEL K. BECKMAN

ARCHITECT

8/15/2022

8/15/2022 11:02:49 AM

Samuel K. Beckman - Architect
License - Missouri WA-2011012130

ACI

BOLAND

ARCHITECTS

ACI/Boland, Inc.
Kansas City | St. Louis
1710 Wyandotte
Kansas City, MO 64108
T: 816.763.9600
Licensee's Certificate of Authority Number:
Missouri: #000958

PULMONARY CLINIC - PHASE 1

SAINT LUKE'S EAST HOSPITAL

FIRST FLOOR MOB

20 NE SAINT LUKE'S BLVD.

LEE'S SUMMIT, MO 64086

Date8/15/22

Job Number3-22015

Drawn ByAuthor

Checked ByChecker

Revision

NumberDateDescription

AD3.1

© 2022 ACI/BOLAND, Inc.

DEMOLITION REFLECTED CEILING PLAN

RELEASED FOR
CONSTRUCTION
8/31/2022 1:49:55 PM
A-20110-0001

STATE OF MISSOURI
SAMPLER
BECKMAN
ARCHITECT
A-20110-0001

8/31/2022 1:49:55 PM
Samuel K. Beckman - Architect
License - Missouri WA-2011012130

ACI
BOLAND
ARCHITECTS

ACI/Boland, Inc.
Kansas City | St. Louis
1710 Wyandotte
Kansas City, MO 64108
T: 816.763.9600
Licensee's Certificate of Authority Number:
Missouri: #000958

PULMONARY CLINIC - PHASE 1
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
20 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

Date8/15/22
Job Number3-22015
Drawn ByKDS
Checked ByABD

Revision

Number	Date	Description
1	8.19.22	ASI 1
2	8.31.22	CITY

A2.1

© 2022 ACI/BOLAND, Inc.

FIRST FLOOR DIMENSION AND
ANNOTATION PLAN AREA A

FFE SCHEDULE			
TYPE MARK	DESCRIPTION	RESPONSIBILITY	COMMENTS
A1015	PHONE, DESK	OFOI	POWER AND DATA AS REQUIRED, RE: MEP
A1080	MIRROR	OFOI	BLOCKING AS REQUIRED, RE: SPECS
A5075	SOAP DISPENSER	OFOI	
A5080	PAPER TOWEL DISPENSER	OFOI	BLOCKING AS REQUIRED
AS108	SHARPS	OFOI	BLOCKING AS REQUIRED
AS108a	GRAB BAR, HORIZONTAL, 36"	OFOI	BLOCKING AS REQUIRED, RE: SPECS
AS108b	GRAB BAR, HORIZONTAL, 42"	OFOI	BLOCKING AS REQUIRED, RE: SPECS
AS108c	GRAB BAR, VERTICAL, 18"	OFOI	BLOCKING AS REQUIRED, RE: SPECS
AS108d	COAT HOOK	OFOI	BLOCKING AS REQUIRED, RE: SPECS
A5200	DISPENSER TOILET PAPER	OFOI	BLOCKING AS REQUIRED
F0205	SIZE CHAIR, W/ ARMIS	VFVI	PROVIDED BY JOHN A. MARSHALL
F0300	CHAIR, TASK	VFVI	PROVIDED BY JOHN A. MARSHALL
F0306	CHAIR, WAITING ROOM, BARIATRIC	VFVI	PROVIDED BY JOHN A. MARSHALL
F0430	MOBILE FILE CABINET	VFVI	PROVIDED BY JOHN A. MARSHALL
F0750	TABLE	VFVI	PROVIDED BY JOHN A. MARSHALL
F2010	STEP TRASHCAN	OFOI	
F0205	DRY ERASE WHITEBOARD	OFOI	
K4665	MICROWAVE	OFOI	POWER REQUIRED, RE: MEP
M0500	MONITOR, TELEVISION, 55"	OFOI	BRACKET, OPCI, BLOCKING AS REQUIRED, POWER & CABLE AS REQUIRED, RE: MEP, COORDINATE FINAL TV SIZE, BRACKET & MOUNTING HEIGHT W/ OWNER.
M1801	COMPUTER MONITOR	OFOI	
M1802	DUAL COMPUTER MONITOR	OFOI	POWER AND DATA AS REQUIRED, RE: MEP
M1825	PRINTER	OFOI	POWER AND DATA AS REQUIRED, RE: MEP
M1840	PRINTER/COPIER/FAX COMBINATION	OFOI	POWER AND DATA AS REQUIRED, RE: MEP
M0373	INFECTIOUS WASTE BASKET	OFOI	
M4020	SCALE	OFOI	
M7040	WHEELED ERGO TABLE FOR LAPTOP	OFOI	
M8133	ERGONOMETER	OFOI	POWER REQUIRED, RE: MEP
M8185	TREADMILL	OFOI	POWER REQUIRED, RE: MEP
M9025	EXAM TABLE W/ CABINET	OFOI	
U1000	CARD READER	OFOI	POWER AND DATA AS REQUIRED, RE: MEP
U1002	PPT BOOTH	OFOI	
U1008	ROWING MACHINE	OFOI	
U1007	ELLIPTICAL	OFOI	POWER REQUIRED, RE: MEP
U1008	LEG PRESS	OFOI	
U1009	REBOUNDER	OFOI	
U1010	MUSTED	OFOI	
U1011	RECLUBENT BIKE	OFOI	
U1012	THERAPY STAIRS	OFOI	
U1013	ENF TREATMENT TABLE	OFOI	
U1014	BARIATRIC PARALLEL BARS	OFOI	
U1015	18"x5" TABLE	OFOI	

- GENERAL PLAN NOTES
1. REFER TO GENERAL NOTES, LEGENDS & SYMBOLS SHEET FOR ADDITIONAL GENERAL NOTES AS APPLICABLE.

2. DO NOT SCALE DRAWINGS

3. THE WORD "ALIGN" AS USED IN THESE DOCUMENTS SHALL SUPERSEDE ANY DIMENSIONAL INFORMATION GIVEN.

4. TYPICAL DIMENSIONS ARE TO FACE OF CONCRETE, DRYWALL, CURTAIN WALL, ETC., OR TO COLUMN CENTERLINE. DIMENSIONS AT WINDOWS ARE TYPICALLY TO FACE OF FRAME. REFER TO PLAN DETAILS FOR ADDITIONAL INFORMATION.

5. IF MATERIAL SUSPECTED OF CONTAINING HAZARDOUS MATERIALS ARE ENCOUNTERED, DO NOT DISTURB. IMMEDIATELY NOTIFY ARCHITECT AND OWNER. OWNER SHALL COORDINATE WITH CONTRACTOR ON THE REMOVAL OF SUCH ITEMS. WORK MAY PROCEED AFTER HAZARDOUS MATERIAL HAS BEEN REMOVED.

6. CONTRACTOR SHALL FURNISH AND INSTALL CONCEALED FIRE-TREATED WOOD BLOCKING BEHIND ALL CABINETS, TOILET ACCESSORIES, PLUMBING FIXTURES, AND OTHER WALL MOUNTED ITEMS AS REQUIRED FOR ADEQUATE SUPPORT.


REMODEL/RENOVATION NOTES

7. THE CONTRACTOR SHALL FIELD VERIFY EXISTING CONDITIONS AND NOTIFY ARCHITECT OF ANY INCONSISTENCIES OR DISCREPANCIES WITH THE PROJECT DOCUMENTS. ACCESS TO THE SITE AND/OR SPACE UNDER CONSTRUCTION DURING BIDDING AND CONSTRUCTION SHALL BE COORDINATED WITH THE OWNER.



8. THE CONTRACTOR SHALL BE RESPONSIBLE FOR EXAMINING AND CONFIRMING ALL SUBSTRATE CONDITIONS WHERE NEW MATERIALS ARE APPLIED. THE SUBSTRATE SHALL BE SMOOTH AND FREE OF DEFECTS AND SHALL CONFORM TO THE REQUIREMENTS OF THE FINISHED MATERIAL MANUFACTURERS RECOMMENDATIONS.


9. UPON VERIFICATION OF THE EXISTING CONDITIONS, THE CONTRACTOR SHALL DETERMINE AND RECOMMEND THE BEST ACTION TO MINIMIZE THE EXTENT OF REMOVAL WORK FOR INSTALLATION OF NEW WORK.

10. ALL EXISTING CONSTRUCTION TO REMAIN SHALL BE PATCHED, REPAIRED, AND PREPPED AS REQUIRED FOR NEW FINISH APPLICATION.




KEYNOTES - FLOOR PLAN AREA A	
NUMBER	COMMENTS
1	REINFORCED WITH 6x6x1/2x2x3 WWR. PROVIDE 10 MIL VAPOR RETARDER BETWEEN SLAB AND GRANULAR FILL. DRILL AND EPOXY #3x2-0" WITH HILTI HY200 ADHESIVE AROUND THE PERIMETER WITH 4" EMBED INTO THE EXISTING SLAB. THE TOP OF THERAPY POOL SLAB SHALL MATCH EXISTING SLAB AROUND THE PERIMETER. RE INFILL DETAIL
2	OFFSET WALL PARTITION AS REQUIRED TO CENTER WALL ON EXISTING MULLION. INSTALL MULLION CAP RE: DETAIL
3	TERMINATE WALL PARTITION INTO COLUMN.
4	NEW BASE AND PAINT TO MATCH ADJACENT FINISHES
5	NEW PREFINISHED CANOPY





#	KEYNOTES - FLOOR PLAN AREA B
NUMBER	COMMENTS
6	COORDINATE EQUIPMENT RELOCATION WITH OWNER.
7	HOLD SEPARATE LINE ITEM ALLOWANCE FOR POWER POLES AS REQUIRED BY NEW EQUIPMENT LAYOUT.
8	RELOCATE TECH WORK DESK AND PROVIDE POWER/DATA RE-MEP.
9	PATCH TO MATCH FLOORING AS REQUIRED AFTER REMOVAL OF WALL.



KEY PLAN AREAS
1" = 50'-0"




A1 DIMENSION AND ANNOTATION PLAN - AREA B
1/4" = 1'-0"




PULMONARY CLINIC - PHASE 1
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
20 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

Date 8/15/22
Job Number 3-22015
Drawn By Author
Checked By Checker


Revision
Number Date Description




E6 BULKHEAD DETAIL
1 1/2" = 1'-0"




E5 SOFFIT DTL.
1 1/2" = 1'-0"




E4 GYPSUM BOARD SOFFIT
1 1/2" = 1'-0"




D6 CUBICLE CURTAIN TRACK DTL.
1 1/2" = 1'-0"




A1 TYPICAL HEAD- HOLLOW METAL DOOR FRAME



D6 TRANSITION STRIP DETAILS
6" = 1'-0"



C6 TYPICAL ELEVATION OF WALL PROTECTION - CORNER GUARD
1" = 1'-0"



C4 TYP. ELEV. OF WALL TILE PATTERN
1/4" = 1'-0"

ROOM FINISH SCHEDULE														
ROOM NUMBER	ROOM NAME	FLOOR FINISH	BASE FINISH	WALLS				CASEWORK				NOTES	REVISION #	
				NORTH	EAST	SOUTH	WEST	BASE CABINETS	WALL CABINETS	COUNTERTOPS	SINKS			CEILING
100	TEMP WAITING FUTURE PROCEDURE & RECEPTION	LVT-2	RB-1	PT-1	PT-1	PT-1	PT-1.9	-	-	-	-	ACT-1 / PT-5		
100A	CORRIDOR	LVT-2	RB-1	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	-	-	-	-	ACT-1		
100A.1	VITALS	LVT-2	RB-1	PT-2 / WP-2	PT-2 / WP-2	PT-2 / WP-2	PT-2 / WP-2	-	-	-	-	PT-2	3	
100B	CORRIDOR	LVT-2	RB-1	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	-	-	-	-	ACT-1 / PT-5		
100C	CORRIDOR	LVT-2	RB-1	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	-	-	-	-	ACT-1 / PT-5		
100D	CORRIDOR	LVT-2	RB-1	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	-	-	-	-	ACT-1 / PT-5		
100E	CORRIDOR	LVT-2	RB-1	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	-	-	-	-	ACT-1 / PT-5		
101	RECEPTION	LVT-1	RB-2	PT-2	PT-2	PT-2	PT-2	PLAM-1	-	SSF-1 / QTZ-1	-	ACT-1	1	
102	PAT. TLT.	PFT-2	MT-1	PT-1A / PWT-1	PT-1A / PWT-1	PT-1A / PWT-1	PT-1A / PWT-1	-	-	-	-	ACT-1		
103	OFFICE MANAGER	LVT-1	RB-2	PT-1.2	PT-1	PT-1	PT-1	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
104	EXAM 1	LVT-1	RB-1	PT-8 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
105	EXAM 2	LVT-1	RB-1	PT-8 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
106	EXAM 3	LVT-1	RB-1	PT-8 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
107	EXAM 4	LVT-1	RB-1	PT-8 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
108	CLEAN / MEDS	RSF-1	IB-1	PT-1A / WP-2	PT-1A / WP-2	PT-1A / WP-2	PT-1A / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-2		
109	SOILED	RSF-1	IB-1	PT-1A / WP-2	PT-1A / WP-2	PT-1A / WP-2	PT-1A / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-2		
110	STAFF TOILET	RSF-2	IB-2	PWT-1	PT-1A	PT-1A	PT-1A	-	-	-	-	ACT-1	1	
111	STORAGE	LVT-2	RB-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	-	-	-	-	ACT-1		
112	EXAM 5 / SLEEP TECH	LVT-2	RB-1	PT-8 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
113	EXAM 6	LVT-1	RB-1	PT-8 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
114	EXAM 7	LVT-1	RB-1	PT-8 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
115	EXAM 8	LVT-1	RB-1	PT-8 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
116	TEMP BREAK / CONF	LVT-1	RB-1	PT-1	PT-1	PT-1	PT-1	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
117	PFT / FUTURE PROCEDURE FLEX	LVT-1	RB-1	PT-1A / WP-2	PT-1A / WP-2	PT-1A / WP-2	PT-1A / WP-2	PLAM-1	PLAM-1	SSF-1	IS-1	ACT-1		
118	PHYSICIAN 4	LVT-1	RB-2	PT-1	PT-2	PT-1	PT-1	-	-	-	-	ACT-1		
119	MA 4	LVT-1	RB-2	PT-2	PT-2	PT-2	PT-2	-	-	-	-	ACT-1		
120	TEAM CENTER 2	LVT-1	RB-2	-	PT-2.9	PT-2	PT-9	-	-	-	-	ACT-1 / PT-9	2	
121	MA 3	LVT-1	RB-2	PT-2	PT-2	PT-2	PT-2	-	-	-	-	ACT-1		
122	PHYSICIAN 3	LVT-1	RB-2	PT-1	PT-1	PT-1	PT-1	-	-	-	-	ACT-1		
123	PHYSICIAN 2	LVT-1	RB-2	PT-1	PT-2	PT-1	PT-1	-	-	-	-	ACT-1		
124	MA 2	LVT-1	RB-2	PT-2	PT-2	PT-2	PT-2	-	-	-	-	ACT-1		
125	TEAM CENTER 1	LVT-1	RB-2	-	PT-2.9	PT-2	PT-2.9	-	-	-	-	ACT-1 / PT-9	2	
126	MA 1	LVT-1	RB-2	PT-2	PT-2	PT-2	PT-2	-	-	-	-	ACT-1		
127	PHYSICIAN 1	LVT-1	RB-2	PT-1	PT-1	PT-1	PT-2	-	-	-	-	ACT-1		
154	CORRIDOR	LVT-2	RB-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	PT-1 / WP-2	-	-	-	-	ACT-1		
154A	VESTIBULE	LVT-2	RB-1	PT-1	PT-1	PT-1	PT-1	-	-	-	-	ACT-1		
D148	STAFF WORKROOM	ETR	PM	ETR	ETR	ETR	PM	ETR	ETR	ETR	ETR	ETR / ACT-1	4	

INTERIOR FINISH LEGEND							
MARK	ITEM	MANUFACTURER	MODEL / PATTERN	COLOR	SIZE	REMARKS	REVISION #
FLOOR							
LVT-1	LUXURY VINYL TILE	MANNINGTON	AMTICO WOOD	REGENCY WALNUT	4 1/2" X 36"	STRAIGHT EDGE ONLY. RANDOM OFFSET INSTALLATION	
LVT-2	LUXURY VINYL TILE	MANNINGTON	AMTICO STONE	CORINTHIAN MARBLE	18" X 18"	STRAIGHT EDGE ONLY. ASHLAR INSTALL	
PFT-2	PORCELAIN FLOOR TILE	CAESAR CERAMICS USA	LINK	CHAIN	12" X 24"	1/3 OFFSET INSTALL. USE GT-2. MINIMUM GROUT SIZE	
RSF-1	RESILIENT SHEET FLOORING	MANNINGTON	BIOFPEC MD	LINEN 15420	6'-0" ROLL	MATCHING WELD ROD. HOMOGENEOUS FLOORING	
RSF-2	RESILIENT SHEET FLOORING	SHAW CONTRACT	TERASU, REED	PAGODA 96710	6'-0" ROLL	MATCHING WELD ROD. HETEROGENEOUS FLOORING	
WOM-1	WALK-OFF CARPET	TANDUS-CENTIVA	ASSERTIVE STRIA - #04839	LEAD SHOT - #26207	6' ROLL; 24" X 24" TILE	VERTICAL ASHLAR INSTALLATION	
BASE							
IB-1	INTEGRAL BASE	MANNINGTON	BIOFPEC MD	LINEN 15420	6" COVE	J MOLD SCHLUTER STRIP AT THE TOP. TO BE USED WITH RSF-1	
IB-2	INTEGRAL BASE	SHAW CONTRACT	TERASU, REED	PAGODA 96710	6" COVE	J MOLD SCHLUTER STRIP AT THE TOP. TO BE USED WITH RSF-2	
MT-1	METAL COVE BASE TRIM	SCHLUTER	DILEX-AHR	STAINLESS STEEL	-	TO BE USED WITH PWT-1 AND PFT-2	
RB-1	RESILIENT BASE	SCHLUTER	PINNACLE PLUS, PROFILE #65	#120 DOLPHIN	4-6"	-	
RB-2	RESILIENT BASE	SCHLUTER	PINNACLE PLUS, PROFILE #65	#120 DOLPHIN	4" COVE	-	
WALL							
CG-1	CORNER GUARDS	CIS ACROVYN	SM-20AN-ACROVYN-4000	#933 MISSION WHITE	3"	90 DEGREE. ABOVE BASE TO 48" AFF	
CG-3	CORNER GUARDS	CIS ACROVYN	SSM-25AN-ACROVYN-4000	#933 MISSION WHITE	2"	END WALL. ABOVE BASE TO CEILING / INCLUDE ALL TRIM AND ACCESSORIES PIECES	
PT-3	PAINT	SHERWIN WILLIAMS	EGGSHELL FINISH	SW7008 ALABASTER	-	FIELD PAINT	
PT-1A	PAINT	SHERWIN WILLIAMS	EPOXY FINISH	SW7008 ALABASTER	-	FIELD PAINT	
PT-2	PAINT	SHERWIN WILLIAMS	EGGSHELL FINISH	SW7041 COLONIADE GRAY	-	ACCENT PAINT	
PT-4	PAINT	SHERWIN WILLIAMS	SEMI-GLOSS FINISH	SW7046 ANONYMOUS	-	ALL HOLLOW METAL DOOR AND WINDOW FRAMES	
PT-5	PAINT	SHERWIN WILLIAMS	FLAT FINISH	SW7008 ALABASTER	-	CEILING PAINT	
PT-8	PAINT	SHERWIN WILLIAMS	EGGSHELL FINISH	SW7021 SILVERMIST	-	ACCENT PAINT	
PT-9	PAINT	SHERWIN WILLIAMS	EGGSHELL FINISH	SW7042 PAVESTONE	-	ACCENT PAINT	
PWT-1	PORCELAIN WALL TILE	ATLAS CONCORDE USA	EON	ELDORADO	12" X 24"	1/3 OFFSET INSTALL. USE GT-2. MINIMUM GROUT SIZE	
WP-2	WALL PROTECTION	CIS ACROVYN	ACROVYN 4000	#933 MISSION WHITE	4' X 10' SHEETS; .040" THICK	WALL PROTECTION AT 48" AFF. INCLUDE ALL ACCESSORIES AND TRIM PIECES	
CASEWORK							
IS-1	INTEGRAL SINK	CORIAN	REFER TO SPEC	BONE	30" X 14" SHEET; .36" X 144" SHEET	-	
PLAM-1	PLASTIC LAMINATE	WILSONART	#7865K-12	WALNUT HEIGHTS	-	CUSTOM 3MM PVC DOELKEN WALNUT HEIGHTS	
QTZ-1	QUARTZ SURFACE	CAMBRIA	PT-1	DARLINGTON	55" X 120" SLAB	2CM, 3CM SEAFLIP EDGE PROFILE	
SSF-1	SOLID SURFACE	CORIAN	-	CLAM SHELL	1/2" 30" X 144" SHEET; .36" X 144" SHEET	-	
CEILING							
ACT-1	ACOUSTIC CEILING TILE	USG	RADAR CLIMA PLUS #2210	WHITE	2' X 2'	SQUARE EDGE, DONN DX TEE 15/16" GRID SYSTEM	
ACT-2	ACOUSTIC CEILING TILE	USG	CLEAN ROOM CLIMA PLUS CLASS 100 #9609 (UNPERFORATED)	WHITE	2' X 2'	VINYL FACED W/ SQUARE EDGE, DONN DX 15/16" TEE GRID SYSTEM	
MISC.							
GT-2	GROUT	MAPEI	KERACOLOR S	#107 IRON	-	MINIMAL. GROUT LINES	
MT-2	METAL TRIM	SCHLUTER	QUADEC	STAINLESS STEEL	-	TO BE USED ON ALL OUTSIDE CORNERS OF EXPOSED WALL TILE	
TRS-1	TRANSITION STRIP	SCHLUTER	SCHIENE	CLEAR SATIN ANODIZED ALUMINUM	-	-	
TRS-2	TRANSITION STRIP	SCHLUTER	RENO-U	CLEAR SATIN ANODIZED ALUMINUM	-	-	

GENERAL ROOM FINISH SCHEDULE NOTES

- REFER TO FINISH PLAN AND INTERIOR ELEVATIONS FOR WALL FINISHES, WALL PROTECTION, CORNER GUARDS, WINDOW TREATMENTS, FLOOR FINISH APPLICATION AND LOCATIONS
- ALL SOLID WOOD, WOOD VENEER, AND PLASTIC LAMINATE GRAIN SHALL BE VERTICALLY ORIENTED UNLESS OTHERWISE NOTED
- DOOR FRAMES, HOLLOW METAL WINDOW FRAMES TO BE PT-4 UNLESS OTHERWISE NOTED
- ALL FACES AND UNDERSIDES OF SOFFITS AND HEADERS TO BE PT-5 UNLESS OTHERWISE NOTED
- WALL EXPANSION JOINTS TO BE PT-1 UNLESS OTHERWISE NOTED
- ALL ELECTRICAL PANELS AND METAL GRILLES SHALL BE PTD TO MATCH ADJACENT WALL SURFACE UNLESS OTHERWISE NOTED
- ALL COLUMN SURROUND FINISHES TO MATCH ADJACENT WALL SURFACE UNLESS OTHERWISE NOTED
- WHERE A WALL IS INDICATED TO HAVE PARTIAL OR FULL HT WALL PROTECTION, THE ENTIRE WALL IS TO BE PTD PRIOR TO WALL PROTECTION INSTALLATION
- EXTEND ALL FINISHES BENEATH, BEHIND, AROUND ALL CASEWORK, EQUIPMENT, SIGNAGE, ETC
- ALL WINDOW SILLS TO BE SSF-2
- ALL SST SINKS, RE- MEP
- SUBMIT SAMPLES OF ALL FINISHES TO ARCHITECT FOR REVIEW PRIOR TO THE ORDERING OF MATERIAL
- NO IRREGULARITIES OR IMPERFECTIONS SHALL BE PRESENT IN ANY OF THE MATERIAL BEING INSTALLED. IF SUCH ITEMS ARE IDENTIFIED DURING APPLICATION, WORK SHALL BE STOPPED AND THE ARCHITECT NOTIFIED
- PROVIDE ALL MAINTENANCE MANUALS AND WARRANTY INFORMATION FOR EACH FINISH MATERIAL TO OWNER AT COMPLETION OF THE PROJECT.
- FURNISH ALL LABOR, MATERIALS, AND EQUIPMENT NECESSARY TO COMPLETE WORK OF FINISH APPLICATIONS
- ALL FINISHES SHALL BE INSTALLED AND MAINTAINED PER MANUFACTURER'S RECOMMENDATION AND INDUSTRY STANDARDS
- THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR EXAMINING AND CONFIRMING ALL SUBSTRATE CONDITIONS WHERE NEW MATERIALS ARE APPLIED. SUBSTRATE SHALL BE SMOOTH, FREE OF DEFECTS AND SHALL CONFORM TO THE REQUIREMENTS OF THE FINISHED MATERIAL MANUFACTURERS RECOMMENDATIONS
- ALL MATERIAL TO COMPLY WITH FLOOR CLASSIFICATION EITHER CLASS (1) ONE OR CLASS A DEPENDING ON GOVERNING CODE IN EFFECT
- SMOKE DEVELOPMENT RATING < 450 FOR ALL FINISHES

SPECIFIC ROOM FINISH SCHEDULE NOTES

- REFER TO TYPICAL WALL TILE PATTERN ELEVATIONS ON A4.2
- FACE OF SOFFIT TO BE THE SAME PAINT COLOR AS ADJACENT WALL UNDERSIDE OF SOFFIT TO BE PT-9
- FACE OF SOFFIT TO BE THE SAME PAINT COLOR AS ADJACENT WALL UNDERSIDE OF SOFFIT TO BE PT-2
- PROVIDE HOLD-DOWN CLIPS FOR VESTIBULE CEILING

PULMONARY CLINIC - PHASE 1
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
20 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

Date 8/15/22
Job Number 3-22015
Drawn By KDS
Checked By ABD

Revision
Number Date Description

FINISH FLOOR PLAN LEGEND

WALL TREATMENT

↻

FLOOR TRANSITION

└─┘

CORNER GUARD

→


FLOOR FINISH DIRECTION

FOR ALL FLOORING TRANSITIONS, REFER TO TYPICAL TRANSITION DETAILS ON SHEET A4.2, UNLESS OTHERWISE NOTED ON THIS PLAN.

RE: ROOM FINISH SCHEDULE AND INTERIOR ELEVATIONS FOR WALL PROTECTION LOCATIONS


A1 FINISH PLAN - PHASE 1
1/4" = 1'-0"

A4.2




B6 PFT/FUTURE PROCEDURE FLEX - WEST
1/4" = 1'-0"

117
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1
SINKS IS-1




A6 TYP. VITALS - NORTH
1/4" = 1'-0"

100A
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1
SINKS




B5 SOILED - NORTH
1/4" = 1'-0"

109
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1
SINKS IS-1




A5 RECEPTION - SOUTH A
1/4" = 1'-0"

101
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1 / QTZ-1
SINKS




B4 CLEAN/MEDS - SOUTH
1/4" = 1'-0"

108
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1
SINKS IS-1




A4 RECEPTION - EAST B
1/4" = 1'-0"

101
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1 / QTZ-1
SINKS




B3 EXAM/SLEEP TECH - WEST
1/4" = 1'-0"

112
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1
SINKS IS-1




A3 RECEPTION - WEST
1/4" = 1'-0"

101
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1 / QTZ-1
SINKS




B2 TYP EXAM - WEST
1/4" = 1'-0"

105
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1
SINKS IS-1




A2 RECEPTION - SOUTH
1/4" = 1'-0"

101
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1 / QTZ-1
SINKS



B1 EXAM VARIANTS - WEST
1/4" = 1'-0"

104
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1
SINKS IS-1



A1 TEMP WAITING - EAST
1/4" = 1'-0"

100
BASE CABINETS PLAM-1
WALL CABINETS PLAM-1
COUNTERTOPS SSF-1
SINKS

PULMONARY CLINIC - PHASE 1
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
20 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

Date 8/15/22
Job Number 3-22015
Drawn By KDS
Checked By ABD

Revision
Number Date Description

A7.2

© 2022 ACI/BOLAND, Inc.
INTERIOR ELEVATIONS


RELEASED FOR CONSTRUCTION
NOT TO BE REPRODUCED
WITHOUT THE WRITTEN CONSENT OF THE ARCHITECT

8/15/2022 11:02:23 AM
Samuel K. Beckman - Architect
License - Missouri WA-2011012130


ACI
BOLAND
ARCHITECTS

ACI/Boland, Inc.
Kansas City | St. Louis
1710 Wyandotte
Kansas City, MO 64108
T: 816.763.9600


Licensee's Certificate of Authority Number:
Missouri: #000958



E5 TYPICAL DOUBLE VINYL CORNER GUARD
3" = 1'-0"




E4 TYPICAL SINGLE VINYL CORNER GUARD



E3 SECTION DETAIL AT SOLID SURFACE BACKSPLASH
3" = 1'-0"

GENERAL CASEWORK NOTES


1. GENERAL CASEWORK ELEMENTS APPLY TO ALL INTERIOR ELEVATIONS.
2. PROVIDE 3 MM PVC EDGE BANDING ON COUNTERTOP EDGE AND 3MM VINYL EDGING ON DRAWER, AND DOOR EDGES UNLESS NOTED OTHERWISE. EDGE BANDING TO MATCH ADJACENT P. LAM SURFACE.
3. ALL EXPOSED FACES AND SHELVES TO BE WRAPPED WITH P. LAM. UNLESS NOTED OTHERWISE.
4. ALL INTERIOR SURFACES TO BE WHITE MELAMINE U.N.O.
5. PROVIDE WOOD BLOCKING AT 12" HIGH X 16 GA. CONTINUOUS SHEET METAL BRIDGING IN WALL AS REQUIRED FOR ADEQUATE SUPPORT OF ALL CASEWORK.
6. WALL BASE TO BE INSTALLED ON ALL CASEWORK UNLESS NOTED OTHERWISE. REFER TO FINISH SCHEDULE FOR TYPE.
7. "F" INDICATES FILLER PANEL. 1-1/2" MIN.
8. "P" INDICATES END PANEL. 1-1/2" MIN.
9. PROVIDE FINISHED ENDS AT ALL EXPOSED ENDS OF CASEWORK.
10. ALL ELECTRICAL, MECHANICAL, AND PLUMBING ITEMS SHOWN IN ELEVATION ARE FOR REFERENCE AND LOCATION ONLY. REFER TO MEP DRAWINGS FOR SIZES, TYPES AND QUANTITIES.
11. ALL SOFFITS ABOVE CASEWORK TO BE P. LAM. UNLESS NOTED OTHERWISE.




TYP. CABINET NOTES:

1. PROVIDE PLAM FILLER WHERE CABINETS BUTT UP TO WALLS.
2. ALL COUNTERTOPS HAVE A 4" BACKSPLASH (MATERIAL TO MATCH COUNTERTOP) AND OUTSIDE CORNERS HAVE 1 1/2" RADIUS EXCEPT WHERE NOTED OTHERWISE.
3. CASEWORK MFR. TO SUPPLY (2" - 2") GROMMETS PER KNEESPACE. GROMMETS TO BE INSTALLED IN FIELD AS DIRECTED BY OWNER. COLOR TO BE SELECTED BY ARCHITECT.
4. PLASTIC LAMINATE COUNTERTOP EDGES SHALL BE 3 MM PLASTIC. COLOR AS SELECTED BY ARCHITECT)


D1 CASEWORK ISOMETRIC
1 1/2" = 1'-0"




A6 CASEWORK SECTION
1 1/2" = 1'-0"




A5 DETAIL AT RECEPTION DESK/NURSE STATION
1 1/2" = 1'-0"





A3 DETAIL AT RECEPTION WINDOW WALL
1 1/2" = 1'-0"




B2 WALL-MOUNTED MICROWAVE SHELF
1 1/2" = 1'-0"



A2 DETAIL AT SINK BASE CABINET
1 1/2" = 1'-0"



A1 CASEWORK SECTION
1 1/2" = 1'-0"



PULMONARY CLINIC - PHASE 1
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
20 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

Date	8/15/22
Job Number	3-22015
Drawn By	Author
Checked By	Checker

Revision		
Number	Date	Description

A7.3

© 2022 ACI/BOLAND, Inc

INTERIOR DETAILS




BranchPattern

www.branchpattern.com

BETTER BUILT ENVIRONMENTS

PROJECT NAME:

PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: AE

Drawn By: AE

Reviewed By: JB

Project No: 1203001

Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title: ELECTRICAL NOTES

Sheet No.: E0.2

ELECTRICAL REMODEL NOTES	ELECTRICAL LIGHTING NOTES	ELECTRICAL GENERAL NOTES
<div>1. REMOVE BOLD ITEMS INDICATED ON PLAN. ITEMS INDICATED WITH (E) ARE EXISTING TO REMAIN. MAINTAIN CIRCUITING TO EXISTING ITEMS OR RECIRCUIT AS INDICATED ON PLANS.</div> <div>2. EXISTING INFORMATION INDICATED ON THE DRAWINGS HAS BEEN TAKEN FROM OWNER FURNISHED DRAWINGS AND / OR LIMITED FIELD OBSERVATIONS. THE ELECTRICAL CONTRACTOR SHALL FIELD VERIFY EXISTING CONDITIONS PRIOR TO BIDDING AND PROVIDE REMOVAL AND/OR RELOCATION OF EXISTING CONDUITS, CONDUCTORS, DEVICES, FIXTURES, OR OTHER EQUIPMENT AS INDICATED ON THE PLANS OR AS REQUIRED TO COORDINATE WITH THE NEW WORK.</div> <div>3. REFER TO ARCHITECTURAL DEMOLITION DRAWINGS FOR LOCATION AND EXTENT OF DEMOLITION REQUIRED. PROVIDE ELECTRICAL DEMOLITION REQUIRED. CONTRACTOR SHALL VISIT SITE PRIOR TO BID TO DETERMINE EXTENT OF WORK INVOLVED. PROVIDE LABOR AND MATERIALS AS REQUIRED TO MAINTAIN AND/OR RESTORE CONTINUITY OF SERVICE TO EXISTING CIRCUITS.</div> <div>4. REMOVE EXISTING UNUSED CONDUIT, WIRE, CABLE, JUNCTION BOXES, DEVICES, LIGHTS, FIRE ALARM COMPONENTS, AND ELECTRICAL APPURTENANCES. COMPLETE WITH ASSOCIATED CIRCUITING TO SOURCE. WHERE IT IS NOT FEASIBLE TO REMOVE THE ABOVE, DEVICE AND WIRE SHALL BE REMOVED, RACEWAY ABANDONED, AND BLANK COVER PLATES PROVIDED.</div> <div>5. SYSTEM OUTAGES SHALL BE PERMITTED ONLY AT TIMES APPROVED BY OWNER. IN WRITING. WORK WHICH COULD RESULT IN AN ACCIDENTAL OUTAGE (BEYOND BRANCH CIRCUITS) SHALL BE PERFORMED WITH THE OWNER'S MAINTENANCE PERSONNEL ADVISED OF SUCH WORK.</div> <div>6. WHERE THE REUSE OF EXISTING RACEWAYS, CONDUCTORS, DEVICES, ETC. IS PERMISSIBLE. VERIFY THE CONDUCTORS ARE CONTINUOUS AND MODIFICATIONS IN THIS PHASE OF WORK WILL NOT RENDER EXISTING DEVICES OR JUNCTION BOXES INACCESSIBLE. RELOCATE JUNCTION BOXES OR DEVICES WHICH ARE MADE INACCESSIBLE FROM WORK PERFORMED. RESUPPORT EXISTING ITEMS AS REQUIRED BY CODE.</div> <div>7. CLEAN AND RELAMP EXISTING FIXTURES WHICH ARE REMOVED AND REINSTALLED.</div> <div>8. THE OWNER SHALL HAVE FIRST SALVAGE RIGHTS TO ITEMS REMOVED AS PART OF DEMOLITION. REMOVE AND PROPERLY DISPOSE OF DEMOLISHED ITEMS.</div> <div>9. PROTECT STRUCTURE AND OWNER EQUIPMENT FROM DAMAGE. IMMEDIATELY REPLACE OR REPAIR, TO ORIGINAL CONDITION, DAMAGE CAUSED BY THE CONTRACTOR WHETHER EQUIPMENT APPEARS TO BE CURRENTLY IN USE OR NOT, UNLESS WRITTEN AUTHORIZATION FROM THE OWNER INDICATES OTHERWISE. PREPARE LISTING OF ALL EXISTING DAMAGED ITEMS AND SUBMIT TO OWNER PRIOR TO BEGINNING WORK.</div> <div>10. FIELD LOCATE EXISTING UNDERGROUND PUBLIC AND OWNER UTILITIES AND BUILDING GROUNDING / LIGHTNING PROTECTION SYSTEMS PRIOR TO ANY EXCAVATION. REPLACE OR REPAIR DAMAGED UTILITIES AND GROUNDING / LIGHTNING PROTECTION SYSTEMS TO ORIGINAL CONDITION.</div> <div>11. IF SUSPECTED HAZARDOUS MATERIALS ARE ENCOUNTERED IN ANY EXISTING BUILDING COMPONENTS THAT WILL BE DISTURBED DURING THE PROJECT, IMMEDIATELY NOTIFY OWNER/ARCHITECT PRIOR TO DISRUPTION OF THE MATERIAL.</div>	<div>1. COORDINATE THE LOCATION AND MOUNTING HEIGHT OF LUMINAIRES AND DEVICES WITH ARCHITECTURAL DRAWINGS. WHERE LUMINAIRES OR DEVICES ARE NOT SPECIFICALLY INDICATED, COORDINATE LOCATIONS AND MOUNTING HEIGHTS WITH ARCHITECT PRIOR TO ROUGH-IN.</div> <div>2. CONNECT EMERGENCY LIGHTING AND EXIT SIGNS AHEAD OF LOCAL SWITCHING.</div> <div>3. COORDINATE PENDANT HUNG INDUSTRIAL STRIP(S) IN UNFINISHED AREAS WITH PIPING, DUCTWORK, EQUIPMENT, CABLE TRAY, ETC. TO AVOID CONFLICTS. MAKE MINOR ADJUSTMENTS TO LUMINAIRE LOCATIONS AS REQUIRED.</div> <div>4. RECESSED LIGHT FIXTURES INSTALLED IN GYP. BOARD OR PLASTER CEILINGS SHALL HAVE PLASTER FRAMES INSTALLED PRIOR TO CEILING MATERIAL.</div> <div>5. FIXTURES RECESSED IN "T-BAR" CEILING SHALL BE SUPPORTED INDEPENDENTLY OF CEILING SYSTEM WITH HANGER WIRES UP TO STRUCTURE. SECURE HANGER WIRES TO CORNERS OF FIXTURE. CLIP FIXTURE TO GRID ON TWO SIDES WITH FACTORY-FURNISHED CLIPS. FINAL ELECTRICAL CONNECTION TO FIXTURE SHALL BE MADE WITH FLEXIBLE CONDUIT OR UL LISTED ASSEMBLY.</div> <div>6. VERIFY TRIM COMPATIBILITY WITH CEILING TYPE INDICATED IN ARCHITECTURAL REFLECTED CEILING PLAN PRIOR TO ORDERING LUMINAIRES. MODIFY TRIMS AS REQUIRED TO WORK WITH SPECIFIED CEILINGS.</div> <div>7. LOSS OF UTILITY POWER SHALL ENERGIZE EMERGENCY EGRESS LIGHTING. COMPONENTS OF SYSTEM SHALL BE UL LISTED FOR EMERGENCY TRANSFER.</div> <div>8. PROVIDE COSTS FOR ADDING 3 ADDITIONAL EXIT SIGNS PER LEVEL AS REQUIRED BY THE FIRE MARSHAL AT THE TIME OF FINAL INSPECTION. LOCATE AS REQUIRED BY FIRE MARSHAL.</div> <div>9. PROVIDE OCCUPANCY/VACANCY SENSOR RELAYS AND POWER PACKS FOR LIGHTING CONTROL FUNCTION INDICATED. PROVIDE 1 SET OF AUXILIARY CONTACTS IN LOW VOLTAGE SENSORS FOR HVAC CONTROLS.</div> <div>10. SET VACANCY/OCCUPANCY SENSORS TO 15 MINUTE TIME DELAY UNLESS NOTED OTHERWISE. DO NOT EXCEED MAXIMUM CODE REQUIRED TIME DELAY.</div> <div>11. CONNECT OCCUPANCY SENSOR(S) AHEAD OF LOCAL LIGHTING CONTROLS.</div> <div>12. WHERE MULTIPLE VACANCY/OCCUPANCY SENSORS ARE LOCATED IN THE SAME ROOM OR SPACE, CONNECT SO EACH SENSOR CONTROLS ALL LIGHTING (EXCEPT NON-SWITCHED EMERGENCY LIGHTING) WITHIN THAT ROOM OR SPACE.</div> <div>13. PROVIDE LOW VOLTAGE VACANCY/OCCUPANCY SENSORS WHERE MULTIPLE SENSORS ARE USED TO CONTROL THE SAME LUMINAIRE(S).</div> <div>14. PROVIDE WALL MOUNTED VACANCY/OCCUPANCY SENSOR TO MATCH THE SPECIFIED DEVICE COLOR.</div> <div>15. INSTALL WALL MOUNTED OCCUPANCY SENSOR IN VACANCY MODE.</div> <div>16. VACANCY/OCCUPANCY SENSOR VENDOR SHALL PROVIDE LAYOUT OF DEVICES AND PROPER DEVICE SELECTION FOR COMPLETE COVERAGE OF AREAS. SUBMIT SHOP DRAWINGS WHICH INDICATE LOCATIONS AND DEVICE TYPE AT EACH LOCATION. PROVIDE ADDITIONAL DEVICES AS REQUIRED. CONTRACTOR SHALL ADJUST DEVICES AS REQUIRED SO THE COVERAGE AREA CORRESPONDS TO THE AREA CONTROLLED AND SHALL RETURN TO SITE AS REQUIRED WITHIN 1 YEAR OF FINAL COMPLETION TO READJUST OR REPLACE ANY DEVICE WHICH IS NOT PROPERLY FUNCTIONING. THE LOCATION OF THE VACANCY/OCCUPANCY SENSOR(S) ON THESE DRAWING ARE DIAGRAMMATIC.</div> <div>17. DO NOT LOCATE VACANCY/OCCUPANCY SENSORS WITHIN 3' OF AN HVAC SUPPLY DEVICE.</div> <div>18. CEILING MOUNTED VACANCY/OCCUPANCY SENSORS SHALL BE DUAL TECHNOLOGY TYPE.</div>	<div>1. DO NOT SCALE DRAWINGS. VERIFY DIMENSIONS ON ARCHITECTURAL DRAWINGS AND IN FIELD PRIOR TO COMMENCEMENT OF WORK.</div> <div>2. REVIEW ARCHITECTURAL, STRUCTURAL, MECHANICAL, AND OTHER DRAWINGS FOR ADDITIONAL SCOPE REQUIREMENTS PRIOR TO BID.</div> <div>3. WORK SHALL BE PERFORMED IN A WORKMANLIKE MANNER TO THE SATISFACTION OF THE ARCHITECT/ENGINEER.</div> <div>4. WORK, MATERIALS, AND EQUIPMENT SHALL CONFORM TO THE CURRENT ADOPTED EDITIONS OF LOCAL, STATE, AND NATIONAL CODES AND STANDARDS.</div> <div>5. OBTAIN PERMITS AND INSPECTIONS REQUIRED.</div> <div>6. FINAL CONNECTIONS TO EQUIPMENT SHALL BE IN ACCORDANCE WITH MANUFACTURER'S APPROVED WIRING DIAGRAMS, DETAILS, AND INSTRUCTIONS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO PROVIDE MATERIALS AND EQUIPMENT COMPATIBLE WITH EQUIPMENT SUPPLIED.</div> <div>7. CONTRACTOR SHALL REPLACE EQUIPMENT WHICH IS DAMAGED DUE TO INCORRECT FIELD WIRING PROVIDED UNDER THIS CONTRACT.</div> <div>8. CONTRACTOR'S FAILURE TO ORDER OR RELEASE ORDER FOR MATERIALS AND/OR EQUIPMENT IN A TIMELY MANNER WILL NOT BE ACCEPTED AS A REASON TO SUBSTITUTE ALTERNATE MATERIALS, EQUIPMENT, OR INSTALLATION METHODS.</div> <div>9. SYSTEMS SHALL BE COMPLETE, AND READY FOR CONTINUOUS OPERATION.</div> <div>10. DEVICE BOXES SHALL BE MINIMUM 4" SQUARE.</div> <div>11. PROVIDE NEW UPDATED TYPED PANELBOARD DIRECTORIES FOR PANELS MODIFIED OR INSTALLED AS A PART OF THIS PROJECT.</div> <div>12. CONDUITS PENETRATING THROUGH ROOF SHALL BE APPROVED BY OWNER'S ROOFING CONTRACTOR. INSTALLATION SHALL BE WATERTIGHT AND PERFORMED BY OWNER'S ROOFING CONTRACTOR AT ELECTRICAL CONTRACTOR'S EXPENSE.</div> <div>13. FINAL CONNECTIONS TO MOTORS, TRANSFORMERS, AND OTHER VIBRATING EQUIPMENT SHALL BE WITH FLEXIBLE CONDUIT AND APPROVED FITTINGS THAT DO NOT REDUCE THE USABLE INTERNAL DIAMETER OF THE CONDUIT. REFERENCE SPECIFICATIONS FOR SPECIFIC PRODUCTS. DO NOT SECURE CONDUITS, DISCONNECTS, OR DEVICES TO DUCTWORK OR MECHANICAL EQUIPMENT.</div> <div>14. WHERE PANELS ARE INSTALLED FLUSH WITH WALLS, EMPTY CONDUITS SHALL BE EXTENDED FROM THE PANEL TO AN ACCESSIBLE SPACE ABOVE OR BELOW. A MINIMUM OF ONE 3/4" CONDUIT SHALL BE INSTALLED FOR EVERY THREE SINGLE POLE SPARE CIRCUIT BREAKERS OR SPACES, OR FRACTION THEREOF, BUT NOT LESS THAN TWO CONDUITS.</div> <div>15. ELECTRICAL SYSTEMS COMPONENTS SHALL BE LISTED OR LABELED BY UL OR OTHER RECOGNIZED TESTING FACILITY.</div> <div>16. PROVIDE AN INSULATED GROUND CONDUCTOR WITH EACH LINE VOLTAGE CIRCUIT.</div> <div>17. PROVIDE A DEDICATED NEUTRAL CONDUCTOR FOR EACH BRANCH CIRCUIT REQUIRING A NEUTRAL CONDUCTOR. PROVIDE MULTI-POLE BREAKERS FOR EACH MULTI-WIRE BRANCH CIRCUIT SERVING EQUIPMENT OR FURNITURE.</div> <div>18. REFERENCE DIVISION 22 AND 23 DRAWINGS AND SPECIFICATIONS FOR LOCATION AND REQUIREMENTS OF MECHANICAL AND PLUMBING EQUIPMENT. PROVIDE SERVICE TO AND CONNECT EQUIPMENT AS REQUIRED.</div> <div>19. PROVIDE FUSES SIZED PER MANUFACTURERS RECOMMENDATIONS.</div> <div>20. COORDINATE THE EXACT MOUNTING LOCATIONS OF WALL AND FLOOR DEVICES WITH ARCHITECTURAL AND EQUIPMENT PLANS AND ELEVATIONS.</div> <div>21. REFER TO TECHNOLOGY DRAWINGS AND SPECIFICATIONS FOR LOW-VOLTAGE SYSTEMS INFRASTRUCTURE REQUIREMENTS. ELECTRICAL CONTRACTOR SHALL PROVIDE ALL CONDUITS AND BACKBOXES REQUIRED FOR LOW-VOLTAGE SYSTEMS.</div> <div>22. RACEWAYS SHALL NOT BE ROUTED HORIZONTALLY ABOVE ROOF. RACEWAY SHALL PENETRATE ROOF AT LOCATION OF EQUIPMENT SERVED.</div> <div>23. FIELD LOCATE EXISTING UNDERGROUND PUBLIC AND OWNER UTILITIES AND BUILDING GROUNDING/LIGHTNING PROTECTION SYSTEMS PRIOR TO ANY EXCAVATION. REPLACE OR REPAIR DAMAGED UTILITIES AND GROUNDING/LIGHTNING PROTECTION SYSTEMS TO ORIGINAL CONDITION.</div> <div>24. PROVIDE FAN RATED BOXES CAPABLE OF SUPPORTING 70 POUNDS FOR BACK BOXES USED TO SUPPORT CEILING FANS.</div>

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: AE

Drawn By: AE

Reviewed By: JB

Project No: 1203001

Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title:

PHASE 1 - FIRST FLOOR
POWER PLAN

Sheet No.:

E1.1

GENERAL NOTES (THIS SHEET)

1. REFER TO SHEET E0.1 & E0.2 FOR ELECTRICAL LEGEND AND ADDITIONAL GENERAL NOTES.
2. REFERENCE ARCHITECTURAL DRAWINGS FOR PHASING AND AREAS OF RENOVATION.
3. EXISTING CONDITIONS SHOWN WERE TAKEN FROM FACILITY PROVIDED AS-BUILT DRAWINGS AND ON-SITE FIELD OBSERVATIONS. EACH CONTRACTOR SHALL VERIFY EXISTING CONDITIONS PRIOR TO PERFORMING WORK.


KEY NOTES (X) (THIS SHEET)


1. CONNECT EXISTING AUTOMATIC DOOR OPERATOR TO NEW WAVE OPERATORS BY DIVISION 8. VERIFY FINAL DEVICE LOCATION WITH ARCHITECT PRIOR TO ROUGH-IN.
2. RECEPTACLES MOUNTED IN BUILT-UP CASEWORK. CONDUIT AND WIRING SHALL BE CONCEALED IN CASEWORK. WITH HOMERUN STUBBED UP FROM BELOW. CUT AND PATCH FLOOR SLAB AS REQUIRED.
3. PROVIDE POWER POLE FOR RECEPTACLES SERVING RECONFIGURED PHYSICAL THERAPY AREA. BASIS OF DESIGN IS WIREMOLD 30TP-2 SERIES OR EQUIVALENT. PROVIDE TWO (2) DUPLEX RECEPTACLES, WHITE FINISH POLE AND WIRING DEVICES. PROVIDE CIRCUITING AS SHOWN ON PLANS. COORDINATE FINAL LOCATIONS WITH ARCHITECT AND FFE PRIOR TO ROUGH-IN.
4. J-BOX BOUNDED TO STRUCTURE ABOVE ACCESSIBLE CEILING FOR CONNECTION TO VAV BOX CONTROL TRANSFORMER POWER. CONNECT TO 120V CONTROL TRANSFORMER AT VAV BOX LOCATIONS AND PROVIDE LOCAL DISCONNECT AS REQUIRED. CONNECT NO MORE THAN TEN (10) VAV BOXES PER CIRCUIT. COORDINATE WITH MECHANICAL AND CONTROLS VENDORS.
5. CONNECTION TO AUTOMATIC DOOR OPERATOR. PROVIDE TOGGLE SWITCH DISCONNECT ABOVE ACCESSIBLE CEILING ADJACENT TO EQUIPMENT SERVED. COORDINATE ADDITIONAL REQUIREMENTS WITH DOOR HARDWARE SCHEDULE PRIOR TO ROUGH-IN. CONNECT TO WAVE OPERATORS AS REQUIRED.
6. BACK BOX FOR WAVE OPERATORS BY DIVISION 8. CONNECT TO AUTOMATIC DOOR OPERATOR AS REQUIRED. VERIFY FINAL DEVICE LOCATION WITH ARCHITECT PRIOR TO ROUGH-IN.

ALTERATION SHADING LEGEND



AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.





www.branchpattern.com
BETTER BUILT ENVIRONMENTS

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawings and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: AE
Drawn By: AE
Reviewed By: JB
Project No: 1203001
Date: 08/15/22
Submittal Level: 100% CDs
Sheet Title:

PHASE 1 - FIRST FLOOR
LIGHTING PLAN

Sheet No.:
E2.1

GENERAL NOTES (THIS SHEET)

- COORDINATE THE LOCATION AND MOUNTING HEIGHT OF LUMINAIRES AND DEVICES WITH ARCHITECTURAL DRAWINGS. WHERE LUMINAIRES OR DEVICES ARE NOT SPECIFICALLY INDICATED, COORDINATE LOCATIONS AND MOUNTING HEIGHTS WITH ARCHITECT PRIOR TO ROUGH-IN.
- CONNECT EMERGENCY LIGHTING AND EXIT SIGNS AHEAD OF LOCAL SWITCHING.
- COORDINATE PENDANT HUNG INDUSTRIAL STRIP(S) IN UNFINISHED AREAS WITH PIPING, DUCTWORK, EQUIPMENT, CABLE TRAY, ETC. TO AVOID CONFLICTS. MAKE MINOR ADJUSTMENTS TO LUMINAIRE LOCATIONS AS REQUIRED.
- RECESSED LIGHT FIXTURES INSTALLED IN GYP. BOARD OR PLASTER CEILINGS SHALL HAVE PLASTER FRAMES INSTALLED PRIOR TO CEILING MATERIAL.
- FIXTURES RECESSED IN "T-BAR" CEILING SHALL BE SUPPORTED INDEPENDENTLY OF CEILING SYSTEM WITH HANGER WIRES UP TO STRUCTURE. SECURE HANGER WIRES TO CORNERS OF FIXTURE. CLIP FIXTURE TO GRID ON TWO SIDES WITH FACTORY-FURNISHED CLIPS. FINAL ELECTRICAL CONNECTION TO FIXTURE SHALL BE MADE WITH FLEXIBLE CONDUIT OR UL LISTED ASSEMBLY.
- VERIFY TRIM COMPATIBILITY WITH CEILING TYPE INDICATED IN ARCHITECTURAL REFLECTED CEILING PLAN PRIOR TO ORDERING LUMINAIRES. MODIFY TRIMS AS REQUIRED TO WORK WITH SPECIFIED CEILINGS.
- LOSS OF UTILITY POWER SHALL ENERGIZE EMERGENCY EGRESS LIGHTING. COMPONENTS OF SYSTEM SHALL BE UL LISTED FOR EMERGENCY TRANSFER.
- PROVIDE COSTS FOR ADDING 3 ADDITIONAL EXIT SIGNS PER LEVEL AS REQUIRED BY THE FIRE MARSHAL AT THE TIME OF FINAL INSPECTION. LOCATE AS REQUIRED BY FIRE MARSHAL.

KEY NOTES (THIS SHEET)

- REINSTALL EXISTING LIGHT FIXTURE IN NEW CEILING. CONNECT TO EXISTING CIRCUIT AND CONTROLS. RE: SHEET ED1.0.
- PROVIDE NEW 20A/1P BREAKER FOR EACH CIRCUIT SHOWN IN THEIR RESPECTIVE EXISTING PANELBOARD.

LIGHTING

- CIRCUIT ZONE BOUNDARY
- CONTROL ZONE CIRCUITING/BOUNDARY. PROVIDE CONTROL ZONE FOR EACH ROOM UNLESS INDICATED OTHERWISE. PROVIDE POWER PACK FOR EACH CONTROL ZONE.
- REFERENCE LIGHTING CONTROLS SCHEDULE FOR CONTROL ZONE TYPE DESCRIPTIONS
- | |
|-------------------------|
| NORMAL POWER CIRCUIT |
| EMERGENCY POWER CIRCUIT |

ALTERATION SHADING LEGEND

- AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1 PHASE 1 - FIRST FLOOR LIGHTING PLAN
SCALE: 1/8" = 1'-0"

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: AE
Drawn By: AE
Reviewed By: JB
Project No: 1203001
Date: 08/15/22
Submittal Level: 100% CDs
Sheet Title:

PHASE 1 - FIRST FLOOR
FIRE ALARM PLAN

Sheet No.:
E3.1


GENERAL NOTES (THIS SHEET)


- REFER TO SHEET E001 & E002 FOR SYMBOL LEGEND AND ADDITIONAL GENERAL NOTES.
- PROVIDE FIRE ALARM SYSTEM DEVICES, CONDUIT, WIRES AND CABLES AS DIRECTED BY EQUIPMENT MANUFACTURER. MATERIALS, EQUIPMENT, AND WORKMANSHIP SHALL MEET ADOPTED CODES. THE SYSTEM SHALL BE COMPLETE AND OPERATIONAL IN EVERY RESPECT. SHOP DRAWINGS SHALL INCLUDE A SINGLE LINE DIAGRAM THAT INDICATES DEVICES, CONDUIT, WIRE, CABLE SIZES, AND EQUIPMENT TO BE USED. SHOP DRAWINGS SHALL BE STAMPED AND SIGNED BY A REGISTERED ENGINEER PROVIDED BY THE FIRE ALARM VENDOR. SYSTEM CALIBRATION AND TESTING SHALL BE BY FACTORY CERTIFIED TECHNICIAN.
- PROVIDE ALL REQUIRED EQUIPMENT FOR A FULLY FUNCTIONING DIGITAL ADDRESSABLE VOICE EVACUATION SYSTEM. TO INCLUDE AS NEEDED: POWER SUPPLIES FOR NACS, AMPLIFIERS FOR SPEAKER CIRCUITS, ANNUNCIATORS, AND FIRE ALARM PANELS.
- PROVIDE ALL NECESSARY CONNECTIONS TO POWERED DOORS TO ALLOW FREE EGRESS UPON ALARM CONDITIONS AS REQUIRED.

KEY NOTES (THIS SHEET)

- REINSTALL EXISTING FIRE ALARM DEVICE SALVAGED FROM DEMOLITION PHASE. CONNECT TO EXISTING WIRING AS REQUIRED TO RESTORE ORIGINAL FUNCTIONALITY. UPDATE DEVICE ADDRESSES AS REQUIRED.


ALTERATION SHADING LEGEND

 AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.




1 PHASE 1 - FIRST FLOOR FIRE ALARM PLAN
SCALE: 1/8" = 1'-0"





www.branchpattern.com
BETTER BUILT ENVIRONMENTS

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date


Designed By: AE
Drawn By: AE
Reviewed By: JB
Project No: 1203001
Date: 08/15/22
Submittal Level: 100% CDs

Sheet Title:
ELECTRICAL DETAILS


Sheet No.:
E4.0

FIRE ALARM GENERAL NOTES


1. PROVIDE FIRE ALARM SYSTEM EQUIPMENT THAT IS INDICATED ON THE RISER AND IN PLANS. REFER TO PLANS FOR ADDITIONAL LOCATIONS AND QUANTITIES.
2. WIRING SHALL BE IN CONDUIT.
3. WORK SHALL BE PERFORMED IN A WORKMANLIKE MANNER TO THE SATISFACTION OF THE ARCHITECT/ENGINEER.
4. WORK, MATERIALS AND EQUIPMENT SHALL CONFORM TO THE LATEST EDITIONS OF LOCAL AND STATE CODES AND ORDINANCES.
5. PROVIDE PERMITS AND INSPECTIONS REQUIRED.
6. GUARANTEE THE INSTALLATION AGAINST DEFECTS IN MATERIALS AND WORKMANSHIP WHICH MAY OCCUR UNDER NORMAL USAGE FOR A PERIOD OF ONE YEAR AFTER OWNER'S ACCEPTANCE. DEFECTS SHALL BE PROMPTLY REMEDIED WITHOUT COST TO THE OWNER.
7. PROVIDE RECORD DRAWINGS TO ARCHITECT/ENGINEER. DRAWINGS SHALL INCLUDE ALL ADDENDUM ITEMS, CHANGE ORDERS, ALTERATIONS REROUTING, ETC.
8. SYSTEMS SHALL BE TESTED FOR PROPER OPERATION. IF TESTS INDICATE THAT WORK IS DEFECTIVE, CONTRACTOR SHALL MAKE CORRECTIONS NECESSARY AT NO COST TO OWNER.
9. PROVIDE DEVICES, CONDUIT, WIRES, AND CABLE AS DIRECTED BY THE EQUIPMENT MANUFACTURER. MATERIALS, AND WORKMANSHIP SHALL MEET PREVAILING CODES. THE SYSTEM SHALL BE COMPLETE AND OPERABLE IN EVERY RESPECT. SUBMIT SINGLE LINE DIAGRAM OF SYSTEM WITH SHOP DRAWINGS. THIS SINGLE LINE DIAGRAM SHALL SHOW DEVICES, CONDUIT, WIRE, CABLE SIZES, AND EQUIPMENT TO BE USED, AND SHALL BE STAMPED AND SIGNED BY STATE OR LOCAL FIRE DEPARTMENT AS APPLICABLE. SYSTEM CALIBRATION AND TESTING SHALL BE BY A FACTORY CERTIFIED TECHNICIAN.
10. SYSTEM SUPPLIER SHALL PROVIDE ALARM DEVICES WITH THE APPROPRIATE CANDELA AND DECIBEL RATINGS TO COMPLY WITH ADA REQUIREMENTS. PROVIDE ADDITIONAL DEVICES AS REQUIRED.
11. PROVIDE ADDITIONAL NOTIFICATION ALARM CIRCUIT POWER SUPPLIES AS REQUIRED. DOCUMENT POWER SUPPLY LOCATIONS AND PROTECT WITH A NEARBY SMOKE DETECTOR.
12. COORDINATE WITH SPRINKLER SYSTEM(S). PROVIDE TAMPER, FLOW, CONTROL, AND MONITOR DEVICES AS REQUIRED.
13. ANNUNCIATOR DISPLAY SHALL INCLUDE DESCRIPTIVE ROOM NAME AND LOCATION APPROVED BY ENGINEER / OWNER.
14. AUDIBLE DEVICE LOUDNESS SHALL BE ADJUSTABLE.
15. DOOR HOLD OPENS SHALL HAVE TIME OF DAY FUNCTION. SOME DOORS ARE TO BE RELEASED (CLOSED) IN THE EVENING AT A PROGRAMMABLE TIME.



1 FIRE ALARM RISER
SCALE: NONE



2 LAY-IN FIXTURE MOUNTING
SCALE: NONE



4 ELECTRICAL ONE-LINE DIAGRAM - FOR REFERENCE ONLY
SCALE: NONE

SAINT LUKE'S EAST HOSPITAL

100 NE SAINT LUKE'S BLVD.



in whole or in part without express written permission.

[illegible]

AE

AF

JB

1203001

08/15/22

100% CDs

ELECTRICAL SCHEDULES

E5.0

LUMINAIRE SCHEDULE - INTERIOR

FIXTURE TYPE	FIXTURE DESCRIPTION	MANUFACTURER	CATALOG NUMBER	SOURCE INFO					REMARKS	
				TYPE	LUMENS	COLOR	CRI	INPUT VA		VOLTAGE
A1	2' X 4' VOLUMETRIC LED RECESSED TROFFER, COLD-ROLLED STEEL HOUSING, PAINTED AFTER FABRICATION, WITH CURVED ACRYLIC CENTER DIFFUSER. 0-10V DIMMING DRIVER.	WILLIAMS	PT-24-L38/835-RA-(L32)-DIM-UNV	LED	3200 lm	3500K	80	26 VA	277 V	
A2	2' X 4' VOLUMETRIC LED RECESSED TROFFER, COLD-ROLLED STEEL HOUSING, PAINTED AFTER FABRICATION, WITH CURVED ACRYLIC CENTER DIFFUSER. 0-10V DIMMING DRIVER.	WILLIAMS	PT-24-L38/835-RA-DIM-UNV	LED	3800 lm	3500K	80	26 VA	277 V	
A3	2' X 4' VOLUMETRIC LED RECESSED TROFFER, COLD-ROLLED STEEL HOUSING, PAINTED AFTER FABRICATION, WITH CURVED ACRYLIC CENTER DIFFUSER. 0-10V DIMMING DRIVER.	WILLIAMS	PT-24-L49/835-RA-DIM-UNV	LED	4900 lm	3500K	80	38 VA	277 V	
A4	2' X 4' VOLUMETRIC LED RECESSED TROFFER, COLD-ROLLED STEEL HOUSING, PAINTED AFTER FABRICATION, WITH CURVED ACRYLIC CENTER DIFFUSER. 0-10V DIMMING DRIVER.	WILLIAMS	PT-24-L61/835-RA-DIM-UNV	LED	6100 lm	3500K	80	49 VA	277 V	
B1	2' X 2' VOLUMETRIC LED RECESSED TROFFER, COLD-ROLLED STEEL HOUSING, PAINTED AFTER FABRICATION, WITH CURVED ACRYLIC CENTER DIFFUSER.	WILLIAMS	PT-22-L26/835-RA-DRV-UNV	LED	2600 lm	3500K	80	22 VA	277 V	
D1	6" DIAMETER RECESSED LED DOWNLIGHT, ALUMINUM HOUSING AND HEAT SINK, GALVANIZED STEEL MOUNTING PAN WITH ADJUSTABLE MOUNTING ARMS, FLUSH PRISMATIC TEMPERED LENS, WIDE DISTRIBUTION, AND WHITE POWDER COAT TRIM.	WILLIAMS	6DR-TL-L 10/835-DIM-UNV-L-W-OF-WH	LED	750 lm	3500K	80	9 VA	277 V	
H1	2' X 4' FLAT LENS LED TROFFER, COLD-ROLLED STEEL HOUSING AND DOOR FRAME, PAINTED AFTER FABRICATION, WITH FROSTED ACRYLIC LENS.	WILLIAMS	50G-S24-L33/835-S-AF12125-DRV-UNV	LED	3300 lm	3500K	80	25 VA	277 V	
W1	24" WALL MOUNTED LED VANITY FIXTURE, SATIN NICKEL FINISH MOUNTING HARDWARE AND END CAPS, WITH CURVED FROSTED LENS, ADA COMPLIANT, TECH LIGHTING TO CONFIRM FINISH PRIOR TO ORDERING.	TECH LIGHTING	700BCBAS-24-S-LED927-277	LED	1000 lm	2700K	90	24 VA	277 V	
X1	CEILING MOUNT LED EXIT SIGN WITH WHITE THERMOPLASTIC HOUSING. SEE PLANS FOR MOUNTING.	WILLIAMS	EXIT-R-EM-WHT-D	LED				5 VA	277 V	

100

- a. SEE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS FOR LUMINAIRES.
- b. CONTRACTOR TO VERIFY LUMINAIRE CATALOG NUMBER AND INSTALLATION REQUIREMENTS PRIOR TO ORDERING.

LIGHTING CONTROL SCHEDULE

ZONE NAME	MANUAL CONTROL	OCCUPANCY SENSOR	VACANCY SENSOR	DAYLIGHT SENSOR	TIMECLOCK/PHOTOCELL	SENSOR MOUNTING	SENSOR TIMEOUT (MIN.)	FUNCTIONAL DESCRIPTION	REMARKS
CONFERENCE/MEETING ROOM	DIMMER / SWITCH	Yes	No	No	No	CEILING	20	LOW VOLTAGE DIMMER SWITCH FOR MANUAL ON/MANUAL OFF AND DIMMING. MAINTAIN 30FC.	
COPY/PRINT ROOM	SWITCH	No	Yes	No	No	CEILING	20	SINGLE POLE SWITCH FOR MANUAL ON/MANUAL OFF.	
CORRIDOR/LOBBY	SWITCH	Yes	No	No	No	CEILING	20	EMERGENCY LUMINAIRES SHALL AUTOMATICALLY TURN ON TO 100% UPON LOSS OF NORMAL POWER.	
JANITOR/STORAGE ROOM, LARGE	SWITCH	No	Yes	No	No	CEILING	15	SINGLE POLE SWITCH FOR MANUAL ON/MANUAL OFF.	
JANITOR/STORAGE ROOM, SMALL	SWITCH	No	Yes	No	No	WALL	15	SINGLE POLE SWITCH FOR MANUAL ON/MANUAL OFF.	
LOUNGE/BREAKROOM	SWITCH	No	Yes	No	No	WALL / CEILING	20	SINGLE POLE SWITCH FOR MANUAL ON/MANUAL OFF.	
OFFICE ROOM	DIMMER / SWITCH	No	Yes	Yes	No	CEILING	20	LOW VOLTAGE DIMMER SWITCH FOR MANUAL ON/MANUAL OFF AND DIMMING. MAINTAIN 30FC.	
RESTROOM, LARGE	NONE	Yes	No	No	No	CEILING	15		
RESTROOM, SMALL	NONE	Yes	No	No	No	WALL	15		

NOTES:

- a. OCCUPANCY SENSOR CONTROLS LUMINAIRES FOR AUTO ON/AUTO OFF.
- b. VACANCY SENSOR CONTROLS LUMINAIRES FOR MANUAL ON/OFF AND AUTO OFF AFTER TIMEOUT
- c. DAYLIGHT SENSOR CONTROLS LUMINAIRE OUTPUT WITHIN DAYLIGHTING ZONE.
- d. TIMELOCK AND PHOTOCCELL CONTROL LUMINAIRES FOR AUTO ON/AUTO OFF.

REMARKS:

1. LUMINAIRES SHALL BE CONTROLLED TO TURN ON TO 50% UPON OCCUPANCY.
2. LUMINAIRES SHALL BE CONTROLLED TO DIM CONTINUOUSLY FROM 100% TO 15% OR LOWER.
3. LUMINAIRES SHALL BE CONTROLLED TO DIM TO 50%.
4. COORDINATE TIME SCHEDULE WITH OWNER.
5. PROVIDE LIGHTING CONTROL RELAY PANEL CAPABLE OF 0-10V DIMMING.
6. TIMECLOCK AND PHOTOCELL OVERRIDE OCCUPANCY SENSOR CONTROL FROM DAWN TO DUSK
7. NOT ALL ROOMS REQUIRE DAYLIGHT HARVESTING. REFER TO PLANS FOR DAYLIGHT ZONES.

(E)Branch Panel: D1-14-LEM

Location:
Supply From:
Mounting: Surface
Enclosure: Type 1
Phase Created: Existing

Volts: 208Y/120V
Phases: 3
Wires: 4

K.A.I.C. Rating: 10
Mains Type: MCB
Mains / Design Rating: 100 A
Bus Rating: 100 A

Notes	CKT NO.	Circuit Description	Load Classification	Trip	Poles	A	B	C	Poles	Trip	Load Classification	Circuit Description	CKT NO.	Notes	
(E)	1	IT ROOM	--	20 A	1	360	150		1	20 A	--	XFMR VAV	2	(E)	
(E)	3	IT ROOM	--	20 A	1			360 150	1	20 A	--	XFMR VAV	4	(E)	
(E)	5	CUH	--	20 A	1				600 150	1	20 A	--	XFMR VAV	6	(E)
(E)	7	DOOR OPERATOR	--	20 A	1	500	500			1	20 A	--	DOOR OPERATOR	8	(E)
(E)	9	DOOR OPERATOR	--	20 A	1			500 1,080		1	20 A	R	REC: TECH WORK DESK	10	(R)
(E)	11	IT ROOM	--	20 A	1				360 1,080	1	20 A	R	REC: TECH WORK DESK	12	(R)
(E)	13	SPARE	--	20 A	1	0	1,200			1	20 A	R	REC: FREEZER	14	(R)
(E)	15	RECEPT COMPUTER	--	20 A	1			360 180		1	20 A	--	HYPERBARIC CHAMBER	16	(E)
(E)	17	RECEPT PRINTER	--	20 A	1				720 180	1	20 A	--	NURSE CALL CABINET	18	(E)
(E)	19	MED GAS ALARM	--	20 A	1	180	180			1	20 A	--	HYPERBARIC CHAMBER	20	(E)
(E)	21	D129 EMG CAN LIGHTS	--	20 A	1			480 500		1	20 A	--	DOOR OPENER	22	(E)
(N)	23	PHYS THERAPY PWR POLES	R	20 A	1				720 0	1	20 A	--	SPARE	24	(E)
(N)	25	PHYS THERAPY PWR POLES	R	20 A	1	1,080	180			1	20 A	--	D133 MASTER NURSE CALL	26	(E)
(N)	27	J-B-BOX: VAV PWR...	E	20 A	1			180 900		1	20 A	--	D131 FREEZER	28	(E)
(N)	29	J-B-BOX: VAV PWR...	E	20 A	1				180 720	1	20 A	--	D131 MANUAL FILL HOT...	30	(E)
(N)	31	J-B-BOX: AUTO DOOR...	E	20 A	1	500	360			1	20 A	--	GYM WORK DESK	32	(E)
	33	SPACE	--	--	1			-- --		1	--	--	SPACE	34	
	35	SPACE	--	--	1				-- --	1	--	--	SPACE	36	
	37	SPACE	--	--	1	--	--			1	--	--	SPACE	38	
	39	SPACE	--	--	1			-- --		1	--	--	SPACE	40	
	41	SPACE	--	--	1				-- --	1	--	--	SPACE	42	
Total Load:						5,190 VA		4,690 VA		4,710 VA					
Total Amps:						43 A		39 A							

Load Classification				Connected Load	Demand Factor	NEC Demand Load	Phase Balance	Panel Totals
L	Lighting			0 VA	0.00%	0 VA		
C	Continuous			0 VA	0.00%	0 VA	91 % A-B	Connected Load (VA): 14,590 VA
R	<u>Total Receptacle Load</u>	1st 10,000 VA	5,160 VA	100%		5,160 VA	100 % B-C	NEC Demand Load (VA): 14,590 VA
	5,160 VA	Remaining	0 VA	0%		0 VA	91 % C-A	Connected Load (A): 40 A
M	<u>Total Motor Load</u>	Largest Motor	0 VA	0.00%		0 VA		NEC Demand Load (A): 40 A
	0 VA	Remaining	0 VA	0.00%		0 VA		Spare Capacity (A): 82 A
E	Equipment		860 VA	100.00%		860 VA		Spare Capacity (%): 82
A	Appliance		0 VA	0.00%		0 VA		
LC	Load Center (# of _____)	0	0 VA	0.00%		0 VA		

Notes:

(E) - EXISTING CIRCUIT, (R) - REUSE BREAKER FOR NEW CIRCUIT, (N) - NEW BREAKER

(E)Branch Panel: D1-17-LN

Location:
Supply From: DP-D1-3LN
Mounting: Surface
Enclosure: Type 1
Phase Created: Existing

Volts: 208Y/120V
Phases: 3
Wires: 4

K.A.I.C. Rating: 10
Mains Type: MCB
Mains / Design Rating: 100 A
Bus Rating: 100 A

(Notes)	CKT NO.	Circuit Description	Load Classification	Trip	Poles	A	B	C	Poles	Trip	Load Classification	Circuit Description	CKT NO.	(Notes)		
(E)	1	D128A/D129 RECEPTS	--	20 A	1	540			1	20 A	R	REC: COFFEE 116	2	(R)		
(E)	3	D125/CORRIDOR RECEPTS	--	20 A	1		540	1,500	1	20 A	R	REC: MICROWAVE 116	4	(R)		
(E)	5	D126 RECEPTS	--	20 A	1				360	1,200	1	20 A	R	REC: REFRIG 116		
(E)	7	D127 RECEPTS	--	20 A	1	360	1,080		1	20 A	R	REC: BREAK 116	8	(R)		
(E)	9	D133 RECEPTS	--	20 A	1			360	1,620	1	20 A	R	REC: PROCEDURE 117	10	(R)	
(R)	11	REC: OFFICE 103	R	20 A	1				1,080	1,620	1	20 A	R	REC: EXAM 114	12	(R)
(R)	13	REC: TLT 102	R	20 A	1	1,440	1,620		1	20 A	R	REC: EXAM 115	14	(R)		
(R)	15	REC: PROCEDURE 100	R	20 A	1			1,440	1,080	1	20 A	R	REC: PHYSICIAN 118	16	(R)	
(R)	17	REC: PHYSICIAN 127	R	20 A	1				1,080	1,080	1	20 A	R	REC: MA 119, 121	18	(R)
(E)	19	EXISTING LOAD	--	20 A	1	0	1,080		1	20 A	R	REC: TEAM CENTER 120	20	(R)		
(E)	21	REC: D131	--	20 A	1			360	1,080	1	20 A	R	REC: TEAM CENTER 120	22	(R)	
(E)	23	REC: D131	--	20 A	1				360	900	1	20 A	R	REC: COPIER 120	24	(R)
(E)	25	REC: D131	--	20 A	1	180	1,620		1	20 A	R	REC: EXAM 113	26	(R)		
(E)	27	REC: D131	--	20 A	1			180	1,620	1	20 A	R	REC: EXAM 112	28	(R)	
(R)	29	REC: SOILED 109, TLT 110	R	20 A	1				1,080	900	1	20 A	R	REC: CLEAN 108, STOR 111	30	(R)
(R)	31	REC: PHYSICIAN 122	R	20 A	1	1,080	600				2	30 A	--	REC: 14-30R D131	32	(E)
(R)	33	REC: EXAM 106	R	20 A	1			1,620	600						34	
(R)	35	REC: EXAM 107	R	20 A	1				1,620	1,080	1	20 A	R	REC: MA 124, 126	36	(N)
(R)	37	REC: EXAM 104	R	20 A	1	1,620	1,080				1	20 A	R	REC: TEAM CENTER 125	38	(N)
(R)	39	REC: EXAM 105	R	20 A	1			1,620	900		1	20 A	R	REC: COPIER 125	40	(N)
(R)	41	REC: PHYSICIAN 123	R	20 A	1				1,080	1,080	1	20 A	R	REC: TEAM CENTER 125	42	(N)
Total Load:						13,800 VA	14,520 VA	14,520 VA								
Total Amps:						115 A	122 A	122 A								

Load Classification				Connected Load	Demand Factor	NEC Demand Load	Phase Balance	Panel Totals
L	Lighting			0 VA	0.00%	0 VA		Connected Load (VA): 42,840 VA NEC Demand Load (VA): 28,640 VA Connected Load (A): 119 A NEC Demand Load (A): 79 A Spare Capacity (A): 66 A Spare Capacity (%): 66
C	Continuous			0 VA	0.00%	0 VA	96 % A-B	
R	<u>Total Receptacle Load</u> 38,400 VA		1st 10,000 VA	10,000 VA	100%	10,000 VA	100 % B-C	
				Remaining	50%	14,200 VA	96 % C-A	
M	<u>Total Motor Load</u> 0 VA		Largest Motor	0 VA	0.00%	0 VA		
				Remaining	0 VA	0.00%	0 VA	
E	Equipment			0 VA	0.00%	0 VA		
A	Appliance			0 VA	0.00%	0 VA		
LC	Load Center	(# of ...)	0	0 VA	0.00%	0 VA		

Notes:

(E) - EXISTING CIRCUIT, (R) - REUSE BREAKER FOR NEW CIRCUIT, (N) - NEW BREAKER

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: AE
Drawn By: AE
Reviewed By: JB
Project No: 1203001
Date: 08/15/22
Submittal Level: 100% CDs
Sheet Title:

FIRST FLOOR
ELECTRICAL PLAN -
DEMOLITION

Sheet No.:
ED1.0

GENERAL NOTES (THIS SHEET)


- REFER TO SHEET E0.1 & E0.2 FOR ELECTRICAL LEGEND AND ADDITIONAL GENERAL NOTES.
- REFERENCE ARCHITECTURAL DRAWINGS FOR PHASING AND AREAS OF RENOVATION.
- EXISTING CONDITIONS SHOWN WERE TAKEN FROM FACILITY PROVIDED AS-BUILT DRAWINGS AND ON-SITE FIELD OBSERVATIONS. EACH CONTRACTOR SHALL VERIFY EXISTING CONDITIONS PRIOR TO PERFORMING WORK.
- COORDINATE CEILING DEMOLITION WORK WITH ARCHITECTURAL DRAWINGS AND WITH GENERAL CONTRACTOR.
- CONTRACTOR SHALL PROVIDE TEMPORARY LIGHTING AND POWER AS REQUIRED.
- ALL EQUIPMENT, CONDUITS, AND WIRING REMOVED ON SITE SHALL BE DISPOSED OF IN ACCORDANCE WITH PROJECT REQUIREMENTS. REFER TO SPECIFICATIONS.
- RESTORE CIRCUIT CONTINUITY IF CIRCUIT WAS BROKEN OR HAS TO BE DISCONNECTED BY REMOVAL OF DEVICES. WHERE DEVICES ARE EXISTING TO REMAIN, THE CONTRACTOR SHALL PROTECT CONDUIT AND WIRING SERVING THESE DEVICES, AND MAINTAIN UP-TO-DATE PANELBOARD DIRECTORIES.
- HEAVY RENOVATION:** DEMOLISH EXISTING LIGHTING, WIRING DEVICES, BRANCH AND FEEDER CIRCUIT WIRING AND CONDUIT, AND OTHER ELECTRICAL EQUIPMENT. EXISTING ELECTRICAL SYSTEMS REQUIRED TO SERVE OUT-OF-SCOPE AREAS SHALL REMAIN. IF REQUIRED BY NEW WORK PLANS, EXISTING CIRCUITS SERVING OUT-OF-SCOPE AREAS SHALL BE MODIFIED.
- ANY EXISTING CIRCUITS THAT ARE MADE SPARE AS A RESULT OF DEMOLITION SHALL BE IDENTIFIED AS "SPARE" IN THEIR RESPECTIVE PANELBOARD DIRECTORY.

DEMOLITION KEY NOTES (THIS SHEET)


- IN DEMOLISHED PANELBOARDS, ANY CIRCUITS SERVING OUT-OF-SCOPE AREAS SHALL BE EXTENDED TO NEAREST EXISTING-TO-REMAIN PANELBOARD. PROVIDE CONDUIT, WIRING, BREAKERS, AND ACCESSORIES AS REQUIRED. COORDINATE ANY WORK IN OUT-OF-SCOPE WITH FACILITY TO MINIMUM DEPARTMENT DISRUPTIONS.
- EXISTING LIGHT FIXTURES AND EXIT SIGNS IN THIS SPACE TO BE REMOVED, STORED, AND REINSTALLED IN NEW CEILING GRID. CLEAN AND RELAMP FIXTURES, AND RECONNECT TO EXISTING CIRCUITS AND CONTROLS AS REQUIRED.
- DEMOLISH PUSH PAD FOR AUTOMATIC DOOR OPERATOR. EXTEND WIRING TO NEW WAVE PAD OPERATOR LOCATION.
- EXISTING TO REMAIN DOOR OPERATOR. MAINTAIN WIRING AND DEVICES. MAKE READY TO CONNECT TO NEW WAVE PAD OPERATORS.
- EXISTING FIRE ALARM DEVICE TO BE REMOVED, STORED, AND REINSTALLED AFTER APPLICATION OF NEW WALL FINISHES. RECONNECT TO EXISTING WIRING AS REQUIRED.
- SYSTEMS, EQUIPMENT, WIRING DEVICES, FEEDERS, CIRCUITS, LIGHT FIXTURES, CONTROLS, AND FIRE ALARM DEVICES IN THIS SPACE ARE EXISTING TO REMAIN, UNLESS OTHERWISE NOTED. REFER TO NEW WORK PLANS FOR MODIFICATIONS MADE IN THIS SPACE.
- REPLACE EXISTING RECEPTACLES AND COVERPLATES IN THIS SPACE TO MATCH THE NEW WALL FINISH COLOR (WHITE). VERIFY WITH ARCHITECTURAL FINISHES PRIOR TO ORDERING.


HATCH LEGEND (THIS SHEET)

HEAVY RENOVATION
(SEE GENERAL NOTES
FOR DESCRIPTION)



ALTERATION SHADING LEGEND


 AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1

FIRST FLOOR ELECTRICAL PLAN - DEMOLITION

SCALE: 1/8" = 1'-0"



MECHANICAL LEGEND			MECHANICAL GENERAL NOTES	
NOTE: THIS IS A MASTER SYMBOLS LIST. ALL SYMBOLS, ABBREVIATIONS, ETC. MAY NOT NECESSARILY BE USED ON ALL DRAWINGS		NOTE: ALL DUCT DIMENSIONS SHOWN ON DRAWINGS ARE INSIDE DIMENSIONS.	ABBREVIATIONS	
PIPING		VALVES / SYMBOLS	HVAC	1. THE PLANS ARE, TO A GREAT EXTENT, DIAGRAMMATIC IN NATURE. DRAWING SCALES SHOULD BE VERIFIED FROM DIMENSIONS ON ARCH. PLANS. THE INFORMATION PRESENTED IS AS EXACT AS COULD BE SECURED. THE CONTRACTOR SHALL OBTAIN EXACT LOCATION, MEASUREMENTS LEVELS, ETC. AT THE SITE AND SHALL SATISFACTORILY ADAPT THE WORK TO THE ACTUAL CONDITIONS AT THE PROJECT SITE. 2. CONTRACTOR SHALL VISIT THE JOB SITE PRIOR TO SUBMITTING A BID TO COVER THE CONDITIONS AT THE SITE INFORMING THEMSELVES OF ALL DETAILS. 3. ALL WORK SHALL COMPLY WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL CODES, LAWS, ACTS AND ORDINANCES, AND ALL AUTHORITIES HAVING JURISDICTION. 4. THE COMPLETED INSTALLATION SHALL BE IN ACCORDANCE WITH ALL ENGINEERING REQUIREMENTS, THE OWNER'S DESIGN CRITERIA, UTILITY COMPANY REQUIREMENTS, APPLICABLE INDUSTRY STANDARDS OF GOOD PRACTICE AND SAFETY, AND THE MANUFACTURER'S STRICTEST RECOMMENDATIONS FOR EQUIPMENT AND PRODUCT APPLICATION AND INSTALLATION. 5. RECORD DRAWINGS - PREPARE AND SUBMIT TO THE OWNER RECORD DRAWINGS INDICATING THE EXACT LOCATION OF ALL EQUIPMENT INCLUDING THE EQUIPMENTS "AS INSTALLED" SIZE(S). MANUFACTURER, MODEL NUMBERS, AND PERFORMANCE RATINGS. 6. SUPPORTS - EQUIPMENT, PIPING, DUCTWORK OR ANY OTHER ACCESSORY SHALL NOT BE SUPPORTED FROM OTHER PIPING, DUCTWORK, METAL ROOF DECK, LATERAL BRACING BRIDGING, OR CONDUIT. ITEMS SHALL ONLY BE SUPPORTED FROM BUILDING STRUCTURE. 7. COORDINATE EXACT LOCATION OF ALL DUCTWORK, AIR TERMINAL UNITS, PIPING, ETC., WITH STRUCTURAL, ARCHITECTURAL, ELECTRICAL, AND OTHER MECHANICAL SYSTEMS. 8. WHERE MOUNTING HEIGHTS ARE NOT DETAILED OR DIMENSIONED, INSTALL MECHANICAL SERVICES AND OVERHEAD EQUIPMENT TO PROVIDE THE MAXIMUM HEADROOM POSSIBLE. 9. ALL DUCTWORK, PIPING, AND TEMPERATURE CONTROL CONDUIT TO VIBRATING EQUIPMENT SHALL HAVE FLEXIBLE CONNECTORS. 10. COORDINATE ALL ROOF AND CHASE PENETRATIONS WITH STRUCTURAL DRAWINGS AND ROOF INSTALLER. 11. OWNER TO HAVE CHOICE SALVAGE OF ALL PLUMBING FIXTURES AND MECHANICAL EQUIPMENT WHICH ARE PLANNED TO BE REMOVED BY CONTRACTOR. EQUIPMENT NOT SALVAGED BY OWNER SHALL BE REMOVED FROM SITE AND PROPERLY DISPOSED OF BY THE CONTRACTOR. 12. BEFORE REMOVAL OF ANY MECHANICAL EQUIPMENT, CONTRACTOR SHALL RECOVER USED REFRIGERANT IN A PROPERLY LABELED D.O.T. APPROVED REFILLABLE CYLINDER TO MEET E.P.A. STANDARDS. RECOVERED REFRIGERANT MUST BE CHEMICALLY ANALYZED AND REPROCESSED OR DISPOSED OF PER E.P.A. REQUIREMENTS, SECTION 608 OF THE CLEAN AIR ACT AND A.R.I. STANDARD 700. 13. THE LOCATION OF EXISTING UNDERGROUND UTILITIES IS SHOWN IN AN APPROXIMATE WAY ONLY. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE COMMENCING WORK. 14. ALL TESTS SHALL BE COMPLETED BEFORE ANY MECHANICAL EQUIPMENT OR PIPING INSULATION IS APPLIED. 15. CONCRETE HOUSEKEEPING PADS TO SUIT MECHANICAL EQUIPMENT SHALL BE SIZED AND LOCATED BY THE MECHANICAL CONTRACTOR. MINIMUM CONCRETE PAD THICKNESS SHALL BE 4 INCHES. PAD SHALL EXTEND BEYOND THE EQUIPMENT A MINIMUM OF 4 INCHES ON EACH SIDE. CONCRETE HOUSEKEEPING PADS SHALL BE PROVIDED BY THE GENERAL CONTRACTOR. IT SHALL BE THE RESPONSIBILITY OF THE MECHANICAL CONTRACTOR TO COORDINATE SIZE AND LOCATION OF CONCRETE HOUSEKEEPING PADS WITH GENERAL CONTRACTOR. 16. PROVIDE MINIMUM 36" ACCESS CLEARANCE TO ALL FAN POWERED BOX AND VAV BOX MAINTENANCE PANELS. 17. CONTRACTOR TO COORDINATE DUCTWORK WITH FIRE RATED WALLS AND FLOORS SHOWN ON ARCHITECTURAL DRAWINGS, MAINTAINING NECESSARY RATING OF WALLS. CONTRACTOR IS RESPONSIBLE FOR ALL CONNECTIONS TO SMOKE-FIRE DAMPERS. 18. ALL SA DUCT BRANCH TAKE-OFFS TO DIFFUSER TO BE SAME SIZE AS DIFFUSER NECK UNLESS OTHERWISE NOTED. 19. ALL INLET DUCT SIZES OF VARIABLE AIR VOLUME OR FAN-POWERED BOX UNITS SHALL BE AS PER BOX SCHEDULE ON MECHANICAL SCHEDULE. 20. ALL DUCTWORK DIMENSIONS, AS SHOWN ON THE DRAWINGS, ARE INTERNAL CLEAR DIMENSIONS AND DUCT SIZE SHALL BE INCREASED TO COMPENSATE FOR DUCT LINING THICKNESS. 21. PROVIDE MIN. OF 5'-0" OF DUCT FROM ROOM TERMINAL UNITS TO FIRST DIFFUSER TAKE-OFFS. 22. CONTRACTOR SHALL COORDINATE LOCATION OF ALL DIFFUSERS AND GRILLES WITH STRUCTURAL, ELECTRICAL, AND ARCHITECTURAL REFLECTED CEILING PLANS. 23. PROVIDE SIZES AND NUMBER OF REFRIGERANT LINES ACCORDING TO MANUFACTURER'S RECOMMENDATIONS. 24. BEFORE INSTALLATION, EQUIPMENT CONTRACTOR SHALL VERIFY THAT COILS CAN BE REMOVED WITHOUT INTERFERENCE. CONTRACTOR SHALL PROVIDE ADEQUATE ACCESS AND COIL REMOVAL SPACE FOR ALL EQUIPMENT. 25. ACCESS PANELS ARE REQUIRED (MIN. 18"x18") FOR ACCESS TO EVERY VALVE, DAMPER, AIR TERMINAL UNIT, AND CONTROL SENSOR IF NOT OTHERWISE ACCESSIBLE. 26. ALL PIPING BRANCH TAKE-OFFS TO REHEAT COIL, CABINET HEATERS, AND UNIT HEATERS SHALL BE INSTALLED WITH A MINIMUM OF THREE (3) PIPE DIRECTION CHANGES. 27. ALL HWS/HWR TAKE-OFFS TO REHEAT COILS TO BE A MINIMUM OF 3/4" PIPE SIZE.
HYDRONIC		<div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></div></div><div><div><div><div></div><div></div></div><div></</div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div>		

PROJECT NAME:

PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MG

Drawn By: JS

Reviewed By: RC

Project No: 1203001


Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title:

MECHANICAL LEGEND & NOTES

Sheet No.: M0.1



www.branchpattern.com
BETTER BUILT ENVIRONMENTS

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MG
Drawn By: JS
Reviewed By: RC
Project No: 1203001
Date: 08/15/22
Submittal Level: 100% CDs
Sheet Title: FIRST FLOOR HVAC PLAN

Sheet No.: M1.0


GENERAL NOTES (THIS SHEET)


- SEE SHEET M0.1 FOR SYMBOLS LEGEND, AND NOTES.

KEY NOTES (X) (THIS SHEET)

- REBALANCE VAV TO 750 CFM.
- NO MECHANICAL SCOPE IN AREA.

ALTERATION SHADING LEGEND

 AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MG

Drawn By: JS

Reviewed By: RC

Project No: 1203001

Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title:

FIRST FLOOR HYDRONIC PLAN

Sheet No.:

M1.1


GENERAL NOTES (THIS SHEET)


- SEE SHEET M0.1 FOR MECHANICAL LEGENDS, AND NOTES.

KEY NOTES (X) (THIS SHEET)


- RELDATE EXISTING THERMOSTAT SERVING EQUIPMENT TO LOCATION SHOWN.
- NO HYDRONIC SCOPE IN AREA.

ALTERATION SHADING LEGEND

 AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1 FIRST FLOOR HYDRONIC PLAN
SCALE: 1/8" = 1'-0"







These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date


Designed By:	MG
Drawn By:	MG
Reviewed By:	RC
Project No:	1203001
Date:	08/15/22
Submittal Level:	100% CDs
Sheet Title:	MECHANICAL DETAILS
Sheet No.:	M4.0




6 ROUND FROM RECTANGULAR TAKE-OFF
SCALE: 1/8" = 1'-0"




3 DIFFUSER/DUCT CONNECTION
SCALE: 1/8" = 1'-0"




5 LINEAR SLOT DIFFUSER
SCALE: 1/8" = 1'-0"




2 AIR TERMINAL BOX COIL
SCALE: 1/8" = 1'-0"



7 MEDIUM PRESSURE DUCT CONSTRUCTION
SCALE: 1/8" = 1'-0"



4 LOW PRESSURE DUCT CONNECTION
SCALE: 1/8" = 1'-0"



1 TYPICAL VAV BOX CONNECTION
SCALE: 1/8" = 1'-0"

NOTE:
DUCT GAUGE USED SHALL BE SUITABLE FOR 4"
W.G. IN ACCORDANCE WITH SMACNA
CONSTRUCTION STANDARDS. DUCT SHALL BE
SEALED FOR SEAL CLASS A.

NOTE:
ALL DUCTWORK SHALL BE SEALED IN
ACCORDANCE WITH SMACNA FOR SEAL CLASS A.
SEE SPEC FOR INSULATION REQUIREMENTS

NOTE:
1. REFER TO AIR TERMINAL UNIT SCHEDULE FOR
RUNOUT PIPE SIZE. MINIMUM PIPE SIZE SHALL BE
3/4".
2. FIELD INSULATE HWS/R HEADER AND CASING IF
NOT FACTORY INSULATED.
3. INTEGRAL VALVE PACKAGES ARE ACCEPTABLE.

AIR OUTLET AND INLET SCHEDULE

MARK	MANUF. & MODEL	TYPE	MODULE SIZE, IN	NECK SIZE (W X H OR DIA), IN	MAX AIRFLOW CFM	MATERIAL	FINISH	OPPOSED BLADE DAMPER	BORDER	PERFO... MAX. NC	MAX. SPD, IN	NOTES:
D-1	TITUS TMS	LOUVERED SQUARE CEILING DIFFUSER 4-WAY THROW	24 X 24	6	140	STEEL	WHITE	NO	LAY-IN OR SURFACE (REF: RCP)	30	0.10	
				8	250					30	0.10	
				10	380					30	0.10	
				12	500					30	0.10	
D-2	TITUS TMS	LOUVERED SQUARE CEILING DIFFUSER 4-WAY THROW	12 X 12	6	155	STEEL	WHITE	NO	LAY-IN OR SURFACE (REF: RCP)	30	0.10	
				8	220					30	0.10	
G-1	TITUS PAR	PERFORATED LAY-IN RETURN / EXHAUST	24 X 24	6 X 6	100	STEEL	WHITE	NO	LAY-IN OR SURFACE (REF: RCP)	30	0.10	
				8 X 8	200					30	0.10	
				10 X 10	300					30	0.10	
				12 X 12	450					30	0.10	
				15 X 15	650					30	0.10	
				18 X 18	1100					30	0.10	
				22 X 22	1500					30	0.10	
										30	0.10	
E-2	TITUS PAR	PERFORATED LAY-IN RETURN / EXHAUST	12 X 12	6	100	STEEL	WHITE	NO	LAY-IN OR SURFACE (REF: RCP)	30	0.10	
				6 X 6	125					30	0.10	
				10 X 10	360					30	0.10	

NOTES:
GEN BORDER TYPES SHALL BE COMPATIBLE WITH ARCHITECTURAL CEILING TYPE FOR THE ROOM IN WHICH THE AIR DEVICE IS LOCATED. CONTRACTOR TO CONFIRM BORDER TYPE PRIOR ...
GEN EQUIVALENT MANUFACTURERS ARE KRUEGER, PRICE, CARNES, ANEMOSTAT, NAILOR.

8/11/2022 16:44

TERMINAL BOX SCHEDULE

MARK	BASIS OF DESIGN	RUNOUT SIZE	INLET SIZE	DESIGN MAX AIRFLOW	HEATING AIRFLOW	MIN AIRFLOW	HOT... MIN. NO. OF ROWS	CALCULATED OUTPUT	MAX. WATER FLOW	MAX. WATER P.D.	NOTES
	Manufacturer "Model"	DIA in.	DIA in.	cfm	cfm	cfm		mbh	gpm	ft. H2O	
1-01	TITUS "DESV"	-	10 ø	1080	470	330	-	27.4	2.0	-	5
1-02	TITUS "DESV"	14 ø	12 ø	1140	380	350	2	27.0	2.0	0.6	1,2,3,4
1-03	TITUS "DESV"	14 ø	12 ø	1170	430	360	2	27.0	2.0	0.6	1,2,3,4
1-04	TITUS "DESV"	-	10 ø	610	285	285	-	16.3	1.0	-	5
1-05	TITUS "DESV"	-	8 ø	380	265	300	-	14.5	1.0	-	5
1-06	TITUS "DESV"	10 ø	9 ø	760	760	565	2	33.6	2.0	0.5	1,2,3,4
1-07	TITUS "DESV"	8 ø	7 ø	480	420	480	2	18.5	1.0	0.2	1,2,3,4
1-08	TITUS "DESV"	8 ø	7 ø	480	420	480	2	18.5	1.0	0.2	1,2,3,4
1-09	TITUS "DESV"	-	5 ø	310	310	285	-	14.5	1.0	-	5

NOTES:
1. BOX SELECTIONS MADE WITH NO LINER AND 0.3" STATIC PRESSURE DOWNSTREAM OF THE BOX.
2. NC LEVELS DETERMINED USING AHRI 885-2005, APPENDIX E.
3. HOT WATER COILS SELECTED AT MAXIMUM AIRFLOW, 140°F EWT, 55°F EAT, 95°F LAT, AND 30% PROPYLENE GLYCOL MIXTURE.
4. PROVIDE 8x8 INSULATED ACCESS PANEL.
5. EXISTING BOX TO REMAIN. REBALANCE TO AIRFLOWS AND GPM SHOWN.

PROJECT NAME:

PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MG

Drawn By: JS

Reviewed By: RC

Project No: 1203001

Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title: MECHANICAL SCHEDULES

Sheet No.: M5.0

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawings and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MG

Drawn By: JS

Reviewed By: RC

Project No: 1203001

Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title:

FIRST FLOOR HVAC
DEMOLITION PLAN

Sheet No.: MD1.0

GENERAL NOTES (THIS SHEET)

1. SEE M0.1 FOR SYMBOLS LEGEND AND NOTES.

DEMOLITION KEY NOTES (THIS SHEET)

1. DEMOLISH ALL DUCTWORK, AIR DEVICES, THERMOSTATS, AND ACCESSORIES SERVED BY POOL DEHUMIDIFICATION AHU D-2. DEMOLISH EXISTING RISER UP TO 3RD FLOOR MECHANICAL ROOM.


2. DEMOLISH EXISTING EXHAUST DUCTWORK BACK TO RISER. CAP AND SEAL SHAFT PENETRATION.

3. DEMOLISH EXISTING VAV BOX AND ALL ASSOCIATED DUCTWORK, BRANCH POIPING, AND THERMOSTAT.


4. NO HVAC WORK IN AREA.

ALTERATION SHADING LEGEND

AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1 FIRST FLOOR HVAC PLAN - DEMOLITION
SCALE: 1/8" = 1'-0"



www.branchpattern.com
BETTER BUILT ENVIRONMENTS

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawings and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MG

Drawn By: JS

Reviewed By: RC

Project No: 1203001

Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title:

FIRST FLOOR HYDRONIC
DEMOLITION PLAN

Sheet No.:

MD1.1

GENERAL NOTES (THIS SHEET)

- SEE SHEET M0.1 FOR SYMBOLS LEGEND AND NOTES.

DEMOLITION KEY NOTES (THIS SHEET)

- DEMOLISH EXISTING VAV BOX AND ALL ASSOCIATED DUCTWORK, BRANCH PIPING, AND THERMOSTAT.
- NO HYDRONIC WORK IN AREA.

ALTERATION SHADING LEGEND




AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1

FIRST FLOOR HYDRONIC - DEMOLITION

SCALE: 1/8" = 1'-0"



PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date



Designed By: **MG**
Drawn By: **MG**
Reviewed By: **RC**
Project No: **1203001**
Date: **08/15/22**
Submittal Level: **100% CDs**
Sheet Title:

**THIRD FLOOR
MECHANICAL &
ELECTRICAL DEMOLITION
PLAN**

Sheet No.:
MED3.0

GENERAL NOTES (THIS SHEET)
1. SEE M0.1 FOR SYMBOLS LEGEND AND NOTES.


DEMOLITION KEY NOTES ☒ (THIS SHEET)
1. XXXXX



1

THIRD FLOOR HVAC PLAN - DEMOLITION

SCALE: 1/8" = 1'-0"





















ALTERATION SHADING LEGEND












AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.

PLUMBING LEGEND















NOTE: THIS IS A MASTER SYMBOLS LIST. ALL SYMBOLS, ABBREVIATIONS, ETC. MAY NOT NECESSARILY BE USED ON ALL DRAWINGS	
PIPING	VALVES / SYMBOLS

	DOMESTIC COLD WATER
	DOMESTIC HOT WATER
	DOMESTIC HOT WATER RECIRC.
	140°F DOMESTIC HOT WATER
	140°F DOMESTIC HOT WATER RECIRC.
	PRIMARY STORM DRAIN
	SECONDARY STORM DRAIN
	SANITARY PUMPED DISCHARGE
	SANITARY WASTE
	CONDENSATE DRAIN
	SANITARY VENT
	GREASE WASTE
	ACID WASTE
	ACID VENT
	LIQUEFIED PETROLEUM GAS (PROPANE)
	NATURAL GAS
	COMPRESSED AIR
	FIRE SUPPRESSION











MISCELLANEOUS























































	SECTION CUT: UPPER NUMBER INDICATES DRAWING NUMBER LOWER NUMBER INDICATES SHEET NUMBER
	CONNECTION POINT OF NEW WORK TO EXISTING
	CONNECTION POINT OF DEMOLITION TO EXISTING
	DETAIL REFERENCE: UPPER NUMBER INDICATES DETAIL NUMBER LOWER NUMBER INDICATES SHEET NUMBER
	RISER DESIGNATION
	NOTE REFERENCE SYMBOL
	EXISTING LINEWORK
	DEMOLITION LINEWORK
	NEW LINEWORK

GAS AND VACUUM PIPING

	MEDICAL AIR
	DENTAL AIR
	LABORATORY AIR
	OXYGEN
	NITROUS OXIDE
	ORAL EVACUATION
	MEDICAL-SURGICAL VACUUM
	WASTE ANESTHESIA GAS DISPOSAL (WAGD)
	COMBINATION MEDICAL VACUUM AND WAGD
	CARBON DIOXIDE
	NITROGEN
	INSTRUMENT AIR
	MEDICAL AIR COMPRESSOR INTAKE
	VACUUM PUMP EXHAUST















GAS AND VACUUM VALVES / SYMBOLS

	ZONE VALVE BOX
	ALARM PANEL (REFERENCE SCHEDULES FOR TYPE)
	WALL MOUNTED MEDICAL AIR OUTLET
	WALL MOUNTED OXYGEN OUTLET
	WALL MOUNTED INSTRUMENT AIR OUTLET
	WALL MOUNTED MEDICAL-SURGICAL VACUUM INLET
	WALL MOUNTED DENTAL AIR OUTLET
	WALL MOUNTED CARBON DIOXIDE OUTLET
	WALL MOUNTED NITROUS OXIDE AIR OUTLET
	WALL MOUNTED WAGD INLET











	DIRECTION OF FLOW IN PIPING
	TWO WAY CONTROL VALVE
	THREE WAY CONTROL VALVE
	BUTTERFLY VALVE
	GLOBE VALVE
	BALANCING VALVE
	SOLENOID VALVE
	CONTROL VALVE
	THERMOSTATIC MIXING VALVE
	TRIPLE DUTY VALVE WITH PRESSURE PORTS
	CHECK VALVE
	STRAINER
	STRAINER WITH BLOWOFF
	RELIEF/SAFETY VALVE
	PRESSURE REDUCING VALVE
	VACUUM BREAKER
	VENTURI
	GAS COCK
	SIGHT GLASS
	BALL VALVE
	3/4" BALL DRAIN VALVE WITH 3/4" HOSE CONNECTION AND CAP ON CHAIN
	THERMOSTATIC TRAP
	F&T TRAP
	GATE VALVE
	PRESSURE GAUGE
	PRESSURE GAUGE WITH PIGTAIL
	THERMOMETER, THERMOMETER W/ TEST WELL
	PRESSURE/TEMPERATURE PORT
	UNION
	FLANGE CONNECTION
	PIPING ELBOW UP
	PIPING ELBOW DOWN
	PIPING TEE UP
	PIPING TEE DOWN
	PIPING CAP
	GAUGE COCK
	WATER HAMMER ARRESTOR
	PIPING REDUCER
	PRESSURE REGULATING VALVE
	FLEXIBLE CONNECTOR
	AUTOMATIC AIR VENT
	MANUAL AIR VENT
	PIPE ANCHOR / ROOF PIPING SUPPORT
	EXPANSION JOINT
	PIPE GUIDE
	VENT THRU ROOF
	FLOOR SINK, SIZE AND TYPE
	FLOOR DRAIN, SIZE AND TYPE
	ROOF DRAIN, SIZE AND TYPE
	HOSE BIBB / WALL HYDRANT
	LINE CLEANOUT / WALL CLEANOUT
	FLOOR CLEANOUT
	GRADE CLEANOUT
	SELF-REGULATING HEATED CABLE - LENGTH AS SHOWN IN DRAWINGS, REFERENCE ELECTRICAL PLANS FOR SPECIFICATION OF COMPLETE HEAT-TRACE SYSTEM. ARROW DENOTES DIRECTION

ABBREVIATIONS	
AAV	AIR ADMITTANCE VALVE
AD	AREA DRAIN
AFF	ABOVE FINISHED FLOOR
AV	ACID VENT
AW	ACID WASTE
BF	BOTTLE FILLER
BFP	BACKFLOW PREVENTER
BHP	BRAKE HORSEPOWER
BP	BOOSTER PUMP
BT	BATH TUB
BTU	BRITISH THERMAL UNIT
CB	CATCH BASIN
CD	CONDENSATE DRAIN
CO	CLEANOUT
CP	CIRCULATION PUMP
CW	COLD WATER
DEG.	DEGREES
DDC	DIRECT DIGITAL CONTROL
DF	DRINKING FOUNTAIN
DN	DOWN
DSN	DOWNSPOUT NOZZLE
DT	DILUTION TANK
DW	DIRECT WASTE
(E)	EXISTING TO REMAIN
EEW	EMERGENCY EYE WASH
ES	EMERGENCY SHOWER
ESP	EXTERNAL STATIC PRESSURE
EVP	ELEVATOR SUMP PUMP
EW	ELECTRIC WATER COOLER
EWT	ENTERING WATER TEMPERATURE
FCO	FLOOR CLEANOUT
FD	FLOOR DRAIN
FFE	FINISHED FLOOR ELEVATION
FHC	FIRE HOSE CABINET
FPM	FEET PER MINUTE
FS	FLOOR SINK
G	NATURAL GAS
GCO	GRADE CLEANOUT
GD	GARBAGE DISPOSAL
GPM	GALLONS PER MINUTE
GT	GAS TURRET
GV	GAS VALVE
GW	GAS WATER HEATER
HB	HOSE BIBB
HD	HEAD
HP	HORSEPOWER
HW	HOT WATER
HW	HOT WATER CIRCULATION
HC	HOT WATER CIRCULATION
HX	HEAT EXCHANGER
HZ	HERTZ
IE	INVERT ELEVATION
IMB	ICE MAKER BOX
IN.WC	INCHES OF WATER COLUMN
IW	INDIRECT WASTE
KW	KILOWATT
L	LAVATORY
LBS	POUNDS
LPG	LIQUEFIED PETROLEUM GAS
LS	LAUNDRY SINK
LWT	LEAVING WATER TEMPERATURE
MBH	1000 BTU PER HOUR
MFR	MANUFACTURER
MH	MANHOLE
MSB	MOP SINK BASIN
(N)	NEW
N2	NITROGEN
N/A	NOT APPLICABLE
NC	NORMALLY CLOSED
NO	NORMALLY OPEN
O2	OXYGEN
OD	OVERFLOW DRAIN
PH	PHASE
PIV	POST INDICATOR VALVE
PRV	PRESSURE REDUCING VALVE
PT	PLASTER TRAP
QTY	QUANTITY
(R)	RELOCATED EXISTING
RC	REFRIGERANT CHARGE
RD	ROOF DRAIN
RPM	REVOLUTIONS PER MINUTE
S	SINK
SA	SHOCK ARRESTOR
SAN	SANITARY
SE	SEWAGE EJECTOR
SF	SQUARE FEET
SH	SHOWER
SP	SUMP PUMP
ST	STORM, STORAGE TANK
TD	TRENCH DRAIN
TDH	TOTAL DYNAMIC HEAD
TEA	THERMAL EXPANSION ABSORBER
TG	TRAP GUARD
TMV	THERMOSTATIC MIXING VALVE
TP	TRAP PRIMER
TSP	TOTAL STATIC PRESSURE
TW	TEPID WATER
U	URINAL
U/F	UNDERFLOOR
UG	UNDERGROUND
U/S	UNDERSLAB
V	VENT
VAC	VACUUM
VTR	VENT THROUGH ROOF
WB	WASHER BOX
WC	WATER COLUMN, WATER CLOSET
WCO	WALL CLEANOUT
WH	WALL HYDRANT

MEDICAL GAS LEGEND

GAS AND VACUUM PIPING	
	MEDICAL AIR
	DENTAL AIR
	LABORATORY AIR
	OXYGEN
	NITROUS OXIDE
	ORAL EVACUATION
	MEDICAL-SURGICAL VACUUM
	WASTE ANESTHESIA GAS DISPOSAL (WAGD)
	COMBINATION MEDICAL VACUUM AND WAGD
	CARBON DIOXIDE
	NITROGEN
	INSTRUMENT AIR
	MEDICAL AIR COMPRESSOR INTAKE
	VACUUM PUMP EXHAUST

GAS AND VACUUM VALVES / SYMBOLS

	ZONE VALVE BOX
	ALARM PANEL (REFERENCE SCHEDULES FOR TYPE)
	WALL MOUNTED MEDICAL AIR OUTLET
	WALL MOUNTED OXYGEN OUTLET
	WALL MOUNTED INSTRUMENT AIR OUTLET
	WALL MOUNTED MEDICAL-SURGICAL VACUUM INLET
	WALL MOUNTED DENTAL AIR OUTLET
	WALL MOUNTED CARBON DIOXIDE OUTLET
	WALL MOUNTED NITROUS OXIDE AIR OUTLET
	WALL MOUNTED WAGD INLET

PLUMBING GENERAL NOTES

- THE PLANS ARE, TO A GREAT EXTENT, DIAGRAMMATIC IN NATURE. DRAWING SCALES SHOULD BE VERIFIED FROM DIMENSIONS ON ARCH. PLANS. THE INFORMATION PRESENTED IS AS EXACT AS COULD BE SECURED. THE CONTRACTOR SHALL OBTAIN EXACT LOCATION, MEASUREMENTS LEVELS, ETC. AT THE SITE AND SHALL SATISFACTORILY ADAPT THE WORK TO THE ACTUAL CONDITIONS AT THE PROJECT SITE.
- CONTRACTOR SHALL VISIT THE JOB SITE PRIOR TO SUBMITTING A BID TO COVER THE CONDITIONS AT THE SITE INFORMING THEMSELVES OF ALL DETAILS.
- ALL WORK SHALL COMPLY WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL CODES, LAWS, ACTS AND ORDINANCES, AND ALL AUTHORITIES HAVING JURISDICTION.
- THE COMPLETED INSTALLATION SHALL BE IN ACCORDANCE WITH ALL ENGINEERING REQUIREMENTS, THE OWNER'S DESIGN CRITERIA, UTILITY COMPANY REQUIREMENTS, APPLICABLE INDUSTRY STANDARDS OF GOOD PRACTICE AND SAFETY, AND THE MANUFACTURER'S STRICTEST RECOMMENDATIONS FOR EQUIPMENT AND PRODUCT APPLICATION AND INSTALLATION.
- RECORD DRAWINGS - PREPARE AND SUBMIT TO THE OWNER RECORD DRAWINGS INDICATING THE EXACT LOCATION OF ALL EQUIPMENT INCLUDING THE EQUIPMENTS "AS INSTALLED" SIZE(S), MANUFACTURER, MODEL NUMBERS, AND PERFORMANCE RATINGS.
- SUPPORTS - EQUIPMENT, PIPING, OR ANY OTHER ACCESSORY SHALL NOT BE SUPPORTED FROM OTHER PIPING, DUCTWORK, METAL ROOF DECK, LATERAL BRACING BRIDGING, OR CONDUIT. ITEMS SHALL ONLY BE SUPPORTED FROM BUILDING STRUCTURE.
- COORDINATE EXACT LOCATION OF ALL PIPING AND EQUIPMENT WITH STRUCTURAL, ARCHITECTURAL, ELECTRICAL, AND OTHER MECHANICAL SYSTEMS.
- WHERE MOUNTING HEIGHTS ARE NOT DETAILED OR DIMENSIONED, INSTALL MECHANICAL SERVICES AND OVERHEAD EQUIPMENT TO PROVIDE THE MAXIMUM HEADROOM POSSIBLE.
- ALL PIPING TO VIBRATING EQUIPMENT SHALL HAVE FLEXIBLE CONNECTORS.
- COORDINATE ALL ROOF AND CHASE PENETRATIONS WITH STRUCTURAL DRAWINGS AND ROOF INSTALLER.
- OWNER TO HAVE CHOICE SALVAGE OF ALL PLUMBING FIXTURES AND EQUIPMENT WHICH ARE PLANNED TO BE REMOVED BY CONTRACTOR. EQUIPMENT NOT SALVAGED BY OWNER SHALL BE REMOVED FROM SITE AND PROPERLY DISPOSED OF BY THE CONTRACTOR.
- BEFORE REMOVAL OF ANY MECHANICAL EQUIPMENT, CONTRACTOR SHALL RECOVER USED REFRIGERANT IN A PROPERLY LABELED D.O.T. APPROVED REFILLABLE CYLINDER TO MEET E.P.A. STANDARDS. RECOVERED REFRIGERANT MUST BE CHEMICALLY ANALYZED AND REPROCESSED OR DISPOSED OF PER E.P.A. REQUIREMENTS, SECTION 608 OF THE CLEAN AIR ACT AND A.R.I. STANDARD 700.
- THE LOCATIONS OF EXISTING UNDERGROUND UTILITIES ARE SHOWN IN AN APPROXIMATE WAY ONLY. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE COMMENCING WORK.
- ALL TESTS SHALL BE COMPLETED BEFORE ANY MECHANICAL EQUIPMENT OR PIPING INSULATION IS APPLIED.
- CONCRETE HOUSEKEEPING PADS TO SUIT MECHANICAL EQUIPMENT SHALL BE SIZED AND LOCATED BY THE MECHANICAL CONTRACTOR. MINIMUM CONCRETE PAD THICKNESS SHALL BE 4 INCHES. PAD SHALL EXTEND BEYOND THE EQUIPMENT A MINIMUM OF 4 INCHES ON EACH SIDE. CONCRETE HOUSEKEEPING PADS SHALL BE PROVIDED BY THE GENERAL CONTRACTOR. IT SHALL BE THE RESPONSIBILITY OF THE MECHANICAL CONTRACTOR TO COORDINATE THE SIZES AND LOCATIONS OF CONCRETE HOUSEKEEPING PADS WITH THE GENERAL CONTRACTOR.
- ACCESS PANELS ARE REQUIRED (MIN. 18"X18", UNLESS NOTED OTHERWISE IN SPECIFICATIONS) FOR ACCESS TO EVERY VALVE AND CONTROL SENSOR IF NOT OTHERWISE ACCESSIBLE. ACCESS PANEL SHALL BE APPROVED BY ARCHITECT/ENGINEER, COORDINATE PANEL LOCATIONS WITH THE ARCHITECT PRIOR TO INSTALLATION.
- PROVIDE SHUTOFF VALVES IN ALL DOMESTIC WATER PIPING SYSTEM BRANCHES IN WHICH BRANCH PIPING SERVES TWO OR MORE FIXTURES.
- ROUTE ALL PIPING PARALLEL TO BUILDING WALLS, STRUCTURE AND FEATURES, AS HIGH AS POSSIBLE, AND OFFSET AS NECESSARY TO AVOID STRUCTURAL MEMBERS, MECHANICAL EQUIPMENT AND THE LIKE.
- REFER TO ARCHITECTURAL DRAWINGS FOR MOUNTING HEIGHTS OF STANDARD AND ACCESSIBLE PLUMBING FIXTURES.
- SLOPE ALL SANITARY WASTE PIPE SIZES 3" AND UNDER AT 1/4" PER FOOT (2.08%) MINIMUM, UNLESS NOTED OTHERWISE.
- SLOPE ALL SANITARY WASTE PIPE SIZES 4" AND ABOVE AT 1/8" PER FOOT (1.04%) MINIMUM, UNLESS NOTED OTHERWISE.
- SLOPE ALL STORM AND OVERFLOW STORM PIPING AT 1/8" PER FOOT (1.04%) MINIMUM, UNLESS NOTED OTHERWISE.
- SLOPE ALL CONDENSATE DRAINAGE PIPING AT 1/8" PER FOOT (1.04%) MINIMUM, UNLESS NOTED OTHERWISE.

PROJECT NAME:

PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MG

Drawn By: JS

Reviewed By: RC

Project No: 1203001


Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title:

PLUMBING LEGEND & NOTES

Sheet No.: P0.1



www.branchpattern.com
BETTER BUILT ENVIRONMENTS

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawings and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MG

Drawn By: JS

Reviewed By: RC

Project No: 1203001

Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title:

UNDERFLOOR
WASTE/VENT PLAN

Sheet No.:

P1.0

GENERAL NOTES (THIS SHEET)



- SEE SHEET P0.1 FOR PLUMBING SYMBOLS, LEGENDS, AND NOTES.

KEY NOTES (THIS SHEET)

- 4" SAN UP TO WC-1
- 2" SAN UP TO L-1
- 2" SAN UP TO S-1
- 2" SAN UP TO ED-1
- 2" V UP.

ALTERATION SHADING LEGEND

AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1

UNDERFLOOR WASTE/VENT PLAN

SCALE: 1/8" = 1'-0"



PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawings and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: **MG**

Drawn By: **JS**

Reviewed By: **RC**

Project No: **1203001**

Date: **08/15/22**

Submittal Level: **100% CDs**

Sheet Title:

**FIRST FLOOR
WASTE/VENT PLAN**

Sheet No.:

P1.1

GENERAL NOTES (THIS SHEET)

1. SEE SHEET P0.1 FOR PLUMBING SYMBOLS, LEGENDS, AND NOTES.



KEY NOTES (X) (THIS SHEET)

1. 4" SAN UP TO WC-1.
2. 2" SAN UP TO L-1.
3. 2" SAN UP TO S-1.
4. 2" SAN UP TO FD-1.
5. 2" V UP.

ALTERATION SHADING LEGEND




AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1

FIRST FLOOR WASTE/VENT PLAN

SCALE: 1/8" = 1'-0"



PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawings and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: **MG**

Drawn By: **JS**

Reviewed By: **RC**

Project No: **1203001**

Date: **08/15/22**

Submittal Level: **100% CDs**

Sheet Title:


FIRST FLOOR DOMESTIC WATER PLAN

Sheet No.:


P2.1


GENERAL NOTES (THIS SHEET)

1. SEE SHEET P0.1 FOR PLUMBING SYMBOLS, LEGENDS, AND NOTES.




ALTERATION SHADING LEGEND

 AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1 FIRST FLOOR DOMESTIC WATER PLAN
SCALE: 1/8" = 1'-0"



PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: **MG**

Drawn By: **JS**

Reviewed By: **RC**

Project No: **1203001**

Date: **08/15/22**

Submittal Level: **100% CDs**

Sheet Title:

FIRST FLOOR MED GAS PLAN

Sheet No.:

P3.1


GENERAL NOTES (THIS SHEET)



1. SEE SHEET P0.1 FOR PLUMBING SYMBOLS, LEGEND, AND NOTES.

KEY NOTES (X) (THIS SHEET)

1. ROUTE 1/2" V, MA, AND O2 TO EACH FUTURE PROCEDURE ROOM. TERMINATE ABOVE CEILING AND CAP FOR FUTURE USE.
2. CAP FOR FUTURE USE

ALTERATION SHADING LEGEND

 AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1

FIRST FLOOR MED GAS PLAN

SCALE: 1/8" = 1'-0"





These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MG

Drawn By: JS

Reviewed By: RC

Project No: 1203001

Date: 08/15/22


Submittal Level: 100% CDs

Sheet Title:

PLUMBING DETAILS

Sheet No.: P4.0


PROVIDE AN INDIVIDUAL VENT ON ALL FLOOR DRAINS. INSTALL VENT IN PARTITION OR CHASE WHERE SHOWN ON PLAN. HORIZONTAL VENT BELOW FLOOR IS NOT PERMITTED. IF FLOOR DRAIN/SINK IS MORE THAN 5' ON A 2" WASTE OR 6' ON A 3" WASTE FROM THE PARTITION, PROVIDE A TRAP AND WASTE LINE TWO PIPE SIZES LARGER THAN THE DRAIN/SINK OUTLET, WITH A REDUCER ON THE TRAP INLET, AND VENT WITHIN 15 FEET. OTHER VENTING METHODS MAY BE USED IF APPROVED BY LOCAL CODE.



LOCATE FLOOR DRAIN/SINK WHERE SHOWN ON DIMENSIONED ARCHITECTURAL PLAN. IF FLOOR STRUCTURE INTERFERES WITH PLACEMENT, MOVE SIDEWAYS IF POSSIBLE. OTHERWISE MOVE BACK. ALWAYS LOCATE WHERE EASILY ACCESSIBLE, BUT NOT IN FOOT TRAFFIC. IF SITUATION IS FLOOR SLAB ON GRADE, PROVIDE BACKFILL PER SPECIFICATIONS. IF FLOOR IS EXISTING, SAW CUT OR CORE DRILL IT. SET DRAIN BODY IN PLACE & POUR AROUND IT. IF SITUATION IS FLOOR NOT ON GRADE, REFER TO "FLOOR PENETRATION" DETAIL FOR VENTS.

1 FLOOR DRAIN/SINK INSTALLATION


SCALE: NONE



NOTES:
1. PROVIDE WCO AT BASE OF ALL SANITARY WASTE AND STORM RISERS. PROVIDE WCO WHERE SHOWN ON PLANS. AND ON SANITARY WASTE BRANCHES NOT SERVED WITH A FLOOR CLEANOUT. CONSULT LOCAL CODES FOR OTHER WCO REQUIREMENTS. REFER TO PLUMBING FIXTURE SCHEDULE FOR FURTHER INFORMATION.
2. CLEANOUT FACE SHALL BE WITHIN 1'-1/2" OF WALL SURFACE. PROVIDE EXTENSION IF REQUIRED.

2 WALL CLEANOUT


SCALE: NONE



(RE: PLANS AND SCHEDULES FOR DESIGNATION.)
SCHEDULES DICTATE NUMBER OF VALVES REQUIRED FOR EACH PARTICULAR INSTANCE.

3 ZONE VALVE BOX DETAIL


SCALE: NONE



NOTE: TRAPEZE HANGERS APPLY TO ALL MULTIPLE HORIZONTAL RUNS WITH OR WITHOUT VAPOR BARRIER INSULATION. COORDINATE INSTALLATION WITH ALL OTHER CONDITIONS TO ALLOW SPACE FOR OTHER SERVICES.


4 TRAPEZE HANGER

SCALE: NONE




5 THERMOSTATIC MIXING VALVE

SCALE: NONE



6 HOT WATER RECIRC IECC 404.5.1

SCALE: NONE




SINGLE HORIZONTAL RUNS WITH NO VAPOR BARRIER INSULATION

SINGLE HORIZONTAL RUNS WITH VAPOR BARRIER INSULATION

7 CLEVIS HANGER


SCALE: NONE



1. PROVIDE CLEANOUT TOP WITH VARIATIONS SUITABLE FOR FLOOR COVERING (CARPET MARKER, RECESSED FOR TILE, SCORIATED CAST IRON FOR UNFINISHED FLOORS).
2. LOCATE AT BUILDING EXIT, AT ENDS OF RUNS, AT TURNS OF PIPE GREATER THAN 45 DEGREES, AT 100' INTERVALS ON STRAIGHT RUNS, AND/OR WHERE SHOWN ON PLANS. PROVIDE BACKFILL PER ARCHITECTURAL SPECIFICATIONS. LOCATE CLEANOUTS WHERE THERE IS 18" CLEAR AROUND. CONSULT LOCAL CODES FOR OTHER ECO REQUIREMENTS.

8 FLOOR CLEANOUT


SCALE: NONE



NOTES:
1. PIPE AND CONDUIT OF ALL TRADES MAY BE COMBINED ON SAME SUPPORT CHANNEL WHERE PRACTICAL.
2. SUPPORT CHANNEL LENGTH SHALL NOT BE DETERMINED UNTIL ALL PIPING AND CONDUIT TO BE SUPPORTED IS COORDINATED.

11 TRAPEZE PIPE HANGER

SCALE: NONE



BranchPattern

www.branchpattern.com

BETTER BUILT ENVIRONMENTS

PROJECT NAME:

PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MG

Drawn By: JS

Reviewed By: RC

Project No: 1203001

Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title:

PLUMBING SCHEDULES

Sheet No.:

P5.0

PLUMBING FIXTURE & EQUIPMENT CONNECTION SCHEDULE

FIXTURE	COMPONENT	MANUFACTURER	MODEL	DESCRIPTION	FLOW RATE (GPM/GPF)	ACCESSIBLE	ELECTRICAL	WASTE	VENT	CW	HW
WC-1	WATER CLOSET SEAT FLUSH VALVE	SLOAN BEMIS SLOAN	ST-2459-STG 2155SSCT REGAL 111 XL CV-1.28	WALL HUNG, SIPHON JET, GLAZING, ELONGATED RIM, ADA MOUNTING HEIGHT. OPEN FRONT SOLID PLASTIC SEAT. MANUALLY OPERATED FLUSH VALVE.	1.28	YES	-	4"	2"	1"	-
L-1	LAVATORY FAUCET	ZURN	Z5344 Z812B4-XL-28F	WALL HUNG, 4" CENTERS, PROVIDE WITH CARRIER, COORDINATE WITH WALL THICKNESS. MANUALLY OPERATED FAUCET, WITH MV-1. PROVIDE WITH IPS CORP 2018SLSS3003 IN PUBLIC/PATIENT AREAS. PROVIDE GRID DRAIN, 17 GAUGE P-TRAP, ANGLE SUPPLIES W/L.K. STOPS, INSULATION KIT.	0.5	YES	-	2"	1-1/2"	1/2"	1/2"
S-1	SINK FAUCET	JUST MFG ZURN	SL-1617-A-GR Z831B4-XL-FC	SELF RIMMING, SINGLE COMPARTMENT, DROP IN, TYPE 304, 18 GAUGE STAINLESS STEEL SINK BASIN. MANUALLY OPERATED FAUCET WITH 4" CENTERS. PROVIDE GRID DRAIN, OFFSET, 17 GAUGE P-TRAP, ANGLE SUPPLIES W/L.K. STOPS, INSULATION KIT.	1.0	-	-	2"	1-1/2"	1/2"	1/2"
WHA	WATER HAMMER ARRESTOR	SIOUX CHIEF	652-A	SIZE "A", PISTON-TYPE WATER HAMMER ARRESTOR, PROVIDE WITH LINE SIZE BALL VALVE FOR ISOLATION AND PROVIDE WITH ACCESS.	-	-	-	-	-	PER DETAIL	-
FD-1	FLOOR DRAIN	ZURN	ZN415B	CAST IRON FLOOR DRAIN, 6" DIAMETER STRAINER, 8"DIA. BODY, SEEPAGE SLOTS, COMBO MEMBRANE CLAMP AND ADJUSTABLE COLLAR, LIGHT DUTY NICKEL BRONZE STRAINER.	-	-	-	PER PLAN	-	-	-
FCO	FLOOR CLEANOUT	ZURN	ZN1400-BZ1-BP-VP	ADJUSTABLE, COATED CAST IRON BODY, BRONZE THREADED PLUG, ROUND SCORIATED NICKEL BRONZE MEDIUM-DUTY TOP.	-	-	-	PER PLAN	-	-	-
WCO	WALL CLEANOUT	ZURN	Z1446-BP	EPOXY COATED CAST IRON BODY WITH BRONZE PLUG, ROUND STAINLESS STEEL WALL ACCESS COVER, AND SECURING SCREW.	-	-	-	PER PLAN	-	-	-

GENERAL NOTE: NO AERATORS ON ALL LAVATORIES AND SINKS.

HOT WATER MIXING VALVE SCHEDULE

MARK	MANUFACTURER & MODEL OR EQUAL	MINIMUM GPM	MAXIMUM GPM	INLET WATER TEMP (F)	OUTLET WATER TEMP (F)	PRESSURE DROP (PSI)	ELECTRICAL VOLTS	PH	NOTES:
MV-1	LEONARD 170A-LF	0.25	1.9	125	105	20	N/A	N/A	1
NOTES: 1 POINT-OF-USE MIXING VALVE FOR SINKS AND LAVATORIES.									

MEDICAL GAS ZONE VALVE BOX SCHEDULE


MARK	MANUFACTURER & MODEL OR EQUAL	ZONE VALVE BOX LOCATION	ROOMS SERVED	VALVE SIZE (IN.)								NOTES
				MA	O	MV	WAGD	N2O	LA	1A	CO2	
ZVB-1	POWEREX - ZVBNXXXXXXX	HALLWAY 170	PROCEDURE 176		X	X			X			1,2
NOTES: 1. MAXIMUM VALVE SIZE IS 2". PANEL MUST BE LOCATED IN A MINIMUM 6" DEEP STUD WALL. VERIFY BOX DEPTH VS VALVE SIZE WITH MANUFACTURER. 2. MODEL NUMBER INFORMATION: N = NUMBER OF VALVES IN BOX, X = VALVE SIZES OR BLANK.												

NOTES:
1. INSTALL IN HORIZONTAL OR VERTICAL POSITION, BUT NEVER UPSIDE DOWN. INSTALL IN LINE WITH WATER FLOW DIRECTION IF POSSIBLE. SIZE THE UNITS AS SHOWN ON THE DRAWINGS AND/OR THE TABLES SHOWN ABOVE. PROVIDE ACCESSIBILITY TO WHA.

2. INSTALL PER PDI STANDARDS AND MANUFACTURER'S INSTRUCTIONS. PROVIDE A WHA AT ALL QUICK-CLOSING VALVES.


3. FOR INDIVIDUAL SINKS/LAVATORIES WITH SOLENOID VALVES, INSTALL COMBINATION LOOSE KEY ANGLE STOP WITH WATER HAMMER ARRESTOR.

4. WATER HAMMER ARRESTORS MAY BE INSTALLED ABOVE CEILING.



PDI SIZE	PIPE SIZE	FIXTURE UNIT LOAD
A	1/2"	1-11
B	3/4"	12-32
C	1"	33-60
D	1-1/4"	61-113
E	1-1/2"	114-154
F	2"	155-330

FIXTURE UNIT TABULATION		
FIXTURE	COLD	HOT
VALVE WATER CLOSET	10	--
TANK WATER CLOSET	5	--
URINAL	5	--
LAVATORY/SINK	1.5	1.5
JANITOR'S SINK	3	3
SHOWER/BATHTUB	2	2




KEY:
1. WATER HAMMER ARRESTER.
2. BALL VALVE. SAME NOMINAL SIZE AS PIPE BRANCH IN CHASE. OPENING IN BALL VALVE TO MATCH PIPE ID.
3. PIPE SAME SIZE AS BRANCH IN CHASE TO WHICH IT IS ATTACHED.

NOTE:
1. PROVIDE REDUCER IF REQUIRED BETWEEN VALVE AND WATER HAMMER ARRESTER.

1 WATER HAMMER ARRESTOR AND PANEL

SCALE: NONE



www.branchpattern.com
BETTER BUILT ENVIRONMENTS

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: **MG**
Drawn By: **JS**
Reviewed By: **RC**
Project No: **1203001**
Date: **08/15/22**
Submittal Level: **100% CDs**
Sheet Title:

**UNDERFLOOR
WASTE/VENT
DEMOLITION PLAN**

Sheet No.: **PD1.0**


GENERAL NOTES (THIS SHEET)



- SEE SHEET P0.1 FOR PLUMBING SYMBOLS, LEGEND, AND NOTES.

DEMOLITION KEY NOTES (THIS SHEET)

- CAP EXISTING 3" SAN.

ALTERATION SHADING LEGEND

 AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.




1

UNDERFLOOR WASTE/VENT - DEMOLITION

SCALE: 1/8" = 1'-0"





www.branchpattern.com
BETTER BUILT ENVIRONMENTS

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date


Designed By:	MG
Drawn By:	JS
Reviewed By:	RC
Project No:	1203001
Date:	08/15/22
Submittal Level:	100% CDs
Sheet Title:	FIRST FLOOR WASTE/VENT DEMOLITION PLAN

Sheet No.:
PD1.1

GENERAL NOTES (THIS SHEET)
1. SEE SHEET P0.1 FOR PLUMBING SYMBOLS, LEGEND, AND NOTES.

ALTERATION SHADING LEGEND

AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1

FIRST FLOOR WASTE/VENT - DEMOLITION
SCALE: 1/8" = 1'-0"

0' 2' 4' 8'

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: **MG**
Drawn By: **JS**
Reviewed By: **RC**
Project No: **1203001**
Date: **08/15/22**
Submittal Level: **100% CDs**
Sheet Title:


**FIRST FLOOR DOMESTIC
WATER DEMOLITION
PLAN**


Sheet No.: **PD2.1**

GENERAL NOTES (THIS SHEET)

- SEE SHEET P0.1 FOR PLUMBING SYMBOLS, LEGEND, AND NOTES.







ALTERATION SHADING LEGEND

 AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1 FIRST FLOOR DOMESTIC WATER - DEMOLITION
SCALE: 1/8" = 1'-0"
0' 2' 4' 8'

SYMBOL TYPES										ABBREVIATIONS					
NOTE: THIS IS A MASTER SYMBOLS LIST. ALL SYMBOLS, ABBREVIATIONS, ETC. MAY NOT NECESSARILY BE USED ON ALL DRAWINGS										AC AFF		ABOVE COUNTER ABOVE FINISHED FLOOR			
TELECOM SYMBOLS										C CFCI CFOI		CONDUIT CONTRACTOR FURNISHED AND CONTRACTOR INSTALLED CONTRACTOR FURNISHED AND OWNER INSTALLED			
XX ▼	TELECOM DATA DEVICE MOUNTED ON WALL. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			XX ▼	TELECOM DATA DEVICE MOUNTED ON FLOOR. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			XX ⬇	TELECOM DATA DEVICE MOUNTED ON CEILING. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			XX ▼	TELECOM ANALOG DEVICE MOUNTED ON WALL. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.		
XX ▣	TELECOM ANALOG DEVICE MOUNTED ON FLOOR. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			XX ⬇	TELECOM ANALOG DEVICE MOUNTED ON CEILING. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			XX ▼	TELECOM DATA/ANALOG COMBINATION DEVICE MOUNTED ON WALL. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			XX ▣	TELECOM DATA/ANALOG COMBINATION DEVICE MOUNTED ON FLOOR. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.		
XX ⬇	TELECOM DATA/ANALOG COMBINATION DEVICE MOUNTED ON CEILING. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.														
AV SYMBOLS										Mbps MM		MEGABITS PER SECOND MULTIMODE			
⬠	AV DEVICE MOUNTED ON WALL. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			⬠	AV DEVICE MOUNTED ON FLOOR. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			⬠	AV DEVICE MOUNTED ON CEILING. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			⬠	AV CAMERA MOUNTED ON WALL. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.		
⬠	AV CAMERA MOUNTED ON CEILING. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.														
SECURITY SYMBOLS										RU		RACK UNIT (1.75")			
⬠	SECURITY DEVICE MOUNTED ON WALL. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			⬠	SECURITY DEVICE MOUNTED ON FLOOR. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			⬠	SECURITY DEVICE MOUNTED ON CEILING. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.			⬠	SECURITY CAMERA MOUNTED ON WALL. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.		
⬠	SECURITY CAMERA MOUNTED ON CEILING. XX INDICATES TYPE, REFER TO SCHEDULE BELOW FOR DEVICE INFORMATION.														
SYSTEM TYPE										QTY		QUANTITY			
MOUNTING TYPE										SBB SEF SM		SECONDARY BONDING BUSBAR SERVICE ENTRANCE FACILITY SINGLE MODE			
TYPE										TIA TYP		TELECOMMUNICATIONS INDUSTRY ASSOCIATION TYPICAL			
DESCRIPTION										UG UNO UPS UTP		UNDERGROUND UNLESS OTHERWISE NOTED UNINTERRUPTIBLE POWER SUPPLY UNSHIELDED TWISTED PAIR			
MOUNTING										W/O WAO WAP		WITHOUT WORK AREA OUTLET WIRELESS ACCESS POINT			
INFRASTRUCTURE BOX										XC		CROSS-CONNECT			
INFRASTRUCTURE CONDUIT															
REFERENCE															
COUNT															
AUDIOVISUAL	CEILING	S	LOUDSPEAKER FOR ROOM SYSTEM	-	INTEGRAL TO LOUNDSPEAKER BACKCAN (PROVIDED BY AV CONTRACTOR)			NA, PLENUM CABLING				14			
AUDIOVISUAL	WALL	AV	AV INTERFACE (2 DATA, 1 HDMI POINT TO POINT TO DISPLAY BOX)	1' - 6" AFF	4-11/16" SQUARE WITH 2-DEVICE MUD RING, FLUSH MOUNTED, 2-1/8" DEEP BACK BOX			(1) 1-1/4" STUBBED TO ACCESSIBLE CEILING				1			
AUDIOVISUAL	WALL	D	DISPLAY - SHARED BOX FOR POWER, (2) DATA AND AV (HDMI CONNECTION TO "AV" BOX)	6' - 0" AFF	CHIEF #PAC525			(2) 1-1/4" STUBBED TO ACCESSIBLE CEILING				1			
AUDIOVISUAL	WALL	TV	TV OUTLET WITH (1) COAX AND (1) DATA, REFER TO TECHNOLOGY DETAIL SHEETS FOR ADDITIONAL INFORMATION.	6' - 0" AFF	4 SQUARE WITH 1 GANG MUD-RING, FLUSH MOUNTED, 2-1/8" DEEP BACK BOX			(2) 1" C. TO IN-ROOM MEDIA PANEL, UNO				5			
DATA DEVICE	WALL	2	2-PORT TELECOM OUTLET	1' - 6" AFF	4-11/16" SQUARE WITH 1-DEVICE MUD RING, FLUSH MOUNTED, 2-1/8" DEEP BACK BOX			(1) 1" C TO ACCESSIBLE CEILING SPACE				50			
DATA DEVICE	WALL	2AC	2-PORT DATA OUTLET MOUNTED ABOVE COUNTER	6" ABOVE COUNTERTOP OR MATCH ELECTRICAL BOXES	4-SQUARE WITH 1 GANG MUD-RING, FLUSH MOUNTED, 2-1/8" DEEP BACK BOX			(1) 1" C. TO NEAREST ACCESSIBLE CEILING				1			
DATA DEVICE	WALL	4	4-PORT TELECOM OUTLET	1' - 6" AFF	4-11/16" SQUARE WITH 1-DEVICE MUD RING, FLUSH MOUNTED, 2-1/8" DEEP BACK BOX			(1) 1" C TO ACCESSIBLE CEILING SPACE				2			
DISPLAY	SURFACE	XX		8' - 0" AFF								2			
NURSE CALL	WALL	EP	EMERGENCY PULL CORD STATION	4' - 0" AFF	4-11/16" SQUARE BOX, 2-1/2" DEEP, WITH 13/16" DEEP 1-DEVICE MUD RING, FLUSH MOUNTED			1" C TO NEAREST ACCESSIBLE CEILING				1			
SECURITY	WALL	DR	Door Release Button Wall Box	1' - 6" AFF	SURFACE MOUNT DEVICE TO UNDERSIDE OF DESK AND ROUTE TO (1) 4" X 4", FLUSH MOUNTED, 2-1/8" DEEP BACK BOX W / 1-GANG PLASTER RING			(1) 3/4" CONDUIT TO NEAREST ACCESSIBLE CEILING				1			
SECURITY	WALL	R	CARD READER	3' - 10" AFF	4-11/16" SQUARE WITH 1-DEVICE MUD RING, FLUSH MOUNTED, 2-1/8" DEEP BACK BOX			(1) 3/4" C STUBBED INTO NEAREST ACCESSIBLE CEILING				9			
SECURITY CAMERA	CEILING	90	SURVEILLANCE CAMERA - INTERIOR 90 DEGREE	-	N/A			N/A, PLENUM CABLING				7			
SECURITY CAMERA	CEILING	360	SURVEILLANCE CAMERA - INTERIOR 360 DEGREE	-	N/A			N/A, PLENUM CABLING				7			

EQUIPMENT LEGEND	
	FLAT PANEL DISPLAY, REFER TO DISPLAY TABLE BELOW FOR ANNOTATION DESCRIPTIONS.
	PROJECTION SCREEN, REFER TO DISPLAY TABLE BELOW FOR ANNOTATION DESCRIPTIONS.
	LADDER RACK
	4-POST RACK
	2-POST RACK
	WALL PANEL, "XX" INDICATES TYPE, CHECK ABBREVIATIONS LIST FOR TYPE.

TECHNOLOGY SHEET INDEX	
T0.1	TECHNOLOGY LEGEND
T0.2	TECHNOLOGY NOTES
TD1.0	TECHNOLOGY DEMOLITION PLAN
T1.0	FIRST FLOOR TECHNOLOGY PLAN
T3.0	TECHNOLOGY DIAGRAMS
T4.0	TECHNOLOGY DETAILS

PROJECT NAME:

PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MM

Drawn By: MM

Reviewed By: JB


Project No: 1203001

Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title: TECHNOLOGY LEGEND

Sheet No.: T0.1



BranchPattern

www.branchpattern.com

BETTER BUILT ENVIRONMENTS

PROJECT NAME:

PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MM

Drawn By: MM

Reviewed By: JB

Project No: 1203001

Date: 08/15/22

Submittal Level: 100% CDs

Sheet Title:

TECHNOLOGY NOTES

Sheet No.: T0.2

GENERAL NOTES

1.

DO NOT SCALE DRAWINGS. VERIFY DIMENSIONS ON ARCHITECTURAL DRAWINGS AND IN FIELD PRIOR TO COMMENCEMENT OF WORK.
2.

REFER TO ALL ARCHITECTURAL/ELECTRICAL/STRUCTURAL/CIVIL AND MECHANICAL DRAWINGS FOR ADDITIONAL REQUIREMENTS AND INFORMATION.
3.

FINAL CONNECTIONS TO EQUIPMENT SHALL BE IN ACCORDANCE WITH MANUFACTURER'S APPROVED WIRING DIAGRAMS, DETAILS, AND INSTRUCTIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO PROVIDE MATERIALS AND EQUIPMENT COMPATIBLE WITH EQUIPMENT ACTUALLY SUPPLIED.
4.

WORK, MATERIALS, AND EQUIPMENT SHALL CONFORM TO THE LATEST EDITIONS OF LOCAL, STATE, AND NATIONAL CODES AND ORDINANCES.
5.

PROVIDE PERMITS AND INSPECTIONS REQUIRED.
6.

SYSTEM SHALL BE TESTED FOR PROPER OPERATION. IF TESTS SHOW THAT WORK IS DEFECTIVE, CONTRACTOR SHALL MAKE CORRECTIONS NECESSARY AT NO COST TO OWNER.
7.

CONTRACTOR'S FAILURE TO ORDER OR RELEASE ORDER FOR MATERIALS AND/OR EQUIPMENT WILL NOT BE ACCEPTED AS REASON TO SUBSTITUTE ALTERNATE MATERIALS, EQUIPMENT, OR INSTALLATION METHODS.
8.

ALL SYSTEMS SHALL BE COMPLETE AND FULLY OPERATIONAL.
9.

IT IS THE INTENT OF THESE DRAWINGS AND SPECIFICATIONS TO ESTABLISH A STANDARD OF QUALITY. THE ENGINEER RESERVES THE RIGHT TO APPROVE METHODS AND MATERIALS NOT REFLECTED HEREIN.
10.

PROVIDE RECORD DRAWINGS TO THE ARCHITECT/ENGINEER. DRAWINGS SHALL INCLUDE ALL ADDENDUM ITEMS, CHANGE ORDERS, ALTERATIONS, REROUTINGS, ETC.
11.

CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING EQUIPMENT WHICH IS DAMAGED DUE TO INCORRECT FIELD WIRING PROVIDED UNDER THIS SECTION, OR FACTORY WIRING IN EQUIPMENT PROVIDED UNDER THIS SECTION.
12.

VERIFY EXACT LOCATIONS OF EXISTING AND NEW UNDERGROUND UTILITIES, PIPING, AND RACEWAY SYSTEMS PRIOR TO TRENCHING. PROVIDE NECESSARY TRENCHING, BACKFILL, EXCAVATION, SUPPORTS, SERVICE FEEDERS (CONDUIT AND/OR WIRE), PULLBOXES, TRANSFORMERS PADS, SAW CUTTING AND PATCHING, CONCRETE PAVING, ETC. REQUIRED. BACKFILL TRENCHES TO 90% COMPACTION AND PATCH TO MATCH EXISTING. CONTRACTOR SHALL OBTAIN AND VERIFY EXACT UTILITY COMPANY DRAWINGS AND REQUIREMENTS.
13.

THE DATA GIVEN ON THE DRAWING IS AS EXACT AS COULD BE SECURED. THE CONTRACTOR SHALL OBTAIN EXACT LOCATION, MEASUREMENTS, LEVELS, ETC. AT THE SITE AND SHALL SATISFACTORILY ADAPT THE WORK TO THE ACTUAL CONDITIONS AT THE PROJECT SITE.
14.

VERIFY EXACT LOCATION OF EQUIPMENT TO BE FURNISHED BY OTHERS PRIOR TO ROUGH-IN.
15.

ROUTE ALL WIRE AND CONDUIT CONCEALED, FOR ALL SYSTEMS, UNLESS NOTED OTHERWISE.
16.

ACCURATE RECORDS OF WORK MODIFICATIONS (AS-BUILTS) SHALL BE KEPT DAILY.
17.

THE COMPLETED INSTALLATION SHALL BE IN ACCORDANCE WITH ALL ENGINEERING REQUIREMENTS, THE OWNERS DESIGN CRITERIA, UTILITY COMPANY REQUIREMENTS, APPLICABLE INDUSTRY STANDARDS OF GOOD PRACTICE AND SAFETY AND THE MANUFACTURER'S STRICTEST RECOMMENDATIONS FOR EQUIPMENT AND PRODUCT APPLICATION AND INSTALLATION.
18.

VALIDATE ALL QUANTITIES. DEVICES SHOWN ON PLANS TAKE PRECEDENCE OVER SCHEDULE QUANTITIES.
19.

CARD READERS MUST BE WITHIN 6" OF DOOR FRAME, UNO.

GENERAL INFRASTRUCTURE NOTES

1.

IF THE ENCLOSURE, BOXES AND CABINETS SPECIFIED ARE NOT PROVIDED FROM THE MANUFACTURER WITH THE REQUIRED KNOCKOUT FOR THE SPECIFIED CONDUIT, FIELD CUT ALL REQUIRED KNOCKOUTS TO TERMINATE THE QUANTITY AND SIZE OF THE SPECIFIED CONDUITS.
2.

MAINTAIN MAXIMUM SEPARATION BETWEEN AV SYSTEM CONDUIT AND ALL POWER CONDUIT.
3.

INSTALL NYLON PULL STRINGS IN ALL CONDUIT.
4.

INSTALL ALL CONDUIT IN A CONCEALED FASHION. SURFACE MOUNTED CONDUIT WILL NOT BE ACCEPTED UNLESS SPECIFICALLY IDENTIFIED IN THE DRAWINGS.
5.

COVER ALL INSTALLED JUNCTION BOXES AND MUD RINGS WITH BLANK COVER PLATES.
6.

ALL CONDUIT SHALL BE A MINIMUM DIAMETER OF 3/4" UNLESS NOTED OTHERWISE.
7.

ALL CONDUIT SHALL BE THIN-WALL EMT UNLESS NOTED OTHERWISE. CONDUIT SIZES AND TERMINATION SHALL BE AS NOTED ON THE TECHNOLOGY INFRASTRUCTURE DRAWINGS.
8.

MAXIMUM OF TWO 90-DEGREE BENDS OR 50 LINEAR FEET BETWEEN PULL BOXES. ADDITIONAL PULL BOXES NOT SHOWN ON DRAWINGS MAY BE REQUIRED. CONDUIT ROUTING IS AT THE ELECTRICAL CONTRACTOR'S DISCRETION.
9.

MOUNT BOXES ON WALLS AT THE HEIGHTS NOTED ON THE TECHNOLOGY INFRASTRUCTURE DRAWINGS IF ELECTRICAL BOXES ARE AT SIMILAR BUT DIFFERENT HEIGHTS, MOUNT BOXES TO MATCH ELECTRICAL BOX HEIGHTS. (18" AFF OR 46" AFF, ETC.). DIMENSIONS SHOWN ON THESE DRAWINGS ARE TO THE CENTER OF BOX UNLESS OTHERWISE NOTED. IF MATCHING HEIGHTS WITH ELEC DOES NOT FOLLOW ADA OR OTHER APPLICABLE CODES OR STANDARDS, SUBMIT A RFI FOR CLARIFICATION.
10.

PROVIDE NYLON BUSHINGS ON ALL CONDUIT STUBS AND NON-TERMINATED CONDUIT ENDS.

GENERAL AV INSTALLATION NOTES

1.

INSTALL ALL EQUIPMENT IN COMPLIANCE WITH THE MANUFACTURER'S WRITTEN INSTRUCTIONS, SEISMIC CODES, AND INDUSTRY ACCEPTED RIGGING PRACTICES. SUPPORT EQUIPMENT WEIGHT FROM STRUCTURE ABOVE CEILINGS. DURING THE SUBMITTAL PROCESS, PROVIDE SHOP DRAWINGS WHICH DETAIL PROPOSED MOUNTING FOR ALL SUCH EQUIPMENT.

GENERAL GROUNDING NOTES

1.

ISOLATE ALL EQUIPMENT FROM CONDUIT AND BUILDING STEEL.
2.

GROUND COMMUNICATIONS SYSTEMS AND EQUIPMENT IN ACCORDANCE WITH ANSI-TIA-EIA GROUNDING STANDARD AND APPLICABLE NEC REQUIREMENTS.
3.

ALL RACKS, METALIC BACKBOARDS, CABLE TRAYS, SPLICE CASES, ETC. IN A TECHNICAL EQUIPMENT SPACE (EITHER RESIDING IN OR ENTERING/EXITING) SHALL BE GROUNDED TO THEIR RESPECTIVE GROUND SYSTEM USING A #6 AWG (MINIMUM) COPPER BONDING CONDUCTOR.
4.

ALL GROUND WIRES USED FOR TECHNICAL SYSTEM GROUNDING SHALL BE IDENTIFIED AT THEIR TERMINATION POINTS WITH GREEN WRAP/TAPE. THESE GROUNDS SHALL BE LABELED/IDENTIFIED AS "TECHNICAL POWER SYSTEM GROUND".

RESPONSIBILITY MATRIX

SYSTEM	SCOPE DESCRIPTION	SPECIFICATION SECTION	FURNISHED BY	INSTALLED BY
ALL LOW-VOLTAGE SYSTEMS	BACKBOXES AND CONDUIT	DIVISION 26	CONTRACTOR	CONTRACTOR
	GROUNDING BUSBAR	DIVISION 26	CONTRACTOR	CONTRACTOR
	GROUND AND BONDING TO EQUIPMENT	27 12 00	CONTRACTOR	CONTRACTOR
	DISCONTINUOUS PATHWAYS (J-HOOKS, RINGS)	27 11 50	CONTRACTOR	CONTRACTOR
	CONTINUOUS PATHWAYS (TRAY)	27 11 50	NOT IN CONTRACT	NOT IN CONTRACT
COMMUNICATIONS	CABLING	27 15 00	CONTRACTOR	CONTRACTOR
	FACEPLATES, CABLE TERMINATIONS AND TESTING	27 15 00 / 27 08 00	CONTRACTOR	CONTRACTOR
	RACKS, ENCLOSURES, LADDER TRAY	27 11 00	CONTRACTOR	CONTRACTOR
NETWORK ACTIVE DEVICES	WIRELESS ACCESS POINTS (WAPS)	N/A	OWNER	CONTRACTOR
	NETWORK SWITCHES	N/A	OWNER	OWNER
	SERVERS / COMPUTERS / PHONES	N/A	OWNER	OWNER
	UPS AND PDU	27 11 00	CONTRACTOR	CONTRACTOR
	CLOCKS	N/A	NOT IN CONTRACT	NOT IN CONTRACT
	MASS NOTIFICATION SYSTEM	N/A	NOT IN CONTRACT	NOT IN CONTRACT
	DISTRIBUTED ANTENNA SYSTEM (RADIO / CELL REPEATER OR BOOSTER)	N/A	NOT IN CONTRACT	NOT IN CONTRACT
AV	CABLING, FACEPLATES, CABLE TERMINATIONS AND TESTING	27 41 00 / 27 15 00	CONTRACTOR	CONTRACTOR
	DISPLAYS	27 41 00	CONTRACTOR	CONTRACTOR
	RACKS, ENCLOSURES, HOUSINGS	27 41 00	CONTRACTOR	CONTRACTOR
	AV EQUIPMENT	27 41 00	CONTRACTOR	CONTRACTOR
	PERFORMANCE SYSTEM EQUIPMENT (AUDITORIUM)	N/A	NOT IN CONTRACT	NOT IN CONTRACT
	CABLE / ANTENNA TELEVISION (CATV)	27 41 33	CONTRACTOR	CONTRACTOR
	PROJECTION SCREENS	N/A	NOT IN CONTRACT	NOT IN CONTRACT
	PUBLIC ADDRESS SYSTEMS	27 51 16	CONTRACTOR	CONTRACTOR
	SOUND MASKING	N/A	NOT IN CONTRACT	NOT IN CONTRACT
ELECTRONIC SECURITY	CABLING	28 13 00 / 27 15 00	CONTRACTOR	CONTRACTOR
	FACEPLATES, CABLE TERMINATIONS AND TESTING	28 13 00	CONTRACTOR	CONTRACTOR
	ENCLOSURES, HOUSINGS, POWER SUPPLIES	28 13 00	CONTRACTOR	CONTRACTOR
	ACCESS CONTROL - DOOR DEVICES	28 13 00	CONTRACTOR	CONTRACTOR
	ACCESS CONTROL - CONTROLLER / SERVER	28 13 00	CONTRACTOR	CONTRACTOR
	ENTRY INTERCOM	N/A	NOT IN CONTRACT	NOT IN CONTRACT
	SURVEILLANCE - CAMERAS	28 23 00	CONTRACTOR	CONTRACTOR
	SURVEILLANCE - RECORDING / SERVERS (NVR) AND LICENSES	28 23 00	CONTRACTOR	CONTRACTOR
	INTRUSION DETECTION (MOTION, GLASS BREAK)	N/A	NOT IN CONTRACT	NOT IN CONTRACT
NURSE CALL	CABLING	27 52 23	CONTRACTOR	CONTRACTOR
	FACEPLATES, CABLE TERMINATIONS AND TESTING	27 52 23	CONTRACTOR	CONTRACTOR
	ENCLOSURES, HOUSINGS, POWER SUPPLIES	27 52 23	CONTRACTOR	CONTRACTOR
	DEVICES (PULL STATIONS, DOME LIGHTS)	27 52 23	CONTRACTOR	CONTRACTOR

These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MM
Drawn By: MM
Reviewed By: JB
Project No: 1203001
Date: 08/15/22
Submittal Level: 100% CDs
Sheet Title:

FIRST FLOOR
TECHNOLOGY PLAN

Sheet No.:
T1.0


GENERAL NOTES (THIS SHEET)


1. THE INSTALLATION OF NEW LOW-VOLTAGE PATHWAYS SHOULD BE COORDINATED IN THE FIELD WITH ALL TRADES BEFORE COMMENCING WORK.
2. ALL PRIMARY CABLE PATHWAYS TO BE SUPPORTED BY METALLIC JHOOKS, AND SIZED AS REQUIRED TO SUPPORT INITIAL CABLE QUANTITIES PLUS GROWTH PER SPECIFICATIONS.
3. TELECOM CONTRACTOR TO COORDINATE WITH OWNER, ELECTRICAL CONTRACTOR AND FURNITURE INSTALLER. ELECTRICAL CONTRACTOR TO PROVIDE PATHWAY FROM ABOVE FINISHED CEILING DOWN TO FURNITURE PATHWAYS AND INSTALLATION PLATES FOR DATA CABLING. TELECOM CONTRACTOR TO COORDINATE WITH FURNITURE INSTALLER FOR COMPATIBLE TERMINATION HARDWARE FOR DATA OUTLETS.
4. OWNER TO PROVIDE HEAT MAP SHOWING WIRELESS ACCESS POINT LOCATIONS FOR RENOVATED SPACE.

KEY NOTES (X) (THIS SHEET)


1. EXISTING SIRIUS XM HEAD END TO BE RELOCATED. COORDINATE FINAL LOCATION WITH OWNER.
2. CONTRACTOR TO PROVIDE AND INSTALL (1) 12-STRAND OS2 FIBER OPTIC CABLE FROM CORE IT TO SLE MOB 1ST FLOOR IDF. ROUTING AND PATHWAY TO BE COORDINATED WITH SLE IT PRIOR TO COMMENCEMENT OF WORK.
3. EXISTING PAGING HEADEND TO REMAIN. CONTRACTOR TO COORDINATE WITH OWNER TO ENSURE EXISTING HEAD END HAS ADEQUATE CAPACITY TO SUPPORT NEW SPEAKERS IN RENOVATED SPACE. CLINIC AND REHAB SPACES SHALL BE SERVED BY SEPARATE ZONES.

ALTERATION SHADING LEGEND


 AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



2 EXISTING IT ROOM TO REMAIN
SCALE: 1/4" = 1'-0"



1 FIRST FLOOR TECHNOLOGY PLAN
SCALE: 1/8" = 1'-0"



These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: MM

Drawn By: MM

Reviewed By: JB

Project No: 1203001



Date: 08/15/22

Submittal Level: 100% CDs


Sheet Title:

TECHNOLOGY DIAGRAMS


Sheet No.: T3.0




3 PAGING SYSTEM SIGNAL FLOW
SCALE: 1/2" = 1'-0"



4 DISPLAY SIGNAL FLOW
SCALE: 1/2" = 1'-0"



2 RECEPTION 100 DISPLAY ELEVATION
SCALE: 1/2" = 1'-0"




1 CONF 117 DISPLAY ELEVATION
SCALE: 1/2" = 1'-0"

These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date


Designed By:	MM
Drawn By:	MM
Reviewed By:	JB
Project No:	1203001
Date:	08/15/22
Submittal Level:	100% CDs
Sheet Title:	TECHNOLOGY DETAILS
Sheet No.:	T4.0




OPERATIONAL THEORY:

1. DOOR SHALL BE LOCKED AND READER IN SECURE STATE AS DOOR IS APPROACHED.
2. WHEN A VALID CARD IS PRESENTED, THE READER BEEPS, THE LED TURNS GREEN, AND THE ELECTRIC STRIKE OR MAGNETIC LOCK DE-ENERGIZES, ALLOWING THE DOOR TO OPEN.
3. THE ELECTRIC STRIKE OR MAGNETIC LOCK SHALL RE-LOCK WHEN THE DOOR POSITION SWITCH DETECTS THE DOOR HAS OPENED.
4. TO EXIT FROM THE SECURE SIDE, THE REQUEST-TO-EXIT SENSOR WILL DISENGAGE THE ELECTRIC STRIKE OR MAGNETIC LOCK AND THE DOOR WILL MOMENTARILY UNLOCK.
5. THE ELECTRIC STRIKE OR MAGNETIC LOCK SHALL RE-LOCK WHEN THE DOOR POSITION SWITCH DETECTS THE DOOR HAS OPENED.
5. IF A FIRE ALARM IS ACTIVATED IN THE BUILDING, THE FIRE ALARM MODULE SHALL ACTIVATE THE DOOR LOCK OVERRIDE, ALL DOORS WILL UNLOCK AUTOMATICALLY, AND WILL REMAIN UNLOCKED UNTIL THE FIRE ALARM MODULE IS REST.
6. ADA PUSH PADS, WHERE PRESENT ON PLANS, WILL ONLY ACTIVATE IF PRESSED WITHIN 5 SECONDS OF A VALID CREDENTIAL. IN CASE OF FIRE ALARM, THE DOOR OPERATOR SHALL LOSE POWER VIA PAMHIGH VOLTAGE RELAY TO ALLOW FREE EGRESS.


8 SINGLE DOOR DETAIL
SCALE: 1/8" = 1'-0"




3 CONFERENCE ROOM DISPLAY BACKBOX DETAIL
SCALE: 1/8" = 1'-0"




7 COMM. OUTLET - INTERIOR CAMERA
SCALE: 1 1/2" = 1'-0"




5 COMM. OUTLET - WAP
SCALE: 1 1/2" = 1'-0"




2 TYPICAL DATA OUTLET
SCALE: 3/4" = 1'-0"




9 COMM. OUTLET - POLE MOUNT
SCALE: 1 1/2" = 1'-0"



6 2' x 2' DROP-TILE CEILING MOUNTED PAGING SPEAKER
SCALE: 12" = 1'-0"



4 DS DISPLAY BACKBOX DETAIL
SCALE: 6" = 1'-0"



- NOTES: (REFER TO SPECIFICATIONS SECTION 27 11 50 FOR ADDITIONAL INFORMATION)
- 1) CABLE HANGERS SHALL BE SPACED NO FURTHER THAN 4' O.C., NOT AT REGULAR REPEATING DISTANCE.
 - 2) CABLE HANGERS SHALL BE SECURED TO STRUCTURAL STEEL UTILIZING APPROPRIATE FASTENERS WHICH SHALL MEET LOCAL SEISMIC CODES.
 - 3) REFER TO ARCHITECTURAL DRAWINGS FOR DECK AND SUSPENDED CEILING TYPE, DETAILS SHOWN FOR CLARITY ONLY.

1 NON-CONTINUOUS CABLE SUPPORT
SCALE: 1/8" = 1'-0"

PROJECT NAME:
PHASE 1 - PULMONARY CLINIC
SAINT LUKE'S EAST HOSPITAL
FIRST FLOOR MOB
100 NE SAINT LUKE'S BLVD.
LEE'S SUMMIT, MO 64086

These drawing and the designs here illustrated are the sole property of BranchPattern, Inc. and may not be reproduced in whole or in part without express written permission.

Description	Date

Designed By: **MM**

Drawn By: **MM**

Reviewed By: **JB**

Project No: **1203001**

Date: **08/15/22**

Submittal Level: **100% CDs**

Sheet Title:

TECHNOLOGY
DEMOLITION PLAN

Sheet No.:

TD1.0


GENERAL NOTES (THIS SHEET)



1. I.T. ROOM SHALL REMAIN AND BE KEPT OPERATIONAL TO SERVE ALL EXISTING TO REMAIN AREAS AND SERVICES THROUGHOUT CONSTRUCTION UNTIL ALL PHASES ARE COMPLETE, AT WHICH TIME THE CONTRACTOR WILL BE RESPONSIBLE FOR DEMOLITION OF ALL UNUSED EQUIPMENT AND CABLING WITHIN THE ROOM. OWNER HAS FIRST RIGHT OF SALVAGE WITH ANY UNUSED ACTIVE EQUIPMENT AND SYSTEMS.
2. AFTER ALL NEWLY RENOVATED CABLING AND SYSTEMS ARE INSTALLED, CONTRACTOR SHALL COORDINATE WITH OWNER TO CONSOLIDATE EXISTING TO REMAIN CABLING/SYSTEMS WITH NEWLY RENOVATED CABLING AND SYSTEMS.
3. THROUGHOUT THE PHASES, DEMOLITION MAY OCCUR IN AREAS WHERE EXISTING LOW-VOLTAGE CABLING IS STILL IN USE. PRIOR TO DEMOLITION OF ANY HORIZONTAL CABLING, ALL EXISTING CABLING MUST BE VERIFIED BY THE CONTRACTOR AND OWNER, AND PATCH CABLES REMOVED BY OWNER I.T. DEPARTMENT TO AVOID DISRUPTION OF SERVICES AND DAMAGE TO ACTIVE ELECTRONICS

DEMOLITION KEY NOTES ☒ (THIS SHEET)

1. EXISTING IT ROOM AND HARDWARE/SYSTEMS SHALL REMAIN INTACT TO SERVE EXISTING CABLING NOT IN SCOPE OF WORK THROUGHOUT ALL PHASES OF PROJECT. ONCE FINAL PHASE OF PROJECT IS COMPLETE, OWNER WILL HAVE THE FIRST RIGHTS OF SALVAGE OF ALL IT ROOM HARDWARE, ACTIVE ELECTRONICS, ETC. CONTRACTOR WILL THEN BE RESPONSIBLE FOR REMOVING ALL REMAINING HARDWARE AND / OR EQUIPMENT AS IDENTIFIED BY OWNER.
2. CONTRACTOR TO DEMO EXISTING COPPER HORIZONTAL CABLING IN NEW SCOPE OF WORK BACK TO POINT OF ORIGIN.
3. EXISTING FIBER AND COPPER BACKBONE CABLING TO REMAIN THROUGHOUT DURATION OF PROJECT.

ALTERATION SHADING LEGEND

-  AREA NOT WITHIN ALTERATION SCOPE. DEVICES IN SPACES OUTSIDE OF THE SCOPE THE ALTERATION SCOPE ARE EXISTING TO REMAIN UNLESS NOTED OTHERWISE, AND ARE SHOWN FOR REFERENCE ONLY.



1

FIRST FLOOR TECHNOLOGY - DEMOLITION

SCALE: 1/8" = 1'-0"

