

VAN DEURZEN AND ASSOCIATES, P.A. CONSULTING STRUCTURAL ENGINEERS 11011 KING STREET, SUITE 130 COMMERCE TERRACE BUILDING D OVERLAND PARK, KANSAS 66210 (913) 451 - 6305 FAX (913) 451 - 1021

Address or Project Name	City	Inspector		Date		Time
370 NW Patch Ct	Lee's Summit	Bob Rowe		10/5/2022		10:45
Permit #		Contractor		General/Owner		
PRRES 2022 2881		Concrete Design of KC		JFE		
Inspection Type		Bill To				
Slab - Basement & Garage		JFE				
		Current Temp	24 hr High		24 hr Low	
Basement and Garage Slabs and Deck Piers						
Site Conditions (all must comply if applicable)		Slab (Basement or Garage As Marked)				
City approved plot plan and building construction		Formed & Reinforced Per City Approved Dwgs				
plans on site.		Suspended floor slab (over usable space)				
Erosion control is in place and functional (inspection		Garage structural slab per approved plan				
shall not be performed if erosion control is not		Basement structural slab per approved plan.				
functionally in compliance with the City		6 mil vapor barrier installed – not required for garage				
requirements).	slab					
Building setbacks per approved plot plan		✓ Isolation rings or block-outs are provided over pier pads				
Soils – bearing capacity as determined by:		for columns				
Bearing on undisturbed soil @ 1,500 psf		Rubber Membrane installed where required metal				
Soils report (comment or attach report)		Footings				
Fill per engineering report		Reinforced per city approved plans.				
Free of organic material	Deck/porch/balcony piers					
Cold weather protection <i>Type:</i>		Footing – width, depth and location				
Footing Elevation Certification		Solid jumps				
"Footing Elevation Certification" form completed by		Frost depth (min. 36 inches)				
contractor has been reviewed for completeness and		Column pads – basement				
allowable tolerances.		Column pads – basement structural slab				
Drilled Piers (refer to footings for deck piers)		Column pads – garage steel column				
Pier foundation per approved plan		Column/pad at garage structural slab				
Quantity:		Undermined fdn elements (recommendation in				
Size:		comments and/or attached report)				
Depth:		Ufer Ground attachment rod provided				
Bearing:		Location:				

Approved basement and garage slabs. Approved three (3) deck piers 24" x 32-36" on rock. This is to certify that I, or qualified individuals working under my direction, inspected and/or tested the above checked items in accordance with the applicable City approved building and site plans, codes and engineering details.

Signed

M. Streeter

10/5/2022

The work is complete and to the best of my knowledge was found to be in substantial compliance with the approved plans and specifications.



Date