

Version 21.80.417 Powered by iStruct[™] Dataset: 22022301.1 This placement plan is to be used as an installation guide only. It is meant to be used in conjunction with the manufacturers installation guide, the architectural and structural drawings, and not to replace them. R.E.O. ENGINEERING, P.C.

Scale 1/4 inch : 1 ft.

GENERAL NOTES

1. FLOOR JOISTS TO BE 11-7/8" LPI20 PLUS @ 16" O.C. TYP. UNLESS OTHERWISE NOTED 2. ALL BLOCKING PER STRUCTURAL PLAN 3. LOADING TO BE 40 PSF LL - 15 PSF DL

AMERHART

400 MARSHVIEW DRIVE SUN PRAIRIE, WI 53590 1-800-879-7123 1-608-834-2253

ADDITIONAL NOTES

. ALWAYS READ PRODUCT BROCHURE BEFORE INSTALLATION OF EWP PRODUCTS. 2. REFER TO HOLE CHARTS PRIOR TO DRILLING

PRODUCT. 3. THIS DOCUMENT IS INTENDED SOLEY AS A PLACEMENT PLAN. IT IS TO BE REVIEWED BY THE ENGINEER OF RECORD AND MUST MEET HIS/HER APPROVAL PRIOR TO INSTALLATION OF OUR PRODUCT.

. THIS DOCUMENT IS NOT TO BE USED AS A REPLACEMENT FOR YOUR ORIGINAL STRUCTURAL PLANS.

5. LAYOUT, QUANTITY AND LENGTH TO BE VERIFIED BY CONTRACTOR.

IF WALLS ARE SPECIFIED IN THIS QUOTE, CONTRACTOR MUST VERIFY ALL DIMENSIONS AND ROUGH OPENING SIZES PRIOR TO CONSTRUCTION OF WALL. ROUGH OPENING SIZES ARE ESTIMATES ONLY. TALL WALL IS DESIGNED FOR VERTICAL LOADS AND DIRECT WIND LOADS ONLY. INLINE LATERAL BRACING OF THE BUILDING DIAPHRAGM IS TO BE ACCOUNTED FOR BY THE BUILDING DESIGNER/ENGINEER

idth	Depth	Qty	Plies	Pcs	Length
2.5	9.5			7	48-0-0
2.5	9.5			8	36-0-0
2.5	9.5			2	32-0-0
2.5	9.5			1	30-0-0
2.5	9.5			1	28-0-0
2.5	9.5			7	26-0-0
2.5	9.5			8	18-0-0
2.5	9.5			15	16-0-0
2.5	9.5			21	8-0-0
2.5	9.5			8	6-0-0
idth	Depth	Qty	Plies	Pcs	Length
2.5	9.5			39	2-0-0
idth	Depth	Qty	Plies	Pcs	Length
125	9.5			20	12-0-0

'idth	Depth	Qty	Plies	Pcs	Length
1.75	9.25	1	2	2	18-0-0
1.75	9.25	1	2	2	14-0-0
1.75	9.25	2	2	4	6-0-0
1.75	9.25	1	2	2	4-0-0

		Beam/Girder	Supported Member
Skew	Slope	fasteners	fasteners
		14 16d	6 10d
		8 10d	









