


CONSTRUCTION PLANS  
FOR  
ISPERING WOODS PO  
CITY OF LEE'S SUMMIT  
JACKSON COUNTY, MISSOURI

DESCRIPTION


PROPERTY DESCRIPTION  
CONTAINING 105,623 SQUARE FEET OR 2.42 ACRES

TRACT C OF WHISPERING WOODS, 1ST PLAT, LOTS 1-33



Sheet List Table	
Sheet Number	Sheet Title
C1.0	TITLE SHEET
C1.1	GENERAL NOTES
C2.0	OVERALL SITE PLAN
C2.1	SITE PLAN
C3.0	GRADING PLAN
C3.1	SPOT ELEVATION PLAN
C3.2	SIDEWALK RAMP PLAN
C3.3	EROSION CONTROL PLAN
C3.4	UTILITY PLAN
C4.0	DETAILS
C4.1	DETAILS
L1.0	LANDSCAPE PLAN

UTILITY SERVICE NUMBERS	
SPECTRUM	886-874-2389
EVERGY	816-220-5213
SPIRE GAS	816-399-9633
LEE'S SUMMIT PUBLIC WORKS	816-969-1800
CITY PLANNING & DEVELOPMENT	816-969-1600
FIRE DEPARTMENT	816-969-1300



APPROVED:

City Engineer

Date \_\_\_\_\_

## DEVELOPER:

WHISPERING WOODS LAND, L.L.C.  
803 P.C.A. ROAD  
WARRENSBURG, MO 64093  
AGENT: RICK FRYE  
PHONE: 816.564.2230  
FAX: 660.429.1801

[illegible]

SHAWN DUKE - ENGINEER  
MO PE#2013006489

# WHISPERING WOODS POOL

TITLE SHEET

**LEE'S SUMMIT, MO**

**SNYDER & ASSOCIATES**  
**ENGINEERS & PLANNERS, INC.**

---

802 FRANCIS STREET  
ST. JOSEPH, MISSOURI 64501  
816-364-5222 | [www.snyder-associates.com](http://www.snyder-associates.com)



Project No:	120.0484.11
Sheet	C1.0




C:\Users\jshewey\AppData\Local\Temp\AutoCAD LT 2020\Projects\2020\120.0484\_1\1\CADD\SP\_1200484\_Pool-Title.dwg RYAN SHEWEY, GENERAL NOTES, 2022/12/07, 9:17 AM, ANSI FULL BLEED D (34.00 X 22.00 INCHES)

25. CONNECTIONS TO EXISTING MANHOLES SHALL BE CORE DRILLED AND CONNECTED WITH A WATERTIGHT FERNCO GASKET OR APPROVED EQUAL. THE GASKET IS TO BE INSTALLED ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS.
26. ALL AREAS WHERE UTILITIES ARE TO BE INSTALLED IN FILL SHALL BE COMPACTED TO 95% TO 18 INCHES ABOVE THE LINE THEN EXCAVATED FOR CONSTRUCTION OF THE LINE.
27. THE CONTRACTOR WILL BE RESPONSIBLE FOR TESTING OF MANHOLES AND PIPES TO THE CITY OF LEE'S SUMMIT DESIGN & CONSTRUCTION MANUAL REQUIREMENTS.
28. THE ENDS OF ALL SANITARY SEWER STUBS SHALL BE SURVEYED AND MARKED BEFORE CONSTRUCTION.
28. ALL UTILITY STREET CROSSINGS SHALL BE BACKFILLED WITH FLOWABLE FILL, OR AB-3. IF CONTRACTOR CHOOSES TO USE OTHER SUITABLE MATERIALS, EXTENSIVE SOIL TESTING REQUIREMENTS WILL BE REQUIRED.
30. TRENCH CHECKS SHALL BE USED FOR ALL SANITARY SEWER STUBS.

1. THE CONTRACTOR SHALL CONTACT THE CITY'S DEVELOPMENT SERVICES ENGINEERING INSPECTORS 48 HOURS PRIOR TO ANY LAND DISTURBANCE WORK AT (816) 969-1200.
2. GRADING CONTRACTOR SHALL BE RESPONSIBLE FOR THE CONTROL OF EROSION AND SILTATION DURING ALL PHASES OF CONSTRUCTION.
3. PRIOR TO ORDERING PRECAST STRUCTURES: SHOP DRAWINGS SHALL BE SUBMITTED TO THE DESIGN ENGINEER FOR APPROVAL. UPON APPROVAL THESE SHALL BE SUBMITTED TO THE CITY OF LEE'S SUMMIT FOR REVIEW.
4. ALL WATER LINES, SANITARY SEWER LINES, AND STORM WATER DRAINAGE CROSSINGS SHALL BE IN PLACE OR A CASING PIPE PROVIDED FOR FUTURE INSTALLATION PRIOR TO BASE AND SURFACE ASPHALT COURSES.
5. SIDEWALKS ARE SHOWN FOR INFORMATIONAL PURPOSES ONLY UNLESS OTHERWISE NOTES. HOWEVER, THE CONTRACTOR SHALL BE RESPONSIBLE FOR HANDICAP RAMP CONSTRUCTION IN CURBS.
6. REFER TO GRADING AND EROSION CONTROL SHEETS IN STREET AND STORM PLANS.
7. SITE TOPOGRAPHY TAKEN FROM SURVEY COMPLETED BY R.L. BUFORD & ASSOCIATES. CONTRACTOR TO VERIFY EXISTING CONDITIONS OF THE SITE THAT MAY NOT BE REPRESENTATIVE OF CONSTRUCTION PLANS.
8. PROTECT EXISTING TREES, SHRUBS, FENCE AND LANDSCAPING UNLESS SPECIFICALLY NOTED OTHERWISE ON PLANS. REPLACE ANY FENCE, TREES, SHRUBS, LANDSCAPING ITEMS, OR OTHER VEGETATION NOT SCHEDULED FOR REMOVAL THAT ARE DAMAGED DURING CONSTRUCTION OPERATIONS WITHOUT ADDITIONAL COMPENSATION.
9. NO OIL/GAS WELLS ARE PRESENT ON PROPERTY, PER MoDNR.

Snyder & Associates Engineers & Planners, Inc.  
Missouri State Certificate of Authority #2006008544



802 FRANCIS STREET

**SNYDER & ASSOCIATES**  
ENGINEERS & PLANNERS, INC.



Sheet C1.1










\\P000000\2020\120\0484.1\TCD\SSP\_1200484\_1200484.dwg, RYAN SNEYDER, SPOT ELEVATION PLAN, 2022/12/07 9:15 AM, ANSI FULL BLEED D (34.00 X 22.00 INCHES)

LEGEND:

- 870- = EXISTING INDEX CONTOUR
- 870- = NEW INDEX CONTOUR



WHISPERING WOODS POOL

SPOT ELEVATION PLAN

LEE'S SUMMIT, MO

**SNYDER & ASSOCIATES**  
ENGINEERS & PLANNERS, INC.



Project No: 120.0484.11

Sheet C3.1



SHAWN DUKE - ENGINEER  
MO PE#2013006489

MARK	REVISION	DATE	BY
Engineer: SD	Checked By: SD	Scale: 1" = 10'	
Technician: JS	Date: 04-26-2022	T-R-S: 47N-32W-24	

Sheet C3.1

Snyder & Associates Engineers & Planners, Inc.  
Missouri State Certificate of Authority #2006008544










c:\p\proj\2020\120.0484\_1\120.0484\_Pool Utility.dwg RYAN SNEYDER UTILITY PLAN 2021/207 8:18 AM AND FULL BLEED (34.00" X 22.00" INCHES)



MARK	REVISION	DATE	BY
Engineer: SD	Checked By: SD	Scale: 1" = 10'	
Technician: JS	Date: 04-26-2022	T-R-S: 47N-32W-24	
Snyder & Associates Engineers & Planners, Inc. Missouri State Certificate of Authority #2006060544			

Sheet C3.4



SHAWN DUKE - ENGINEER  
MO PE#2013006489

WHISPERING WOODS POOL

UTILITY PLAN

LEE'S SUMMIT, MO

**SNYDER & ASSOCIATES**  
ENGINEERS & PLANNERS, INC.



802 FRANCIS STREET  
ST. JOSEPH, MISSOURI 64501  
816-364-5222 | www.snyder-associates.com



Project No: 120.0484.11


Sheet C3.4










U:\Projects\2020\120.0484.1CADD\SP-120.0484.1SP.dwg, RYAN SNEYDER, DETAILS, 2022/12/07 5:18 AM, ANSI FULL BLEED D (34.00 X 22.00 INCHES)




ASPHALT SECTION  
NO SCALE



JOINT PAVING DETAILS  
NOT TO SCALE



ACCESSIBLE SIGN & SYMBOL DETAILS  
NO SCALE



MARK	REVISION	DATE	BY
Engineer: SD	Checked By: SD	Scale: 1" = 20'	
Technician: JS	Date: 04-26-2022	T-R-S: 47N-32W-24	

Sheet C4.1  
Snyder & Associates Engineers & Planners, Inc.  
Missouri State Certificate of Authority #200608544



SHAWN DUKE - ENGINEER  
MO PE#2013006489

WHISPERING WOODS POOL

DETAILS

LEE'S SUMMIT, MO

802 FRANCIS STREET  
ST. JOSEPH, MISSOURI 64501  
816-364-5222 | www.snyder-associates.com

SNYDER & ASSOCIATES  
ENGINEERS & PLANNERS, INC.




Project No: 120.0484.11  
Sheet C4.1





\\p000000\2021\121.0484.11\CD\DDSP\_120.0484\_120.0484.dwg, RYAN SNEYDER, LANDSCAPE PLAN, 2021.2017, 9:18 AM, ANSI FULL BLEED D (34.00 X 22.00 INCHES)



BUFFER AREA = 4,285 S.F.  
STREET FRONTAGE = 80 FT

LANDSCAPE REQUIRED

- 1 SHADE TREE PER 1,000 S.F. = 4.29 TREES
- 1 ORNAMENTAL TREE PER 500 S.F. = 8.57 TREES
- 1 EVERGREEN TREE PER 300 S.F. = 14.28 TREES
- 1 SHRUB PER 200 S.F. = 21.43 SHRUBS
- 1 STREET TREE PER 30 FT STREET FRONTAGE = 3 STREET TREES
- 1 SHRUB PER 20 FT STREET FRONTAGE = 4 STREET SHRUBS
- 2 SHRUBS PER 5000 S.F. OPEN AREA = 3.63 SHRUBS
- 1 TREE PER 5000 S.F. OPEN AREA = 1.81 TREES
- 12 SHRUBS PER 40 FT PARKING LOT SCREENING

LANDSCAPE PROVIDED

- 5 TREES
- 9 TREES
- 15 TREES
- 22 SHRUBS
- 3 STREET TREES
- 4 STREET SHRUBS
- 4 OPEN AREA SHRUBS
- 2 OPEN AREA TREES
- 14 SCREENING SHRUBS

SHADE TREES			ORNAMENTAL TREES			EVERGREEN TREES			SHRUBS		
SYMBOL	QUANTITY	SIZE	SYMBOL	QUANTITY	SIZE	SYMBOL	QUANTITY	HEIGHT	SYMBOL	QUANTITY	SIZE
	3	3" CAL.		4	3" CAL.		5	8 FT		10	24" B&B
	2	3" CAL.		4	3" CAL.		5	8 FT		8	24" B&B
				6	3" CAL.		5	8 FT		9	24" B&B
										9	24" B&B
										8	24" B&B

= AREA TO BE SODDED

0 10  
FEET

MARK	REVISION	DATE	BY
Engineer: SD	Checked By: SD	Scale: 1" = 10'	
Technician: JS	Date: 04-26-2022	T-R-S: 47N-32W-24	

Snyder & Associates Engineers & Planners, Inc.  
Missouri State Certificate of Authority #200608544

SHAWN DUKE - ENGINEER  
MO PE#2013006489

STATE OF MISSOURI  
SHAWN DUKE  
NUMBER  
PE-2013006489  
PROFESSIONAL ENGINEER

WHISPERING WOODS POOL

LANDSCAPE PLAN


LEE'S SUMMIT, MO

**SNYDER & ASSOCIATES**  
ENGINEERS & PLANNERS, INC.

802 FRANCIS STREET  
ST. JOSEPH, MISSOURI 64501  
816-364-5222 | www.snyder-associates.com


Project No: 120.0484.11

Sheet L1.0




FRONT EL.


SIDING STUCCO AND STONE ALL SIDES  
COLORS TO BE EARTHTONES



LEFT EL.  
1/8" = 1'-0"




REAR EL.  
1/8" = 1'-0"



RIGHT EL.  
1/8" = 1'-0"

Review and Approval  
Structural Only

David Mezger Engineering LLC  
212 NE Circle Dr.  
Kansas City, MO 64116



BUILD IN ACCORDANCE WITH  
2018 INTERNATIONAL  
BUILDING CODE AND LOCAL  
CODES.

POOL HOUSE  
1901 SW RIVER RUN DR  
LEE SUMMIT MO


SCALE  
1/4" = 1'-0"

DATE  
5-27-22

PLAN NO.  
3781

SHEET NO.  
1 OF 5






FOUNDATION PLAN

Review and Approval  
Structural Only

David Mezger Engineering LLC  
212 NE Circle Dr.  
Kansas City, MO 64116



BUILD IN ACCORDANCE WITH  
2018 INTERNATIONAL  
BUILDING CODE AND LOCAL  
CODES.


POOL HOUSE  
1901 SW RIVER RUN DR  
LEE SUMMIT MO

SCALE  
1/4" = 1'-0

DATE  
5-27-22

PLAN NO.  
3781


SHEET NO.  
2 OF 5



MAIN FLOOR  
POOL HOUSE  
522 SF FINISHED

Review and Approval  
Structural Only

David Mezger Engineering LLC  
212 NE Circle Dr.  
Kansas City, MO 64116



BUILD IN ACCORDANCE WITH  
2018 INTERNATIONAL  
BUILDING CODE AND LOCAL  
CODES.

POOL HOUSE  
1901 SW RIVER RUN DR  
LEE SUMMIT MO

SCALE  
1/4" = 1-0

DATE  
5-27-22

PLAN NO.  
3781

SHEET NO.  
3 OF 5



ENERGY CONSERVATION CODE  
THE FOLLOWING VALUES ARE NEEDED.

R-15 IN WALLS

R-49 IN ATTICS

R-38 IN VAULTS  
R-30 REDUCTION FOR VAULTS IS ONLY FOR 500 SF  
PF AREA

R-19 IN FLOORS OVER UNCONDITIONED SPACES


R-10 IN CRAWL SPACE WALLS

BASEMENT WALLS R-13 CAVITY OR R-10 CONTINUOUS


SLABS SHALL BE R-10 FOR A DEPTH OF 2 FOOT

A WINDOW U FACTOR OF .35 OR BETTER


DUCTWORK NEEDS TO HAVE AN R-8 VALUE




1. DWELLING / GARAGE OPENINGS BETWEEN GARAGE AND SLEEPING PURPOSES SHALL NOT BE PERMITTED. OTHER OPENINGS SHALL BE EQUIPPED WITH SOLID WOOD OR STEEL DOORS NOT LESS THAN 1-3/8" THICK OR 20 MINUTE RATED DOORS, WITH SELF CLOSING DEVICES REQUIRED FOR GARAGE / DWELLING SEPERATION DOORS R302.5.1
2. WHOLE HOUSE MECHANICAL VENTILATION SYSTEM IS REQUIRED FOR ANY DWELLING IN COMPLIANCE WITH IRC M 1505
3. CARBON MONOXIDE DETECTORS REQUIRED IRC R 315
4. STEEL COLUMNS SHALL BE MINIMUM SCHEDULE 40 R407.3
5. DECK SHALL BE BUILT PER TABLES 507.2 , 507.2.1, 507.3, 507.6, 507.5.1(1)&(2), 507.5, AND 507.6
6. STUDS SHALL BE CONTINUOUS BETWEEN FLOOR, CEILING AND OR ROOF DIAPHRAGMS R602.3
7. ADDED REQUIREMENTS FOR WINDOW FALL PROTECTION R312.2
8. NEW PROVISIONS FOR ATTACHMENT OF RAFTERS, TRUSSES AND ROOF BEAMS R802.3.1 R802.11
9. INSULATION REQUIRED FOR ALL BASEMENT WALLS ( INCLUDING UNFINISHED BASEMENTS) N1102.1
10. EXTERIOR WINDOWS/DOORS SHALL HAVE U-FACTOR 0.35 AND GLAZING SHALL HAVE SOLAR HEIGTH GAIN FACTOR OF 0.40 N1102.1
11. HOUSE LEAKAGE AND DUCT LEAKAGE PERFORMANCE STANDARDS EFFECTIVE JANUARY 1, 2014. A SAMPLE TESTING PROGRAM WILL BE IMPLEMENTED OCTOBER 1, 2012 KCBRC N1102.4.1.2 N1103.2.2
12. LIGHTING FIXTURES PENETRATING THE THERMAL ENVELOPE ( E.G. CAN LIGHTS IN ATTIC ) SHALL BE IC- RATED, LEAKAGE- RATED AND SEALED TO THE GYPSUM WALLBOARD N1102.4.4
- 13.PROGRAMMABLE THERMOSTAT REQUIRED N1103.1.1
14. AIR HANDLERS SHALL BE RATED FOR MAXIMUM 2 % AIR LEAKAGE RATE N1103.2.2.1
15. BUILDING CAVITIES USED AS RETURN AIR PLENUMS SHALL BE SEALED TO PREVENT LEAKAGE ACROSS THE THERMAL ENVELOPE KCBRC N1103.2.2
16. CERTAIN HOT WATER PIPES SHALL BE INSULATED N1103.4
17. ALL EXHAUST FANS SHALL TERMINATE TO THE BUILDING EXTERIOR M1507.2
18. MAKEUP AIR SYSTEM REQUIRED FOR KITHCHEN EXHAUST HOODS THAT EXCEED 400 CFM M1503.4
19. BUILDING CAVITIES IN A THERMAL ENVELOPE WALL ( INCLUDING THE WALL BETWEEN THE HOUSE AND GARAGE ) SHALL NOT BE USED AS RETURN AIR PLENUMS
20. AN AIR HANDLING SYSTEM SHALL NOT SERVE BOTH THE LIVING SPACE AND THE GARAGE M1601.6
21. A CONCRETE- ENCASED GROUNDING ELECTRODE ( 'UFER' GROUND ) CONNECTION SHALL BE PROVIDED TO THE ELECTRICAL SERVICE E3608.1
22. COMPLIANCE WITH THE REQUIRMENT AND SHOW CONNECTION AS NEEDED FOR ROOF BEAM, TRUS, RAFTER, AND GIRDER CONNECTION FOR UPLIFT PER IRC 802.11. ALL RAFTERS BE IN COMPLIANCE WITH IRC 502.11 AMENDED RAYMORE CODE



ROOF PLAN  
1/8 = 1-0  
ROOF PITCHES 8/12  
16" SOFFITS TYP.  
RAFTERS 2 X 6 DF NO 2 @ 16" O.C.  
HIPS AND RIDGES 2 X 8 DF NO 2



ALL CONCRETE EXPOSED TO  
WEATHER GARAGE SLABS  
FOOTINGS WALLS AND FLATWORK  
MUST HAVE 6% AIR ENTRAINMENT



#### PIER PADS

TYP. U.N.O. 3-0 X 3-0 X 12" PEIR PADS MIN.  
WITH # 4 REBAR, 6 EACH WAY

STUDS OVER 10-0 SHALL HAVE  
BLOCKING ALONG WALL MAX  
OF 6-0 O.C.

#### WINDOW SAFETY GLAZING PER 308


SAFETY GLAZING REQUIRED ALONG WALKING SURFACES AND STAIRS LOCATED WITHIN 36 INCHES HORIZONTALLY OF THE STEPS. SAFETY GLAZING REQUIRED IF EXPOSED SINGLE PANEL IS IN EXCESS OF 9 SQUARE FEET OR THE BOTTOM EDGE OF THE GLAZING IS LESS THAN 18 INCHES ABOVE THE FINISHED FLOOR.

SAFETY GLAZING REQUIRD WHERE THE NEAREST EXPOSED EDGE OF THE GLAZING IS WITHIN 24 INCHES OF EITHER VERTICAL EDGE OF THE DOOR IN A CLOSED POSITION AND WHERE THE BOTTOM EXPOSED EDGE OF THE GLAZING IS LESS THAN 60 INCHES ABOVE A WALKING SURFACE, SAFETY OR TEMPERED GLAZING IS REQUIRED.

WINDOWS ARE TO HAVE FALL  
PROTECTION PER IRC 312.2

#### WINDOW EGRESS REQUIREMENTS


BEDROOM WINDOW EGRESS MINIMUM FOR A DOUBLE HUNG WINDOW IS 34 INCH CLEAR WIDTH MIN. AND 24 INCH CLEAR HEIGHT MIN. WITH A CLEAR OPENABLE AREA OF 5.7 SQUARE FEET MIN.  
A CASEMENT OR SLIDER WINDOW MINIMUMS ARE 20 INCH CLEAR WIDTH MINIMUM AND 41 INCH CLEAR HEIGHT MINIMUM. WITH A MINIMUM 5.7 SQUARE FOOT OF OPENABLE AREA.  
OPENING OF EGRESS WINDOW NOT MORE THAN 42" FROM THE FLOOR



EGRESS WINDOW WELL AS NEEDED  
PER SECTION 308 MIN 3-0 X 3-0  
WITH LADDER

Review and Approval  
Structural Only

David Mezger Engineering LLC  
212 NE Circle Dr.  
Kansas City, MO 64116



BUILD IN ACCORDANCE WITH  
2018 INTERNATIONAL  
BUILDING CODE AND LOCAL  
CODES.

POOL HOUSE  
1901 SW RIVER RUN DR  
LEE SUMMIT MO

SCALE

1/4" = 1-0

DATE

5-27-22

PLAN NO.

3781

SHEET NO.

4 OF 5



EXPOSURE CATEGORY B • 39-FOOT MEAN ROOF HEIGHT • 10-FOOT WALL HEIGHT • 2 BRACED WALL LINES		MINIMUM TOTAL LENGTH (FEET) OF BRACED WALL PANELS REQUIRED ALONG EACH BRACED WALL LINE <sup>a</sup>					
Ultimate Design Wind Speed (mph)	Story Location	Braced Wall Line Spacing (feet)	Method LIB <sup>b</sup>	Method GB	Methods DWB, WSP, SFB, PBS, FCP, HPS, BV-WSP, ABW, PFH, PFC, CS-SFB	Methods CS-WSP, CS-G, CS-PF	
≤ 115		10	3.5	3.5	2.0	2.0	
		20	6.5	6.5	3.5	3.5	
		30	9.5	9.5	5.5	4.5	
		40	12.5	12.5	7.0	6.0	
		50	15.0	15.0	9.0	7.5	
		60	18.0	18.0	10.5	9.0	
		10	7.0	7.0	4.0	3.5	
		20	12.5	12.5	7.5	6.5	
		30	18.0	18.0	10.5	9.0	
		40	23.5	23.5	13.5	11.5	
		50	29.0	29.0	16.5	14.0	
		60	34.5	34.5	20.0	17.0	
		10	NP	10.0	6.0	5.0	
		20	NP	18.5	11.0	9.0	
		30	NP	27.0	15.5	13.0	
		40	NP	35.0	20.0	17.0	
		50	NP	43.0	24.5	21.0	
		60	NP	51.0	29.0	25.0	





FIGURE R602.10.6.1  
METHOD ABW—ALTERNATE BRACED WALL PANEL



FRONT ELEVATION

SECTION

4 mm, 1 foot = 304.8 mm.

FIGURE R602.10.6.2  
METHOD PFH—PORTAL FRAME WITH HOLD-DOWNS

METHODS, MATERIAL	MINIMUM THICKNESS	FIGURE	CONNECTION CRITERIA <sup>a</sup>	
			Fasteners	Spacing
Intermittent Bracing Methods	LIB Let-in-bracing		Wood: 2-8d common nails or 3-8d (2 1/2\"/>	Wood: per stud and top and bottom plates Metal: per manufacturer
	DWB Diagonal wood boards		2-8d (2 1/2\"/>	Per stud
	WSP Wood structural panel (See Section R604)		Exterior sheathing per Table R602.3(3) Interior sheathing per Table R602.3(1) or R602.3(2)	6\"/>
	BV-WSP <sup>b</sup> Wood structural panels with stone or masonry veneer (See Section R602.10.6.5)		8d common (2 1/2\"/>	4\"/>
	SFB Structural fiberboard sheathing		1 1/2\"/>	3\"/>
	GB Gypsum board		Nails or screws per Table R602.3.5 for exterior locations Nails or screws per Table R702.3.5 for interior locations	For all braced wall panel locations: 7\"/>
	PBS Particleboard sheathing (See Section R605)		For 3/4\"/>	3\"/>
	PCP Portland cement plaster		See Section R703.7 for maximum 16\"/>	6\"/>
	HPS Hardboard panel siding		1 1/2\"/>	4\"/>
	ABW Alternate braced wall		See Section R602.10.6.1	See Section R602.10.6.1

METHOD (See Table R602.10.4)	MINIMUM LENGTH <sup>a</sup> (inches)					CONTRIBUTING LENGTH (inches)
	8 feet	9 feet	10 feet	11 feet	12 feet	
DWB, WSP, SFB, PBS, FCP, HPS, BV-WSP	48	48	48	53	58	Actual <sup>b</sup>
GB	48	48	48	53	58	Double sided = Actual Single sided = 0.5 × Actual
LIB	55	62	69	NP	NP	Actual <sup>b</sup>
ABW	SDC A, B and C, ultimate design wind speed < 140 mph	28	32	34	38	42
	SDC D <sub>0</sub> , D <sub>1</sub> and D <sub>2</sub> , ultimate design wind speed < 140 mph	32	32	34	NP	NP
CS-G	Adjacent clear opening height (inches)	24	27	30	33	36
CS-WSP, CS-SFB	≤ 64	24	27	30	33	36
	68	26	27	30	33	36
	72	27	27	30	33	36
	76	30	29	30	33	36
	80	32	30	30	33	36
	84	35	32	32	33	36
	88	38	35	33	33	36
	92	43	37	35	35	36
	96	48	41	38	36	36
	100	—	44	40	38	38
	104	—	49	43	40	39
	108	—	54	46	43	41
	112	—	—	50	45	43
	116	—	—	55	48	45
	120	—	—	60	52	48
	124	—	—	—	56	51
	128	—	—	—	61	54
	132	—	—	—	66	58
	136	—	—	—	—	62
	140	—	—	—	—	66
	144	—	—	—	—	72
METHOD (See Table R602.10.4)	Supporting roof only	16	16	16	Note c	Note c
	Supporting one story and roof	24	24	24	Note c	Note c
PFH	PFG	24	27	30	Note d	Note d
CS-PF	SDC A, B and C	16	18	20	Note e	Note e
	SDC D <sub>0</sub> , D <sub>1</sub> and D <sub>2</sub>	16	18	20	Note e	Note e

For SI: 1 inch = 25.4 mm, 1 foot = 304.8 mm, 1 mile per hour = 0.447 m/s.  
NP = Not Permitted.  
a. Linear interpolation shall be permitted.  
b. Use the actual length where it is greater than or equal to the minimum length.  
c. Maximum header height for PFH is 10 feet in accordance with Figure R602.10.6.2, but wall height shall be permitted to be increased to 12 feet with pony wall.  
d. Maximum header height for PFG is 10 feet in accordance with Figure R602.10.6.3, but wall height shall be permitted to be increased to 12 feet with pony wall.  
e. Maximum header height for CS-PF is 10 feet in accordance with Figure R602.10.6.4, but wall height shall be permitted to be increased to 12 feet with pony wall.

METHODS, MATERIAL	MINIMUM THICKNESS	FIGURE	CONNECTION CRITERIA <sup>a</sup>	
			Fasteners	Spacing
Intermittent Bracing Methods	PFH Portal frame with hold-downs		See Section R602.10.6.2	See Section R602.10.6.2
	PFG Portal frame at garage		See Section R602.10.6.3	See Section R602.10.6.3
	CS-WSP Continuously sheathed wood structural panel		Exterior sheathing per Table R602.3(3) Interior sheathing per Table R602.3(1) or R602.3(2)	6\"/>
Continuous Sheathing Methods	CS-G <sup>a</sup> Continuously sheathed wood structural panel adjacent to garage openings		See Method CS-WSP	See Method CS-WSP
	CS-PF Continuously sheathed portal frame		See Section R602.10.6.4	See Section R602.10.6.4
	CS-SFB <sup>d</sup> Continuously sheathed structural fiberboard		1 1/2\"/>	3\"/>

For SI: 1 inch = 25.4 mm, 1 foot = 304.8 mm, 1 degree = 0.0175 rad, 1 pound per square foot = 47.8 N/m<sup>2</sup>, 1 mile per hour = 0.447 m/s.  
a. Adhesive attachment of wall sheathing, including Method GB, shall not be permitted in Seismic Design Categories C, D<sub>0</sub>, D<sub>1</sub> and D<sub>2</sub>.  
b. Applies to panels next to garage door opening where supporting gable end wall or roof load only. Shall only be used on one wall of the garage. In Seismic Design Categories D<sub>0</sub>, D<sub>1</sub> and D<sub>2</sub>, roof covering dead load shall not exceed 3 psf.  
c. Garage openings adjacent to a Method CS-G panel shall be provided with a header in accordance with Table R602.7(1). A full-height clear opening shall not be permitted adjacent to a Method CS-G panel.  
d. Method CS-SFB does not apply in Seismic Design Categories D<sub>0</sub>, D<sub>1</sub> and D<sub>2</sub>.  
e. Method applies to detached one- and two-family dwellings in Seismic Design Categories D<sub>0</sub> through D<sub>2</sub> only.




FIGURE R602.10.6.4  
METHOD CS-PF—CONTINUOUSLY SHEATHED PORTAL FRAME PANEL CONSTRUCTION

For SI: 1 inch = 25.4 mm, 1 foot = 304.8 mm.

Review and Approval  
Structural Only

David Mezger Engineering LLC  
212 NE Circle Dr.  
Kansas City, MO 64116



BUILD IN ACCORDANCE WITH  
2018 INTERNATIONAL  
BUILDING CODE AND LOCAL  
CODES.

POOL HOUSE  
1901 SW RIVER RUN DR  
LEE SUMMIT MO

SCALE  
1/4" = 1-0

DATE  
5-27-22

PLAN NO.

3781

SHEET NO.

5 OF 5




~~30x35~~ 30x50



50,000 gallon  
2 pumps  
2 Filters  
6 hour turnover

4 Skimmers  
8 Return valves  
6 Lights  
4 3 tread ladders

# Bonding grid





# BADU® Pro UVS Series

## Self-Priming High Flow Pump

Our flagship pump, the BADU® Pro was designed with pool service pros in mind. A drop-in replacement for both the Hayward® Super Pump® and Pentair® SuperFlo®, it directly replaces the majority of pumps on the market.

### Features

- The BADU Pro pump series saves you time & money while making your life simpler.
- Easily serviceable 4-bolt design & handle
- Lid lock ring that incorporates handles. These handles provide the user with a convenient way to easily remove the lid.
- Suction and Discharge comes equipped with quick disconnect unions as well as internal threads for easy installation and maintenance.
- Every pump is wet tested before leaving the Speck factory.
- Available with Variable Speed motors in 1.65, 2.25 and 2.7 THP.
- All variable speed models are equipped with an LED light in the basket lid, for ease of maintenance.
- Most variable speed models are Energy Star compliant and qualify for all applicable utility rebates.
- Variable Speed Motors also come with digital inputs, for easy connection to automation.
- All Models are additionally available with our Universal Automation Control Board, allowing for seamless communication with all major equipment manufacturers.
- The models use our imported French 20mm seal, allowing the pump to run dry for up to an hour.
- Most models can be ordered with 1.5" or 2.0" fittings.

### Part Numbers

#### Variable or Multi-Speed - Energy Star

Order #	Model #	THP	WEF	HHP	Volts	Amps	Motor/Frame	Port Size
<b>Standard Models</b>								
IG385-V165T-TUS	BADU Pro-III UVS	1.65	8.9	1.009	230/115	6.8/13.6	ODP/56	2.0"
IG385-V225T-TUS	BADU Pro-IV UVS	2.25	7.616	1.354	230	9.5	ODP/56	2.0"
IG385-V270T-TUS	BADU Pro-V UVS	2.7	7.766	1.405	230	11.1	ODP/56	2.0"

#### Models with Universal Automation Control Board

IG385-V165T-TCB	BADU Pro-III UVS	1.65	8.9	1.009	230/115	6.8/13.6	ODP/56	2.0"
IG385-V225T-TCB	BADU Pro-IV UVS	2.25	7.616	1.354	230	9.5	ODP/56	2.0"
IG385-V270T-TCB	BADU Pro-V UVS	2.7	7.766	1.405	230	11.1	ODP/56	2.0"

**NOTE:** The BADU Pro-IV UVS Model is not listed on Energy Star

Hayward® & Super Pump® are trademarks and/or registered trademarks of Hayward Industries, Inc.  
Pentair® & SuperFlo® are trademarks and/or registered trademarks of Pentair Inc. and/or its affiliated companies.

# SPECK X




BADU Pro-III UVS

### Trademarks and Certifications



Select BADU Pro models are ENERGY STAR certified

### Performance Curves




57,600 per 6 hrs

# TRITON® II SIDE MOUNT FILTERS

## FIBERGLASS SAND FILTER WITHOUT VALVES

### TRADEGRADE

2 pumps  
2 Filters



Triton II Side Mount Filter  
(Unions not included)

The original and still the industry standard. Our process creates a one-piece, fiberglass reinforced tank with UV resistant surface finish for years of strength and durability. This method locks in fiberglass, preventing fibers from "blooming" under harsh conditions.

### Featured Highlights

- Heavy-duty closure provides easy inspection, and features an easy-to-read pressure gauge with air relief valve
- Swing-away diffuser allows instant access to sand and all internal parts
- All internal parts are threaded for ease of service
- Internal air bleed
- Bulkhead connectors are threaded for easy installation and service
- Combination sand and water drain makes servicing and winterizing fast and easy
- Maximum Operating Pressure 50 psi

#### CALIFORNIA PROPOSITION 65 WARNING

⚠ **WARNING:** Cancer and Reproductive Harm.  
 ⚠ **AVERTISSEMENT:** Peut Causer le Cancer et des Dommages au Système Reproducteur.  
 ⚠ **ADVERTENCIA:** Cáncer y Daño Reproductivo.  
[www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

### Ordering Information

Product	Model	Effective Filtration Area (Sq. Ft.)	Flow Rate (GPM Comm)	Turnover Capacity (In Gal.)			Filter Media		All Sand Req'd (Lbs.)	Ctn Qty.	Ctn Wt. (Lbs.)
				8 Hour	10 Hour	12 Hour	Pea Gravel Req'd (Lbs.)	Sand Req'd (Lbs.)			
TRITON II SAND FILTERS											
140236	TR 40	1.92	38	18,240	22,800	27,360	50	125	175	1	25
140264	TR 60	3.14	63	30,240	37,800	45,360	75	250	325	1	40
140210	TR 100	4.91	74	35,520	44,400	53,280	150	450	600	1	65
140243	TR 140	7.06	106	50,880	63,600	76,320	275	650	925	1	75
TRITON II VALVE OPTIONS <sup>1</sup>											
261173	1-1/2 in. MPV, for sand filters (SM 10-3)									1	6
263079	2 in. PVC Slide valve w/o plumbing, for D.E. & sand filters									1	3
261049	2 in. HiFlow valve, no plumbing									1	7
261050	2 in. HiFlow w/ plumbing, for sand filters									1	11
261055	2 in. MPV, for sand filters (SM 20-3)									1	10
263064	Push Pull 7-1/2 in. Center Valve, Almond PVC									1	5
263080	Valve for Sand and Quad D.E., inlet port on top, Pentair 2 in. unions glued on XF Valve									1	10

<sup>1</sup> Valves must be purchased separately.

Note: Operating Limits -- maximum continual operating pressure of 50 PSI. Maximum operating water temperature (internal filter) 104°F (40°C).

See page 387-388 for replacement parts.





# ... HIGH PERFORMANCE NICHELESS DESIGN



## TECHNICAL GUIDE

- ETL Certified
- Available in 11 or 8 watt configurations
- Nicheless non-metallic design; no bonding; no grounding
- Standard model includes nine colors & five light shows
- 12V AC transformer required (not included)
- 140 degree beam angle
- Water-cooled with heat conductive PPS body
- 4" minimum water depth
- Wall or floor installation
- Clear gunite fitting with integrated waterstop
- Retrofit in most 1.5" wall fitting
- Durable, bayonet-style quarter turn installation
- 4.5" body with 6" watertight quick disconnect IP68 cord
- Synchronize with other popular pool OEM lighting systems









[\\_ \(https://www.c-m-](https://www.c-m-p.com/wp-content/uploads/2014/08/25620-320-channel-relief.jpg)

[p.com/wp-content/uploads/2014/08/25620-320-channel-relief.jpg\)](https://www.c-m-p.com/wp-content/uploads/2014/08/25620-320-channel-relief.jpg)

**GET DETAILS**



[\(https://www.c-m-p.com/wp-content/uploads/2013/12/Channel-Drain-Black-White-Product-Image.png\)](https://www.c-m-p.com/wp-content/uploads/2013/12/Channel-Drain-Black-White-Product-Image.png)



[\\_ \(https://www.c-m-p.com/wp-](https://www.c-m-p.com/wp-content/uploads/2014/02/25506-320-000-channel-drain-view-2.png)  
**RELIEF VALVE**

[content/uploads/2014/02/25506-320-000-channel-drain-view-2.png\)](https://www.c-m-p.com/wp-content/uploads/2014/02/25506-320-000-channel-drain-view-2.png)



[\\_ \(https://www.c-m-p.com/wp-](https://www.c-m-p.com/wp-content/uploads/2014/02/25506-320-000-channel-drain-angle-view-2.png)

[content/uploads/2014/02/25506-320-000-channel-drain-angle-view-2.png\)](https://www.c-m-p.com/wp-content/uploads/2014/02/25506-320-000-channel-drain-angle-view-2.png)



**25620-320-000**  
[\\_ \(https://www.c-m-p.com/wp-](https://www.c-m-p.com/wp-content/uploads/2013/12/25506-320-000-channel-drain-bottom.png)  
**2" MIP Hydrostatic Relief Valve; White**  
[content/uploads/2013/12/25506-320-000-channel-drain-bottom.png\)](https://www.c-m-p.com/wp-content/uploads/2013/12/25506-320-000-channel-drain-bottom.png)



[\\_ \(https://www.c-m-p.com/wp-](https://www.c-m-p.com/wp-content/uploads/2013/12/25506-320-000-channel-drain-no-cover.png)  
[content/uploads/2013/12/25506-320-000-channel-drain-no-cover.png\)](https://www.c-m-p.com/wp-content/uploads/2013/12/25506-320-000-channel-drain-no-cover.png)

close



[\\_ \(https://www.c-m-](https://www.c-m-p.com/wp-content/uploads/2016/10/25520-050-020-plug.jpg)

[p.com/wp-content/uploads/2016/10/25520-050-020-plug.jpg\)](https://www.c-m-p.com/wp-content/uploads/2016/10/25520-050-020-plug.jpg)

**GET DETAILS**




**2" NPT PLUG**

25520-050-020  
2" NPT Plug; White

**32" CHANNEL MAIN DRAIN  
DRAIN & SUMP**

# POWERCLEAN® TAB OFFLINE



## PRODUCT FEATURES

- 2.5 - 3" Pipe Adapter Sizes
- Larger Hose Than Other Brands
- Includes Base, Two Mounting Brackets and Tubing plus 3/4" Fittings for Hard Plumbing Installation



## SPECIFICATIONS

POOL SIZE	5,000 - 50,000 GALLONS
CAPACITY	TWELVE 3" TABS / 5LBS OF 1" TABS
FLOW INDICATOR	•
UNIONS INCLUDED	•
GLASS LID OPTION	•

## ORDERING GUIDE

REF	CMP P/N	DESCRIPTION	CLAMP SIZE	LID STYLE	BOX QTY
A	25280-300-000	POWERCLEAN TAB ULTRA OFF-LINE CHLORINATOR	1.5" - 2"	CLEAR GLASS	6
A	25280-309-000	POWERCLEAN TAB ULTRA OFF-LINE CHLORINATOR	1.5" - 2"	CLEAR PLASTIC	6
A	25280-310-000	POWERCLEAN TAB ULTRA OFF-LINE CHLORINATOR	1.5" - 2"	WHITE	6
--	25280-300-300	POWERCLEAN TAB ULTRA OFF-LINE CHLORINATOR	2.5" - 3"	CLEAR GLASS	--
--	25280-309-300	POWERCLEAN TAB ULTRA OFF-LINE CHLORINATOR	2.5" - 3"	CLEAR PLASTIC	--
--	25280-310-300	POWERCLEAN TAB ULTRA OFF-LINE CHLORINATOR	2.5" - 3"	WHITE	--
B	25280-300-200	POWERCLEAN TAB ULTRA OFF-LINE HOSE CLAMP ASSEMBLY	1.5" - 2"	--	--
B	25280-300-990	POWERCLEAN TAB ULTRA OFF-LINE HOSE CLAMP ASSEMBLY	2.5"	--	50
B	25280-300-900	POWERCLEAN TAB ULTRA OFF-LINE CLAMP KIT	3"	--	100

REPLACEMENT PARTS PAGE 236

WARNING: NEVER MIX CHLORINE AND BROMINE