

# LEE'S SUMMIT LOGISTICS 43 I K SPEC BUILDING



NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO  
64086  
11.02.22

## BUILD OUT CONSTRUCTION SET

**OWNER**  
SCANNELL PROPERTIES  
8801 RIVER CROSSING BLVD, SUITE 300  
INDIANAPOLIS, IN 46240  
O : 317 . 218 . 1648

**CIVIL ENGINEER**  
OLLSON  
7301 W. 133RD ST. SUITE 200  
OVERLAND PARK, KS 66213  
O : 913 . 381 . 1170

**ARCHITECT**  
  
**CURRAN**  
ARCHITECTURE  
5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O : 317 . 288 . 0681  
CONTACT : SHAWN CURRAN

**STRUCTURAL ENGINEER**  
WALLACE DESIGN  
COLLECTIVE  
1741 MCGEE STREET  
KANSAS CITY, MO 64108  
O : 816 . 421 . 8282

**CONTRACTOR**  
KADEAN CONSTRUCTION  
1821 MCGEE STREET  
KANSAS CITY, MO 64108  
O : 816 . 708 . 1199

### DRAWINGS INDEX BUILD OUT

#### CIVIL - BUILD OUT

C4.01 DIMENSION PLAN  
C4.02 DIMENSION PLAN  
C5.01 GRADING PLAN  
C5.02 GRADING PLAN  
C5.05 GRADING DETAIL  
L1.01 LANDSCAPE PLAN  
L1.02 LANDSCAPE PLAN

#### ARCHITECTURAL - BUILD OUT

A108 ENLARGED LIFE SAFETY PLAN  
A109 1ST FLOOR PLAN BUILD OUT  
A110 ENLARGED FLOOR PLANS  
A111 ENLARGED FLOOR PLANS  
A112 OVERALL REFLECTED CEILING PLAN  
A113 ENLARGED REFLECTED CEILING PLANS  
A504 SECTIONS & DETAILS  
A505 SECTIONS & DETAILS  
A602 INTERIOR DOOR SCHEDULE  
A603 FINISH SCHEDULE  
A701 EXTERIOR ENCLOSURE  
A702 COMPACTOR ENCLOSURE

#### STRUCTURAL - BUILD OUT

S0.0 GENERAL NOTES  
S0.1 GENERAL NOTES  
S1.0 OVERALL FOUNDATION PLAN  
S1.1 ENLARGED PARTIAL FOUNDATION PLAN  
S1.2 ENLARGED MEZZANINE ROOF FRAMING PLAN  
S2.0 OVERALL FRAMING PLAN  
S2.1 ENLARGED PARTIAL FRAMING PLAN  
S2.2 ENLARGED PARTIAL FRAMING PLAN  
S2.3 ENLARGED PARTIAL FRAMING PLAN  
S2.4 ENLARGED PARTIAL FRAMING PLAN  
S3.0 FOUNDATION DETAILS  
S3.1 FRAMING DETAILS  
S3.2 FOUNDATION DETAILS  
S4.0 FRAMING DETAILS  
S4.1 FRAMING DETAILS  
S4.2 FRAMING DETAILS

#### MECHANICAL - BUILD OUT

M1.1 OVERALL MECHANICAL FLOOR PLAN  
M1.2 ENLARGED MECHANICAL FLOOR PLANS  
M1.3 ENLARGED MECHANICAL FLOOR PLANS  
M1.4 MECHANICAL DETAILS  
M1.5 MECHANICAL DETAILS  
M1.6 MECHANICAL DETAILS  
M1.7 OVERALL MECHANICAL FLOOR PLAN  
M2.1 SPECIFICATIONS & DETAILS  
M3.1 MECHANICAL SCHEDULES

#### PLUMBING - BUILD OUT


P0.0 PLUMBING SPECIFICATIONS  
P1.0 PLUMBING PLAN  
P1.1 COMPRESSED AIR PLAN  
P1.2 ENLARGED PLUMBING PLANS  
P2.0 PLUMBING SCHEDULES AND DETAILS  
P2.1 PLUMBING RISERS  
P106 PLUMBING SPECIFICATIONS

#### ELECTRICAL - BUILD OUT

E1.0 WAREHOUSE LIGHTING  
E1.1 OFFICE LIGHTING  
E2.0 WAREHOUSE POWER  
E2.1 OFFICE POWER  
E3.0 HVAC POWER  
E3.1 OFFICE HVAC  
E4.0 SITE  
E5.0 RISER  
E6.0 PANEL SCHEDULE  
E6.1 PANEL SCHEDULE

#### FIRE PROTECTION - BUILD OUT

FP0.0 SYSTEM NOTES  
FP1.0 HYDRAULIC SITE PLAN  
FP2.0 OVERHEAD PIPING LAYOUT  
FP2.1.1 AREA 1: SYSTEMS 01-02  
FP2.1.2 AREA 1 (CONT): SYSTEMS 01-02  
FP2.2.1 AREA 2: SYSTEMS 03-03  
FP2.2.2 AREA 2 (CONT): SYSTEMS 02-03  
FP2.3.1 AREA 3: SYSTEMS 03-04  
FP2.3.2 AREA 3 (CONT): SYSTEMS 03-04  
FP2.4 AREA 4: SYSTEM 05  
FP2.5 AREA 5: SYSTEM 06  
FP2.6 AREA 6: SYSTEM 07  
FP2.7.1 AREA 7: SYSTEMS 08-09  
FP2.7.2 AREA 7 (CONT): SYSTEMS 08-09  
FP2.8.1 AREA 8: SYSTEMS 09-10  
FP2.8.2 AREA 8 (CONT): SYSTEMS 09-10  
FP2.9.1 AREA 9: SYSTEMS 10-11  
FP2.9.2 AREA 9 (CONT): SYSTEMS 10-11  
FP2.10 TENANT IMPROVEMENT OFFICE PLAN  
FP2.11 TENANT IMPROVEMENT COOLER PLAN  
FP3.0 FIRE PUMP & RISER DETAIL







CURRAN  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



SCANNELL  
PROPERTIES

CERTIFICATION



THIS DRAWING AND THE IDEAS, DESIGNS  
AND CONCEPTS CONTAINED HEREIN ARE  
THE EXCLUSIVE INTELLECTUAL PROPERTY  
OF CURRAN ARCHITECTURE, AND ARE NOT  
TO BE USED OR REPRODUCED, WHOLE OR  
IN PART, WITHOUT THE WRITTEN  
CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE

PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I  
  
NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086

ISSUE DATES

PERMIT SET	02.18.22
PERMIT COMMENTS	10.24.22
VE REVISIONS	12.20.22

210300

ENLARGED LIFE SAFETY  
PLANS

A108

KEYED NOTES

- EXIT, EXIT SIGN, AND EMERGENCY LIGHTING ABOVE DOOR  
INTERIOR WITH BATTERY BACKUP, EXTERIOR EGRESS  
LIGHTING ABOVE DOOR TIED TO BATTERY BACK UP.
- FINAL QUANTITY AND LOCATIONS TO BE DETERMINED  
WITH FINAL RACKING PLAN AND FIRE DEPARTMENT REVIEW.

CODE ANALYSIS

APPLICABLE CODES

BUILDING CODE  
2018 INTERNATIONAL BUILDING CODE  
  
PLUMBING CODE  
2017 INTERNATIONAL PLUMBING CODE  
  
ELECTRICAL CODE  
2017 NATIONAL ELECTRICAL CODE  
  
FIRE CODE  
2018 INTERNATIONAL FIRE CODE  
  
MECHANICAL CODE  
2018 INTERNATIONAL MECHANICAL CODE  
  
FUEL GAS CODE  
2018 FUEL GAS CODE  
  
HANDICAPPED ACCESSIBILITY CODE  
2009 ANSI A117.1  
ADA ACCESSIBILITY GUIDELINES

OCCUPANCY (OVERALL BUILDING)

CLASSIFICATION (302.1): S-I

OCCUPANCY (TENANT SPACE)

CLASSIFICATION (302.1): S-I  
ACCESSORY USES (508.2.1): B  
NON-SEPARATED USES (508.3.2): N/A  
SEPARATED USES (508.3.3): N/A

AUTOMATIC SPRINKLER SYSTEM

SPRINKLER SYSTEM REQUIRED (903): YES  
SPRINKLER SYSTEM PROVIDED: YES / ESR

ALLOWABLE BUILDING HEIGHT

TABULAR HEIGHT (503): 2 STORY

ALLOWABLE BUILDING AREA

TABULAR AREA (503): 17,500 SF

BUILDING AREA INCREASE

INCREASE FOR SPRINKLERED BUILDING (506.3): 300%  
UNLIMITED AREA (507): UNLIMITED  
FRONTAGE INCREASE (506.2): N/A  
If = (FP + 25) x W / 30  
TOTAL ALLOWABLE AREA WITH INCREASES:  
A<sub>2</sub> = A<sub>t</sub> + (A<sub>c</sub> x If) + (A<sub>c</sub> x Is)  
A<sub>2</sub> = FILL IN

ACTUAL BUILDING HEIGHT AND AREA

BUILDING AREA: 433,301 SF  
BUILDING HEIGHT (FEET / # FLOORS): 45'-6" / 1 FLR

TABULAR OCCUPANT LOAD (1004.1.2)

OCCUPANT LOAD FACTOR: 1 / 500

ACTUAL OCCUPANT LOAD (1004.1.2)

SQUARE FOOTAGE / OCCUPANT LOAD FACTOR: 433301 / 500  
TOTAL OCCUPANTS: 867

FIRE RESISTIVE REQUIREMENTS (601 AND 602)

CONSTRUCTION TYPE: II-B  
STRUCTURAL FRAME: NR  
EXTERIOR BEARING WALLS: NR  
INTERIOR BEARING WALLS: NR  
EXTERIOR NON-BEARING WALLS: NR  
INTERIOR NON-BEARING WALLS: NR  
FLOOR CONSTRUCTION: NR  
ROOF CONSTRUCTION: NR  
SHAFTS: N/A

FIRE RESISTANCE RATED CONSTRUCTION (704, 601, 402)

RATED EXTERIOR WALLS: N/A  
FIRE SEPARATION DISTANCE: 60' +  
UNPROTECTED OPENING AREA: N/A

INTERIOR WALL AND CEILING FINISH REQUIREMENTS (803)


SEE FINISH SCHEDULE FOR MATERIALS  
ALL MATERIALS ARE CLASS A RATED

FIRE PROTECTION SYSTEMS


STANDPIPE SYSTEM (905): YES  
PORTABLE FIRE EXTINGUISHERS (906.1): BY TENANT  
FIRE ALARM AND DETECTION SYSTEMS (907): YES  
SMOKE CONTROL SYSTEMS (909): N/A  
SMOKE AND HEAT VENTS (910): N/A

EGRESS


MINIMUM WIDTH FACTOR (1005.1): 0.15  
REQUIRED MINIMUM WIDTH FROM SPACE (1005.1): 130.05"  
MINIMUM NUMBER OF EXITS (1015): 3  
ACTUAL NUMBER OF EXITS: 20  
ACTUAL WIDTH OF EXITS: 792"  
ALLOWABLE TRAVEL DISTANCE (1016.2): 400'  
CORRIDOR CONSTRUCTION (1018.1): NR  
MINIMUM CORRIDOR WIDTH (1018.2): 44"  
MAXIMUM DEAD END CORRIDOR (1018.4): 20'




ENLARGED LIFE SAFETY PLAN 2  
1/8" = 1'-0"



ENLARGED LIFE SAFETY PLAN 1  
1/8" = 1'-0"








# CURRAN ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



## CERTIFICATION



THIS DRAWING AND THE IDEAS, DESIGNS  
AND CONCEPTS CONTAINED HEREIN ARE  
THE EXCLUSIVE INTELLECTUAL PROPERTY  
OF CURRAN ARCHITECTURE, AND ARE NOT  
TO BE USED OR REPRODUCED, WHOLE OR  
IN PART, WITHOUT THE WRITTEN  
CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE

## PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I


NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086

## ISSUE DATES

PERMIT SET	02.18.22
REVISIONS	06.14.22
PERMIT COMMENTS	10.24.22

1st FLOOR PLAN  
BUILD OUT


# A109



1st FLOOR PLAN








**CURRAN**  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



**SCANNELL**  
PROPERTIES


## GENERAL NOTES

- CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATION OF ALL DIMENSIONS AND JOB CONDITIONS. ANY DEVIATION FROM WHAT IS NOTED IN DRAWINGS SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT IMMEDIATELY.
- ALL DIMENSIONS SHOWN ARE FACE OF BRICK, MASONRY OR METAL STUD FRAMING, UNLESS OTHERWISE NOTED.
- PROVIDE DEEP LEG DEFLECTION TRACK AT ALL METAL STUD CONNECTIONS WITH STRUCTURE ABOVE, TYPICAL.
- PROVIDE FIRE RATED WOOD BLOCKING IN METAL STUD WALLS FOR ANY WALL SUPPORTED ITEMS.
- PROVIDE APPROVED FIRE RATED STOPPING MATERIALS IN ANY OPENINGS IN FIRE RATED ASSEMBLIES.
- REFER TO DOOR AND WINDOW SCHEDULES FOR ALL MATERIALS, FINISHES, AND HARDWARE INFORMATION.
- REFER TO EXTERIOR ELEVATIONS FOR ALL BRICK, MASONRY, AND OTHER EXPANSION JOINT LOCATIONS.
- ALL MATERIALS LOCATED IN CEILING PLENUM SHALL BE RATED FOR SUCH INSTALLATION OR PROTECTED TO PROVIDE COMPLIANCE. THIS INCLUDES BUT IS NOT LIMITED TO INSULATION (FHC 25/50) POWER AND LOW VOLTAGE WIRING, TELECOMMUNICATIONS CABLING, PLUMBING SUPPLY AND DRAIN LINES AND SUPPORTING BRACKETS AND/OR BLOCKING FOR CEILING HUNG ITEMS.
- PRIOR TO ORDERING ANY PRODUCTS, CONTRACTOR SHALL SUBMIT SAMPLES TO THE ARCHITECT OF ALL FINISH MATERIALS TO BE USED ON THE PROJECT. THE CONTRACTOR SHALL BEAR SOLE RESPONSIBILITY FOR ANY MATERIALS ORDERED INCORRECTLY WHEN THAT MATERIAL WAS NOT REVIEWED BY THE ARCHITECT.
- PROVIDE CONCRETE FILLED STEEL PIPE BOLLARDS AT ALL REQUIRED UTILITY EQUIPMENT LOCATIONS SUCH AS GAS METERS, ELECTRICAL TRANSFORMER PANELS, ETC. COORDINATE WITH UTILITY COMPANY AND CONTRACTORS, WHEN APPLICABLE, FOR NECESSARY LOCATIONS. REFER TO CIVIL DRAWINGS FOR BOLLARD SPECIFICATIONS AND ADDITIONAL INFORMATION.
- ALL DOORS, UNLESS OTHERWISE NOTED, TO HAVE HINGE SIDE SET 4" FROM CORNER SHOWN TO OUTSIDE OF FRAME.
- UNLESS SPECIFIED ELSEWHERE, ALL INTERIOR SLABS AND SLAB INFILLS TO BE FF-50/FL-35 OVERALL AND FF-35/FL-25 LOCAL.
- ALL EXIT DOORS TO HAVE TACTILE EXIT SIGNAGE PER 703.4 OF THE ANSI 117.1 2009.

## KEYED NOTES

- ADA COMPLIANT WALL MOUNTED LAVATORY. PROVIDE SCALD GUARDS ON SUPPLY / WASTE LINE. REFER TO PLUMBING DWGS. SEE TYPICAL ACCESSIBILITY DETAILS FOR ACCESSIBLE MOUNTING INFORMATION.
- ADA COMPLIANT WALL MOUNT FLUSH VALVE TOILET. REFER TO PLUMBING DWGS. SEE TYPICAL ACCESSIBILITY DETAILS FOR ACCESSIBLE MOUNTING INFORMATION.
- ADA COMPLIANT WALL MOUNTED URINAL W/ FLUSH VALVE CONTROL. CENTER IN WIDTH OF STALL. REFER TO PLUMBING DRAWINGS. SEE TYPICAL ACCESSIBILITY DETAILS FOR ACCESSIBLE MOUNTING INFORMATION.
- STANDARD HEIGHT WALL MOUNT FLUSH VALVE TOILET. CENTER IN WIDTH OF STALL.
- STANDARD HEIGHT URINAL. CENTER IN WIDTH OF PARTITIONS (OR WALL).
- WALL MOUNTED LAVATORY. MATCH HEIGHT OF ADA LAVATORIES
- ADA COMPLIANT H-L-O WATER FOUNTAIN.
- ALIGN FINISH FACE OF WALL, BOTH SIDES.
- WASHER & DRYER.
- 8'-0" TALL GALVANIZE D FENCE. PROVIDE GATE PER DETAIL 4/A504.
- PLASTIC LAMINATE 12" WIDE COUNTER. CENTER ON WIDTH OF WALL.
- PASS THRU CABINET W/ DOORS ON BOTH SIDES SEE 6/A504. CENTER ON WIDTH OF WALL.
- NOT USED.
- PROVIDE FR BLOCKING FOR TENANT PROVIDED TV.
- STRUCTURAL STEEL COLUMN.
- HALF HEIGHT LOCKERS 12" x 12" w/ 4" CURB & SLOPED TOP. PROVIDE 2 ADA COMPLIANT LOCKERS IN EACH ROOM.
- WALL MOUNT SHELF. REFER TO 5/A504.
- STEEL STAIRS, PAINT SAFETY YELLOW. REFER TO 1/A505.
- 2' x 2' MOP SINK w/ WALL MOUNT FAUCET.
- NOT USED.
- BAR JOIST ROOF FRAMING ABOVE. COORDINATE WITH STRUCTURAL DRAWINGS
- ALIGN FINISH FACE OF GYP BOARD WITH FACE OF CMU WALL.
- NOT USED.
- 4' TALL CMU WALL WITH BULLNOSE TOP AND OUTER EDGES. PAINT WITH EPOXY PAINT.
- FLOOR SLAB TO SLOPE TO CATCH BASIN. REFER TO PLUMBING DRAWINGS FOR WATER SUPPLY AND DRAIN
- PROVIDE INSULATED STEEL DOOR AT PENTHOUSE, FACING SOUTH. DOOR #200 ON SCHEDULE.

## CERTIFICATION



THIS DRAWING AND THE IDEAS, DESIGNS AND CONCEPTS CONTAINED HEREIN ARE THE EXCLUSIVE INTELLECTUAL PROPERTY OF CURRAN ARCHITECTURE, AND ARE NOT TO BE USED OR REPRODUCED, WHOLE OR IN PART, WITHOUT THE WRITTEN CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE

## PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I

NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086

## ISSUE DATES


PERMIT SET	02.18.22
REVISIONS	06.14.22
VE REVISIONS	12.20.22

210300


ENLARGED  
FLOOR PLANS

**A110**


TOILET ACCESSORY SCHEDULE			
MARK	SYMBOL	MFR #	DESCRIPTION
TT1		BOBRICK B-2888	MULTI-ROLL TOILET TISSUE DISPENSER
GB1		BOBRICK B-5806 X 36 B-5806 X 42	36" AND 42" GRAB BARS
GB2		BOBRICK B-5806 X 18	18" VERTICAL GRAB BAR
MI		BOBRICK B-165	MIRROR 2'-0" X 4'-0"
TD1		BOBRICK B-3944	TOWEL DISPENSER / WASTE RECEPTACLE
SD1		BOBRICK B-2112	SOAP DISPENSER
ND1		BOBRICK B-353 B-270	B-353: SANITARY NAPKIN DISPOSAL UNIT AT GWB LOCATIONS. B-270: SURFACE MOUNT SANITARY NAPKIN DISPOSAL UNIT AT PARTITIONS
TP1		GENERAL PARTITION	TOILET PARTITION AND/OR URINAL SCREEN POWDER COATED URINAL SCREEN BOTTOM 12" FROM FLOOR AND TOP 60" MAX FROM FLOOR




**OUTBOUND DRIVER LOUNGE** 2  
1/4" = 1'-0"




**INBOUND DRIVER LOUNGE** 3  
1/4" = 1'-0"




**ENLARGED FLOOR PLAN** 4  
1/4" = 1'-0"



**ENLARGED FLOOR PLAN** 5  
1/8" = 1'-0"




**PENTHOUSE FLOOR PLAN** 6  
1/4" = 1'-0"



**1st FLOOR PLAN** 1  
1/8" = 1'-0"




TOILET ACCESSORY SCHEDULE			
MARK	SYMBOL	MFR #	DESCRIPTION
TT1		BOBRICK B-2888	MULTI-ROLL TOILET TISSUE DISPENSER
GB1		BOBRICK B-5806 X 36 B-5806 X 42	36" AND 42" GRAB BARS
GB2		BOBRICK B-5806 X 18	18" VERTICAL GRAB BAR
MI		BOBRICK B-165	MIRROR 2'-0" X 4'-0"
TD1		BOBRICK B-3944	TOWEL DISPENSER / WASTE RECEPTACLE
SD1		BOBRICK B-2112	SOAP DISPENSER
ND1		BOBRICK B-353 B-270	B-353: SANITARY NAPKIN DISPOSAL UNIT AT GWB LOCATIONS B-270: SURFACE MOUNT SANITARY NAPKIN DISPOSAL UNIT AT PARTITIONS
TPI		GENERAL PARTITION	TOILET PARTITION AND/OR URINAL SCREEN POWDER COATED URINAL SCREEN BOTTOM 12" FROM FLOOR AND TOP 60" MAX FROM FLOOR



ENLARGED RESTROOM PLAN

1


1/4" = 1'-0"



ENLARGED RESTROOM PLAN

2

1/4" = 1'-0"



UPPER STAIR PLAN

4

1/4" = 1'-0"



INTERMEDIATE LANDING PLAN

3


1/4" = 1'-0"

## GENERAL NOTES

- CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATION OF ALL DIMENSIONS AND JOB CONDITIONS. ANY DEVIATION FROM WHAT IS NOTED IN DRAWINGS SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT IMMEDIATELY.
- ALL DIMENSIONS SHOWN ARE FACE OF BRICK, MASONRY OR METAL STUD FRAMING, UNLESS OTHERWISE NOTED.
- PROVIDE DEEP LEG DEFLECTION TRACK AT ALL METAL STUD CONNECTIONS WITH STRUCTURE ABOVE, TYPICAL.
- PROVIDE FIRE RATED WOOD BLOCKING IN METAL STUD WALLS FOR ANY WALL SUPPORTED ITEMS.
- PROVIDE APPROVED FIRE RATED STOPPING MATERIALS IN ANY OPENINGS IN FIRE RATED ASSEMBLIES.
- REFER TO DOOR AND WINDOW SCHEDULES FOR ALL MATERIALS, FINISHES, AND HARDWARE INFORMATION.
- REFER TO EXTERIOR ELEVATIONS FOR ALL BRICK, MASONRY, AND OTHER EXPANSION JOINT LOCATIONS.
- ALL MATERIALS LOCATED IN CEILING PLENUM SHALL BE RATED FOR SUCH INSTALLATION OR PROTECTED TO PROVIDE COMPLIANCE. THIS INCLUDES BUT IS NOT LIMITED TO INSULATION (FHC 25/50) POWER AND LOW VOLTAGE WIRING, TELECOMMUNICATIONS CABLING, PLUMBING SUPPLY AND DRAIN LINES AND SUPPORTING BRACKETS AND/OR BLOCKING FOR CEILING HUNG ITEMS.
- PRIOR TO ORDERING ANY PRODUCTS, CONTRACTOR SHALL SUBMIT SAMPLES TO THE ARCHITECT OF ALL FINISH MATERIALS TO BE USED ON THE PROJECT. THE CONTRACTOR SHALL BEAR SOLE RESPONSIBILITY FOR ANY MATERIALS ORDERED INCORRECTLY WHEN THAT MATERIAL WAS NOT REVIEWED BY THE ARCHITECT.
- PROVIDE CONCRETE FILLED STEEL PIPE BOLLARDS AT ALL REQUIRED UTILITY EQUIPMENT LOCATIONS SUCH AS GAS METERS, ELECTRICAL TRANSFORMER PANELS, ETC.. COORDINATE WITH UTILITY COMPANY AND CONTRACTORS, WHEN APPLICABLE, FOR NECESSARY LOCATIONS. REFER TO CIVIL DRAWINGS FOR BOLLARD SPECIFICATIONS AND ADDITIONAL INFORMATION.
- ALL DOORS, UNLESS OTHERWISE NOTED, TO HAVE HINGE SIDE SET 4" FROM CORNER SHOWN TO OUTSIDE OF FRAME.
- UNLESS SPECIFIED ELSEWHERE, ALL INTERIOR SLABS AND SLAB INFILLS TO BE FF-50/FL-25 OVERALL AND FF-35/FL-25 LOCAL.
- ALL EXIT DOORS TO HAVE TACTILE EXIT SIGNAGE PER 703.4 OF THE ANSI 117.1 2009.

## KEYED NOTES

- ADA COMPLIANT WALL MOUNTED LAVATORY. PROVIDE SCALD GUARDS ON SUPPLY / WASTE LINE. REFER TO PLUMBING DWGS. SEE TYPICAL ACCESSIBILITY DETAILS FOR ACCESSIBLE MOUNTING INFORMATION.
- ADA COMPLIANT WALL MOUNT FLUSH VALVE TOILET. REFER TO PLUMBING DWGS. SEE TYPICAL ACCESSIBILITY DETAILS FOR ACCESSIBLE MOUNTING INFORMATION.
- ADA COMPLIANT WALL MOUNTED URINAL W/ FLUSH VALVE CONTROL. CENTER IN WIDTH OF STALL. REFER TO PLUMBING DRAWINGS. SEE TYPICAL ACCESSIBILITY DETAILS FOR ACCESSIBLE MOUNTING INFORMATION.
- STANDARD HEIGHT WALL MOUNT FLUSH VALVE TOILET. CENTER IN WIDTH OF STALL.
- STANDARD HEIGHT URINAL. CENTER IN WIDTH OF PARTITIONS (OR WALL).
- WALL MOUNTED LAVATORY. MATCH HEIGHT OF ADA LAVATORIES.
- ADA COMPLIANT H2O WATER FOUNTAIN.
- ALIGN FINISH FACE OF WALL, BOTH SIDES.
- WASHER & DRYER.
- 8'-0" TALL GALVANIZE D FENCE. PROVIDE GATE PER DETAIL 4/A504.
- PLASTIC LAMINATE 12" WIDE COUNTER. CENTER ON WIDTH OF WALL.
- PASS THRU CABINET W/ DOORS ON BOTH SIDES SEE 6/A504. CENTER ON WIDTH OF WALL.
- NOT USED.
- PROVIDE FR BLOCKING FOR TENANT PROVIDED TV.
- STRUCTURAL STEEL COLUMN.
- HALF HEIGHT LOCKERS 12' x 12' w/ 4" CURB & SLOPED TOP. PROVIDE 2 ADA COMPLIANT LOCKERS IN EACH ROOM.
- WALL MOUNT SHELF. REFER TO 5/A504.
- STEEL STAIRS, PAINT SAFETY YELLOW. REFER TO 1/A505.
- 2' x 2' MOP SINK w/ WALL MOUNT FAUCET.
- NOT USED.
- BAR JOIST ROOF FRAMING ABOVE. COORDINATE WITH STRUCTURAL DRAWINGS.
- ALIGN FINISH FACE OF GYP BOARD WITH FACE OF CMU WALL.
- NOT USED.
- 4' TALL CMU WALL WITH BULLNOSE TOP AND OUTER EDGES. PAINT WITH EPOXY PAINT.
- FLOOR SLAB TO SLOPE TO CATCH BASIN. REFER TO PLUMBING DRAWINGS FOR WATER SUPPLY AND DRAIN.
- PROVIDE INSULATED STEEL DOOR AT PENTHOUSE, FACING SOUTH. DOOR #200 ON SCHEDULE.




**CURRAN**  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



**SCANNELL**  
PROPERTIES

## CERTIFICATION



THIS DRAWING AND THE IDEAS, DESIGNS AND CONCEPTS CONTAINED HEREIN ARE THE EXCLUSIVE INTELLECTUAL PROPERTY OF CURRAN ARCHITECTURE, AND ARE NOT TO BE USED OR REPRODUCED, WHOLE OR IN PART, WITHOUT THE WRITTEN CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE

## PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I

NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086

## ISSUE DATES


PERMIT SET	02.18.22
PERMIT COMMENTS	10.24.22
VE REVISIONS	12.20.22

210300

ENLARGED  
FLOOR PLANS


**AIII**





REFLECTED CEILING PLAN

1" = 30'








CURRAN  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



SCANNELL  
PROPERTIES

CERTIFICATION



THIS DRAWING AND THE IDEAS, DESIGNS  
AND CONCEPTS CONTAINED HEREIN ARE  
THE EXCLUSIVE INTELLECTUAL PROPERTY  
OF CURRAN ARCHITECTURE, AND ARE NOT  
TO BE USED OR REPRODUCED, WHOLE OR  
IN PART, WITHOUT THE WRITTEN  
CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE

PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I

NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086

ISSUE DATES

PERMIT SET 02.18.22


210300

ENLARGED REFLECTED  
CEILING PLANS

A113

CEILING LEGEND


(NOT ALL MAY APPLY)




ACOUSTICAL TILE CEILING / GRID. REFER TO FINISH  
SCHEDULE FOR TYPE AND HEIGHT.




GYPSUM BOARD BULKHEAD OR CEILING. HEIGHT  
AS NOTED ON SCHEDULE OR KEYNOTES.




ENLARGED REFLECTED CEILING PLAN 2  
1/4" = 1'-0" N




ENLARGED REFLECTED CEILING PLAN 3  
1/4" = 1'-0" N



ENLARGED REFLECTED CEILING PLAN 4  
1/8" = 1'-0" N



ENLARGED REFLECTED CEILING PLAN 1  
1/8" = 1'-0" N



KEY PLAN




# CURRAN ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



## CERTIFICATION



THIS DRAWING AND THE IDEAS, DESIGNS  
AND CONCEPTS CONTAINED HEREIN ARE  
THE EXCLUSIVE INTELLECTUAL PROPERTY  
OF CURRAN ARCHITECTURE, AND ARE NOT  
TO BE USED OR REPRODUCED, WHOLE OR  
IN PART, WITHOUT THE WRITTEN  
CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE

## PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I

NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086


## ISSUE DATES

PERMIT SET 02.18.22


210300

SECTIONS AND DETAILS


# A504




**CASEWORK SECTION** 1  
3/4" = 1'-0"




**CASEWORK SECTION** 2  
3/4" = 1'-0"




**CASEWORK SECTION** 3  
3/4" = 1'-0"




**CASEWORK ELEVATION** 1  
1/2" = 1'-0"




**ADJUSTABLE SHELVING** 5  
3/4" = 1'-0"



**CASEWORK ELEVATION** 2  
1/2" = 1'-0"




**PASS-THRU CABINET SECTION** 6  
3/4" = 1'-0"



**GATE DETAIL** 4  
1/2" = 1'-0"



5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



**SCANNELL**  
PROPERTIES

THIS DRAWING AND THE IDEAS, DESIGNS,  
AND CONCEPTS CONTAINED HEREIN ARE  
THE EXCLUSIVE INTELLECTUAL PROPERTY  
OF CURRAN ARCHITECTURE, AND ARE NOT  
TO BE USED OR REPRODUCED, WHOLE OR  
IN PART, WITHOUT THE WRITTEN  
CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1


NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086

PERMIT SET	02.18.22
VE REVISIONS	12.20.22


210300

## SECTIONS AND DETAILS

# A505







# CURRAN


## ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



SCANNELL  
PROPERTIES

### CERTIFICATION



THIS DRAWING AND THE IDEAS, DESIGNS  
AND CONCEPTS CONTAINED HEREIN ARE  
THE EXCLUSIVE INTELLECTUAL PROPERTY  
OF CURRAN ARCHITECTURE, AND ARE NOT  
TO BE USED OR REPRODUCED, WHOLE OR  
IN PART, WITHOUT THE WRITTEN  
CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE

### PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I

NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086

### ISSUE DATES

PERMIT SET	02.18.22
REVISIONS	06.14.22

210300

INTERIOR  
DOOR SCHEDULE

A602

## GENERAL DOOR AND GLAZING NOTES

- ALL PRE-FINISHED WOOD DOORS SHALL BE SOLID CORE WITH WOOD VENEER, MARSHFIELD OR EQUIVALENT. PROVIDE FINISH SAMPLE AND DOOR CONSTRUCTION DIAGRAM FOR APPROVAL AND HARDWARE BLOCKING COORDINATION. VENEER TO BE WHITE BIRCH OR MAPLE, FREE OF DARK GRAINS UNLESS OTHERWISE NOTED.
- WOOD DOORS SHALL ONLY BE INSTALLED IN CONDITIONED SPACE.
- ALL HARDWARE TO BE MINIMUM 6 PIN BEST COMPATIBLE SYSTEM. COORDINATE KEYING WITH OWNER.
- TEMPERED AND ANNEALED GLASS TO BE CLEANED PER MANUFACTURER REQUIREMENTS. NYLON CLOTH METHODS PREFERRED. DO NOT USE RAZOR BLADES ON GLASS.
- GLASS AROUND DOORS AND IN DOORS SHALL BE TEMPERED UNLESS OTHERWISE NOTED IN ELEVATIONS.
- ANY RATED DOORS TO HAVE LABEL INSTALLED IN JAMB.
- ALL EXITS DOORS TO HAVE TACTILE EXIT SIGNAGE PER 703.4 OF THE ANSI 117.1 2009.
- INSTALL OWNER PROVIDED ADA COMPLIANT RESTROOM SIGNAGE. VERIFY WITH ARCHITECT.

## GLAZING TYPES

- SECTION OF GLAZING REQUIRED TO BE 1" INSULATED GREY TINTED GLASS.
- SECTION OF GLAZING REQUIRED TO BE 1" INSULATED TEMPERED GLASS.
- SECTION OF GLAZING REQUIRED TO BE 1/4" GLASS.
- SECTION OF GLAZING REQUIRED TO BE 1/4" TEMPERED GLASS.
- SECTION OF GLAZING REQUIRED TO BE 1" INSULATED TEMPERED GREY TINTED SPANDREL GLASS.

EXTERIOR GLAZING MUST MEET THE FOLLOWING SPECIFICATIONS FOR ENERGY CODE COMPLIANCE:

LOW "E" COATING  
"U" VALUE - MINIMUM OF 0.28  
"SHGC" VALUE - MAXIMUM OF 0.47

## DOOR HARDWARE

### HARDWARE SET 1

- CONTINUOUS HINGES
  - PANIC DEVICES
  - PERIMETER SEAL
  - THRESHOLD
  - SWEEPS
  - HD CLOSERS
  - PULLS
- FINISH: MATCH STOREFRONT

### HARDWARE SET 2

- BALL BEARING HINGES
  - PANIC DEVICE W/ LEVER
  - PERIMETER SEAL
  - THRESHOLD W/ DRAINAGE SUBSILL
  - SWEEP
  - HD CLOSER
  - DRIP TRIM
- FINISH: US26D

### HARDWARE SET 3

- BALL BEARING HINGES
  - STOREROOM LOCKSET
  - PERIMETER SEAL
  - THRESHOLD W/ DRAINAGE SUBSILL
  - SWEEP
  - HD CLOSER
  - DRIP TRIM
- FINISH: US26D

### HARDWARE SET 4

- HINGES
  - OFFICE LOCKSET
  - MUTES
  - DOOR STOP
- FINISH: US26D

### HARDWARE SET 5

- HINGES
  - PASSAGE SET
  - MUTES
  - DOOR STOP
- FINISH: US26D

### HARDWARE SET 6

- HINGES
  - PRIVACY LOCKSET
  - MUTES
  - CLOSER
  - DOOR STOP
- FINISH: US26D

### HARDWARE SET 7

- HINGES
  - PUSH PULLS
  - MUTES
  - MAG LOCK (BY TENANT)
  - DOOR STOPS
- FINISH: US26D

### HARDWARE SET 8

- HINGES
  - PASSAGE SET
  - MUTES
  - CLOSER
  - DOOR STOP
- FINISH: US26D

### HARDWARE SET 9

- HINGES
  - STOREROOM LOCKSET
  - MUTES
  - CLOSER
  - ELECTRIC STRIKE (BY TENANT)
  - DOOR STOP
- FINISH: US26D

### HARDWARE SET 10

- HINGES
  - PUSH PULL
  - MUTES
  - CLOSER
  - DOOR STOP
- FINISH: US26D

### HARDWARE SET 11


- HINGES
  - OFFICE LOCKSET
  - MUTES
  - PAIR FLUSH BOLTS
  - DOOR STOP
- FINISH: US26D

### HARDWARE SET 12

- HINGES
  - EXIT DEVICE
  - MUTES
  - CLOSER
  - ELECTRIC STRIKE (BY TENANT)
  - DOOR STOP
- FINISH: US26D



## DOOR SCHEDULE

MARK	DOOR	SIZE	MATERIAL	GLAZING	FINISH	RATING	FRAME	MATERIAL	FINISH	RATING	HARDWARE	REMARKS
101	FG	(2) 3-0 x 7-0	SCWD	D	PRE-FIN	-	F2	KD	PAINT	-	7	
102A	F	3-0 x 7-0	SCWD	--	PRE-FIN	--	F1	KD	PAINT	-	4	
102B	-	-	-	-	-	-	F4	KD	PAINT	-	-	
103	F	3-0 x 7-0	SCWD	--	PRE-FIN	--	F3	KD	PAINT	-	4	
104	F	3-0 x 7-0	SCWD	--	PRE-FIN	--	F3	KD	PAINT	-	4	
105	F	3-0 x 7-0	SCWD	--	PRE-FIN	--	F3 (OH)	KD	PAINT	-	4	
107	F	3-0 x 7-0	SCWD	--	PRE-FIN	--	F3	KD	PAINT	-	5	
108	N	3-0 x 7-0	SCWD	D	PRE-FIN	--	F1	KD	PAINT	-	8	
110	F	3-0 x 7-0	SCWD	-	PRE-FIN	-	F1	KD	PAINT	-	6	
111	F	3-0 x 7-0	SCWD	-	PRE-FIN	-	F1	KD	PAINT	-	9	
111A	F	3-0 x 7-0	SCWD	-	PRE-FIN	-	F1	KD	PAINT	-	4	
112A	F	3-0 x 7-0	SCWD	-	PRE-FIN	-	F1	KD	PAINT	-	8	
112B	N	3-0 x 7-0	HM	D	PAINT	-	F1	KD	PAINT	-	9	
112C	-	-	-	-	-	-	F8	KD	PAINT	-	-	
112D	-	-	-	-	-	-	F7	KD	PAINT	-	-	
112E	-	-	-	-	-	-	F7	KD	PAINT	-	-	
112F	-	-	-	-	-	-	F7	KD	PAINT	-	-	
112G	-	-	-	-	-	-	F7	KD	PAINT	-	-	
112H	-	-	-	-	-	-	F7	KD	PAINT	-	-	
113	N	3-0 x 7-0	HM	D	PAINT	-	F1	KD	PAINT	-	9	
114	F	3-0 x 7-0	SCWD	-	PRE-FIN	-	F1	KD	PAINT	-	4	
115A	N	3-0 x 7-0	SCWD	D	PRE-FIN	--	F1	KD	PAINT	-	8	
115B	N	3-0 x 7-0	SCWD	D	PRE-FIN	--	F1	KD	PAINT	-	8	
116A	N	3-0 x 7-0	SCWD	D	PRE-FIN	-	F1 W/ 4" HEAD	HM	PAINT	-	9	
116B	N	3-0 x 7-0	HM	D	PAINT	-	F1 W/ 4" HEAD	HM	PAINT	-	10	
116C	N	3-0 x 7-0	HM	D	PAINT	-	F1 W/ 4" HEAD	HM	PAINT	-	10	
118	F	3-0 x 7-0	HM	-	PAINT	-	F1	KD	PAINT	-	8	
119	-	-	-	-	-	-	F1	KD	PAINT	-	--	
120	F	3-0 x 7-0	HM	--	PAINT	-	F1	KD	PAINT	-	8	
122	F	3-0 x 7-0	HM	--	PAINT	-	F1	KD	PAINT	-	10	
125	F	(2)3-0 x 7-0	HM	--	PAINT	-	F1	KD	PAINT	-	11	
126	F	3-0 x 7-0	HM	--	PAINT	-	F1	KD	PAINT	-	4	
127A	F	3-0 x 7-0	HM	--	PAINT	-	F1	KD	PAINT	-	12	
127B	-	-	-	-	-	-	F6	KD	PAINT	-	--	
128	F	3-0 x 7-0	HM	--	PAINT	-	F1	KD	PAINT	-	6	
129A	F	3-0 x 7-0	HM	--	PAINT	-	F1	KD	PAINT	-	12	
129B	-	-	-	-	-	-	F6	KD	PAINT	-	--	
130	F	3-0 x 7-0	HM	--	PAINT	-	F1	KD	PAINT	-	6	
200	F	3-0 x 7-0	INSUL STL	--	PAINT	--	F1	HM	PAINT	--	3	
201	F	3-0 x 7-0	INSUL STL	--	PAINT	--	F1	HM	PAINT	--	3	
300	F	3-0 x 7-0	INSUL STL	--	PAINT	--	F1	HM	PAINT	--	3	



### DOOR TYPES

NOT TO SCALE



### FRAME TYPES

NOT TO SCALE



719 LAWTON LOOP E. DR. #21  
INDIANAPOLIS, IN 46216  
O :: 317.288.0681  
F :: 317.288.0753



## PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1

PERMIT SET	02.18.22
VE REVISIONS	12.20.22


[illegible]

## FINISH SCHEDULE

MARK	MATERIAL	MANUFACTURER	COLOR	PATTERN / TEXTURE	NUMBER	REMARKS
S-1	SEALED CONCRETE	ASHFORD	CLEAR	CURE-N-SEAL	--	
CPT-1	CARPET TILE	MOHAWK	TBD	UNCHARTED SOLVE II	BT416	
CPT-2	CARPET TILE	MOHAWK	TBD	STEP IN STYLE II	QL312	
T-1	WALL TILE	DALTILE	TBD	COLOR WHELL CLASSIC LINE 3X6 RUNNING BOND	TBD	PROVIDE SHLUTER STRIP AT TOP EDGE, AND SHLUTER SANITARY COVE AT FLOOR/WALL INTERSECTION
T-2	FLOOR TILW	DALTILE	TBD	IRONCRAFT 12X24	TBD	
B-1	BASE	JOHNSONITE TARKETT	TBD	4" COVE	TBD	
P-1	PAINT	SHERWIN WILLIAMS	TBD	EGGSHELL	TBD	
P-2	PAINT	SHERWIN WILLIAMS	TBD	EGGSHELL	TBD	
P-3	PAINT	SHERWIN WILLIAMS	TBD	EGGSHELL	TBD	
P-4	PAINT	SHERWIN WILLIAMS	MATCH BASE COLOR	SEMI GLOSS	TBD	INTERIOR DOOR FRAMES AND HOLLOW METAL DOORS
FRP-1	FIBERGLASS REINFORCED PLASTIC	TBD	TBD	SMOOTH FINISH	TBD	
PL-1	PLASTIC LAMINATE	TBD	TBD	MATTE FINISH	TBD	
PL-2	PLASTIC LAMINATE	TBD	TBD	MATTE FINISH	TBD	
SS-1	SOLID SURFACE	TBD	TBD	TBD	TBD	GRADE C PRICE
ACT-1	ACOUSTICAL CBLING TILE	ARMSTRONG	WHITE	CORTEGA 2nd LOOK	2767	

ROOM #	ROOM NAME	FLOORING	BASE	NORTH WALL	EAST WALL	SOUTH WALL	WEST WALL	CABINETS / COUNTERTOPS	CEILING MAT / HEIGHT	REMARKS
101	LOBBY	CPT-2	B-1	P-1	P-1	P-1	P-1	--	ACT-1/9-8	
102	OFFICE	CPT-1	B-1	P-2	P-1	P-1	P-1	--	ACT-1/9-8	
103	OFFICE	CPT-1	B-1	P-2	P-1	P-1	P-1	--	ACT-1/9-8	
104	OFFICE	CPT-1	B-1	P-2	P-1	P-1	P-1	--	ACT-1/9-8	
105	VISITOR OFFICE	CPT-1	B-1	P-2	P-1	P-1	P-1	--	ACT-1/9-8	
106	OPEN OFFICE	CPT-1	B-1	P-1	P-1	P-1	P-1	--	ACT-1/9-8	
107	CONF ROOM	CPT-1	B-1	P-3	P-3	P-3	P-3	--	ACT-1/9-8	
108	HALL	CPT-1	B-1	P-1	P-1	P-1	P-1	--	ACT-1/9-8	
109	COPY / PRINT	CPT-1	B-1	P-1	P-1	P-1	P-1	PL-1/PL-2	ACT-1/9-8	
110	TLT	T-2	--	T-1/P-3	T-1/P-3	T-1/P-3	T-1/P-3	--	ACT-1/9-8	T-1 TO 5'-0" AFF AND P-3 TO CEILING
111	SERVER	SC-1	B-1	P-1	P-1	P-1	P-1	--	ACT-1/9-8	
112	SHARED OFFICE	CPT-1	B-1	P-1	P-2	P-1	P-1	--	ACT-1/9-8	
113	HALL	CPT-2	B-1	P-1	P-2	P-1	P-1	--	ACT-1/9-8	
114	STOR	CPT-1	B-1	P-1	P-1	P-1	P-1	--	ACT-1/9-8	
115	TRAINING ROOM	CPT-1	B-1	P-1	P-2	P-1	P-1	--	ACT-1/9-8	
116	BREAK ROOM	SC-1	--	P-1	P-1	P-1	P-1	PL-1/SS-1	ACT-1/9-8	
117	LOCKER ROOM	SC-1	B-1	P-2	P-1	P-1	P-1	--	ACT-1/9-8	
118	MEN	SC-1	B-1*	P-2	T-1/P-1	T-1/P-1	T-1/P-1	--	ACT-1/9-8	B-1 ON NON TILED WALLS ONLY, T-1 TO 5'-0" AFF AND P-1 TO CEILING
119	HALL	SC-1	B-1	P-1	P-1	P-1	P-1	--	ACT-1/9-8	
120	WASHER / DRYER	SC-1	B-1	FRP-1/P-1	FRP-1/P-1	FRP-1/P-1	FRP-1/P-1	--	ACT-1/9-8	FRP-1 TO 4'-0" AFF AND P-1 TO CEILING
121	LOCKER ROOM	SC-1	B-1	P-1	P-1	P-2	P-1	--	ACT-1/9-8	
122	WOMEN	SC-1	B-1*	T-1/P-1	T-1/P-1	P-2	T-1/P-1	--	ACT-1/9-8	B-1 ON NON TILED WALLS ONLY, T-1 TO 5'-0" AFF AND P-1 TO CEILING
125	MAINT SHOP	SC-1	B-1	P-1	P-1	P-1	P-1	--	ACT-1/9-8	COVER WALLS W/ FIRE RATED PLYWOOD TO 8'-0" AFF
126	MAINT OFFICE	SC-1	B-1	P-1	P-1	P-1	P-1	--	ACT-1/9-8	
127	DRIVER LOUNGE	SC-1	B-1	P-1	P-1	P-1	P-1	PL-1	ACT-1/9-8	
128	TLT	SC-1	B-1	FRP-1/P-1	FRP-1/P-1	FRP-1/P-1	FRP-1/P-1	--	ACT-1/9-8	FRP-1 TO 4'-0" AFF AND P-1 TO CEILING
129	DRIVER LOUNGE	SC-1	B-1	FRP-1/P-1	FRP-1/P-1	FRP-1/P-1	FRP-1/P-1	--	ACT-1/9-8	
130	TLT	SC-1	B-1	FRP-1/P-1	FRP-1/P-1	FRP-1/P-1	FRP-1/P-1	--	ACT-1/9-8	FRP-1 TO 4'-0" AFF AND P-1 TO CEILING


- A. PROCEEDING WITH THE INSTALLATION OF FINISHES WILL BE CONSTRUED THAT THE INSTALLER AND/OR FINISHER HAS INSPECTED AND ACCEPTED THE SUBSTRATE FOR RECEIVING THE WORK. NO CHANGE ORDER WILL BE ISSUED TO RECTIFY CORRECTED, UNKNOWN CONDITIONS OR UNSATISFACTORY SUBSTRATE ONCE THE FINISH WORK HAS PROCEEDED.
- B. USE MANUFACTURER'S RECOMMENDED INSTALLATION METHODS AND MATERIALS FOR ALL FINISHES.
- C. CONTRACTOR TO NOTIFY ARCHITECT IMMEDIATELY IF A SPECIFIED FINISH ITEM BECOMES UNAVAILABLE.
- D. CONTRACTOR TO SUBMIT SHOP DRAWINGS, FLOORING, TRANSITIONGRAPHIC, CATALOGS AND SUBMITTALS OF ALL FINISHES AND FINISH MATERIALS TO ARCHITECT REVIEW PRIOR TO PLACING ANY MATERIAL ORDERS. CONTRACTOR MUST ACCEPT FOR SUBMITTAL REVIEW, ORDERING AND DELIVERY WHEN SCHEDULING PRODUCT INSTALLATION.
- E. USE SUBFLOOR REDUCER STRIPS (UNDER FLOORING) TO LEVEL MATERIALS OF UNEQUAL HEIGHTS.
- F. PROVIDE JOHNSONITE SLIM-LINE TRANSITION STRIPS WHERE FLOORING MATERIALS OF UNEQUAL THICKNESS MEET. TRANSITION STRIPS AT DOORS TO BE LOCATED UNDER THE CENTERLINE OF THE DOOR IN CLOSED POSITION. COLOR OF TRANSITION STRIPS TO BE SELECTED BY ARCHITECT.
- G. ALL WALL TILE TO BE INSTALLED TO FLOOR WITH NO BASE UNLESS NOTED OTHERWISE.
- H. ANY GRILLES, FIRE EXTINGUISHER CABINETS, ETC., TO BE PAINTED TO MATCH WALL COLOR ON WHICH THEY OCCUR.
- I. PROVIDE OWNER WITH A MINIMUM OF ONE FULL BOX OR 2% OF EACH FINISH PRODUCT/MATERIAL SPECIFIED ON THE PROJECT.
- J. ALL WOODWORK/MILLWORK SHALL CONFORM TO THE QUALITY STANDARDS OF ARCHITECTURAL WOODWORK INSTITUTE (AWI) PREMIUM GRADE. FABRICATOR SHALL BE FAMILIAR WITH AWI STANDARDS.
- K. FABRICATE WOODWORK/MILLWORK ITEMS TO ACTUAL FIELD DIMENSIONS. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS, SAMPLES AND/OR MATERIAL LITERATURE FOR ALL ITEMS. SHOP DRAWINGS SHALL SHOW SUFFICIENT DETAIL TO DETERMINE COMPLIANCE WITH THE QUALITY STANDARDS AND DESIGN INTENT.
- L. PROVIDE ALL NECESSARY FURRING AND GROUNDS FOR WOODWORK AND FINISH ITEMS. COORDINATE LOCATION OF BLOCKING WITHIN WALLS FOR ITEMS TO BE SECURED TO SURFACE. ALL FASTENERS SHALL BE CONCEALED.
- M. FINISH ALL SIDES AND BACK OF MILLWORK/CASEWORK.
- N. ALL COUNTERTOPS TO BE 1" THICK WITH A SQUARE EDGE. UNLESS OTHERWISE NOTED. PROVIDE COUNTERTOP SUPPORTS AS REQUIRED.
- O. PROVIDE GROMMETS IN COUNTERTOPS ABOVE RECEPTACLES. COLOR TO MATCH COUNTER SURFACE. COORDINATE WITH OWNER AND ARCHITECT ON FINAL LOCATION AND SIZE OF GROMMETS BEFORE INSTALLATION.
- P. REFER TO FINISH SCHEDULE, INTERIOR ELEVATIONS AND SPECIFICATIONS FOR ALL MATERIAL INFORMATION AND LOCATIONS.












**CURRAN**  
ARCHITECTURE  
5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



CERTIFICATION



THIS DRAWING AND THE IDEAS, DESIGNS AND CONCEPTS CONTAINED HEREIN ARE THE EXCLUSIVE INTELLECTUAL PROPERTY OF CURRAN ARCHITECTURE, AND ARE NOT TO BE USED OR REPRODUCED, WHOLE OR IN PART, WITHOUT THE WRITTEN CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE

PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I  
NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086


ISSUE DATES

PERMIT SET	02.18.22
REVISIONS (ENTIRE SHEET)	06.14.22



210300

COMPACTOR ENCLOSURE


**A702**



ELEVATION - SIDE 3  
3/8" = 1'-0"



PLAN 1  
3/8" = 1'-0"



ELEVATION - FRONT 2  
3/8" = 1'-0"





# CURRAN

## ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753




SCANNELL  
PROPERTIES



wallace  
design  
collective

wallace design collective, pc  
structural, civil, landscape, survey  
1703 wyandotte street, suite 200  
kansas city, missouri 64108  
816.421.8282 800.364.5858

### CERTIFICATION



07/11/2022

### PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO

### ISSUE DATES

ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022


210300

S0.0

GENERAL NOTES

## DESIGN PARAMETERS

1.	BUILDING CODE	2018 INTERNATIONAL BUILDING CODE (IBC)
	OCCUPANCY CATEGORY	II
2.	LIVE LOADS	
	A. ROOF – NON–REDUCIBLE	20 PSF
	B. SLAB–ON–GRADE	350 PSF
3.	ROOF SNOW LOAD	
	A. GROUND SNOW LOAD, Pg	20 PSF
	B. FLAT ROOF SNOW LOAD, Pf	20 PSF
	C. SNOW EXPOSURE FACTOR, Ce	1.0
	D. SNOW LOAD IMPORTANCE FACTOR, I	1.0
	E. THERMAL FACTOR, Ct (BUILDING)	1.0
	F. SNOW DRIFT	PER REFERENCED CODE
4.	WIND DESIGN DATA	
	A. ULTIMATE WIND SPEED (3 SECOND GUST), V	109 MPH
	B. WIND IMPORTANCE FACTOR, I	1.00
	C. WIND EXPOSURE CATEGORY	C
	D. INTERNAL PRESSURE COEFFICIENT, Gcpi	+/- 0.18
	E. DESIGN WIND PRESSURE ON COMPONENTS AND CLADDING (1.0W)	
	1) WALLS (500 SQUARE FEET EFFECTIVE WIND AREA)	
	END ZONES	23.7 PSF
	INTERIOR ZONES	23.7 PSF
	2) ROOF (10 SQUARE FEET EFFECTIVE WIND AREA FOR DECK ATTACHMENT)	
	CORNER ZONES	89.1 PSF
	END ZONES	65.4 PSF
	INTERIOR ZONE 1	49.6 PSF
	INTERIOR ZONE 2	28.5 PSF
	F. WIDTH OF END ZONES, α	18.9 FT
5.	EARTHQUAKE DESIGN DATA	
	A. SEISMIC IMPORTANCE FACTOR, I	1.0
	B. MAPPED SPECTRAL RESPONSE ACCELERATION, Ss	9.9 %
	C. MAPPED SPECTRAL RESPONSE ACCELERATION, S1	6.8 %
	D. SITE CLASS	C
	E. SPECTRAL RESPONSE COEFFICIENT, Sds	0.086
	F. SPECTRAL RESPONSE COEFFICIENT, Sd1	0.068
	G. SEISMIC DESIGN CATEGORY	B
	H. STRUCTURAL SYSTEM (DUAL SYSTEM)	
	1) BASIC SEISMIC FORCE–RESISTING SYSTEM TYPE	H. STEEL SYSTEM
	2) VERTICAL ELEMENT TYPE	1) STEEL SYSTEM NOT SPECIFICALLY DETAILED FOR SEISMIC RESISTANCE
	3) BASIC SEISMIC FORCE–RESISTING SYSTEM TYPE	A. BEARING WALL SYSTEMS
	4) VERTICAL ELEMENT TYPE	2) ORDINARY PRECAST SHEAR WALLS
	5) DESIGN BASE SHEAR, LRFD	0.029 W
	6) SEISMIC RESPONSE COEFFICIENT, Cs	0.029
	7) CONTROLLING RESPONSE MODIFICATION FACTOR, R	3
J.	ANALYSIS PROCEDURE	EQUIVALENT LATERAL FORCE
6.	DEAD LOAD	
	A. EPDM MEMBRANE	0.3 PSF
	B. RIGID INSULATION	0.7 PSF
	C. ROOF DECK	2.0 PSF
	D. LIGHTS, PLUMBING, & HVAC	3.0 PSF
	E. SPRINKLERS	2.0 PSF
	F. STEEL JOISTS	2.0 PSF
	G. STEEL GIRDERS	2.0 PSF
	H. TOTAL DEAD LOAD ON JOISTS	10.0 PSF
	J. TOTAL DEAD LOAD ON COLUMNS	12.0 PSF

## GENERAL NOTES

### GENERAL

- STRUCTURAL ELEMENTS ARE NON–SELF SUPPORTING AND REQUIRE INTERACTION WITH OTHER ELEMENTS FOR STABILITY AND RESISTANCE TO LATERAL FORCES. FRAMING AND WALLS SHALL BE TEMPORARILY BRACED BY THE CONTRACTOR UNTIL PERMANENT BRACING, ROOF DECKS, AND WALLS HAVE BEEN INSTALLED AND CONNECTIONS BETWEEN THESE ELEMENTS HAVE BEEN MADE.
- THE STRUCTURAL DRAWINGS REPRESENT THE FINISHED STRUCTURE AND DO NOT INDICATE THE METHOD OF CONSTRUCTION, UNLESS NOTED OTHERWISE. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR THE MEANS, METHODS, TECHNIQUES, SEQUENCES, AND OPERATION OF CONSTRUCTION AND SAFETY PRECAUTIONS AND PROGRAMS INCIDENTAL THERETO.
- THE SIZE AND LOCATION OF EQUIPMENT PADS AND PENETRATIONS THROUGH THE STRUCTURE FOR MECHANICAL, ELECTRICAL, AND PLUMBING WORK SHALL BE VERIFIED BY THE CONTRACTOR. PENETRATIONS SHALL BE SUBJECT TO APPROVAL BY THE STRUCTURAL ENGINEER. REFER TO MECHANICAL, ELECTRICAL, AND PLUMBING DRAWINGS FOR OPENING LOCATIONS NOT SHOWN ON THE STRUCTURAL DRAWINGS.
- USE ONLY DIMENSIONS INDICATED ON THE DRAWINGS. DO NOT SCALE DRAWINGS OR USE ANY DIMENSIONS TAKEN FROM ELECTRONIC DRAWING FILES. CONTRACTOR SHALL COORDINATE IN–PLACE DIMENSIONS BASED ON TOLERANCES OF THE RESPECTIVE TRADES.
- ASSUME EQUAL SPACING IF NOT INDICATED ON DRAWINGS.
- THE GENERAL NOTES ARE AN INTEGRAL PART OF THE CONTRACT DOCUMENTS AND SHALL BE USED IN CONJUNCTION WITH THE STRUCTURAL DRAWINGS. WHERE REQUIREMENTS INDICATED ON THE STRUCTURAL DRAWINGS DIFFER FROM THE GENERAL NOTES, NOTIFY THE ARCHITECT AND THE STRUCTURAL ENGINEER.
- THE STRUCTURAL DRAWINGS ARE NOT INTENDED TO BE AN INDEPENDENT SET OF THE CONSTRUCTION DOCUMENTS. SEE ARCHITECTURAL, MEP, CIVIL AND OTHER DRAWINGS FOR INFORMATION RELATED TO THE STRUCTURAL WORK. CONTRACTOR SHALL VERIFY COORDINATION OF THE DESIRED DETAILS PRIOR TO CONSTRUCTION AND NOTIFY THE ARCHITECT AND THE STRUCTURAL ENGINEER IF ADDITIONAL COORDINATION IS REQUIRED.
- ARCHITECTURAL, MECHANICAL AND ELECTRICAL COMPONENTS AND SYSTEMS SHALL BE DESIGNED AND CONSTRUCTED TO RESIST SEISMIC FORCES AS DETERMINED IN CHAPTER 13 OF ASCE 7.

### FOUNDATIONS

- FOUNDATION DESIGNS, SUBGRADE PREPARATION NOTES, AND STRUCTURAL EARTH MOVING SPECIFICATION ARE BASED ON THE RECOMMENDATIONS PROVIDED IN THE GEOTECHNICAL REPORT, BY: OLSSON, INC. OF 1700 E 123RD ST., OLATHE, KANSAS 64080 (PHONE NO. 913–829–0078) DATED: FEBRUARY 2022.
- FOOTING DESIGNS ARE BASED ON AN ASSUMED STABLE, NON–EXPANSIVE SOIL WITH AN ALLOWABLE FOUNDATION PRESSURE OF 2500 PSF WITH A MAXIMUM DIFFERENTIAL SETTLEMENT OF 3/4 INCH. CONTRACTOR SHALL HIRE A GEOTECHNICAL ENGINEER TO DETERMINE WHETHER OR NOT SOIL MEETS THIS MINIMUM CRITERIA AND IF IT DOES NOT, SHALL NOTIFY ENGINEER SO THAT THE FOUNDATION MAY BE REDESIGNED ACCORDINGLY.
- CONTRACTOR AND TESTING LABORATORY REPRESENTATIVE SHALL READ THE GEOTECHNICAL REPORT AND BECOME THOROUGHLY FAMILIAR WITH SITE AND SUBGRADE INFORMATION GIVEN THEREIN. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DETERMINING EXACT QUANTITIES OF CUT AND FILL FOR ESTIMATING AND CONSTRUCTION. SUBGRADE SHALL BE PREPARED AS NOTED IN THE GEOTECHNICAL REPORT.
- A QUALIFIED AND REGISTERED GEOTECHNICAL ENGINEER, LICENSED IN THE STATE WHERE THE PROJECT IS LOCATED AND WORKING FOR THE TESTING LABORATORY, SHALL DETERMINE CONFORMANCE OF THE FOUNDATION BEARING STRATA WITH THE FOUNDATION DESIGN CRITERIA ABOVE, AND ALL OTHER CONTRACT DOCUMENTS. TESTING LABORATORY SHALL NOTIFY CONTRACTOR, ARCHITECT AND CONSULTING ENGINEER OF ANY CONDITIONS NOT IN ACCORDANCE WITH FOUNDATION DESIGN CRITERIA OR CONTRACT DOCUMENTS.

- USE ONLY STRUCTURAL FILL MATERIAL AS NOTED IN THE GEOTECHNICAL REPORT FOR FILL BELOW BUILDING AND FIVE FEET BEYOND THE EDGES OF THE BUILDING.
- FOUNDATION WALLS SHALL HAVE ADEQUATE TEMPORARY BRACING INSTALLED BY THE CONTRACTOR BEFORE BACKFILL IS PLACED AGAINST THEM. TEMPORARY BRACING SHALL NOT BE REMOVED UNTIL WALL IS PERMANENTLY BRACED.
- FOOTINGS SHALL BE POURED AGAINST UNDISTURBED SOIL, UNLESS NOTED OTHERWISE.
- AVOID DAMAGE TO UNDERGROUND UTILITIES SUCH AS WATER MAINS, SANITARY SEWERS, BURIED CABLES, ETC., WHICH MIGHT EXTEND ACROSS OR ADJOIN SITE.

### CONCRETE

- MINIMUM COMPRESSIVE STRENGTH (f'c) AT THE END OF 28 DAYS SHALL BE AS FOLLOWS:

A. FOOTINGS (GRADE BEAMS)	3000 PSI U.N.O. ON PLAN
B. FOUNDATION WALLS	3000 PSI
C. SLABS–ON–GRADE	4000 PSI
D. CONCRETE WALL PANELS (MINIMUM STRENGTH)	4000 PSI

MAXIMUM WATER/CEMENT RATIO = 0.48 TO 0.50 FOR FOOTINGS AND 0.52 FOR SLABS–ON–GRADE AND PRECAST WALLS PANELS  
  
SLUMP LIMITS = 4" + 1"  
  
CONCRETE SHALL BE NORMAL WEIGHT (145 PCF), UNLESS NOTED OTHERWISE.

- CEMENTITIOUS MATERIALS CONTENT SHALL NOT BE LESS THAN 520 POUNDS PER CUBIC YARD. USE OF ANY FLY ASH IN FLOOR SLAB MIXES SHALL BE NO MORE THAN 20%.
- AIR–ENTRAINED IS NOT REQUIRED FOR STRUCTURAL CONCRETE.
- AGGREGATES SHALL COMPLY WITH ASTM C 33 AND SHALL BE FREE OF DELETERIOUS MATTER AND SHALL BE MADE OF COARSE LIMESTONE OR GRANITE AGGREGATES.
- MATERIALS OR ADMIXTURES SHALL NOT CONTAIN ANY CALCIUM CHLORIDE. IF ADMIXTURES ARE UTILIZED, THEY SHALL BE COMPATIBLE WITH OTHER ADMIXTURES AND MUST NOT CONTRIBUTE WATER–SOLUBLE CHLORIDE IONS EXCEEDING THOSE PERMITTED IN HARDENED CONCRETE.
- REINFORCING STEEL SHALL MEET THE FOLLOWING:

A. DEFORMED BARS	ASTM A615, GRADE 60
B. WELDABLE DEFORMED BARS	ASTM A706, GRADE 60
C. WELDED WIRE FABRIC	ASTM A185
- WHERE DOWELS ARE INDICATED BUT NOT SIZED, PROVIDE DOWELS THAT MATCH SIZE AND LOCATION OF MAIN REINFORCING STEEL AND LAP SPLICE WITH THE MAIN REINFORCING STEEL. REINFORCING BARS SHALL BE SPLICED AS NOTED IN THE REINFORCING LAP SCHEDULE.
- REFER TO ACI 318 LATEST EDITION FOR CONCRETE COVER, ACI 315 LATEST EDITION FOR DETAILING, FABRICATION, PLACEMENT AND SUPPORT PRACTICES, ACI 347 FOR FORMWORK, ACI 305 FOR HOT WEATHER CONCRETING, ACI 306 FOR COLD WEATHER CONCRETING, AND ACI 301 LATEST EDITION FOR STANDARD PRACTICE FOR MIXING AND PLACING CONCRETE. PROVIDE CONCRETE COVER DIMENSIONS IN SHOP DRAWINGS FOR STRUCTURAL ENGINEER REVIEW.
- "C.J." INDICATES SAW CUT CONTRACTION JOINT OR DOWELED CONSTRUCTION JOINT IN SLAB–ON–GRADE. SLAB POURS SHALL BE SEPARATED BY A DOWELED CONSTRUCTION JOINT. CONTRACTION/CONSTRUCTION JOINTS SHALL BE LOCATED AS SHOWN ON PLANS OR AS DIRECTED BY THE STRUCTURAL ENGINEER.
- PROVIDE CORNER BARS THAT MATCH CONTINUOUS REINFORCEMENT SIZE AND QUANTITY AT INTERSECTIONS AND CORNERS OF FOUNDATIONS.
- REINFORCING BAR SUPPORTS SHALL BE BOLSTERS, CHAIRS, SPACERS AND OTHER DEVICES TO HOLD REINFORCING BARS AND WELDED WIRE REINFORCEMENT IN PLACE. MANUFACTURE BAR SUPPORTS FROM STEEL, PLASTIC OR PRECAST CONCRETE ACCORDING TO CRSI'S "MANUAL OF STANDARD PRACTICE" OF GREATER COMPRESSIVE STRENGTH THAN THE CONCRETE PLACED IN.
- FORM–FACING PANELS THAT WILL BE EXPOSED TO VIEW SHALL BE CONSTRUCTED TO MINIMIZE THE NUMBER OF JOINTS AND SHALL BE MADE OF PLYWOOD, METAL OR OTHER APPROVED PANEL MATERIAL. PLYWOOD MUST COMPLY WITH DOC PS 1 AND BE CLASS 1 OR BETTER.
- CHAMFER EXTERIOR CORNERS AND EDGES OF PERMANENTLY EXPOSED CONCRETE.
- THE CONCRETE SLABS SHOWN ON THE STRUCTURAL DRAWINGS HAVE BEEN DESIGNED FOR THE FINISHED STRUCTURE AND HAVE NOT BEEN DESIGNED FOR MEANS AND METHODS OF CONSTRUCTION, INCLUDING BUT NOT LIMITED TO, FORK LIFTS, MAN LIFTS, AND OTHER VEHICULAR TRAFFIC.
- A VAPOR RETARDER NOT LESS THAN 10 MILS THICK SHALL BE INSTALLED ONLY AT AREAS NOTATED ON THE CONSTRUCTION DOCUMENTS. THE RETARDER SHALL BE INSTALLED PER THE MANUFACTURER'S RECOMMENDATION WITH JOINTS USING THE MANUFACTURER'S RECOMMENDED ADHESIVE OR PRESSURE SENSITIVE JOINT TAPE AND INCLUDING THE MANUFACTURER'S PROPRIETARY PENETRATION FLASHING FOR ALL THROUGH–SLAB PENETRATIONS. LAP VAPOR RETARDER JOINTS 6 INCHES MINIMUM.
- CONCRETE SLABS–ON–GRADE SHALL BE CONSTRUCTED WITH A HARD TROWEL FINISH AND BE FINISHED ACCORDING TO ASTM E 1155 TO ACHIEVE THE MINIMUM TOLERANCES BELOW:  
  
OVERALL VALUES: FF = 50 FL = 35  
LOCAL VALUES: FF = 25 FL = 20
- THE CONCRETE SLAB–ON–GRADE SHALL BE CURED WITH AN APPROVED CURING MATERIAL THAT HAS BEEN SUBMITTED AND APPROVED BY THE ARCHITECT AND ENGINEER OF RECORD. THE FLOOR SHALL BE CURED WITH ONE COAT OF HARDENER/DENSIFIER (ASHFORD FORMULA SEALER OR APPROVED ALTERNATE).
- CONTRACTOR SHALL VERIFY ALL DIMENSIONS, OPENINGS, BLOCKOUTS, RECESSES, ELEVATIONS, ANCHOR RODS AND EMBED LOCATIONS PRIOR TO CONCRETE PLACEMENT. THE CONTRACTOR SHALL VERIFY WITH ARCHITECTURAL, STRUCTURAL AND MEP DRAWINGS FOR LOCATIONS OF REQUIRED COORDINATION ITEMS. CONTRACTOR SHALL CONTACT THE ARCHITECT OR ENGINEER IF AN ERROR OR OMISSION OCCURS AFTER CONCRETE PLACEMENT.
- ANCHOR BOLTS AND EMBED PLATES SHALL BE TIED INTO THE REBAR CAGE AND HELD IN PLACE WITH A RIGID TEMPLATE TO PREVENT MOVEMENT DURING CONCRETE PLACEMENT.
- NON–SHRINK GROUT SHALL BE PRE–MIXED, NON–SHRINKING WITH A MINIMUM COMPRESSIBE STRENGTH OF 5000 PSI IN 28 DAYS CONFORMING TO USACE SPECIFICATIONS NO. CRD–6821.

### CONCRETE WALL PANELS

- THE STRUCTURAL DRAWINGS REPRESENT THE REQUIRED FINAL IN PLACE LOADINGS FOR THE CONCRETE WALL PANELS. THE PANELS SHALL BE DESIGNED BY THE TILT–UP SUPPLIER FOR THE FINAL IN PLACE LOADINGS ALONG WITH BEING DESIGNED FOR ERECTION STRESSES, TEMPORARY BRACING OR LIFTING OF THE WALL PANELS. WALL PANELS SHALL BE DESIGNED AND DETAILED TO ADHERE TO ALL LOCAL CODES.
- THE CONTRACTOR SHALL PROVIDE SHOP DRAWINGS FOR THE TILT–UP WALL PANELS. SHOP DRAWINGS SHALL INCLUDE CALCULATIONS FOR FINAL IN PLACE LOADINGS, ERECTION, LIFTING AND TEMPORARY BRACING OF THE WALL PANELS ALONG WITH ANY OTHER ADDITIONAL CONSTRUCTION CONSIDERATIONS. SHOP DRAWINGS AND CALCULATIONS FOR THE CONSTRUCTION CONSIDERATIONS SHALL BE DESIGNED, SEALED AND SIGNED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE WHERE THE PROJECT IS LOCATED. DESIGN CALCULATIONS SHALL SHOW STRESSES IN THE PANELS FOR THE LOADS PRESCRIBED IN THE CONSTRUCTION DOCUMENTS ALONG WITH THERMAL DIFFERENTIAL AND ERECTION AND LIFTING FORCES. THE DEFERRED SUBMITTAL DOCUMENTS SHALL BE SUBMITTED TO THE ARCHITECT OR ENGINEER OF RECORD WHO SHALL REVIEW THEM AND FORWARD THEM TO THE BUILDING OFFICIAL AS REQUESTED WITH A NOTATION INDICATING THAT THE DEFERRED SUBMITTAL DOCUMENTS HAVE BEEN REVIEWED AND BEEN FOUND TO BE IN GENERAL CONFORMANCE TO THE DESIGN OF THE BUILDING. THE DEFERRED SUBMITTAL ITEMS SHALL NOT BE INSTALLED UNTIL THE DESIGN AND SUBMITTAL DOCUMENTS HAVE BEEN APPROVED BY THE BUILDING OFFICIAL.
- THE CONTRACTOR SHALL VERIFY THE PROPOSED TILT–UP WALL PANELS ARE CAPABLE OF MEETING THE FINAL IN PLACE AND ERECTION REQUIREMENTS PRIOR TO BEGINNING THE WORK. ANY DEVIATIONS FROM THE WALL PANELS SHOWN ON THE STRUCTURAL DRAWINGS SHALL BE QUALIFIED IN THE CONTRACTOR'S BID.
- THE CONTRACTOR SHALL PROVIDE ADEQUATE VERTICAL AND LATERAL SYSTEM COMPONENTS TO SUPPORT THE LOADINGS STIPULATED IN THE CONSTRUCTION DOCUMENTS. THE FOUNDATIONS HAVE BEEN DESIGNED BASED ON THESE LOADING REQUIREMENTS. ANY DEVIATIONS IN THE LOADINGS SHALL BE APPROVED BY THE ENGINEER OF RECORD PRIOR TO PROCEEDING.
- THE CONCRETE WALL PANELS SHALL CONFORM TO ACI 301, ACI 318, ACI 551, CONCRETE REINFORCING STEEL INSTITUTE (CRSI) "MANUAL OF STANDARD PRACTICE", AND AWS D1.4 STRUCTURAL WELDING CODE FOR REINFORCING STEEL. SEE THE CONCRETE GENERAL NOTES FOR ADDITIONAL CONFORMANCE SPECIFICATIONS.
- SEE THE CONCRETE GENERAL NOTES AND SPECIFICATIONS FOR MIX DESIGN DATA AND REQUIREMENTS.
- THE TILT–UP WALL PANEL SHALL ADHERE TO THE MECHANISMS SET FORTH IN THE STRUCTURAL CONSTRUCTION DOCUMENTS. ADDITIONALLY, THE DESIGN SHALL INCLUDE ALL BOLTS, EMBEDMENT PLATES, BLOCKOUTS, FUTURE KNOCKOUT PANEL LOCATIONS, BRACING AND SUPPORTING STRUCTURE.
- SEE THE STEEL GENERAL NOTES AND SPECIFICATIONS FOR SECTION PROPERTY REQUIREMENTS. ALL STEEL SHAPES, PLATES, ANCHORS, BOLTS, NUTS AND WASHERS SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.
- CAST–IN–PLACE ANCHORS SHALL BE HEADED STUDS OR DEFORMED BAR ANCHORS. ASTM 615 REINFORCING BARS SHALL NOT BE USED AS ANCHORS.
- ALL WELDS SHALL BE PERFORMED BY A AWS CERTIFIED WELDER AND IN ACCORDANCE WITH AWS D1.1 "STRUCTURAL WELDING CODE" AND AWS D1.4 "STRUCTURAL WELDING CODE FOR REINFORCING STEEL". ALL WELDS SHALL BE PAINTED WITH ZINC RICH REPAIR PAINT AFTER WELDING.
- ALL WELDS FOR DEFORMED BAR ANCHORS SHALL USE E90XX ELECTRODES.
- PROVIDE BEARING PADS AND GROUT MATERIALS AS REQUIRED PER CODE AND INDUSTRY STANDARDS.
- COORDINATE WITH THE ARCHITECTURAL DRAWINGS AND SPECIFICATIONS ANY ADDITIONAL REQUIREMENTS FOR DIMENSIONS, FINISH, REVEALS AND ANY OTHER REQUIREMENTS OF THE CONCRETE WALL PANELS.

- CONTRACTOR SHALL ERECT THE CONCRETE WALL PANELS SUCH THAT IT IS SAFE FOR PERSONNEL AND PROPERTY AND PROVIDE BRACING TO PROTECT THE PANELS AGAINST WIND, SEISMIC AND FORCES THAT MAY OCCUR THROUGHOUT THE CONSTRUCTION PROCESS. TEMPORARY BRACING SHALL REMAIN IN PLACE UNTIL ALL PERMANENT BRACING, DECKING, CONNECTIONS AND WALL PANELS HAVE BEEN FULLY INSTALLED.
- CONCRETE WALL PANELS SHALL BE ERECTED TO ADHERE TO THE TOLERANCES OF THE LATEST AMERICAN CONCRETE INSTITUTE SPECIFICATIONS. ERECTION TOLERANCES SHALL BE COORDINATED WITH THE STEEL SUPPLIER TO PROVIDE PROPER FIT–UP. DEFLECTIONS OF THE STRUCTURAL STEEL SYSTEM MAY OCCUR DURING CONCRETE WALL PANEL ERECTION. THESE DEFLECTIONS MAY REQUIRE ADJUSTMENT AND RESETTING OF CONCRETE WALL PANELS IN ORDER TO MEET THE TOLERANCES. THE CONTRACTOR SHALL BE AWARE OF THIS ITERATION PROCESS IN HIS BID AND IS RESPONSIBLE FOR THE TOLERANCES BEING MET.
- THE CONCRETE SLABS SHOWN ON THE STRUCTURAL DRAWINGS HAVE BEEN DESIGNED FOR THE FINISHED STRUCTURE AND HAVE NOT BEEN DESIGNED FOR CRANE USE AND CONCRETE WALL PANEL BRACING. THE CONTRACTOR SHALL VERIFY THE SLAB ADEQUACY AND SUBMIT PROPOSED DESIGNED, IF REQUIRED, TO THE STRUCTURAL ENGINEER FOR REVIEW.
- ALL CONCRETE WALL PANELS COMPONENTS SHALL ADHERE TO THE DETAILING, FABRICATION AND ERECTION REQUIREMENTS OF THE LATEST EDITIONS OF ACI 301 (SPECIFICATIONS FOR CONCRETE), ACI 318 (STRUCTURAL CONCRETE BUILDING CODE), AWS D1.4 (WELDING CODE FOR REINFORCING STEEL), CRSI (MANUAL OF STANDARD PRACTICE), PCI MNL 116 (MANUAL FOR QUALITY CONTROL FOR PLANS AND PRODUCTION OF PRECAST CONCRETE PRODUCTS), PCI MNL 120 (PCI DESIGN HANDBOOK) AND PCI MNL 135 (TOLERANCE MANUAL FOR PRECAST PRESTRESSED CONCRETE CONSTRUCTION).
- CONCRETE WALL PANELS SHALL PROVIDE EXPANSIONS JOINTS AT THE ROOF EXPANSION JOINT TO ALLOW FOR THERMAL EXPANSION AND CONTRACTION. ADDITIONALLY, THE PRECAST SUPPLIER SHALL ALLOW FOR DIFFERENTIAL MOVEMENT BETWEEN WALL PANELS BY ALLOWING EXPANSION EVERY FIFTH WALL PANEL.
- CONCRETE WALL PANELS SHALL BE SOLID CORE BELOW FINISH FLOOR ELEVATION.

### STRUCTURAL STEEL

- STRUCTURAL STEEL SHALL MEET THE FOLLOWING MINIMUM YIELD STRESS (Fy), UNLESS NOTED OTHERWISE:

	YIELD	ASTM SPECIFICATION
A. W, WT SHAPES:	50 KSI	A992
B. BARS, PLATES, CHANNELS, ANGLES:	36 KSI	A36
C. SQUARE, RECTANGULAR HSS:	50 KSI	A500, GRADE C
D. ANCHOR RODS:	36 KSI OR 55 KSI	F1554
E. ALL–THREAD RODS:	36 KSI	A36
F. HEADED STUD ANCHORS:	65 KSI TENSILE STRESS	A108, GRADES 1010–1020
- ALL STRUCTURAL STEEL SHALL ADHERE TO THE DETAILING, FABRICATION AND ERECTION REQUIREMENTS OF THE LATEST EDITIONS OF THE AISC SPECIFICATION FOR STRUCTURAL STEEL BUILDINGS AND THE AISC CODE OF PRACTICE.
- BOLTS FOR STEEL BEAM AND COLUMN CONNECTIONS SHALL BE 3/4–INCH DIAMETER ASTM A325–N HIGH–STRENGTH BOLTS UNLESS NOTED OTHERWISE. ALL BOLTED CONNECTIONS ARE BEARING TYPE AND SHALL BE SNUG TIGHTENED UNLESS NOTED OTHERWISE. FOR PRETENSIONED OR SLIP–CRITICAL JOINTS, THE METHOD OF INSTALLATION SHALL BE TURN–OF–NUT WITH MATCH MARKING, TWIST–OFF–TYPE TENSION CONTROL BOLT ASSEMBLIES (ASTM F1852), OR DIRECT TENSION INDICATORS (ASTM F959).
- WELDING SHALL MEET ANSI / AWS D1.1, STRUCTURAL WELDING CODE LATEST REVISION. ELECTRODES SHALL BE E70XX, LOW HYDROGEN. ALL STRUCTURAL STEEL WELDS SHALL BE PERFORMED BY A AWS CERTIFIED WELDER.
- WELDS NOT SPECIFICALLY SIZED ON THE STRUCTURAL DRAWINGS SHALL BE THE MINIMUM SIZE PER THE LATEST AWS D1.1.
- PROVIDE DOUBLE NUTS AND DOUBLE WASHERS FOR STEEL COLUMN ANCHOR BOLTS TO ALLOW FOR ADJUSTMENT IN BASE PLATE ELEVATION. PROVIDE 1 1/2 INCH NON–SHRINK GROUT UNDER BASE PLATE AFTER ERECTION. USE 2 1/2 INCHES NON–SHRINK GROUT WHEN COLUMN ANCHOR BOLTS ARE 1 1/4 INCH DIAMETER OR LARGER. NON–SHRINK GROUT SHALL BE NON–METALLIC WITH A MINIMUM COMPRESSIVE STRENGTH OF 5,000 PSI AT 28 DAYS.
- SHEAR CONNECTORS SHALL BE A CARBON STEEL HEADED STUD TYPE ASTM A108 GRADES 1010 THRU 1020, AWS D1.1, TYPE B WITH ARC SHIELDS.
- ALL CONNECTIONS ON THE STRUCTURAL DRAWINGS, UNLESS NOTED OTHERWISE, SHALL BE DESIGNED AND DETAILED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE WHERE THE PROJECT IS LOCATED, EMPLOYED OR RETAINED BY THE STEEL FABRICATOR. THE DESIGN AND DETAILING SHALL COMPLY WITH ALL APPLICABLE CODES AND SPECIFICATION SECTIONS.
- THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR INCLUDING THE COSTS FOR ALL MISCELLANEOUS STEEL IN THEIR BID REGARDLESS OF WHETHER THOSE ITEMS ARE INDICATED ON THE STRUCTURAL DRAWINGS. THESE COSTS SHALL INCLUDE BUT ARE NOT LIMITED TO MISCELLANEOUS STEEL ITEMS SHOWN ON ARCHITECTURAL, CIVIL, MECHANICAL, PLUMBING AND ELECTRICAL DRAWINGS SUCH AS SHELF ANGLES, GLAZING SUPPORTS AND LINTELS.
- LEDGER ANGLES AND LINTELS IN EXTERIOR WALL SYSTEMS SHALL BE HOT DIPPED GALVANIZED PER ASTM A123.
- ALL STRUCTURAL STEEL SHALL HAVE A COAT OF LIGHT GRAY PAINT TO PROVIDE PROTECTION AND GOOD APPEARANCE.



5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317.288.0681  
F :: 317.288.0753



**wallace design collective, pc**  
structural • civil • landscape • survey  
1703 wyandotte street, suite 200  
kansas city, missouri 64108  
816.421.8282 • 800.364.5858

STATE OF MISSOURI  
JAMES M. GRANICH  
NUMBER  
PE-2014023909  
PROFESSIONAL ENGINEER

07/11/2022

## LEE'S SUMMIT LOGISTICS BUILDING A LOT 1 TENANT IMPROVEMENTS

NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO

ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022

## S0.1

1. THE FOLLOWING STRUCTURAL COMPONENTS SHALL BE DESIGNED AND SUBMITTED BY OTHERS FOR APPROVAL IN ACCORDANCE WITH DRAWINGS AND SPECIFICATIONS.
  - A. STRUCTURAL STEEL CONNECTIONS OF FRAMING AND BRACING ELEMENTS
  - B. STEEL JOISTS AND JOIST GIRDERS (CONTRACTOR SHALL OBTAIN FIRE LINE LOCATIONS AND SIZES PRIOR TO SUBMITTAL OF JOIST SHOP DRAWINGS.)
  - C. STEEL SELF-SUPPORTING STAIRS AND HANDRAIL FRAMING
  - D. STOREFRONT AND CURTAINWALL FRAMING, ACCESSORIES AND ATTACHMENTS TO STRUCTURE
  - E. EXCAVATION SUPPORT
  - F. TEMPORARY BRACING AND SUPPORT
  - G. CONCRETE WALL PANEL REINFORCING
  - H. ROOF ACCESS LADDERS AND SAFETY CAGES
  - I. SEISMIC ANCHORAGE AND BRACING OF MEP COMPONENTS
  - J. HOLLOW-CORE PRECAST CONCRETE
2. DOCUMENTS FOR DEFERRED STRUCTURAL SUBMITTAL ITEMS SHALL BE DESIGNED, SEALED AND SIGNED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE WHERE THE PROJECT IS LOCATED. THE DEFERRED SUBMITTAL DOCUMENTS SHALL BE SUBMITTED TO THE ARCHITECT OR ENGINEER OF RECORD WHO SHALL REVIEW THEM AND FORWARD THEM TO THE BUILDING OFFICIAL AS REQUESTED WITH A NOTATION INDICATING THAT THE DEFERRED SUBMITTAL DOCUMENTS HAVE BEEN REVIEWED AND BEEN FOUND TO BE IN GENERAL CONFORMANCE TO THE DESIGN OF THE BUILDING. THE DEFERRED SUBMITTAL ITEMS SHALL NOT BE INSTALLED UNTIL THE DESIGN AND SUBMITTAL DOCUMENTS HAVE BEEN APPROVED BY THE BUILDING OFFICIAL.

1. SHOP DRAWINGS AND SUBMITTALS SHALL BE REVIEWED AND APPROVED BY THE CONTRACTOR PRIOR TO SUBMITTAL FOR THE ENGINEER'S REVIEW. THE STRUCTURAL ENGINEER'S REVIEW IS TO CHECK THE GENERAL CONFORMANCE OF THE SHOP DRAWINGS WITH THE CONTRACT DOCUMENTS. THE CONTRACTOR IS RESPONSIBLE FOR ANY ALTERATIONS FROM THE CONTRACT DOCUMENTS WHICH MAY INCLUDE QUANTITIES, DIMENSIONAL ERRORS OR OTHER ERRORS AND OMISSIONS IN THE SHOP DRAWINGS.
2. SHOP DRAWINGS SHALL NOT BE REPRODUCTIONS OF THE CONTRACT DOCUMENTS.
3. THE FOLLOWING STRUCTURAL COMPONENTS SHALL BE SUBMITTED AS A SHOP DRAWING FOR REVIEW:

- A. CONCRETE MIX DESIGN AND MATERIALS
- B. CONCRETE REINFORCING STEEL
- C. CONCRETE FORMWORK
- D. STRUCTURAL STEEL
- E. STEEL JOISTS
- F. STEEL ROOF DECK AND THEIR ATTACHMENTS
- G. ALL DEFERRED SUBMITTAL ITEMS

1. THE OWNER SHALL EMPLOY ONE OR MORE SPECIAL INSPECTORS TO PROVIDE INSPECTIONS DURING CONSTRUCTION OF THE TYPES OF WORK LISTED IN THE STATEMENT OF SPECIAL INSPECTIONS PER SECTION 1704 OF THE IBC. THE SPECIAL INSPECTOR SHALL BE A QUALIFIED PERSON WHO SHALL DEMONSTRATE COMPETENCE, TO THE SATISFACTION OF THE BUILDING OFFICIAL, FOR INSPECTION OF THE PARTICULAR TYPE OF CONSTRUCTION OR OPERATION REQUIRING SPECIAL INSPECTION. THESE INSPECTIONS ARE IN ADDITION TO THE INSPECTIONS SPECIFIED IN THE PROJECT SPECIFICATIONS.
2. SPECIAL INSPECTORS SHALL KEEP RECORDS OF INSPECTIONS. THE SPECIAL INSPECTOR SHALL FURNISH INSPECTION REPORTS TO THE BUILDING OFFICIAL, AND TO THE REGISTERED DESIGN PROFESSIONAL IN RESPONSIBLE CHARGE. REPORTS SHALL INDICATE THAT WORK INSPECTED WAS DONE IN CONFORMANCE TO APPROVED CONSTRUCTION DOCUMENTS. DISCREPANCIES SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF THE CONTRACTOR FOR CORRECTION. IF THE DISCREPANCIES ARE NOT CORRECTED, THE DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE BUILDING OFFICIAL AND TO THE REGISTERED DESIGN PROFESSIONAL IN RESPONSIBLE CHARGE. UPON COMPLETION OF EACH PHASE OF WORK, A FINAL REPORT DOCUMENTING REQUIRED SPECIAL INSPECTIONS AND CORRECTION OF ANY DISCREPANCIES NOTED IN THE INSPECTIONS SHALL BE SUBMITTED AT A POINT IN TIME AGREED UPON BY THE PERMIT APPLICANT AND THE BUILDING OFFICIAL PRIOR TO THE START OF WORK.
3. THE CONTRACTOR IS RESPONSIBLE FOR NOTIFYING THE SPECIAL INSPECTOR REGARDING INDIVIDUAL INSPECTION FOR ITEMS LISTED ON THE STATEMENT OF SPECIAL INSPECTIONS AND AS NOTED ON THE BUILDING DEPARTMENT APPROVAL PLANS. ADEQUATE NOTICE AND ACCESS TO APPROVED PLANS SHALL BE PROVIDED SO THAT THE SPECIAL INSPECTOR HAS TIME TO BECOME FAMILIAR WITH THE PROJECT.
4. FABRICATORS OF STRUCTURAL LOAD-BEARING MEMBERS AND ASSEMBLIES SHALL CONFORM TO THE REQUIREMENTS OF SECTION 1704.2 OF THE IBC.
5. THE FOLLOWING ITEMS REQUIRE SPECIAL INSPECTION PER SECTION 1700 OF THE REFERENCED BUILDING CODE.

- A. BOLTS & ANCHORS EMBEDDED IN CONCRETE
- B. PLACEMENT OF REINFORCING STEEL IN CONCRETE
- C. CONCRETE MIX DESIGN
- D. CONCRETE FORMWORK
- E. STRUCTURAL STEEL FABRICATIONS
- F. STRUCTURAL STEEL BOLTING AND WELDING
- G. ON SITE STRUCTURAL FRAMING
- H. INSPECTION OF ROOF DECK ATTACHMENTS
- I. SHEAR WALL ATTACHMENTS AND ANCHORS
- J. POST INSTALLED ANCHORS
- K. ON SITE SOILS, EXCAVATIONS, FILLING AND COMPACTION
- L. ERECTION OF PRECAST CONCRETE MEMBERS

1. ANCHORS SHALL ONLY BE INSTALLED WHERE SPECIFIED ON THE CONTRACT DRAWINGS. THE CONTRACTOR SHALL OBTAIN APPROVAL FROM THE STRUCTURAL ENGINEER PRIOR TO INSTALLING POST INSTALLED ANCHORS IN PLACE OF MISSING OR MIS-PLACED CAST-IN-PLACE ANCHORS. CARE SHALL BE TAKEN IN PLACING POST-INSTALLED ANCHORS TO AVOID CONFLICTS WITH EXISTING REINFORCING.
2. THE CONTRACTOR SHALL SUBMIT PRODUCT DATA WITH DESIGN VALUES AND PHYSICAL PROPERTIES FOR ALL POST INSTALLED ANCHORS. ADDITIONALLY, THE CONTRACTOR SHALL SUBMIT CERTIFIED ICC ESR OR ESR REPORTS WHICH VERIFY COMPLIANCE WITH THE SPECIFIED CRITERIA.
3. SUBSTITUTION REQUESTS FOR PRODUCTS OTHER THAN THOSE SPECIFIED ON THE CONTRACT DRAWINGS SHALL BE SUBMITTED BY THE CONTRACTOR TO THE STRUCTURAL ENGINEER ALONG WITH CALCULATIONS THAT ARE SIGNED AND SEALED BY A QUALIFIED PROFESSIONAL ENGINEER RESPONSIBLE FOR THEIR PREPARATION AND LICENSED IN THE STATE WHERE THE PROJECT IS LOCATED. THE CALCULATIONS SHALL DEMONSTRATE THAT THE SUBSTITUTED PRODUCT IS CAPABLE OF ACHIEVING THE PERTINENT EQUIVALENT PERFORMANCE VALUES OF THE SPECIFIED PRODUCT USING THE APPROPRIATE DESIGN PROCEDURE AND/OR STANDARDS AS REQUIRED BY THE BUILDING CODE.
4. ALL HOLES SHALL BE DRILLED, DRY, AND CLEANED AND ANCHORS SHALL BE INSTALLED IN ACCORDANCE PER ANCHOR MANUFACTURER'S WRITTEN SPECIFICATIONS. THE LATEST VERSION OF THE WRITTEN SPECIFICATION SHALL BE ON-SITE AND FOLLOWED DURING THE INSTALLATION OF THE ANCHORS.
5. THE ANCHOR EMBEDMENT DEPTH SHALL BE DEFINED AS THE DEPTH FROM THE SURFACE FACE OF THE LOAD BEARING BASE MATERIAL TO THE DEEPEST PART OF THE ANCHOR AFTER THE ANCHOR HAS BEEN DRIVEN INTO THE HOLE, BUT NOT YET EXPANDED, IF APPLICABLE.
6. ANCHORS AT ALL WEATHER EXPOSED LOCATIONS SHALL BE STAINLESS STEEL.
7. NON-EPOXY BASED ADHESIVES SHALL BE USED WHEN BASE MATERIAL TEMPERATURE IS BELOW 40 DEGREES FAHRENHEIT.
8. THE FOLLOWING CONCRETE MECHANICAL ANCHORS ARE ALLOWED FOR USE IN CRACKED AND UNCRACKED CONCRETE AND HAVE BEEN TESTED AND QUALIFIED FOR USE IN ACCORDANCE WITH ACI 355.2 AND ICC-ES AC193.
  - A. SIMPSON STRONG-TIE "STRONG BOLT Z" (ICC-ES ESR-3037)
  - B. SIMPSON STRONG-TIE "TITEN HD" (ICC-ES ESR-2713)
  - C. HILTI "KWIK BOLT TZ" EXPANSION ANCHOR (ICC-ES ESR 1917)
  - D. HILTI "HSL-3" HEAVY DUTY EXPANSION ANCHOR (ICC-ES ESR 1545)
  - E. HILTI "HDA" UNDERCUT ANCHOR (ICC-ES ESR 1546)
  - F. HILTI "KWIK HUS EZ" EXPANSION ANCHOR (ICC-ES ESR 3027)
9. THE FOLLOWING CONCRETE ADHESIVE ANCHORS ARE ALLOWED FOR USE IN CRACKED AND UNCRACKED CONCRETE AND HAVE BEEN TESTED AND QUALIFIED FOR USE IN ACCORDANCE WITH ACI 355.4 AND ICC-ES AC308.
  - A. SIMPSON STRONG-TIE "SET-XP" (ICC-ES ESR-2508)
  - B. HILTI "HIT-HY200" (ICC-ES ESR-1385)
  - C. HILTI "HIT-RE 500 V3" (ICC-ES ESR-3814)

1. CONCRETE MASONRY UNITS SHALL MEET ASTM SPECIFICATION C90, WITH A MINIMUM UNIT COMPRESSIVE STRENGTH = 1900 PSI. THE SPECIFIED DESIGN COMPRESSIVE STRENGTH OF THE CONCRETE MASONRY ASSEMBLY (f'm) SHALL BE 1900 PSI.
2. MORTAR SHALL BE A PREBLENDED DRY MIX CONFORMING TO ASTM C1714 AND MEETING THE PROPERTY SPECIFICATIONS OF ASTM C270 TYPE "S" MORTAR FOR BELOW GRADE. TYPE "N" MORTAR FOR ABOVE GRADE. MASONRY CEMENT SHALL NOT BE USED FOR MORTAR.
3. GROUT SHALL MEET ASTM SPECIFICATION C476 AND HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 2000 PSI.
4. SOLID GROUT HOLLOW MASONRY CELLS AS NOTED ON STRUCTURAL DRAWINGS. USE GROUT METHOD OF CONSTRUCTION CONFORMING TO REQUIREMENTS OF CURRENT MSJC. GROUT SPACE DIMENSIONS AND MAXIMUM POUR HEIGHTS SHALL COMPLY WITH MSJC.
  - A. LIMIT THE HEIGHT OF VERTICAL GROUT POURS TO 4'-0" OR THE DISTANCE BETWEEN BOND BEAMS, WHICHEVER IS LESS.
  - B. GROUTING SHALL BE A CONTINUOUS PROCEDURE FOR EACH LIFT. DO NOT ALLOW HORIZONTAL CONSTRUCTION JOINT TO FORM BY DISCONTINUING GROUTING.
  - C. VERTICAL GROUT POUR EXCEEDING 12 INCHES SHALL BE MECHANICALLY CONSOLIDATED USING A VIBRATOR WITH A MAXIMUM 3/4 INCH DIAMETER HEAD.
5. CONTRACTOR SHALL CLEAN THE GROUT SPACES SUCH THAT THEY ARE FREE OF MORTAR DROPPINGS, DEBRIS, LOOSE AGGREGATES AND ANY MATERIAL THAT WOULD PREVENT CONTINUITY OF THE GROUT.
6. HORIZONTAL JOINT REINFORCEMENT SHALL BE LADDER TYPE. JOINT REINFORCEMENT SHALL BE SPACED AT 8 INCHES ON CENTER BELOW FINISHED FLOOR AND IN PARAPETS, AND 16 INCHES ON CENTER ABOVE FINISHED FLOOR.
7. CONCRETE MASONRY SHALL BE LAID IN RUNNING BOND.
8. CONCRETE MASONRY BELOW FINISHED FLOOR SHALL BE NORMAL WEIGHT UNITS AND SHALL HAVE ALL THE CELLS FULLY GROUTED. CONCRETE MASONRY ABOVE FINISHED FLOOR SHALL BE MEDIUM WEIGHT AND IS TO BE GROUTED ONLY AT REINFORCED CELLS AND BOND BEAMS, UNLESS NOTED OTHERWISE. ALL CELLS WITH REINFORCING OR EMBEDDED ITEMS SHALL BE GROUTED SOLID.
9. REFERENCE WALL SECTIONS AND DETAILS FOR MISCELLANEOUS BOND BEAM LOCATIONS AND EMBEDDED ITEMS. USE OPEN KNOCK OUT BOND BEAM BLOCK. DO NOT USE TROUGH TYPE BLOCKS FOR BOND BEAMS. DO NOT CONTINUE BOND BEAM REINFORCING THROUGH CONTROL JOINTS, UNLESS NOTED OTHERWISE.
10. REINFORCING STEEL SHALL MEET ASTM SPECIFICATION A615, GRADE 60. REINFORCING STEEL SHALL BE SPLICED AS NOTED IN THE REINFORCING LAYOUT SCHEDULE.
11. PROVIDE TEMPORARY BRACING FOR WALLS, LINTELS, AND OTHER MASONRY DURING ERECTION. BRACING SHALL BE DESIGNED IN ACCORDANCE WITH THE MASON CONTRACTORS ASSOCIATION OF AMERICA STANDARD PRACTICE FOR BRACING MASONRY WALLS UNDER CONSTRUCTION. DESIGN SHALL BE PERFORMED BY AN ENGINEER LICENSED IN THE STATE WHERE THE PROJECT IS LOCATED. BRACING SHALL REMAIN UNTIL ROOFING AND OTHER STRUCTURAL ELEMENTS ARE COMPLETE AND PROVIDE PERMANENT STABILITY.

1. MINIMUM COMPRESSIVE STRENGTH ( $f'_c$ ) AT THE END OF 28 DAYS OF 5000 PSI. REFERENCE SPECIFICATIONS FOR MAXIMUM WATER/CEMENT RATIOS, MINIMUM CEMENT CONTENTS AND OTHER MIX DESIGN REQUIREMENTS. CONCRETE SHALL BE NORMAL WEIGHT (145 PCF), UNLESS NOTED OTHERWISE.
2. THE STRUCTURAL DRAWINGS REPRESENT THE FINAL IN PLACE CONCRETE WALL PANELS. THE PANELS HAVE NOT BEEN DESIGNED FOR ERECTION STRESSES, TEMPORARY BRACING OR LIFTING OF THE WALL PANELS.
3. ALL PRECAST COMPONENTS AND CONNECTIONS SHALL BE DESIGNED AND DETAILED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE WHERE THE PROJECT IS LOCATED, EMPLOYED OR RETAINED BY THE PRECAST MANUFACTURER. CALCULATIONS SHALL INCLUDE CONSIDERATIONS FOR ERECTION, LIFTING AND TEMPORARY BRACING ALONG WITH ANY OTHER ADDITIONAL CONSTRUCTION CONSIDERATIONS.
4. THE CONTRACTOR SHALL VERIFY THE PROPOSED PRECAST COMPONENTS ARE CAPABLE OF MEETING THE ERECTION REQUIREMENTS PRIOR TO BIDDING THE WORK. ANY DEVIATIONS FROM THE WALL PANELS SHOWN ON THE STRUCTURAL DRAWINGS SHALL BE QUALIFIED IN THE CONTRACTOR'S BID. ANY DEVIATIONS SHALL BE APPROVED BY THE ARCHITECT AND ENGINEER OF RECORD PRIOR TO PROCEEDING.
5. THE PRECAST CONTRACTOR SHALL PROVIDE ADEQUATE COMPONENTS TO SUPPORT THE VERTICAL AND LATERAL LOADINGS STIPULATED IN THE CONSTRUCTION DOCUMENTS. ANY DEVIATIONS SHALL BE APPROVED BY THE ENGINEER OF RECORD PRIOR TO PROCEEDING. THE SUPPORTING STRUCTURE HAS BEEN DESIGNED BASED ON THE DETAILS SHOWN.
6. REFERENCE THE STEEL GENERAL NOTES AND SPECIFICATIONS FOR STRUCTURAL STEEL REQUIREMENTS. ALL STEEL SHAPES, PLATES, ANCHORS, BOLTS, NUTS AND WASHERS SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.
7. CAST-IN-PLACE ANCHORS SHALL BE HEADED STUDS OR WELDABLE DEFORMED BARS. ASTM A615 REINFORCING BARS SHALL NOT BE USED AS ANCHORS.
8. REFERENCE ARCHITECTURAL DRAWINGS AND SPECIFICATIONS FOR PANEL SIZE, LOCATIONS, JOINTS, FINISH, REVEALS AND OTHER AESTHETIC REQUIREMENTS OF THE PRECAST WALL PANELS.
9. REFERENCE ARCHITECTURAL AND MEP DRAWINGS FOR OPENINGS, SLEEVES AND INSERTS NOT SHOWN ON THE STRUCTURAL DRAWINGS. ITEMS SHALL BE SHOWN ON SHOP DRAWINGS FOR APPROVAL.
10. PROVIDE TEMPORARY BRACING FOR PRECAST COMPONENTS DURING ERECTION. BRACING SHALL BE DESIGNED IN ACCORDANCE WITH PRECAST/PRESTRESSED CONCRETE INSTITUTE (PCI) HANDBOOK DESIGN SHALL BE PERFORMED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE WHERE THE PROJECT IS LOCATED. BRACING SHALL REMAIN UNTIL STRUCTURAL ELEMENTS THAT PROVIDE PERMANENT SUPPORT ARE FULLY INSTALLED.
11. ERECTION TOLERANCES SHALL BE COORDINATED WITH THE STEEL SUPPLIER TO PROVIDE PROPER FIT-UP. DEFLECTIONS MAY REQUIRE ADJUSTMENT AND RESETTING OF PRECAST WALL PANELS IN ORDER TO MEET THE TOLERANCES. THE CONTRACTOR SHALL BE AWARE OF THIS ITERATION PROCESS AND IS RESPONSIBLE FOR THE TOLERANCES BEING MET.
12. WALL PANELS SHALL HAVE EXPANSION JOINTS AT THE ROOF EXPANSION JOINT TO ALLOW FOR THERMAL EXPANSION AND CONTRACTION. ADDITIONALLY, THE PRECAST SUPPLIER SHALL ALLOW FOR DIFFERENTIAL MOVEMENT BETWEEN WALL PANELS.

A.B.	ANCHOR BOLTS
ACI	AMERICAN CONCRETE INSTITUTE
AESS	ARCHITECTURALLY EXPOSED STRUCTURAL STEEL
A.F.F.	ABOVE FINISHED FLOOR
ARCH.	ARCHITECTURAL
BAL.	BALANCE
B.L.	BLOCK LINTEL
BLDG.	BUILDING
B.O.	BOTTOM OF
B.O.D.	BOTTOM OF DECK
BRG.	BEARING
C.J.	CONTRACTION JOINT
C.L.	CENTER LINE
CLR.	CLEAR
CMU	CONCRETE MASONRY UNIT
COL.	COLUMN
CONC.	CONCRETE
CONST.	CONSTRUCTION
CONT.	CONTINUOUS
D.B.A.	DEFORMED BAR ANCHOR
DIA.	DIAMETER
DWG.	DRAWING
E.F.	EACH FACE
E.J.	EXPANSION JOINT
ELEV.	ELEVATION
E.O.D.	EDGE OF DECK
E.O.S.	EDGE OF SLAB
EQ.	EQUAL
E.W.	EACH WAY
EXIST.	EXISTING
FDN.	FOUNDATION
F.F.E.	FINISHED FLOOR ELEV.
F.S.	FAR SIDE
FTG.	FOOTING
GA.	GAGE
GALV.	GALVANIZED
G.B.	GRADE BEAM
HORIZ.	HORIZONTAL
H.S.A.	HEADED STUD ANCHOR
IBC	INTERNATIONAL BUILDING CODE
INFO.	INFORMATION
J.B.E.	JOIST BEARING ELEVATION
J.	JOINT
K	UNIT OF 1,000 POUNDS (KIP)

KSI	KIPS PER SQUARE INCH
LBS.	POUNDS
LLH	LONG LEG HORIZONTAL
LLV	LONG LEG VERTICAL
LONG.	LONGITUDINAL
MAX.	MAXIMUM
MECH.	MECHANICAL
MFR.	MANUFACTURER
MIN.	MINIMUM
MISC.	MISCELLANEOUS
N.I.C.	NOT IN CONTRACT
NO.	NUMBER
N.T.S.	NOT TO SCALE
N.S.	NEAR SIDE
O.C.	ON CENTER
O.D.	OUTSIDE DIAMETER
O.P.	OPPOSITE HAND
P.A.F.	POWER ACTUATED FASTENER
PCF	POUNDS PER CUBIC FOOT
P.F.M.E.J.	PREMOLDED EXPANSION JOINT
P.M.F.	POUNDS PER SQUARE FOOT
PSI	POUNDS PER SQUARE INCH
QTY.	QUANTITY
RE:	REFER
REINF.	REINFORCING
REQD.	REQUIRED
R.O.	ROUGH OPENING
RTU	ROOF TOP UNIT
SCHED.	SCHEDULE
S.D.S.	SELF-DRILLING SCREWS
S.I.M.	SIMILAR
SPECS.	SPECIFICATIONS
STD.	STANDARD
STL.	STEEL
T&B	TOP AND BOTTOM
T.O.	TOP OF
T.O.P.	TOP OF PIER
T.O.W.	TOP OF WALL
T.R.S.	TRANSVERSE
TYP.	TYPICAL
U.N.O.	UNLESS NOTED OTHERWISE
VERT.	VERTICAL
W.P.	WORK POINT
WT.	WEIGHT
W.W.R.	WELDED WIRE REINFORCEMENT





CERTIFICATION



PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO

ISSUE DATES

ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022

210300

S1.0


OVERALL FOUNDATION PLAN

PLAN NOTES

1. RE: 1/S3.2 FOR CMU WALL SECTIONS.


PLAN REFERENCE NOTES

Ⓐ 8" PRECAST WALL SCREEN AT COMPACTOR LOCATIONS,  
RE:1/S3.0 SIM. RE: ARCH FOR FINAL LOCATIONS.



1 OVERALL FOUNDATION PLAN  
SCALE: 1"=40'-0"





**CURRAN**  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



CERTIFICATION



PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO

ISSUE DATES

ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022



210300

**S1.1**

ENLARGED PARTIAL  
FOUNDATION PLAN

PLAN NOTES:


1. CONCRETE SLAB-ON-GRADE, SHALL BE A 8" THICK SLAB (U.N.O.) WITH #4 AT 18" O.C. EACH WAY PLACED 2" BELOW TOP OF CONCRETE OVER 4" ROCK, RE: THE GEOTECHNICAL REPORT. T.O. SLAB ELEV = 100'-0".
2. THE CONCRETE SLABS SHOWN ON THE STRUCTURAL DRAWINGS HAVE BEEN DESIGNED FOR THE FINISHED STRUCTURE AND HAVE NOT BEEN DESIGNED FOR MEANS AND METHODS OF CONSTRUCTION, INCLUDING BUT NOT LIMITED TO, FORK LIFTS, MAN LIFTS, AND OTHER VEHICULAR TRAFFIC. THE CONTRACTOR SHALL VERIFY THE SLAB DESIGN MEETS THE CONSTRUCTION NEEDS AND SHALL SUBMIT TO THE ENGINEER OF RECORD FOR REVIEW.
3. ALL PIPING OR CONDUITS THAT OCCUR THROUGH OR UNDER A GRADE BEAM OR FOOTING SHALL BE APPROVED BY THE ENGINEER OF RECORD PRIOR TO PLACEMENT.
4. RE: 8/S3.0 FOR REINFORCING LAP SCHEDULE.
5. VERIFY OVERALL SLAB DIMENSIONS WITH ARCH.



**3 PARTIAL FOUNDATION PLAN AT GENERATOR ENCLOSURE**  
SCALE: 1/4"=1'-0"

PLAN REFERENCE NOTES:


- (A) PRE-ENGINEERED SHADE CANOPY BY OTHERS, RE: 4/S3.0 FOR CANOPY FOOTING SUPPORT. RE: ARCH FOR FINAL CANOPY LOCATION.
- (B) RE: 6/S3.0 FOR STAIR COLUMN FOOTING.
- (C) RE: 9/S4.0 FOR STAIR FRAMING REQUIREMENTS.
- (D) W18x40 OPERABLE PARTITION SUPPORT BEAM ABOVE, RE: 1/S3.1
- (E) HSS6x3x1/4 CENTERED IN INTERIOR WALL AND ALIGNED WITH OPERABLE PARTITION. RE: ARCH FOR FINAL LOCATION.
- (F) RE: 5/S3.0 FOR THICKENED SLAB AT BASE OF STAIR.
- (G) RE: 6/S3.0 FOR OPERABLE PARTITION COLUMN FOOTING.



**2 ENLARGED PARTIAL FOUNDATION PLAN**  
SCALE: 1"=20'-0"

PLAN REFERENCE NOTES:

- (A) 8" CMU PARTITION WALL EACH SIDE OF SCRUBBER DUMP RE: 2/S3.2 AND ARCH.
- (B) HSS5x5x3/8 POST AT NEW HIGH SPEED OVERHEAD DOOR SUPPORTS. LOCATE WITHIN IMP WALL CAVITY. RE: ARCH FOR FINAL LOCATIONS.
- (C) RE: 6/S3.0 FOR POST SUPPORT FOOTING.
- (D) RE: 3/S3.1 FOR TYP. COOLER SLAB DETAIL. RE: 2/S3.1 FOR TYP. FREEZER SLAB DETAIL. RE: ARCH FOR EXTENTS. WHERE REFERENCED, SLAB-ON-GRADE SHALL BE A 8" THICK UNREINFORCED SLAB (U.N.O.) OVER 4" ROCK, RE: THE GEOTECHNICAL REPORT.



**1 ENLARGED PARTIAL FOUNDATION PLAN**  
SCALE: 1"=20'-0"




**CURRAN**  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



wallace design collective, pc  
structural - civil - landscape - survey  
1703 Wyandotte Street, Suite 200  
Kansas City, Missouri 64108  
816-421-8282 - 800-364-5858

CERTIFICATION



PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO

ISSUE DATES

ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022

210300


S1.2

ENLARGED MEZZANINE  
ROOF FRAMING PLAN

PLAN REFERENCE NOTES:

- A


8" HOLLOWCORE PLANKS WITH 2" TOPPING SLAB REINFORCED WITH 6x6--W2.9xW2.9 W.W.R. WITH 3/4" COVER.  
  
T.O. FINISHED CONCRETE ELEVATION = 11'-8"  
  
DESIGN LOADS:  
DEAD LOAD = SELF-WEIGHT  
                  MISC. UNDERHUNG 10 PSF  
LIVE LOAD = 150 PSF  
  
MAX. DIAPHRAGM EDGE FORCE = 11.7 KIPS



1 ENLARGED MEZZANINE FRAMING PLAN  
SCALE: 3/16"=1'-0"







**CURRAN**  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



CERTIFICATION



07/11/2022

PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO


ISSUE DATES

ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022


210300

S2.0


OVERALL FRAMING PLAN



PLAN REFERENCE NOTES:

- Ⓐ L8x8x1/2, WELD TO STEEL BAR JOISTS  
RE: 3/S4.0.
- Ⓑ PROVIDE HEADER H1 AT NEW DOOR  
OPENING. RE: ARCH FOR FINAL LOCATION.  
RE: 2/S4.1 AND 2/S4.1 FOR HEADER  
REQUIREMENTS.
- ▨ SHEAR WALL SW1. RE: 2/S4.2 FOR  
WALL FRAMING REQUIREMENTS.

2 PENTHOUSE FRAMING PLAN  
SCALE: 1/8"




PLAN REFERENCE NOTES:

- Ⓐ ROOF SHEATHING SHALL BE 5/8"  
STRUCTURAL 1 EXPOSURE 1 OSB. ROOF  
SHEATHING SHALL BE FASTENED WITH  
NO. 10 SCREWS AT 6" O.C. ALONG  
PANEL EDGES AND AT 12" O.C. IN THE  
FIELD. RUN PANELS PERPENDICULAR  
TO SUPPORTS AND STAGGER ENDS BY  
HALF PANEL LENGTH.

3 PENTHOUSE ROOF FRAMING PLAN  
SCALE: 1/8" = 1'-0"

PLAN REFERENCE NOTES:

- Ⓐ ATTACH COLUMNS TO ROOF  
FRAMING WITH VERTICAL SLIP  
CONNECTIONS RE: 4/S4.0



1 OVERALL FRAMING PLAN  
SCALE: 1"=40'-0"



5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317.288.0681  
F :: 317.288.0753



**LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1  
TENANT IMPROVEMENTS**  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO

[illegible]

## S2.1

- (A) NEW ROOF TOP EQUIPMENT, RE: ARCH./MEP. PROVIDE ANGLE FRAME AND CURB REF. 6/4.0. JOIST SUPPLIER SHALL ACCOUNT FOR LOAD SHOWN ON PLAN IN JOIST DESIGN IN ADDITION TO LOADING PREVIOUSLY INDICATED IN BASE DRAWINGS ISSUED JULY 15, 2022.
- (B) RE: 6/4.0.4 FOR ADDITIONAL SPECIAL JOIST LOADING REQUIREMENTS. JOIST SUPPLIER SHALL ACCOUNT FOR LOAD SHOWN ON PLAN IN JOIST DESIGN IN ADDITION TO LOADING PREVIOUSLY INDICATED IN BASE DRAWINGS ISSUED JULY 15, 2022.
- (C) NEW ROOF PENTHOUSE, RE: ARCH. FOR FINAL LOCATION. JOIST SUPPLIER SHALL ACCOUNT FOR LOAD SHOWN ON PLAN IN JOIST DESIGN IN ADDITION TO LOADING PREVIOUSLY INDICATED IN BASE DRAWINGS ISSUED JULY 15, 2022.

1. VERIFY ALL WALL OPENING, DIMENSIONS, JOINTS, BLOCKOUTS, REVEALS AND FUTURE KNOCK OUT PANELS WITH ARCHITECTURAL DRAWINGS.
2. JOIST SHALL BE DESIGNED FOR ROOF TOP EQUIPMENT, RE: ARCH./MEP. PROVIDE ANGLE FRAME AND CURB. RE: 5/54.0. JOIST SUPPLIER SHALL ACCOUNT FOR LOAD SHOWN ON PLAN IN JOIST DESIGN.
3. JOIST AND JOIST GIRDER DEPTHS SHALL BE LIMITED SO THAT 36"-0" CLEAR HEIGHT TO BOTTOM OF STRUCTURE IS MAINTAINED.
4. RE: 6/54.0 FOR SPECIAL JOIST LOADS WHERE REFERENCED ON PLAN.

Diagram illustrating the components of a precast joist design:

- JOIST DEPTH
- JOIST SERIES
- TOTAL ASD UNIFORM LOAD (DL + LL) IN PLF
- ASD UNIFORM SNOW LOAD IN PLF
- LRFD FACTORED REACTION FOR PRECAST SUPPLIER DESIGN


A diagram of a precast concrete girder with various design parameters labeled. The girder is represented by a horizontal line with a dashed centerline. Labels with arrows pointing to specific parts of the girder include:

- GIRDER DEPTH (MAXIMUM, JOIST SUPPLIER MAY REDUCE)**: Points to the top flange of the girder.
- NUMBER OF EQUAL SPACED LOADING LOCATIONS**: Points to the top flange of the girder.
- ADDITIONAL ASD LOAD IN KIPS**: Points to the top flange of the girder.
- 54GN9.4K**: Points to the centerline of the girder.
- XXX**: Points to the centerline of the girder.
- LRFD FACTORED REACTION FOR PRECAST SUPPLIER DESIGN**: Points to the bottom flange of the girder.
- ASD LOAD IN KIPS AT EACH LOADING LOCATION**: Points to the bottom flange of the girder.
- GIRDER WEB CONFIGURATION**: Points to the bottom flange of the girder.

STEEL FABRICATOR SHALL DESIGN THE BEAM CONNECTIONS FOR THE STRENGTH  
LEVEL LOADS (ASD) SHOWN ON THIS PLAN, TYP. (RE: 1/54.0)


USE MINIMUM TWO BOLT CONNECTION

The diagram shows a horizontal beam labeled "W21x50". At the right end of the beam, a vertical arrow points downwards, labeled "50K (30K)". A dimension line indicates a distance of "10K MIN." from the end of the beam to the point of application of the reaction. Labels with arrows point to the beam and the reaction: "BEAM SIZE" points to the beam, and "GRAVITY BEAM STRENGTH (ASD) END REACTION (IN KIIPS) FOR CONNECTION DESIGN. REACTION IS APPLIED VERTICALLY PARALLEL TO BEAM WEB, 10K MIN. WHERE VALUE NOT PROVIDED ON PLAN" points to the reaction arrow.



## S2.1





**CURRAN**  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



CERTIFICATION



PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO


ISSUE DATES

ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022



210300

**S2.2**  
ENLARGED PARTIAL  
FRAMING PLAN

JOIST LEGEND





JOIST GIRDER LEGEND



BEAM REACTION LEGEND

STEEL FABRICATOR SHALL DESIGN THE BEAM CONNECTIONS FOR THE STRENGTH LEVEL LOADS (ASD) SHOWN ON THIS PLAN, TYP. (RE: 1/54.0)  
USE MINIMUM TWO BOLT CONNECTION



**1 ENLARGED PARTIAL FRAMING PLAN**  
SCALE: 1"=20'-0"



**CURRAN**  
ARCHITECTURE  
5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753

**SCANNELL**  
PROPERTIES

wallace  
design  
collective

wallace design collective, pc  
structural · civil · landscape · survey  
1703 wyandotte street, suite 300  
kansas city, missouri 64108  
816.421.8282 · 800.364.5858


CERTIFICATION

STATE OF MISSOURI  
JAMES M. GRANICH  
NUMBER  
PE-2014023909  
PROFESSIONAL ENGINEER  
07/11/2022


PROJECT INFORMATION  
LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO

ISSUE DATES	
ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022



JOIST LEGEND



JOIST GIRDER LEGEND




BEAM REACTION LEGEND



1 ENLARGED PARTIAL FRAMING PLAN  
SCALE: 1"=20'-0"







**CURRAN**  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



CERTIFICATION



PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO

ISSUE DATES

ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022


210300

S2.4  
ENLARGED PARTIAL  
FRAMING PLAN


PLAN REFERENCE NOTES:

- Ⓐ NEW ROOF TOP EQUIPMENT, RE: ARCH./MEP. PROVIDE ANGLE FRAME AND CURB RE: 5/54.0. JOIST SUPPLIER SHALL ACCOUNT FOR LOAD SHOWN ON PLAN IN JOIST DESIGN IN ADDITION TO LOADING PREVIOUSLY INDICATED IN BASE DRAWINGS ISSUED JULY 15, 2022.


PLAN NOTES

1. VERIFY ALL WALL OPENING, DIMENSIONS, JOINTS, BLOCKOUTS, REVEALS AND FUTURE KNOCK OUT PANELS WITH ARCHITECTURAL DRAWINGS.
2. JOIST SHALL BE DESIGNED FOR ROOF TOP EQUIPMENT, RE: ARCH./MEP. PROVIDE ANGLE FRAME AND CURB, RE: 5/54.0. JOIST SUPPLIER SHALL ACCOUNT FOR LOAD SHOWN ON PLAN IN JOIST DESIGN.
3. JOIST AND JOIST GIRDER DEPTHS SHALL BE LIMITED SO THAT 36"-0" CLEAR HEIGHT TO BOTTOM OF STRUCTURE IS MAINTAINED.
4. RE: 6/54.0 FOR SPECIAL JOIST LOADS WHERE REFERENCED ON PLAN.

JOIST LEGEND





JOIST GIRDER LEGEND



BEAM REACTION LEGEND

STEEL FABRICATOR SHALL DESIGN THE BEAM CONNECTIONS FOR THE STRENGTH LEVEL LOADS (ASD) SHOWN ON THIS PLAN, TYP. (RE: 1/54.0)

USE MINIMUM TWO BOLT CONNECTION



1 ENLARGED PARTIAL FRAMING PLAN  
SCALE: 1"=20'-0"







ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022

BAR SIZE	CONCRETE					
	f'c = 3000 PSI		f'c = 4000 PSI		f'c = 5000 PSI	
	TOP	OTHER	TOP	OTHER	TOP	OTHER
#3	22	17	20	16	17	13
#4	29	22	27	21	23	17
#5	36	28	33	26	28	22
#6	43	33	40	31	34	26
#7	63	48	58	45	49	38
#8	72	55	66	51	56	43
#9	91	70	79	61	71	54


8 CONC. LAP SCHEDULE  
3/4" = 1'-0"




9 ANCHOR ROD EMBEDMENT/BASE PLATE DIAGRAM




10 FOUNDATION SECTION  
3/4" = 1'-0"




7 SLAB-ON-GRADE DETAILS  
3/4" = 1'-0"




6 FOUNDATION SECTION  
3/4" = 1'-0"




5 STAIR STRINGER BASE CONNECTION DETAIL  
3/4" = 1'-0"




1 GENERATOR ENCLOSURE WALL SECTION  
3/4" = 1'-0"



2 GATE ENCLOSURE FOUNDATION SECTION  
3/4" = 1'-0"




3 GATE ENCLOSURE SECTION  
3/4" = 1'-0"



4 FOUNDATION SECTION  
3/4" = 1'-0"






CURRAN  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



wallace design collective, pc  
structural · civil · landscape · survey  
1703 Wyandotte Street, Suite 200  
Kansas City, Missouri 64108  
816.421.8282 · 800.364.5858

CERTIFICATION



PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO




ISSUE DATES

ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022


210300

S3.1

FRAMING DETAILS







**CURRAN**  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



**SCANNELL**  
PROPERTIES

wallace  
design  
collective

wallace design collective, pc  
structural, civil, landscape, survey  
1703 wyandotte street, suite 200  
kansas city, missouri 64108  
816.421.8282 - 800.364.5858

CERTIFICATION



07/11/2022

PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO


ISSUE DATES

ISSUE DATE  
ISSUE FOR PERMIT 07.11.2022


210300

S3.2


FOUNDATION DETAILS



MASONRY REINFORCING LAP SCHEDULE *						
(ACI 530-05) (IBC 2006)						
BAR SIZE	8" BLOCK		10" BLOCK		12" BLOCK	
	SINGLE REINF.	DOUBLE REINF.	SINGLE REINF.	DOUBLE REINF.	SINGLE REINF.	DOUBLE REINF.
#3	16"	16"	16"	16"	16"	16"
#4	21"	23"	21"	21"	21"	21"
#5	26"	36"	26"	30"	26"	26"
#6	43"	70"	40"	56"	40"	43"
#7	60"	98"	46"	79"	46"	60"
#8	92"	151"	71"	121"	61"	92"


\* BASED ON f'm = 1500 PSI

CMU VERTICAL REINFORCING SCHEDULE	
MW-1	8" CMU W/ (1)-#5 VERT. AT 8" O.C. WITH (1)-#4 DOWEL TO MATCH.
* PROVIDE HIGH STRENGTH BLOCK - fm = 2000 PSF	



TYPICAL 8" CORNER


CORNER DETAIL




BOND BEAM STEP (NOT AT CONTROL JOINT)

PROVIDE VERT. WALL REINF. IN FIRST CELL EACH SIDE OF CONTROL JOINT

GROUT, CONCRETE, REINF. BARS, JOINT REINF. AND BOND BEAMS SHALL BE DISCONTINUOUS DOWN TO TOP OF FOOTING AT CONTROL JOINTS. RE: FOUNDATION PLAN FOR CONTROL JOINT LOCATIONS. DO NOT LOCATE CONTROL JOINT WITHIN 2'-0" OF OPENINGS



EXPANSION/CONTROL JOINT DETAIL




NOTES:

1. REFER CMU REINFORCING DIAGRAM FOR SPLICES IN VERTICAL REINFORCING.
2. BOND BEAM.
3. EXTEND GROUTED LINTEL A MINIMUM OF 2'-0" BEYOND FACE OF OPENING EACH SIDE FOR STRAIGHT LINTEL REINFORCEMENT AND 1'-4" FOR HOOKED LINTEL, U.N.O. REINFORCEMENT WITH STANDARD ACI HOOK.
4. USE LINTEL BLOCKS ONLY FOR BOTTOM COURSE OF LINTEL BEAMS.
5. CONTINUE VERTICAL REINFORCING INTO LINTEL BEAM WITH STANDARD ACI HOOK.
6. PROVIDE DOWELS TO MATCH ALL VERTICAL REINFORCING LOCATIONS.
7. ALL VERTICAL BARS AT JAMBS AND PILASTERS SHALL EXTEND FROM THE BOND BEAM BELOW THE OPENING TO THE BOND BEAM ABOVE THE OPENING.
8. CONTINUE HORIZONTAL REINFORCING INTO JAMB AND PROVIDE STANDARD ACI HOOK INTO END CELL.
9. BOND BEAM AT FIRST FULL COURSE BELOW FLOOR FRAMING. GROUT SOLID UP TO FIRST FULL COURSE ABOVE FINISH FLOOR.
10. BOND BEAM AT FIRST FULL COURSE BELOW ROOF FRAMING. VERTICALLY REINFORCE AND GROUT UP TO TOP OF WALL PER REINFORCING SCHEDULE
11. BOND BEAM AT TOP OF WALL.

GENERAL NOTES:

12. GROUT SOLID ALL CELLS WITH REINFORCING.
13. USE BOND BEAM BLOCKS WITH OPEN BOTTOMS ONLY AT BOND BEAM LOCATIONS. DO NOT USE TROUGH-TYPE BLOCKS AT BOND BEAMS.
14. DO NOT CONTINUE BOND BEAM REINFORCING THROUGH CONTROL JOINTS.
15. ALL MASONRY SHALL BE LAID IN RUNNING (COMMON) BOND.
16. REFER TO DETAILS FOR LOCATION OF ADDITIONAL BOND BEAMS.
17. HORIZ. JOINT REINFORCING SHALL BE GALV. LADDER TYPE SPACED AT 16" O.C. ABOVE GRADE AND 8" O.C. BELOW GRADE AND IN PARAPETS.
18. MASONRY REQUIRES SPECIAL INSPECTION. RE: SPECIFICATIONS.
19. MASONRY DESIGN IS BASED UPON A MINIMUM COMPRESSIVE STRENGTH OF f'm=1500 PSI, ESTABLISHED IN ACCORDANCE WITH THE UNIT STRENGTH METHOD, U.N.O.
20. MASONRY UNITS SHALL MEET THE REQUIREMENTS OF ASTM C90 (UBC STANDARD 21-4) WITH A NET AREA COMPRESSIVE STRENGTH OF 1,900 PSI, U.N.O. MASONRY UNITS SHALL BE LIGHT WEIGHT (LESS THAN 105 PCF) -OR- MEDIUM WEIGHT (103 TO 125 PCF) -OR- NORMAL WEIGHT (MORE THAN 125 PCF).
21. MORTAR SHALL BE PREPARED IN ACCORDANCE WITH THE REQUIREMENTS OF ASTM C270 (USE STANDARD 21-15) FOR TYPE "S" MORTAR.
22. GROUT SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 2,000 PSI AT 28 DAYS. BATCHING AND MIXING SHALL MEET THE REQUIREMENTS OF ASTM C476 (UBC STANDARD 21-19)



1 CMU WALL REINFORCING DIAGRAM

3/4" = 1'-0"



# CURRAN ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753

# SCANNELL PROPERTIES

# wallace design collective

wallace design collective, pc  
structural · civil · landscape · survey  
1703 wyandotte street, suite 200  
kansas city, missouri 64108  
816-421-8282 · 800-364-5558

# CERTIFICATION



# PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO


# ISSUE DATES

ISSUE DATE  
ISSUE FOR PERMIT 07.11.2022



210300

S4.0


FRAMING DETAILS




10 PENTHOUSE BASE DETAIL  
3/4" = 1'-0"



9 STAIR FRAMING DETAIL  
3/4" = 1'-0"




8 ROOF OPENING DETAIL  
3/4" = 1'-0"





7 JOIST REINFORCING DETAIL  
3/4" = 1'-0"










SPECIAL JOIST LOADS		
MARK	SNOW DRIFT (PSF)	SNOW WIDTH (X)
SP3	72	17'-0"




6 SPECIAL JOIST SCHEDULE  
3/4" = 1'-0"




5 MECHANICAL UNIT SUPPORT DETAIL  
3/4" = 1'-0"





4 EDGE ANGLE CONNECTION DETAIL  
3/4" = 1'-0"



3 ANGLE CONNECTION DETAILS  
3/4" = 1'-0"



2 BOTTOM FLANGE BRACING DETAIL  
3/4" = 1'-0"




BEAMS AND BOLTS		
BEAM,S	NUMBER OF BOLTS	NOTE:
W8/W10	(2)	PROVIDE STANDARD ROUND OR HORIZONTAL SHORT SLOTTED HOLES IN THE CONNECTOR PLATE. TIGHTEN BOLTS TO A SNUG CONDITION. TYPICAL AT ALL BM. TO BM. CONNECTIONS UNLESS NOTED OTHERWISE
W12/W14	(3)	
W16/W18	(4)	
W21/W24	(5)	
W27/W30	(6)	

1 BEAM CONNECTION DETAIL  
3/4" = 1'-0"

- NOTES:
- ALL CONNECTIONS ON THE STRUCTURAL DRAWINGS, UNLESS NOTED OTHERWISE, SHALL BE DESIGNED AND DETAILED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE WHERE THE PROJECT IS LOCATED, EMPLOYED OR RETAINED BY THE STEEL FABRICATOR. THE DESIGN AND DETAILED SHALL COMPLY WITH ALL APPLICABLE CODES AND SPECIFICATION SECTIONS.
  - CONNECTIONS SHOWN ARE FOR REFERENCE ONLY. FABRICATOR MAY USE OTHER AISC APPROVED CONNECTIONS.
  - ALL BOLTS SHALL BE 3/4" DIAMETER A325 W/ HEAVY HEX NUTS, UNLESS NOTED OTHERWISE.
  - ALL CONNECTIONS SHALL BE BEARING TYPE CONNECTIONS AND SHALL BE SNUG TIGHTENED UNLESS NOTED OTHERWISE.
  - FOR BEAMS WITH AXIAL REACTIONS PER PLAN, CONNECTIONS SHALL BE DESIGNED AS FULLY TENSIONED SLIP CRITICAL PER AISC SPECIFICATIONS.





# CURRAN

## ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



SCANNELL  
PROPERTIES



wallace  
design  
collective

wallace design collective, pc  
structural · civil · landscape · survey  
1703 wyandotte street, suite 200  
kansas city, missouri 64108  
816.421.8282 · 800.364.5858

### CERTIFICATION



07/11/2022

### PROJECT INFORMATION

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT 1  
TENANT IMPROVEMENTS  
NW CORNER TUDOR RD & MAINST  
LEE'S SUMMIT, MO

### ISSUE DATES


ISSUE	DATE
ISSUE FOR PERMIT	07.11.2022


210300


S4.1

FRAMING DETAILS


STRUCTURAL HEADER AND JAMB SCHEDULE				
MARK	OPENING	HEADER	KING STUDS	SCREW QUANTITY
H1	RE: PLAN	(2) 600S162-33	(2) 600S162-33	(8) 1/4" SCREWS




F HEADER CONNECTION




C WALL BRIDGING DETAIL




A STUD TO TRACK AT BOTTOM




G SILL PLATE ASSEMBLY AND CONNECTION




E BUILT-UP JAMB ASSEMBLY




D HEADER ASSEMBLY



B STUD TO TRACK AT TOP



3 STAIR LANDING SECTION



### NOTES:

1. WALL STUDS SHALL BE CONTINUOUS FROM BOTTOM TRACK TO TOP TRACK.
2. RE: 2/54.1 FOR REFERENCED DETAILS.


1 FRAMING SECTION

3/4" = 1'-0"

2 FRAMING SECTION


3/4" = 1'-0"






## 9 INT. JOIST BEARING – STANDARD

N.T.S.




## 8 JOIST LAP – STANDARD

N.T.S.



## 7 WEB STIFFENER – STANDARD

N.T.S.




## 6 JOIST HANGER – SIMPSON S-JCT8

N.T.S.


## 5 SUPPORT CLIP – DIETRICH E-SERIES

N.T.S.




## 4 JOIST RIM – RIM SPLICE

N.T.S.




## 3 JOIST BRIDGING – STANDARD

N.T.S.



## 2 SHEAR WALL ELEVATION

3/4" = 1'-0"



SHEAR WALL SCHEDULE							
MARK	SHEATHING	SHEATHING ATTACHMENT PATTERN		WALL STUDS	BOTTOM TRACK ATTACHMENT	HOLD DOWNS	END POST
		AT PANEL EDGES AND BOUNDARIES	AT INTERMEDIATE FRAMING MEMBERS				
SW1	5/8" RATED SHEATHING (OSB), ONE SIDE	#10 SELF-DRILLING SCREWS AT 6" O.C.	#10 SELF-DRILLING SCREWS AT 12" O.C.	600S162-33 AT 16" O.C.	HILTI 0.157" X-8 AT 16" O.C. MIN.	SIMPSON S/HDU4 HOLD DOWN WITH 5/8" DIA. BOLT	(2)-600S162-33

### NOTES:


1. REFER TO FOUNDATION PLANS FOR ANCHOR BOLT AND HOLD DOWN LOCATIONS. ANCHOR BOLTS SHALL BE CAST IN PLACE FOR EMBEDMENT DEPTH SHOWN IN SCHEDULE.
2. PROVIDE GALVANIZED SCREWS AT EXTERIOR FACE OF WALL.
3. ALL VERTICAL WALL SHEATHING TO BE 5/8" RATED SHEATHING (OSB).
4. HOLD DOWN ANCHORS SHALL BE APPROVED BY THE SPECIAL STRUCTURAL INSPECTION AS REQUIRED BY BUILDING CODE.
5. HOLD DOWN POSTS SHALL BE ATTACHED TOGETHER PER BUILT-UP SECTION DETAIL.
6. PANEL BLOCKING SHALL BE A 1 1/2"x16 GA. FLAT STRAP CENTERED ON THE JOINT WHERE REQUIRED.
7. SHEARWALL SHEATHING SHALL RUN CONTINUOUS THROUGH BREAKS CAUSED BY INTERSECTING WALLS.
8. PLUMBING / MECHANICAL ACCESS HOLES IN STUDS OR TRACKS TO BE PLACED IN CENTER LINE OF MEMBER, SPACED NO CLOSER THAN 10'-0" AND NOT EXCEED 2 1/2" DIA. FOR 6" WALLS - 1 1/2" DIA. FOR 3 5/8" WALLS. AT TRACKS AND HOLD DOWN MEMBERS, STRAP ACROSS HOLE WITH SIMPSON ST2115, NO SCREWS AT HOLE.
9. SHEAR WALL SHEATHING AND FASTENING SHALL BE CONTINUOUS BETWEEN HOLD DOWN LOCATIONS AS SHOWN ON PLAN.

## 1 SHEAR WALL SCHEDULE










**CURRAN**  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



**SCANNELL**  
PROPERTIES

THIS DRAWING AND THE IDEAS, DESIGNS  
AND CONCEPTS CONTAINED HEREIN ARE  
THE EXCLUSIVE INTELLECTUAL PROPERTY  
OF CURRAN ARCHITECTURE, AND ARE NOT  
TO BE USED OR REPRODUCED, WHOLE OR  
IN PART, WITHOUT THE WRITTEN  
CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE


LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I

NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086

PERMIT SET 04.21.22

210300

M1.1



**1 Overall Mechanical Floor Plan**  
scale: 1" = 25'-0"



THIS PRINT IS CONFIDENTIAL TO METRO AIR CONDITIONING CO.  
REPRODUCTION OR DISCLOSURE TO OUTSIDE PARTIES IS  
PROHIBITED WITHOUT OUR WRITTEN CONSENT.  
© 2022 METRO AIR CONDITIONING CO.



LSCC BLDG. #1 - TI		
LEE'S SUMMIT, MO		
SCALE: AS NOTED	DATE: 12/15/22	DRAWN BY: M.D.K.
APPROVED BY: JDG	DWG #	M1
COORDINATION DWGS		of 5





**CURRAN**  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753



THIS DRAWING AND THE IDEAS, DESIGNS  
AND CONCEPTS CONTAINED HEREIN ARE  
THE EXCLUSIVE INTELLECTUAL PROPERTY  
OF CURRAN ARCHITECTURE, AND ARE NOT  
TO BE USED OR REPRODUCED, WHOLE OR  
IN PART, WITHOUT THE WRITTEN  
CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE


LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I

NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086


PERMIT SET 04.21.22

210300

M1.2



1 Cooler Mechanical Floor Plan  
scale: 1/16" = 1'-0"



2 Office Mechanical Floor Plan  
scale: 1/8" = 1'-0"



**MECHANICAL PLAN NOTES:**

- COORDINATE LOCATION OF RTU WITH FIRE SUPPRESSION PIPING AND STRUCTURE. PROVIDE INTERNALLY LINED RETURN AIR DUCT DROP WITH MESH SCREEN AND PROVIDE SUPPLY AIR DISCHARGE DROP BOX DIFFUSER SIMILAR TO CURBS PLUS DLPD 4015-30. NO TO BE UNDER 35 AT 8,000 CFM. PROVIDE SUPPLY AIR TRANSITION FROM RTU OPENING TO DROPBOX DIFFUSER AS REQUIRED. MOUNT THERMOSTAT ON ADJACENT COLUMN.
- PROVIDE 6" EXHAUST VENT UP THROUGH ROOF. PROVIDE WITH WEATHERCAP.
- ROUTE CONDENSATE AS DIRECTED TO FLOOR DRAIN. PROVIDE HEAT TRACE ON ALL FREEZER CONDENSATE PIPING.
- COORDINATE EXACT LOCATION OF HVLS FAN. PROVIDE ASSOCIATED FAN CONTROLLER ON ADJACENT COLUMN.
- ROUTE FULL SIZE RETURN AIR DUCT DOWN TO 36" ABOVE FINISH CEILING AND PROVIDE WITH SCREENED MESH OPENING.
- PROVIDE 6" EXHAUST VENT OUT THROUGH WALL. PROVIDE WITH WEATHERCAP.
- INSTALL BATTERY CHARGING EXHAUST DUCTWORK TIGHT TO BOTTOM OF STRUCTURE. PROVIDE EXHAUST GRILLES AS NOTED AT 30" FROM BOTTOM OF DUCT. EXHAUST FAN TO RUN CONTINUOUSLY.
- ROUTE CONDENSATE PIPING TO SINK TAILPIECE OR HUB DRAIN ABOVE CEILING FURNISHED BY PLUMBER
- INSTALL CONDENSING UNIT ON ROOF RAILS.
- EXISTING SHELL BUILDING EQUIPMENT TO REMAIN AS CURRENTLY INSTALLED.

**LEGEND**

- HVLS**  
1 GREENHECK HVLS/CIRCULATION FAN 24'-0" DIAMETER MODEL DS-6-24-170HV - 2HP, 460/3 PHASE, 250 LBS AND 6 BLADES. PROVIDE WITH MOUNTING ACCESSORIES AND CONTROL PANEL. CONDUIT AND CONTROL WIRING BY OTHERS. (TYP. 10)
- AC**  
X AIR CURTAIN - POWERED AIR MODEL XXXX. UNIT TO BE 80" LONG WITH 10 KW ELECTRIC HEATING. XX MCA @ 460/3 PHASE, 375 LBS. PROVIDE WITH MAGNETIC DOOR SWITCH, WHITE INTAKE SUPPLY GRILLE, WALL MOUNTED THERMOSTAT AND WASHABLE ALUMINUM FILTER
- EW**  
1 ELECTRIC WALL HEATER - RAYWALL OR EQUAL. 2KW @ 277/1 PHASE. PROVIDE WITH RECESS MOUNTING FRAME, DISCONNECT, INTEGRAL THERMOSTAT.
- SD**  
1 SUPPLY AIR DIFFUSER - AS SCHEDULED
- RG**  
1 RETURN AIR GRILLE - AS SCHEDULED
- RG**  
2 RETURN AIR GRILLE - AS SCHEDULED
- EX**  
1 EXHAUST AIR GRILLE - AS SCHEDULED
- EX**  
2 EXHAUST AIR GRILLE - AS SCHEDULED
- SG**  
1 SUPPLY AIR GRILLE - AS SCHEDULED  
SG-2 SUPPLY AIR GRILLE - AS SCHEDULED
- RETURN AIR GRILLE - AS SCHEDULED
- T**  
THERMOSTAT WITH ZONE/UNIT DESIGNATION. MOUNT AT 48" A.F.F.
- VAV**  
1-3
- CO2**  
CARBON DIOXIDE SENSOR - MOUNT IN RETURN OR WALL AS SHOWN



LSCC BLDG. #1 - TI

LEE'S SUMMIT, MO

SCALE: AS NOTED DATE: 12/15/22 DRAWN BY: M.D.K.

APPROVED BY: JDG

DWG #

M2

COORDINATION DWGS

of 5

THIS PRINT IS CONFIDENTIAL TO METRO AIR CONDITIONING CO.  
REPRODUCTION OR DISCLOSURE TO OUTSIDE PARTIES IS  
PROHIBITED WITHOUT OUR WRITTEN CONSENT.  
© 2022 METRO AIR CONDITIONING CO.



CURRAN  
ARCHITECTURE

5719 LAWTON LOOP E. DR. #212  
INDIANAPOLIS, IN 46216  
O :: 317 . 288 . 0681  
F :: 317 . 288 . 0753

SCANNELL  
PROPERTIES

THIS DRAWING AND THE IDEAS, DESIGNS  
AND CONCEPTS CONTAINED HEREIN ARE  
THE EXCLUSIVE INTELLECTUAL PROPERTY  
OF CURRAN ARCHITECTURE, AND ARE NOT  
TO BE USED OR REPRODUCED, WHOLE OR  
IN PART, WITHOUT THE WRITTEN  
CONSENT OF CURRAN ARCHITECTURE.  
© COPYRIGHT 2021, CURRAN ARCHITECTURE

LEE'S SUMMIT LOGISTICS  
BUILDING A LOT I

NW CORNER OF  
NE TUDOR RD & MAIN ST  
LEE'S SUMMIT, MO 64086

PERMIT SET 04.21.22

210300


M1.3

MECHANICAL PLAN NOTES:


- COORDINATE LOCATION OF RTU WITH FIRE SUPPRESSION PIPING AND STRUCTURE. PROVIDE INTERNALLY LINED RETURN AIR DUCT DROP WITH MESH SCREEN AND PROVIDE SUPPLY AIR DISCHARGE DROP BOX DIFFUSER SIMILAR TO CURBS PLUS DLPD 4015-30. NC TO BE UNDER 35 AT 9,000 CFM. PROVIDE SUPPLY AIR TRANSITION FROM RTU OPENING TO DROPBOX DIFFUSER AS REQUIRED. MOUNT THERMOSTAT ON ADJACENT COLUMN.
- PROVIDE 6" EXHAUST VENT UP THROUGH ROOF. PROVIDE WITH WEATHERCAP.
- ROUTE CONDENSATE AS DIRECTED TO FLOOR DRAIN. PROVIDE HEAT TRACE ON ALL FREEZER CONDENSATE PIPING.
- COORDINATE EXACT LOCATION OF HVLS FAN. PROVIDE ASSOCIATED FAN CONTROLLER ON ADJACENT COLUMN.
- ROUTE FULL SIZE RETURN AIR DUCT DOWN TO 36" ABOVE FINISH CEILING AND PROVIDE WITH SCREENED MESH OPENING.
- PROVIDE 6" EXHAUST VENT OUT THROUGH WALL. PROVIDE WITH WEATHERCAP.
- INSTALL BATTERY CHARGING EXHAUST DUCTWORK TIGHT TO BOTTOM OF STRUCTURE. PROVIDE EXHAUST GRILLES AS NOTED AT 30" FROM BOTTOM OF DUCT. EXHAUST FAN TO RUN CONTINUOUSLY.
- ROUTE CONDENSATE PIPING TO SINK TAILPIECE OR HUB DRAIN ABOVE CEILING FURNISHED BY PLUMBER
- INSTALL CONDENSING UNIT ON ROOF RAILS.
- EXISTING SHELL BUILDING EQUIPMENT TO REMAIN AS CURRENTLY INSTALLED.

LEGEND


- HVLS 1 GREENHECK HVLS/CIRCULATION FAN 24'-0" DIAMETER MODEL DS-6-24-170HV - 2HP, 460/3 PHASE, 250 LBS AND 6 BLADES. PROVIDE WITH MOUNTING ACCESSORIES AND CONTROL PANEL. CONDUIT AND CONTROL WIRING BY OTHERS. (TYP. 10)
- AC X AIR CURTAIN - POWERED AIR MODEL XXXX. UNIT TO BE 80" LONG WITH 10 KW ELECTRIC HEATING. XX MCA @ 460/3 PHASE, 375 LBS. PROVIDE WITH MAGNETIC DOOR SWITCH, WHITE INTAKE SUPPLY GRILLE, WALL MOUNTED THERMOSTAT AND WASHABLE ALUMINUM FILTER
- EW 1 ELECTRIC WALL HEATER - RAYWALL OR EQUAL. 2KW @ 277/1 PHASE. PROVIDE WITH RECESS MOUNTING FRAME, DISCONNECT, INTEGRAL THERMOSTAT.
- SD-1 SUPPLY AIR DIFFUSER - AS SCHEDULED
- RG-1 RETURN AIR GRILLE - AS SCHEDULED
- RG-2 RETURN AIR GRILLE - AS SCHEDULED
- EX-1 EXHAUST AIR GRILLE - AS SCHEDULED
- EX-2 EXHAUST AIR GRILLE - AS SCHEDULED
- SG-1 SUPPLY AIR GRILLE - AS SCHEDULED
- SG-2 SUPPLY AIR GRILLE - AS SCHEDULED
- RETURN AIR GRILLE - AS SCHEDULED
- T THERMOSTAT WITH ZONE/UNIT DESIGNATION. MOUNT AT 48" A.F.F.
- WV 1-3 CARBON DIOXIDE SENSOR - MOUNT IN RETURN OR WALL AS SHOWN




1 Driver's Mechanical Floor Plan  
scale: 1/8" = 1'-0"



2 Driver's Mechanical Floor Plan  
scale: 1/8" = 1'-0"



3 Maintenance Mechanical Floor Plan  
scale: 1/8" = 1'-0"



4 Charging Area Mechanical Plan  
scale: 1/8" = 1'-0"

THIS PRINT IS CONFIDENTIAL TO METRO AIR CONDITIONING CO.  
REPRODUCTION OR DISCLOSURE TO OUTSIDE PARTIES IS  
PROHIBITED WITHOUT OUR WRITTEN CONSENT.  
© 2022 METRO AIR CONDITIONING CO.

MetroAir

LSCC BLDG. #1 - TI  
LEE'S SUMMIT, MO  
SCALE: AS NOTED DATE: 12/15/22 DRAWN BY: M.D.K.  
APPROVED BY: JDG DWG # M2 of 5  
coordination dwgs