
	ROOF PANELS:	PLANS A GOVERN
BUILDING SYSTEMS TOULD 905 West 9th Street Pella, A 50219 (800) 225-0481 www.pellabuidings.com Take: Bios 00100 (200) 225-0481 www.pellabuidings.com FARE: Bios 011010 (000) 225-0481 www.pellabuidings.com FRAE: Bios 01101 (000) 2000 (200) (200 (200 (200 (200 (2		<u>a+ w/</u> drip StopDRAWING Agreemi IS Actin
BUILDING SYSTEMS TRIN CLOSE 906 West 9th Street Pella, IA 50219 (800) 225-0481 www.pellobuildings.com UNEXPECTION UIDING LOADS / DESCRIPTION: www.pellobuildings.com UIDING COADS / DESCRIPTION: model / 1000 UIDING COADS / DESCRIPTION: model / 1000 Wistranding Sampadows And Northal, REFER TO LOADS // 1000 model / 1000 Wistranding Sampadows And Northal, REFER TO LOADS // 1000 model / 1000 Wistranding Sampadows And Northal, REFER TO LOADS // 1000 model / 1000 Wistranding Sampadows And Northal, REFER TO LOADS // 1000 model / 1000 Wistranding Sampadows And Northal, REFER TO LOADS // 1000 model / 1000 Wistranding Sampadows And Northal, REFER TO LOADS // 1000 model / 1000 Sampadows And Northal, REFER TO LOADS // 0.02 model / 1000 Sampadows And Loads // 0000 model / 0000 Sampadows And Loads // 0000 model / 10000 Sampadows And Loads // 0000 model / 10000 Sampadows And Loads // 0000 model / 10000 <td></td> <td>PROJEC</td>		PROJEC
OPERATING STOTEMENT CAB L: Elecation 906 West 9th Street Pello, IA 50219 LAVE: Head 000 225 - 0481 www.pellabuildings.com LAVE: Head 011: 0405 / 0405 / 0450 WWW.pellabuildings.com LAVE: Head 011: 0405 / 0405 / 0450 HIGO IS 16.88 / 15.88 OII CLASS: COURS: N/A 011: 040 / 0405 / 0450 DESCRIPTION: OPERANCE OFFEN 085: INC N/A 011: 040 / 0405 / 0450 DESCRIPTION: OPERANCE OFFEN 085: N/A 011: 040 / 0405 / 0405 / 0405 / 0406 / 01000 HE CLASS: OPERANCE OFFEN 085: N/A 010: 0405 / 0406 / 051 (0406 / 0405 / 0406 / 01000 HE CLASS: OPERANCE OFFEN 085: N/A 010: 0405 / 0406 / 051 (0406 / 0405 / 0406 / 0006 / 01000 / 0406 / 0006 / 01000 / 0406 / 0006 / 01000 / 0406 / 01000 / 0406 / 01000 / 0406 / 01000 / 0406 / 01000 / 0406 / 01000 / 01000 / 0406 / 01000 / 0406 / 01000 / 0406 / 01000 / 0406 / 0406 / 0406 / 01000 / 0406 / 01000 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406 / 0406		MANUFA
000 West 9th Street Pello, IA 50219 LANE: Diack 000 West 9th Street Pello, IA 50219 LANE: Hook 010 DAG 10ADS / DESCRIPTION: INTER PANELS: Diack 011 DAG 10ADS / DESCRIPTION: INTER PANELS: OD 08: N/A 011 DAG 10ADS / DESCRIPTION: INTER PANELS: OD 08: N/A 011 DAG 10ADS / DESCRIPTION: INTER PANELS: OD 08: N/A 012 DAG 10ADS AC DESCRIPTION: INTER PANELS: OD 08: N/A 013 SERVICIDAE IS DESCRIPTION: INTER PANELS: OD 08: N/A 014 DAG 10AD INTER PANELS: OD 08: N/A 015 SERVICIDAE IS DESCRIPTION: INTER PANELS: OD 08: N/A 016 SERVICIDAE IS DESCRIPTION: INTER PANELS: N/A N/A 016 SERVICIDAE IS DESCRIPTION: INTER PANELS: N/A N/A 016 SERVICIDAE IS DESCRIPTION OF PANELS & PURINES N/A N/A N/A NATERAL LOAD: 2000 PSF N/D DESCRIPT: DOOD 101 INTE NAME LOAD: 10.0 PSF N/D DESCRIPT: N/A 102 SERVICIDAE IS DESCRIPTION: 10.5 N/A DEFLECTION LINTS: 103 SERVICIDAE IS DESCRIPTION: 10.5 N/A DEFLECTION LINTS: 104 SERVICIDAE IS D		SYSTEM CONTRA
(800) 225-0481 www.pellobuildings.com TRAMED OPEN NGS: Buek UILDING LOADS / DESCRIPTION: INC. INC. INC. INC. INC. UILDING DIRENSIONS ARE NOMINAL REFER TO PLANS): CCUBALCY CATEGORY: I - Low LINER PANELS: UILDING DIRENSIONS ARE NOMINAL REFER TO PLANS): CCUBALCY CATEGORY: I - Low LINER TRIM: IS STRUCTURE IS DESCENDE UTULIZING THE LOADS COMPY SEE SMIC DESCN. CATEGORY: I - Low LINER TRIM: IS STRUCTURE IS DESCENDE UTULIZING THE LOADS COMPY SEE SMIC DESCN. CATEGORY: I - Low LINER TRIM: IS STRUCTURE IS DESCENDE UTULIZING THE LOADS COMPY SEE SMIC DESCN. CATEGORY: III. N/A DEF DEAL LOAD: 2.000 PSF 0.18 / -0.18 VID DAD: 1.1242 PSF 0.18 / -0.18 VID DAD: 1.02 SAI 0.11 SI 0.07 DEFLECTION 1.03 MPI SECOND RASE SHEAR D.10 Si 0.10 VIND LOAD 1.00 SAI 0.11 SI 0.07 DEFLECTION LIMITS: VIND LOAD 1.00 FEGON RASE SHEAR D.10 Si 0.07 DEFLECTION LIMITS: VIND LOAD 1.00 FEGON RASE SHEAR 0.87 0.10 D.10		PRACTIC MANUFAC
UILDING LOADS / DESCRIPTION: UILDING UILDING THE A3.5 IFIGHT 15.88 / 15.88 SILE CLASS: I UULDING DIMENSIONS ARE NOMINAL REFER TO PLANS). COLORS (1 - 1 - 1 ow) LINER TRIM: UULDING DIMENSIONS ARE NOMINAL REFER TO PLANS). COLORS (1 - 1 - 1 ow) LINER TRIM: SISSINCTURE IS DESIGNED UTULIZING THE LOADS COMPLY SFISM C DESIGN CALEGORY, E COLOR: N/A SESSINCTURE IS DESIGNED UTULIZING THE LOADS COMPLY SFISM C DESIGN CALEGORY, E COLOR: N/A SECONTRACTOR IS TO CONFRM THAT THESE LOADS COMPLY SFISM C DESIGN CALEGORY, E COLOR: N/A SECONTRACTOR IS TO CONFRM THAT THESE LOADS COMPLY SFISM C DESIGN CALEGORY, E COLOR: N/A SECONTRACTOR IS TO CONFRM THAT THESE LOADS COMPLY SFISM C DESIGN CALEGORY, E COLOR: N/A SECONTRACTOR IS TO CONFRM THAT THESE LOADS COMPLY COLOR: N/A COLOR: N/A SECONTRACTOR IS TO CONFRM THAT THESE LOADS CONFLY COLOR: COLOR: N/A SECONTRACTOR IS TO CONFRM THAT THESE LOADS CONFLY COLOR: COLOR: N/A SECONTRACTOR IS TO CONFRM THAT THESE LOADS CONFLY COLOR: COLOR: N/A SECONTRACTOR IS TO CONFRM THAT THESE LOADS COLOR: COLOR: N/A SECONTRACTOR: COLOR: COLOR: COLOR: COLOR:	906 West 9th Street Pella, IA 50219 EAVE:Black	STRUCTU 9TH ED. DESIC
UILDING LOADS / DESCRIPTION: UILDING DESCRIPTION: UILDING DESCRIPTION: UILDING DESCRIPTION: UILDING DIMENSIONS ARE NOMINAL REFER TO PLANS): OCCURANCY CATEGORY:	(800) 225–0481 www.pellabuildings.com FRAMED OPENINGS: <u>Black</u>	
DILTING TOADS / DUSCINFTION: DUILDING TOADS / DUSCINFTION: COLOR: N/A THE AGO LINGTER ASS. HEICHT: 15.88 / 15.88 SIELCLASS: d LINER TRIM: UULDING DIMENSIONS ARE NOMINAL, REFER TO PLANS). DOUDRESIONS ARE NOMINAL, REFER TO PLANS). N/A SISTELCTURE IS DESIGNED UTILIZING THE LOADS INDICATED SLAME DESIGN CALEGORY, B COLOR: N/A DAPPLIED AS REQUIRED BY : IS TO CONDRAM THAT THESE LOADS COMPLY L Low LINER TRIM: TH THE REQUIREMENTS OF THE LOCAL BUILDING DEPARTMENT. DEFLECTION LINES N/A DEFLECTION LINES SIZE ULDE CALL 0.00 PSF NOM EXPOSURE C DEFLECTION LIMTS: ODE NOW LOAD: 20.00 PSF 0.1A -0.1A DEFLECTION LIMTS: SIZE UND SPEED: 1.03 MPH SPECTRAL RESPONSE COFFE. MAPPED SPECTRAL RESPONSE ACC. EW RAF WINC: 180 EWAL FACTOR: 1.20 Sol 0.11 Si 0.07 PRIL UKE: 180 EWAL FACTOR: DESIGN BASE SHEAR, Y: MANDED FORMULA 0.866746*To*S*W//R 0.07 PRIL UKE: 80 SINOW LOAD 1.00 EXPANDED FORMULA 0.86746*To*S*W//R	LINER PANELS:	MANUFA(THE
UILDING DIMENSIONS ARE NOMINAL REFER TO PLANS).	COLOR: N/A	IN COMP DRAWING
IS STRUCTURE IS DESIGNED UTILIZING THE LOADS INDICATED SEISMIC DESIGN CATEGORY_B COUR: N/A DAPPLED AS REQUIRED BY : LEC 18 COURS CONFIRM THAT THESE LOADS COMPLY TH THE REQUIREMENTS OF THE LOCAL BUILDING DEPARTMENT. DIDE DEAD [OAD] 2.000 PSF (ROOF PANELS & PURLINS) DILALERAL LOAD: 0.5 PSF SNOW EXPOSURE: 1.0000 DIDE LIVE LOAD: 20.00 PSF (WIND EXPOSURE: C.C. DIDE SNOW LOAD: 13.44 PSF INTERNAL PRESSURE COEFE. DIDE SNOW LOAD: 13.44 PSF INTERNAL PRESSURE COEFE. DIDE SNOW LOAD: 20 PSF (0.18 / -0.18 DEFLECTION LIMITS: SIGUID SNOW LOAD: 20 PSF (0.18 / -0.18 DEFLECTION LIMITS: DISMIC ZONE: B Sds 0.10 Ss 0.10 ERMAN LOAD: 20 Sd1 0.11 St 0.07 PMIL LIMITS: DECIDE ALL RESPONSE STARE SHEAR V: WIND LOAD 1.00 ERMANDED FORMULA 0.667*Le*For%2*W/R SNOW LOAD 1.00 ICONGTUDINAL 0.88 SEISMIC LOAD 1.00 ICONGTUDINAL 0.88 ISON LOAD 0.8000 ICONGTUDINAL 0.88 ISON LOAD 0.8000 ICONGTUDINAL 0.88 ISON LOAD 1.00 ICONGTUDINAL 0.88 ISON LOAD 0.8000 ICONGTUDINAL 0.88 ISON LOAD 1.00 ICONGTUDINAL 0.88 ISON LOAD 1.00 ICONGTUDINAL 0.88 ISON LOAD		ALL E Manufac
TH THE REQUIREMENTS OF THE LOCAL BUILDING DEPARTMENT. DOE DEAD LOAD: 2.000 PSF (ROOF PANELS & PURLINS) DILATERAL LOAD: 0.5 PSF SNOW EXPOSURE: 0 NOF SNOW LOAD: 13.44 PSF INTERNAL PRESSURE COFFE: NUMD SNOW LOAD: 13.44 PSF INTERNAL PRESSURE COFFE: NUMD SNOW LOAD: 20 PSF 0.18 / -0.18 NSIC WIND SPEED: 103 MPH SPECTRAL RESPONSE COFFE: NUMD SNOW LOAD: 103 MPH SPECTRAL RESPONSE COFFE: NSIC ZONE: 8 Sds 0.10 Ss 0.10 EFRMAL FACTORS: DESIGN BASE SHEAR V: WIND LOAD 1.00 Sd1 0.11 St 0.07 PORTANCE FACTORS: DESIGN BASE SHEAR V: WIND LOAD 1.00 EXPANDED FORMULA 0.667*Ie*Fo*Ss*W/R SIGUE COAD 1.00 TRANSVERSE 0.87 FF VERTICAL: 80 WIND LOAD 1.00 TRANSVERSE 0.87 FF VERTICAL: 80 WIND BENT SEES: 0 EFRAL NOTES: MINIMUM YIELD: HOT ROLLED BAR FY = KaI MIN. STRUCTURAL STEEL SHEET FY = KAI MIN.	DESIGNED LITULZING THE LOADS INDICATED	ERECTOI TEMP OR OTH FURNISH
LATERAL LOAD: 0.5 PSF SNOW EXPOSURE: 1.000 LOE LVE LOAD: 20.00 PSF WIND EXPOSURE: C LOF SNOW LOAD: 13.44 PSF INTERNAL PRESSURE COEFF.: DEFLECTION LIMTS: COUND SNOW LOAD: 20 PSF 0.18 /		THE STE COMPAR RESULTI
OF LIVE LOAD: 20.00 PSF WIND EXPOSURE: C OF SNOW LOAD: 13.44 PSF INTERNAL PRESSURE COFFE. D OUND SNOW LOAD: 20 PSF 0.18 /0.18 D SIC WIND SPEED: 103 MPH SPECTRAL RESPONSE COFFF. MAPPED SPECTRAL RESPONSE ACC, BURK RESPONSE ACC, SIGN RASE EW COL: 180 ISMIC ZONE: B Sds 0.10 Ss 0.10 ERMAL FACTOR: 1.20 Sd1 0.11 St 0.07 PORTAINCE FACTORS: DESIGN RASE SHEAR. V: MIND LOAD 1.00 EXPANDED FORMULA 0.667*le*Fa*Ss*W/R ROOF PANEL WR: 180 SNOW LOAD 0.3000 LONGITUDINAL 0.86 RF HORIZONTAL: 180 RF HORIZONTAL: 180 SNOW LOAD 0.3000 TRANSVERSE 0.87 WIND BENT: 60 RF HORIZONTAL: 180 SNOW LOAD 1.00 TRANSVERSE 0.87 WIND BENT: 60 RF HORIZONTAL: 180 SNOW LOAD 1.00 TRANSVERSE 0.87 WIND BENT: 60 RF HORIZONTAL: 180 SNOW LOAD 1.00 TRANSVERSE 0.87 WIND BENT: 60	2.000 PSF (ROOF PANELS & PURLINS)	RESULTII UNPRED
OF SNOW LOAD: 13.44 PSF INTERNAL PRESSURE COEFF. MAPPED SPECTRAL RESPONSE ACC. DEFLECTION LIMTS: SIC WIND SPEED: 103 MPH SPECTRAL RESPONSE COEFF. MAPPED SPECTRAL RESPONSE ACC. EW COL: 180 ISMIC ZONE: B Sds 0.10 Ss 0.10 ERMAL FACTOR: 1.20 Sd1 0.11 St 0.07 PORTANCE FACTORS: DESIGN BASE SHEAR. V: VIND LOAD 1.00 EXPANDED FORMULA 0.667*le*Fo*Ss*W/R PURL WIND: 150 SNOW LOAD 1.00 EXPANDED FORMULA 0.667*le*Fo*Ss*W/R ROF PAREL WIND: 180 SNOW LOAD 1.00 EXPANDED FORMULA 0.667*le*Fo*Ss*W/R ROF PAREL WIND: 60 SNOW LOAD 1.00 TRANSVERSE 0.87 WIND ENTITIES 0.07 ERAL NOTES: WIND MUM YIELD: Fy = ksi MIN. 0.88 SEISMIC LOAD 0.00 STRUCTURAL STEEL SHEET Fy = ksi MIN. STRUCTURAL STEEL SHEET Fy = ksi MIN. COLD FORMED SHAPES Fy = ksi MIN. Fy = ksi MIN. STRUCTURAL STEEL SHEET	0.5 PSF <u>SNOW EXPOSURE:</u> 1.0000	7.9.1 AI <u>WARN</u>
OUIND_SNOW_LOAD: 20 PSF 0.18 -0.18 SIC_WIND_SPEED: 103 MPH SPECTRAL RESPONSE COEFF. MAPPED_SPECTRAL RESPONSE ACC. EW CO.10 Sis 0.10 Sis 0.10 Sis 0.10 Sis 0.10 EW RAF_UNDS EW RAF_UNDS EW CO.11 Sis 0.01 EW RAF_UNDS 180 ERMAL_FACTOR: 1.20 Sd1 0.11 St 0.07 OPURL UVES 180 CONTANCE_FACTORS: DESIGN_BASE_SHEAR, V: DESIGN_BASE_SHEAR, V: 0.07 OPURL UVES: 180 WIND_LOAD 1.00 EXPANDED FORMULA 0.667*le*Fo*Ss*W/R 0.07 PURL WIND: 180 SNOW_LOAD 0.8000 LONGITUDINAL 0.88 SISSING: 0.07 PURL WIND: 60 SISSUCTURAL STEEL SHEET Fy = Ksi MIN. SISSUCTURAL STEEL SHEAF SISSUCTURAL STEEL SHEAF SISSUCTURAL STEEL SHEAF SISSUND SISSUCTURAL STEEL SHEAF SISSUND SISSUCTURAL STEEL SHEAF SISSUCTURAL STEEL SHEAF SISSUCTURAL STEEL SHEAF Fy = Ksi MIN. SISSUCTURAL STEEL SHEAF S	20.00 PSF <u>WIND EXPOSURE:</u> C	WITH LE The Alu
SIC WIND SPEED: 103 MPH SPECTRAL RESPONSE COFF. MAPPED SPECTRAL RESPONSE ACC. ISMIC ZONE: B Sds 0.10 Ss 0.10 ERMAL FACTOR: 1.20 Sd1 0.11 St 0.07 PORTANCE FACTORS: DESIGN_BASE_SHEAR. V: 0.07 WALL GIRT: 90 VIND LOAD 1.00 EXPANDED FORMULA 0.667*le*Fa*Ss*W/R 0.07 WALL GIRT: 90 SNOW LOAD 0.8000 LONGITUDINAL 0.867*le*Fa*Ss*W/R ROF PANEL LIVE: 60 SEISMIC LOAD 1.00 TRANSVERSE 0.87 RF CRANCE: 0 REAL NOTES: MINIMUM YIELD: HON 0.867*le*Fa*Ss*W/R RF CRANCE: 0 HOT ROLLED BAR Fy = ksi MIN. 0.87 RF CRANCE: 0 RF CRANCE: 0 STRUCTURAL STEEL SHEET Fy = ksi MIN. STRUCTURAL STEEL PLATE Fy = ksi MIN. NON RSI MIN. VALL SHEETING Fy = ksi MIN. KIN. KIN KIND KIND KIND KIND KIND RERAL NOTES: MATENALS <t< td=""><td>13.44 PSF INTERNAL PRESSURE COEFF.:</td><td>STEEL F GALVALU</td></t<>	13.44 PSF INTERNAL PRESSURE COEFF.:	STEEL F GALVALU
ISMIC ZONE:BSds0.10Ss0.10EW RAF LIVE:180ERMAL FACIOR:1.20Sd10.11St0.07WALL GIRT:90PURL LIVE:1800.11St0.07WALL GIRT:90PURL LIVE:1.00SSDESIGN BASE SHEAR, V:WALL GIRT:90WIND LOAD1.00EXPANDED FORMULA0.667*le*Fo*Ss*W/RWALL PANEL:60SNOW LOAD0.8000LONGITUDINAL0.88RF HORIZONTAL:180SEISMIC LOAD1.00TRANSVERSE0.87RF VERTICAL:60REAL NOTES:MINIMUM YIELD:0.87RF SEIS:0WIND BARFy =ksi MIN.Ksi MIN.RF SEIS:0STRUCTURAL STEEL SHEETFy =ksi MIN.Ksi MIN.RF SEIS:0COLD FORMED SHAPESFy =ksi MIN.Ksi MIN.Kim.Ksi MIN.WALL SHEETINGFy =ksi MIN.Ksi MIN.Ksi MIN.WALL SHEETINGFy =ksi MIN.Ksi MIN.Ksi MIN.WALL SHEETINGFy =ksi MIN.Ksi MIN.WALL SHEETINGFy =ksi MIN.Ksi MIN.WALL SHEETINGFy =ksi MIN.WALL SHEETINGFy =ksi MIN.WALL SHEETINGFy =ksi MIN.WALL SHEETINGFy =Koof SHEETINGFy =Koof SHEETINGFy =Kasi MIN.WALL SHEETINGFy =Kasi MIN.WALL SHEETINGFy = <t< td=""><td><u>D: _20 PSF _0.18 /0.18</u> DEFLECTION LIMTS:</td><td></td></t<>	<u>D: _20 PSF _0.18 /0.18</u> DEFLECTION LIMTS:	
LSMOC ZUNKL B JSGS 0.10 JSS 0.10 SS 0.10 EW RAF WIND: 180 EFMAL FACTOR: 1.20 Sd1 0.11 St 0.07 WIRD LIVE: 180 PORTANCE FACTORS: DESIGN BASE SHEAR, V: 0.11 St 0.07 PURL LIVE: 180 PORTANCE FACTORS: DESIGN BASE SHEAR, V: VIND LOAD 1.00 EXPANDED FORMULA 0.667*le*Fo*Ss*W/R ROOF PANEL LIVE: 60 SNOW LOAD 0.8000 LONGITUDINAL 0.88 RF HORIZONTAL: 180 SEISMIC LOAD 1.00 TRANSVERSE 0.87 RF VERTICAL: 60 WIND BENT: 60 RF CRANE: 0 0 RF VERTICAL: 60 SEISMIC LOAD 1.00 TRANSVERSE 0.87 RF VERTICAL: 60 WIND BENT: Structural Steel SHEAR Fy = ksi MIN. NIND BENT SEIS: 0 WIND BAR Fy = ksi MIN. STRUCTURAL STEEL PLATE Fy = ksi MIN. NIND. SUB STRUCTURAL STEEL PLATE Fy = ksi MIN. KSI MIN. KSI MIN. KSI MIN. KSI MIN. COLD FORMED SHAPES Fy = ksi MIN. KSI MIN. KSI MIN. KSI MIN. KSI	EW COL: 180	THE APPROVA
LEMAL FACTOR:1.20Sdi0.11St0.07PURL LIVE:180PORTANCE FACTORS:DESIGN BASE SHEAR, V:WALL PANEL:60WIND LOAD1.00EXPANDED FORMULA0.667*le*Fo*Ss*W/RROOF PANEL LIVE:60SNOW LOAD0.8000LONGITUDINAL0.88RF HORIZONTAL:180SEISMIC LOAD1.00TRANSVERSE0.87WIND BENT:60ERAL NOTES:MINIMUM YIELD:TRANSVERSE0.87WIND BENT:60RF SEIS:OWIND BENT SEIS:OWATERIALS :MINIMUM YIELD:WIND BENT SEIS:0HOT ROLLED BARFy =ksi MIN.STRUCTURAL STEEL SHEETFy =ksi MIN.STRUCTURAL STEEL PLATEFy =ksi MIN.WIN.WINDSTRUCTURAL STEEL PLATEFy =ksi MIN.WIN.ROOF SHEETINGFy =ksi MIN.ROOF SHEETINGFy =ksi MIN.ROOF SHEETINGFy =ksi MIN.ROOF SHEETINGFy =ksi MIN.	<u> </u>	IN CONT INDICATE
PORTANCE FACTORS: DESIGN BASE SHEAR, V: WALL PANEL: 60 WIND LOAD 1.00 EXPANDED FORMULA 0.667*le*Fo*Ss*W/R ROOF PANEL LIVE: 60 SNOW LOAD 0.8000 LONGITUDINAL 0.88 RF HORIZONTAL: 180 SEISMIC LOAD 1.00 TRANSVERSE 0.87 RF VERTICAL: 60 ERAL NOTES: TRANSVERSE 0.87 WIND BENT: 60 MATERIALS : MINIMUM YIELD: 0.87 RF CRANE: 0 HOT ROLLED BAR Fy = ksi MIN. STRUCTURAL STEEL SHEET Fy = ksi MIN. STRUCTURAL STEEL PLATE Fy = ksi MIN. Kim. Kim. COLD FORMED SHAPES Fy = ksi MIN. Kim. ROOF SHEETING Fy = ksi MIN. Kim. ROOF SHEETING Fy = ksi MIN.	<u>1.20</u> Sal <u>0.11</u> St <u>0.07</u> PURL LIVE: 180	ALL PAG Extensi
WIND LOAD1.00EXPANDED FORMULA0.667*le*Fa*Ss*W/RROOF PANEL WIND: 60SNOW LOAD0.8000LONGITUDINAL0.88RF HORIZONTAL:180SEISMIC LOAD1.00TRANSVERSE0.87WIND BENT:60REAL NOTES: WATERIALS :MINIMUM YIELD: HOT ROLLED BARFy =ksi MIN.Kinn.KF VERTICAL:0STRUCTURAL STEEL SHEETFy =ksi MIN. STRUCTURAL STEEL SHEETFy =ksi MIN. STRUCTURAL STEEL PLATEFy =ksi MIN. STRUCTURAL STEEL PLATEFy =ksi MIN. STRUCTURAL STEEL SHAPESFy =Ksi MIN. STRUCTURAL STEEL SHAPES	<u>RS:</u> <u>Design base shear, v:</u> Wall panel: 60	THE DEL THE MET C ONTRA
SNOW LOAD 0.800 LONGTODINAL 0.88 RF VERTICAL: 60 SEISMIC LOAD 1.00 TRANSVERSE 0.87 WIND BENT: 60 RF CRANE: 0 RF CRANE: 0 RF SEIS: 0 WIND BENT SEIS: 0 WATERIALS : MINIMUM YIELD: WIND BENT SEIS: 0 HOT ROLLED BAR Fy = ksi MIN. STRUCTURAL STEEL SHEET Fy = ksi MIN. STRUCTURAL STEEL PLATE Fy = ksi MIN. STRUCTURAL STEEL PLATE Fy = ksi MIN. COLD FORMED SHAPES Fy = ksi MIN. KALL SHEETING Fy = ksi MIN. WALL SHEETING Fy = ksi MIN. KSI MIN. KAL SHEETING Fy = Ksi MIN.	1.00 EXPANDED FORMULA 0.667*Ie*Fa*Ss*W/R ROOF PANEL WIND:60	DRAWN SUPPLIE
ERAL NOTES: RF CRANE: O ERAL NOTES: MINIMUM YIELD: WIND BENT SEIS: O MATERIALS : MINIMUM YIELD: WIND BENT SEIS: O HOT ROLLED BAR Fy = ksi MIN. STRUCTURAL STEEL SHEET Fy = ksi MIN. STRUCTURAL STEEL PLATE Fy = ksi MIN. STRUCTURAL STEEL PLATE Fy = ksi MIN. COLD FORMED SHAPES Fy = ksi MIN. STRUCTURAL SHEETING Fy = ksi MIN. WALL SHEETING Fy = ksi MIN. STRUCTURAL SHEETING Fy = ksi MIN.	RF VERTICAL: 60	C OMFOR MANUFAC
MATERIALS:MINIMUM YIELD:HOT ROLLED BARFy =ksi MIN.STRUCTURAL STEEL SHEETFy =ksi MIN.STRUCTURAL STEEL PLATEFy =ksi MIN.COLD FORMED SHAPESFy =ksi MIN.WALL SHEETINGFy =ksi MIN.ROOF SHEETINGFy =ksi MIN.	RF CRANE: 0 RF SEIS: 0	SUB SEQ ORDER STAMPS
STRUCTURAL STEEL SHEETFy =ksi MIN.STRUCTURAL STEEL PLATEFy =ksi MIN.COLD FORMED SHAPESFy =ksi MIN.WALL SHEETINGFy =ksi MIN.ROOF SHEETINGFy =ksi MIN.	MINIMUM YIELD:	MERE RI CHANGE
COLD FORMED SHAPES Fy = ksi MIN. NALL SHEETING Fy = ksi MIN. ROOF SHEETING Fy = ksi MIN.	EL SHEET Fý = ksi MIN.	WITH US Languac
ROOF SHEETING Fy = ksi MIN.	HAPES Fý = ksi MIN.	ENGINEE TO THES OBLICAT
		OBLIGAT
HE METAL BUILDING MANUFACTURER RESERVES THE RIGHT TO UBSTITUTE THE ABOVE MATERIALS WITH EQUAL OR BETTER MATERIAL.	NG MANUFACTURER RESERVES THE RIGHT TO	AL DETAILING F.
BOLT TIGHTENING REQUIREMENTS:		· · · · · · · · · · · · · · · · · · ·

HIGH STRENGTH BOLTS SHALL BE TIGHTENED BY THE TURN OF THE NUT METHOD IN ACCORDANCE WITH THE LATEST EDITION AISC "SPECIFICATION FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS". A325 BOLTS SHALL BE INSTALLED WITH OUT WASHERS WHEN TIGHTENED BY THE "TURN OF THE NUT" METHOD. ALL BOLTED CONNECTIONS, FOR SHEAR/BEARING CONNECTION TYPE WITH BOLT THREADS EXCLUDED FROM THE SHEAR PLANE SHALL BE SNUG TIGHT ONLY.

3) ALL STRUCTUAL STEEL TO RECEIVE A RUST INHIBITIVE PRIMER. THIS PAINT IS NOT INTENDED FOR LONG TERM EXPOSURE TO THE ELEMENTS.



\triangle		
\triangle		PURCHASER:
\bigtriangleup		
<u> </u>	FOR CONSTRUCTION	PROJECT:
<u>A</u> //	FOR APPROVAL	JOB NUMBEF
REV. DATE	REVISION	

BUILDER / CONTRACTOR RESPONSIBILITIES

SPONSIBILITY OF THE BUILDER/CONTRACTOR TO INSURE THAT ALL PROJECT CIFICATIONS COMPLY WITH THE APPLICABLE REQUIREMENTS OF ANY DING AUTHORITIES. THE SUPPLYING OF SEALED ENGINEERING DATA AND THE METAL BUILDING SYSTEM DOES NOT IMPLY OR CONSTITUTE AN T THE METAL BUILDING SYSTEM MANUFACTURER OR ITS DESIGN ENGINEER HE ENGINEER OF RECORD OR DESIGN PROFESSIONAL FOR A CONSTRUCTION

CTOR MUST SECURE ALL REQUIRED APPROVALS AND PERMITS FROM THE ENCY AS REQUIRED. APPROVAL OF THE METAL BUILDING SYSTEM S DRAWINGS AND CALCULATIONS INDICATE THAT THE METAL BUILDING CTURER CORRECTLY INTERPRETED AND APPLIED THE REQUIREMENTS OF THE /INGS AND SPECIFICATIONS. (SECT. 4.2.1 AISC CODE OF STANDARD ED.) WHERE DISCREPANCIES EXIST BETWEEN THE METAL BUILDING SYSTEM S STRUCTURAL STEEL PLANS AND THE PLANS FOR OTHER TRADES, THE EEL PLANS SHALL GOVERN. (SECT. 3.3 AISC CODE OF STANDARD PRACTICE

SIDERATIONS OF ANY MATERIALS IN THE STRUCTURE WHICH ARE NOT THE METAL BUILDING SYSTEM MANUFACTURER ARE THE RESPONSIBILITY OF RS AND ENGINEERS OTHER THAN THE METAL BUILDING SYSTEM S. ENGINEER UNLESS SPECIFICALLY INDICATED

CTOR IS RESPONSIBILE FOR ALL ERECTION OF STEEL AND ASSOCIATED WORK WITH THE METAL BUILDING SYSTEM MANUFACTURER "FOR CONSTRUCTION"

AS SHOWN AND PROVIDED BY THE METAL BUILDING SYSTEM FOR THIS BUILDING IS REQUIRED AND SHALL BE INSTALLED BY THE PERMANENT PART OF THE STRUCTURE.

SUPPORTS, SUCH AS TEMPORARY GUYS, BRACES, FALSE WORK, CRIBBING ENTS REQUIRED FOR THE ERECTION OPERATION WILL BE DETERMINED AND INSTALLED BY THE ERECTOR. THESE TEMPORARY SUPPORTS WILL SECURE MING, OR ANY PARTLY ASSEMBLIED STEEL FRAMING, AGAINST LOADS INTENSITY TO THOSE FOR WHICH THE STRUCTURE WAS DESIGNED, 4 WIND, SEISMIC FORCES AND ERECTION OPERATIONS, BUT NOT THE LOADS 4 THE PERFORMANCE OF WORK BY OR THE ACTS OF OTHERS, NOR SUCH LOADS AS THOSE DUE TO TORNADO, EXPLOSION, OR COLLISION. (SECT. E OF STANDARD PRACTICE, 9TH ED.)

NO CASE SHOULD GALVALUME STEEL PANELS BE USED IN CONJUNCTION COPPER. BOTH LEAD AND COPPER HAVE HARMFUL CORROSION EFFECTS ON ZINC ALLOY COATING WHEN THEY ARE USED IN CONTACT WITH GALVALUME EVEN RUN-OFF FROM COPPER FLASHING, WIRING, OR TUBING ONTO ULD BE AVOIDED.

APPROVAL NOTES


NG CONDITIONS APPLY IN THE EVENT THAT THESE DRAWINGS ARE USED AS INGS: IT IS IMPERATIVE THAT ANY CHANGES TO THESE DRAWINGS BE MADE INK (PREFERABLY RED INK), HAVE ALL INSTANCES OF CHANGE CLEARLY BE LEGIBLE AND UNAMBIGUOUS. A SIGNATURE AND DATE IS REQUIRED ON UFACTURER RESERVES THE RIGHT TO RE-SUBMIT DRAWINGS WITH OMPLEX CHANGES REQUIRED TO AVOID MISFABRICATION. THIS MAY IMPACT CHEDULE. APPROVAL OF THESE DRAWINGS INDICATES CONCLUSIVELY THAT DING SYSTEM MANUFAACTURER HAS CORRECTLY INTERPRETED THE JIRGMENTS, AND FURTHER CONSTITUTES AGREEMENT THAT THE BUILDING AS DICATED CHANGES REPRESENTS THE TOTAL OF THE MATERIALS TO BE ANUFACTURER. ANY CHANGES NOTED ON THHE DRAWINGS NOT IN WITH THE TERMS AND REQUIREMENTS OF THE CONTRACT BETWEEN AND ITS CUSTOMER ARE NOT BINDING ON MANUFACTURER UNLESS SPECIFICALLY ACKNOWLEDGED AND AGREED TO IN WRITING BY CHANGE RATE DOCUMENTATION. MANUFACTURER RECONGNIZES THAT RUBBER UTINELY USED FOR INDICATING APPROVAL, DISAPPROVAL, REJECTION, OR 7 THE DRAWINGS SUBMITTED. HOWEVER, MANUFACTURER DOES NOT ACCEPT DDITIONS TO CONTRACTURAL TERMS AND CONDITIONS THAT MAY APPEAR STAMP OR SIMILIAR INDICATION OF APPROVAL, DISAPPROVAL, ETC. SUCH ED TO MANUFACTURER'S DRAWINGS BY THE CUSTOMER, ARCHITECT, NY OTHER PARTY WILL BE CONSIDERED AS UNACCEPTABLE ALTERNATIONS ING NOTES, AND WILL NOT ALTER THE CONTRACTUAL RIGHTS AND ISTING RETWEFN MANUFACTURER AND LTS CUSTOMER

ATION, AND DELIVERY DATE OF THIS PROJECT APPROVALS ARE RETURNED TO THE METAL G MANUFACTURER.

: MEGA Storage

60x84

R: R



DESCRIPTION: FLOOR PLAN PELLA CUSTOMER: LOCATION: DRN. BY С JB


DOO	R SCHED	ULE	
∇ ID	QUAN	DESCRIPTION	COLOR
1	4	Janus 1214 M1950 Rollup	Silhouette Gray
2	4	Janus 1214 M1950 Rollup	WHITE

COMPARTMENT TABLE

○ ID	QUAN	WIDTH	LENGTH	
1	4	13'-9"	30'-0"	
2	4	28'-0"	60'-0"	


* PROFMISSO * RICHARD K. JOYCE NUMBER PE-2003005438
ONAL ENSE

MEGA Storage PROJECT: 60x84								
_ee's s	UMMIT							
CK'D BY	DATE	SCALE	REV.	QUOTAT	ION NO.		SHEET	NO.
	2/20/23	N.T.S.	00	R		1	OF	14





R:	MEGA Sto	rage			PROJECT:	60x84			
٧:	LEE'S S	имміт							
	CK'D BY	DATE	SCALE	REV.	QUOTAT	ION NO.		SHEET	NO.
		2/20/23	N.T.S.	00	R		2	OF	14






MEMBER 1	TABLE	
MARK	PART	LENGTH
S-1	6X2C16	16'-1"
S-2	6X2C16	16'-3 1/2"
S-3	6X2C16	16'-6"
S-4	6X2C16	16'-8 1/2"
S-5	6X2C16	16'-11"
S-6	6X2C16	17'-1 1/2"
S-7	6X2C16	16'-0"




MEGA Sto	rage		PROJECT:	60x84				
_EE'S S	UMMIT							
CK'D BY	DATE	SCALE	REV.	QUOTAT	ION NO.		SHEET	NO.
	2/20/23	N.T.S.	00	R		3	OF	14



RIM TABLE				
D PART	5	LENGTH 10'-2"		DETAIL
4 PBDT-1. 5 FL16D		10 –2 15'–4" 1'–4"		TRIM_229
6 FL16B	MBER TA			
		PART		ENGTH
S	-1 -2	6X2C16	1	6'-1"
S	-3	6X2C16 6X2C16		6'-3 1/2" 6'-6"
S	-4	6X2C16 6X2C16		6'-8 1/2" 6'-11" 7'-1 1/2"
G	-6 -1	6X2C16 6X2C16	4	'-1 1/2 '-5 3/4" '-9 1/2"
G	-2 -3	6X2C16 6X2C16	4	-9 1/2 '-7 1/2"
	ſ	ANGLE TAI	BLE	
	-		K LI	ENGTH 0'-0"
		1 L3x 2 PB6	EC 2	0'-0"
	Į	3 PB6		CRAP TION PLATES
				ARK/PART
				BMC-6
			-10000	ITT
		E.	EOFN	ISSO
		EN?	pur	Ne &
	Ë	×/R	ICHAR	ФК. \=
	a	PR	JOYC NUMB	
	Ý	PE PE	E-20030(15438 Jul
	1	W.	B 2 7 20	$\rightarrow a$
		All all	ONAL	EN
		-0	alline	The second
	PRO	DJECT:	ee's Sur	nmit
SCALE RI	EV.	QUOTATION	NO.	SHEET NO.

JB


MEGA STO	orage			PROJECT:	Lee s	Summ	זור	
_ee's s	UMMIT							
CK'D BY	DATE	SCALE	REV.	QUOTAT	ION NO.		SHEET N	۱٥.
	2/13/23	N.T.S.	00	R		4	OF	14





JB


TRIM TABLE		
◇ID PART 4 PBDT−1.5	LENGTH	DETAIL
5 FL16D 6 FL16B	LENGTH 10'-2" 15'-4" 1'-4"	TRIM_229
MEMBER		
MARK S-1	PART 6X2C16	LENGTH 16'-1"
S-2 S-3	6X2C16 6X2C16	$16^{-1} - 3 1/2^{"}$ $16^{-} - 6^{"}$ $16^{-} - 8 1/2^{"}$ $16^{-} - 11^{"}$
S-4 S-5	6X2C16 6X2C16	16'-8 1/2" 16'-11"
S-6 G-1	6X2C16 6X2C16	1/1/-1/1/2
G-2 G-3	6X2C16 6X2C16	4'-5 3/4" 4'-9 1/2" 4'-7 1/2"
	ANGLE TABLE	
	◇ID MARK 1 L3x3	LENGTH 20'-0"
	2 PB6EC 3 PB6EC	20'-0" 20'-0" SCRAP
		NECTION PLATES
		MARK/PART
	1	PBMC-6
		FMIST
	E. T.	FMISSO
	RICH	ROKE
	JC JC	YCE *
	PE-200	MBER 23005438
		7 2023 58
	NON.	ALENS
	alle	TUTTER
<u></u>		
G		Summit
	PROJECT: Lee's	Summit
SCALE REV	ΟΠΟΤΑΤΙΟΝ ΝΟ	SHEET NO


MEGA Sto	rage			PROJECT: Lee's S	Summit
	5		TROJECT. Lee 3 .		
_EE'S S	UMMIT				
CK'D BY	DATE	SCALE	REV.	QUOTATION NO.	SHEET NO.
	2/13/23	N.T.S.	00	R	5 OF 14












ROOF FRAMING



MEMBER TABLE									
MARK	PART	LENGTH							
TC-1	PB6EC	13'-9"							
TC-2	PB6EC	28'-0"							
P-1	6X25Z14	14'-9"							
P-2	12X25Z12	33'-0"							




MEGA Sto	rage			PROJECT:	60x84			
_EE'S S	UMMIT							
CK'D BY	DATE	SCALE	REV.	QUOTAT	ION NO.		SHEET	NO.
	2/20/23	N.T.S.	00	R		8	OF	14

	A												83'-6"	OUT-TC	-OUT OF	F STEEL												
	-		13'-9"						2	28'-0"				E)				<u>28'-0"</u>					F		<u>13'-9"</u>		•
	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	<u>30'-4"</u>
60'-0"															>— -													
13	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30°-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"	30'-4"


ROOF SHEETING & TRIM PANELS: 26 Ga. PR - Galvalume+ w/ Drip Stop




TRIM	TABLE		
○ID	PART	LENGTH	DETAIL
1	FL49	3'-0"	TRIM_320



MEGA Sto	orage			PROJECT:	60x84			
.EE'S S	UMMIT							
CK'D BY	DATE	SCALE	REV.	QUOTAT	ION NO.		SHEET	NO.
	2/20/23	N.T.S.	00	R		9	OF	14





<u>13'-10"</u>
13'-10"
13'-10"
13'-10"
13'-10"
13'-10"

WALL SHEETING & TRIM FRAME LINE: 7 PANELS: 29 Ga. PR - Galvalume +


D C B A

<u> </u>	-10"
13'-	-10"
13'-	-10"
13'-	-10"
13'-	-10"
13'-	-10"

WALL SHEETING & TRIM FRAME LINE: 7 PANELS: 29 Ga. PR - Galvalume +



	MEMBER	TABLE	
	MARK	PART	LENGTH
	S-6	6X2C16	17'-1 1/2"
		ANGLE TABLE	
		◇ID MARK 1 STUD	LENGTH 10'-0"
			INNECTION PLATES
			D MARK/PART
			1 BASECLIP
		TO REC	OF MISSOURIE THARD K. OYCE JMBER 003005438
RTITION DRAWING			AL L'INTERNET
A Storage	F	ROJECT: Lee's	Summit
S SUMMIT			
BY DATE SCALE 2/13/23 N.T.S.	REV. 00	QUOTATION NO.	SHEET NO. 10 OF 14
2/10/20 11.1.3.	50		




WALL SHEETING & TRIM FRAME LINE: (Typ of 3) PANELS: 29 Ga. PR - Galvalume +




MARK	PART	LENGTH
S-1 S-2	6X2C16 6X2C16	LENGIH 16'-1" 16'-3 1/2" 16'-6" 16'-8 1/2" 16'-11" 17'-1 1/2"
S-3	6X2C16	16'-6"
S-4 S-5	6X2C16 6X2C16	16'-8 1/2" 16'-11"
S-6	6X2C16	17'-1 1/2"
		CONNECTION PLATES
		DID MARK/PART
		1 BASEĈLIP



MEGA Sto	rage			PROJECT:	Lee's S	umm	it	
lee's s	UMMIT							
CK'D BY	DATE	SCALE	REV.	QUOTAT	ION NO.		SHEET	NO.
	2/13/23	N.T.S.	00	R		11	OF	14









MEGA Storage				PROJECT:	Lee's S	Summit			
_EE'S S	UMMIT								
CK'D BY	DATE	SCALE	REV.	QUOTAT	SHEET NO.				
	2/13/23	N.T.S.	00	R		13	OF	14	