

1. General Information:

- A. The contractor shall verify dimensions and conditions before construction and notify the engineer of any discrepancies, inconsistencies, or difficulties affecting the work before proceeding.
- B. The contractor shall coordinate all disciplines, verifying size and location of all openings, whether shown on structural drawings or not, as called for on architectural, mechanical, or electrical drawings. In the case of work in an existing building the contractor shall scan existing structure to locate all rebar in the area of the new core/opening using ground penetrating radar and notify the engineer of record for review prior to commencing. Conflicts, inconsistencies, or other difficulties affecting structural work shall be called to the architect or engineer's attention for direction before proceeding.
- C. All design and construction work for this project shall conform to the requirements of the following governing design codes:
1. International Building Code (IBC 2018) as amended by the City of Lee's Summit, Missouri
  2. Minimum Design Loads for Buildings and Other Structures (ASCE7-16)
  3. Specification for Structural Steel Buildings (AISC 360-16)
  4. Structural Welding Code (AWS D14.1-17)
  5. Building Code Requirements for Structural Concrete (ACI 318-14)
  6. Building Code Requirements for Masonry Structures (TMS 402-16)
  7. North American Specification for the Design of Cold-Formed Steel Structural Members (AIS1 5100-16)
  8. National Design Specification (NDS) for Wood Construction with 2018 Supplements (ANSI/AWC NDS-2018)
  9. Special Design Provisions for Wind and Seismic (AWC SDPWS-2015)
- D. These drawings are for this specific project and no other use is authorized.

2. Structural Design Load Criteria:

- A. Dead Loads:
- |                  |          |
|------------------|----------|
| Floor, Apartment | = 35 psf |
| Floor, Balcony   | = 55 psf |
| Floor, Corridor  | = 30 psf |
| Roof             | = 25 psf |
| Stair, Wood      | = 25 psf |
- B. Live Loads:
- |                                     |           |
|-------------------------------------|-----------|
| Floor, Apartment                    | = 40 psf  |
| Floor, Balcony                      | = 60 psf  |
| Floor, Corridor (Serving Apartment) | = 40 psf  |
| Floor, Corridor (Serving Public)    | = 100 psf |
| Floor, Public (Clubhouse)           | = 100 psf |
| Floor, Storage                      | = 125 psf |
| Roof                                | = 20 psf  |
| Roof, MEP Equipment Zone            | = 45 psf  |
| Stair                               | = 100 psf |
- C. Snow =  $P_g = 20$  psf,  $P_f = 14$  psf,  $I_s = 1.0$   
 $C_e = 1.0$ ,  $C_t = 1.0$ , Drift per ASCE/SEI 7-16
- D. Lateral Loads:
1. Wind  $V = 109$  mph, exposure C  
Occupancy [Risk] Category I,  $w = 1.0$   
 $G C_p = +0.18$   
Design wind pressures to be used for the design of exterior component and cladding materials on the designated zones of wall and roof surfaces shall be per section 30.7.7 and Table 30.7-2 of ASCE/SEI 7-16. Tabulated pressures shall be multiplied by effective area reduction factors, exposure adjustment factors, and topographic factors where applicable.
  2. Seismic =  $S_a = 0.101g$ ,  $S_1 = 0.069g$   
Occupancy [Risk] Category II,  $I_e = 1.0$   
Site Classification C,  $S_{ds} = 0.088g$ ,  $S_{d1} = 0.069g$   
Seismic Design Category B  
Equivalent Lateral Force Procedure  
Above Podium:  
 $A_{17} =$  Light framed walls with shear panels of all materials  
 $R = 2$ ,  $\Omega = 2.5$ ,  $C_d = 2$ ,  $V = 0.001W$   
Podium:  
 $A_2 =$  Ordinary Reinforced Concrete Shearwalls  
 $R = 4$ ,  $\Omega = 2.5$ ,  $C_d = 2.5$ ,  $V = 0.001W$
- E. This project is designed to resist the most critical effects resulting from the load combinations of section 1605.3 of the 2018 International Building Code.

3. Concrete:

- A. All concrete for foundations (grade beams, footings and piers) shall develop minimum ultimate compressive strength of 3600 psi in 28 days, but not less than 500 pounds of cement shall be used per cubic yard of concrete regardless of strengths obtained, not over 6 gallons of water per 100 pounds of cement and not over 4 inches of slump (except piers which shall have a 6" slump).
- B. All concrete for interior flat work and walls (including wall columns) shall develop minimum ultimate compressive design strength of 4000 psi in 28 days, but not less than 550 pounds of cement shall be used per cubic yard of concrete regardless of strengths obtained, not over 5.5 gallons of water per 100 pounds of cement and not over 4 inches of slump.
- C. All concrete for exterior flatwork shall have a minimum design compressive strength of 4500 psi in 28 days, with not less than 560 pounds of cement per cubic yard of concrete, not over 5 gallons of water per 100 pounds of cement, with 6% +/- 1% air entrainment, and a maximum of 4 inches of slump.
- D. All concrete for elevated decks and columns shall develop a minimum ultimate compressive design strength of 5000 psi in 28 days, but not less than 400 pounds of cement shall be used per cubic yard of concrete regardless of strength obtained, not over 5.5 gallons of water per 100 pounds of cement and not over 4 inches of slump.
- E. The preceding minimum mix requirements may have water-reducing admixtures conforming to ASTM C494 added to the mix at manufacturer's dosage rates for improved workability.
- F. The preceding minimum mix requirements may have up to 15% maximum of the cement content replaced with an approved ASTM C618 Class C fly ash, provided the total minimum cementitious content is not reduced.
- G. Combined aggregate (coarse plus fine) for all concrete shall be well graded from coarsest to finest with more than 18 percent and not less than 8 percent retained on an individual sieve, except that less than 8 percent may be retained on coarsest sieve and on No. 50 and finer sieves. Submit this gradation report with the concrete mix design shop drawings.
- H. All interior concrete slabs on grade shall be placed over 15 mil, Class A Vapor Barrier per ASTM E1745 with less than 0.01 perms, tested after mandatory conditioning. All joints shall be lapped and sealed per manufacturer's recommendations. All penetrations, as well as damaged vapor barrier material shall also be sealed per manufacturer's recommendation prior to concrete placement. Install barrier per manufacturer recommended details at all discontinuous edges (at interior columns, exterior edge of slab, etc.) to ensure terms of warranty are followed. The vapor barrier shall be placed over free-draining granular material as prescribed by the project soils report.
- I. All concrete is reinforced concrete unless specifically called out as unreinforced. Reinforce all concrete not otherwise shown with same steel as in similar sections or areas. Any details not shown shall be detailed per ACI 315 and meet requirements of ACI 318, current editions.
- J. Contractor shall verify that all concrete inserts, reinforcing and embedded items are correctly located and rigidly secured prior to concrete placement.
- K. No aluminum items shall be embedded in any concrete.

4. Reinforcing Steel:

- A. All reinforcing steel shall conform to the requirements of ASTM A615 or A706 grade 60 steel. Welded plain wire fabric shall be supplied in sheets and conform to the requirements of ASTM A185.
- B. Clear minimum coverage of concrete over reinforcing steel shall be as follows:
- |                                |        |
|--------------------------------|--------|
| Concrete placed against earth: | 3"     |
| Formed concrete against earth: | 2"     |
| Slabs:                         | 1"     |
| Beams or Columns:              | 1-1/2" |
| Other:                         | 2"     |
- C. All coverage shall be nominal bar diameter minimum.
- D. All dowels shall be the same size and spacing as adjoining main bars (splice lap 48 bar diameters or 24" minimum unless noted otherwise).
- E. At corners of all walls, beams, and grade beams supply corner bars (minimum 2'-0" in each direction or 48 bar diameters) in outside face of wall, matching size and spacing of horizontal bars. Where there are no vertical bars in outside face of wall, supply 3 - #4 vertical support bars for corner bars.
- F. Bars marked continuous and all vertical steel shall be lapped 48 bar diameters (2'-0" minimum) at splices and embedments, unless shown otherwise. Splice top bars near midspan and splice bottom bars over supports, unless noted otherwise.

- F. At all holes in concrete walls and slabs, add 2 - #5 bars (opening dimension plus 96 diameters long) at each of four sides and add 2 - #5 x 5'-0" diagonally at each of four corners of hole. Openings in 8" thick walls are reinforced similar, but with 1 - #5 instead of 2 - #5, respectively.
- G. Unless otherwise covered on architectural plans or specifications, vertical control joints in concrete wall shall be spaced at a maximum of 20'-0" on center and coordinated with the architect. Every other horizontal wall reinforcing bar shall be discontinuous at control joints except heavy top and bottom bars unless noted otherwise. Provide base seal waterstop style number 772 by Greenstreak Inc. or approved equal on dirt face side of wall at all walls below grade.
- H. Accessories shall be as specified in latest edition of the ACI Detailing Handbook and the concrete Reinforcing Steel Institute Design Handbook. Maximum accessory spacing shall be 4'-0" on center, and all accessories on exposed surfaces are to have plastic coated feet.
- I. All slabs and stairs not shown otherwise shall be 6" thick with #4 bars at 12" on center each way. All exterior porches and stoops not otherwise detailed may be constructed in any standard manner, solid or hollow, but must be reinforced with #4 bars at 12" on center each way minimum. Porches shall be dowelled to adjacent walls or grade beams with #4 bars at 12" on center, hooked or embedded 48 diameters into both members. Slope porches 1/8" per foot for drainage unless noted otherwise.
- J. Allow 2 tons of reinforcing bars #4 or larger to be used as directed in the field for special conditions by the engineer of record (labor for placing same to be included).

5. Structural Steel:

- A. All structural steel beams and columns shall be ASTM A992, grade 50 steel and all miscellaneous steel shall be ASTM A36 grade steel. Hollow Structural Sections (HSS) shall be ASTM A500, grade B. Fabrication and erection shall be in accordance with AISC 303-05 "Code of Standard Practice for Steel Buildings and Bridges" in the 13th Edition of the AISC Steel Construction Manual.
- B. All welding shall conform to the recommendations of the AWS.
- C. All exterior steel and connections, and brack relief angles shall be hot-dip galvanized.
- D. All bolts not otherwise specified shall be 3/4" diameter high strength (ASTM A325-N). All bolts shall be fully pretensioned. All beam connections shall be designed per the AISC Manual of Steel Construction "Framed Beam Connections" for the indicated reactions or at least 0.4 x beam total shear capacity,  $V_n/\Omega_m$ , shown in the maximum total uniform load tables, whichever is greater; and, shall account for eccentricity when the bolt line is more than 2" from the center of the support. All connections must be two bolt minimum. Connection design and shop drawing preparation shall be completed under the direct supervision of a professional engineer licensed in the state the project is located and shop drawings and connection calculations shall bear his seal.
- E. All anchor bolts shall be 3/4" diameter, ASTM F1554, Grade 36 unless noted otherwise. Washers of minimum size and thickness for the given anchor diameter in Table 14-2 of the AISC Steel Construction Manual shall be provided at every column anchor bolt. Washers shall have a standard size hole for the anchor bolt. At building perimeter columns and columns at braced frames washers shall be welded all around to the column base plate with 3/16" fillet weld.
- F. Handrails, guards and grab bars shall be designed to meet the requirements of the 2018 IRC. Refer to specifications for more explicit requirements. Submit structural calculations sealed by a licensed engineer in the state of the project location.

6. Foundations:

- A. The soil investigation was prepared by Terracon Consultants, Inc., and the project number is 02225084 and the telephone number is 913-492-7777.
- B. Spider findings, grade beams, and retaining walls are designed to bear on undisturbed soil or geotechnical approved structural fill capable of safely sustaining 2500 psf.
- C. Retaining structures are designed for an active lateral load of 51 pcf equivalent fluid pressure and an at-rest lateral load of 72 pcf based on geotechnical approved clay backfill.
- D. Contractor shall provide for dewatering at excavations from either surface water or seepage.
- E. All concrete in the structural portion retaining the backfill shall have attained its design strength prior to being backfilled.
- F. All basement walls shall not be backfilled until the first floor slab or wood decking is installed or the wall is temporarily braced by the contractor and the concrete has reached its design strength.
- G. Moisture content in soils beneath building foundations should not be allowed to change after footing excavations and after grading for slabs on grade are completed. If subgrade materials become desiccated or softened by water content specified for engineered fill. Do not place concrete on frozen ground.

7. Concrete Masonry Units:

- A. Concrete block used in exterior walls or load bearing walls shall meet the requirements of ASTM C90 and have a minimum net compressive strength of 2150 psi and laid up using type N mortar such that  $f_m$  equals 1500 psi. Mortar shall be volume proportion based cement mortar. Proportioning shall be completed by block measure. Any block in contact with earth shall be normal weight units, laid using type "S" mortar and grouted solid.
- B. The contractor shall provide adequate temporary bracing for all masonry walls during construction.
- C. All concrete block shall have 9 gage (or larger) horizontal joint reinforcing (ladder or truss) per architectural drawings and specifications (16" maximum vertical spacing).
- D. Cavity wall construction shall be reinforced as designed for specific concrete block used. The horizontal joint reinforcing shall be of the ladder or truss style per specification and continuous between brick and block, as prescribed by the architectural drawings.
- E. Concrete block shall be reinforced as follows in 8" walls:
1. Vertical reinforcing shall be as indicated on S0.05, on center, at each corner, at each door and window jamb, each side of control joints and in the end void of each length of wall. Lap splices for masonry vertical reinforcing shall be 48 bar diameters or 24" minimum.
  2. Horizontal reinforcing:
    - A. Horizontal joint reinforcing as noted above.
    - B. Continuous horizontal bars shall be included per section or detail in bond beam or optional running bond beam where noted. Where bond beams are continuous at corners of walls, supply corner bars matching size of horizontal bars (minimum 2'-0" or 40 bar diameters in each direction).
- F. Grout, where noted above, shall have a minimum design ultimate compressive strength of 2500 psi at 28 day test and 3/8" maximum aggregate size.
- G. Unless otherwise covered on architectural plans or specifications, vertical control joints in masonry construction shall be 3/8" wide, full height of wall. Joints shall be spaced at a maximum of 24'-0" on center and coordinated with the architect. All horizontal joint reinforcing shall be discontinuous at control joints in masonry. All All bond beam horizontal reinforcing shall be continuous through control joints.

8. Post-Installed Anchors:

- A. Post-installed anchors shall be used only where specified on the drawings unless approved in writing by the engineer of record. See drawings for anchor diameter, spacing and embedment. Performance values of the anchors shall be obtained for specified products using appropriate design procedures and/or standards as required by the governing building code. Anchors installed in concrete shall have an ICC-ES Evaluator Service Report. Special inspection is required for all post installed anchors. The contractor shall coordinate an on-site meeting with the post installed anchor manufacturer field representative to educate the construction team on the anchor installation guidelines and requirements.
- B. Mechanical anchors used in cracked and uncracked concrete shall have been tested and qualified for use in accordance with ACI 308.2 and ICC-ES AC193. All anchors shall be installed per the anchor manufacturer's written instructions.
- C. Adhesive anchors used in cracked and uncracked concrete shall have been tested and qualified for use in accordance with ICC-ES AC308. All anchors shall be installed per the anchor manufacturer's written instructions.
- D. Mechanical anchors used in solid grouted masonry shall have been tested and qualified for use in accordance with ICC-ES AC01. All anchors shall be installed per the anchor manufacturer's written instructions.
- E. Adhesive anchors used in solid grouted masonry shall have been tested and qualified for use in accordance with ICC-ES AC508. All anchors shall be installed per the anchor manufacturer's written instructions.
- F. Anchors used in hollow concrete masonry shall have been tested and qualified in accordance with ICC-ES AC106 or ICC-ES AC58 as appropriate. All anchors shall be installed per the anchor manufacturer's written instructions with appropriate screen tubes used for adhesives.

9. Timber and Wood Framing:

- A. Quality and construction of wood framing members and their fasteners for load supporting purposes not otherwise indicated on the drawings shall be in accordance with the 2018 International Building Code.
- B. All studs and top and bottom plates shall be Douglas Fir No. 2 grade or Southern yellow pine No. 2 grade, visually grade unless noted otherwise, with an allowable fiber stress in bending of 900 psi minimum and an elastic modulus of 1,400,000 psi unless noted otherwise. All joist, truss members and headers to be No. 2 grade DF (unless noted otherwise) All lumber for exterior decks and balconies shall be preservative-treated Southern yellow pine No. 2 grade, visually grade unless noted otherwise.
- C. Bridging of stud bearing walls and shear walls shall be solid, matching sheathing joints.
- D. Joist blocking and bridging shall be solid wood or cross bridging of either wood or metal straps. Spacing, in any case, shall not exceed 8'-0".
- E. Wood members and sheathing shall be fastened with number and size of fasteners not less than that set forth in Table 2304.9.1 of the 2018 International Building Code. Floor sheathing shall be APA rated tongue and groove Stud-Floor, exposure 1, glued and nailed with 10d nails or #10 screws at 6" on center to supports at edges and 12" on center field. Roof diaphragms shall be edge screwed with #10 screws at 6" on center and screwed to intermediate framing and/or blocking members with #10 screws at 12" on center unless noted on the drawings.
- F. Sill plates shall be bolted to concrete slabs with 1/2" diameter bolts at 32" on center (UNO, Re: shearwall sched.). Provide plate washers at sill plate anchors for shearwalls per shearwall sched. Plates in direct contact with concrete or masonry shall be treated lumber.
- G. All hangers, ties and connections shown are based on Simpson Strong Tie as the basis of design, provide Simpson Strong Tie or an approved equal. Joist hangers shall be equal to "LUS" for wood application and "LB" for steel weld-on application. Roof truss ties shall be equal to "H2.5A" and tie the roof truss to the top plate (provide 2" H2.5A". Diagonally across from each other when uplift load shown in truss shop submittal exceeds 545 lbs). Roof girder ties shall be equal to a "LGT2", "LGT3" or "LGT4" (ie dependent on number of piles) and tie the truss girder to the top track. Provide "H2.5A" at the top of each stud to top plate when the top track has roof truss attached.
- H. Service condition - dry with moisture content at or below 19% in service.
- I. Laminated strand lumber (LSL) shall have an allowable flexural stress (Fb) of 1,700 psi (reduced by size factor) and an elastic modulus (E) of 1,300,000 psi.
- J. Laminated veneer lumber (LVL) shall have an allowable flexural stress (Fb) of 2,600 psi (reduced by size factor) and an elastic modulus (E) of 1,900,000 psi.
- K. Parallel Strand Lumber (PSL) shall have an allowable flexural stress (Fb) of 2,300 psi (reduced by size factor) and an elastic modulus (E) of 2,000,000 psi. (E) = 2,200,000 psi for members > 18")
- L. Pre-engineered wood trusses shall be designed in accordance with the Truss Plate Institute's national design standard for metal-plate connected wood truss construction (ANSI/TPI-1 latest edition). Trusses shall be designed and manufactured by an authorized member of the Wood Truss Council of America (WTCOA). Truss design shall conform to specified codes, allowable stress increases, deflection limitations and other applicable criteria of the governing code.
- M. Shop drawings showing complete erection and fabrication details and calculations (including connections) shall be submitted to the project architect / engineer for review prior to fabrication and/or erection. Calculations shall bear the seal of a professional engineer, registered in the state of the project location. Shop drawings shall also be submitted to the local government controlling agency when requested by that agency.
- N. All trusses shall be securely braced both during erection and permanently, as indicated on the approved truss design drawings and in accordance with TPI's commentary and recommendations for handling, installing and bracing metal-plate connected wood trusses (HIB-91, booklet) and the latest edition of ANSI/TPI-1.
- O. The truss manufacturer shall supply all hardware and fasteners for joining truss members together and fastening truss members to their supports. Metal connector plates shall be manufactured by a member of the Wood Truss Council of America (WTCOA) and shall be 20 gauge minimum. Connector plates shall meet or exceed ASTM A653, grade 33, with ASTM A924 galvanized coating designation G60.
- P. Shipment, handling, and erection of trusses shall be by experienced, qualified persons and shall be performed in a manner so as not to endanger life or property. Apparent truss damage shall be reported to the truss manufacturer for evaluation prior to erection. Cutting or alteration of trusses is not permitted.
- Q. Roof Truss Design Criteria:
- |                        |  |
|------------------------|--|
| Top Chord Dead Load    | = 15 psf.  |
| Top Chord Live Load    | = 20 psf. (Plus Rooftop Equipment)   |
| Top Chord Total Load   | = 20 psf or 14 psf plus Drift  |
| Bottom Chord Dead Load | = 10 psf   |
| Bottom Chord Live Load | = 0 psf  |
| Live Load Deflection   | = L/360  |
| Total Load Deflection  | = L/300 (1" MAX)   |
| Corridor Trusses Only  | = 250 pf Point Load at any location on the top and bottom chord (no concurrent with each other or typical live load - concurrent with MEP equipment) |

- R. Floor Truss Design Criteria:
- |                        |                       |
|------------------------|-----------------------|
| Top Chord Dead Load    | = 30 psf              |
| Top Chord Live Load    | = Per General Note 5B |
| Bottom Chord Dead Load | = 10 psf              |
| Live Load Deflection   | = L/480 (1/2" MAX)    |
| Total Load Deflection  | = L/360 (3/4" MAX)    |
- S. Roof trusses shall be designed per IBC 2018 for net uplift resulting from wind loading based on component and cladding loading. Reference details 1, 2, 2A, 2B, 3, 3A, 3B, 4 and 5 on S0.20/for net uplift holdown detail and requirements.
- T. Refer to sheet S0.05 for wood shrinkage recommendations.
- U. Shrinkage bracing shall be provided by the contractor as required to keep the building and studs plumb.
- V. Structural members shall not be cut for pipes, etc., unless specifically detailed. Notching and boring of studs and top of plates shall conform to the provisions of section 2308.8.10 and 2308.9.11 of the IBC. Where top plates or sole plates are cut for pipes, install tie with minimum 0.058 inches thick and 1 1/2" inches wide shall be fastened to each plate across and to each side of the opening with not less than (6) 16d nails, in accordance section 2308.9.8 of the IBC.
- W. All fasteners for wood to wood connections and wood connectors shall be as indicated in structural drawings or manufacturer literature to achieve full capacity of connector. Submittal must show that alternative will not reduce the capacity of the connection.

10. Shop Drawing Review:

- A. Bob D. Campbell and Company, Inc. will review the General Contractor's (GC) shop drawings and related submittals (as indicated below) with respect to the ability of the detailed work, when complete, to be a properly functioning integral element of the overall structural system designed by Bob D. Campbell and Company, Inc.
- B. Prior to submittal of a shop drawing or any related material to Bob D. Campbell and Company, Inc., the GC shall:
1. Review each submission for conformance with the means, methods, techniques, sequences and operations of construction and safety precautions and programs incidental thereto, all of which are the sole responsibility of the GC.
  2. Review and approve each submission.
  3. Stamp each submission as approved.
- C. Bob D. Campbell and Company, Inc. shall assume that no submission comprises a variation unless the GC advises Bob D. Campbell and Company, Inc. with written documentation.

LEGEND:

- ..... SPAN DIRECTION OF DECK - TYPE PER SCHED ON S0.01
- ① HSS 6x6x1/4 COLUMN SIZE
- BASE PLATE MARK - SEE SCHEDULE ON SHEET S0.04
- A# BEAM OR HEADER PER SCHED ON S0.02
- A#-BU UPSET BEAM OR HEADER PER SCHED ON S0.02
- # BEARING WALL TYPE PER SCHED ON S0.02
- A SHEARWALL HOLDDOWN TYPE PER SCHED ON S0.03
- # NUMBER OF RESPECTIVE JACKING STUDS IN A STUD PACK. REFER TO DETAIL 6 ON S1.11
- # NUMBER OF WALL STUDS IN STUD PACK EQUAL TO KING & JAMB STUDS FROM HEADER ABOVE - TYP AT ALL LOCATIONS WITHIN A PILASTER
- SW# SHEARWALL TYPE PER SCHED ON S0.03

- D. Shop drawings and related material (if any) required are indicated below. Should Bob D. Campbell and Company, Inc. require more than ten (10) working days to perform the review, Bob D. Campbell and Company, Inc. shall so notify the GC.
- 1) Structural steel shop drawings including erection drawings and piece details. Include connection submittals and miscellaneous framing.
  - 2) Miscellaneous anchors shown on the structural drawings.
  - 3) Elevations of all reinforced concrete masonry walls at a scale of no smaller than 3/8"=1'-0" showing all required reinforcing.
  - 4) Grout mix designs (for CMU).
  - 5) Construction and control joint plans and/or elevations.
  - 6) Wood truss design and calculations and detailed erection and fabrication drawings.
  - 7) Wood shearwall holdown system.
- E. Bob D. Campbell and Company, Inc. shall review shop drawings and related materials with comments provided that each submission has met the above requirements. Bob D. Campbell and Company, Inc. shall return without comment unrequired material or submissions without GC approval stamp.

11. Structural Special Inspection:

- A. The structural design for this project is based on completion of special inspections during construction in accordance with section 1704 of the International Building Code. The owner shall employ one or more qualified special inspectors to provide the required special inspections.
- B. The special inspector shall furnish inspection reports to the building official, owner, architect and structural engineer, and any other designated person.
- C. All discrepancies shall be brought to the immediate attention of the contractor for correction; then, if uncorrected, to the proper design authority, building official and structural engineer.
- D. The special inspector shall submit a final signed report stating that the work requiring special inspection was, to the best of the inspector's knowledge, in conformance with the approved plans and specifications and the applicable workmanship provisions of the building code.
- E. The following inspections and tests are required with the frequency (continuous or periodic) as defined within the referenced section or standard listed below. The General Contractor shall provide notification to the inspector when items requiring inspection are ready to be inspected and provide access for those inspections.
1. Shop fabrication - structural steel per Section 1704.2.5 unless AISC certified shop
  2. Shop Fabrication - pre-engineered wood trusses per Section 1704.2.5 unless TPI certified shop
  3. Steel Construction per Section 1705.2 and the quality assurance requirements of AISC 341 Chapter J (as referenced in AISC 360)
  4. Concrete Construction per Section 1705.3 and Table 1705.3
    - a. Reinforcing Steel Placement
    - b. Reinforcing Steel Welding
    - c. Cast in Place Anchors
    - d. Post Installed Anchors
    - e. Design Mix Verification
    - f. Concrete Sampling and Testing
    - g. Concrete Placement
    - h. Concrete Curing
    - i. Formwork Shape, Location and Dimensions
  5. Masonry Construction per Section 1705.4 and the quality assurance requirements of TMS 402/ACI303/ASCE5 and TMS602/AS30.1/ASCE6 Level B
  6. Wood Lateral System (periodic)
    - a. Wood shearwalls (include sheathing, rim board and bottom plate attachments)
    - b. Portal frames
    - c. Shear wall and portal frame holdowns
    - d. Shear wall tension rod system
  7. Wood Gravity Framing and Placement (adjust frequency of random sampling where indicated as required)
    - a. Heavy timber/SCG/ulam beams and supports (periodic)
    - b. Headers and jams (random sampling)
    - c. Bearing walls (random sampling)
    - d. Connector/hardware installation (random sampling)
    - e. Floor and roof trusses (random sampling)

12. Structural Observation:

- A. The general contractor shall notify the engineer of record and allow for safe access to the appropriate items requiring structural observation.
- B. The engineer of record shall be notified such that the following items can be observed:
- a. Reinforcement at Elevated Concrete Floors/Roofs
  - b. Reinforcement is placed and 48 hours (min) before a pour
  - c. Structural Steel Framing
    - i. Erection is completed, prior to covering steel
  - c. Wood Framed Floors
    - i. Floor/Roof is erected, prior to MEP system routing
    - i. MEP routing is completed and all hardware installed - prior to insulating or sheathing.
- C. At the discretion of the engineer of record a site observation report will be issued to the general contractor and architect of record.
- D. The structural observations are performed at the discretion of the engineer of record and are not required per the IBC for this project.

13. Copyright and Disclaimer:

- A. All drawings in the structural set (S-series drawings) are the copyrighted work of Bob D. Campbell and Company, Inc. These drawings may not be photographed, traced, or copies in any manner without the written permission of Bob D. Campbell and Company, Inc. Exception: (Original) drawings may be printed for distribution to the owner, architect, and general contractor for coordination, bidding, and construction. Subcontractors may not reproduce these drawings for any purpose or in any manner.
- B. For any purpose or in any manner.
- I. Christopher A. Beverlin, P.E., registered engineer and a representative of Bob D. Campbell and Company, Inc., do hereby accept professional responsibility as required by the professional registration laws of this state for the structural design drawings consisting of S-series drawings. I hereby disclaim responsibility for all other drawings in the construction document package, they being the responsibility of other design professionals whose seals and signed statements may appear elsewhere in the construction document package.

STRUCTURAL DECK & SLAB SCHEDULE	
MARK	DESCRIPTION
FD-1	1/2" GYPCRETE ATOP 23/32" T&G APA-RATED STURDI-FLOOR, EXP 1 SHEATHING.
CD-1	SHATHING SHALL BE GLUED AND NAILED W/ 8d RING SHANK NAILS OR #10 SCREWS @ 6"o.c. @ EDGES & 12"o.c. AT FIELD.
CD-2	3" CONCRETE SLAB (4000psi) REINFORCE WITH 6x6 - W2.9xW2.9 WWF ATOP WATERPROOFING MEMBRANE (RE: ARCH.) ATOP 15/32" EXT. GRADE PLYWOOD SHEATHING SLOPE TO DRAIN PER ARCH. RE: NOTE 6 BELOW.
SOG-1	6" (MIN) CONCRETE SLAB (4,500psi, AIR-ENTRAINED) REINFORCE WITH #4 @ 12"oc LONGITUDINAL AT #4 12"oc TRANSVERSE BOTTOM. T/S LAB EL. = PER PLAN.
SOG-2	4" CONC. SLAB (4000psi) REINFORCE WITH 6x6-W2.9xW2.9 WWF ATOP 15 mil VAPOR BARRIER ATOP 6" OF 3/4" CLEAN GRANULAR LEVELING COURSE, ATOP SUITABLE SUBGRADE MAXIMUM PER GEOTECH SPECIFICATIONS. T/S LAB EL. = PER PLAN, SLOPE TO DRAIN.
SOG-3	4" CONC. SLAB (4500psi, AIR ENTRAINED) REINFORCE WITH 6x6-W2.9xW2.9 WWF ATOP 6" OF 3/4" CLEAN GRANULAR LEVELING COURSE, ATOP SUITABLE SUBGRADE MATERIAL PER GEOTECH SPECIFICATIONS. T/S LAB EL. = PER PLAN.
RD-1	19/32" APA-RATED, EXP 1 SHEATHING ATTACHED WITH #10 SCREWS @ 6"o.c. AT EDGES & 12"o.c. AT FIELD. (ATTACH WITH #8 SCREWS AT SAME SPACING AT FLAT ROOF AREAS)

- NOTES:
1. FD = FLOOR DECK TYPE
  2. CD = CONCRETE DECK TYP.
  3. SOG = SLAB-ON-GRADE TYP.
  4. RD = ROOF DECK TYP.
  5. PROVIDE 1" DEEP TOOLED CONTROL JOINT (TRANSVERSE DIRECTION) AT MID-SPAN OF SINGLE BAY BALCONY OR AT THIRD POINTS OF DOUBLE BAY BALCONY (6'-0" MAX SPACING). FILL JOINT WITH SEALANT.

CONCRETE FOOTING SCHEDULE

BRG PRESSURE (PSF):		CONCRETE (PSI):	REBAR (KSI):
2,500		3500	60
TYPE	FOOTING SIZE (FT.) THICKNESS (IN.)	QTY/SIZE OF BARS	
3	3'-0" x 3'-0" x 18"	#4 @ 6"oc EA WAY BOTTOM	
3A	3'-0" x 3'-0" x 32"	#4 @ 6"oc EA WAY TOP & BOTTOM	
3/6	3'-0" x 6'-0" x 32"	#4 @ 6"oc EA WAY TOP & BOTTOM	
4	4'-0" x 4'-0" x 18"	#4 @ 6"oc EA WAY BOTTOM	
4A	4'-0" x 4'-0" x 32"	#4 @ 6"oc EA WAY TOP & BOTTOM	
4x2	4'-0" x 2'-0" x 12"	#4 @ 6"oc EA WAY BOTTOM	
5	5'-0" x 5'-0" x 18"	#4 @ 6"oc EA WAY BOTTOM	
6	6'-0" x 6'-0" x 18"	#4 @ 6"oc EA WAY BOTTOM	

- NOTE:
1. EXTERIOR FOOTINGS OR FOOTING AT GRADE BEAM SHALL MATCH GRADE BEAM DEPTH AND BE PLACED WITH GRADE BEAM. PROVIDE SPECIFIED REBAR TOP AND BOTTOM WITH A STANDEEES TO SUPPORT MATS.
  2. OUTER FOOTINGS OR FOOTING AT GRADE BEAM SHALL BE PLACED WITH AN U.O.
  3. SPREAD FOOTINGS LOCATED AT INTERIOR SHALL BE POURED MONOLITHIC W/ THE SLAB AS A THICKENED PORTION OF SLAB UNLESS THEY HAVE A STEEL COLUMN BEARING ATOP.
  4. SPREAD FOOTINGS LOCATED AT INTERIOR WITH STEEL COLUMNS BEARING ATOP SHALL BE LOCATED AT 99'-0".

STRUCTURAL ABBREVIATIONS





































@	AT	FLR	FLOOR	PL	PLATE
&	AND	FAR	FAR SIDE	PLF	POUNDS PER LINEAR FOOT
Ø	ROUND, DIAMETER	FTG	FOOTING	PJP	PARTIAL JOINT PENETRATION
ADTL	ADDITIONAL	FV	FIELD VERIFY	PSF	POUNDS PER SQUARE FOOT
AFF	ABOVE FINISHED FLOOR	GA	GAGE	PSI	POUNDS PER SQUARE INCH
ALT	ALTERNATE	GALV	GALVANIZE(D)	QTY	QUANTITY
ARCH	ARCHITECTURAL	GEN	GENERAL	RAD	RADIUS
BLDG	BUILDING	GR	GRADE	RD-#	ROOF DECK TYPE
B/	BOTTOM OF	HORIZ	HORIZONTAL	REF	REFERENCE
BM	BEAM	HSS	HOLLOW STRUCTURAL SECTION	REINF	REINFORCEMENT
BOTT	BOTTOM	INS	INSIDE FACE	REQD	REQUIRED
BRG	BEARING	ISO	ISOLATION JOINT	REV	REVISION
C	CAMBER	INFO	INFORMATION	RL	ROOF LIFE LOAD
CD-#	CONCRETE DECK TYPE	INT	INTERIOR	RTU	ROOF TOP UNIT
CJ	CONSTRUCTION/CONTROL JOINT	JST	JOIST	SC	SLIP CRITICAL
CJP	COMPLETE JOINT PENETRATION	JT	JOINT	SCHED	SCHEDULE(D)
CL	CENTERLINE	K	KIPS (1000 LBS)	SECT	SECTION
CMU	CONCRETE MASONRY UNIT	KSF	KIPS PER SQUARE FOOT	SHT	SHEET
COL	COLUMN	KSI	KIPS PER SQUARE INCH	SIM	SIMILAR
CONC	CONCRETE	LBS, #	POUNDS	SJ	SAW JOINT
CONN	CONNECTION	Ld	DEVELOPMENT LENGTH	SL	SNOE LOAD
CONT	CONTINUOUS	LL	LIVE LOAD	SOG	SLAB-ON-GRADE
COORD	COORDINATE	LLH	LONG LEG HORIZONTAL	SOG-#	SLAB-ON-GRADE TYPE
COV, CVR	COVER	LLV	LONG LEG VERTICAL	SPCG	SPACING
COTR	COUNTER	LONG	LONGitudinal	SPEC	SPECIFICATION
DBL	DOUBLE	LSLT	LONG-SLOTTED HOLE TRANSVERSE	SPRT	SUPPORT
DET	DETAIL	LWT	LIGHTWEIGHT	SQ	SQUARE
DIA	DIAMETER	M	MOMENT FORCE	SS	STAINLESS STEEL
DIM	DIMENSION	MAX	MAXIMUM	SSLT	SHORT-SLOTTED HOLE TRANSVERSE
DL	DEAD LOAD	MECH	MECHANICAL	STD	STANDARD
DWG	DRAWING	MFR	MANUFACTURER	STIFF	STIFFENER
EA	EACH	MIN	MINIMUM	STIR	STIRRUP
EF	EACH FACE	MISC	MISCELLANEOUS	STR	STEEL
EL, ELEV	ELEVATION JOINT	MSTRY	MASONRY	STRUCT	STRUCTURAL
EMB	EMBEDMENT, EMBEDDED	MTL	METAL	SW	SHEARWALL
ENGR	ENGINEER	MTL	METAL	T/	TOP OF
EOD	EDGE OF DECK	NS	NEAR SIDE	THRU	THROUGH
EOR	ENGINEER OF RECORD	NTS	NOT TO SCALE	TOF	TOP OF FOOTING
EQ	EQUAL	NORM WT	NORMAL WEIGHT	TOS	TOP OF STEEL, TOP OF SLAB
EQU	EQUIPMENT	OC	ON CENTER	TRANS	TRANSVERSE
EW	EACH WAY	OF	OUTSIDE FACE	TYP	TYPICAL
EXP	EXPANSION	OPNG	OPENING	UNO	UNLESS NOTED OTHERWISE
EXT	EXTERIOR	OPP	OPPOSITE		SHEAR FORCE
EXTG, EXIST	EXISTING	OVHD	OVERHEAD HOLE	VERT	VERTICAL
FD-#	FLOOR DECK TYPE	P	AXIAL FORCE	W/	WITH
FDN	FOUNDATION	PAF	POWDER ACTUATED FASTENER	W/O	WITHOUT
FF	FAR FACE	PC	PRECAST	WF	WIDE FLANGE
FIN	FINISH	PCF	POUND PER CUBIC FOOT	WLD	WELD LOAD
		PEMB	PRE-ENGINEERED METAL BUILDING	WP	WORK POINT
		PERP	PERPENDICULAR	WWE	WELDED WIRE FABRIC

























## SHEARWALL SCHEDULE

SHEARWALL SCHEDULE							
SHEARWALL TYPE		FLOOR					PLATE CONNECTION (SILL TO RIM BOARD & RIM BOARD TO TOP PLATE) (RE: NOTES 6 & 7)
		BASEMENT WALLS	1st FLOOR WALLS	2nd FLOOR WALLS	3rd FLOOR WALLS	4th FLOOR WALLS	
SW1-5	MATERIAL & THICKNESS	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	3rd FLR - 20d NAILS @ 8"oc 2nd FLR - 20d NAILS @ 6"oc 1st FLR - 120d NAILS @ 4"oc
	NAIL SIZE & SPACING	8d NAILS 4/12	8d NAILS 4/12	8d NAILS 4/12	8d NAILS 6/12	8d NAILS 6/12	
	SHEAR FORCE	532 plf	532 plf	532 plf	364 plf	364 plf	
SW1-4a	MATERIAL & THICKNESS		7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	3rd FLR - 20d NAILS @ 8"oc 2nd FLR - 20d NAILS @ 6"oc
	NAIL SIZE & SPACING		8d NAILS 4/12	8d NAILS 4/12	8d NAILS 6/12	8d NAILS 6/12	
	SHEAR FORCE		532 plf	532 plf	364 plf	364 plf	
SW1-4b	MATERIAL & THICKNESS	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED		3rd FLR - 20d NAILS @ 8"oc 2nd FLR - 20d NAILS @ 6"oc 1st FLR - 120d NAILS @ 4"oc
	NAIL SIZE & SPACING	8d NAILS 4/12	8d NAILS 4/12	8d NAILS 6/12	8d NAILS 6/12		
	SHEAR FORCE	532 plf	532 plf	364 plf	364 plf		
SW1-3	MATERIAL & THICKNESS		7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED		3rd FLR - 20d NAILS @ 8"oc 2nd FLR - 20d NAILS @ 6"oc 1st FLR - 20d NAILS @ 4"oc
	NAIL SIZE & SPACING		8d NAILS 4/12	8d NAILS 6/12	8d NAILS 6/12		
	SHEAR FORCE		532 plf	364 plf	364 plf		
SW2-5	MATERIAL & THICKNESS	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING ONE SIDE, w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING ONE SIDE, w/ EDGES BLOCKED	3rd FLR - 20d NAILS @ 8"oc 2nd FLR - 20d NAILS @ 6"oc 1st FLR - 120d NAILS @ 4"oc
	NAIL SIZE & SPACING	8d NAILS 4/12	8d NAILS 4/12	8d NAILS 6/12	6d NAILS @ 4/4	6d NAILS @ 7/7	
	SHEAR FORCE	532 plf	532 plf	364 plf	175 plf	145 plf	
SW2-4	MATERIAL & THICKNESS		7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING ONE SIDE, w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING ONE SIDE, w/ EDGES BLOCKED	3rd FLR - 20d NAILS @ 8"oc 2nd FLR - 20d NAILS @ 6"oc
	NAIL SIZE & SPACING		8d NAILS 4/12	8d NAILS 6/12	6d NAILS @ 4/4	6d NAILS @ 7/7	
	SHEAR FORCE		532 plf	364 plf	175 plf	145 plf	
SW3-5	MATERIAL & THICKNESS	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING ONE SIDE, w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING ONE SIDE, w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING ONE SIDE, w/ EDGES UNBLOCKED	3rd FLR - 20d NAILS @ 8"oc 2nd FLR - 20d NAILS @ 6"oc 1st FLR - 20d NAILS @ 4"oc
	NAIL SIZE & SPACING	8d NAILS 6/12	8d NAILS 6/12	6d NAILS @ 4/4	6d NAILS @ 7/7	6d NAILS @ 7/7	
	SHEAR FORCE	364 plf	364 plf	175 plf	145 plf	115 plf	
SW3-4 SW3-3	MATERIAL & THICKNESS		7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING ONE SIDE, w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING EACH SIDE w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING EACH SIDE w/ EDGES UNBLOCKED	NO 4th FLOOR AT SW3-3
	NAIL SIZE & SPACING		8d NAILS 6/12	6d NAILS @ 4/4	6d NAILS 7/7	6d NAILS 7/7	
	SHEAR FORCE		364 plf	175 plf	145 plf	115 plf	
SW4-4	MATERIAL & THICKNESS		(2) 5/8" GYPSUM SHEATHING ONE SIDE w/ EDGES BLOCKED	(2) 5/8" GYPSUM SHEATHING ONE SIDE w/ EDGES BLOCKED	(2) 5/8" GYPSUM SHEATHING ONE SIDE w/ EDGES BLOCKED	(2) 5/8" GYPSUM SHEATHING ONE SIDE w/ EDGES BLOCKED	3rd FLR - 20d NAILS @ 8"oc 2nd FLR - 20d NAILS @ 6"oc 1st FLR - 120d NAILS @ 4"oc
	NAIL SIZE & SPACING		BASE PLY: 6d COOLER NAILS @ 9/9 FACE PLY: 8d COOLER NAIL @ 7/7	BASE PLY: 6d COOLER NAILS @ 9/9 FACE PLY: 8d COOLER NAIL @ 7/7	BASE PLY: 6d COOLER NAILS @ 9/9 FACE PLY: 8d COOLER NAIL @ 7/7	BASE PLY: 6d COOLER NAILS @ 9/9 FACE PLY: 8d COOLER NAIL @ 7/7	
	SHEAR FORCE		250 plf	250 plf	250 plf	250 plf	
SW5 SW5-1 SW5-2	MATERIAL & THICKNESS	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED	7/16" OSB SHEATHING ONE SIDE, w/ EDGES BLOCKED				SW5 @ 1ST FLOOR ONLY SW5-1 @ BSMT LEVEL ONLY SW5-2 @ BOTH LEVELS
	NAIL SIZE & SPACING	8d NAILS 6/12	8d NAILS 6/12				
	SHEAR FORCE	364 plf	364 plf				
SW6 SW6-1 SW6-2	MATERIAL & THICKNESS	5/8" GYPSUM SHEATHING ONE SIDE, w/ EDGES BLOCKED	5/8" GYPSUM SHEATHING ONE SIDE, w/ EDGES BLOCKED				SW6 @ 1ST FLOOR ONLY SW6-1 @ BSMT LEVEL ONLY SW6-2 @ BOTH LEVELS
	NAIL SIZE & SPACING	6d NAILS @ 4/4	6d NAILS @ 4/4				
	SHEAR FORCE	175 plf	175 plf				

1. NAILING SHALL BE TO ALL STUDS, TOP & BOTTOM PLATES, AND BLOCKING WHERE INDICATED. NAILS FOR GYPSUM SHEATHING ARE COOLER NAILS AND NAILS FOR OSB SHEATHING ARE COMMON NAILS. GYPSUM CAN BE ATTACHED WITH DRYWALL SCREWS AT SAME SPACING INDICATED FOR NAILS.
2. HOLDUPS PER PLAN & SCHEDULE
3. WHERE THE ENDS OF PERPENDICULAR SHEAR WALLS INTERSECT AND ONLY ON HOLDDOWN SHOWN ON PLAN, FASTEN ALL STUDS TOGETHER PER SCHEDULE AND USE LARGER OF THE TWO HOLDDOWNS SHOWN IN THE SHEARWALL SCHEDULE.
4. TO GO TO HOLDDOWN SCHEDULE FOR NUMBER OF STUDS REQ'D AT EA END OF THE SHEARWALL.
5. NAIL AND STAPLE SPACING SHOWN AS (#/IN) INDICATES FASTENERS SPACING IN INCHES AT THE EDGES/FIELD WHERE FIELD IS THE INTERMEDIATE MEMBERS.
6. TYPICAL SILL PLATE TO WOOD (RIM BOARD) AND WOOD (RIM BOARD) TO TOP PLATES SHALL BE 20d NAILS AT 12"oc UNLESS NOTED OTHERWISE IN SCHEDULE.
7. TYPICAL TOP PLATE TO CONCRETE SHALL BE 12"x96" Lx 1" SIMPSON TITEN HD ANCHORS.
  - AT 24" WALL SPACING AT 24"oc MAX WITH 1/4"x12"x1/2" PLATE WASHER OR SIMPSON BPS1/2-6 @ CONTRACTORS OPTION
  - AT 24" WALLS SPACE AT 24"oc MAX WITH 1/4"x12"x1/2" PLATE WASHER OR SIMPSON BPS1/2-6 @ CONTRACTORS OPTION
8. PLATE WASHERS TO MAINTAIN MAX OF 1/2" BETWEEN EDGE OF SILL PLATE AND EDGE OF PLATE WASHER.
9. OSB INTERIOR WALL SHEATHING BE IN ADDITION TO 5/8" GYP SHEATHING
10. SHEARWALL SHEATHING CALLED OUT AT CORRIDOR WALLS SHALL BE LOCATED AT UNIT SIDE OF WALL.


PROVIDE NAIL



HOLDOWN SCHEDULE					
MARK	FLOOR LEVEL (W/ APPLICABLE HOLDOWN TYPE PER FLOOR)				
	BASEMENT	1st FLOOR	2nd FLOOR	3rd FLOOR	4th FLOOR
(A5)	3/4"Ø STANDARD THREADED ROD w/ (6)2x4 OR (4)2x6	3/4"Ø STANDARD THREADED ROD w/ (6)2x4 OR (4)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6
(A4a)		3/4"Ø STANDARD THREADED ROD w/ (6)2x4 OR (4)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6
(A4b)	3/4"Ø STANDARD THREADED ROD w/ (6)2x4 OR (4)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	
(A3)		5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	
(B6)	1"Ø STANDARD THREADED ROD w/ (6)2x4 OR (4)2x6	1"Ø STANDARD THREADED ROD w/ (6)2x4 OR (4)2x6	3/4"Ø STANDARD THREADED ROD w/ (6)2x4 OR (4)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6
(B4)		1"Ø STANDARD THREADED ROD w/ (6)2x4 OR (4)2x6	3/4"Ø STANDARD THREADED ROD w/ (6)2x4 OR (4)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6	5/8"Ø STANDARD THREADED ROD w/ (4)2x4 OR (2)2x6
(C)		SIMPSON HDU2			
(D)	SIMPSON HDU2				
(E)	SIMPSON HDU2	SIMPSON HDU2			

NOTES:

1. HOLD-DOWN TYPES ARE BASED UPON CONTINUOUS THREADED RODS UTILIZING THE SIMPSON ATS SYSTEM.
2. 3/8" RODS SHALL HAVE A MINIMUM TENSILE CAPACITY OF 6,975 LBS.
3. 3/4" RODS SHALL HAVE A MINIMUM TENSILE CAPACITY OF 9,600 LBS.
4. 1"Ø RODS SHALL HAVE A MINIMUM TENSILE CAPACITY OF 17,080 LBS.
5. REFER TO SECTION DETAILS ON S0.03 FOR TYPICAL HOLD-DOWN DETAILS.
6. ALL HOLD-DOWN TYPES LISTED ON THE LISTED SECTION OF THREADED ROD TO MATCH STUD SIZE & GRADE NOTED IN WALL SCHEDULE. HOLD-DOWN STUDS ARE IN ADDITION TO BEARING WALL OR HEADER JAMB STUDS - PROVIDE ADDITIONAL STUDS AS REQ'D TO MEET QUANTITY NOTED IN SCHED. OFFSET STUD PACK 3" TYPICAL FROM CENTERLINE OF THREADED ROD. PROVIDE SQUASH BLOCKS WITHING FLOOR PLATE DEPTH (TRUSS DEPTH) ALIGNED WITH STUD PAKS. QUANTITY OF SQUASH BLOCK TO MATCH QUANTITY OF STUDS BELOW.
7. PROVIDE SIMPSON ANCHORS WELDING TO STEEL WIDE FLANGE POURING CONCRETE.
8. PROVIDE PLATE WASHER AND NUT CAPABLE OF DEVELOPING CAPACITY OF ROD AT EACH FLOOR.
9. PROVIDE TAKE-UP DEVICE AT EACH FLOOR CAPABLE OF ACCOMMODATING THE SHRINKAGE INDICATED IN DETAIL 1/S0.21
10. PROVIDE COUPLING TAKE-UP DEVICE AS REQUIRED.
11. PROVIDE DISCRETE DOWNING LOCATIONS OFF ALL HOLD-DOWNS AND HARDWARE FOR REVIEW BY THE EOR PRIOR TO INSTALLATION.
12. THE HOLE THRU THE TOP AND SILL PLATES SHALL BE EQUAL TO THE ROD DIAMETER PLUS 1/4".



### TYPICAL SINGLE ATS ROD AT DOUBLE SHEARWALLS

# 14 SECTION PERMIT SET

## A NEW DEVELOPMENT:

**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO

**NSPJ**  
**ARCHITECTS**<sup>SM</sup>  
3315 W. 75TH ST., SUITE 201  
PRAIRIE VILLAGE, KS 66208  
P. 913.831.1563  
F. 913.831.1563  
NSPJARCH.COM  
© COPYRIGHT 2022




DRAWING RELIANCE

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.



# S0.03






COLUMN BASE PLATE SCHEDULE					
TYPE	COLUMN	BASE PLATE (xByxN)	SHAPE	ANCHOR BOLTS	EMBEDMENT
1	PER PLAN	3/4"x11"x11"	A	4- 3/4" DIA.	12"
2	PER PLAN	3/4"x12"x12"	A	4- 3/4" DIA.	12"
NOTES:					
1. SEE PLAN FOR ORIENTATION OF COLUMNS.					
2. PROVIDE PLATE WASHER & EMBEDDED PLATE PER SCHEDULE @ ALL ANCHOR BOLTS.					
3. U.N.O. ALL THREADED ROD A.B's SHALL BE F1554 (36ksi) MATERIAL.					

COLUMN BASE PLATE ANCHOR-ROD CRITERIA				
ANCHOR-ROD DIAMETER.	MAX. HOLE DIAMETER.	MIN. WASHER SIZE.	MIN. WASHER THICKNESS	EMBEDDED ANCHOR PLATE SIZE
3/4"	1 5/16"	2"	1/4"	1/2"x2 1/2"x2 1/2"



1 TYPICAL ANCHOR BOLT

1 1/2" = 1'-0"



A NEW DEVELOPMENT:

RESIDENCES AT BLACKWELL

50 Highway & Blackwell, Lee's Summit, MO



**\$0.05**



SLAB NOTES

1.

SEE GENERAL NOTES (STRUCTURAL) ON SHEET S0.01.

2.

PODIUM SLAB IS 12" THICK AND REINFORCED WITH A CONTINUOUS (12" LAP AT COLUMN CENTERLINE OF COLUMN STRIPS AND 24" LAP AT COLUMN CENTERLINE OF MID-STRIPS) BOTTOM MAT OF #5 @ 12" EACH WAY. THE BOTTOM MAT EXTENDING NORTH-SOUTH (PLAN EAST-WEST) SHALL BE SUPPORTED ON 1" SLAB BOLSTERS @ 4'-0"oc MAX. TOP OF CONCRETE ELEVATION PER PLAN (STEP TOP OF SLAB AND SLOPE AS INDICATED AT EXTERIOR LOCATIONS.) EXTRA REINFORCING BARS PLACING SEQUENCE:

3.

14

A5

19'-9"

TOTAL LENGTH OF BAR IN FEET AND INCHES

SIZE OF BAR AND LOCATION IN SLAB AS NOTED BELOW

TOTAL NUMBER OF EXTRA BARS IN STRIP DEFINED ON PLAN

A. #5 EXTRA BOTTOM BARS WITH 1" CLEAR COVER BOTTOM. (PLACE WITH 1" CLEAR COVER BOTTOM MAT BARS.)

B. #5 EXTRA BOTTOM BARS WITH 1 5/8" CLEAR COVER BOTTOM. (PLACE WITH 1 5/8" CLEAR COVER BOTTOM MAT BARS.) PLACE ON TOP OF PERPENDICULAR (1" CLEAR COVER) BOTTOM MAT AND 7A" BARS.

C. #5 TOP BARS WITH 1 5/8" CLEAR COVER WHERE TWO LAYERS OF BARS OCCUR AND 1" CLEAR COVER WHERE ONE LAYER OF BARS OCCUR ON IHC @4'-0" o.c. AND #5 SUPPORT BARS @4'-0"o.c.

D. #5 TOP BARS WITH 1" CLEAR COVER TOP. PLACE ON TOP OF "C" BARS WHERE THEY OCCUR OR OTHERWISE PLACE ON IHC AT 4'-0"o.c. AND #5 SUPPORT BARS AT 4'-0" o.c.

E. #5 TOP BARS WITH 1" CLEAR COVER TOP. PLACE ON IHC AT 4'-0"o.c. AND #5 SUPPORT BARS AT 4'-0"o.c.

4.

REINFORCING SHALL BE SPAYED AROUND OPENINGS LESS THAN 18" WIDE. REINFORCING SHALL BE CUT AT OPENINGS GREATER THAN 18" WIDE WITH EQUAL CONTINUOUS BARS ADDED ONE-HALF EACH SIDE OF OPENING. PROVIDE REINFORCING PER GENERAL NOTE 4F AT ALL OPENINGS LAGER THAN 8".

5.

STRIP LINES ARE LOCATED AT 1/4 POINTS BETWEEN COLUMN CENTERLINES UNLESS NOTED ON PLAN OTHERWISE.

6.

SEE DETAIL 2/S3.10 FOR PLACING PATTERN FOR TOP REINFORCING BARS OVER INTERIOR COLUMN AS NOTED.

7.

TOP BARS SHOWN STAGGERED ON PLAN SHALL BE STAGGERED WHEN PLACED. THE END OF EVERY OTHER BAR TO BE PLACED AT RELATIVE STRIP LINE. UNLESS NOTED ON PLAN.

8.

BOTTOM BARS ARE SHOWN THUS 

-----

 TOP BARS ARE SHOWN THUS 

=====

 TOP BARS SHOWN ON PLAN THUS 

=====

 SHALL HAVE A STANDARD ACI 90 DEG. HOOK.

9.

UNLESS SHOWN ON "S" SERIES DRAWINGS, NO HOLES LARGER THAN TEN INCH DIAMETER SHALL BE PLACED THROUGH SLAB. NOT MORE THAN ONE, SIX TO EIGHT INCH DIAMETER HOLES, OR TWO FOUR INCH DIAMETER HOLES, OR THREE TWO INCH DIAMETER OR SMALLER HOLES SHALL BE PLACE WITHIN 20"OF THE FACE OF THE COLUMNS. CAMBER ALL SPANS BETWEEN 16'-0" AND 24'-0" (CENTERLINE TO CENTERLINE OF SUPPORTS) FOR L/600 MINIMUM AT MIDSPAN (WITH L = SPAN IN INCHES) (I.E., 3/8 AT MIDSPAN FOR 18'-0" SPAN. CAMBER ALL SPANS LONGER THAN 24'-0" FOR L/480 (I.E., 3/4" AT MIDSPAN FOR 30'-0" SPAN.) DO NOT CAMBER SLAB IN COURTYARD AREA WHEN DRAIN IS LOCATED AT CENTER OF SPAN.

11.

AT TERMINATION OF COLUMN STRIP AT COLUMN, WALL, BEAM, PROVIDE 90 DEGREE STANDARD ACI HOOKED END AT (4) BOTTOM BARS NEAREST COLUMN CENTERLINE PER 6/S3.10
- | REBAR DEVELOPMENT LENGTH AND LAP SPLICE SCHEDULE |                                   |            |             |            |                              |                                   |            |             |            |                              |                                   |            |             |            |
|--|-----------------------------------|------------|-------------|------------|------------------------------|-----------------------------------|------------|-------------|------------|------------------------------|-----------------------------------|------------|-------------|------------|
| CONCRETE STRENGTH = 5000 psi                     |                                   |            |             |            | CONCRETE STRENGTH = 4000 psi |                                   |            |             |            | CONCRETE STRENGTH = 3500 psi |                                   |            |             |            |
| CASE<br><br>BAR SIZE                             | DEVELOPMENT LENGTH OR CLASS A LAP |            | CLASS B LAP |            | CASE<br><br>BAR SIZE         | DEVELOPMENT LENGTH OR CLASS A LAP |            | CLASS B LAP |            | CASE<br><br>BAR SIZE         | DEVELOPMENT LENGTH OR CLASS A LAP |            | CLASS B LAP |            |
|  | TOP BARS                          | OTHER BARS | TOP BARS    | OTHER BARS |                              | TOP BARS                          | OTHER BARS | TOP BARS    | OTHER BARS |                              | TOP BARS                          | OTHER BARS | TOP BARS    | OTHER BARS |
| #3   | 24                                | 24         | 24          | 24         | #3                           | 24                                | 24         | 24          | 24         | #3                           | 24                                | 24         | 26          | 24         |
| #4   | 24                                | 24         | 29          | 24         | #4                           | 25                                | 24         | 33          | 25         | #4                           | 27                                | 24         | 35          | 27         |
| #5   | 28                                | 24         | 36          | 28         | #5                           | 31                                | 24         | 41          | 31         | #5                           | 33                                | 26         | 43          | 33         |
| #6   | 34                                | 26         | 43          | 34         | #6                           | 37                                | 29         | 49          | 37         | #6                           | 40                                | 31         | 52          | 40         |
| #7   | 49                                | 38         | 63          | 49         | #7                           | 54                                | 42         | 71          | 54         | #7                           | 58                                | 45         | 75          | 58         |
| #8   | 56                                | 43         | 72          | 56         | #8                           | 62                                | 48         | 81          | 62         | #8                           | 66                                | 51         | 86          | 66         |
| #9   | 63                                | 48         | 81          | 63         | #9                           | 70                                | 54         | 91          | 70         | #9                           | 75                                | 58         | 97          | 75         |
| #10  | 71                                | 54         | 92          | 70         | #10                          | 79                                | 61         | 102         | 79         | #10                          | 84                                | 65         | 109         | 84         |
| #11  | 78                                | 60         | 102         | 78         | #11                          | 87                                | 67         | 113         | 87         | #11                          | 93                                | 72         | 121         | 93         |
- NOTES:

1.

UNLESS SPECIFICALLY INDICATED OTHERWISE, USE THE MINIMUM LENGTH FOR A CLASS B LAP SPLICE OR THE MINIMUM DEVELOPMENT LENGTH INDICATED IN THE TABLES ABOVE MULTIPLIED BY THE APPLICABLE FACTOR(S) LISTED BELOW.

2.

WHERE THE CLEAR SPACING BETWEEN BARS LAP SPICED OR EMBEDDED AT ANY SECTION IS LESS THAN 2 BAR DIAMETERS, OR WHERE THE BAR COVER IS LESS THAN OR EQUAL TO THE BAR DIAMETER. INCREASE THE INDICATED BAR SPLICE OR DEVELOPMENT LENGTH BY 50%.

3.

TOP BARS ARE HORIZONTAL BARS WITH MORE THAN 12 INCHES OF CONCRETE CAST BELOW THE BARS.

4.

MECHANICAL COUPLERS MAY BE SUBSTITUTED FOR TENSION LAP SPICED BARS PROVIDED THAT THEY MEET THE REQUIREMENTS OF ACI 318-11, 12.14.

5.

AT LOCATIONS WHERE REINFORCING WITHIN A STRUCTURAL ELEMENT WILL BE SPICED, ALTERNATING SPLICES SHALL BE STAGGERED A MINIMUM OF THE CLASS B SPLICE LENGTH UNLESS INDICATED OTHERWISE.
- | CONCRETE COLUMN SCHEDULE |  |
|--------------------------|--|
| COLUMN SIZE              | REINFORCEMENT                          |
| 18x18                    | (8) #8 VERTICAL<br>(2) #3 TIES @ 12"oc |
- NOTES:

1)

PROVIDE (4) SETS OF TIES AT 3"oc TOP & BOTTOM OF EACH COLUMN

2)

ALL COLUMNS TO CENTER ON GRIDLINE AND PIER/FOUNDATION U.N.O.
- 
- 18"x18"  
COLUMN
- 1 COLUMN DETAILS  
3/4" = 1'-0"
- A NEW DEVELOPMENT:
- RESIDENCES AT BLACKWELL  
50 Highway & Blackwell, Lee's Summit, MO
- 
- DRAWING RELEASE LOG
- REVISIONS:
- DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.
- PERMIT SET
- S0.10
- ARCHITECTURE  
LANDSCAPE  
ARCHITECTURE  
ENERGY SERVICES  
P. 913.831.1415  
F. 913.831.1563  
NSPJARCH.COM  
© COPYRIGHT 2023
- 
-








3/4" = 1'-0"

**$\frac{3}{4}" = 1'-0"$**


# S0.21









ARCHD 24" x 36" 4/5/2023 11:36:50 AM NSPJ ARCHITECTS © L:\N\NSPJ\Projects\NSPJ-2217 - Blackwell Apartments\NSPJ-2217 Dwg\NSPJ-2217 - SZ2 - Blackwell\_JLF.rvt




**1 STAIR 1 LOWER LEVEL FRAMING PLAN**  
3/8" = 1'-0"




**2 STAIR 1 1ST FLOOR FRAMING PLAN**  
3/8" = 1'-0"



**3 STAIR 1 2ND FLOOR FRAMING PLAN**  
3/8" = 1'-0"



**4 STAIR 1 3RD FLOOR FRAMING PLAN**  
3/8" = 1'-0"



**5 STAIR 1 4TH FLOOR FRAMING PLAN**  
3/8" = 1'-0"

ARCHITECTURE  
LANDSCAPE  
ARCHITECTURE  
ENERGY SERVICES  
P. 913.831.1415  
F. 913.831.1563  
NSPJARCH.COM  
© COPYRIGHT 2023



A NEW DEVELOPMENT:  
**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO

DRAWING RELEASE LOG


REVISIONS:  
1 4/5/2023 Addendum 1

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.


PERMIT SET

**\$1.00**







**1 STAIR 2 & ELEVATOR LOWER LEVEL FRAMING PLAN**  
3/8" = 1'-0"



**2 STAIR 2 & ELEVATOR 1ST FLOOR FRAMING PLAN**  
3/8" = 1'-0"



**3 ELEVATOR 2ND/3RD/4TH FLOOR FRAMING PLAN**  
3/8" = 1'-0"




**4 ELEVATOR ROOF FRAMING PLAN**  
3/8" = 1'-0"












# 1 SECTION




## 2 SECTION




### 3 SECTION




## 4 SECTION




## 5 SECTION



## 5A SECTION



## 6 SECTION




TYPICAL ELEVATOR RAIL BRACKET  
SUPPORT BELOW TOP MOST LANDING

## 7 SECTION











DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

**S1.21**







# 1 SECTION




## 2 SECTION




### 3 SECTION




### 3A SECTION




## 4 SECTION




## 5 SECTION



## 6 SECTION



## 7 SECTION




## 7A SECTION

## PERMIT SET

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

**\$1.30**



**A NEW DEVELOPMENT:**  
**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO

 DRAWING RELEASE LOG

△ REVISIONS:





**A NEW DEVELOPMENT:  
RESIDENCES AT BLACKWELL  
50 Highway & Blackwell, Lee's Summit, MO**




DRAWING RELEASE LOG

△ REVISIONS:  
1 4/05/2023 Addendum 1

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.


# PERMIT SET

**\$2.00**



## **1 LOWER LEVEL FOUNDATION PLAN**

- 1) REFER TO GENERAL NOTES ON SHEET \$0.01.
- 2) REFER TO CIVIL AND ARCH DRAWING FOR SLAB ELEVATIONS.
- 3) ELEVATION 100'-0" VARIES PER BUILDING - RE: CIVIL.
- 4) TOP OF FOOTING ELEVATIONS PER PLAN.
- 5) REFER TO FOOTING SCHEDULE ON \$0.10.
- 6) REFER TO ARCH AND MECH DRAWINGS FOR LOCATIONS OF SPOT AND TRENCH DRAINS.
- 7) REFER TO CONCRETE COLUMN SCHEDULE ON \$0.10.
- 8) REFER TO \$3.00 SERIES DRAWINGS FOR TYPICAL FOUNDATION DETAILS.
- 9) PROVIDE POCKET AT TOP OF FOUNDATION WALL TO RECEIVE GRADE BEAM ABOVE PER 15/53.00



## **2 LOWER LEVEL FOUNDATION PLAN**

$$3/32'' = 1'-0''$$






 DRAWING RELEASE LOG

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

# S2.01



### 3 1ST FLOOR FOUNDATION PLAN



$$3/32'' = 1'-0''$$

- 3) ELEVATION 100.0 - VARIOUS PER BUILDING - REL. CIVIL.
- 4) TOP OF FOOTING ELEVATIONS PER PLAN.
- 5) REFER TO FOOTING SCHEDULE ON S0.10.
- 6) REFER TO ARCH AND MECH DRAWINGS FOR LOCATIONS OF SPOT AND TRENCH DRAINS
- 7) REFER TO CONCRETE COLUMN SCHEDULE ON S0.10.
- 8) REFER TO S3.00 SERIES DRAWINGS FOR TYPICAL FOUNDATION DETAILS.
- 9) PROVIDE POCKET AT TOP OF FOUNDATION WALL TO RECEIVE GRADE BEAM ABOVE PER

- 1) REFER TO GENERAL NOTES ON SHEET S0.01
- 2) REFER TO STUD BEARING WALL SCHEDULE TO SHEET S0.02
- 3) REFER TO HEADER/BEAM SCHEDULE ON SHEET S0.02
- 4) REFER TO SHEARWALL SCHEDULE ON SHEET S0.03
- 5) REFER TO STAIR FRAMING PLANS ON SHEET S2.00
- 6) REFER TO BALCONY FRAMING PLANS ON SHEET S1.20
- 7) REFER TO S3.30-SERIES DRAWINGS FOR ADDITIONAL FLOOR FRAMING DETAILS NOT INDICATED HEREIN
- 8) PROVIDE TRUSS SPACE DIRECTLY ABOVE AND CENTERED OVER HVAC CLOSETS; REFER TO ARCH & ME DRAWING FOR DUCT LOCATIONS
- 9)   - STORAGE AREA: DESIGN FOR LL PER GENERAL NOTE 2.B ON S0.01
- 10) TOP OF STEEL ELEVATION FOR STEEL BEARING ON WOOD MEMBERS SHALL BE FIELD COORDINATED BY THE CONTRACTOR & ARCHITECTURAL ROUGH OPENING SCHEDULE.

- 1) REFER TO GENERAL NOTES ON SHEET S0.01.
- 2) REFER TO CIVIL AND ARCH DRAWINGS FOR SLAB ELEVATIONS.
- 3) REFER TO ARCH AND MEP DRAWINGS FOR LOCATIONS OF SPOT AND TRENCH DRAINS.
- 4) REFER TO CONCRETE COLUMN SCHEDULE ON S0.10.
- 5) REFER TO STRUCTURAL SLAB (PODIUM SLAB) NOTES ON S0.10.
- 6) ELEVATIONS AND SLAB STEPS INDICATED OCCUR IN THE STRUCTURAL SLAB. REFER TO S0.10 FOR SLOPE.
- 7) ALL ADDITIONAL REINFORCEMENT (PER PLAN) SHALL PROJECT TO OPPOSITE FACE OR STRIP LAP WITH SAME SIZE BAR.





## 2 2ND FLOOR FRAMING PLAN

## 1 2ND FLOOR FRAMING PLAN


$$3/32'' = 1'-0''$$

WOOD FLOOR FRAMING NOTES:

- 1) REFER TO GENERAL NOTES ON SHEET S0.01
- 2) REFER TO STUD BEARING WALL SCHEDULE TO SHEET S0.02
- 3) REFER TO HEADER/BEAM SCHEDULE ON SHEET S0.02
- 4) REFER TO SHEARWALL SCHEDULE ON SHEET S0.03
- 5) REFER TO STAIR FRAMING PLANS ON SHEET S2.02
- 6) REFER TO BALCONY FRAMING PLANS ON SHEET S1.20
- 7) REFER TO S3.30-SERIES DRAWINGS FOR ADDITIONAL FLOOR FRAMING DETAILS NOT INDICATED HERE
- 8) PROVIDE TRUSS SPACE DIRECTLY ABOVE AND CENTERED OVER HVAC CLOSETS; REFER TO ARCH & ENG DRAWINGS FOR EXACT LOCATIONS
- 9) **STORAGE AREA DESIGN FOR LL PER GENERAL NOTE 2.B ON S0.01**
- 10) **TOP OF STEEL ELEVATION FOR STEEL BEARING ON WOOD MEMBERS SHALL BE FIELD COORDINATED BY THE CONTRACTOR & ARCHITECTURAL ROUGH OPENING SCHEDULE.**



**ARCHITECTS<sup>PA</sup>**  
33515 W. 75TH ST., SUITE 201  
PRAIRIE VILLAGE. KS 66208



## A NEW DEVELOPMENT:

**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO

50 Highway & Blackwell, Lee's Summit, MO



DRAWING RELEASE LOG


△ REVISIONS:  
1 4/05/2023 Addend

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

## PERMIT SET

# S2.02





## A NEW DEVELOPMENT:

**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO




DRAWING RELEASE LOG

△ REVISIONS:

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

# PERMIT SET

## S2.03



# 1 3RD FLOOR FRAMING PLAN

$$3/32'' = 1'-0''$$

WOOD FLOOR FRAMING NOTES:


- 1) REFER TO GENERAL NOTES ON SHEET S0.01
- 2) REFER TO STUD BEARING WALL SCHEDULE TO SHEET S0.02
- 3) REFER TO HEADER/BEAM SCHEDULE ON SHEET S0.02
- 4) REFER TO SHEARWALL SCHEDULE ON SHEET S0.03
- 5) REFER TO STAIR FRAMING PLANS ON SHEET S2.00
- 6) REFER TO BALCONY FRAMING PLANS ON SHEET S1.20
- 7) REFER TO S3.30-SERIES DRAWINGS FOR ADDITIONAL FLOOR FRAMING DETAILS NOT INDICATED HERE
- 8) PROVIDE TRUSS SPACE DIRECTLY ABOVE AND CENTERED OVER HVAC CLOSETS. REFER TO ARCH & MECH DRAWINGS FOR EXACT LOCATION
- 9) **STORAGE AREA DESIGN FOR LL PER GENERAL NOTE 2.B ON S0.01**
- 10) TOP OF STEEL ELEVATION FOR STEEL BEARING ON WOOD MEMBERS SHALL BE FIELD COORDINATED BY THE CONTRACTOR & ARCHITECTURAL ROUGH OPENING SCHEDULE.



 DRAWING RELEASE LOG

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

## S2.04








△ REVISIONS:  
1 4/05/2023 Addendum 1

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.


**S2.05**




# PERMIT SET

$$3/32'' = 1'-0''$$


## WOOD ROOF FRAMING NOTES

- 1) REFER TO GENERAL NOTES ON SHEET S0.01
- 2) REFER TO STUD BEARING WALL SCHEDULE TO SHEET S0.02
- 3) REFER TO HEADER/BEAM SCHEDULE ON SHEET S0.02
- 4) REFER TO SHEARWALL SCHEDULE ON SHEET S0.03
- 5) PROVIDE (3) STUD (MINIMUM) ALIGNED UNDER EACH END OF GIRDER TRUSS (CONTINUOUS FOUNDATION) - FINAL QUANTITY TO MATCH NUMBER OF FLIES OF GIRDER TRUSS. PROVIDE SIMPSON LSTA-STYLE HOLDOWN AT EACH END OF GIRDER TRUSS.
- 6) REFER TO S0.40-SERIES DRAWINGS FOR ADDITIONAL ROOF FRAMING DETAILS NOT INDICATED HERE.
- 7) PROVIDE UPRIGHT UPLIFT SCREWS AT UPPER FLOOR PER DETAILS 2, 2A, 3, 3A, 3B, 4 AND 5 ON SHEET S0.20.
- 8) PRE-ENGINEERED TRUSSES TO HAVE A MINIMUM DEPTH OF 24". SLOPE TOP CHORD PER ARCHITECTURAL DRAWINGS.
- 9)  INDICATES AREA ON ROOF THAT IS REQ'D TO BE DESIGNED FOR MEP EQUIPMENT ZONE PER GENERAL NOTE "2.B" ON SHEET S0.01
- 10) TOP OF SILL ELEVATION OF STEEL BEARING ON WOOD MEMBERS SHALL BE FIELD COORDINATED BY THE CONTRACTOR & ARCHITECTURAL ROUGH OPENING SCHEDULE.
- 11) PRE-ENG TRUSSES TO HAVE SLOPING TOP CHORD WITH MINIMUM TRUSS DEPTH OF 24".










**1 CLUBHOUSE FOUNDATION PLAN**

- FOUNDATION NOTES:
- 1) REFER TO GENERAL NOTES ON SHEET S0.01.
  - 2) REFER TO CIVIL AND ARCH DRAWING FOR SLAB ELEVATIONS.
  - 3) ELEVATION 100'-0" VARIES PER BUILDING - RE: CIVIL.
  - 4) TOP OF FOOTING ELEVATIONS PER PLAN.
  - 5) REFER TO FOOTING SCHEDULE ON S0.10.
  - 6) REFER TO ARCH AND MECH DRAWINGS FOR LOCATIONS OF SPOT AND TRENCH DRAINS.
  - 7) REFER TO CONCRETE COLUMN SCHEDULE ON S0.10.
  - 8) REFER TO S3.00 SERIES DRAWINGS FOR TYPICAL FOUNDATION DETAILS.
  - 9) PROVIDE POCKET AT TOP OF FOUNDATION WALL TO RECEIVE GRADE BEAM ABOVE PER 15/S3.00



A NEW DEVELOPMENT:  
**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO

DRAWING RELEASE LOG

REVISIONS:  
1 4/5/2023 Addendum 1

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

PERMIT SET


**S2.10**



CLUBHOUSE PLAN NOTES	
A	18" DEEP PRE-ENGINEERED FLOOR TRUSSES @ 24"oc MAX
A1	18" DEEP PRE-ENGINEERED FLOOR TRUSSES @ 16"oc MAX
A2	24" DEEP PRE-ENGINEERED ROOF TRUSSES @ 24"oc MAX (SLOPE TOP CHORD PER ARCH)
B1	2x12 @ 16"oc JOISTS
B2	(2) 2x12 @ 12"oc JOISTS
C1	2x10 @ 24"oc JOISTS
C2	(2) 2x10 @ 16"oc JOISTS
C3	(2) 2x10 @ 12"oc JOISTS
C4	2x10 @ 24"oc JOISTS OVERBUILD ABOVE
D	STAIR STRINGERS PER 1/S1.10
E	8x8 WOOD COLUMN ATOP SIMPSON ABU88Z W/ (2) 5/8"Øx6"Lg SIMPSON TITEN HD SCREW ANCHORS
E1	(3) 2x10 CONT W/ XX POST CAP @ EA COLUMN
E2	(3) 2x8 CONT W/ XX POST CAP @ COLUMN & HUC26-3 HANGER FACEMOUNTED TO SHEATHING W/ (3) 2x6 KING STUDS ALIGNED W/ BEAM
F	STEEL BUCKET PER 4/S3.20
G1	2x8 JOISTS @ 16"oc. TAPER JOIST PER 4/S3.42 W/ SLOPE PER ARCH
G2	2x6 JOISTS @ 16"oc. TAPER JOIST PER 1/S3.44
H1	HUCQ612-SDS HANGER
J	UPSET (3) 1 3/4"x11 1/4" BEAM. PROVIDE CONTINUOUS BLOCKING FOR EXTENTS OF EXTERIOR WALL ABOVE BTWN T/BEAM AND B/DECK.
K	(4) 2x8 HIGH & LOW w/ (2) TOP PL & 2x8 BOTT PL w/ 1 JACK / 3 KING EA END w/ (4) 2x8 JACKS AT INTERIOR JAMBS. AT LOW HEADER INTERIOR JAMBS TO HAVE OUTER PLIES INTERRUPTED.

CLUBHOUSE HEADERS/BEAMS SCHEDULE			
MARK	HEADER	JAMB TYPE #	NOTES
D1	(3) 2x8	1 JACK / 1 KING	
D2	(3) 2x8	1 JACK / 2 KING	
E1	(3) 2x10	1 JACK / 1 KING	
E2	(3) 2x10	1 JACK / 2 KING	
F1	(3) 2x12	1 JACK / 2 KING	
F2	(3) 2x12	2 JACK / 2 KING	
J1	(3) 1 3/4"x7 1/8" LVL	2 JACK / 2 KING	
N1	(3) 1 3/4"x11 1/4" LVL		
Q1	(3) 1 3/4"x14" LVL		HGU5.50-SDS (H=14") HANGER @ BEAM CONNECTION
S1	(3) 1 3/4"x16" LVL	3 KING	
T1	(2) 1 3/4"x18" LVL	3 KING	
U1	(3) 1 3/4"x18" LVL	3 KING	
V1	(4) 1 3/4"x18" LVL	3 KING	
X1	(5) 1 3/4"x18" LVL	4 KING @ WALL / SIMPSON EG9 HANGER TO Y1 BEAM	ATTACH PLIES TOGETHER w/ 3 ROWS OF 1/4"x8" SDS SCREWS @ 12"oc FROM EA SIDE - MATCH EDGE DISTANCE PER 5A/S0.02
Y1	(3) 1 3/4"x24" LVL	4 KING	

- NOTES:
- JAMB STUDS SHALL MATCH SIZE & GRADE OF WALL STUDS U.N.O.
  - WHERE BEAM IS NOTED "U", ALL JAMB STUDS NOTED WILL EXTEND TO DOUBLE TOP PLATE.
  - ALL EXTERIOR LUMBER TO BE TREATED AGAINST MOISTURE. REFER TO NOTE 12.T ON SHEET S0.01 FOR FIRE RETARDANT TREATED HEADER AND STUD REQUIREMENTS.
  - PROVIDE SQUASH BLOCKS AT TRUSSES & BLOCKING FRAMING WHERE JAMBS OR STUD PACKS ARE DISCONT AND IN TRUSS CAVITY. QUANTITY TO MATCH JAMB OR STUD PACK ABOVE.
  - PROVIDE 1/2" PLYWOOD SPACER PLATES AT INTERIOR HEADERS CONSTRUCTED WITH 2x LUMBER.
  - AT CONTRACTOR'S OPTION, PROVIDE GLULAM IN LIEU OF PSL OF EQUAL OR GREATER STRENGTH.
  - REFER TO DETAIL 4/S0.02 FOR MULTI-PLY MEMBER CONNECTION REQUIREMENTS.
  - ATTACH JAMB & KING STUDS TOGETHER PER CONNECTION TYPE 24 ON NAILING SCHEDULE ON S0.01.



# 1 CLUBHOUSE 1ST FLOOR FRAMING PLAN

- WOOD FLOOR FRAMING NOTES:
- REFER TO GENERAL NOTES ON SHEET S0.01
  - REFER TO STUD BEARING WALL SCHEDULE TO SHEET S0.02
  - REFER TO HEADER/BREAM SCHEDULE ON SHEET S0.02
  - REFER TO SHEARWALL SCHEDULE ON SHEET S0.03
  - REFER TO STAIR FRAMING PLANS ON SHEET S2.00
  - REFER TO BALCONY FRAMING PLANS ON SHEET S1.20
  - REFER TO S3.30-SERIES DRAWINGS FOR ADDITIONAL FLOOR FRAMING DETAILS NOT INDICATED HERE
  - PROVIDE TRUSS SPACE DIRECTLY ABOVE AND CENTERED OVER HVAC CLOSETS; REFER TO ARCH & MEP DRAWINGS FOR EXACT LOCATIONS
  - STORAGE AREA: DESIGN FOR LL PER GENERAL NOTE 2.B ON S0.01
  - TOP OF STEEL ELEVATION FOR STEEL BEARING ON WOOD MEMBERS SHALL BE FIELD COORDINATED BY THE CONTRACTOR & ARCHITECTURAL ROUGH OPENING SCHEDULE.

PERMIT SET

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

S2.11

ARCHITECTURE  
LANDSCAPE  
ARCHITECTURE  
ENERGY SERVICES  
P. 913.831.1415  
F. 913.831.1563  
NSPJARCH.COM  
© COPYRIGHT 2023



A NEW DEVELOPMENT:  
**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO

DRAWING RELEASE LOG

REVISIONS:  
1 4/05/2023 Addendum 1



ARCH D 24" x 36"

U:\N\F\NSPJ\Projects\NSPJ\2217 - Blackwell Apartments\NSPJ\2217 Dwg\NSPJ\2217 - S22 - Blackwell\_JLF.rvt

4/5/2023 11:37:47 AM NSPJ ARCHITECTS ©

ARCHITECTURE  
LANDSCAPE  
ARCHITECTURE  
ENERGY SERVICES

NSPJ ARCHITECTS<sup>SM</sup>

3515 W. 75TH ST., SUITE 201  
PRAIRIE VILLAGE, KS 66208

P. 913.831.1415  
F. 913.831.1563  
NSPJARCH.COM  
© COPYRIGHT 2023

CLUBHOUSE PLAN NOTES

A

18" DEEP PRE-ENGINEERED FLOOR TRUSSES @ 24"oc MAX

A1

18" DEEP PRE-ENGINEERED FLOOR TRUSSES @ 16"oc MAX

A2

24" DEEP PRE-ENGINEERED ROOF TRUSSES @ 24"oc MAX (SLOPE TOP CHORD PER ARCH)

B1

2x12 @ 16"oc JOISTS

B2

(2) 2x12 @ 12"oc JOISTS

C1

2x10 @ 24"oc JOISTS

C2

(2) 2x10 @ 16"oc JOISTS

C3

(2) 2x10 @ 12"oc JOISTS

C4

2x10 @ 24"oc JOISTS OVERBUILD ABOVE

D

STAIR STRINGERS PER 1/S1.10

E

8x8 WOOD COLUMN ATOP SIMPSON ABU88Z W/ (2) 5/8"x6"Lg SIMPSON TITEN HD SCREW ANCHORS

E1

(3) 2x10 CONT W/ XX POST CAP @ EA COLUMN

E2

(3) 2x8 CONT W/ XX POST CAP @ COLUMN & HUC26-3 HANGER FACEMOUNTED TO SHEATHING W/ (3) 2x6 KING STUDS ALIGNED W/ BEAM

F

STEEL BUCKET PER 4/S3.20

G1

2x8 JOISTS @ 16"oc. TAPER JOIST PER 4/S3.42 W/ SLOPE PER ARCH

G2

2x6 JOISTS @ 16"oc. TAPER JOIST PER 1/S3.44

H

HUCQ612-SDS HANGER

J

UPSET (3) 1 3/4"x11 1/4" BEAM. PROVIDE CONTINUOUS BLOCKING FOR EXTENTS OF EXTERIOR WALL ABOVE BTWN T/B EAM AND B/DECK.

K

(4) 2x8 HIGH & LOW w/ (2) TOP PL & 2x8 BOTT PL w/ 1 JACK / 3 KING EA END w/ (4) 2x8 JACKS AT INTERIOR JAMBS. AT LOW HEADER INTERIOR JAMBS TO HAVE OUTER PLIES INTERRUPTED.

CLUBHOUSE HEADERS/BEAMS SCHEDULE

MARK	HEADER	JAMB TYPE #	NOTES
D1	(3) 2x8	1 JACK / 1 KING	
D2	(3) 2x8	1 JACK / 2 KING	
E1	(3) 2x10	1 JACK / 1 KING	
E2	(3) 2x10	1 JACK / 2 KING	
F1	(3) 2x12	1 JACK / 2 KING	
F2	(3) 2x12	2 JACK / 2 KING	
J1	(3) 1 3/4"x7 1/8" LVL	2 JACK / 2 KING	
N1	(3) 1 3/4"x11 1/4" LVL		
Q1	(3) 1 3/4"x14" LVL		HGU5.50-SDS (H=14") HANGER @ BEAM CONNECTION
S1	(3) 1 3/4"x16" LVL	3 KING	
T1	(2) 1 3/4"x18" LVL	3 KING	
U1	(3) 1 3/4"x18" LVL	3 KING	
V1	(4) 1 3/4"x18" LVL	3 KING	
X1	(5) 1 3/4"x18" LVL	4 KING @ WALL / SIMPSON EGG HANGER TO Y1 BEAM	ATTACH PLIES TOGETHER w/ 3 ROWS OF 1/4"x8" SDS SCREWS @ 12"oc FROM EA SIDE - MATCH EDGE DISTANCE PER 5A/S0.02
Y1	(3) 1 3/4"x24" LVL	4 KING	

NOTES:

1.

JAMB STUDS SHALL MATCH SIZE & GRADE OF WALL STUDS U.N.O.

2.

WHERE BEAM IS NOTED "-u", ALL JAMB STUDS NOTED WILL EXTEND TO DOUBLE TOP PLATE.

3.

ALL EXTERIOR LUMBER TO BE TREATED AGAINST MOISTURE. REFER TO NOTE 12.T ON SHEET S0.01 FOR FIRE RETARDANT TREATED HEADER AND STUD REQUIREMENTS.

4.

PROVIDE SQUASH BLOCKS AT TRUSSES & BLOCKING FRAMING WHERE JAMBS OR STUD PACKS ARE DISCONT AND IN TRUSS CAVITY. QUANTITY TO MATCH JAMB OR STUD PACK ABOVE.

5.

PROVIDE 1/2" PLYWOOD SPACER PLATES AT INTERIOR HEADERS CONSTRUCTED WITH 2x LUMBER.

6.

AT CONTRACTOR'S OPTION, PROVIDE GLULAM IN LIEU OF PSL OF EQUAL OR GREATER STRENGTH.

7.

REFER TO DETAIL 4/S0.02 FOR MULTIPLY MEMBER CONNECTION REQUIREMENTS.

8.

ATTACH JAMB & KING STUDS TOGETHER PER CONNECTION TYPE 24 ON NAILING SCHEDULE ON S0.01.

1 CLUBHOUSE ROOF FRAMING PLAN

3/16" = 1'-0"

WOOD ROOF FRAMING NOTES:

1.

REFER TO GENERAL NOTES ON SHEET S0.01

2.

REFER TO STUD BEARING WALL SCHEDULE TO SHEET S0.02

3.

REFER TO HEADER/B EAM SCHEDULE ON SHEET S0.02

4.

REFER TO SHEARWALL SCHEDULE ON SHEET S0.03

5.

PROVIDE (3) STUD (MINIMUM) ALIGNED UNDER EACH END OF GIRDER TRUSS (CONTINUOUS FOUNDATION) - FINAL QUANTITY TO MATCH NUMBER OF PLIES OF GIRDER TRUSS. PROVIDE SIMPSON LSTA-STYLE HOLDDOWN AT EACH END OF GIRDER TRUSS

6.

REFER TO S3.40-SERIES DRAWINGS FOR ADDITIONAL ROOF FRAMING DETAILS NOT INDICATED HERE.

7.

PROVIDE UNIFORM UPLIFT SCREWS AT UPPER FLOOR PER DETAILS 2, 2A, 3, 3A, 3B, 4 AND 5 ON SHEET S0.20.

8.

PRE-ENGINEERED TRUSSES TO HAVE A MINIMUM DEPTH OF 24". SLOPE TOP CHORD PER ARCHITECTUAL DRAWINGS.

9.

XXXX

INDICATES AREA ON ROOF THAT IS REQ'D TO BE DESIGNED FOR MEP EQUIPMENT ZONE PER GENERAL NOTE "2.B" ON SHEET S0.01

10.

TOP OF STEEL ELEVATION FOR STEEL BEARING ON WOOD MEMBERS SHALL BE FIELD COORDINATED BY THE CONTRACTOR & ARCHITECTURAL ROUGH OPENING SCHEDULE.

11.

PRE-ENG TRUSSES TO HAVE SLOPING TOP CHORD WITH MINIMUM TRUSS DEPTH OF 24".

2 CLUBHOUSE ELEVATOR ROOF FRAMING PLAN

3/16" = 1'-0"

PRE-ENG GIRDER TRUSS @ ALL (4) SIDES OF ELEVATOR OVERRUN

RESIDENCES AT BLACKWELL

50 Highway & Blackwell, Lee's Summit, MO

A NEW DEVELOPMENT:

DRAWING RELEASE LOG

REVISIONS:

1

4/05/2023

Addendum 1

DATE: 3/24/2023

JOB NO. 696521

DRAWN BY: CAB/JLF

SHEET NO.

PERMIT SET


S2.12








ARCH D 24" x 36"  
UNP/NSPJ/Projects/NSPJ/2217 - Blackwell Apartments/NSPJ/2217 Dwg/NSPJ/2217 - S3.01  
4/5/2023 11:37:53 AM NSPJ/ARCHITECTS ©  
Blackwell, JLF.rvt



TYPICAL BOTT. PL CONNECTION TO CONCRETE


## 1 SECTION

3/4" = 1'-0"



## 5 SECTION


3/4" = 1'-0"



TYP. SECTION AT DOORS/GARAGE DOORS

## 9 SECTION


3/4" = 1'-0"



INTERIOR BRG. WALL FTG AT GARAGE WALLS

## 13 SECTION


3/4" = 1'-0"



TYPICAL BOTT. PL CONNECTION TO CONCRETE AT EXTERIOR JAMBS & ENDS OF WALL


## 1A SECTION

3/4" = 1'-0"



## 6 SECTION


3/4" = 1'-0"



TYPICAL INTERIOR COLUMN FOOTING

## 10 SECTION


3/4" = 1'-0"



INTERIOR BRG. WALL FTG AT GARAGE WALLS WITH OPTIONAL CONSTRUCTION JOINT

## 13B SECTION


3/4" = 1'-0"



TYPICAL BOTT. PL CONNECTION TO CONCRETE AT SHORT PL SEGMENTS & JAMBS


## 1B SECTION

3/4" = 1'-0"




## 2 SECTION

3/4" = 1'-0"



## 7 SECTION


3/4" = 1'-0"



INTERIOR BRG. WALL FTG AT SINGLE WALLS


## 11,11B SECTION

3/4" = 1'-0"



## 7A SECTION


3/4" = 1'-0"



INTERIOR BRG. WALL FTG AT DBL WALLS


## 12 SECTION

3/4" = 1'-0"



## 8 SECTION


3/4" = 1'-0"



## 4 SECTION

3/4" = 1'-0"

ARCHITECTURE  
LANDSCAPE  
ARCHITECTURE  
ENERGY SERVICES  
ARCHITECTS  
3515 W. 75TH ST., SUITE 201  
PRAIRIE VILLAGE, KS 66208  
P. 913.831.1415  
F. 913.831.1563  
NSPJARCH.COM  
© COPYRIGHT 2023



A NEW DEVELOPMENT:  
**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO

DRAWING RELEASE LOG

REVISIONS:  
1 4/5/2023 Addendum 1

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

PERMIT SET





S3.01



DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

SHEET NO.  
**S3.02**





A NEW DEVELOPMENT:














# RESIDENCES AT BLACKWELL

50 Highway & Blackwell, Lee's Summit, MO

REVISIONS:

1	4/5/2023	Addendum 1
---	----------	------------





DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY  
CAB/JLF  
SHEET NO.

**S3.10**















**A NEW DEVELOPMENT:  
RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO

 DRAWING RELEASE LOG

△ REVISIONS:

---

1 4/05/2023 Addendum 1

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.


## PERMIT SET

**S3.31**











**1 SECTION**  
3/4" = 1'-0"




**1A SECTION**  
3/4" = 1'-0"




**TYPICAL PARAPET KICKER  
WHERE T/Parapet EXCEEDS  
4'-0" ABOVE T/TOP CHORD**


**1B SECTION**  
3/4" = 1'-0"




**2 SECTION**  
3/4" = 1'-0"




**2A SECTION**  
3/4" = 1'-0"




**3 SECTION**  
3/4" = 1'-0"



**3A SECTION**  
3/4" = 1'-0"




**4 SECTION**  
3/4" = 1'-0"



**5 SECTION**  
3/4" = 1'-0"

PERMIT SET



A NEW DEVELOPMENT:  
**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO


DRAWING RELEASE LOG

REVISIONS:  
1 4/05/2023 Addendum 1


DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

**S3.41**







**1 SECTION**  
3/4" = 1'-0"




**2 SECTION**  
3/4" = 1'-0"



**3 SECTION**  
3/4" = 1'-0"



**4 SECTION**  
3/4" = 1'-0"



**5 SECTION**  
3/4" = 1'-0"



A NEW DEVELOPMENT:  
**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO



REVISIONS:

1	4/5/2023	Addendum 1
---	----------	------------

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

PERMIT SET

**S3.42**



### S3.43

# 1 SECTION

# 1A SECTION

## 2 SECTION

### 3 SECTION




## 4 SECTION

## 5 SECTION

## 6 SECTION

## S3.43





**A NEW DEVELOPMENT:  
RESIDENCES AT BLACKWELL  
50 Highway & Blackwell, Lee's Summit, MO**



DRAWING RELEASE LOG


△ REVISIONS:

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.


## PERMIT SET

**S3.44**












# 1 DET. GARAGE 1A FOUNDATION PLAN




## 2 DET. GARAGE 1A FRAMING PLAN



### 3 DET. GARAGE 1B, 1C, 2A, 2B, & 2C FOUNDATION PLAN



#### 4 DET. GARAGE 1B, 1C, 2A, 2B, & 2C FRAMING PLAN




## 5 SECTION

## 6 SECTION

TYP. SECTION AT GARAGE DOORS

**7 SECTION**  
3/4" = 1'-0"




### GARAGE PORTAL FRAMING DETAIL

## 8 SECTION

**8A SECTION**  
3/4" = 1'-0"

## 9 SECTION



# 11 SECTION

## PERMIT SET

 **NSPJ**  
ARCHITECTURE  
LANDSCAPE  
ARCHITECTURE  
ENERGY SERVICES

**ARCHITECTS<sup>PA</sup>**  
3515 W. 75TH ST., SUITE 201  
PRAIRIE VILLAGE, KS 66208

P. 913.831.1415  
F. 913.831.1563  
NSPJARCH.COM  
© COPYRIGHT 2022

**A NEW DEVELOPMENT:  
RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO


 DRAWING RELEASE LOG

△ REVISIONS:


DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.

**\$4.00**







**1 DET. GARAGE 3A & 3B FOUNDATION PLAN**  
1/8" = 1'-0"




**2 DET. GARAGE 3A & 3B FRAMING PLAN**  
1/8" = 1'-0"




**3 DET. GARAGE 3C, 4A, & 4B FOUNDATION PLAN**  
1/8" = 1'-0"



**4 DET. GARAGE 3C, 4A, & 4B FRAMING PLAN**  
1/8" = 1'-0"



**5 DET. GARAGE 4C FOUNDATION PLAN**  
1/8" = 1'-0"



**6 DET. GARAGE 4C FRAMING PLAN**  
1/8" = 1'-0"



A NEW DEVELOPMENT:  
**RESIDENCES AT BLACKWELL**  
50 Highway & Blackwell, Lee's Summit, MO

DRAWING RELEASE LOG


△ REVISIONS:

DATE:  
3/24/2023  
JOB NO.  
696521  
DRAWN BY:  
CAB/JLF  
SHEET NO.


PERMIT SET

**S4.01**






**1 CARPORT FOUNDATION PLAN**  
1/8" = 1'-0"




**2 CARPORT FRAMING PLAN**  
1/8" = 1'-0"



**TYPICAL CARPORT FRAME**  
NOTE: FRAME PROFILE APPROXIMATE, RE: PRE-ENG. STRUCTURE MANUFACTURER PER EXACT PROFILE, COORD. W/ ARCH


**3 SECTION**  
1/4" = 1'-0"



**TYPICAL CARPORT COLUMN PIER**

**4 SECTION**  
3/4" = 1'-0"





TYPICAL CMU WALL REINFORCING AT OPENINGS

LEGEND:


- FULL HEIGHT VERTICAL BARS AS JAMB REINFORCING IN FIRST 2 CELLS ADJACENT TO OPENING. REINFORCE EACH CELL WITH SIZE & QUANTITY OF BAR TO MATCH WALL REINFORCING (1 BAR TYPICAL IN 8" WALLS AND 2 BARS TYPICAL IN 12" WALLS).
- LINTEL REINFORCING PER SECTION C. EXTEND 2'-0" PAST EDGE OF OPENING ON EACH SIDE (TYPICAL).
- 2-#5 CONTINUOUS HORIZONTAL BARS AS SILL REINFORCING IN 8" COURSE BELOW OPENING (U.N.O.). EXTEND 2'-0" PAST EDGE OF OPENING ON EACH SIDE (TYPICAL).
- FULL HEIGHT VERTICAL BARS PER MASONRY VERTICAL REINFORCING SCHEDULE LOCATED IN END CELL AT EACH SIDE OF VERTICAL WALL CONTROL JOINTS.

GENERAL CRITERIA: (SECTION A CONTINUED):

- VERTICAL REINFORCING BARS SHALL BE DOWELED TO FOUNDATION WITH A DOWEL OF MATCHING SIZE AND SPACING.
- CONTRACTOR SHALL COORDINATE AND VERIFY OPENINGS IN MASONRY WALLS. OPENINGS SHALL BE DETAILED ON REINFORCING STEEL SHOP DRAWING ELEVATIONS.
- VERTICAL CONTROL JOINTS IN MASONRY WALLS SHALL BE 36" WIDE, FULL HEIGHT OF WALL. JOINTS SHALL BE SPACED AT A MAXIMUM OF 24'-0" ON CENTER AND NOT LESS THAN 2'-0" FROM THE EDGE OF ANY OPENING. ALL HORIZONTAL JOINT REINFORCING SHALL BE DISCONTINUOUS AT CONTROL JOINTS. ALL BOND BEAM HORIZONTAL REINFORCING SHALL BE CONTINUOUS THROUGH CONTROL JOINTS. CONTRACTOR SHALL COORDINATE AND VERIFY ALL CONTROL JOINT LOCATIONS.


MASONRY VERTICAL REINFORCING SCHEDULE FOR LOAD BEARING MASONRY (CMU) WALLS			
WALL THICKNESS	LOCATION	VERTICAL REINF. (IN GROUTED CELLS)	SPACING
8"	TRASH ENCLOSURE	1- #5	24"oc
NOTES: 1. IN ADDITION TO SPACING SHOWN IN SCHEDULE, VERTICAL REINFORCING SHALL BE PROVIDED IN GROUTED CELLS AT THE FOLLOWING LOCATIONS A.) IN THE FIRST 2 CELLS ADJACENT TO EACH OPENING B.) IN THE END CELLS ON EACH SIDE OF VERTICAL CONTROL JOINTS C.) IN THE END CELLS OF EACH LENGTH OF WALL D.) AT EACH CORNER OF WALLS 2. ALL MASONRY VOIDS AND BOND BEAMS TO BE GROUTED SHALL BE FREE OF DEBRIS AND MORTAR DROPPINGS PRIOR TO GROUTING. ANY MASONRY w/ DROPPINGS OR DEBRIS OBSERVED IN VOIDS SHALL BE REJECTED.			

**A CMU WALL ELEVATION**  
1 1/2" = 1'-0"



TYPICAL REBAR POSITIONING DETAIL


**B SECTION**  
1 1/2" = 1'-0"



**1 TRASH ENCLOSURE FOUNDATION PLAN**  
1/8" = 1'-0"


TYPICAL MASONRY REINFORCING NOTE:

ALL INTERIOR & EXTERIOR MASONRY WALLS SHOWN ON ARCHITECTURAL AND STRUCTURAL DRAWINGS ARE TO BE REINFORCED HORIZONTALLY WITH BOND BEAMS (2- #5 BOTTOM) AT BOTTOM COURSE, TOP COURSE, JOIST BEARING ELEVATION AND AT 8'-0" MAXIMUM O.C. AND VERTICALLY AS INDICATED ON DRAWINGS. THESE WALLS ARE TO BE ANCHORED TOP AND BOTTOM TO THE FOUNDATION, FLOOR, OR ROOF PER TYPICAL DETAILS. THE VERTICAL REINFORCING IS CONTINUOUS (IN 6'-8" MAXIMUM LENGTHS, LAPPED 2'-6" MINIMUM). FILL BLOCK CELLS AND BOND BEAMS WITH 2,500psi GROUT. RE: DETAILS "A" THROUGH "E" ON THIS SHEET.




TYPICAL LINELS AT ALL CMU WALLS (U.N.O.)

**C SECTION**  
1 1/2" = 1'-0"




**2 SECTION**  
3/4" = 1'-0"



TYPICAL BOND BEAM DETAIL AT CORNER OF CMU WALL

**D DETAIL**  
3/4" = 1'-0"



TYPICAL MASONRY COLUMN

**E SECTION**  
1 1/2" = 1'-0"

