

								SCH	HEDULE 4
SYM	PIER PAD SIZE	DEPTH	MINIMUM REINFORCEMENT GRADE 60 KSI STEEL				СП	STEEL LUMN, MIN = 35 KS	
	30″×30″	1'-0"	((5)	#4	BAR	E.W.	3″	DIAMETER
B	36 " ×36 "	1'-0"	((6)	#4	BAR	E.W.	3″	DIAMETER
\land	42″×42″	1′-2 ″	((7)	#4	BAR	E.W.	3″	DIAMETER
\triangle	48"×48"	1'-4″	((8)	#4	BAR	E.W.	3″	DIAMETER
E	54″×54″	1'-4"	(9)	#4	BAR	E.W.	3.5″	DIAMETE
F	60″×60″	1′-6″	(1	10>	#4	BAR	E.W.	3.5″	DIAMETE
ANY SIZE FOOTING WITH AN (*)									COLUMN EEDED
IS	SOLATE	D FO		NG	S	AND	COLL	IMN	PADS
SYM	PIER DIAMETE		PTH MINIMUM REINFORCE						GRADE 4
A	12″	3'-()"	(4) VERTICAL #4					
\bigtriangleup	16″	3'-()"	(4) VERTICAL #4					
\triangle	18″	3'-()"	(4) VERTIC				AL #	ŧ4
ĸ	24″	3'-()"	(4) VERTIC				AL ‡	ŧ4
\wedge	28″	3'-()"	(4) VERTICAL #4					