

CENTURY CONCRETE

CONDITION OF SALE: All accounts payable C.O.D. There will be a \$20.00 service charge on returned checks.

11011 CODY STREET, SUITE 150
OVERLAND PARK, KANSAS 66210
PHONE: 913-345-2030 FAX: 913-345-8027

SOLD TO:

SHIP TO:

621107216537

COD CASH SALES
1255 N.E. DOUGLAS / C.L. HOWERTO

470 AND DOUGLAS S PAST VICTORIA DR. TO
JOB ON E SIDE

Customer Signature X

TIME OUT	CUSTOMER ID	JOB #	ORDER #	SLUMP	TRUCK	TICKET	COD	CHECK
9:35	00003550	003766	565	2.00 in	339	216537	*YES*	
DATE	PLANT	P.O. NUMBER	LOT	ZONE	USE	YDS DEL	YDS ORDERED	
07/08/11	62	CREDIT CARD			<UNKNOWN>	1.00	1.00	

WARNING: INJURIOUS TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are light at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, where knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1% Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear an appropriate NIOSH-approved respirator during these activities.

QUANTITY	CODE	DESCRIPTION	UNIT PRICE	EXTENDED PRICE
1.00	0545	4000 AE FA W/MR	\$90.25	\$90.25
1.00	FUEL	FUEL SURCHARGE	\$1.00	\$1.00
1.00	ME23	DELIVERY CHARGE	\$16.00	\$16.00
1.00	ML	MINIMUM LOAD	\$50.00	\$50.00
1.00	NOCHILL	NO CHILLED WATER CUSTOMER		

Subtotal: \$157.25

Total: \$164.67

LEFT PLANT	ARRIVED JOB	STARTED UNLOAD	FINISHED UNLOAD	LEFT JOB	RETURNED PLANT	WATER ADDED AT CUSTOMER REQUEST	ESTIMATED SLUMP AT UNLOADING
						Gallons Added	Inches

UNUSUAL INCIDENT OF NOTE ON THIS DELIVERY:

SEE REVERSE SIDE FOR CONDITIONS OF SALE

Truck Driver User Disp Ticket Num Ticket ID Time Date
339 0410 user 216537 22276 9:35 7/8/11

Load Size Mix Code Returned Qty Mix Age Seq Load ID
1.00 CY 0545 D 22610

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat
MODSCA3GRN	1685 lb	1693 lb	1780 lb	+ 5.11%	0.50% M	1 gl
SAND-9	1400 lb	1435 lb	1440 lb	0.35%	2.50% M	4 gl
TYPE I/II	480 lb	480 lb	480 lb	0.00%		
C-ASH JEF	50.0 lb	50.0 lb	48.0 lb	* -4.00%		
WATER	29.50 gl	21.30 gl	17.00 gl	--20.17%		17.00 gl
AEA-92S	1.10 /C	5.83 oz	6.00 oz	2.92%		
MRX	4.00 /C	21.20 oz	20.00 oz	-5.66%		

Actual Num Batches: 1

Load Total: 3891 lb Design 0.465 Water/Cement A Design 29.5 gl Actual 22.3 gl To Add: 7.2 gl

Slump: 2.00 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -3.0 gl/ CY