11011 CODY STREET, SUITE 150 OVERLAND PARK, KANSAS 66210 PHONE: 913-345-2030 FAX: 913-345-8027 SOLD TO:



621107216672

SHIP TO:

COD CASH SALES 1255 N.E. DOUGLAS / C.L. HOWERTO 470 AND DOUGLAS S PAST VICTORIA DR. TO JOB ON E SIDE

## Customer Signature X\_

TIME OUT	CUSTOMER ID	J08#	ORDER#	SLUMP	TRUCK	TICKET	COD	CHECK
9:01	00003550	003766	899	2.00 i	n 340	216672	*YES*	
DATE	PLANT	P.O. NUM	BER	LOT	ZONE	USE	YOS DEL	YDS ORDERED
07/12/11	62	CREDIT	CARD			<unknown></unknown>	1.00	1.00

## WARNING: INJURIOUS TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. if you have to stand in wet concrete, use waterproof boots that are light at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, where knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURSON SUPPORT OF CRILDTEN MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1% Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear an appropriate NIOSH-approved respirator during these activities.

QUANTITY	CODE	DESCRIPTION	UNIT PRICE	EXTENDED PRICE
1.00	1221	MCIB WA610-1-4 FA (KCMO 1")	\$92.25	\$92.25
	FUEL	FUEL SURCHARGE	\$1.00	\$1.00
1.00	ME23	DELIVERY CHARGE	\$16.00	\$16.00
1.00	ML	MINIMUM LOAD	\$50.00	\$50.00
1.00	NOCHILL	NO CHILLED WATER CUSTOMER		

Subtotal:

\$159.25

Total:

\$166.84

WATER ADDED AT CUSTOMER REQUEST	CEPT LOB RETURNED	FINISHED UNLGAD	STARTED UNLOAD	ARRIVED JOE	LEFT PLANT
Gallons Added					
OFF DEVENOR OFF FOR CONDITIONS OF CALL					

UNUSUAL INCIDENT OF NOTE ON THIS DELIVERY:

SEE REVERSE SIDE FOR CONDITIONS OF SALE

340	Oriver User user Mix Code Retur	216672 2241:	et ID Time Date 1 9:01 7/12/11 Seq Load ID		I here by certify that City of KCMO inspected and approved materials have been proportioned and mixed in accordance with communicative direments.
1.00 CY 1	1221		D 22746		1 (1) CELL ANAL
Material	Design Qty	Required Batched	% Var % Moistur	e Actual Wat	Willy -
KCMO 1 STP	1770 lb	1779 lb 1800 lb	1.19% 0.50% M	1 gl	Lee's Summit Plant
SAND-9	1205 lb	1235 lb 1240 lb	0.39% 2.50% M	4 gl	Century Concrete
TYPE I/II	520 lb	520 lb 528 lb	1.54%		William R. Owings
DURAPOZ F	90.0 lb	90.0 lb 88.0 lb	-2.22%		Tech Services Manager
WATER	30.20 gl	20.53 gl 20.00 gl	-2.58%	20.00 gl	
AEA-92S	1.80 /C	10.98 oz 11.00 oz	0.18%		
WR-91	3.00 /C	18.30 oz 17.00 oz	-7.10%		
Actual	Num Batches:	: 1			
Load Total:	3825 lb	Design 0.413 Water/Ceme	nt A Design	30.2 gl	Actual 24.7 gl To Add: 2.5 gl
Slump: 2.0	00 in # Water	r in Truck: 3.0 gl Adju	st Water: 0.0 gl / Load	Trim Water: -2.0	gl/ CY