



HANGER SPACING CHART									
MAXIMUM DISTANCE BETWEEN HANGERS (FT-IN) PER NFPA-13									
PIPE SIZE	1/2"	3/4"	1"	1 1/2"	2"	2 1/2"	3"	4"	6"
STEEL PIPE	N/A	1'-0"	1'-0"	1'-0"	1'-0"	1'-0"	1'-0"	1'-0"	1'-0"
THREADED LIGHTWALL	N/A	1'-0"	1'-0"	1'-0"	1'-0"	1'-0"	1'-0"	N/A	N/A
COPPER	6'-0"	6'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
CPVC	6'-0"	6'-0"	6'-6"	1'-0"	6'-0"	10'-0"	10'-0"	N/A	N/A
DISTANCE FROM SPRINKLER TO HANGER PER NFPA-13									
HANGER ROD SIZE PER NFPA-13									
PIPE SIZE	DIAM. OF ROD		PIPE SIZE	DIAM. OF ROD					
UP TO AND INCLUDING 4"	3/8"		6" AND 8"	1/2"					
NOTE: IF PRESSURE EXCEEDS 100 PSI, PROVIDE HANGER FOR ANTI-OVERS (10' PENDENT HEAD) EXCEEDING 1'-0"									

EXTERIOR CANOPIES / BALCONIES

PER NFPA 13B, SECTION 8.5.3.3, SPRINKLERS SHALL BE PERMITTED TO BE OMITTED FROM BELOW THE CANOPIES, ROOFS, PORTE-COCHERES, BALCONIES OR SIMILAR PROJECTIONS OF COMBUSTIBLE CONSTRUCTION PROVIDED THE EXPOSED FINISH MATERIAL ON THE ROOFS, CANOPIES OR PORTE-COCHERES ARE NON-COMBUSTIBLE, LIMITED-COMBUSTIBLE OR FIRE RETARDANT-TREATED WOOD AS DEFINED IN NFPA 103, Standard for Fire Retardant-Treated Wood and Fire-Retardant Coatings for Building Materials.

THE BALCONIES ARE CONSTRUCTED OF NON-COMBUSTIBLE MATERIALS AND FINISHED WITH NON-COMBUSTIBLE SOFFIT MATERIALS - FIRE SPRINKLERS ARE NOT REQUIRED.

