



11011 Cody St Suite 150
Overland Park, KS 66210

Phone: 913.780.4605

A CRH COMPANY

Customer Signature X _____

CONDITION OF SALE: All accounts payable C.O.D. There will be a \$25.00 service charge on returned checks.

CUSTOMER # 257465		CUSTOMER JD Bishop Construction LLC			PROJECT # 015523		PROJECT 2023 PRICING	
PLANT 372	DATE 11/22/23 9:23	TIME 9:19	ORDER 354	TRUCK 302	DRIVER 874	REQUESTED TIME 11/22/23 9:50	PREVIOUS TRUCK	
DELIVERY ADDRESS 805 MISSOURI 150/LSMO				DIRECTIONS 50 HWY AND 3RD ST - WEST TO WARD RD - SOUTH TO WARD RD - EAST TOLEMANS LN - EAST TO JOB (FIRESTATION # 5))				
SLUMP 5.00		USAGE DESCRIPTION PAVING						
PO NUMBER J2863		JOB NUMBER						

LOAD QUANTITY	CUMULATIVE QUANTITY	ORDERED QUANTITY	PROD ID	PRODUCT DESCRIPTION	UNIT	\$/UNIT	EXTENDED
10.00	10.00	75.00	340D7E04	KCMMB GR 4K S 4"	yd		
10.00	10.00	1.00	FIBERS-TS3	3 LB (CY) TUF-STRAND FIBERS	lb		
10.00		0.00	901.ENVN	ENVIRONMENTAL FEE - NON TAX	/l		
1.00		0.00	901.FSCR	FUEL FEE PER LOAD	ea		
10.00		0.00	NONTAXDE	NON TAXABLE DELIVERY CHARGE	/y		
				HEATED WATER			

TICKET NUMBER

37226167

WATER ADDED:

GALLONS TO _____ YARDS X _____
GALLONS TO _____ YARDS X _____
GALLONS TO _____ YARDS X _____

Sub-Total
Sales Tax
Total \$
Balance Due

LEAVE PLANT	ARRIVE JOB	START POUR	FINISH POUR	LEAVE JOB	ARRIVE PLANT	QUALITY / TESTING	
						SLUMP	AIR CYLINDERS TAKEN

WARNING: INJURIES TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement, or cement mixture can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are tight at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, wear knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1%. Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear and appropriate NIOSH approved respirator during these activities.

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	Trim
HOL-T1L(8)	450 lb	4500 lb	4480 lb	-0.44%			
HOLSLAG	150.0 lb	1500.0 lb	1490.0 lb	-0.67%			
3/4GRANITE	1701 lb	17095 lb	17020 lb	-0.44%	0.50% M	10 gl	
SAND-9	1266 lb	13231 lb	13300 lb	0.52%	4.51% A	69 gl	
H2OGL	30.50 gl	220.92 gl	221.00 gl	0.04%		221.00 gl	-.50 gl
AEA-92S	.60 /C	36.00 oz	36.00 oz	0.00%			
P-6420	5.0 /C	300.0 oz	300.0 oz	0.00%			

Actual Load Slump: 38155 lb 5.00 in #
Num Batches: 1
Design W/C: 0.424
Water/Cement: 0.419 A
Water in Truck: 0.0 gl
Adjust Water:
Design 305.0 gl
0.0 gl / Load
Trim Water:
Actual 299.9 gl
To Add: 5.1 gl
-0.5 gl / CYL