

NTURY CONCRETE

CONDITION OF SALE: All accounts payable C.O.D. There will be a \$20.00 service charge on returned checks.

11011 CODY STREET, SUITE 150
OVERLAND PARK, KANSAS 66210
PHONE: 913-345-2030 FAX: 913-345-8027



SHIP TO:

621107217330

COD CASH SALES
1255 N.E. DOUGLAS / C.L. HOWERTO

470 AND DOUGLAS S PAST VICTORIA DR. TO
JOB ON E SIDE

Customer Signature X

TIME OUT	CUSTOMER ID	JOB #	ORDER #	SLUMP	TRUCK	TICKET	COD	CHECK
14:04	00003550	003766	638	2.00 in	238	217330	*YES*	
DATE	PLANT	P.O. NUMBER	LOT	ZONE	USE	YDS DEL	YDS ORDERED	
7/28/11	62	CREDIT CARD			KICKERS	1.00	1.00	

WARNING: INJURIOUS TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.

Contact with wet (unhardened) concrete, mortar, cement or cement mixtures can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are light at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, where knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE. USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1% Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear an appropriate NIOSH-approved respirator during these activities.

QUANTITY	CODE	DESCRIPTION	UNIT PRICE	EXTENDED PRICE
1.00	1221	MCIB WA610-1-4 FA (KCMO 1")	\$92.25	\$92.25
1.00	FUEL	FUEL SURCHARGE	\$1.00	\$1.00
1.00	ME23	DELIVERY CHARGE	\$16.00	\$16.00
1.00	ML	MINIMUM LOAD	\$50.00	\$50.00
1.00	NOCHILL	NO CHILLED WATER CUSTOMER		

Subtotal: \$159.25

Total: \$166.84

LEFT PLANT	ARRIVED JOB	STARTED UNLOAD	FINISHED UNLOAD	LEFT JOB	RETURNED PLANT	WATER ADDED AT CUSTOMER REQUEST	ESTIMATED SLUMP AT UNLOADING
						Gallons Added	Inches

UNUSUAL INCIDENT OF NOTE ON THIS DELIVERY:

SEE REVERSE SIDE FOR CONDITIONS OF SALE

CERTIFICATION
I hereby certify that City of KCMO inspected and approved materials have been proportioned and mixed in accordance with contract requirements.

William R. Owings

Lee's Summit Plant
Century Concrete
William R. Owings
Tech Services Manager

Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
	user		217330	23058	14:04	7/28/11
Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID
CY	1221				D	23408
al	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat
STP	1770 lb	1770 lb	1780 lb	0.56%	M	
	1205 lb	1229 lb	1240 lb	0.89%	2.00% M	3 gl
/II	520 lb	520 lb	704 lb	+ 35.38%		
Z F	90.0 lb	90.0 lb	88.0 lb	-2.22%		
	30.20 gl	24.31 gl	22.00 gl	-9.51%		22.00 gl
S	1.80 /C	10.98 oz	12.00 oz	9.29%		
	3.00 /C	18.30 oz	19.00 oz	3.83%		
Num Batches: 1						

otal: 3998 lb Design 0.413 Water/Cement A Design 30.2 gl Actual 24.9 gl To Add: 5.3 gl
2.00 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -3.0 gl/ CY