



Customer Signature X \_\_\_\_\_

**CONDITION OF SALE:** All accounts payable C.O.D. There will be a \$20.00 service charge on returned checks.

LEAVE PLANT	ARRIVE JOB	START POUR	FINISH POUR	LEAVE JOB	ARRIVE PLANT	QUALITY / TESTING	
						SLUMP	AIR CYLINDERS TAKEN
PLANT	DATE	TIME	ORDER	TRUCK	DRIVER	REQUESTED TIME	PREVIOUS TRUCK
352	12/12/23 8:30	8:26	394	139	Teel, Shawn	12/12/23 8:54	
CUSTOMER #	CUSTOMER			PROJECT #	PROJECT		
257465	JD Bishop Construction LLC			015523	2023 PRICING		
DELIVERY ADDRESS				DIRECTIONS			
805 MISSOURI 150/LSMO				350 HWY SOUTH TO 291 HWY - SOUTH TO 150 HWY - WEST TO JOB ON SOUTH SIDE OF RD.			
SLUMP	USAGE DESCRIPTION						
5.00	PAVING						
PO NUMBER	JOB NUMBER						
12863							

LOAD QUANTITY	CUMULATIVE QUANTITY	ORDERED QUANTITY	PROD ID	PRODUCT DESCRIPTION	UNIT	\$/UNIT	EXTENDED
10.00	10.00	100.00	340D5E04	KCMMB GR 4K S 4"	yd		
10.00	10.00	1.00	FIBERS-TS3	3 LB (CY) TUF-STRAND FIBERS	lb		
1.00	10.00	1.00	NCA1	ACCELGAURD NCA 1%	oz		
10.00		0.00	901.ENVN	ENVIRONMENTAL FEE - NON TAX	/l		
1.00		0.00	901.FSCR	FUEL FEE PER LOAD	ea		
10.00		0.00	NONTAXDE	NON TAXABLE DELIVERY CHARGE	/y		

**WATER ADDED:**

GALLONS TO	YARDS X	HEATED WATER	
GALLONS TO	YARDS X		Sub-Total
GALLONS TO	YARDS X		Sales Tax
TICKET NUMBER			Total \$
35275346			<b>Balance Due</b>

**WARNING: INJURIES TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.**

Contact with wet (unhardened) concrete, mortar, cement, or cement mixture can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are tight at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, wear knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

**KEEP OUT OF REACH OF CHILDREN**

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1%. Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear and appropriate NIOSH approved respirator during these activities.

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	Trim
H2OGL	30.5 gl	218.7 gl	218.0 gl	-0.33%		218.0 gl	-1.0 gl
AG-T1L	450 lb	4500 lb	4490 lb	-0.22%			
HOLSLAG	150 lb	1500 lb	1495 lb	-0.33%			
3/4GRANITE	1697 lb	17097 lb	17100 lb	0.02%	0.75% M	15 gl	
SAND-9	1263 lb	13092 lb	13060 lb	-0.25%	3.66% A	55 gl	
AEA-92S	.50 /C	30.00 oz	30.00 oz	0.00%			
P-6420	5.00 /C	300.00 oz	300.00 oz	0.00%			
ECNCA	12.00 /C	720.00 oz	720.00 oz	0.00%			

Actual Load 38030 lb Slump: 5.00 in Num Batches: 1 Design W/C: 0.424 Water/Cement: 0.402 A Design 305.0 gl Actual 288.5 gl To Add: 16.5 gl Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -1.0 gl / CYL



# FORDYCE

A CRH COMPANY

Customer Signature X \_\_\_\_\_

**CONDITION OF SALE:** All accounts payable C.O.D. There will be a \$20.00 service charge on returned checks.

LEAVE PLANT	ARRIVE JOB	START POUR	FINISH POUR	LEAVE JOB	ARRIVE PLANT	QUALITY / TESTING	
						SLUMP	AIR CYLINDERS TAKEN
PLANT	DATE	TIME	ORDER	TRUCK	DRIVER	REQUESTED TIME	PREVIOUS TRUCK
352	12/12/23 10:58	10:54	394	140	Vogel, Matt	12/12/23 11:16	131
CUSTOMER #	CUSTOMER			PROJECT #	PROJECT		
257465	JD Bishop Construction LLC			015523	2023 PRICING		
DELIVERY ADDRESS				DIRECTIONS			
805 MISSOURI 150/LSMO				350 HWY SOUTH TO 291 HWY - SOUTH TO 150 HWY - WEST TO JOB ON SOUTH SIDE OF RD.			
SLUMP		USAGE DESCRIPTION					
5.00		PAVING					
PO NUMBER		JOB NUMBER					
12863							

LOAD QUANTITY	CUMULATIVE QUANTITY	ORDERED QUANTITY	PROD ID	PRODUCT DESCRIPTION	UNIT	\$/UNIT	EXTENDED
10.00	50.00	100.00	340D5E04	KCMMB GR 4K S 4"	yd		
10.00	50.00	1.00	FIBERS-TS3	3 LB (CY) TUF-STRAND FIBERS	lb		
10.00		0.00	901.ENVN	ENVIRONMENTAL FEE - NON TAX	/l		
1.00		0.00	901.FSCR	FUEL FEE PER LOAD	ea		
10.00		0.00	NONTAXDE	NON TAXABLE DELIVERY CHARGE	/y		

**WATER ADDED:**

GALLONS TO	YARDS X	HEATED WATER	
GALLONS TO	YARDS X		Sub-Total
GALLONS TO	YARDS X		Sales Tax
TICKET NUMBER			Total \$
35275376			<b>Balance Due</b>

**WARNING: INJURIES TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.**

Contact with wet (unhardened) concrete, mortar, cement, or cement mixture can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are tight at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, wear knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

**KEEP OUT OF REACH OF CHILDREN**

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1%. Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear and appropriate NIOSH approved respirator during these activities.

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	Trim
H2OGL	30.5 gl	230.6 gl	230.0 gl	-0.26%		230.0 gl	-1.0 gl
AG-T1L	450 lb	4500 lb	4485 lb	-0.33%			
HOLSLAG	150 lb	1500 lb	1490 lb	-0.67%			
3/4GRANITE	1697 lb	17097 lb	17120 lb	0.13%	0.75% M	15 gl	
SAND-9	1263 lb	13040 lb	13020 lb	-0.16%	3.25% A	49 gl	
AEA-92S	.60 /C	36.00 oz	36.00 oz	0.00%			
P-6420	5.00 /C	300.00 oz	300.00 oz	0.00%			

Actual Load 38055 lb Slump: 5.00 in # Num Batches: 1 Design W/C: 0.424 Water/Cement: 0.411 A Design 305.0 gl Actual 294.4 gl To Add: 10.6 gl Adjust Water: 0.0 gl / Load Trim Water: -1.0 gl / CYC




# FORDYCE

A CRH COMPANY

Customer Signature X \_\_\_\_\_

**CONDITION OF SALE:** All accounts payable C.O.D. There will be a \$20.00 service charge on returned checks.

LEAVE PLANT	ARRIVE JOB	START POUR	FINISH POUR	LEAVE JOB	ARRIVE PLANT	QUALITY / TESTING	
						SLUMP	AIR CYLINDERS TAKEN
PLANT	DATE	TIME	ORDER	TRUCK	DRIVER	REQUESTED TIME	PREVIOUS TRUCK
352	12/12/23 13:07	13:04	394	140	Vogel, Matt	12/12/23 13:23	143
CUSTOMER #	CUSTOMER			PROJECT #	PROJECT		
257465	JD Bishop Construction LLC			015523	2023 PRICING		
DELIVERY ADDRESS				DIRECTIONS			
805 MISSOURI 150/LSMO				350 HWY SOUTH TO 291 HWY - SOUTH TO 150 HWY - WEST TO JOB ON SOUTH SIDE OF RD.			
SLUMP	USAGE DESCRIPTION						
5.00	PAVING						
PO NUMBER	JOB NUMBER						
12863							

LOAD QUANTITY	CUMULATIVE QUANTITY	ORDERED QUANTITY	PROD ID	PRODUCT DESCRIPTION	UNIT	\$/UNIT	EXTENDED
10.00	80.00	100.00	340D5E04	KCMMB GR 4K S 4"	yd		
10.00	80.00	1.00	FIBERS-TS3	3 LB (CY) TUF-STRAND FIBERS	lb		
10.00		0.00	901.ENVN	ENVIRONMENTAL FEE - NON TAX	/l		
1.00		0.00	901.FSCR	FUEL FEE PER LOAD	ea		
10.00		0.00	NONTAXDE	NON TAXABLE DELIVERY CHARGE	/y		
WATER ADDED:							
GALLONS TO		YARDS X	HEATED WATER				
GALLONS TO		YARDS X					Sub-Total
GALLONS TO		YARDS X					Sales Tax
TICKET NUMBER							Total \$
							Balance Due
35275399							

**WARNING: INJURIES TO EYES, CAUSES SKIN IRRITATION READ THIS WARNING BEFORE USING. Contains Portland Cement.**

Contact with wet (unhardened) concrete, mortar, cement, or cement mixture can cause skin irritation, severe chemical burns, or serious eye damage. Avoid contact with eyes and skin. Wear waterproof gloves, a fully buttoned long-sleeved shirt, full length trousers, and tight fitting eye protection when working with these materials. If you have to stand in wet concrete, use waterproof boots that are tight at tops and high enough to keep concrete from flowing into them. If you are finishing concrete, wear knee pads to protect knees. Wash wet concrete, mortar, cement or cement mixtures from your skin with fresh, clean water immediately after contact. Indirect contact through clothing can be as serious as direct contact, so promptly rinse out wet concrete, mortar, cement or cement mixtures from clothing. Seek immediate medical attention if you have persistent or severe discomfort. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

**KEEP OUT OF REACH OF CHILDREN**

USER AGREES TO CONVEY THIS WARNING TO ALL PERSONS WHO MAY PURCHASE, USE OR COME IN CONTACT WITH WET (UNHARDENED) CONCRETE, MORTAR, CEMENT OR CEMENT MIXTURES. Concrete contains crystalline silica in concentrations greater than 0.1%. Respirable silica is considered by IARC and NTP to be a human carcinogen. Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its unhardened state. However, respirable dust can be generated by grinding, sawing, drilling, breaking, etc. hardened concrete. Wear and appropriate NIOSH approved respirator during these activities.

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	Trim
H2OGL	30.5 gl	231.1 gl	231.0 gl	-0.02%		231.0 gl	-1.0 gl
AG-T1L	450 lb	4500 lb	4490 lb	-0.22%			
HOLSLAG	150 lb	1500 lb	1495 lb	-0.33%			
3/4GRANITE	1697 lb	17097 lb	17080 lb	-0.10%	0.75% M	15 gl	
SAND-9	1263 lb	13036 lb	13060 lb	0.18%	3.22% A	49 gl	
AEA-92S	.60 /C	36.00 oz	36.00 oz	0.00%			
P-6420	5.00 /C	300.00 oz	300.00 oz	0.00%			

Actual Load 38074 lb Design W/C: 0.424 Water/Cement: 0.411 A Design 305.0 gl Actual 295.0 gl To Add: 10.0 gl  
Slump: 5.00 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -1.0 gl / CYT