

# MCC LONGVIEW COMMUNITY COLLEGE METROPOLITAN COMMUNITY COLLEGE

500 SW LONGVIEW ROAD  
LEE SUMMIT, MO 64081

## Construction Documents

hollis + miller architects

we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1.816.442.7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1.720.949.1689  
HOLLISANDMILLER.COM

Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture # 0200161

RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #2014035826  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

Apex Engineers, Inc.  
Structural Engineer  
State Certificate of Authority # 2003004673  
1625 Locust St  
Kansas City, MO 64108  
816.421.3222 phone

### INDEX OF DRAWINGS

GENERAL	
G000	COVER SHEET
G021	OVERALL CODE PLAN
DEMOLITION - ARCHITECTURE	
DA101	DEMOLITION PLAN - OVERALL LEVEL 2
ARCHITECTURE	
A001	GENERAL ARCHITECTURAL INFORMATION
A101	FLOOR & REFLECTED CEILING PLANS - LEVEL 2
A621	INTERIOR ELEVATIONS
A681	MATERIAL FINISH LEGEND
STRUCTURAL	
S100	GENERAL NOTES AND SPECIFICATIONS
S200	RTU FRAMING
S500	TYPICAL STEEL DETAILS
MECHANICAL/ELECTRICAL	
ME100	SYMBOLS LEGEND / GENERAL NOTES
PLUMBING	
P101	FIRST FLOOR PLUMBING PLAN
P102	SECOND FLOOR PLUMBING PLAN
P401	PLUMBING SCHEDULES AND DETAILS
MECHANICAL	
M102	SECOND FLOOR HVAC PLAN
M103	ROOF HVAC PLAN
M301	MECHANICAL DETAILS
M401	MECHANICAL SCHEDULES & CONTROLS
DEMOLITION - ELECTRICAL	
ED101	ELECTRICAL DEMOLITION PLAN
ELECTRICAL	
E101	BASEMENT / FIRST FLOOR / ROOF ELECTRICAL PLAN
E102	SECOND FLOOR ELECTRICAL PLAN
E301	ELECTRICAL DETAILS / SCHEDULES

### ALTERNATES

- ALTERNATE 1: EXTERIOR WINDOWS**
- Base Bid: Do not provide the exterior windows shown. No exterior work except for new mechanical units and devices on the roof.
  - Add Alternate: Provide the exterior storefront windows as shown in the documents.

### DESIGN TEAM

**ARCHITECT:**  
Hollis + Miller Architects  
1828 Walnut Street Ste 922  
Kansas City, MO 64108  
CONTACT: Marissa Carroll  
PHONE: 816.282.2983

**STRUCTURAL ENGINEER:**  
Apex Engineers  
1625 Locust St  
Kansas City, MO 64108  
CONTACT: Logan Chamberlin  
PHONE: 816.421.3222

**MECH/ELECT ENGINEER:**  
RTM Engineering Consultants  
9225 Indian Creeek Pkwy  
Suite 1075  
Overland Park, KS 66210  
CONTACT: Keith Hammerschmidt  
DIRECT: 913.303.0048

### VICINITY MAP

SCIENCE AND TECHNOLOGY BUILDING



MCC Longview Community College Lab Refresh  
Metropolitan Community College  
500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

#### REVISIONS:

#	Description	Date



JOB NO: 23011.00  
DRAWN BY: MC  
CHECKED BY: AR/NY  
DATE: 10/06/2023

# G000

we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1 816.442.7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1 720.949.1689  
HOLLISANDMILLER.COM

Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture # 0200051

RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #2014035826  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

Apex Engineers, Inc.  
Structural Engineer  
State Certificate of Authority # 2003004673  
1625 Locust St.  
Kansas City, MO 64108  
816.421.3222 phone

MCC Longview Community College Lab Refresh  
Metropolitan Community College  
500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

#	Description	Date

CODE NOTES

- SCOPE OF PROJECT IS TO REPLACE EXISTING CASEWORK, FUME HOODS, AND RELATED COMPONENTS, 1:1.
- NO CHANGE TO EXISTING OCCUPANT LOAD.
- REFERENCE MECHANICAL AND STRUCTURAL SPECS AND DRAWINGS FOR RTU PLACEMENT AND SUPPORT.
- FIRE EXTINGUISHERS AND RELATED EQUIPMENT HAVE ONLY BEEN VERIFIED IN ROOMS RECEIVING WORK.
- ONLY ROOMS RECEIVING WORK HAVE BEEN VERIFIED.

CODE LEGEND

- EXISTING BUILDING - NO WORK
- EXISTING BUILDING - ALTERATION LEVEL 1 ALTERATIONS DO NOT INVOLVE SPACE RECONFIGURATION
- FIRE EXTINGUISHER: ON BRACKET; MOUNT HANDLE 48" MAX AFF IN CABINET; BOTTOM OF CABINET 32" AFF

JOB NO: 23011.00  
DRAWN BY: MC  
CHECKED BY: ARNY  
DATE: 10/06/2023

**G021**

OVERALL CODE PLAN

PROJECT INFORMATION

PROJECT NUMBER: 23011.00  
PROJECT NAME: MCC Longview Community College Lab Refresh  
OWNER: Metropolitan Community College  
500 SW Longview Rd  
Lee's Summit, MO 64081  
AUTHORITY HAVING JURISDICTION: City of Lee's Summit, Missouri  
220 SE Green  
Lee's Summit, MO 64063  
RESPONDING FIRE SERVICE: Lee's Summit Fire Department  
ANTICIPATED OCCUPANCY: 8/12/2024 12:00:00 AM  
ADOPTED CODES AND ORDINANCES: 2018 International Building Code  
2018 International Existing Building Code  
2017 National Electric Code (NFPA 70)  
2018 International Mechanical Code  
2018 International Plumbing Code  
2018 International Fuel Gas Code  
2018 International Fire Code  
2009 ICC A117.1 Accessible and Usable Buildings and Facilities

BUILDING INFORMATION


OCCUPANCY CLASSIFICATION: Business, Group B (304.1)  
CONSTRUCTION TYPE: II-B (602.2, Non-combustible, non-protected)  
Renovation of existing structure  
BUILDING HEIGHT: Allowable Height (Table 504.3): 75' above grade plane  
Building Height: Existing: 42' - 4"  
Allowable Stories (Table 504.4): 4 stories above grade plane  
Building Stories: Existing: 3 stories  
BUILDING AREA: SM: Building 2 or more stories above grade plane with automatic sprinkler system  
Sprinkler Qualifier (Table 506.2): 69,300 without frontage increase, 362,250 with frontage.  
Allowable Area: 52,159 sf  
BUILDING AREA: 52,159 sf  
OCCUPANCY SEPARATION: No separation requirement (Table 508.4)  
FIRE RESISTANCE RATINGS: (Per Table 601, 602)  
Primary Structural Frame: 0-Hour fire-resistance rating  
Exterior Bearing Walls: 0-Hour fire-resistance rating  
Interior Bearing Walls: 0-Hour fire-resistance rating  
Exterior Nonbearing Walls: 0-Hour fire-resistance rating  
Interior Nonbearing Walls: 0-Hour fire-resistance rating  
Floor Construction / Secondary Members: 0-Hour fire-resistance rating  
Roof Construction / Secondary Members: 0-Hour fire-resistance rating  
Fire Walls: No fire walls  
Fire Barriers: No fire barriers  
Fire Partitions: No fire partitions  
Smoke Barriers / Partitions: No smoke barriers / partitions  
Shafts: No shaft enclosures

EGRESS COMPONENTS


NUMBER OF EXITS: 2 per space greater than 49 occupants (Table 1006.2.1)  
3 per space with load 501 to 1,000; 4 per space over 1,000  
DEAD-END CORRIDORS: 50' Max. with automatic sprinkler system in groups B, E, F, I-1, M, R-1, R-2, R-4, S, U (1020.4, Exception 2)  
COMMON PATH OF TRAVEL: 100' (Table 1006.2.1)  
TRAVEL DISTANCE TO EXIT: 250' Maximum for A, E, F-1, I-1, M, R, S-1 with sprinkler (Table 1017.2)  
CORRIDOR CONSTRUCTION: 0-hour fire rating in A, B, E, F, I-2, I-4, M, S, U occupancies with sprinkler (1020.1)  
CORRIDOR WIDTH: 44" minimum corridor width (Table 1020.2)  
MEANS OF EGRESS CAPACITY: 0.2" for stairways (1005.3.1) / 0.15" for doors / other (1005.3.2) (sprinklered bldg)

FIRE SAFETY FEATURES

SPRINKLER: Existing, Automatic sprinkler system provided throughout  
FIRE ALARM SIGNALING: Existing  
EMERGENCY LIGHTING / POWER: Existing  
SMOKE CONTROL SYSTEM: Existing




**MATH AND SCIENCE BUILDING - LEVEL 2**  
NO WORK ON OTHER FLOORS. NEW DOAS UNIT AND RELATED EXHAUST ON ROOF TO SERVE THIS CLASSROOM.  
NO CHANGE TO OCCUPANCY, OCCUPANT LOAD, EXITING, OR SPATIAL CONFIGURATION.



**A1** Scale Level 2 - Code Plan  
1/16" = 1'-0"

REVISIONS:

#	Description	Date



The Professional Address and other information shown on this seal are subject to the public address book of the state. All changes, corrections and other information are subject to the public address book of the state. The seal and other information are not valid if they are not shown on the public address book of the state.

JOB NO: 23011.00  
DRAWN BY: MC  
CHECKED BY: ARNY  
DATE: 10/06/2023

**DA101**

**SHEET KEYNOTE LEGEND**


**DEMOLITION NOTES**

- FLOORS & BASE**
- 1 REMOVE EXISTING BASE INCLUDING ADHESIVE. PREP FOR NEW BASE (ENTIRE ROOM).
  - 2 REMOVE EXISTING CONCRETE SLAB AS REQUIRED FOR UNDER SLAB MECHANICAL, ELECTRICAL AND PLUMBING WORK. SAW CUT OR CORE CONCRETE PRIOR TO REMOVAL. DO NOT SAW CUT OR CORE INTO EXISTING FOUNDATIONS OR OTHER STRUCTURAL MEMBERS, SUCH AS EXISTING STRUCTURAL JOISTS. REF. STRUCT FOR FURTHER INFO. COORDINATE WITH MEP SHEETS FOR NEW WORK AND CAPPING OF ABANDONED SERVICES. ALL CORES, DEBRIS, AND SPOILS TO BE REMOVED.

- WALLS**
- 1 REMOVE EXISTING FUME HOOD AND RELATED CASEWORK, REFINISHING COUNTER AND END FACE WHERE CASEWORK REMAINS. PREP SPACE AS REQUIRED FOR NEW FUME HOOD AND BASES. REF MEP FOR FURTHER DIRECTION.
  - 2 REMOVE EXISTING FUME HOOD AND RELATED COMPONENTS. REF MEP AND NEW PLANS FOR FURTHER DIRECTION.
  - 3 REMOVE EXISTING CASEWORK, SHELVING, & RELATED COMPONENTS.
  - 4 REMOVE EXISTING SINK AND BASE. REF MEP FOR FURTHER DIRECTION ON PLUMBING. RETAIN TOILET ACCESSORIES TO BE REINSTALLED.
  - 5 REMOVE EXISTING LAB CASEWORK, SINKS, AND ALL RELATED FIXTURES. REF MEP FOR DIRECTION ON RELOCATION OR CAPPING OF WATER AND GAS LINES.
  - 6 RELOCATED EXISTING FIRE EXTINGUISHER AS SHOWN ON NEW PLANS AND ELEVATIONS.
  - 7 REMOVE EXISTING DOOR KNOB/HANDLE. REF DOOR HARDWARE SPECIFICATIONS FOR NEW HARDWARE AND DOOR FUNCTION.
  - 8 REMOVE EXISTING EYEWASH AND SHOWER UNIT. REF MEP FOR FURTHER DIRECTION ON CAPPING/REUSE OF WATER LINE.
  - 9 REMOVE EXISTING MARKERBOARDS/TACKBOARDS INCLUDING ADHESIVE AND BRACKETS.
  - 10 REMOVE EXISTING PROJECTION SCREEN AND PROJECTOR.
  - 11 EXISTING COUNTER TOP LAB EQUIPMENT TO BE RETURNED TO THE OWNER.
  - 12 REMOVE EXISTING RAIL OF COAT HOOKS & SUPPORTS.
  - 13 DEMO DISCONNECT PER MEP'S DIRECTIONS.
  - 14 REF SECTIONS AND DETAILS ON A001 FOR DIRECTION ON CUTTING NEW OPENING FOR WINDOW.

- CEILINGS**
- 1 REMOVE EXISTING LAY-IN ACOUSTICAL TILE, SUSPENSION SYSTEM, AND LIGHTING FIXTURES. EXISTING HANGER WIRE MAY BE REUSED FOR NEW SUSPENSION SYSTEM. REF MEP FOR ADDITIONAL DIRECTION ON FIXTURES AND CEILING DEVICES.
  - 2 REMOVE EXISTING PROJECTOR AND PROJECTION SCREEN. VERIFY W/ OWNER IF ITEMS SHALL BE RETURNED OR DISPOSED OF.
  - 3 REMOVE EXISTING ELEPHANT TRUNKS. REF MEP FOR FURTHER DIRECTION.
  - 4 REF MEP FOR DUCT/ ADDITIONAL DEMOLITION INSTRUCTIONS AT DEMOLISHED FUME HOOD.

- GENERAL**
- ALL TOILET ACCESSORIES (SOAP AND PAPER TOWEL DISPENSERS) TO BE REINSTALLED.
- ALL WAPs, CEILING MOUNTED CAMERAS, CLOCKS, AND FIRE PROTECTION DEVICES TO BE REINSTALLED.
- REFER TO MEP SHEETS FOR EXISTING PLUMBING, GAS, AND ELECTRICAL CONDUIT TO BE CAPPED
- ALL EXISTING FIRE EXTINGUISHERS TO REMAIN. REF PLANS AND ELEVATIONS FOR ITEMS TO BE RELOCATED.
- REPLACE ALL DAMAGED CEILING TILES IN AREAS WHERE CEILINGS ARE DISTURBED TO PERFORM OVERHEAD WORK.




**K1** Scale 1/8" = 1'-0" Level 2 - Demolition Ceiling Plan

PLAN NORTH TRUE NORTH

**K6** Scale Existing Images for Reference

PLAN NORTH TRUE NORTH



**A1** Scale 1/4" = 1'-0" Level 2 - Demolition

PLAN NORTH TRUE NORTH

we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1.816.442.7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1.720.949.1689  
HOLLISANDMILLER.COM

Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture # 02000161

RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #2014035826  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

Apex Engineers, Inc.  
Structural Engineer  
State Certificate of Authority # 2003004673  
1625 Locust St.  
Kansas City, MO 64108  
816.421.3222 phone

MCC Longview Community College Lab Refresh  
Metropolitan Community College  
500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

Construction Documents

REVISIONS:

#	Description	Date



JOB NO: 23011.00  
DRAWN BY: MC  
CHECKED BY: ARNY  
DATE: 10/06/2023

**A001**


### ABBREVIATIONS

<b>A</b>	ACT acoustical	<b>M</b>	MAS masonry
ADJ adjustable/adjacent	MATL material	MAX maximum	MEB markerboard
ALUM aluminum	MB mechanical	MEP mechanical/electrical/plumbing	MFR manufacturer
ALT alternate	MEP mechanical/electrical/plumbing	MIN minimum	MISC miscellaneous
ANOD anodized	MFR manufacturer	MO masonry opening	MTD mounted
APPROX approximate(ly)	MIN minimum	MISC miscellaneous	MTG HT mounting height
ARCH architect(ural)	MISC miscellaneous	MO masonry opening	MULL metal mullion
<b>B</b>	BLDG building	<b>N</b>	N north
BLKG blocking	BM beam	NIC not in contract	NO (#) number
BOB bottom of bearing	BRK bracket	NOM nominal	NRC noise reduction coefficient
BTM bottom	BSMT basement	NTS not to scale	
BTWN between			
<b>C</b>	CAB cabinet	<b>O</b>	OC on center
CC center to center	CEM cement(itious)	OD outside diameter	OTS open to structure
CG corner guard	CJ ceiling	OPNG opening	OPP opposite
CLG clear(ance)	CM construction manager		
CLR clear(ance)	CMU concrete masonry unit	<b>P</b>	PAR parallel
COL column	CONC concrete	PCP portland cement plaster	PERP perpendicular
CONC concrete	CONST construction continuous	PL plumbing	PLBG plumbing
CONT continuous	CTR center	PLYWD plywood	PNL panel
CY cubic yard(s)		PR pair	PREFAB prefabricated
		PTD painted	PVC polyvinyl chloride
<b>D</b>	DF drinking fountain	<b>R</b>	RAD radius
DIA diameter	DN down	RD roof drain	RE refer to
DIM dimension(s)	DSL downspout	REIN reinforcing (ed)	REV reversed
DSL downspout	DTL detail	REQD required	RFG roofing
DWG drawing			
		<b>S</b>	S south
<b>E</b>	EA east	SCHED schedule	SECT section
EA east	EF each face	SF square foot	SHT sheet
EFS exterior insulation finish system	EJ expansion joint	SHWR shower	SIM similar
EJ expansion joint	ELEC electrical	SPEC specification	SQ square
ELEC electrical	ELEV elevation	STL stainless steel	STC sound transmission coefficient
EQ equal	EQ EQUIP equipment	STD standard	STL steel
ETR existing to remain	EW each way	STRUCT structure(al)	SUSP suspend(ed)
EW each way	EXIST existing	SY square yard	SYM symmetrical
EXP expansion	EXT exterior		
EXT exterior		<b>T</b>	T&B top & bottom
		T&G tongue & groove	TO top of
<b>F</b>	FA fire alarm	TOC top of curb	TOM top of masonry
FD floor drain	FND foundation	TOS top of slab/steel	TOW top of wall
FND foundation	FE fire extinguisher	TS tube steel	TYP typical
FE fire extinguisher	FEC fire extinguisher cabinet		
FEC fire extinguisher cabinet	FF finish floor	<b>U</b>	U unless noted otherwise
FF finish floor	FH fire hose		
FH fire hose	FIN finish(ed)	<b>V</b>	VERT vertical
FIN finish(ed)	FIXT fixture	VTR vent thru roof	
FIXT fixture	FLR floor		
FLR floor	FLEX flexible	<b>W</b>	W west
FLEX flexible	FOM face of masonry	WD wood	WDO window
FOM face of masonry	FOPC face of precast	W with	W/O without
FOPC face of precast	FOS face of stud		
FOS face of stud	FT (') foot	<b>Y</b>	Y yard
FT (') foot	FTG footing		
FTG footing	FV field verify	<b>SYMBOLS</b>	/ per (or by)
FV field verify		& and	@ at
		[ channel	⊖ centerline
<b>G</b>	GA gauge	∅ diameter/round	± plus/minus
GALV galvanized	GC general contractor		
GC general contractor	GEN general		
GEN general	GL glass		
GL glass	GR grade		
GR grade	GYP gypsum		
GYP gypsum	GYP BD gypsum board		
GYP BD gypsum board			
<b>H</b>	HC handicapped		
HD head	HDWD hardwood		
HDWD hardwood	HDWR hardware		
HDWR hardware	HM hollow metal		
HM hollow metal	HORIZ horizontal		
HORIZ horizontal	HR hour		
HR hour	HT height		
HT height	HVAC heating, ventilation & air conditioning		
HVAC heating, ventilation & air conditioning			
<b>I</b>	ID inside diameter		
IN (") inches	INDIV individual		
INDIV individual	INFO information		
INFO information	INSUL insulation		
INSUL insulation	INT interior		
INT interior			
<b>J</b>	JST joist		
JT joist			
<b>K</b>	KIT kitchen		
<b>L</b>	LKR locker		
LKR locker	LT light		
LT light			

### SYMBOL LEGEND


	BRICK (in section)	Classroom	RM NAME
	CONCRETE MASONRY UNIT - CMU (in section)	A101	RM NUMBER
	CONCRETE (in section)		
	GYP BD (in section)	A123	DOOR NUMBER
	PLYWOOD (in section)	◊	WALL TYPE
	RIGID INSUL & EIFS (in section)	◊	FRAME TYPE
	BATT INSUL (in section)	1	GLASS TYPE
	ACOUSTICAL TILE (in section)	◊	SECTION CUT LINE
	STUCCO (in section)	◊	ELEVATION SYMBOL
	SOIL	◊	ELEV NUMBER SHEET NUMBER
	SAND	◊	ENLARGED DETAIL
	CONTINUOUS LUMBER	◊	Joist Bearing 100'-0"
	BLOCKING/SHIM	◊	DATUM MARKER
	FINISH LUMBER/HARDWOOD	◊	AREA "A"
	STEEL OR METAL	◊	AREA "B"
		●	MATERIAL JOINT
		◆	BUILDING EXPANSION JOINT

### WALL TYPE LEGEND




### KEYNOTES


04 20 00.A31	METAL DRIP EDGES
04 20 00.A39	WEEP HOLE/VENT
06 10 00.A22	PRESERVATIVE TREATED PLYWOOD BLOCKING
06 20 23.A03	MOLDINGS - TRANSPARENT
07 27 26.A03	TRANSITION MEMBRANE
07 62 00.A35	PRE-FINISHED MISC METAL FLASHING
07 92 00.A01	SEALANT
07 92 00.A02	SEALANT W/BACKER ROD
08 41 13.A01	THERMAL BROKEN STOREFRONT FRAMING (4.5")
08 41 13.A21	ALUMINUM SUBSILL
09 21 16.A01	NON-STRUCTURAL FRAMING
09 29 00.A02	GYPSUM BOARD - TYPE X
09 29 00.A06	MOLD AND MOISTURE RESISTANT GYPSUM BOARD
09 29 00.A10	CEMENTITIOUS BACKER UNITS
09 30 00.A01	TILE
09 51 13.A01	ACOUSTICAL CEILING PANELS




**N1** Scale 3" = 1'-0" Premanufactured Curb @ Single Ply Roof



**A1** Scale 3/4" = 1'-0" Wall Section @ New Window Opening



**E4** Scale 3" = 1'-0" Exterior Detail - Window Head @ New Opng



**A4** Scale 3" = 1'-0" Exterior Detail - Window Sill @ New Opng

we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1.816.442.7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1.720.949.1689  
HOLLISANDMILLER.COM

**RTM Engineering Consultants**  
MEPP Engineer  
State Certificate of Authority #2014035826  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

**Apex Engineers, Inc.**  
Structural Engineer  
State Certificate of Authority # 2003004673  
1625 Locust St.  
Kansas City, MO 64108  
816.421.3222 phone

**MCC Longview Community College Lab Refresh**  
Metropolitan Community College  
500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

REVISIONS:

#	Description	Date
1	City Comments	12/19/23

**SHEET NOTES**

- REFER TO SHEET G000 FOR SHEET INDEX
- DO NOT SCALE THIS DRAWING
- ALL NEW INTERIOR WALLS ARE WALL TYPE 13C UNLESS NOTED OTHERWISE.
- INTERIOR DIMENSIONS ARE TO THE FOLLOWING, UNLESS NOTED OTHERWISE:  
A. TO FACE OF STUD  
B. TO FACE OF MASONRY UNIT  
C. TO FACE OF DOOR AND WINDOW ROUGH OPENINGS
- COORDINATE LOCATIONS WHERE BACKING IS REQUIRED FOR WALL HUNG CASEWORK, MARKERBOARDS, WALL HUNG ACCESSORIES AND TECHNOLOGY
- "MIR" STANDS FOR MIRRORRED LAYOUT.
- COORDINATE WALL REPAIR AND INSTALLATION OF NEW DOORS AND WINDOWS WITH DEMOLITION SHEETS
- COORDINATE FINISHES TO REMAIN WITH DEMOLITION SHEET
- NEW STUDENT LAB CASEWORK AND DEMO STATION TO BE PLACED IN THE SAME LOCATION AS DEMOLISHED CASEWORK.



JOB NO: 23011.00  
DRAWN BY: MC  
CHECKED BY: ARNY  
DATE: 10/06/2023


**A101**

**SHEET KEYNOTE LEGEND**

- 09 51 13.A01 ACOUSTICAL CEILING PANELS
- 10 51 13.A02 WELDED CORRIDOR LOCKERS
- 11 53 13.A01 LABORATORY FUME HOODS
- 12 35 53.A04 LABORATORY COUNTERTOP
- 12 36 33.A01 EPOXY RESIN SINK
- 12 36 33.A08 EPOXY RESIN SINK





**MATH AND SCIENCE BUILDING**



- GENERAL NOTES:**
- FIELD VERIFY AND MATCH EXISTING CEILING HEIGHTS.
  - REINSTALL ALL EXISTING CEILING MOUNTED DEVICES U.N.O.
  - RE: MEP FOR ALL DEVICES TO BE DEMO'ED OR REINSTALLED.


**M1** Scale Level 2 - Partial Ceiling Plan  
1/8" = 1'-0"

PLAN NORTH TRUE NORTH




**J1** Scale Enlarged Plan - Student Station Top Typ Module  
1/2" = 1'-0"

**J6** Scale Enlarged Plan - Student Station ADA  
1/2" = 1'-0"



**A1** Scale Level 2 - Chem 201  
1/4" = 1'-0"

PLAN NORTH TRUE NORTH



**A10** Scale Interior Elevation - Corridor Lockers  
1/2" = 1'-0"

PLAN NORTH TRUE NORTH

REVISIONS:		
#	Description	Date
1	City Comments	12/19/23



JOB NO: 23011.00  
DRAWN BY: MC  
CHECKED BY: ARNY  
DATE: 10/06/2023

**A621**

**SHEET KEYNOTE LEGEND**


08 41 13.A01	THERMAL BROKEN STOREFRONT FRAMING (4.5")
09 65 13.A01	RESILIENT BASE
10 11 00.A02	MARKERBOARDS
10 11 00.A03	TACKBOARDS
10 11 00.A09	ELECTRONIC MARKERBOARDS
11 31 00.A10	ICEMAHER
11 53 13.A01	LABORATORY FUME HOODS
11 53 13.A04	FIRE BLANKET CABINET
11 53 13.A05	ACID/CORROSIVE STORAGE CABINET
11 53 13.A09	UPRIGHT ROD AND CROSS BAR ASSEMBLY
11 53 13.A15	SCIENCE DEMONSTRATION TABLE
11 53 13.A17	
12 30 00.A01	BASE CABINET
12 35 53.A01	PLASTIC LAMINATE LABORATORY CASEWORK
12 35 53.A02	
12 35 53.A04	LABORATORY COUNTERTOP
12 35 53.A09	ISLAND WORKSTATION
12 36 33.A01	EPOXY RESIN COUNTERTOP

**SHEET MATERIAL FINISH LEGEND**


ID	MATERIAL	COLOR/FINISH
P1	Paint	REPOSE GRAY SW7015
P2	Paint	BLUELOOD SW6966
P3	Paint	CAVIAR SW 6990
RB1	Resilient Base & Accessories	BLACK
T1	Tile	AZUR GLOSS

**SHEET NOTES**


- REFER TO SHEET G000 FOR SHEET INDEX
- COORDINATE LOCATIONS WHERE BACKING REQUIRED FOR WALL HUNG CASEWORK, MARKERBOARDS, AND TECHNOLOGY
- COLOR/MATERIAL TRANSITIONS ARE NOTED WHEN THEY DO NOT OCCUR AT INSIDE CORNERS
- ALL EXPOSED SURFACES TO BE FINISHED.
- ALL STUDENT STATIONS AND DEMO STATIONS TO BE WOOD LABORATORY CASEWORK. ALL PERIMETER CASEWORK TO BE WHITE METAL LABORATORY CASEWORK.
- ALL BACKSPLASH MATERIAL TO MATCH COUNTERTOP MATERIAL. UNO. ALL COUNTERTOPS TO BE EPOXY RESINOUS LAB COUNTERTOPS.
- PROVIDE 4" BACKSPLASH, UNO
- PROVIDE 1" OVERHANG AT ALL COUNTERTOPS, UNO
- PROVIDE ONE 2" DIAMETER GROMMET PER 30 INCH OF KNEE-SPACE AT COUNTERS - COORDINATE EXACT LOCATION WITH OWNER
- REFER TO PLUMBING DRAWINGS FOR LOCATIONS OF SINKS, GAS, AND OTHER PLUMBING FIXTURES LOCATED WITHIN CASEWORK
- ALL WOOD BASE CABINETS ARE TO BE 22 1/2" DEEP, UNO (STANDARD FOR BOD).
- ALL METAL BASE CABINETS ARE TO BE 22" DEEP, UNO (STANDARD FOR BOD).
- ALL UPPER CABINETS ARE TO BE 16" DEEP, UNO
- ALL TALL STORAGE AND WARDROBE CABINETS ARE TO BE 22" DEEP, UNO
- ALL SCIENCE CASEWORK TO HAVE LOCKS.
- PROVIDE WOOD CLEAT AT BACK AND SIDE WALLS OF ALL COUNTERTOPS WITH NO BASE CABINET BELOW.
- REFER TO MEP SHEETS FOR LOCATION DIAGRAM OF SWITCHES, THERMOSTATS, FIRE ALARM STROBES TO BE MOUNTED ADJACENT TO ENTRY DOORS OR AT OUTSIDE CORNERS WITHIN ROOMS
- COORDINATE WITH ELECTRICAL SHEETS FOR HEIGHT OF OUTLETS A.F.F. AND/OR ABOVE COUNTERTOPS
- COORDINATE WITH MECHANICAL SHEETS FOR LOCATIONS OF WALL MOUNTED GRILLES AND REGISTERS
- ALL FUME HOOD BASES TO BE PROVIDED BY FUME HOOD MANUF. FUME HOODS TO BE STANDARD GRAY.




**N1** Scale 1/2" = 1'-0"  
Interior Elevation - 201 North




**N11** Scale 1/2" = 1'-0"  
Interior Elevation - 201 East




**J1** Scale 1/2" = 1'-0"  
Interior Elevation - 201 West




**J12** Scale 1/2" = 1'-0"  
Interior Elevation - Prep 201C North




**E1** Scale 1/2" = 1'-0"  
Interior Elevation - 201 South




**A1** Scale 1/2" = 1'-0"  
Interior Elevation - Teacher's Demo Station



**A6** Scale 1/2" = 1'-0"  
Interior Elevation - Student Island Top



**A12** Scale 1/2" = 1'-0"  
Interior Elevation - Student Station 4 Top w/ ADA Station



**A16** Scale 1/2" = 1'-0"  
Interior Elevation - Station Chase

we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1 816-442-7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1 720-949-1689  
HOLLISANDMILLER.COM


RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #2014035826  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

Apex Engineers, Inc.  
Structural Engineer  
State Certificate of Authority # 2003004673  
1625 Locust St  
Kansas City, MO 64108  
816.421.3222 phone

MCC Longview Community College Lab Refresh  
Metropolitan Community College  
500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

REVISIONS:

#	Description	Date



JOB NO: 23011.00  
DRAWN BY: MC  
CHECKED BY: AR/NY  
DATE: 10/06/2023

**A681**

### MATERIAL FINISH LEGEND

MATERIAL	ID	KEYNOTE	MANUFACTURER	STYLE/MODEL NO	COLOR/FINISH	COMMENTS
Ceiling	CLG1	09 51 13.A01	ARMSTRONG	ULTIMA #1915, BEVELED, 86185	WHITE	24"X 48", TYPICAL, NRC .75. USE WITH 9/16" SUPERFINE SUSPENSION SYSTEM
Concrete Finish	CON1	03 30 00.A26	HI-TECH SYSTEMS, PROSOCO LS	HT SPALL-TX3; FOLLOWED BY CONSOLIDECK, POLISH GUARD & CONCRETE PROTECTOR SB	CLEAR	GROUT COAT WITH DENSIFIER AND SEALER
Paint	P1	09 91 23.A02	SHERWIN WILLIAMS	REFER TO MASTER SPEC	REPOSE GRAY SW7015	FIELD
Paint	P2	09 91 23.A02	SHERWIN WILLIAMS	REFER TO MASTER SPEC	BLUEBLOOD SW6966	ACCENT, TEACHING WALL
Paint	P3	09 91 23.A02	SHERWIN WILLIAMS	REFER TO MASTER SPEC	CAVIAR SW 6990	HOLLOW METAL DOORS AND FRAMES
Resilient Base & Accessories	RB1	09 65 13.A01	ROPPE	STANDARD TOE BASE	BLACK	4"
Tile	T1	09 30 00.A01	WOW CERAMIC TILE, VIRGINIA TILE	BEJMAT	AZUR GLOSS	5X15 cm (2"X6")

### ROOM FINISH SCHEDULE

NO	ROOM Name	FLOOR Finish	Base	WALLS				CEILING Finish	Finish Remarks
				North	East	South	West		
201	Chemistry Lab	CON1	RB1	P1	P1	P1	P2	CLG1	1
201A	Balance Room							CLG1	3
201B	Instru/ Comp Room							CLG1	3
201C	Stor/Prep			P1				CLG1	2

### DOOR SCHEDULE




Number	DOOR Size	Type	Glass	Frame		Fire Rating	Remarks
				Type	Material		
201	3'-0" x 7'-0" x 1 3/4"	--	--	--	HM	--	Existing, new HW
201A.1	3'-0" x 7'-0" x 1 3/4"	--	--	--	HM	--	Existing, new HW
201B	3'-0" x 7'-0" x 1 3/4"	--	--	--	HM	--	Existing, new HW
201C	3'-0" x 7'-0" x 1 3/4"	--	--	--	HM	--	Existing, new HW

REF SPEC 087100 FOR NEW DOOR HARDWARE SETS. NO OTHER CHANGES TO THE DOORS THEMSELVES.

### ROOM SCHEDULE REMARKS

- DOOR FRAMES TO BE PAINTED P3. REFINISH ALL WOOD DOORS WITH A CLEAR COAT. REF 099300.
- PATCH AND REFINISH WALL WHERE EXISTING FUME HOOD WAS REMOVED.
- CEILING WORK ONLY. RE: MEP FOR ADDITIONAL INFO.

- ### GENERAL FINISH NOTES
- REFER TO FINISH FLOOR PLANS, REFLECTED CEILING PLANS, ELEVATIONS, AND DETAILS FOR EXTENT OF MULTIPLE FINISHES.
  - DO NOT PAINT NATURAL OR MANUFACTURED STONE, BRICK, GLAZED BLOCK OR ANY OTHER PREFINISHED MATERIALS.
  - DO NOT PAINT ALUMINUM OR OTHER NON-FERROUS METALS THAT ARE PREFINISHED.
  - MATCH VERTICAL FINISH OF ALL INTERIOR GYPSUM BOARD SOFFITS TO HORIZONTAL FINISH AS NOTED ON RCP OR ROOM FINISH SCHEDULE, UNO.
  - PAINT ALL EXPOSED CEILINGS DESIGNATED AS 'OTS' AS INDICATED ON ROOM FINISH SCHEDULE. PAINTING INCLUDES, BUT IS NOT LIMITED TO: EXPOSED STRUCTURE, JOISTS, METAL DECKING, EXISTING TECTUM PANELS, DUCTWORK AND MECHANICAL EQUIPMENT.
  - PAINT ALL EXPOSED STEEL, UNO.
  - PAINT ALL INTERIOR HOLLOW METAL DOORS AND FRAMES COLOR P3, UNO.
  - PAINT OR FINISH THE FOLLOWING ITEMS TO MATCH ADJACENT PAINT OR FINISH:
    - ELECTRICAL PANELS IN FINISHED ROOMS
    - GRILLES, LOUVERS ETC. PRIMED OR SPECIFIED TO BE PAINTED
    - UNFINISHED SPEAKER OUTLET GRILLES
    - VISIBLE PORTIONS OF DUCTWORK AND MECH EQUIPMENT BEHIND VENTS, GRILLES AND DIFFUSERS



**hollis J. miller architects**

we design the future™

1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1.816.442.7100

115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1.720.949.1889

HOLLISANDMILLER.COM

Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture # 0000014

**RTM Engineering Consultants**  
MEPP Engineer  
State Certificate of Authority #  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

**Apex Engineers, Inc.**  
Structural Engineer  
#2003004673  
1625 LOUCST ST  
KANSAS CITY, MO 64108  
816.421.3222 phone  
www.apex-engineers.com

**APEX ENGINEERS, INC.**  
1625 LOUCST ST  
KANSAS CITY, MO 64108  
816.421.3222  
www.apex-engineers.com

**Metropolitan Community College - Longview**

**Metropolitan Community College**

2601 NE Barry Rd  
Kansas City, MO 64156

Construction Documents

Occupancy or Use

FLOOR DEAD LOADS  
FLOOR LIVE LOADS  
CLASSROOMS  
CORRIDORS ABOVE FIRST FLOOR  
FIRST-FLOOR CORRIDORS  
STAIRS AND EXIT WAYS  
ROOF DEAD LOADS  
TYPICAL ROOF  
ROOF LIVE LOADS  
ROOF AREAS NOT INTENDED FOR OCCUPANCY  
ROOF AREAS USED FOR ASSEMBLY PURPOSES  
ROOF AREAS USED FOR ASSEMBLY PURPOSES  
ROOF AREAS USED FOR OCCUPANTS  
ROOF AREAS USED FOR OTHER OCCUPANCIES  
ROOF FABRIC AWNINGS AND CANOPIES SUPPORTED BY A SKELETON STRUCTURE  
ROOF SCREEN ENCLOSURE SUPPORT FRAME

DRIFT DATA

COMMENTS	LOAD, P/sf	WIDTH, W'
	30.4 p/sf	7'-0"
TYPICAL FLOOR	127 p/sf	N/A
FLOOR LIVE LOADS	40 p/sf	1000 lbs
CLASSROOMS	80 p/sf	1000 lbs
CORRIDORS ABOVE FIRST FLOOR	100 p/sf	1000 lbs
FIRST-FLOOR CORRIDORS	100 p/sf	300 lbs
STAIRS AND EXIT WAYS	100 p/sf	300 lbs
TYPICAL ROOF	21 p/sf	N/A
ROOF LIVE LOADS	20 p/sf	N/A
ROOF AREAS NOT INTENDED FOR OCCUPANCY	100 p/sf	N/A
ROOF AREAS USED FOR ASSEMBLY PURPOSES	100 p/sf	N/A
ROOF AREAS USED FOR ASSEMBLY PURPOSES	100 p/sf	N/A
ROOF AREAS USED FOR OCCUPANTS	SAME AS OCCUPANCY SERVED	N/A
ROOF AREAS USED FOR OTHER OCCUPANCIES	SAME AS OCCUPANCY SERVED	N/A
ROOF FABRIC AWNINGS AND CANOPIES SUPPORTED BY A SKELETON STRUCTURE	5 p/sf	N/A
ROOF SCREEN ENCLOSURE SUPPORT FRAME	5 BASED ON TRIBUTARY AREA OF ROOF SUPPORTED BY THE FRAME MEMBER	200 lbs

\* ROOF: ALL OTHER CONSTRUCTION  
\* ROOF: ORDINARY FLAT, PITCHED, AND CURVED  
\* VEGETATIVE AND LANDSCAPED ROOFS

**REVISIONS:**

#	Description	Date

**SHEET LIST - STRUCTURAL**

SHEET NUMBER	SHEET NAME
S100	GENERAL NOTES AND SPECIFICATIONS
S200	RTU FRAMING
S500	TYPICAL STEEL DETAILS

STATE OF MISSOURI  
LOCALITY: MOBILE  
PROFESSIONAL ENGINEER  
NUMBER: 000200069  
10/06/23

10 Unlicensed Engineers and others in this state apply only to the extent and within the limits of their jurisdiction. This registration is not a license to practice and does not constitute an endorsement of any product or service. The engineer and the engineer's employer shall be responsible for any and all errors on these drawings.

JOB NO: 23011.00  
DRAWN BY: APEX  
CHECKED BY: AGK  
DATE: 10/06/23

**S100**

GENERAL NOTES AND SPECIFICATIONS

Please consider the environment before printing this.

**DESIGN INFORMATION**

**BUILDING CODE:**  
2018 INTERNATIONAL BUILDING CODE AS ADOPTED AND/OR AMENDED BY LOCAL BUILDING CODES

**WIND DESIGN DATA:**

WIND DESIGN DATA:	Main Building
OCCUPANCY CATEGORY	III
ULTIMATE WIND SPEED (3 SECOND GUST), V	115 mph
WIND EXPOSURE CATEGORY	C
VELOCITY PRESSURE, q <sub>s</sub>	30.0 p/sf
INTERNAL PRESSURE COEFFICIENT, GC <sub>p</sub>	+/-0.18

**WIND DESIGN COMPONENTS & CLADDING DATA:**

WIND DESIGN COMPONENTS & CLADDING DATA:	Main Building
EDGE REGION, a	8' - 1"

**WALL ZONES**

WALL ZONES	16 SF	20 SF	30 SF	50 SF	100 SF	200 SF
4 & 5	35 p/sf	34 p/sf	32 p/sf	30 p/sf	29 p/sf	29 p/sf
4	-38 p/sf	-37 p/sf	-35 p/sf	-33 p/sf	-32 p/sf	-32 p/sf
5	-47 p/sf	-44 p/sf	-40 p/sf	-37 p/sf	-34 p/sf	-34 p/sf
<b>ROOF ZONES</b>	<b>10 SF</b>	<b>20 SF</b>	<b>50 SF</b>	<b>100 SF</b>	<b>200 SF</b>	
All Zones	16 p/sf	16 p/sf	16 p/sf	16 p/sf	16 p/sf	
1	-32 p/sf	-32 p/sf	-32 p/sf	-32 p/sf	-28 p/sf	
2	-56 p/sf	-53 p/sf	-48 p/sf	-44 p/sf	-40 p/sf	
3	-74 p/sf	-70 p/sf	-63 p/sf	-59 p/sf	-54 p/sf	
4	-102 p/sf	-92 p/sf	-79 p/sf	-70 p/sf	-60 p/sf	
1' & 1' OH	-51 p/sf	-50 p/sf	-49 p/sf	-48 p/sf	-40 p/sf	
2 OH	-69 p/sf	-63 p/sf	-54 p/sf	-48 p/sf	-41 p/sf	
3 OH	-96 p/sf	-85 p/sf	-70 p/sf	-59 p/sf	-48 p/sf	

**SEISMIC DESIGN SITE DATA:**

SPECTRAL RESPONSE COEFFICIENTS	S <sub>0</sub> = 0.094
	S <sub>1</sub> = 0.068
SITE CLASS (ASSUMED)	D
DESIGN SPECTRAL RESPONSE ACCELERATIONS	S <sub>DS</sub> = 0.100
	S <sub>1</sub> = 0.109

**SEISMIC ANALYSIS PROCEDURE:** EQUIVALENT LATERAL FORCE

**SEISMIC DESIGN BUILDING DATA:** Main Building

LATERAL SYSTEM: B. BUILDING FRAME SYSTEMS, No. 2. STEEL SPECIAL CENTRICALLY BRACED FRAMES

**RESPONSE MODIFICATION, R** = 6.00


**DEF. AMPLIFICATION FACTOR, C<sub>d</sub>** = 5.00

**OVERSTRENGTH FACTOR, Q** = 2.00

**SEISMIC RESPONSE COEF., C<sub>s</sub>** = 0.021

**SEISMIC BASIC SHEAR, V** = 84.2 kip

**SEISMIC DESIGN CATEGORY** = III



**DRIFT DATA**

DRIFT DATA	LOAD, P/sf	WIDTH, W'
	30.4 p/sf	7'-0"

**DRIFT LOAD DATA:**

DRIFT LOAD DATA:	LOAD, P/sf	WIDTH, W'
	30.4 p/sf	7'-0"

**OCCUPANCY OR USE:**


OCCUPANCY OR USE:	LOAD, P/sf	POINT
FLOOR DEAD LOADS	127 p/sf	N/A
FLOOR LIVE LOADS	40 p/sf	1000 lbs
CLASSROOMS	80 p/sf	1000 lbs
CORRIDORS ABOVE FIRST FLOOR	100 p/sf	1000 lbs
FIRST-FLOOR CORRIDORS	100 p/sf	300 lbs
STAIRS AND EXIT WAYS	100 p/sf	300 lbs
TYPICAL ROOF	21 p/sf	N/A
ROOF LIVE LOADS	20 p/sf	N/A
ROOF AREAS NOT INTENDED FOR OCCUPANCY	100 p/sf	N/A
ROOF AREAS USED FOR ASSEMBLY PURPOSES	100 p/sf	N/A
ROOF AREAS USED FOR ASSEMBLY PURPOSES	100 p/sf	N/A
ROOF AREAS USED FOR OCCUPANTS	SAME AS OCCUPANCY SERVED	N/A
ROOF AREAS USED FOR OTHER OCCUPANCIES	SAME AS OCCUPANCY SERVED	N/A
ROOF FABRIC AWNINGS AND CANOPIES SUPPORTED BY A SKELETON STRUCTURE	5 p/sf	N/A
ROOF SCREEN ENCLOSURE SUPPORT FRAME	5 BASED ON TRIBUTARY AREA OF ROOF SUPPORTED BY THE FRAME MEMBER	200 lbs

\* ROOF: ALL OTHER CONSTRUCTION  
\* ROOF: ORDINARY FLAT, PITCHED, AND CURVED  
\* VEGETATIVE AND LANDSCAPED ROOFS

**SYMBOLS & ABBREVIATIONS**

SYMBOLS & ABBREVIATIONS	DETAIL ON SHEET	DETAILS, SECTIONS, AND ELEVATIONS
T.O.W. = XXX' - XX"	SHEET NUMBER	ELEVATIONS
B.O.W. = XXX' - XX"	ELEVATION (TOP)	FOUNDATION WALLS AND LEDGES (SIM)
T.O.X. = XXX' - XX"	ELEVATION (BOTTOM)	
XXX' - XX"	ELEVATION MARK	LEVELS, SPOT ELEVATIONS & PLAN ELEVATIONS
REVISION MARK		SHEET REVISIONS

ABV	DEFINITION	ABV	DEFINITION
ARCH	ARCHITECT	LLV	LONG LEG VERTICAL
BO	BOTTOM OF	LONG	LONGITUDINAL
BOF	BOTTOM OF FOOTING	MECH	MECHANICAL
BOB	BOTTOM OF STEEL	MEP	MECH. ELECTRICAL, PLUMBING
BOT   B	BOTTOM	MFR	MANUFACTURER
BOW	BOTTOM OF WALL	NA	NOT APPLICABLE
BRG	BEARING	NS	NEAR SIDE
CTR   C	CENTER	NTS	NOT TO SCALE
CGS	CENTER OF GRAVITY STRAND	OC	ON CENTER
CIP	CAST-IN-PLACE	OPP	OPPOSITE
CJ	CONTRACTION/CONTROL JOINT	PAP	POWDER ACTUATED FASTENER
CL	CENTERLINE	PARL	PARALLEL
CLR	CLEAR	PERP	PERPENDICULAR
COL	COLUMN	PI	POST-INSTALLED
CONT	CONTINUOUS	PT	POST-TENSION
DIA	DIAMETER	RAD	RADIUS
DT	DRAG TRUSS	REF	REFERENCE
EA	EACH	RTU	ROOF TOP UNIT
EL	ELEVATION	SM	SIMILAR
EOD	EDGE OF DECK	SGD	SLAB ON GRADE
EOR	ENGINEER OF RECORD	STD	STANDARD
EOS	EDGE OF STEEL	TJ	TOP
EQ	EQUAL	T&B	TOP AND BOTTOM
EW	EACH WAY	TO	TOP OF
[E]	EXISTING	TOC	TOP OF CONCRETE
EXT	EXTERIOR	TOF	TOP OF DECK
FS	FACE SIDE	TOF	TOP OF FOOTING
FRT	FIRE RETARDANT TREATED	TOL	TOP OF LEDGE
FV	FIELD VERIFY	TOM	TOP OF MASONRY
GA	GAUGE	TOS	TOP OF STEEL
GC	GENERAL CONTRACTOR	TOW	TOP OF WALL
GT	GRIDDER TRUSS	TR	TREATED
H&S	HEADED ANCHOR STUD	TRANS	TRANSVERSE
HORIZ	HORIZONTAL	TY	TYPICAL
INT	INTERIOR	UNO	UNLESS NOTED OTHERWISE
ISO	ISOMETRIC	VERT	VERTICAL
LHL	LONG LEG HORIZONTAL	WP	WORK POINT



**MATERIAL SPECIFICATIONS**

MATERIAL	STEEL MATERIAL SPECIFICATIONS	SPECIFICATION
WIDE FLANGE SHAPES (W)		ASTM A992
CHANNELS (C), ANGLES (L)		ASTM A36
PLATES		ASTM A36
HOLLOW STRUCTURAL SHAPES (HSS)		ASTM A500, GRADE C
HEADED ANCHOR STUDS		AWG D1.1 TYPE B / ASTM A29
HIGH STRENGTH BOLTS		ASTM F1554, GRADE A325
ANCHOR BOLTS (HEX-HEAD UNO)		ASTM F1554 (65 KSI) "S1"
EPOXY ANCHOR RODS		ASTM A36
POWDER-ACTUATED FASTENERS		HLLT 0.157" DIA X 4" OR SIMPSON 0.157" DIA PAPA
STEEL DECK, PLAIN STEEL		ASTM A1008, (33 ksi)
STEEL DECK, GALVANIZED		ASTM A653, (33 ksi)
NON-SHRINK GROUT, COLUMN BASES		5000 psi (28 DAY STRENGTH)

**STATEMENT OF SPECIAL INSPECTION**

IBC CODE REFERENCE	CONSTRUCTION TYPE	FREQUENCY CONT.	PER.
1705.2	STEEL CONSTRUCTION		
1705.2.1	STRUCTURAL STEEL		

1. SPECIAL INSPECTION FOR STRUCTURAL STEEL SHALL BE IN ACCORDANCE WITH THE QUALITY ASSURANCE INSPECTION REQUIREMENTS OF AISC 310. (REFER TO AISC CHARTS ON THIS SHEET)

1705.2.2 COLD-FORMED STEEL DECK

1. SPECIAL INSPECTIONS AND QUALIFICATIONS OF WELDING SPECIAL INSPECTORS FOR COLD-FORMED STEEL FLOOR AND ROOF DECK SHALL BE IN ACCORDANCE WITH THE QUALITY ASSURANCE INSPECTION REQUIREMENTS OF SDCI QAQC. (REFER TO SDCI CHARTS ON THIS SHEET)

1705.2.3 OPEN-WEB STEEL JOIST AND JOIST GIRDERS

1. INSTALLATION OF OPEN-WEB STEEL JOISTS AND JOIST GIRDERS:

DESCRIPTION	QC	QA
A. END CONNECTIONS - WELDING OR BOLTED		X
B. BRIDGING - HORIZONTAL OR DIAGONAL		X
1. STANDARD BRIDGING		X
2. BRIDGING THAT DIFFERS FROM THE SJI SPECIFICATIONS LISTED IN SECTION 2207.1		X

**AISC TABLE N5.4-1**

**INSPECTION TASKS PRIOR TO WELDING**

INSPECTION TASKS PRIOR TO WELDING	QC	QA
1. WELDING PROCEDURE SPECIFICATIONS (WPSs) AVAILABLE	P	P
2. MANUFACTURER CERTIFICATIONS FOR WELDING CONSUMABLES AVAILABLE	P	P
3. MATERIAL IDENTIFICATION (TYPE/GRADE)	O	O
4. WELDER IDENTIFICATION SYSTEM	O	O
5. FIT-UP OF GROOVE WELDS (INCLUDING JOINT GEOMETRY)		
6. JOINT PREPARATION		
7. DIMENSIONS (ALIGNMENT, ROOT OPENING, ROOT FACE, BEVEL)	O	O
8. CLEANLINESS (CONDITION OF STEEL SURFACES)		
9. TACKING (TACK WELD QUALITY AND LOCATION)		
10. BACKING TYPE AND FIT (IF APPLICABLE)		
11. CONFIGURATION AND FINISH OF ACCESS HOLES	O	O
12. IDENTIFICATION OF FILLET WELDS		
13. DIMENSIONS (ALIGNMENT, GAPS AT ROOT)	O	O
14. CLEANLINESS (CONDITION OF STEEL SURFACES)		
15. TACKING (TACK WELD QUALITY AND LOCATION)		
16. CHECK WELDING EQUIPMENT	O	-

\* THE FABRICATOR OR ERECTOR, AS APPLICABLE, SHALL MAINTAIN A SYSTEM BY WHICH A WELDER WHO HAS WELDED A JOINT OR MEMBER CAN BE IDENTIFIED. STAMPS, IF USED, SHALL BE THE LOW-STRESS TYPE.

**AISC TABLE N5.4-2**

**INSPECTION TASKS DURING WELDING**

INSPECTION TASKS DURING WELDING	QC	QA
1. USE OF QUALIFIED WELDERS	O	O
2. CONTROL AND HANDLING OF WELDING CONSUMABLES		
3. PACKAGING	O	O
4. EXPOSURE CONTROL		
5. NO WELDING OVER CRACKED TACK WELDS	O	O
6. ENVIRONMENTAL CONDITIONS	O	O
7. WIND SPEED WITHIN LIMITS	O	O
8. PRECIPITATION AND TEMPERATURE	O	O
9. WPS FOLLOWED		
10. SETTINGS ON WELDING EQUIPMENT		
11. TRAVEL SPEED		
12. SELECT WELDING MATERIALS	O	O
13. SHIELDING GAS TYPE/FLOW RATE		
14. PREHEAT APPLIED		
15. INTERPASS TEMPERATURE MAINTAINED (MIN./MAX.)		
16. PROPER POSITION (F, V, H, OH)		
17. WELDING TECHNIQUES		
18. INTERPASS AND FINAL CLEANING	O	O
19. EACH PASS WITHIN PROFILE LIMITATIONS		
20. EACH PASS MEETS QUALITY REQUIREMENTS		

**AISC TABLE N5.4-3**

**INSPECTION TASKS AFTER WELDING**

INSPECTION TASKS AFTER WELDING	QC	QA
1. WELDS CLEANED	O	O
2. SIZE, LENGTH AND LOCATION OF WELDS	P	P
3. WELDS MEET VISUAL ACCEPTANCE CRITERIA		
4. CRACK PROHIBITION		
5. WELD/BASE-METAL FUSION	P	P
6. CRATER CROSS SECTION		
7. WELD PROFILES		
8. WELD SIZE		
9. UNDERCUT		
10. POROSITY		
11. ARC STRIKES	P	P
12. K-AREA <sup>1</sup>	P	P
13. BACKING REMOVED AND WELD TABS REMOVED (IF REQUIRED)	P	P
14. REPAIR ACTIVITIES	P	P
15. DOCUMENT ACCEPTANCE OR REJECTION OF WELDED JOINT OR MEMBER	P	P

\* WHEN WELDING OF DOUBLER PLATES, CONTINUITY PLATES OR STIFFENERS HAS BEEN PERFORMED IN THE K-AREA, VISUALLY INSPECT THE WEB K-AREA FOR CRACKS WITHIN 3 IN. (75 MM) OF THE WELD

**AISC TABLE N5.6-1**

**INSPECTION TASKS PRIOR TO BOLTING**

INSPECTION TASKS PRIOR TO BOLTING	QC	QA
1. MANUFACTURER'S CERTIFICATIONS AVAILABLE FOR FASTENER MATERIALS	O	P
2. FASTENERS MARKED IN ACCORDANCE WITH ASTM REQUIREMENTS	O	O
3. PROPER FASTENERS SELECTED FOR THE JOINT DETAIL (GRADE, TYPE, BOLT LENGTH IF THREADS ARE TO BE EXCLUDED FROM SHEAR PLANE)	O	O
4. PROPER BOLTING PROCEDURE SELECTED FOR JOINT DETAIL	O	O
5. CONNECTING ELEMENTS, INCLUDING THE APPROPRIATE FINISH SURFACE CONDITION AND HOLE PREPARATION, IF SPECIFIED, MEET APPLICABLE REQUIREMENTS	O	O
6. PRE-INSTALLATION VERIFICATION TESTING BY INSTALLED PERSONNEL OBSERVED AND DOCUMENTED FOR FASTENER ASSEMBLIES AND METHODS USED	P	O
7. PROPER STORAGE PROVIDED FOR BOLTS, NUTS, WASHERS AND OTHER FASTENER COMPONENTS	O	O

**AISC TABLE N5.6-2**

**INSPECTION TASKS DURING BOLTING**

INSPECTION TASKS DURING BOLTING	QC	QA
1. FASTENER ASSEMBLIES, OF SUITABLE CONDITION, PLACED IN ALL HOLES AND WASHERS (IF REQUIRED) ARE POSITIONED AS REQUIRED	O	O
2. JOINT BROUGHT TO THE SNUG-TIGHT CONDITION PRIOR TO THE PRETENSIONING OPERATION	O	O
3. FASTENER COMPONENT NOT TURNED BY THE WRENCH PREVENTED FROM ROTATING	O	O
FASTENERS ARE PRETENSIONED IN ACCORDANCE WITH THE RCSC SPECIFICATION, PROGRESSING SYSTEMATICALLY FROM THE MOST RIGID POINT TOWARD THE FREE EDGES	O	O

**AISC TABLE N5.6-3**

**INSPECTION TASKS AFTER BOLTING**

INSPECTION TASKS AFTER BOLTING	QC	QA
1. DOCUMENT ACCEPTANCE OR REJECTION OF BOLTED CONNECTIONS	P	P

**AISC TABLE N6.1**

**INSPECTION OF STEEL ELEMENTS OF COMPOSITE CONSTRUCTION PRIOR TO CONCRETE PLACEMENT**

INSPECTION OF STEEL ELEMENTS OF COMPOSITE CONSTRUCTION PRIOR TO CONCRETE PLACEMENT	QC	QA
1. PLACEMENT AND INSTALLATION OF STEEL DECK	P	P
2. PLACEMENT AND INSTALLATION OF STEEL HEADED STUD ANCHORS	P	P
3. DOCUMENT ACCEPTANCE OR REJECTION OF STEEL ELEMENTS	P	

we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1 816.442.7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1 720.949.1689  
HOLLISANDMILLER.COM

Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture #02000161

RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

Apex Engineers, Inc.  
Structural Engineer  
#2003004673  
1625 Locust St.  
Kansas City, MO 64108  
816.421.3222 phone  
www.apex-engineers.com



Metropolitan Community College - Longview  
Metropolitan Community College  
2601 NE Barry Rd  
Kansas City, MO 64156

REVISIONS:

#	Description	Date



No professional Engineer seal shall be used unless the seal is in full compliance with the laws of the State of Missouri. The seal is the property of the State of Missouri and shall not be used for any other purpose. The seal is the property of the State of Missouri and shall not be used for any other purpose.

JOB NO: 23011.00  
DRAWN BY: Author  
CHECKED BY: Checker  
DATE: 10/06/23

**S200**

RTU FRAMING



**PLAN NOTES - STEEL ROOF FRAMING**

- FIELD VERIFY TOP OF STEEL ELEVATIONS TO PROVIDE MINIMUM 12" CLEARANCE BETWEEN NEW FRAME AND ROOF MEMBRANE.
- BEAMS SHALL NOT BE CAMBERED UNLESS INDICATED IN BEAM CALLOUT.

**SCHEDULE - CAP PLATES**

- NOTES:
- BOLT SIZE NOTE: FOR BEAMS WITH A FLANGE WIDTH LESS THAN 5", 5/8" BOLTS MAY BE USED FOR DETAILING TOLERANCES.
  - b = WIDTH OF BEAM FLANGE.
  - D = VARIES, COORDINATE WITH BEAM FLANGE WIDTH.
  - W = JOIST GIRDER SEAT WIDTH PLUS 1" FOR FILLET WELD CONNECTION. VERIFY SEAT WIDTH WITH JOIST SUPPLIER PRIOR TO FABRICATION.
  - VERIFY BOLT PLACEMENT WITH JOIST SUPPLIER.

PLATE TYPE	SHAPE	PLATE THICKNESS	BOLT SIZE
A	1	1/2"	3/4"



we design the future<sup>®</sup>  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1.816.442.7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1.720.949.1689  
HOLLISANDMILLER.COM

RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

Apex Engineers, Inc.  
Structural Engineer  
#2003004673  
1625 Locust St  
Kansas City, MO 64108  
816.421.3222 phone



Metropolitan Community College - Longview  
Metropolitan Community College  
2601 NE Barry Rd  
Kansas City, MO 64156

Construction Documents


REVISIONS:

#	Description	Date




JOB NO: 23011.00  
DRAWN BY: APEX  
CHECKED BY: LKC  
DATE: 10/06/23

**S500**



**4** 3/8" SINGLE PLATE CONNECTION - BEAM TO HSS COLUMN  
S500 | 3/4" = 1'-0"



**3** 3/8" SINGLE PLATE CONNECTION - PLATE WELD CONNECTION  
S500 | 1" = 1'-0"


**2** 3/8" SINGLE PLATE 3/4" BOLT CONNECTION - SHEAR TAB DIMENSIONS  
S500 | 1" = 1'-0"

**SCHEDULE - 3/8" PLATE CONNECTION**


NOMINAL BEAM DEPTH, d	NUMBER OF 3/4" DIA A325N BOLTS
8" - 10"	2
12" - 14"	3
16"	4
18"	5
21"	6
24"	7

NOTES:  
1. d = DEPTH OF THE CARRIED BEAM.  
2. LISTED NUMBER OF BOLTS ARE APPLICABLE TO SIMPLE SHEAR CONNECTIONS DEFINED AS "CONVENTIONAL CONFIGURATION" PER ALSO STEEL CONSTRUCTION MANUAL CHAPTER 10. INCLUDED SUPPLEMENTAL DETAILS SPECIFY REQUIRED DIMENSIONAL REQUIREMENTS TO MEET THIS CONNECTION TYPE AND SHALL BE FOLLOWED FOR USE OF THIS TABLE.  
3. TYPICAL SINGLE PLATE CONNECTIONS AS SPECIFIED BY THIS TABLE AND SUPPORTING TYPICAL DETAILS ARE UNO BY PLAN NOTES OR SPECIFIC CUT DETAILS ON PLAN, SECTION, ETC.  
4. IT IS THE RESPONSIBILITY OF THE CONTRACTOR AND/OR FABRICATOR TO CONTACT THE EOR IF BEAM TO SUPPORT DIMENSION CONSTRAINTS DO NOT MEET TYPICAL SINGLE PLATE CONNECTION CRITERIA FOR ALTERNATE CONNECTION INFORMATION.


**1** 3/8" SINGLE PLATE 3/4" BOLT CONNECTION - BOLT SCHEDULE  
S500 | 12" = 1'-0"




**7** 3/8" SINGLE PLATE CONNECTION - BEAM TO GIRDER  
S500 | 3/4" = 1'-0"




**6** TYP STEEL BEAM TO STEEL HSS COLUMN CONNECTION  
S500 | 3/4" = 1'-0"




**5** 3/8" SINGLE PLATE 3/4" BOLT CONNECTION - TYPICAL BEAM COPE  
S500 | 1" = 1'-0"




**11** POST BEARING ON BEAM  
S500 | 3/4" = 1'-0"




**10** TYPICAL JOIST REINFORCEMENT DETAIL  
S500 | 3/4" = 1'-0"




**9** TYPICAL METAL DECK OPENING  
S500 | 3/4" = 1'-0"



**8** TYPICAL COLUMN CAP PLATE  
S500 | 3/4" = 1'-0"



**13** STEEL ANGLE BRACE CONNECTION INTO BEAM WEB  
S500 | 3/4" = 1'-0"



**12** STEEL ANGLE BRACE CONNECTION INTO BEAM WEB  
S500 | 3/4" = 1'-0"




we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1.816.442.7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1.720.949.1689  
HOLLISANDMILLER.COM

Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture # 02000161


RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

Apex Engineers, Inc.  
Structural Engineer  
State Certificate of Authority #  
1625 Locust St.  
Kansas City, MO 64108  
816.421.3222 phone

- GENERAL NOTES:**  
REFER TO SHEET ME100 FOR GENERAL NOTES.
- PLAN HEX NOTES:**
- 0.5" DI UP, ROUTE EXISTING TO CENTER OF SINK
  - 2.0" WASTE UP TO ACID REDUCER
  - 3.0" WASTE UP TO SERVE FINISH FLOOR GRADE CLEANOUT
  - 0.5" CW UP TO SERVE SINK
  - 0.5" HW UP TO SERVE SINK
  - 2.0" WASTE UP TO SERVE TRAPPED FLOOR SINK
  - 3.0" WASTE UP TO TRAPPED FLOOR DRAIN
  - 0.75" CW UP TO SERVE MIXING VALVE FOR EYE WASH SHOWER
  - 0.75" HW UP TO SERVE MIXING VALVE FOR EYE WASH SHOWER
  - 0.5" CW UP TO SERVE CHEMISTRY HOOD SINK
  - 0.5" NATURAL GAS UP TO SERVE CHEMISTRY HOOD TURRET
  - 2.0" WASTE UP TO SERVE SINK
  - 2.0" CIRCUIT VENT UP
  - 0.5" CW UP TO SERVE ICE MACHINE
  - 0.5" CW UP TO SERVE LAB STATION
  - 0.5" HW UP TO SERVE LAB STATION
  - REMOVE PORTION OF EXISTING PIPING AND ALL ASSOCIATED HANGERS, INSULATION, ETC. FIELD VERIFY EXISTING SIZE, ELEVATION, LOCATION, ETC.
  - 0.75" CW UP TO SERVE LAB STATION SINKS
  - 0.75" HW UP TO SERVE LAB STATION SINKS
  - 0.5" NATURAL GAS UP TO SERVE LAB STATION TURRET
  - 1.5" VENT UP



2  
P101  
**FIRST FLOOR PLUMBING PLAN**  
SCALE: 1/4" = 1'-0"



1  
P101  
**FIRST FLOOR PLUMBING PLAN**  
SCALE: 1/4" = 1'-0"

MCC Longview Community College Lab Refresh  
Metropolitan Community College

500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

100% Construction Documents

REVISIONS:

#	Description	Date



JOB NO: 23011.00  
DRAWN BY: MAO  
CHECKED BY: KEH  
DATE: 10/06/2023

P101

we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1 816.442.7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1 720.949.1689  
HOLLISANDMILLER.COM

Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture # 0000161

RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone


Apex Engineers, Inc.  
Structural Engineer  
State Certificate of Authority #  
1625 Locust St.  
Kansas City, MO 64108  
816.421.3222 phone

**GENERAL NOTES:**


REFER TO SHEET ME100 FOR GENERAL NOTES.

**PLAN HEX NOTES:**

- 1 1.5" VENT UP, 2.00" WASTE DOWN, ROUTE WASTE TO ACID REDUCER FROM SINK
- 2 0.5" CW DOWN TO SERVE CHEMISTRY HOOD SINK
- 3 0.5" NATURAL GAS UP TO SERVE CHEMISTRY HOOD TURRET
- 4 1.5" VENT DOWN
- 5 0.5" CW, 0.5" HW DOWN TO SERVE LAB STATION
- 6 0.5" NATURAL GAS DOWN TO SERVE LAB STATION
- 7 2.0" WASTE DOWN
- 8 2.0" WASTE DOWN, ROUTE TO ACID REDUCER FROM SINK
- 9 2.0" VENT UP
- 10 0.5" CW, 0.5" HW DOWN TO SERVE EYE WASH STATION MIXING VALVE TO REMAIN
- 11 0.5" CW UP TO SERVE ICE MACHINE
- 12 0.5" TEMPERED WATER DOWN TO SERVE EYE WASH STATION ROUTE TO MIXING VALVE
- 13 4.00" WASTE DOWN
- 14 REMOVE EXISTING SINK AND ALL ASSOCIATED PIPING, FAUCETS, ETC. PREPARE FOR REPLACEMENT SINK PER IMPROVEMENT PLANS
- 15 REMOVE EXISTING GAS TURRETS AND ASSOCIATED PIPING TO BELOW FLOOR. MAINTAIN EXISTING EMERGENCY GAS SHUT-OFF SOLENOID.
- 16 INSTALL MIXING VALVE ABOVE ACCESSIBLE CEILING
- 17 0.75" CW, 0.75" HW DOWN TO SERVE LAB STATION SINKS, 0.5" PIPE TO EACH CONNECTION
- 18 0.5" NATURAL GAS DOWN TO SERVE LAB STATION TURRET
- 19 REMOVE NEUTRALIZATION BASIN AND ALL ASSOCIATED PIPING
- 20 EXISTING GAS SHUT-OFF SHALL REMAIN WITH REVISION OF GAS PIPING



**2 SECOND FLOOR PLUMBING DEMOLITION PLAN**  
SCALE: 1/4" = 1'-0"



**1 SECOND FLOOR PLUMBING PLAN**  
SCALE: 1/4" = 1'-0"

MCC Longview Community College Lab Refresh  
Metropolitan Community College

500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

100% Construction Documents

REVISIONS:

#	Description	Date



JOB NO: 23011.00  
DRAWN BY: MAO  
CHECKED BY: KEH  
DATE: 10/06/2023

**P102**

### PLUMBING FIXTURE SCHEDULE

PLAN MARK	DESCRIPTION	MANUFACTURER	MODEL	TRIM	CONNECTION SIZES				NOTES
					CW (IN)	HW (IN)	W (IN)	V (IN)	
P1	LAB SINK	REFER TO ARCHITECTURAL PLANS	EPOXY INTEGRAL WITH COUNTERTOP	FAUCET: (2) CHICAGO FAUCETS 900 SERIES LAB, 895-3170N2B7E7CP, DECK MOUNTED 4" CENTER SET, 6" RIDGID GOOSENECK SPOUT WITH ATMOSPHERIC VACUUM BREAKER, (1) REMOVABLE LABORATORY NOZZLE FOR LAB HOSE AND (1) VACUUM PUMP ASPIRATOR/AERATORS SHALL BE INTERCHANGEABLE. 4" WRISTBLADE HANDLE, GRID STRAINER.	0.5	0.5	2	1.5	FAUCET HOLES TO MATCH FAUCET SPECIFIED. COORDINATE WITH COUNTERTOP SUPPLIER NUMBER OF HOLES. PROVIDE POINT OF USE NEUTRALIZATION BASIN AT EACH SINK - STRIEM LB-2'S
P2	ADA LAB SINK	REFER TO ARCHITECTURAL PLANS	EPOXY INTEGRAL WITH COUNTERTOP	FAUCET: (2) CHICAGO FAUCETS 900 SERIES LAB, 895-3170N2B7E7CP, DECK MOUNTED 4" CENTER SET, 6" RIDGID GOOSENECK SPOUT WITH ATMOSPHERIC VACUUM BREAKER, (1) REMOVABLE LABORATORY NOZZLE FOR LAB HOSE AND (1) VACUUM PUMP ASPIRATOR/AERATORS SHALL BE INTERCHANGEABLE. 4" WRISTBLADE HANDLE, GRID STRAINER.	0.5	0.5	2	1.5	FAUCET HOLES TO MATCH FAUCET SPECIFIED. COORDINATE WITH COUNTERTOP SUPPLIER NUMBER OF HOLES. PROVIDE POINT OF USE NEUTRALIZATION BASIN AT EACH SINK - STRIEM LB-2'S
P3	CHEMISTRY HOOD LAB SINK	LABCONCO	OVVAL CUPSINK	FAUCET: CHICAGO FAUCETS 900 SERIES LAB, 895-3170N2B7E7CP, DECK MOUNTED 4" CENTER SET, 6" RIDGID GOOSENECK SPOUT WITH ATMOSPHERIC VACUUM BREAKER, (1) REMOVABLE LABORATORY NOZZLE FOR LAB HOSE, 4" WRISTBLADE HANDLE, GRID STRAINER.	0.5	0.5	2	1.5	FAUCET HOLES TO MATCH FAUCET SPECIFIED. PROVIDE POINT OF USE NEUTRALIZATION BASIN AT EACH SINK - STRIEM LB-2'S
P4	RECESSED SAFETY STATION WITH DRAIN PAN, SURFACE MOUNTED	Guardian Equipment	GBF2173	RECESSED SAFETY STATION SURFACE MOUNTED WITH DRAIN AND WALL MOUNTED EXPOSED SHOWER HEAD. PROVIDE WITH EMERGENCY THERMOSTATIC MIXING VALVE TO MEET ANSI Z358.1 REQUIREMENTS.	-	-	-	-	EMERGENCY SHOWER/ EYEWASH SHALL BE APPROVED AND INSTALLED PER ACCESSIBILITY.
P5	2 STATION HAND WASHING TROUGH SINK	ELKAY	EWMAAR20C	FAUCET: (2) CHICAGO MODEL 631-1N2CABCP, 3" GOOSENECK SPOUT WITH 1.5 GPM FLOW CONTROL, 4" WRISTBLADE HANDLE WALL MOUNTED POLISHED CHROME. PROVIDE ASSE. 10/8" MIXING VALVE SET TO 105°F IF NOT INTEGRAL TO FAUCET. GRID STRAINER. COORDINATE WITH SINK MANUFACTURER OF LOCATING A 3RD HOLE FOR DI WATER LOCATION.	-	-	-	-	FAUCET HOLES TO MATCH FAUCET SPECIFIED. FIXTURE ASSEMBLY MUST BE APPROVED BY AND INSTALLED PER BUILDING CODE ACCESSIBLE REQUIREMENTS. PROVIDE INSULATION KIT ON ALL ACCESSIBLE FIXTURES WITH EXPOSED TRAP AND SUPPLIES.
P6	LABORATORY GAS TURRET	T&S BRASS AND BRONZE WORKS, INC.	BL-4200-6	POLISHED CHROME PLATED BRASS BODY, SERRATED TIP OUTLETS AT 90 DEGREES AND 3/8" NPT FEMALE INLET	-	-	-	-	
P7	ICE MAKER VALVE BOX	GLY GRAY	BM875	0.25" OUTLET, COMPRESSION ANGLE VALVE, 20 GAUGE UNPAINTED STEEL BOX	0.5	-	-	-	

### DRAINAGE PIPE SPECIALTY SCHEDULE

PLAN MARK	DESCRIPTION	MANUFACTURER	MODEL	TRIM	NOTES
FD-C	NEUTRALIZATION TANK FOR ADA SINK 7" ROUND FLOOR DRAIN	STRIEM	LB-2-ADA 3020-F-C	NICKEL BRONZE TOP, NICKEL BRONZE STRAINER, NICKEL BRONZE SEEPAGE CONTROL FLANGE, DEEP SEAL TRAP AND ACID-RESISTANT COATING.	DRAIN SIZE SHALL MATCH SANITARY BRANCH SERVING DRAIN. REFERENCE PLANS FOR SIZE.
FFCO	FINISHED FLOOR CLEANOUT	J.R. SMITH	4023	HARD FLOOR: ROUND CHROME PLATED SCOTATED COVER, CARPET AREAS: NICKEL BRONZE TOP AND CARPET CLAMP OR CARPET MARKER.	VERIFY FLOOR MATERIALS USED FROM ARCHITECTURAL PLANS. CLEANOUT TO BE FULL SIZE OF SOIL PIPE UP TO AND INCLUDING 4-INCH ID. REFERENCE PLANS FOR SOIL PIPE SIZE.
F-S-C	FLOOR SINK	J.R. SMITH	2450	ACID RESISTANT COATING, SEEPAGE CONTROL FLANGE, REMOVAL STRAINER, 10" DEEP BODY.	DRAIN SIZE SHALL MATCH SANITARY BRANCH SERVING DRAIN. REFERENCE PLANS FOR SIZE.
NTS	NEUTRALIZATION TANK	STRIEM	LB-2-ADA	POINT OF USE NEUTRALIZATION BASIN AT EACH SINK.	
WCO	WALL CLEANOUT	J.R. SMITH	4532 WITH CLEANOUT PLUG OR 4512 WITH COUNTERSINK PLUG	PROVIDE CLEANOUT PLUG AND STAINLESS STEEL ACCESS COVER IN FINISHED AREAS. PROVIDE COUNTER SINK PLUG IN UNFINISHED AREAS.	CLEANOUT TO BE FULL SIZE OF SOIL PIPE UP TO AND INCLUDING 4-INCH ID. REFERENCE PLANS FOR SOIL PIPE SIZE.

### PIPE MATERIAL SCHEDULE

SYSTEM	SIZE	TYPE	PIPING				FITTINGS		MAX. WORKING		FIELD TEST		DESIGN NOTES (HIDE)
			SCHEDULE	GRD	ASTM	MATERIAL	MATERIAL	TYPE	PRESS. (PSI)	TEMP. (°F)	PRESS. (PSI)	TIME	
DOMESTIC WATER ABOVE GRADE	ALL	L	-	-	B88	CP	CP	SJ	120	40-180	150	1 HR	DOMESTIC WATER ABOVE GRADE
DOMESTIC WATER BELOW GRADE	ALL	K	-	-	B88	CP	CP	SJ	120	40-180	150	1 HR	DOMESTIC WATER BELOW GRADE
TEMPERATURE & PRESSURE RELIEF DRAIN	ALL	M	-	-	B88	CP	CP	DRS	10.8	140-210	10.8	1 HR	TEMPERATURE & PRESSURE
NATURAL GAS ABOVE GRADE	0.5", 2.5"	OW	40	A	A53	CSBLK	MI	THRD	1	-	100	1 HR	NATURAL GAS ABOVE GRADE
ACID WASTE & VENT ABOVE GRADE (IN RETURN AIR PLENUMS)	ALL	DWV	40	-	F1673	PVDF	PVDF	DRSF	10 FT	50-180	10 FT	1 HR	ACID WASTE & VENT ABOVE GRADE. ACID WASTE & VENT PIPING SHALL BE NON-COMBUSTIBLE AND LISTED & LABELED TO HAVE A FLAME SPREAD INDEX OF NOT MORE THAN 25 AND A SMOKE DEVELOPED INDEX OF NOT MORE THAN 50 WHEN TESTED IN ACCORDANCE WITH ASTM E84 OR UL 723.

### GENERAL NOTES:

REFER TO SHEET ME100 FOR GENERAL NOTES.

### SCHEDULE LEGEND

ABBREVIATED SCHEDULE HEADINGS:  
EFFICIENCY: MINIMUM EFFICIENCY OF WATER HEATER

GPH	GALLONS PER HOUR
HP	HORSEPOWER
LOAD	NOMINAL CONNECTED GAS LOAD TO UNIT, USED TO SIZE GAS PIPING
NPSH	NET POSITIVE STATIC HEAD
OUTPUT	MINIMUM REQUIRED OUTPUT TO MEET GPM RISE AS SCHEDULED
RPM	REVOLUTIONS PER MINUTE

### PIPE MATERIAL SCHEDULE

ATP	TARBOC TRUSS PIPE
BLK	BLACK
BS	BELL & SPIGOT
CF	CRIMPED FITTING
CI	CAST IRON
CP	COPPER
CS	CARBON STEEL
CTD	PIPE LINE SERVICE COMPANY X-TRU-COAT HIGH DENSITY POLYETHYLENE COATING EXTRUDED OVER PIPE
OW	CONTINUOUS WELD
DI	DUCTILE IRON
DR	DRAINAGE FITTING
GLV	GALVANIZED
HF	HEAT FUSED
LC	LEAD CAILLINO
MI	MALLEABLE IRON
MJ	MECHANICAL JOINT
NS	NICKERME GASKET
NH	NO-HUB
PE	POLYETHYLENE
PVC	POLYVINYL CHLORIDE
S	BRAZED JOINT - SILVER BRAZING ALLOY
SJ	SOLDER JOINT 95-5 TIN-ANTIMONY
SS	SEAMLESS STEEL
SS	STANDARD STRENGTH - SERVICE WEIGHT
SW	SOLVENT WELD
THRD	THREADED
TS	TY-SEAL
VCP	VITRIFIED CLAY PIPE
WELD	WELDED
XH	EXTRA HEAVY

### PUMP SCHEDULE

AB	ALL BRONZE
AI	ALL IRON
BF	BRONZE FITTED
BMCCES	BASE MOUNTED CLOSED COUPLED END SUCTION
BMES	BASE MOUNTED END SUCTION
BMHS	BASE MOUNTED HORIZONTAL SPLIT CASE
BMVSC	BASE MOUNTED VERTICAL SPLIT CASE
C	CONDENSER WATER
CH	CHILLED HOT WATER
OW	CHILLED WATER
DCW	DOMESTIC COLD WATER
DHW	DOMESTIC HOT WATER
HW	HEATING HOT WATER
IL	IN-LINE

### WATER HEATER SCHEDULE

PTRV	PRESSURE & TEMPERATURE RELIEF VALVE
------	-------------------------------------


we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1.816.442.7700

RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

Apex Engineers, Inc.  
Structural Engineer  
State Certificate of Authority #  
1625 Locust St  
Kansas City, MO 64108  
816.421.3222 phone


MCC Longview Community College Lab Refresh  
Metropolitan Community College  
500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

#	Description	Date
1	City Comments	12/19/2023




JOB NO: 23011.00  
DRAWN BY: MAO  
CHECKED BY: KEH  
DATE: 10/06/2023


# P401




9  
P401  
**ROOF PIPE SUPPORT DETAIL**  
SCALE: NOT TO SCALE




8  
P401  
**PIPE HANGER DETAIL**  
SCALE: NOT TO SCALE




7  
P401  
**WALL CLEANOUT DETAIL**  
SCALE: NOT TO SCALE




6  
P401  
**VENT THRU ROOF DETAIL**  
SCALE: NOT TO SCALE




5  
P401  
**MIXING VALVE DETAIL**  
SCALE: NOT TO SCALE




4  
P401  
**ISLAND VENT DETAIL**  
SCALE: NOT TO SCALE



3  
P401  
**FLOOR DRAIN DETAIL**  
SCALE: NOT TO SCALE



2  
P401  
**FLOOR CLEANOUT DETAIL**  
SCALE: NOT TO SCALE



1  
P401  
**EMERGENCY EYE WASH STATION**  
SCALE: NOT TO SCALE

hollis J. miller architects

100% Construction Documents

12/18/2023 1:19:29 PM

- GENERAL NOTES:**  
REFER TO SHEET ME100 FOR GENERAL NOTES.
- PLAN HEX NOTES:**
- REMOVE EXISTING TRANSFER GRILLE INTO CORRIDOR, SEAL ALL OPENINGS INTO THE CORRIDOR
  - REMOVE EXISTING FAN POWERED BOX AND ALL ASSOCIATED CONTROLS, DUCTWORK, HANGERS, INSULATION, ETC. CAP DUCT AT MAIN
  - REMOVE EXISTING DUCTWORK AND ASSOCIATED INSULATION, HANGERS, ETC. TO MAKE ROOM FOR NEW EXHAUST HOOD, DUCTWORK PER IMPROVEMENT PLANS. FIELD VERIFY EXACT SIZE, ELEVATION, LOCATION, ETC.
  - REMOVE EXISTING FUME HOOD AND ALL ASSOCIATED EXHAUST FAN/MAKE-UP AIR UNIT, DUCTWORK, ACCESSORIES, ETC.
  - REMOVE EXISTING EXHAUST CONE AND ALL ASSOCIATED HANGERS, INSULATION, ETC.
  - ALL LAB EXHAUST DUCT SHALL BE 316 STAINLESS STEEL WITH ONE SEAM WELDED ON TOP SIDE. REFER TO SPECIFICATIONS.
  - MECHANICAL CONTRACTOR SHALL REMOVE AND REPLACE CEILING TILES IN ALL EXISTING AREAS WITH NEW DUCT AND IS RESPONSIBLE FOR REPLACING TILES IF DAMAGED DURING CONSTRUCTION.
  - LABORATORY FUME HOOD. REFER TO ARCHITECTURAL PLANS FOR SPECIFICATION
  - ENSURE ROOM AND PLENUM ARE COMPLETELY SEALED TO ADJACENT SPACES.
  - 24"x16" DUCT UP TO EXHAUST FAN.
  - 20"x16" DUCT UP TO DOAS UNIT
  - ALL DUCTWORK SHALL BE SEALED AT MEDIUM PRESSURE DUCTWORK, 3"-6" WC PER SPECIFICATIONS.
  - PROVIDE LOW VOLTAGE MOTORIZED DAMPER, PROVIDED BY CONTROLS CONTRACTOR. DAMPER SHALL OPEN TO ALLOW TRANSFER AIR FROM ROOM 203 TO PREP ROOM WHEN SASH ON PASS THROUGH HOOD IS OPEN ON THE PREP ROOM SIDE AND SHALL CLOSE AS PREP ROOM SASH IS CLOSED.
  - SASH ON PASS THROUGH HOOD ON PREP SIDE SHALL REMAIN CLOSED, ONLY OPEN FOR USE. BOTH SASHES ON EACH SIDE SHALL NOT BE OPENED AT THE SAME TIME AND SHALL HAVE AN ERROR IF THEY ARE BOTH OPEN.

we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1 816-442-7700


115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1 720-949-1689  
HOLLISANDMILLER.COM

Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture # 00000161


**RTM Engineering Consultants**  
MEPP Engineer  
State Certificate of Authority #  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

**Apex Engineers, Inc.**  
Structural Engineer  
State Certificate of Authority #  
1625 Locust St.  
Kansas City, MO 64108  
816.421.3222 phone

hollis + miller architects  
R  
Q  
P  
N  
M  
L  
K  
J  
H  
G  
F  
E  
D  
C  
B  
A



**2 SECOND FLOOR HVAC DEMOLITION PLAN**  
SCALE: 1/4" = 1'-0"



**1 SECOND FLOOR HVAC PLAN**  
SCALE: 1/4" = 1'-0"

MCC Longview Community College Lab Refresh  
Metropolitan Community College  
500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

100% Construction Documents

REVISIONS:

#	Description	Date




The Professional Engineer and Architect seal and signature shall apply only to the portion of the drawings and shall not be used on any other drawings. The Professional Engineer and Architect seal and signature shall not be used on any drawings prepared by the engineer and the architect separately, unless the engineer and architect are jointly responsible for such plan, drawing, or document and are both signatories.

JOB NO: 23011.00  
DRAWN BY: JGG  
CHECKED BY: KEH  
DATE: 10/06/2023

**M102**


- GENERAL NOTES:**  
REFER TO SHEET ME100 FOR GENERAL NOTES.
- PLAN HEX NOTES:**
- 1 MAINTAIN MANUFACTURER RECOMMENDED CLEARANCES. COORDINATE ROUGH-IN LOCATION WITH OTHER TRADES. (TYPICAL)
  - 2 CIRCLE REPRESENTS THE 10'-0" MINIMUM DISTANCE REQUIRED FOR OUTSIDE AIR INTAKE CLEARANCE FROM EXHAUST, FLUE, VENT OR ANY OTHER SOURCE OF CONTAMINATED AIR. NOT EXHAUST FANS, FLUE OUTLETS, PLUMBING VENTS, ETC. SHALL BE LOCATED INSIDE THIS CIRCLE.
  - 3 MAINTAIN CODE REQUIRED MINIMUM 10'-0" CLEARANCE FROM ROOF EDGE.
  - 4 REMOVE EXISTING EXHAUST FAN / MAU ASSOCIATED WITH LABORATORY EXHAUST HOOD AND PATH ROOF AS REQUIRED PER ARCHITECTURAL PLANS.
  - 5 PAINT EXPOSED GAS PIPING ON ROOF WITH 2 COATS OF EPOXY ENAMEL PAINT.
  - 6 GAS PIPING ON ROOF. SUPPORT AS PER DETAIL. (TYPICAL)
  - 7 PROVIDE GAS COCK AND DIRT LEG AT EACH PIECE OF GAS FIRED EQUIPMENT.
  - 8 ROUTE 2" GAS PIPE DOWN ALONG SIDE OF BUILDING TO EXISTING BUILDING REGULATOR. AFTER REGULATOR CONNECT 2" PIPE ROUTE TO ROOF AND RECONNECT PIPE TO THE EXISTING 1.25" PIPE.
  - 9 2" NATURAL GAS PIPE CONNECTED TO DOAS1 SIZED FOR 7" WC PER TABLE 402.4(2) 2018 IFGC. SIZED FOR 400 CFH.
  - 10 PAINT EXPOSED GAS PIPING WITH 2 COATS OF EPOXY ENAMEL PAINT. PAINT AS DIRECTED BY ARCHITECT.

**2 ROOF - HVAC Plan DEMO**  
SCALE: 1/8" = 1'-0"




**1 ROOF - HVAC Plan**  
SCALE: 1/8" = 1'-0"

**GENERAL NOTES:**  
REFER TO SHEET ME100 FOR GENERAL NOTES.




**3 DUCTWORK CONSTRUCTION DETAIL**  
SCALE: NOT TO SCALE




DUCT HANGER SCHEDULE					
DUCT SIZE (INCH)	TYPE OF HANGER	HANGER SPACING (FT)	STRAP SIZE (INCH)	ROD SIZE (INCH)	ANGLE FOR BRACING
UP TO 12	A	8'-0"	1"x1/8GA	N.A.	N.A.
13 TO 18	A	8'-0"	1"x1/8GA	N.A.	N.A.
19 TO 30	A/B	8'-0"	1"x1/8GA	1/4"	1-1/2"x1-1/2"x1/8"
31 TO 42	B	8'-0"	N.A.	1/4"	1-1/2"x1-1/2"x1/8"
43 TO 54	B	8'-0"	N.A.	1/4"	1-1/2"x1-1/2"x1/8"
55 TO 60	B	8'-0"	N.A.	1/4"	1-1/2"x1-1/2"x1/8"
61 TO 84	B	8'-0"	N.A.	1/4"	1-1/2"x1-1/2"x3/16"
85 TO 96	B	8'-0"	N.A.	1/4"	1-1/2"x1-1/2"x3/16"
OVER 96	B	8'-0"	N.A.	3/8"	2"x2"x1/4"

NOTES:  
1. FOR SEVERAL DUCTS ON ONE HANGER, TYPE "B" MAY BE USED. SIZE OF HANGER WILL BE SELECTED ON THE SUM OF DUCT WIDTHS EQUAL TO MAX WIDTH OF DUCT SCHEDULE.  
2. ON TYPE "A" HANGER, PROVIDE 3 HANGERS AT EACH TAKE-OFF OR BRANCH.


**2 DUCT SUPPORT DETAIL**  
SCALE: NOT TO SCALE



**5 MAKE-UP AIR UNIT DETAIL**  
SCALE: NOT TO SCALE



**4 CEILING DIFFUSER DETAIL**  
SCALE: NOT TO SCALE



**1 EXHAUST FAN DETAIL**  
SCALE: NOT TO SCALE

we design the future®  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1 816.442.7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1 720.949.1689  
HOLLISANDMILLER.COM

Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture # 000001

RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

Apex Engineers, Inc.  
Structural Engineer  
State Certificate of Authority #  
1625 Locust St.  
Kansas City, MO 64108  
816.421.3222 phone

MCC Longview Community College Lab Refresh  
Metropolitan Community College  
500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

REVISIONS:

#	Description	Date



The Professional Engineer and Architect seal of the State of Missouri and the State of Kansas shall be used only on drawings and specifications prepared by the engineer and the architect respectively and shall be a responsibility for such plan, drawing, or document and shall not be used on any other project.

JOB NO: 23011.00  
DRAWN BY: JGG  
CHECKED BY: KEH  
DATE: 10/06/2023

**M301**

MECHANICAL DETAILS

100% Construction Documents

### OUTSIDE AIR VENTILATION UNIT SCHEDULE

PLAN MARK	MANUFACTURER	MODEL	OUTDOOR AIR FLOW		SUPPLY FAN		COOLING DATA						HOT GAS REHEAT			GAS HEATING			ELECTRICAL DATA				NOTES			
			MAX (CFM)	MIN (CFM)	SUPPLY AIR FLOW (CFM)	MOTOR (HP)	EST. ESP (IN WG)	MIN. EER	E.A.T. (DB)	W.B. (BTU/H)	MIN. (BTU/H)	TCC (BTU/H)	L.A.T. (°F)	E.A.T. (°F)	W.B. (°F)	L.A.T. (°F)	APPROXIMATE CAPACITY (BTU/H)	GAS LOAD (BTU/H)	OUTPUT (BTU/H)	EFFICIENCY (%)	VOLTAGE	PHASE		FLA	MCA	MOPC (A)
DOAS1	VALENT	VX212-3044-E1	3,750	200	3,750	2	1	4.9	116.0	79.7	119,400	326,700	542.7	54.2	54.1	75.0	211,300	400,000	324,000	91	460	3	52	76	100	AD CURB DDC DS.F.HG.LL.MHGR.PM.R410A.SA.VFD SF.VSC

### AIR VALVE SCHEDULE

ROOM SERVED BY EQUIPMENT	MARK	FUNCTION	MANUFACTURER / MODEL	PRIMARY AIR FLOW		VALVE SIZE	APD (W.C)	KW	ELECTRIC REHEAT COIL			NOTES															
				MAX (CFM)	MIN (CFM)				E.A.T. (°F)	L.A.T. (°F)	HEATER PHASE																
201C	EV1	HOOD/EXHAUST	CRITICAL ROOM CONTROL - CLV-ST108-SO-FS-FHC/VSS	725 CFM	440 CFM	8	0.11 in.wg	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	316 STAINLESS, FAIL SAFE, STEP DOWN 24V TRANSFORMER PROVIDED BY CONTROLS CONTRACTOR	
201	EV2	HOOD/EXHAUST	CRITICAL ROOM CONTROL - CLV-ST108-SO-FS-FHC/VSS	725 CFM	440 CFM	8	0.11 in.wg	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	316 STAINLESS, FAIL SAFE, STEP DOWN 24V TRANSFORMER PROVIDED BY CONTROLS CONTRACTOR
201	EV3	HOOD/EXHAUST	CRITICAL ROOM CONTROL - CLV-ST108-SO-FS-FHC/VSS	725 CFM	440 CFM	8	0.11 in.wg	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	316 STAINLESS, FAIL SAFE, STEP DOWN 24V TRANSFORMER PROVIDED BY CONTROLS CONTRACTOR
201	GV1	GENERAL EXHAUST	CRITICAL ROOM CONTROL - CLV-ST114-EC-FS	1,850 CFM	2,735 CFM	14	0.24 in.wg	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	316 STAINLESS, FAIL SAFE, STEP DOWN 24V TRANSFORMER PROVIDED BY CONTROLS CONTRACTOR
201AB	GV2	GENERAL EXHAUST	CRITICAL ROOM CONTROL - CLV-ST106-EC-FS	200 CFM	200 CFM	6	0.08 in.wg	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	316 STAINLESS, FAIL SAFE, STEP DOWN 24V TRANSFORMER PROVIDED BY CONTROLS CONTRACTOR
201	SV1	SUPPLY	CRITICAL ROOM CONTROL - CLV-SP116-A0-FS	3,000 CFM	3,000 CFM	16	0.19 in.wg	40	55	3	480	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	ALUMINUM, FAIL SAFE, SCR ELECTRIC HEAT, MANUFACTURER INTEGRAL DISCONNECT SWITCH, STEP DOWN 24V TRANSFORMER PROVIDED BY CONTROLS CONTRACTOR
201C	SV2	SUPPLY	CRITICAL ROOM CONTROL - CLV-ST106-EC-FS	400 CFM	400 CFM	6	0.14 in.wg	6	55	3	208	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	ALUMINUM, FAIL SAFE, SCR ELECTRIC HEAT, MANUFACTURER INTEGRAL DISCONNECT SWITCH, STEP DOWN 24V TRANSFORMER PROVIDED BY CONTROLS CONTRACTOR
201AB	SV3	SUPPLY	CRITICAL ROOM CONTROL - CLV-ST106-EC-FS	200 CFM	200 CFM	6	0.14 in.wg	3	55	3	208	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	ALUMINUM, FAIL SAFE, SCR ELECTRIC HEAT, MANUFACTURER INTEGRAL DISCONNECT SWITCH, STEP DOWN 24V TRANSFORMER PROVIDED BY CONTROLS CONTRACTOR

\* AIR VALVES PROVIDED BY THE CONTROLS CONTRACTOR.

### GRILLE, REGISTER AND DIFFUSER SCHEDULE

PLAN MARK	MANUFACTURER	MODEL	APPLICATION	FINISH	FRAME TYPE	VOLUME DAMPER	MAXIMUM NC	MINIMUM THROW (FT)	MAXIMUM THROW (FT)	MAXIMUM AP (IN WG)	NOTES
EAT	TITUS	PAR-24 x 24	EXHAUST	WHITE	GRID	No	30	0	0	0.10	24x24 SQUARE PERFORATED FACE WITH ROUND DUCT CONNECTION
RA1	TITUS	PAR-24 x 24	RETURN	WHITE	GRID	No	30	0	0	0.10	24x24 SQUARE PERFORATED FACE WITH ROUND DUCT CONNECTION
SA1	TITUS	TRI-TEC-AL	SUPPLY	WHITE	GRID	No	30	5	18	0.10	24"x48" PERFORATED FACE - ALUMINUM BACKPAN, HIGH VOLUME/LOW VELOCITY
SA2	TITUS	DMN-24 x 24	SUPPLY	WHITE	GRID	No	30	0	0	0.10	24x24 SQUARE PLAQUE FACE WITH ROUND DUCT CONNECTION

### FAN SCHEDULE

PLAN MARK	MANUFACTURER	MODEL	AIR FLOW (CFM)	EST. ESP (IN WG)	VOLTAGE	PHASE	FLA	MOTOR (HP)	NOTES
EF1	COOK	195TCNHLE14	1,225	2	460	3	8	5	CURB, DM VFD, EPC, WVC

### DOAS UNIT SEQUENCE OF OPERATION (DOAS-1)

ROOFTOP DEDICATED OUTSIDE AIR UNIT. (CONSTANT VOLUME SUPPLY, VARIABLE COOLING, HEAT PUMP HEATING DOWN TO 10°F WITH SECONDARY ELECTRIC HEAT, VARIABLE SUPPLY TEMPERATURE, DEHUMIDIFICATION AND DISCHARGE TEMPERATURE CONTROL, VAV MODULATING HOT GAS REHEAT, FILTER MONITORING, SMOKE CONTROL).

DOAS UNIT MANUFACTURER SHALL PROVIDE BACNET COMPLIANT CONTROLLER AND ALL PROGRAMMING REQUIRED TO MEET THE SEQUENCE OF OPERATION AS DESCRIBED BELOW. DDC CONTROLS CONTRACTOR SHALL PROVIDE INTERFACE TO CONNECT WITH DOAS UNIT MANUFACTURER'S CONTROLLER AND SHALL PROVIDE ALL PROGRAMMING AND GRAPHICS NECESSARY LIST EACH INDIVIDUAL CONTROL POINT SHOWN ON THE DIAGRAM AND/OR LISTED IN THE SEQUENCE BELOW. DDC SYSTEM SHALL BE CAPABLE OF SENDING ALL OUTPUTS AND ACCEPTING ALL INPUTS LISTED BELOW IN THIS SEQUENCE OF OPERATION. ALL OTHER REQUIRED SENSORS, RELAYS, SWITCHES, ETC. NOT PROVIDED BY MANUFACTURER SHALL BE PROVIDED BY MECHANICAL CONTRACTOR AND/OR DDC CONTRACTOR.

ROOM PRESSURIZATION CONTROL: UNIT SHALL RUN CONTINUOUSLY TO MAINTAIN NEGATIVE PRESSURE SPACE PER LAB CONTROL SEQUENCE. ONLY SHUTDOWN BY THE MANUAL DISCONNECT, BUILDING AUTOMATION SYSTEM, FIRE ALARM, OR HIGH STATIC PRESSURE SWITCH IN FAN DISCHARGE. OUTSIDE AIR DAMPER SHALL MODULATE TO MAINTAIN PROPER OUTSIDE AIR FLOW WITH ASSOCIATION WITH SUPPLY FAN.

AHU FAN SPEED WILL BE CONTROLLED BY A VARIABLE FREQUENCY DRIVE. SUPPLY FAN SPEED SHALL BE CONTROLLED BY STATIC PRESSURE CONTROLLERS.

DISCHARGE TEMPERATURE SHALL MAINTAIN DISCHARGE TEMPERATURE COOLING / HEATING MODE 55°F (ADJUSTABLE). VARIABLE SPEED COMPRESS / SCR HEATING CONTROLS SHALL MAINTAIN DISCHARGE TEMPERATURE UNOCCUPIED MODE / EXTEND BREAK MODE.

UNIT SHALL MODULATE FAN SPEED AND OUTSIDE AIR MOTORIZED DAMPER TO MAINTAIN LAB SEQUENCE REQUIREMENTS.

SMOKE ACTIVATED FIRE PROTECTION CONTROL: DUCT MOUNTED SMOKE DUCT DETECTORS SHALL BE INSTALLED AS SHOWN ON THE HVAC AIR FLOW SCHEMATIC TO AUTOMATICALLY SHUT DOWN THE UNIT AND SEND SIGNAL TO THE FIRE ALARM SYSTEM. IF THIS ACTION OCCURS, CONTROLLER SHALL SEND EMERGENCY ALARM SIGNAL TO SYSTEM UNIT SHALL REQUIRE MANUAL START-UP IF THIS ACTION OCCURS.

FILTER MONITORING: PROVIDE DIFFERENTIAL PRESSURE SENSOR TO MEASURE PRESSURE ACROSS THE FILTERS. CONTROLLER SHALL SEND ALARM SIGNAL WHEN FILTERS ARE IN NEED OF CHANGING BASED UPON THE DIFFERENTIAL PRESSURE SENSOR SETPOINT (ADJUSTABLE).

- ALARMS:
- FINAL ALARMS SHALL BE COORDINATED WITH OWNER PRIOR TO OCCUPANCY.
  - SUPPLY FAN PROOF OF RUN
  - EXHAUST FAN PROOF OF RUN
  - DISCHARGE AIR TEMPERATURE HIGH / LOW LIMIT (115°F / 45°F) (ADJUSTABLE)
  - SUPPLY FILTER STATUS - DIRTY FILTER
  - EXHAUST FILTER STATUS - DIRTY FILTER


### LAB DOAS CONTROL SCHEMATIC

SCALE: NOT TO SCALE



### LAB CONTROL SEQUENCE

SCALE: NOT TO SCALE



### AIR VALVE / LAB EXHAUST FAN - POINTS LIST

TYPE	POINT	DESCRIPTION	UNITS	TREND	ALARM	TOTALIZE
AI	EHT	ELECTRIC REHEATING LAY	DEG F	X	X	
AI	DA-T	DISCHARGE AIR TEMPERATURE	DEG F	X	X	
AI	SAV-T	SUPPLY AIR VALVE - EAT	DEG F	X	X	
AI	CA-T	OUTSIDE AIR TEMPERATURE	DEG F	X	X	
AI	SAV-F	SUPPLY AIR VALVE AIRFLOW	CFM	X	X	
AI	EAV-F	EXHAUST VALVE AIRFLOW	CFM	X	X	
AI	EF-F	EXHAUST FAN AIRFLOW	CFM	X	X	
AI	DP-HL	DUCT PRESS. EXHAUST	IN WG	X	X	
DI	EF-S	EXHAUST FAN STATUS	OFF ON	X	X	X
DI	EF-C	EXHAUST FAN COMMAND	OFF ON	X		
AO	EF-O	EXHAUST FAN VFD OUTPUT	%	X		
AO	EHO-O	ELECTRIC HEATING OUTPUT	%	X		
AO	EAV-O	EXHAUST AIR VALVE OUTPUT	%	X		
AO	RAV-O	RETURN AIR VALVE OUTPUT	%	X		
AO	DAT-SP	DISCHARGE AIR TEMP SETPOINT	DEG F	X		
AO	EAP-SP	EXHAUST AIR PRESS. SETPOINT	IN WG	X		

**GENERAL NOTES:**  
REFER TO SHEET ME100 FOR GENERAL NOTES.

**SCHEDULE LEGEND**

ABBREVIATED SCHEDULE HEADINGS

CAP CAPACITY  
CFM CUBIC FEET PER MINUTE  
DB DRY BULB  
E.A.T. ENTERING AIR TEMPERATURE  
E.S.P. EXTERNAL STATIC PRESSURE INCLUDES ALL WORK EXTERNAL TO UNIT  
E.W.T. ENTERING WATER TEMPERATURE  
EER ENERGY EFFICIENCY RATIO  
EST. ESTIMATED  
FLA FULL LOAD AMPS  
FPM FEET PER MINUTE  
GPH GALLONS PER HOUR  
GPM GALLONS PER MINUTE  
GRLB GRAINS OF MOISTURE PER POUND OF DRY AIR  
HP HORSEPOWER  
IN INCH  
ISP INLET STATIC PRESSURE  
L.A.T. LEAVING AIR TEMPERATURE  
L.W.T. LEAVING WATER TEMPERATURE  
LES LBS  
LOAD NOMINAL CONNECTED GAS LOAD TO UNIT, USED TO SIZE GAS PIPING  
MCA MINIMUM CIRCUIT AMPACITY  
MIN. MINIMUM  
MOPC MAXIMUM OVERCURRENT PROTECTION  
NC MAXIMUM NOISE CRITERIA RATING  
NPSH NET PRESSURE SUCTION HEAD  
OA OUTSIDE AIR  
OUTFIT MINIMUM REQUIRED OUTPUT TO SATIFY SCHEDULED HEATING REQUIREMENTS  
PPH POUNDS PER HOUR  
PSI POUNDS PER SQUARE INCH  
RPM REVOLUTIONS PER MINUTE  
SEER SEASONAL ENERGY EFFICIENCY RATIO  
SHC SENSIBLE HEAT CAPACITY  
TCC TOTAL COOLING CAPACITY  
TEMP TEMPERATURE  
THC TOTAL HEAT CAPACITY  
WB WET BULB  
WPD WATER PRESSURE DROP

**EXHAUST FAN SCHEDULE**

AF ALUMINUM FINISH  
DD DIRECT DRIVE MOTOR  
DM DISCONNECT MEANS  
EPC INDUSTRIAL STRENGTH EPOXY POWDER COAT FOR ALL PARTS EXPOSED TO AIR STREAM  
GBD GRAVITY BACKDRAFT DAMPER  
VFD VARIABLE FREQUENCY DRIVE PROVIDED BY CONTROLS CONTRACTOR  
WC ZERO PRESSURE WEATHER CAP.

**OUTSIDE AIR VENTILATION SCHEDULE**

CURB INSULATED FULL ROOF CURB  
DDC DIRECT DIGITAL CONTROL  
DS SINGLE POINT MEANS OF DISCONNECT  
F PROVIDE MERV 8 PRE-FILTER AND MERV-13 FINAL FILTER. PROVIDE WITH HOLDING FRAME.  
HG HAIL GUARDS FOR CONDENSER COILS.  
LL LOW LEAK EXHAUST AIR DAMPER  
MHGR MODULATING HOT GAS REHEAT.  
PM ELECTRICAL PHASE MONITORING.  
RH20A ROOM UNIT WITH RH20A REFRIGERANT  
SA SUPPLY AIR RESET SCHEDULE TO SHUTDOWN HOT GAS REHEAT WHEN OUTSIDE AIR TEMPERATURE IS ABOVE 90°F LEAVING AIR TEMPERATURE WOULD BE REDUCED TO COOLING COIL LEAVING AIR TEMPERATURE.  
SCAD HINGED ACCESS DOORS  
VFD SA VARIABLE FREQUENCY DRIVE  
VSC VARIABLE SPEED COMPRESSOR.

**REVISIONS:**

#	Description	Date

**JOB NO: 23011.00**  
**DRAWN BY: JGG**  
**CHECKED BY: KEH**  
**DATE: 10/06/2023**

**M401**

**MCC Longview Community College Lab Refresh**  
Metropolitan Community College  
500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

**100% Construction Documents**

**RELEASED FOR CONSTRUCTION**  
As Noted on Plans Review  
Professional Services Department  
Lee's Summit, Missouri  
62024

**we design the future™**  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1.816.442.7700  
115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1.720.949.1889  
HOLLISANDMILLER.COM

Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture # 00000161

**RTM Engineering Consultants**  
MEFP Engineer  
State Certificate of Authority #  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone

**Apex Engineers, Inc.**  
Structural Engineer  
State Certificate of Authority #  
1625 Locust St  
Kansas City, MO 64108  
816.421.3222 phone

**JAMES R. SASQUETTE**  
Professional Engineer  
No. 101018  
E-29112  
James R. Sasquette, Inc.  
10000 E. 120th St., Suite 100  
Overland Park, KS 66213  
913.648.8888

The Professional Engineer used herein is the only one who is licensed and held out as such. No other person is authorized to use the name of the engineer and the engineer's signature on any drawings or documents without the written consent of the engineer.

**MECHANICAL SCHEDULES & CONTROLS**

REVISIONS:

#	Description	Date



The Professional Engineer and Architect seal of the State of Missouri and the State of Kansas are hereby acknowledged as being in full compliance with the requirements of the engineer and the architect respectively, and the responsibility for any error, omission, or inaccuracy in the drawings shall rest with the engineer and the architect.

JOB NO: 23011.00  
DRAWN BY: CLT  
CHECKED BY: KEH  
DATE: 10/06/2023


**ED101**

**GENERAL NOTES:**

REFER TO SHEET ME100 FOR GENERAL NOTES.

**PLAN HEX NOTES:**

- CONTRACTOR SHALL DEMOLISH EXISTING LIGHT SWITCHES. NEW LIGHT SWITCHES SHOWN ON LIGHTING PLAN SHALL BE LOCATED IN PLACE OF DEMOLISHED SWITCHES.
- EXISTING FIRE ALARM STROBE SHALL REMAIN AS EXISTING.
- EXISTING LIGHTING CONTROL DEVICE SHALL BE DEMOLISHED.
- CONTRACTOR SHALL DEMOLISH EXISTING ELECTRICAL DEVICE INCLUDING ALL ASSOCIATED WIRING, CONDUIT AND RACEWAY, ETC. CONTRACTOR SHALL ALSO MAKE ANY REQUIRED SPLICES AND CONNECTIONS TO MAINTAIN CIRCUIT FOR ANY EXISTING TO REMAIN DOWNSTREAM DEVICES.
- CONTRACTOR SHALL DEMOLISH POWER AND DATA SERVING EXISTING PROJECTOR.
- CONTRACTOR SHALL DEMOLISH EXISTING LIGHT FIXTURE. NEW LIGHT FIXTURE AND CONTROLS SHALL TIE INTO EXISTING CIRCUIT SERVING DEMOLISHED FIXTURES FROM UNSWITCHED PORTION OF EXISTING CIRCUIT.
- CONTRACTOR SHALL DEMOLISH EXISTING RECEPTACLES ON DEMOLISHED LAB HOOD. CIRCUIT SERVING DEMOLISHED RECEPTACLES SHALL REMAIN AND SERVE NEW RECEPTACLES ON NEW HOOD. CONTRACTOR SHALL MAKE ALL EXTENSIONS AND SPLICES TO EXTEND EXISTING CIRCUIT TO NEW HOOD RECEPTACLES.
- EXISTING EMERGENCY GAS SHUTOFF SHALL REMAIN AS EXISTING.
- EXISTING SURFACE MOUNTED RECEPTACLE SHALL BE DEMOLISHED. EXISTING CIRCUIT SHALL SERVE NEW SURFACE RECEPTACLE SHOWN ON IMPROVEMENT PLAN. CONTRACTOR SHALL MAKE ALL NECESSARY SPLICES AND CONNECTIONS TO EXTEND CIRCUIT TO NEW DEVICE LOCATION.
- EXISTING DISCONNECT SWITCH SERVING EXISTING EXHAUST SYSTEM SHALL BE DEMOLISHED INCLUDING ALL ASSOCIATED WIRING, CONDUIT, RACEWAY ETC BACK TO PANEL OF ORIGINATION.



**1 ELECTRICAL DEMOLITION PLAN - LEVEL 2**  
ED101 SCALE: 1/4" = 1'-0"



we design the future™  
1828 Walnut Street Suite 922  
Kansas City, MO 64108  
1 816-442-7700

115 Wilcox Street Suite 210  
Castle Rock, CO 80104  
1 720-949-1689

HOLLISANDMILLER.COM  
Hollis + Miller Architects  
Missouri State Certificate of Authority  
Architecture # 0000161

RTM Engineering Consultants  
MEPP Engineer  
State Certificate of Authority #  
9225 Indian Creek Pkwy, Suite 1075  
Overland Park, KS 66210  
913.322.1400 phone


Apex Engineers, Inc.  
Structural Engineer  
State Certificate of Authority #  
1625 Locust St.  
Kansas City, MO 64108  
816.421.3222 phone

**GENERAL NOTES:**


REFER TO SHEET ME100 FOR GENERAL NOTES.

**PLAN HEX NOTES:**

- CONTRACTOR SHALL PROVIDE HUBBELL SURFACE MOUNT 2 GANG BOX MODEL NUMBER SA888G. PROVIDE 2 DUPLEX RECEPTACLES AND STAINLESS STEEL COVER PLATE. ONE OF THE TWO DUPLEXES IN THE BOX SHALL BE GFI AND THE OTHER SHALL BE WIRED DOWNSTREAM OF THE GFI RECEPTACLE TO BE GFI PROTECTED. WIRING SHALL BE FED FROM BELOW IN CASEWORK. RECEPTACLES SHALL FACE IN THE DIRECTION AS SHOWN BY ARROW ON PLANS.
- CONTRACTOR SHALL THE NEW LIGHT FIXTURES INTO EXISTING CIRCUIT SERVING DEMOLISHED LIGHT FIXTURES. CONTRACTOR SHALL TIE INTO UNSWITCHED PART OF CIRCUIT TO SERVE NEW CONTROLS FOR NEW LIGHT FIXTURES.
- CONTRACTOR SHALL CONNECT NEW HOOD RECEPTACLES TO EXISTING CIRCUIT(S) SERVING THE DEMOLISHED HOOD RECEPTACLES.
- RECEPTACLE SHALL BE GFI PROTECTED BY UPSTREAM GFI RECEPTACLE.
- MAKE POWER CONNECTION TO (2) DUPLEX RECEPTACLES LOCATED INTEGRAL WITH FUME HOOD. BOTH RECEPTACLES ON HOOD SHALL BE SERVED BY CIRCUIT SHOWN.
- CIRCUIT SERVING NEW SURFACE MOUNTED BOX SHALL BE FED FROM BELOW AND CONCEALED IN CASEWORK.
- CIRCUIT SERVING NEW SURFACE MOUNTED RECEPTACLE SHALL BE FED FROM EXISTING BREAKER IN PFB(S) SUB PANEL SERVING DEMOLISHED SURFACE MOUNT BOX. NEW WIRING AND CIRCUITRY SHALL BE FED FROM BELOW AND CONCEALED IN CASEWORK.
- EXISTING EMERGENCY GAS SHUTOFF SHALL REMAIN AS EXISTING.



**2 SECOND FLOOR POWER PLAN**  
SCALE: 1/4" = 1'-0"



**1 SECOND FLOOR LIGHTING PLAN**  
SCALE: 1/4" = 1'-0"

MCC Longview Community College Lab Refresh  
Metropolitan Community College  
500 SW LONGVIEW ROAD,  
LEE SUMMIT, MO - 64081

100% Construction Documents

REVISIONS:

#	Description	Date



JOB NO: 23011.00  
DRAWN BY: CLT  
CHECKED BY: KEH  
DATE: 10/06/2023

**E102**

**GENERAL NOTES:**  
REFER TO SHEET ME100 FOR GENERAL NOTES.  
**PLAN HEX NOTES:**

### EXISTING CIRCUIT BREAKER PANELBOARD SCHEDULE

PANEL NAME: "PP1A"		LOCATION: LEVEL 1 FED BY: EXISTING MOUNTING: SURFACE		VOLTAGE: 120/208V, 3PH, 4W ENCLOSURE: WESTINGHOUSE MANUFACTURER: WESTINGHOUSE PANEL TYPE: WESTINGHOUSE		MAIN TYPE: MCB BUS RATING (A): 225 MCB RATING (A): 225 MIN. AIC RATING (A): EXISTING							
CKT	LOAD DESCRIPTION	CIRCUIT CONFIGURATION	VD%	CB P TYPE	A	B	C	TYPE P	CB	VD%	CIRCUIT CONFIGURATION	LOAD DESCRIPTION	CKT
1	EXISTING LOAD	--	--	20 1	0 0			--	1 20	--	--	EXISTING LOAD	2
3	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	4
5	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	6
7	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	8
9	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	10
11	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	12
13	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	14
15	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	16
17	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	18
19	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	20
21	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	22
23	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	24
25	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	26
27	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	28
29	SPACE	--	--	1				--	1 20	--	--	EXISTING LOAD	30
31	SPACE	--	--	1				--	1 20	--	--	EXISTING LOAD	32
33	SPACE	--	--	1				--	1 20	--	--	SPACE	34
35	SPACE	--	--	1				--	1 20	--	--	SPACE	36
37	PP1C	4#1, #8G, 1-1/2"	0.85%	100 3	7920			--	1 20	--	--	SPACE	38
39	--	--	--	--	7920			--	1 20	--	--	SPACE	40
41	--	--	--	--	--			--	1 20	--	--	SPACE	42
		<b>CONNECTED PHASE LOAD</b>		7920 VA		7920 VA		8760 VA				<b>CALCULATED PANEL AMPS:</b>	
		<b>*PHASE DIVERSIFIED LOAD</b>		7920 VA		7920 VA		8760 VA					
		<b>*PHASE DIVERSIFIED AMPS</b>		66 A		66 A		73 A					
												(DIVERSIFIED LOADS CALCULATED PER THE NATIONAL ELECTRIC CODE.)	
<b>NOTES/ACCESSORIES:</b>												<b>PANEL TOTALS</b>	
1. BOLD AND UNDERLINED CKT NUMBER INDICATED NEW CIRCUIT BREAKER.												TOTAL CONNECTED LOAD: 24600 VA	
												TOTAL DIVERSIFIED LOAD: 24600 VA	
												CONTROLLING LOAD: N/A	

### CIRCUIT BREAKER PANELBOARD SCHEDULE

PANEL NAME: "PP1C"		LOCATION: LEVEL 1 FED BY: "PP1A" MOUNTING: SURFACE		VOLTAGE: 120/208V, 3PH, 4W ENCLOSURE: NEMA 1 MANUFACTURER: SQUARE D PANEL TYPE: NQ		MAIN TYPE: MLO BUS RATING (A): 100 MCB RATING (A): N/A MIN. AIC RATING (A): 10000 A							
CKT	LOAD DESCRIPTION	CIRCUIT CONFIGURATION	VD%	CB P TYPE	A	B	C	TYPE P	CB	VD%	CIRCUIT CONFIGURATION	LOAD DESCRIPTION	CKT
1	CLASS 201 AC RECEPT	2#12, #12G, 3/4"	1.40%	20 1	540 540			--	1 20	1.61%	2#12, #12G, 3/4"	CLASS 201 AC RECEPT	2
3	CLASS 201 TEACHING WALL	2#12, #12G, 3/4"	3.51%	20 1		1080 1920		--	1 20	5.13%	2#12, #12G, 3/4"	LAB STATION RECEPT	4
5	LAB STATION RECEPT	2#12, #12G, 3/4"	4.73%	20 1		1920 1920		--	1 20	5.77%	2#12, #12G, 3/4"	LAB STATION RECEPT	6
7	LAB STATION RECEPT	2#12, #12G, 3/4"	5.73%	20 1	1920 1920			--	1 20	5.41%	2#12, #12G, 3/4"	LAB STATION RECEPT	8
9	LAB STATION RECEPT	2#12, #12G, 3/4"	5.45%	20 1		1920 2000		--	3 20	2.52%	4#12, #12G, 3/4"	SV2	10
11	LAB STATION RECEPT	2#12, #12G, 3/4"	6.05%	20 1		1920 2000		--	--	--	--	--	12
13	SV3	4#10, #10G, 3/4"	0.72%	25 3	1000 2000			--	--	--	--	--	14
15	--	--	--	--		1000		--	1	--	--	SPACE	16
17	--	--	--	--			1000	--	1	--	--	SPACE	18
19	SPACE	--	--	1				--	1	--	--	SPACE	20
21	SPACE	--	--	1				--	1	--	--	SPACE	22
23	SPACE	--	--	1				--	1	--	--	SPACE	24
25	SPACE	--	--	1				--	1	--	--	SPACE	26
27	SPACE	--	--	1				--	1	--	--	SPACE	28
29	SPACE	--	--	1				--	1	--	--	SPACE	30
		<b>CONNECTED PHASE LOAD</b>		7920 VA		7920 VA		8760 VA				<b>CALCULATED PANEL AMPS:</b>	
		<b>*PHASE DIVERSIFIED LOAD</b>		7920 VA		7920 VA		8760 VA					
		<b>*PHASE DIVERSIFIED AMPS</b>		66 A		66 A		73 A					
												(DIVERSIFIED LOADS CALCULATED PER THE NATIONAL ELECTRIC CODE.)	
<b>NOTES/ACCESSORIES:</b>												<b>PANEL TOTALS</b>	
1. PROVIDE BLANK SPACE COVER WHERE "SPACE" IS SHOWN ON SCHEDULE												TOTAL CONNECTED LOAD: 24600 VA	
												TOTAL DIVERSIFIED LOAD: 24600 VA	
												CONTROLLING LOAD: N/A	

### EXISTING CIRCUIT BREAKER PANELBOARD SCHEDULE

PANEL NAME: "PP2B(S)"		LOCATION: LEVEL 2 FED BY: PP2B MOUNTING: SURFACE		VOLTAGE: 120/208V, 3PH, 4W ENCLOSURE: WESTINGHOUSE MANUFACTURER: WESTINGHOUSE PANEL TYPE: WESTINGHOUSE		MAIN TYPE: EXISTING BUS RATING (A): EXISTING MCB RATING (A): EXISTING MIN. AIC RATING (A): EXISTING							
CKT	LOAD DESCRIPTION	CIRCUIT CONFIGURATION	VD%	CB P TYPE	A	B	C	TYPE P	CB	VD%	CIRCUIT CONFIGURATION	LOAD DESCRIPTION	CKT
1	LAB STATION RECEPT	2#12, #12G, 3/4"	4.97%	20 1	1920 1920			--	1 20	4.69%	2#12, #12G, 3/4"	LAB STATION RECEPT	2
3	LAB STATION RECEPT	2#12, #12G, 3/4"	4.65%	20 1	1920 1920			--	1 20	4.37%	2#12, #12G, 3/4"	LAB STATION RECEPT	4
5	LAB STATION RECEPT	2#12, #12G, 3/4"	4.33%	20 1		1920 1920		--	1 20	4.04%	2#12, #12G, 3/4"	LAB STATION RECEPT	6
7	EXISTING LOAD	--	--	20 1		0 1920		--	1 20	4.86%	2#12, #12G, 3/4"	HOOD RECEPT	8
9	EXISTING LOAD	--	--	20 1		0 1920		--	1 20	6.18%	2#12, #12G, 3/4"	HOOD RECEPT	10
11	EXISTING LOAD	--	--	20 1			0 0	--	1 20	--	--	EXISTING LOAD	12
13	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	14
15	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	16
17	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	18
19	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	20
21	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	22
23	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	24
		<b>CONNECTED PHASE LOAD</b>		5760 VA		5760 VA		3840 VA				<b>CALCULATED PANEL AMPS:</b>	
		<b>*PHASE DIVERSIFIED LOAD</b>		5760 VA		5760 VA		3840 VA					
		<b>*PHASE DIVERSIFIED AMPS</b>		50 A		50 A		32 A					
												(DIVERSIFIED LOADS CALCULATED PER THE NATIONAL ELECTRIC CODE.)	
<b>NOTES/ACCESSORIES:</b>												<b>PANEL TOTALS</b>	
1. BOLD AND UNDERLINED CKT NUMBER INDICATED NEW CIRCUIT BREAKER.												TOTAL CONNECTED LOAD: 15360 VA	
												TOTAL DIVERSIFIED LOAD: 15360 VA	
												CONTROLLING LOAD: N/A	

### EXISTING CIRCUIT BREAKER PANELBOARD SCHEDULE

PANEL NAME: "HP2C"		LOCATION: LEVEL 2 FED BY: MOUNTING: SURFACE		VOLTAGE: 480/277V, 3PH, 4W ENCLOSURE: WESTINGHOUSE MANUFACTURER: WESTINGHOUSE PANEL TYPE: WESTINGHOUSE		MAIN TYPE: MLO BUS RATING (A): 100 MCB RATING (A): 100 MIN. AIC RATING (A): EXISTING							
CKT	LOAD DESCRIPTION	CIRCUIT CONFIGURATION	VD%	CB P TYPE	A	B	C	TYPE P	CB	VD%	CIRCUIT CONFIGURATION	LOAD DESCRIPTION	CKT
1	EXISTING LOAD	--	--	20 3	0 0			--	3 20	--	--	EXISTING LOAD	2
3	--	--	--	--		0 0		--	--	--	--	--	4
5	--	--	--	--		0 0		--	--	--	--	--	6
7	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	8
9	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	10
11	EXISTING LOAD	--	--	20 1		0 0		--	1 30	--	--	EXISTING LOAD	12
13	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	14
15	EXISTING LOAD	--	--	20 1		0 0		--	1 20	--	--	EXISTING LOAD	16
17	SV1	4#4, #8G, 1-1/4"	0.46%	70 3			13333 2018	--	3 20	0.57%	3#12, #12G, 3/4"	EF1	18
19	--	--	--	--		13333 2018		--	--	--	--	--	20
21	--	--	--	--		13333 2018		--	--	--	--	--	22
23	SPACE	--	--	1				--	1	--	--	SPACE	24
25	SPACE	--	--	1				--	1	--	--	SPACE	26
27	SPACE	--	--	1				--	1	--	--	SPACE	28
29	SPACE	--	--	1				--	1	--	--	SPACE	30
		<b>CONNECTED PHASE LOAD</b>		15352 VA		15352 VA		15352 VA				<b>CALCULATED PANEL AMPS:</b>	
		<b>*PHASE DIVERSIFIED LOAD</b>		15856 VA		15856 VA		15856 VA					
		<b>*PHASE DIVERSIFIED AMPS</b>		57 A		57 A		57 A					
												(DIVERSIFIED LOADS CALCULATED PER THE NATIONAL ELECTRIC CODE.)	
<b>NOTES/ACCESSORIES:</b>												<b>PANEL TOTALS</b>	
1. BOLD AND UNDERLINED CKT NUMBER INDICATED NEW CIRCUIT BREAKER.												TOTAL CONNECTED LOAD: 14925 VA	
												TOTAL DIVERSIFIED LOAD: 17589 VA	
												CONTROLLING LOAD: N/A	

### LIGHTING DEVICE SCHEDULE


PLAN MARK	MOUNTING TYPE	MANUFACTURER	MODEL	FINISH	NOTES
MS	CEILING	HLIGHT	#CM P0T-A-RJB	WHITE	LOW VOLTAGE DUAL TECH CEILING SMALL MOUNTION OCCUPANCY SENSOR.
RC1	PLENUM	HLIGHT	#P18-D-ESP-SA	WHITE	1 ZONE 0-10V DIMMING ROOM CONTROLLER PROGRAMMED TO MANUAL ON / AUTO OFF AFTER 20 MIN.
LVD	WALL	HLIGHT	#P00M-DX-WH	WHITE	LOW VOLTAGE 3 BUTTON DIMMING WALL SWITCH, 1 ON/OFF, 2 RAISE, 3 LOWER.
V1	WALL	SENSOR SWITCH	W5XA-P0T-D-SA	WHITE	WALL MOUNTED LINE VOLTAGE OCCUPANCY DIMMING SWITCH PROGRAMMED TO MANUAL ON / AUTO OFF AFTER 20 MIN.
V2	WALL	SENSOR SWITCH	W5XA-MND-P0T-D-SA	WHITE	WALL MOUNTED LINE VOLTAGE OCCUPANCY DIMMING SWITCH PROGRAMMED TO MANUAL ON / AUTO OFF AFTER 20 MIN. SWITCH SHALL BE COMPATIBLE FOR 3-WAY APPLICATIONS.

### LUMINAIRE SCHEDULE


PLAN MARK	MANUFACTURER	MODEL	MOUNTING TYPE	FINISH	LUMINAIRE SOURCE	ELECTRICAL	DESCRIPTION
A	METALUX	2#ENL02-S4-LVW-LMD-CD	RECESSED	WHITE	SOURCE TYPE: LUMENS: 5400 COLOR TEMP (K): 4000 CRI: 90	VOLTAGE: 277 LOAD (VA): 43	RECESSED 2X4 LED TROFFER WITH UNIVERSAL DRIVER, WHERE EMERGENCY FIXTURE IS SHOWN ON PLANS, PROVIDE METALUX OPTION EL10WS 10W EMERGENCY INTEGRAL BATTERY PACK.

### DISCONNECT SCHEDULE

PLAN MARK	EQUIPMENT SERVED	VOLTAGE	DUTY	SWITCH AMP	POLES	FUSE AMP	TYPE	ENCLOSURE NEMA TYPE	NOTES
DS1	DOALU1	480	HD	200	3	200	LPN-RK	NEMA 3R	
DS#	(EQUIPMENT SERVED)	480	HD	200	3	200	LPN-RK	NEMA 3R	




**2 ROOF RECEPTACLE MOUNTING**  
E301 SCALE: NOT TO SCALE



**1 ROOM CONTROLLER - VACANCY/OCCUPANCY SENSOR DETAIL**  
E301 SCALE: NOT TO SCALE

**MCC Longview Community College Lab Refresh**  
 Metropolitan Community College  
 500 SW LONGVIEW ROAD,  
 LEE SUMMIT, MO - 64081



JOB NO: 23011.00  
 DRAWN BY: CLT  
 CHECKED BY: KEH  
 DATE: 10/06/2023

**E301**