

RE: B240069 - Lot 183 HT

Site Information:

Project Customer: Summit Homes Project Name:
Lot/Block: 183 Subdivision: Hawthorn Ridge
Model: Carbondale - Craftsman
Address: 1613 SW Arborway Terr
City: Lee's Summit State: MO

MiTek, Inc.

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200

General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):

Design Code: IRC2021/TPI2014 Design Program: MiTek 20/20 8.7
Wind Code: ASCE 7-16 [Wind Speed: 115 mph] Design Method: MWFRS (Envelope) ASCE 7-16 [Low Rise]
Roof Load: 45.0 psf Floor Load: N/A psf
Mean Roof Height (feet): 25 Exposure Category: C

No.	Seal#	Truss Name	Date	No.	Seal#	Truss Name	Date
1	I64799572	A1	4/11/24	35	I64799606	J1	4/11/24
2	I64799573	A2	4/11/24	36	I64799607	J2	4/11/24
3	I64799574	A3	4/11/24	37	I64799608	J3	4/11/24
4	I64799575	A4	4/11/24	38	I64799609	J4	4/11/24
5	I64799576	A5	4/11/24	39	I64799610	J5	4/11/24
6	I64799577	A6	4/11/24	40	I64799611	J6	4/11/24
7	I64799578	A7	4/11/24	41	I64799612	J7	4/11/24
8	I64799579	A8	4/11/24	42	I64799613	J8	4/11/24
9	I64799580	A9	4/11/24	43	I64799614	J9	4/11/24
10	I64799581	A10	4/11/24	44	I64799615	J10	4/11/24
11	I64799582	A11	4/11/24	45	I64799616	J11	4/11/24
12	I64799583	A12	4/11/24	46	I64799617	J12	4/11/24
13	I64799584	A13	4/11/24	47	I64799618	J13	4/11/24
14	I64799585	A14	4/11/24	48	I64799619	J14	4/11/24
15	I64799586	A15	4/11/24	49	I64799620	J15	4/11/24
16	I64799587	A16	4/11/24	50	I64799621	J16	4/11/24
17	I64799588	A17	4/11/24	51	I64799622	J17	4/11/24
18	I64799589	B1	4/11/24	52	I64799623	J18	4/11/24
19	I64799590	B2	4/11/24	53	I64799624	J19	4/11/24
20	I64799591	B3	4/11/24	54	I64799625	J20	4/11/24
21	I64799592	B4	4/11/24	55	I64799626	J21	4/11/24
22	I64799593	B5	4/11/24	56	I64799627	J22	4/11/24
23	I64799594	B6	4/11/24	57	I64799628	J23	4/11/24
24	I64799595	B7	4/11/24	58	I64799629	J24	4/11/24
25	I64799596	B8	4/11/24	59	I64799630	J25	4/11/24
26	I64799597	B9	4/11/24	60	I64799631	J26	4/11/24
27	I64799598	C1	4/11/24	61	I64799632	J27	4/11/24
28	I64799599	C2	4/11/24	62	I64799633	J28	4/11/24
29	I64799600	C3	4/11/24	63	I64799634	J29	4/11/24
30	I64799601	C4	4/11/24	64	I64799635	J30	4/11/24
31	I64799602	D1	4/11/24	65	I64799636	LAY1	4/11/24
32	I64799603	D2	4/11/24	66	I64799637	LAY2	4/11/24
33	I64799604	D3	4/11/24	67	I64799638	LAY3	4/11/24
34	I64799605	D4	4/11/24	68	I64799639	LAY4	4/11/24

The truss drawing(s) referenced above have been prepared by
MiTek USA, Inc. under my direct supervision based on the parameters
provided by Wheeler - Waverly.

Truss Design Engineer's Name: Johnson, Andrew

My license renewal date for the state of Missouri is December 31, 2025.

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.



April 11, 2024



RE: B240069 - Lot 183 HT

MiTek, Inc.
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200

No.	Seal#	Truss Name	Date
69	I64799640	LAY5	4/11/24
70	I64799641	LAY6	4/11/24
71	I64799642	LAY7	4/11/24
72	I64799643	R1	4/11/24
73	I64799644	V1	4/11/24
74	I64799645	V2	4/11/24
75	I64799646	V3	4/11/24
76	I64799647	V4	4/11/24
77	I64799648	V5	4/11/24
78	I64799649	V6	4/11/24
79	I64799650	V7	4/11/24
80	I64799651	V8	4/11/24


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	A1	Hip Girder	1	4		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:44:56 Page: 1
ID:xtkJ_ecVQwTrluO9vs_d4czX58l-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWCD0i7J42zC0P

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799572
LEE'S SUMMIT, MISSOURI

05/02/2024



Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	RELEASE FOR CONSTRUCTION
B240069	A1	Hip Girder	1	4	Job Reference (optional)	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 164799572 LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:44:58 Page: 2
ID:xtkJ_ecVQwTrluO9vs_d4czX58I-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWCDoi7J42zC9H

05/02/2024

13) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 138 lb down and 93 lb up at 9-0-0, 138 lb down and 93 lb up at 11-0-0, 138 lb down and 93 lb up at 13-0-0, 138 lb down and 93 lb up at 15-0-0, 138 lb down and 93 lb up at 17-0-0, 138 lb down and 93 lb up at 19-0-0, 138 lb down and 93 lb up at 21-0-0, 137 lb down and 92 lb up at 23-0-0, 137 lb down and 92 lb up at 25-0-0, 137 lb down and 92 lb up at 27-0-0, 137 lb down and 92 lb up at 29-0-0, 137 lb down and 92 lb up at 31-0-0, 137 lb down and 92 lb up at 33-0-0, and 137 lb down and 92 lb up at 35-0-0, and 137 lb down and 92 lb up at 37-0-0 on top chord, and 456 lb down and 132 lb up at 5-0-0, 232 lb down and 76 lb up at 7-0-0, 68 lb down at 9-0-0, 68 lb down at 11-0-0, 68 lb down at 13-0-0, 68 lb down at 15-0-0, 68 lb down at 17-0-0, 68 lb down at 19-0-0, 68 lb down at 21-0-0, 68 lb down at 23-0-0, 68 lb down at 25-0-0, 68 lb down at 27-0-0, 68 lb down at 29-0-0, 68 lb down at 31-0-0, 68 lb down at 33-0-0, 68 lb down at 35-0-0, 68 lb down at 37-0-0, and 230 lb down and 73 lb up at 39-0-0, and 451 lb down and 132 lb up at 41-0-0 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-3=-70, 3-9=-70, 9-11=-70, 1-21=-20, 17-21=-20, 10-16=-20
Concentrated Loads (lb)
Vert: 18=-51 (F), 20=-232 (F), 15=-52 (F), 7=-110 (F), 8=-110 (F), 13=-52 (F), 12=-230 (F), 22=-110 (F), 23=-110 (F), 24=-110 (F), 25=-110 (F), 26=-110 (F), 27=-110 (F), 28=-110 (F), 29=-110 (F), 30=-110 (F), 31=-110 (F), 32=-110 (F), 33=-110 (F), 34=-110 (F), 35=-456 (F), 36=-51 (F), 37=-51 (F), 38=-51 (F), 39=-51 (F), 40=-51 (F), 41=-51 (F), 42=-52 (F), 43=-52 (F), 44=-52 (F), 45=-52 (F), 46=-52 (F), 47=-52 (F), 48=-451 (F)

 **WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	A2	Hip	1	2	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:44:53 Page: 1
ID:K0gbVL0pIqa7IqwK6LIR?zzX5Ae-RfC?PsB70Hq3NSgPqnL8w3uITxbGKvRcDOI7JzZJC61

05/02/2024



Scale = 1:82.2

Plate Offsets (X, Y): [1:0-2-13,0-2-13], [10:0-2-8,0-5-8], [15:0-2-8,0-3-0], [21:0-6-12,0-2-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.66	Vert(LL)	-0.54	17-19	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.87	Vert(CT)	-0.99	17-19	>553	240	M18AHS	142/136
BCLL	0.0*	Rep Stress Incr	YES	WB	0.84	Horz(CT)	0.38	12	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.41	17-19	>999	240	Weight: 353 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2 *Except* 1-3:2x6 SPF No.2
BOT CHORD	2x4 SPF No.2 *Except* 1-21:2x6 SPF No.2, 21-18:2x4 SPF 2100F 1.8E, 5-16:2x3 SPF No.2
WEBS	2x3 SPF No.2 *Except* 21-2:2x4 SPF No.2, 12-10:2x8 SP 2400F 2.0E

BRACING

TOP CHORD	Structural wood sheathing directly applied or 4-1-14 oc purlins, except end verticals, and 2-0-0 oc purlins (4-0-6 max.): 3-8.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size) 1=0-3-8, 12=0-3-8
 Max Horiz 1=-68 (LC 9)
 Max Uplift 1=-271 (LC 4), 12=-309 (LC 5)
 Max Grav 1=2049 (LC 1), 12=2133 (LC 1)

FORCES

Tension

TOP CHORD

1-2=-9096/1230, 2-3=-5208/789,
3-4=-4770/759, 4-5=-7102/1206,
5-7=-7055/1204, 7-8=-3551/582,
8-9=-3896/608, 9-10=-986/103, 10-11=0/32,
10-12=-653/116

BOT CHORD

1-21=-1105/8314, 20-21=-996/7376,
19-20=-948/6407, 17-19=-948/6407,
16-17=0/143, 5-17=-452/184, 15-16=-37/348,
13-15=-774/5168, 12-13=-490/3467

WEBS

2-21=-268/2581, 2-20=-2581/420,
3-20=-142/1367, 4-20=-2003/370,
4-19=0/246, 4-17=-165/891,
15-17=-744/4865, 7-17=-340/2079,
7-15=-525/194, 7-13=-1961/376,
8-13=-871/1044, 9-13=0/356, 9-12=-2979/524

NOTES

- 1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc, 2x8 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc, 2x3 - 1 row at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc, 2x3 - 1 row at 0-9-0 oc.
- 2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- 3) Unbalanced roof live loads have been considered for this design.
- 4) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 5) Provide adequate drainage to prevent water ponding.
- 6) All plates are MT20 plates unless otherwise indicated.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) Bearings are assumed to be: Joint 1 SPF No.2 , Joint 12 SPF No.2 .
- 10) Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 271 lb uplift at joint 1 and 309 lb uplift at joint 12.

12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024



Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	RELEASE FOR CONSTRUCTION
B240069	A3	Hip	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 164799574 LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:44:55 Page: 1
ID:kzBAjVbJ3P5ANdslp30EV5zX5CB-RfC?PsB70Hq3NSgPqnL8w3uITXbGhWwCDoi1342067

05/02/2024




Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	RELEASE FOR CONSTRUCTION
B240069	A4	Hip	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW
						DEVELOPMENT SERVICES
						164799575
						LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:44:55 Page: 1

ID: ?OUUZK06yYjRu3MMHANPzX5F6-RfC?PsB70Hq3NSgPqnL8w3uITXb6KWwCD0rJ42u0?r

05/02/2024



Scale = 1:82.5

Plate Offsets (X, Y): [1:0-3-13,0-1-5], [13:0-3-8,0-2-12], [14:0-2-8,0-3-0], [17:0-2-8,Edge], [19:0-8-0,0-5-0], [22:0-2-8,0-1-8], [23:0-10-2,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.79	Vert(LL)	-0.54	19-21	>999	360	M18AHS 186/179
TCDL	10.0	Lumber DOL	1.15	BC	0.97	Vert(CT)	-0.97	19-21	>565	240	MT20 197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.89	Horz(CT)	0.50	13	n/a	n/a	MT18HS 197/144
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.37	19-21	>999	240	Weight: 203 lb FT = 10%

LUMBER	
TOP CHORD	2x4 SPF 2100F 1.8E *Except* 1-4:2x6 SP 2400F 2.0E, 6-8:2x4 SPF No.2
BOT CHORD	2x4 SPF No.2 *Except* 1-23:2x6 SP 2400F 2.0E, 23-20:2x4 SPF 2400F 2.0E, 5-18:2x3 SPF No.2, 20-19:2x4 SPF 2100F 1.8E
WEBS	2x3 SPF No.2 *Except* 17-19:2x4 SPF No.2, 13-11:2x8 SP 2400F 2.0E
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (2-5-13 max.): 4-8.
BOT CHORD	Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS	1 Row at midpt 2-22, 3-21, 5-21, 7-15
REACTIONS	
(size)	1=0-3-8, 13=0-3-8
Max Horiz	1=-104 (LC 9)
Max Uplift	1=-213 (LC 4), 13=-250 (LC 5)
Max Grav	1=2049 (LC 1), 13=2133 (LC 1)
FORCES	
(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-8605/908, 2-3=-5380/629, 3-4=-4206/570, 4-5=-3820/548, 5-7=-4531/676, 7-8=-3171/482, 8-10=-3542/496, 10-11=-4043/463, 11-12=0/32, 11-13=-2050/286
BOT CHORD	1-23=-815/7812, 22-23=-745/7062, 21-22=-504/5010, 19-21=-500/4544, 18-19=0/93, 5-19=-10/229, 17-18=-26/138, 15-17=-381/3627, 14-15=-356/3635, 13-14=-171/1057
WEBS	2-23=-185/2422, 2-22=-2067/351, 3-22=0/420, 3-21=-1386/289, 4-21=-78/1218, 5-21=-1078/183, 17-19=-365/3584, 7-19=-169/1307, 7-17=-735/148, 7-15=-882/148, 8-15=-62/917, 10-15=-527/223, 10-14=-54/166, 11-14=-239/2584

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Bearings are assumed to be: Joint 1 SP 2400F 2.0E, Joint 13 SPF No.2.
- Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 213 lb uplift at joint 1 and 250 lb uplift at joint 13.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	RELEASE FOR CONSTRUCTION
B240069	A5	Hip	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 164799576 LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:00 Page: 1
ID: g0bnEc4j8V_FW8GQvWJWKDzX5I1-RfC?PsB70Hq3NSgPqnL8w3ulTXb6KWrcD6wJ42dC?

05/02/2024





Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.72	Vert(LL)	-0.46	17-18	>993	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.99	Vert(CT)	-0.82	17-18	>549	240	MT18HS	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.93	Horz(CT)	0.32	11	n/a	n/a	M18AHS	142/136
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.29	17-18	>999	240	Weight: 170 lb	FT = 10%

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) All plates are MT20 plates unless otherwise indicated.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Bearings are assumed to be: Joint 2 SP 2400F 2.0E , Joint 11 SPF 2100F 1.8E .
- 8) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 243 lb uplift at joint 2 and 147 lb uplift at joint 11.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	A7	Hip	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:00 Page: 1
ID:hPLDIEJCiIT?sljuOTmMvLzX5OA-RfC?PsB70Hq3NSgPqnL8w3ulTXbGK?VrCDoi7J4ZJ6G4

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799578
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:72.1
Plate Offsets (X, Y): [2:0-2-13,0-2-13], [5:0-4-0,Edge], [10:0-2-8,Edge], [11:0-3-8,Edge], [18:0-7-4,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.73	Vert(LL)	-0.49	15-17	>934	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	1.00	Vert(CT)	-0.85	17-18	>533	240	MT18HS	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.75	Horz(CT)	0.32	11	n/a	n/a	M18AHS	142/136
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.31	17-18	>999	240	Weight: 175 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2 *Except* 8-10:2x4 SPF 2100F 1.8E, 1-5:2x6 SP 2400F 2.0E
BOT CHORD 2x4 SPF No.2 *Except* 2-18:2x6 SP 2400F 2.0E, 18-16:2x4 SPF 2100F 1.8E
WEBS 2x3 SPF No.2 *Except* 18-3:2x4 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 2-7-9 oc purlins, except end verticals, and 2-0-0 oc purlins (4-2-1 max.): 7-8.
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 1 Row at midpt 6-15, 7-14, 9-14

REACTIONS (size) 2=0-3-8, 11=0-3-8
Max Horiz 2=200 (LC 8)
Max Uplift 2=-259 (LC 8), 11=-171 (LC 9)
Max Grav 2=1843 (LC 2), 11=1795 (LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/10, 2-3=-7422/1095, 3-4=-6571/1071, 4-6=-3877/529, 6-7=-2266/319, 7-8=-1891/287, 8-9=-2128/299, 9-10=-2037/193, 10-11=-1702/199
BOT CHORD 2-18=-1159/6738, 17-18=-700/4199, 15-17=-359/2762, 14-15=-141/2026, 12-14=-163/1915, 11-12=-36/52
WEBS 3-18=-79/1256, 4-18=-434/2179, 4-17=-1050/357, 6-17=-148/1293, 6-15=-1045/312, 7-15=-138/1007, 7-14=-550/129, 8-14=-84/584, 9-14=-192/184, 10-12=-104/1916, 9-12=-569/141

NOTES
1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) All plates are MT20 plates unless otherwise indicated.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Bearings are assumed to be: Joint 2 SP 2400F 2.0E , Joint 11 SPF No.2 .
- 8) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 259 lb uplift at joint 2 and 171 lb uplift at joint 11.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	A8	Roof Special	2	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:00 Page: 1
ID: c5BiUoHpG8IrixtbYBlz5wzX5Qo-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWCDoi7J42uCW

05/02/2024



Scale = 1:73.3

Plate Offsets (X, Y): [2:0-2-13,0-2-13], [2:2-7-0,0-0-7], [5:0-4-0,Edge], [9:0-2-8,Edge], [10:0-3-8,Edge], [16:0-6-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.92	Vert(LL)	-0.52	15-16	>874	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.88	Vert(CT)	-0.99	15-16	>458	240	MT18HS	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.96	Horz(CT)	0.31	10	n/a	n/a	M18AHS	142/136
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.31	15-16	>999	240	Weight: 167 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2 *Except* 1-5:2x6 SP 2400F 2.0E, 7-9:2x4 SPF 2100F 1.8E
BOT CHORD	2x4 SPF 2100F 1.8E *Except* 2-16:2x6 SP 2400F 2.0E, 12-10:2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 15-4:2x4 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 9-1-1 oc bracing.
WEBS	1 Row at midpt 6-13, 8-13

REACTIONS

(size)	2=0-3-8, 10=0-3-8
Max Horiz	2=225 (LC 8)
Max Uplift	2=-289 (LC 8), 10=-182 (LC 9)
Max Grav	2=1906 (LC 2), 10=1802 (LC 2)

FORCES

	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/38, 2-3=-7355/1078, 3-4=-6572/1056, 4-6=-3640/496, 6-7=-2109/306, 9-10=-1727/205, 7-8=-2117/331, 8-9=-1989/202
BOT CHORD	2-16=-1147/6665, 15-16=-738/4158, 13-15=-385/2785, 11-13=-184/1922, 10-11=-37/48
WEBS	3-16=-79/1238, 4-16=-388/2226, 4-15=-1126/377, 6-15=-91/1109, 6-13=-1198/341, 7-13=-105/1187, 8-13=-274/196, 8-11=-607/153, 9-11=-111/1900

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Bearings are assumed to be: Joint 2 SP 2400F 2.0E , Joint 10 SPF No.2 .
- Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 289 lb uplift at joint 2 and 182 lb uplift at joint 10.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	A9	Roof Special	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66671,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:00 Page: 1
ID:5mcDU?MaZbUpq86KZ8x_zbzX5Vs-RfC?PsB70Hq3NSgPqnL8w3ulTXb6KWwCD0rJ42u0?r

05/02/2024



Scale = 1:73.8

Plate Offsets (X, Y): [2:0-3-9,Edge], [4:0-5-0,Edge], [9:Edge,0-2-0], [13:0-2-8,0-2-0], [14:0-6-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.90	Vert(LL)	-0.39	13-14	>872	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.96	Vert(CT)	-0.78	13-14	>433	240	M18AHS	142/136
BCLL	0.0*	Rep Stress Incr	YES	WB	0.87	Horz(CT)	0.33	9	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.34	13-14	>978	240	Weight: 144 lb	FT = 10%

LUMBER

TOP CHORD 2x6 SPF No.2 *Except* 7-8:2x4 SPF No.2,
4-7:2x4 SPF 2100F 1.8E
BOT CHORD 2x4 SPF No.2 *Except* 2-14:2x6 SPF No.2,
14-12:2x4 SPF 2100F 1.8E, 6-10:2x3 SPF
No.2
WEBS 2x4 SPF No.2 *Except*
5-13,11-7,9-8,9-11:2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
2-2-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc
bracing. Except:

1 Row at midpt 6-11
WEBS 1 Row at midpt 3-13, 5-11, 8-9, 7-9

REACTIONS (size) 2=0-3-8, 9=0-3-8
Max Horiz 2=345 (LC 7)
Max Uplift 2=241 (LC 8), 9=185 (LC 8)
Max Grav 2=1410 (LC 1), 9=1259 (LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 1-2=0/38, 2-3=5510/1063, 3-5=2350/372,
5-6=1051/208, 6-7=977/321, 7-8=140/139,
8-9=172/96

BOT CHORD 2-14=-1153/5034, 13-14=-1047/4450,
11-13=-388/2114, 10-11=0/149,
6-11=-502/279, 9-10=-21/46

WEBS 3-14=-260/1622, 3-13=-2343/660,
5-13=0/542, 5-11=-1412/354,
7-11=-356/1362, 9-11=-136/543,
7-9=-1241/168

NOTES

1) Unbalanced roof live loads have been considered for
this design.

- Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- Bearings are assumed to be: Joint 2 SPF No.2, Joint 9
SPF No.2.
- Bearing at joint(s) 2 considers parallel to grain value
using ANSI/TPI 1 angle to grain formula. Building
designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 241 lb uplift at joint
2 and 185 lb uplift at joint 9.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	A10	Hip	1	1	Job Reference (optional)


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:00 Page: 1

ID:dEKiM5o6LI_J6CntzTgaB5zX5bl-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrcDoi7J42JC?

Page: 1

05/02/2024



Scale = 1:73.6

Plate Offsets (X, Y): [2:0-3-5,0-1-12], [5:0-4-0,Edge], [10:Edge,0-2-0], [13:0-2-4,0-2-12], [16:0-7-0,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.60	Vert(LL)	-0.38	13-15	>882	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.91	Vert(CT)	-0.67	13-15	>502	240	M18AHS	142/136
BCLL	0.0*	Rep Stress Incr	YES	WB	0.67	Horz(CT)	0.24	10	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.23	15-16	>999	240	Weight: 144 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2 *Except* 5-1:2x6 SP 2400F 2.0E
BOT CHORD	2x6 SPF No.2 *Except* 14-13:2x4 SPF 2400F 2.0E, 17-12:2x3 SPF No.2, 12-10:2x4 SPF No.2, 14-16:2x4 SPF 2100F 1.8E
WEBS	2x3 SPF No.2 *Except* 16-3,0-0,0-0,0-0,10-8:2x4 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 2-11-10 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 7-8.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 7-7-1 oc bracing: 2-16.
WEBS	1 Row at midpt 9-10, 8-10, 6-13

REACTIONS

Max Horiz 2=338 (LC 7)
Max Uplift 2=-215 (LC 8), 10=-161 (LC 8)
Max Grav 2=1384 (LC 2), 10=1337 (LC 2)

FORCES

Tension

TOP CHORD 1-2=0/10, 2-3=-5274/874, 3-4=-4689/871,
4-6=-2486/395, 6-7=-974/207, 7-8=-835/224,
8-9=-133/128, 9-10=-135/87

BOT CHORD 2-16=949/4775, 15-16=-563/2793,
13-15=-247/1551, 11-12=0/0, 10-11=0/21

WEBS 3-16=-45/817, 8-10=-1280/194,
10-13=-144/489, 8-13=-172/1069,
11-13=0/149, 7-13=0/143, 6-13=-1039/303,
6-15=-128/1181, 4-15=-886/347,
4-16=-372/1767

NOTES

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) All plates are MT20 plates unless otherwise indicated.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Bearings are assumed to be: Joint 2 SPF No.2 , Joint 10 SPF No.2 .
- 8) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 215 lb uplift at joint 2 and 161 lb uplift at joint 10.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024



Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcscomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-UIS.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	A11	Hip	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:00 Page: 1

ID: i2YfAtEKM3e7qLUmqDVvFYzX5h7-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcDof7d423COf

RELEASE FOR CONSTRUCTION


AS NOTED FOR PLAN REVIEW

DEVELOPMENT SERVICES

164799582

LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:68.6
Plate Offsets (X, Y): [2:0-3-9,Edge], [4:0-4-0,Edge], [12:0-2-3,0-2-0], [14:0-2-8,0-2-0], [15:0-6-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.38	14-15	>893	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.98	Vert(CT)	-0.73	14-15	>463	240	M18AHS	142/136
BCLL	0.0*	Rep Stress Incr	YES	WB	0.77	Horz(CT)	0.32	10	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.32	14-15	>999	240	Weight: 145 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2 *Except* 1-4:2x6 SPF No.2, 4-6:2x4 SPF 2100F 1.8E
BOT CHORD 2x4 SPF No.2 *Except* 2-15:2x6 SPF No.2, 15-13:2x4 SPF 2100F 1.8E
WEBS 2x3 SPF No.2 *Except* 10-9,15-3,14-3,12-5:2x4 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (5-4-2 max.): 6-8.
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 1 Row at midpt 9-10, 3-14, 8-10, 5-12

REACTIONS (size) 2=0-3-8, 10=0-3-8
Max Horiz 2=342 (LC 7)
Max Uplift 2=210 (LC 8), 10=175 (LC 5)
Max Grav 2=1335 (LC 1), 10=1261 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 6-7=-928/193, 7-8=-930/198, 8-9=-157/113, 9-10=-121/76, 1-2=0/10, 2-3=-5565/1023, 3-5=-2422/355, 5-6=-1088/184
BOT CHORD 2-15=-1089/5090, 14-15=-985/4497, 12-14=-349/2186, 11-12=0/145, 7-12=-361/129, 10-11=-13/17
WEBS 3-15=-255/1640, 5-14=0/545, 3-14=-2319/638, 6-12=0/184, 10-12=-110/208, 8-10=-1222/297, 5-12=-1408/334, 8-12=-159/1194

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- 3) Provide adequate drainage to prevent water ponding.
- 4) All plates are MT20 plates unless otherwise indicated.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Bearings are assumed to be: Joint 2 SPF No.2 , Joint 10 SPF No.2 .
- 8) Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 210 lb uplift at joint 2 and 175 lb uplift at joint 10.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®



16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:01 Page: 1
ID:UFJXxeBV1_HKhnM1GxuckYzX5mt-RfC?PsB70Hq3NSgPqnL8w3uLTxbGKWrcDofJ4z2G?f

[illegible]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.88	Vert(LL)	-0.23	10-12	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.82	Vert(CT)	-0.43	10-12	>780	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.63	Horz(CT)	0.05	8	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.11	10-12	>999	240	Weight: 113 lb	FT = 10%

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.



MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	A13	Half Hip	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:01 Page: 1
ID: M8n2jpGqeF7x_OJ?UgcPtKzX5tD-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi734z30%

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799584
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:57.4									
Plate Offsets (X, Y): [2:Edge,0-0-8], [3:0-0-11,0-2-3], [5:0-4-0,Edge], [11:Edge,0-2-8], [14:0-6-0,0-2-12]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.93	Vert(LL)	-0.34	3-16	>988
TCDL	10.0	Lumber DOL	1.15	BC	0.64	Vert(CT)	-0.78	3-16	>430
BCLL	0.0*	Rep Stress Incr	YES	WB	0.71	Horz(CT)	0.26	11	n/a
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.29	3-16	>999
									Weight: 130 lb
									FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2 *Except* 5-1:2x6 SP 2400F 2.0E
BOT CHORD 2x4 SPF No.2 *Except* 17-3,6-15,13-9:2x3 SPF No.2, 3-16:2x4 SPF 2100F 1.8E
WEBS 2x3 SPF No.2
BRACING
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (4-8-9 max.): 7-10.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-17.
REACTIONS (size) 2=0-3-8, 11=0-3-8
Max Horiz 2=215 (LC 8)
Max Uplift 2=-172 (LC 8), 11=-210 (LC 5)
Max Grav 2=1351 (LC 1), 11=1264 (LC 1)
FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/6, 2-3=-634/0, 3-4=-3183/475, 4-6=-2450/310, 6-7=-2317/364, 7-8=-1258/212, 8-9=-1121/218, 9-10=-1105/212, 10-11=-1216/217
BOT CHORD 2-17=-41/0, 3-17=0/82, 3-16=-580/3027, 15-16=0/141, 6-16=-11/94, 14-15=-19/50, 13-14=0/15, 12-13=0/111, 9-12=-284/123, 11-12=-30/23
WEBS 14-16=-228/1490, 7-16=-226/1082, 7-14=-476/168, 8-14=-422/189, 12-14=-265/1528, 8-12=-241/52, 10-12=-282/1606, 4-16=-1034/318

- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 210 lb uplift at joint 11 and 172 lb uplift at joint 2.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

NOTES
1) Unbalanced roof live loads have been considered for this design.



April 11,2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 164799585 LEE'S SUMMIT, MISSOURI
B240069	A14	Half Hip	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:01 Page: 1

ID:vicEt9X?PJBnPVbctGZxrAzX5y2-RfC?PsB70Hq3NSgPqnL8w3ulTXbKGVrCDoi7J4zJCA

05/02/2024



Scale = 1:58.4

Plate Offsets (X, Y): [2:Edge,0-0-8], [3:0-0-11,0-2-3]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.94	Vert(LL)	-0.34	3-13	>991	360	MT20 197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.67	Vert(CT)	-0.80	3-13	>422	240	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.71	Horz(CT)	0.41	20	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.27	14	>999	240	Weight: 130 lb FT = 10%

LUMBER

TOP CHORD 2x6 SP 2400F 2.0E *Except* 5-8:2x4 SPF No.2

BOT CHORD 2x4 SPF No.2 *Except* 14-3,15-16,17-18,7-10:2x3 SPF No.2, 12-3:2x4 SPF 2100F 1.8E

WEBS 2x3 SPF No.2

OTHERS 2x4 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 1-11-14 oc purlins, except end verticals, and 2-0-0 oc purlins (3-3-3 max.): 5-8.

BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (size) 2=0-3-8, 20=0-3-8

Max Horiz 2=182 (LC 8)

Max Uplift 2=150 (LC 8), 20=214 (LC 4)

Max Grav 2=1349 (LC 1), 20=1239 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum

Tension

TOP CHORD 1-2=0/6, 2-3=-633/0, 3-4=-3190/414, 4-5=-2337/299, 5-6=-2080/290, 6-7=-1600/273, 7-8=-1602/279, 9-19=0/129, 8-19=0/129

BOT CHORD 2-14=-41/0, 3-14=0/82, 3-13=-484/3035, 11-13=-366/2000, 10-11=0/133, 7-11=-447/186, 9-10=0/19

WEBS 9-11=-48/78, 8-11=-311/1793, 5-13=-21/667, 6-13=-75/201, 6-11=-553/105, 4-13=-1099/346, 8-20=-1244/215

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

3) Provide adequate drainage to prevent water ponding.

4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

6) All bearings are assumed to be SPF No.2 .

7) Bearing at joint(s) 20 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 150 lb uplift at joint 2 and 214 lb uplift at joint 20.

9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	A15	Half Hip	1	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1

ID:3JDLGTEx4sS5GV2CiY9EJzX61I-RfC?PsB70Hq3NSgPqnL8w3uITxbGhWrCDoi7342067

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799586
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:58.3									
Plate Offsets (X, Y): [2:Edge,0-0-8], [3:0-0-11,0-2-3]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	l/defl	L/d
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.89	Vert(LL)	-0.29 3-15	>999	360
TCDL	10.0	Lumber DOL	1.15	BC	0.76	Vert(CT)	-0.61 3-15	>552	240
BCLL	0.0*	Rep Stress Incr	YES	WB	0.79	Horz(CT)	0.38 22	n/a	n/a
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.23 3-15	>999	240
					Weight: 125 lb FT = 10%				

LUMBER	
TOP CHORD	2x4 SPF No.2 *Except* 1-5:2x6 SP 2400F 2.0E
BOT CHORD	2x4 SPF No.2 *Except* 16-3:17-18,19-20,8-11:2x3 SPF No.2, 13-3:2x4 SPF 2100F 1.8E
WEBS	2x3 SPF No.2
OTHERS	2x4 SPF No.2
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (2-7-13 max.): 5-9.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
REACTIONS (size) 2=0-3-8, 22=0-3-8	
Max Horiz 2=148 (LC 5)	
Max Uplift 2=-160 (LC 4), 22=-220 (LC 4)	
Max Grav 2=1349 (LC 1), 22=1239 (LC 1)	
FORCES (lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/6, 2-3=-633/21, 3-4=-3622/510, 4-5=-2728/394, 5-6=-2481/380, 6-8=-2085/375, 8-9=-2083/380, 10-21=0/135, 9-21=0/135
BOT CHORD	2-16=-41/0, 3-16=0/82, 3-15=-579/3497, 14-15=-490/2728, 12-14=-490/2728, 11-12=0/133, 8-12=-472/196, 10-11=0/68
WEBS	5-15=-39/748, 6-12=-742/104, 10-12=-62/70, 9-12=-406/2195, 6-14=0/216, 6-15=-450/101, 4-15=-1134/291, 9-22=-1250/222

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2 .
- Bearing at joint(s) 22 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 160 lb uplift at joint 2 and 220 lb uplift at joint 22.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11,2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:04 Page: 1
ID: NrACUox8IsX6W91tSJl8GEzX64Z-RfC?PsB70Hq3NSgPqnL8w3uLTxBGk-WrCDoi754z3C?# 05/02/2022

The drawing illustrates a roof truss system with the following details:

- Members:**
 - Top chord: 6x8, 3x10, 3x4, 2x4, 6x12
 - Bottom chord: 3x6, 2x4, 3x4, 2x4, 2x4, 2x4, 8x12, 3x4, 6x6, 3x4
 - Verticals: 15, 14, 13, 12, 10, 9
 - Diagonals: 5, 4, 6, 7, 8, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21
- Joints:** 1 through 21.
- Dimensions:**
 - Horizontal: 0-10-8, 7-3-14, 14-3-15, 19-3-14, 21-2-12, 28-4-0
 - Vertical: 3-10-15, 3-8-10, 1-0-0, 3-6-15, 1-0-0, 2-6-15, 0-1-11, 0-8-0, 1-0-0, 1-6-15, 2-0-0, 1-0-0, 1-0-0
- Notes:**
 - MT18HS 3x8 =
 - 15-11-14
 - 14-3-15
 - 1-7-15

Plate Offsets (X, Y): [2:Edge,0-0-8], [3:0-0-15,0-2-3]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.39	13-14	>870	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.68	Vert(CT)	-0.70	13-14	>481	240	MT18HS	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.74	Horz(CT)	0.40	21	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.31	13-14	>999	240	Weight: 117 lb	FT = 10%

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
 Vasd=91mph; TCDF=6.0psf; BCDF=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.

- 4) All plates are MT20 plates unless otherwise indicated.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) All bearings are assumed to be SPF No.2 .
- 8) Bearing at joint(s) 21 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 183 lb uplift at joint 2 and 224 lb uplift at joint 21.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024



Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria**, and **DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	A17	Half Hip Girder	1	2	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871.

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:02 Page: 1
ID:gPRZAft?fwKeggwUKSnaBbzX69o-RfC?PsB70Hg3NSgPqnL8w3ulTXbGKWrcDof34z2C?f

05/02/2024



Scale = 1:55.1

Plate Offsets (X, Y): [3:0-0-12,0-2-3], [3:0-10-7,0-3-7], [4:0-4-0,0-3-3], [9:0-2-8,Edge], [13:0-2-8,0-1-8], [15:0-2-0,0-0-8], [18:0-2-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	1.00	Vert(LL)	-0.64	13-15	>523	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.82	Vert(CT)	-1.16	13-15	>291	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.91	Horz(CT)	0.37	10	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.61	13-15	>555	240	Weight: 288 lb	FT = 10%

LUMBER

TOP CHORD	2x6 SP 2400F 2.0E *Except* 4-7:2x4 SPF No.2, 7-9:2x4 SPF 2100F 1.8E
BOT CHORD	2x3 SPF No.2 *Except* 2-21,8-11:2x4 SPF No.2, 14-12,14-3:2x6 SP 2400F 2.0E, 17-16,11-10:2x6 SPF No.2
WEBS	2x3 SPF No.2 *Except* 10-12,12-9:2x4 SPF No.2
OTHERS	2x3 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (2-8-10 max.): 4-9.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-21.

REACTIONS

Max Horiz 2=102 (LC 5)
Max Uplift 2=-458 (LC 4), 10=-413 (LC 5)
Max Grav 2=1919 (LC 1), 10=1730 (LC 1)

FORCES

Tension

TOP CHORD 1-2=0/6, 2-3=-927/231, 3-4=-7121/1876,
4-5=-9162/2406, 5-6=-9162/2406,
6-8=-10080/2575, 8-9=-7397/1890,
9-10=-1546/428

BOT CHORD 2-21=-44/0, 3-21=0/94, 3-20=-1846/6787,
19-20=-1820/6685, 18-19=-2612/10080,
15-18=-2569/9896, 13-15=-2612/10080,
12-13=-2087/8082, 17-18=0/49,
16-17=-43/184, 15-16=0/49, 11-12=0/144,
8-12=-939/340, 10-11=-200/884

WEBS 10-12=-789/195, 9-12=-1912/7408,
4-20=-305/1215, 5-19=-448/218,
6-13=-270/221, 4-19=-654/2630,
6-19=-1001/186, 8-13=-538/2047


NOTES

- 1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc, 2x3 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x4 - 1 row at 0-9-0 oc, 2x3 - 1 row at 0-9-0 oc, 2x6 - 2 rows staggered at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc, 2x3 - 1 row at 0-9-0 oc.
- 2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- 3) Unbalanced roof live loads have been considered for this design.
- 4) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Bearings are assumed to be: Joint 2 SPF No.2 , Joint 10 SPF No.2 .
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 413 lb uplift at joint 10 and 458 lb uplift at joint 2.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

- 11) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 71 lb down and 39 lb up at 4-11-2, 76 lb down and 38 lb up at 7-0-0, 76 lb down and 38 lb up at 9-0-0, 86 lb down and 67 lb up at 11-0-0, 86 lb down and 67 lb up at 13-0-0, 86 lb down and 66 lb up at 15-0-0, and 86 lb down and 66 lb up at 17-0-0, and 86 lb down and 66 lb up at 19-0-0 on top chord, and 269 lb down and 111 lb up at 4-11-2, 55 lb down and 37 lb up at 7-0-0, 55 lb down and 37 lb up at 9-0-0, 32 lb down at 10-11-4, 32 lb down at 13-0-0, 30 lb down at 15-0-0, 30 lb down at 17-0-0, and 30 lb down at 19-0-0, and 262 lb down and 79 lb up at 21-3-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15,
Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-3=-70, 3-4=-70, 4-9=-70, 2-21=-20, 3-18=-20,
12-15=-20, 16-17=-20, 10-11=-20
Concentrated Loads (lb)



April 11, 2024

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

WARNING – Verify design parameters and READ NOTES on this and INCLUDED MITER KEEF ELEMENT # ASL-111473 before use. Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	A17	Half Hip Girder	1	2	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:02 Page: 2
ID:gPRZAFt?fwKeggwUKSnaBbzX69o-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDontJ4L3C?r

Vert: 4=-17 (B), 7=-45 (B), 14=-23 (B), 18=-23 (B),
12=-262 (B), 20=-269 (B), 22=-17 (B), 23=-17 (B),
24=-48 (B), 25=-48 (B), 26=-45 (B), 27=-45 (B),
28=-54 (B), 29=-54 (B), 30=-23 (B), 31=-23 (B),
32=-23 (B)

RELEASE FOR CONSTRUCTION

AS NOTED FOR PLAN REVIEW

DEVELOPMENT SERVICES

164799588

LEE'S SUMMIT, MISSOURI

05/02/2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	RELEASE FOR CONSTRUCTION AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 164799589 LEE'S SUMMIT, MISSOURI
B240069	B1	Common Supported Gable	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:02 Page: 1
ID:p6BPZ7Ybm_3YaxR7zAJG9zX7L6-RfC?PsB70Hq3NSgPqnL8w3uiTXbCKWwCD0rJ42u0?r

05/02/2024



Scale = 1:50.7

Plate Offsets (X, Y): [13:Edge,0-3-8]												
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.10	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.09	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.13	Horz(CT)	0.01	13	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R							Weight: 103 lb	FT = 10%

LUMBER	
TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x4 SPF No.2
OTHERS	2x4 SPF No.2

WEBS 4-20=-134/41, 3-21=-152/80, 2-22=-134/86,
5-19=-150/79, 6-18=-138/79, 7-17=-140/77,
8-16=-140/81, 9-15=-140/67, 10-14=-139/121

BRACING	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(size)	13=20-0-0, 14=20-0-0, 15=20-0-0, 16=20-0-0, 17=20-0-0, 18=20-0-0, 19=20-0-0, 20=20-0-0, 21=20-0-0, 22=20-0-0, 23=20-0-0
Max Horiz		23=-242 (LC 4)
Max Uplift		13=-38 (LC 5), 14=-125 (LC 9), 15=-35 (LC 9), 16=-59 (LC 9), 17=-53 (LC 9), 18=-55 (LC 9), 19=-55 (LC 9), 21=-59 (LC 8), 22=-47 (LC 8), 23=-31 (LC 9)
Max Grav		13=210 (LC 15), 14=182 (LC 22), 15=179 (LC 1), 16=180 (LC 22), 17=180 (LC 22), 18=178 (LC 1), 19=190 (LC 22), 20=174 (LC 16), 21=192 (LC 21), 22=173 (LC 1), 23=67 (LC 15)

FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-23=-74/51, 1-2=-86/76, 2-3=-81/97, 3-4=-83/126, 4-5=-87/131, 5-6=-104/119, 6-7=-118/106, 7-8=-133/92, 8-9=-148/79, 9-10=-159/72, 10-11=-207/78, 11-12=0/32, 11-13=-175/44
BOT CHORD	22-23=-68/200, 21-22=-68/200, 20-21=-68/200, 19-20=-68/200, 18-19=-68/200, 17-18=-68/200, 16-17=-68/200, 15-16=-68/200, 14-15=-68/200, 13-14=-68/200

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 2x4 MT20 unless otherwise indicated.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 7) Gable studs spaced at 2-0-0 oc.
 - 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 10) All bearings are assumed to be SPF No.2.
 - 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 31 lb uplift at joint 23, 38 lb uplift at joint 13, 59 lb uplift at joint 21, 47 lb uplift at joint 22, 55 lb uplift at joint 19, 55 lb uplift at joint 18, 53 lb uplift at joint 17, 59 lb uplift at joint 16, 35 lb uplift at joint 15 and 125 lb uplift at joint 14.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	B2	Common	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:02 Page: 1
ID:3TPMs4uDd52oO?QSz_olqZzX7JN-RfC?PsB70Hq3NSgPqnL8w3ulTXbCKWrCDon7d423C7f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799590
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:53.9

Plate Offsets (X, Y): [6:0-3-5,0-5-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.77	Vert(LL)	-0.32	7-9	>732	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.51	Vert(CT)	-0.49	7-9	>477	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.62	Horz(CT)	0.02	6	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.03	7-9	>999	240	Weight: 74 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF 2400F 2.0E
WEBS 2x3 SPF No.2 *Except* 9-1:2x4 SPF No.2,
6-4:2x6 SP 2400F 2.0E

6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 149 lb uplift at joint 6 and 107 lb uplift at joint 9.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-11-13 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 2-9

REACTIONS (size) 6=0-3-8, 9=0-3-8

Max Horiz 9=-243 (LC 4)
Max Uplift 6=-149 (LC 9), 9=-107 (LC 9)
Max Grav 6=993 (LC 2), 9=960 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-174/110, 2-3=-1080/202,
3-4=-1314/207, 4-5=0/35, 1-9=-210/89,
4-6=-862/202
BOT CHORD 7-9=0/546, 6-7=-90/1084
WEBS 2-9=-769/118, 2-7=-102/817, 3-7=-450/274

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) All bearings are assumed to be SPF 2400F 2.0E .



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Wheeler Lumber, Waverly, KS - 66871.

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 '24 15:45:02 Page: 1
ID: rvaNWVQit62n7Wesv9a4ULzX7HO-RfC?PsB70Hg3NSqPanL8w3ulTxbGxWrcDofJ3423Cpf

05/02/2024



Scale = 1:51.1

Plate Offsets (X, Y): [4:Edge.0-5-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.61	Vert(LL)	-0.33	6-8	>705	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.50	Vert(CT)	-0.53	6-8	>444	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.61	Horz(CT)	0.02	5	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.07	6-8	>999	240	Weight: 73 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF 2400F 2.0E
WEBS 2x3 SPF No.2 *Except* 8-1:2x4 SPF No.2,
5-4:2x6 SP 2400F 2.0E

7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 106 lb uplift at joint 8 and 122 lb uplift at joint 5.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-2-9 oc purlins, except end verticals.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

WEBS	1 Row at midpt	2-8
------	----------------	-----

REACTIONS (size) 5= Mechanical. 8=0-3-8

Max Horiz 8=-232 (LC 6)

Max Uplift 5=-122 (LC 9), 8=-106 (LC 9)

Max Grav 5=922 (LC 2), 8=954 (LC 2)

FORCES

(Ib) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-176/110, 2-3=-1061/199,
3-4=-1293/205, 1-8=-211/89, 4-5=-762/170

BOT CHORD 6-8=0/532, 5-6=-112/1071

WEBS 2-8=-756/116, 2-6=-99/797, 3-6=-459/276

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grf DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) Bearings are assumed to be: Joint 8 SPF 2400F 2.0E , Joint 5 SPF No.2 .
- 6) Refer to girder(s) for truss to truss connections.



April 11, 2024



Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcscomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 164799592 LEE'S SUMMIT, MISSOURI
B240069	B4	Roof Special Girder	1	2	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:02 Page: 1
ID:nMoVswEWIrgwz4XecUXWKDzX6Q7-RFC?PsB70Hq3NSgPqnL8w3uITXGKWrcDof7342JC?

05/02/2024



Scale = 1:64.6

Plate Offsets (X, Y): [4:0-6-4,Edge], [6:0-6-0,0-0-15], [7:Edge,0-0-13], [12:0-2-4,0-2-4], [15:0-3-8,0-4-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.55	Vert(LL)	-0.47	13-14	>763	360	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.80	Vert(CT)	-0.83	13-14	>427	240	
BCLL	0.0*	Rep Stress Incr	NO	WB	0.96	Horz(CT)	0.14	7	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.36	13-14	>997	240	Weight: 359 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2 *Except* 2-4:2x6 SPF No.2, 4-6:2x4 SPF 2100F 1.8E

BOT CHORD 2x6 SPF No.2 *Except* 13-11:2x4 SPF No.2, 16-12:2x8 SP 2400F 2.0E

WEBS 2x4 SPF No.2 *Except* 11-12:2x3 SPF No.2

WEDGE Right: 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-9-11 oc purlins, except end verticals, and 2-0-0 oc purlins (4-2-11 max.): 4-6.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size) 7=0-3-8, 18=0-3-8

Max Horiz 18=257 (LC 4)

Max Uplift 7=468 (LC 9), 18=247 (LC 9)

Max Grav 7=2477 (LC 1), 18=1732 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-1319/272, 2-3=-1354/241, 3-4=-4515/721, 4-5=-12157/1987, 5-6=-9732/1668, 6-7=-4626/841, 7-8=0/6, 1-18=-1663/272

BOT CHORD 17-18=-51/236, 15-17=-500/4022, 14-15=-1886/12118, 13-14=-1601/9972, 12-13=-1494/9356, 11-13=-529/2933, 10-11=-600/3480, 9-10=-646/3858, 7-9=-670/3946

WEBS 1-17=-200/1433, 2-17=-95/741, 3-17=-3326/666, 3-15=-308/2483, 4-14=-307/299, 5-14=-310/2311, 9-12=-51/85, 6-12=-929/5968, 6-9=-6/495, 10-12=-305/169, 5-12=-1219/315, 4-15=-8288/1418, 11-12=-3826/659

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-6-0 oc, 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x8 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc, 2x3 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 247 lb uplift at joint 18 and 468 lb uplift at joint 7.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 131 lb down and 73 lb up at 30-2-4, and 131 lb down and 75 lb up at 32-2-4, and 131 lb down and 75 lb up at 34-3-10 on top chord, and 958 lb down and 127 lb up at 28-1-4, 51 lb down at 30-2-4, and 51 lb down at 32-2-4, and 258 lb down and 53 lb up at 34-2-4 on bottom chord. The design/selection of such connection device (s) is the responsibility of others.

LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-4=-70, 4-6=-70, 6-8=-70, 13-18=-20, 7-11=-20
Concentrated Loads (lb)
Vert: 6=-81 (F), 13=-889 (F), 9=-258 (F), 19=-81 (F), 20=-81 (F), 21=-37 (F), 22=-37 (F)



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcscomponents.com)


MiTek®16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	B5	Roof Special	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:02 Page: 1
ID: LpJgzjyKVTktAt?7Ua7zd9zX6T5-RfC?PsB70Hq3NSgPqnL8w3ulTxbGKV/rCDoi7Jz2Jb?1

05/02/2024



Scale = 1:60.1

Plate Offsets (X, Y): [4:0-7-8,0-2-0], [6:0-4-12,Edge], [9:0-3-8,0-2-12], [12:0-11-0,0-3-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.84	Vert(LL)	-0.42	13	>842	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.97	Vert(CT)	-0.75	13-15	>477	240	M18AHS	142/136
BCLL	0.0*	Rep Stress Incr	YES	WB	1.00	Horz(CT)	0.15	9	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.30	12-13	>999	240	Weight: 127 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2 *Except* 2-4:2x4 SPF 2100F 1.8E
BOT CHORD	2x4 SPF No.2 *Except* 5-11:2x3 SPF No.2, 14-12:2x4 SPF 2100F 1.8E
WEBS	2x3 SPF No.2 *Except* 13-3,16-2:2x4 SPF No.2, 9-7:2x6 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 3-0-5 oc purlins, except end verticals, and 2-0-0 oc purlins (2-2-0 max.): 4-6.
BOT CHORD	Rigid ceiling directly applied or 2-2-0 oc bracing.

WEBS	1 Row at midpt	3-15, 2-16
------	----------------	------------

REACTIONS (size) 9=0-3-8, 16=0-3-8
 Max Horiz 16=-267 (LC 4)
 Max Uplift 9=-248 (LC 9), 16=-177 (LC 9)
 Max Grav 9=1446 (LC 2), 16=1419 (LC 2)

FORCES

Tension

TOP CHORD 1-2=-153/112, 2-3=-1590/293,
3-4=-5154/818, 4-5=-4674/689,
5-6=-4607/739, 6-7=-2242/360, 7-8=0/35,
1-16=-198/86, 7-9=-1354/275

BOT CHORD 15-16=0/894, 13-15=-143/1992,
12-13=-627/4661, 11-12=0/84,
5-12=-421/106, 10-11=-13/170,
9-10=-151/496

WEBS 2-15=-230/1578, 3-15=-1312/371,
3-13=-558/3519, 4-13=-2447/462,
5-13=-49/147, 10-12=-239/1840,
6-12=-411/2897, 6-10=-486/138,
2-16=-1393/188, 7-10=-90/1460

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) All plates are MT20 plates unless otherwise indicated.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) All bearings are assumed to be SPF No.2 .
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 248 lb uplift at joint 9 and 177 lb uplift at joint 16.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

NOTES

- 1) Unbalanced roof live loads have been considered for this design.



April 11, 2024



WARNING – Verify design parameters and READ NOTES on THIS and INCLUDED MITER KEEF REFERENCE ASSESSMENT REPORT (MFR) BEFORE USE. Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinet.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-UIS.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	B6	Roof Special	2	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:Z6cEIJb?PEaJuf?S2LYCoozX6VL-RfC?PsB70Hq3NSgPqnL8w3ulTXbGK?VrCDoi7J42J647

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799594
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:60.1									
Plate Offsets (X, Y): [8:0-3-4,0-2-12], [11:0-5-12,0-4-4]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	l/defl	L/d
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.75	Vert(LL)	-0.25 11-12	>999	360
TCDL	10.0	Lumber DOL	1.15	BC	0.94	Vert(CT)	-0.48 12-14	>734	240
BCLL	0.0*	Rep Stress Incr	YES	WB	0.89	Horz(CT)	0.13 8	n/a	n/a
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.19 11-12	>999	240
								Weight: 133 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2 *Except* 2-3:2x6 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 15-13:2x4 SPF 2100F 1.8E, 4-10:2x3 SPF No.2
WEBS 2x3 SPF No.2 *Except* 14-3:2x4 SPF No.2, 15-1:2x4 SP No.2, 8-6:2x6 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (2-9-2 max.): 3-5.
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 2 Rows at 1/3 pts 3-14


REACTIONS (size) 8=0-3-8, 15=0-3-8
Max Horiz 15=267 (LC 4)
Max Uplift 8=248 (LC 9), 15=177 (LC 9)
Max Grav 8=1412 (LC 1), 15=1332 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=1012/214, 2-3=1077/162, 3-4=3379/542, 4-5=3156/546, 5-6=2145/357, 6-7=0/35, 1-15=1297/200, 6-8=1340/288
BOT CHORD 14-15=69/228, 12-14=394/3381, 11-12=401/3184, 10-11=0/20, 4-11=438/96, 9-10=15/73, 8-9=254/763
WEBS 2-14=0/413, 3-14=2678/543, 3-12=80/140, 4-12=0/240, 9-11=219/1886, 5-11=245/1854, 5-9=666/155, 1-14=136/1091, 6-9=42/1051

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Bearings are assumed to be: Joint 15 SPF 2100F 1.8E , Joint 8 SPF No.2 .
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 177 lb uplift at joint 15 and 248 lb uplift at joint 8.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	RELEASE FOR CONSTRUCTION
B240069	B7	Roof Special	2	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW
						DEVELOPMENT SERVICES
						164799595
						LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:J0xi1a22YLkeclpOYbs9_zzX6Wp-RfC?PsB70Hq3NSgPqnL8w3ulTXbGK1WrCDoi7J42J641

05/02/2024



Scale = 1:62.1									
Plate Offsets (X, Y): [1:0-2-0,0-1-8], [3:0-6-0,0-2-1], [5:0-4-12,Edge], [7:Edge,0-3-4]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	l/defl	L/d
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.92	Vert(LL)	-0.19 12-13	>999	360
TCDL	10.0	Lumber DOL	1.15	BC	0.75	Vert(CT)	-0.39 12-13	>921	240
BCLL	0.0*	Rep Stress Incr	YES	WB	0.80	Horz(CT)	0.14 9	n/a	n/a
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.14 12-13	>999	240
								Weight: 126 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2 *Except* 3-5:2x4 SPF 2100F 1.8E
BOT CHORD 2x4 SPF No.2 *Except* 4-11:2x3 SPF No.2
WEBS 2x3 SPF No.2 *Except* 14-3,9-7:2x4 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (4-1-11 max.): 3-5.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 10-11.
WEBS 1 Row at midpt 3-14, 6-9

REACTIONS (size) 9=0-3-8, 15=0-3-8
Max Horiz 15=267 (LC 4)
Max Uplift 9=247 (LC 9), 15=177 (LC 9)
Max Grav 9=1411 (LC 1), 15=1338 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-1002/222, 2-3=-1061/185, 3-4=-2607/440, 4-5=-2533/472, 5-6=-2014/362, 6-7=-601/110, 7-8=0/32, 1-15=-1291/207, 7-9=-481/130
BOT CHORD 14-15=-67/228, 13-14=-251/2606, 12-13=-289/2556, 11-12=-182/0, 4-12=-528/204, 10-11=-33/58, 9-10=-296/1840
WEBS 2-14=-24/435, 3-14=-1994/417, 3-13=0/213, 4-13=-7/82, 10-12=-189/2336, 5-12=-343/2308, 5-10=-1334/186, 1-14=-142/1085, 6-9=-1614/309, 6-10=-115/151

NOTES
1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) All bearings are assumed to be SPF No.2 .
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 177 lb uplift at joint 15 and 247 lb uplift at joint 9.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	RELEASE FOR CONSTRUCTION
B240069	B8	Roof Special	2	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW
						DEVELOPMENT SERVICES
						164799596
						LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID: ?Woe0hKLDpXyKNvf3ndhpzX6Z2-RfC?PsB70Hq3NSgPqnL8w3ulTXbGHWrCDoi734z3C7

05/02/2024



Scale = 1:60.7

Plate Offsets (X, Y): [1:0-2-0,0-1-8], [4:0-6-12,0-1-4], [9:Edge,0-5-13]												
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.82	Vert(LL)	-0.26	13-14	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.98	Vert(CT)	-0.47	12-13	>758	240	M18AHS	142/136
BCLL	0.0*	Rep Stress Incr	YES	WB	0.87	Horz(CT)	0.08	9	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.13	12-13	>999	240	Weight: 128 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2 *Except* 3-4:2x4 SPF 2100F 1.8E
BOT CHORD 2x4 SPF No.2 *Except* 5-11:2x3 SPF No.2
WEBS 2x3 SPF No.2 *Except* 9-7:2x4 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 3-1-3 oc purlins, except end verticals, and 2-0-0 oc purlins (3-4-13 max.): 3-4.
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 1 Row at midpt 2-14, 1-15

REACTIONS (size) 9=0-3-8, 15=0-3-8
Max Horiz 15=-267 (LC 4)
Max Uplift 9=-247 (LC 9), 15=-177 (LC 9)
Max Grav 9=1449 (LC 2), 15=1426 (LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-657/151, 2-3=-2498/474, 3-4=-2191/357, 4-5=-2148/406, 5-6=-2377/409, 6-7=-2261/371, 7-8=0/32, 1-15=-1489/175, 7-9=-1352/271
BOT CHORD 14-15=-69/226, 13-14=0/898, 12-13=-188/2063, 11-12=0/90, 5-12=-153/330, 10-11=-29/44, 9-10=-115/471
WEBS 2-14=-868/180, 2-13=-400/2201, 3-13=-1507/409, 4-13=-3/185, 4-12=0/366, 10-12=-233/1964, 6-12=-53/153, 6-10=-432/135, 1-14=-95/1195, 7-10=-142/1491

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- All bearings are assumed to be SPF No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 177 lb uplift at joint 15 and 247 lb uplift at joint 9.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard






April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcscomponents.com)

MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

LOAD CASE(S) Standard



Scale = 1:32.9

Plate Offsets (X, Y): [4:0-4-0,0-1-13]												
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.84	Vert(LL)	-0.09	8	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.64	Vert(CT)	-0.15	7-8	>632	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.36	Horz(CT)	0.08	6	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.08	8	>999	240	Weight: 27 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2 *Except* 9-2:2x6 SP 2400F 2.OE

BRACING
TOP CHORD Structural wood sheathing directly applied or 3-11-13 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 6=0-3-8, 9=0-3-8
Max Horiz 9=97 (LC 22)
Max Uplift 6=-150 (LC 5), 9=-128 (LC 8)
Max Grav 6=575 (LC 1), 9=573 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 2-9=-845/220, 1-2=0/30, 2-3=-1251/278, 3-4=-1034/272, 4-5=-49/25, 5-6=-134/70
BOT CHORD 8-9=-299/1080, 7-8=-270/984, 6-7=-267/955
WEBS 3-8=-53/265, 4-7=-50/388, 4-6=-1000/281

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Provide adequate drainage to prevent water ponding.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 5) All bearings are assumed to be SPF No.2 .
 - 6) Bearing at joint(s) 9 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 128 lb uplift at joint 9 and 150 lb uplift at joint 6.
 - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 81 lb down and 67 lb up at 4-11-2, and 86 lb down and 66 lb up at 7-0-0 on top chord, and 237 lb down and 64 lb up at 4-11-2, and 30 lb down at 7-0-0 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
 - 10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-4=-70, 4-5=-70, 8-9=-20, 6-8=-20
Concentrated Loads (lb)
Vert: 7=-237 (B), 4=-45 (B), 10=-45 (B), 11=-23 (B)






Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	C3	Monopitch	2	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871.

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 '25 05:45:03 Page: 1
ID:sAzw?S1sZyC4WUjxOHlCAtzX717-RfC?PsB70Hq3NSgPqnL8w3ulTXbGjWRcDofJ4ZJC#f

05/02/2024



Scale = 1:34.7

Plate Offsets (X, Y): [4:0-3-3,Edge], [5:Edge,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.63	Vert(LL)	-0.22	5-6	>437	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.37	Vert(CT)	-0.39	5-6	>246	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.16	5	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.22	5-6	>429	240	Weight: 24 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF 2100F 1.8E
BOT CHORD	2x4 SPF 2100F 1.8E
WEBS	2x3 SPF No.2 *Except* 7-2:2x6 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	5=0-3-8, 7=0-3-8
Max Horiz	7=157 (LC 5)
Max Uplift	5=-85 (LC 8), 7=-74 (LC 8)
Max Grav	5=355 (LC 1), 7=443 (LC 1)

FORCES

(Ib) - Maximum Compression/Maximum Tension

TOP CHORD 2-7=-347/45, 1-2=0/30, 2-3=-192/0,
3-4=-131/17, 4-5=-238/97

BOT CHORD 6-7=-28/82, 5-6=-36/80
WEBS 3-6=-54/116

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grf DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF 2100F 1.8E .
- 5) Bearing at joint(s) 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 74 lb uplift at joint 7 and 85 lb uplift at joint 5.

LOAD CASE(S) Standard



April 11, 2024




Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcscomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:04 Page: 1
ID:OK2gdB2Ynmn9bP84JwGvaaxZ7?p-RfC?PsB70HQ3NSgPqnL8w3uLTxbGKWrcDofJ4z2G?i



April 11, 2024

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	D1	Hip Girder	1	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:04 Page: 1

ID:9m061JEEmDMu4fGaHK?HCxEzX6iC-RfC?PsB70Hq3NSgPqnL8w3ulTXhGKWrCDor7342JC?

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799602
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:37.4

Plate Offsets (X, Y): [2:0-3-8,Edge], [3:0-1-8,0-3-7], [4:0-6-0,0-2-2], [7:0-3-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.06	11-12	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.61	Vert(CT)	-0.12	11-12	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.10	Horz(CT)	0.06	7	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.06	11-12	>999	240	Weight: 48 lb	FT = 10%

LUMBER

TOP CHORD 2x6 SPF No.2 *Except* 4-5:2x4 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 14-3:6-9:2x6 SP
2400F 2.0E
WEBS 2x3 SPF No.2
WEDGE Left: 2x3 SPF No.2
Right: 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
5-6-9 oc purlins, except
2-0-0 oc purlins (3-4-2 max.): 4-5.
BOT CHORD Rigid ceiling directly applied or 9-3-13 oc
bracing.

REACTIONS

(size) 2=0-3-8, 7=0-3-8
Max Horiz 2=-34 (LC 9)
Max Uplift 2=-188 (LC 8), 7=-185 (LC 9)
Max Grav 2=789 (LC 1), 7=779 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum
Tension
TOP CHORD 1-2=0/6, 2-3=-982/229, 3-4=-1698/440,
4-5=-1572/404, 5-6=-1664/417,
6-7=-967/227, 7-8=0/6
BOT CHORD 2-14=-169/690, 13-14=0/42, 3-13=-28/6,
12-13=-403/1583, 11-12=-403/1605,
10-11=-361/1549, 9-10=0/42, 6-10=-33/6,
7-9=-146/679
WEBS 4-12=-9/295, 4-11=-115/56, 5-11=-16/310

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed ; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.

- 5) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 6) All bearings are assumed to be SPF No.2 .
- 7) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 188 lb uplift at joint
2 and 185 lb uplift at joint 7.
- 8) Graphical purlin representation does not depict the size
or the orientation of the purlin along the top and/or
bottom chord.
- 9) Hanger(s) or other connection device(s) shall be
provided sufficient to support concentrated load(s) 159
lb down and 93 lb up at 3-0-5, 81 lb down and 46 lb up
at 5-1-1, and 81 lb down and 46 lb up at 6-10-15, and
74 lb down and 47 lb up at 8-11-11 on top chord, and 78
lb down and 43 lb up at 3-0-5, 33 lb down and 17 lb up
at 5-1-1, and 33 lb down and 17 lb up at 6-10-15, and
78 lb down and 43 lb up at 8-10-3 on bottom chord.
The design/selection of such connection device(s) is the
responsibility of others.
- 10) In the LOAD CASE(S) section, loads applied to the face
of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15,
Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-4=-70, 4-5=-70, 5-8=-70, 2-14=-20,
10-13=-20, 7-9=-20
Concentrated Loads (lb)
Vert: 4=-51 (B), 5=-33 (B), 12=-78 (B), 11=-78 (B),
15=-33 (B), 16=-33 (B), 17=-33 (B), 18=-33 (B)



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com




Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	D3	Roof Special	2	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:04 Page: 1
ID:JBH?fxJ1gWse4qwjW6ww?izX6kh-RfC?PsB70Hq3NSgPqnL8w3uITXbGHWrCDoit34z3C7?

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799604
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:37.2									
Plate Offsets (X, Y): [8:Edge,0-3-8]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	l/defl	L/d
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.42	Vert(LL)	-0.08 10-11	>999	360
TCDL	10.0	Lumber DOL	1.15	BC	0.50	Vert(CT)	-0.14 10-11	>999	240
BCLL	0.0*	Rep Stress Incr	YES	WB	0.09	Horz(CT)	0.11 8	n/a	n/a
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.08 11-12	>999	240
						PLATES		GRIP	
						MT20		197/144	
						Weight: 37 lb		FT = 10%	

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2 *Except* 11-4:2x3 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 5-10-1 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 8=0-3-8, 14=0-3-8
Max Horiz 14=64 (LC 6)
Max Uplift 8=88 (LC 9), 14=88 (LC 8)
Max Grav 8=598 (LC 1), 14=598 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/32, 2-3=-584/75, 3-4=-753/91, 4-5=-753/105, 5-6=-584/76, 6-7=0/32, 2-14=-544/97, 6-8=-544/93
BOT CHORD 13-14=-71/416, 12-13=-20/18, 3-12=-55/55, 11-12=-24/653, 10-11=-24/653, 9-10=-20/16, 5-10=-55/56, 8-9=-30/416
WEBS 4-11=0/276

6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 88 lb uplift at joint 14 and 88 lb uplift at joint 8.

LOAD CASE(S) Standard

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 5) All bearings are assumed to be SPF No.2 .



April 11,2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	D4	Common	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:04 Page: 1

ID:IfFhA9xatGi7AKrnbwwbrMzX6Db-RfC?PsB70Hq3NSgPqnL8w3uITXbGKW/rCDoi7J4ZJ03

RELEASE FOR CONSTRUCTION


AS NOTED FOR PLAN REVIEW

DEVELOPMENT SERVICES

164799605

LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:31.6

Plate Offsets (X, Y): [3:Edge,0-3-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.47	Vert(LL)	-0.03	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.26	Vert(CT)	-0.06	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.07	Horz(CT)	0.01	4	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.01	5-6	>999	240	Weight: 33 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2 *Except* 5-2:2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
6'-0" oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10'-0" oc
bracing.

REACTIONS (size) 4=0-3-8, 6=0-3-8

Max Horiz 6=-57 (LC 4)
Max Uplift 4=-64 (LC 9), 6=-64 (LC 8)
Max Grav 4=527 (LC 1), 6=527 (LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 1-2=-642/89, 2-3=-642/89, 1-6=-458/102,
3-4=-458/102

BOT CHORD 5-6=-24/488, 4-5=-24/488

WEBS 2-5=0/236

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
- 5) All bearings are assumed to be SPF No.2 .
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 64 lb uplift at joint 6 and 64 lb uplift at joint 4.

LOAD CASE(S) Standard




April 11,2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com



16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-UIS.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J2	Jack-Open	1	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:04 Page: 1
ID: xnkGUwOwtzy37YrMGw5sbOzX6n9-RfC?PsB70Hq3NSgPqnL8w3uITXbCKWwCD0rJ42dC?r

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799607
LEE'S SUMMIT, MISSOURI

05/02/2024

-0-10-8	2-2-6
0-10-8	2-2-6



Scale = 1:23.4

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 7 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
2-2-6 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical,
5=0-3-8
Max Horiz 5=52 (LC 8)
Max Uplift 3=-37 (LC 8), 5=-23 (LC 8)
Max Grav 3=56 (LC 1), 4=38 (LC 3), 5=177
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 2-5=-155/44, 1-2=0/31, 2-3=-42/19
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 23 lb uplift at joint
5 and 37 lb uplift at joint 3.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com




Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J4	Jack-Closed	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:hWd0TDty?lY9Tx35FOpnLKzX6nq-RfC?PsB70Hq3NSgPqnL8w3uITXbGhWrCDoin34Z0C7#

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799609
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:33.3												
Plate Offsets (X, Y): [3:Edge,0-2-7]												
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.44	Vert(LL)	-0.04	5-6	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.27	Vert(CT)	-0.09	5-6	>738	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	5	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.03	5-6	>999	240	Weight: 18 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2 *Except* 4-5:2x3 SPF No.2
BRACING
TOP CHORD Structural wood sheathing directly applied or 5-11-4 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-4.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS (size) 5= Mechanical, 6=0-3-8
Max Horiz 6=144 (LC 5)
Max Uplift 5=-61 (LC 8), 6=-54 (LC 8)
Max Grav 5=250 (LC 1), 6=334 (LC 1)
FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 2-6=-292/101, 1-2=0/32, 2-3=-153/32, 3-4=-57/47, 4-5=-177/83
BOT CHORD 5-6=-42/43

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 6) All bearings are assumed to be SPF No.2.
 - 7) Refer to girder(s) for truss to truss connections.

- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 54 lb uplift at joint 6 and 61 lb uplift at joint 5.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	J5	Jack-Open	8	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:hRWJCz2l0szpJUs0G6bqb_zX6ou-RfC?PsB70Hq3NSgPqnL8w3uITXbGtWwCDor73429C7#

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799610
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:27.7

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.52	Vert(LL)	-0.05	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.31	Vert(CT)	-0.11	4-5	>610	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.04	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.06	4-5	>999	240	Weight: 16 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical, 5=0-3-8
Max Horiz 5=127 (LC 8)
Max Uplift 3=99 (LC 8), 5=33 (LC 8)
Max Grav 3=180 (LC 1), 4=108 (LC 3), 5=336 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=293/89, 1-2=0/32, 2-3=112/62
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 33 lb uplift at joint 5 and 99 lb uplift at joint 3.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J6	Jack-Open	7	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:sk6BoHZCRZxUWLokWitSzYzX6pW-RfC?PsB70Hq3NSgPqnL8w3uITXb6KWrcD0WJ42JC7?

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799611
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:30.3

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.53	Vert(LL)	-0.05	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.29	Vert(CT)	-0.11	4-5	>598	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.05	4	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.06	5-6	>999	240	Weight: 16 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical, 6=0-3-8
Max Horiz 6=127 (LC 8)
Max Uplift 3=-100 (LC 8), 6=-32 (LC 8)
Max Grav 3=180 (LC 1), 4=108 (LC 3), 6=336 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-6=-292/88, 1-2=0/32, 2-3=-112/63
BOT CHORD 5-6=-46/1, 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint 3 and 32 lb uplift at joint 6.



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	J7	Jack-Closed	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1

ID: VVntBmlPdp9ctz76d5UI4vzX6ps-RfC?PsB70Hq3NSgPqnL8w3uITXbGK/rCDoi7J4zJCA

05/02/2024



Scale = 1:32.8

Plate Offsets (X, Y): [4:Edge,0-2-7]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.39	Vert(LL)	-0.03	7	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.25	Vert(CT)	-0.05	7	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.09	Horz(CT)	0.02	6	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.02	7	>999	240	Weight: 21 lb FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 5-11-4 oc purlins, except end verticals, and 2-0-0 oc purlins: 4-5.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	6= Mechanical, 8=0-3-8
Max Horiz	8=128 (LC 5)
Max Uplift	6=-64 (LC 8), 8=-51 (LC 8)
Max Grav	6=252 (LC 1), 8=332 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	2-8=-398/108, 1-2=0/31, 2-3=-452/103, 3-4=-72/25, 4-5=-37/27, 5-6=-118/40
BOT CHORD	7-8=-135/360, 6-7=-123/325
WEBS	3-7=-7/175, 3-6=-317/147

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2 .
- Refer to girder(s) for truss to truss connections.

- Bearing at joint(s) 8 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 51 lb uplift at joint 8 and 64 lb uplift at joint 6.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J8	Jack-Closed Girder	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:juB8EnNkWSaOIHJVA77T?tzX6r2-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi734z3G7

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799613
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:33.3

Plate Offsets (X, Y): [4:0-3-0,0-2-0]												
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	-0.03	8	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.41	Vert(CT)	-0.05	8	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.14	Horz(CT)	0.03	6	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.03	8	>999	240	Weight: 20 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2 *Except* 9-2:2x4 SPF 2100F 1.8E

BRACING
TOP CHORD Structural wood sheathing directly applied or 5-11-4 oc purlins, except end verticals, and 2-0-0 oc purlins: 4-5.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 6= Mechanical, 9=0-3-8
Max Horiz 9=94 (LC 22)
Max Uplift 6=-120 (LC 5), 9=-93 (LC 8)
Max Grav 6=476 (LC 1), 9=453 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 2-9=-583/153, 1-2=0/32, 2-3=-730/157, 3-4=-569/170, 4-5=-27/19, 5-6=-64/33
BOT CHORD 8-9=-175/586, 7-8=-160/543, 6-7=-156/518
WEBS 3-8=-17/148, 4-7=-75/340, 4-6=-632/195

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Provide adequate drainage to prevent water ponding.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 5) All bearings are assumed to be SPF No.2 .
 - 6) Refer to girder(s) for truss to truss connections.

- 7) Bearing at joint(s) 9 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 120 lb uplift at joint 6 and 93 lb uplift at joint 9.
 - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 10) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 102 lb down and 75 lb up at 3-11-6 on top chord, and 264 lb down and 55 lb up at 3-11-6 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
 - 11) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-4=-70, 4-5=-70, 8-9=-20, 6-8=-20
Concentrated Loads (lb)
Vert: 7=-264 (B), 4=-82 (B)



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	J9	Diagonal Hip Girder	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:36eLx9FDUblZYIjwUh8VOazX74i-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJG7

05/02/2024



Scale = 1:30.6

Plate Offsets (X, Y): [5:Edge,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	-0.05	6-7	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.25	Vert(CT)	-0.09	6-7	>734	240	197/144
BCLL	0.0*	Rep Stress Incr	NO	WB	0.02	Horz(CT)	0.03	5	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.05	6-7	>999	240	Weight: 18 lb FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 7-2:2x4 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(size) 5= Mechanical, 7=0-3-11
	Max Horiz 7=96 (LC 22)
	Max Uplift 5=-56 (LC 8), 7=-110 (LC 4)
	Max Grav 5=249 (LC 1), 7=383 (LC 1)

FORCES	(lb) - Maximum Compression/Maximum Tension
---------------	--

TOP CHORD	2-7=-353/134, 1-2=0/32, 2-3=-208/9, 3-4=-126/44, 4-5=-140/36
BOT CHORD	6-7=-48/142, 5-6=-47/137
WEBS	3-6=-18/76

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 110 lb uplift at joint 7 and 56 lb uplift at joint 5.
 - 8) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 80 lb down and 49 lb up at 3-0-14, and 67 lb down and 42 lb up at 3-6-3 on top chord, and 7 lb down at 3-0-14, and 6 lb down and 0 lb up at 3-6-3 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
 - 9) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-4=-70, 6-7=-20, 5-6=-20
Concentrated Loads (lb)
Vert: 10=-6 (B), 11=0 (F)



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J10	Jack-Open	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:Lf_iibjcs4opGXLTVSMBolzX75O-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWCDoi7J4zuC9W

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799615
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:26.1

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 7 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
2-2-6 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc
bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical,
5=0-3-8
Max Horiz 5=51 (LC 8)
Max Uplift 3=-37 (LC 8), 5=-23 (LC 8)
Max Grav 3=54 (LC 1), 4=36 (LC 3), 5=179
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 2-5=-157/44, 1-2=0/32, 2-3=-42/18
BOT CHORD 4-5=-17/11

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 5 considers parallel to grain value
using ANSI/TPI 1 angle to grain formula. Building
designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 23 lb uplift at joint
5 and 37 lb uplift at joint 3.



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	J11	Jack-Open	1	1	Job Reference (optional)

AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799616
LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:ekNwbhbLC?YD3?ayJLArCBzX75Y-RfC?PsB70Hq3NSgPqnL8w3ulTXbCKWwCDonJ42aU?f

05/02/2024



Scale = 1:22.9

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.08	Vert(LL)	0.00	3-4	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	0.00	3-4	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.00	3-4	>999	240	Weight: 7 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

LOAD CASE(S) Standard**BRACING**

TOP CHORD Structural wood sheathing directly applied or
2-6-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc
bracing.

REACTIONS (size) 2= Mechanical, 3= Mechanical,
4=0-3-8
Max Horiz 4=36 (LC 5)
Max Uplift 2=-39 (LC 8), 4=-4 (LC 8)
Max Grav 2=75 (LC 1), 3=44 (LC 3), 4=103
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 1-4=-86/27, 1-2=-38/23
BOT CHORD 3-4=-12/11

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 4 considers parallel to grain value
using ANSI/TPI 1 angle to grain formula. Building
designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 4 lb uplift at joint 4
and 39 lb uplift at joint 2.



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	J12	Jack-Open	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:LNSH7IWysfDjwYCPNYCQjzX75f-RfC?PsB70Hq3NSgPqnL8w3uITxbGKwRCDot73429C7#

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799617
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:25

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.36	Vert(LL)	-0.02	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.22	Vert(CT)	-0.05	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.02	2	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.03	4-5	>999	240	Weight: 12 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS (size) 2= Mechanical, 3= Mechanical, 5=0-3-8
Max Horiz 5=74 (LC 8)
Max Uplift 2=-76 (LC 8), 5=-15 (LC 8)
Max Grav 2=152 (LC 1), 3=90 (LC 3), 5=213 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-5=-179/60, 1-2=-78/46
BOT CHORD 4-5=-31/7, 3-4=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 15 lb uplift at joint 5 and 76 lb uplift at joint 2.



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J13	Jack-Open	2	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1

ID:6fPtFDPJz5XV8YMTN_u4YpzX75o-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDof73423Cf

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799618
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:25.2

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.21	Vert(LL)	-0.01	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.13	Vert(CT)	-0.02	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.01	4-5	>999	240	Weight: 11 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical, 5=0-3-8
Max Horiz 5=87 (LC 8)
Max Uplift 3=-68 (LC 8), 5=-27 (LC 8)
Max Grav 3=118 (LC 1), 4=72 (LC 3), 5=247 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-215/63, 1-2=0/31, 2-3=-75/41
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 27 lb uplift at joint 5 and 68 lb uplift at joint 3.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	J14	Jack-Closed Girder	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1

ID: A5xqBA73KJ9nRi5IH3nsTfzX6ty-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwCDoi7J4z0C9

05/02/2024



Scale = 1:43.5

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.26	Vert(LL)	-0.01	6-7	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.41	Vert(CT)	-0.02	6-7	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.01	4	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.01	6-7	>999	240	Weight: 12 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2 *Except* 6-2:2x3 SPF No.2
WEBS	2x3 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 3-11-4 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 4= Mechanical, 7=0-3-8

Max Horiz	7=80 (LC 22)
Max Uplift	4=-67 (LC 8), 7=-34 (LC 8)
Max Grav	4=282 (LC 1), 7=278 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD	1-7=-217/35, 1-2=-222/28, 2-3=-43/15, 3-4=-68/20
BOT CHORD	6-7=-38/136, 5-6=-33/107, 2-5=-92/26, 4-5=-20/44

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 34 lb uplift at joint 7 and 67 lb uplift at joint 4.

- 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 153 lb down and 8 lb up at 2-0-0 on top chord, and 109 lb down and 65 lb up at 2-0-0 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-3=-70, 6-7=-20, 4-5=-20
Concentrated Loads (lb)
Vert: 8=-116 (B), 9=-109 (B)



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	J15	Diagonal Hip Girder	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:W8_Jb?dXH6KjrYu_3rDrQ6zX76p-RfC?PsB70Hq3NSgPqnL8w3uITxhBgKWrCDoi74z3C??

05/02/2024



Scale = 1:27.3

Plate Offsets (X, Y): [5:Edge,0-2-8], [6:0-3-0,0-2-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.40	Vert(LL)	-0.06	6	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.27	Vert(CT)	-0.11	6	>604	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.03	Horz(CT)	0.04	5	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.06	6	>999	240	Weight: 18 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2 *Except* 7-2:2x4 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size) 5= Mechanical, 7=0-3-11
 Max Horiz 7=95 (LC 5)
 Max Uplift 5=-55 (LC 8), 7=-109 (LC 4)
 Max Grav 5=245 (LC 1), 7=379 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-7=-348/127, 1-2=0/32, 2-3=-195/0,
3-4=-122/36, 4-5=-149/47
BOT CHORD 6-7=-41/126, 5-6=-42/123
WEBS 3-6=-11/80

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. I; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate girf DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.

- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 109 lb uplift at joint 7 and 55 lb uplift at joint 5.
- 8) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 76 lb down and 44 lb up at 2-11-11, and 67 lb down and 42 lb up at 3-6-3 on top chord, and 4 lb down at 2-11-11, and 6 lb down and 0 lb up at 3-5-2 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 9) In the LOAD CASE(S) section, loads applied to the face of the TRUSS are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15,
Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-4=-70, 6-7=-20, 5-6=-20
Concentrated Loads (lb)
Vert: 6=0 (B), 9=-1 (F)



April 11, 2024



WARNING – Verify design parameters and READ NOTES on this and INCLUDED WITH REFERENCE ASCE MIP-473 Rev. 1/2/2023 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinet.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-USA.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	J16	Jack-Open	5	1	Job Reference (optional)

AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799621
LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:GbMd0UuvPhnEeKISZE8m_SzX77I-RfC?PsB70Hq3NSgPqnL8w3ulTXbCKWrCDn7d42a07f

05/02/2024



Scale = 1:27.9

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.20	Vert(LL)	-0.01	5-6	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.11	Vert(CT)	-0.02	5-6	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.01	5-6	>999	240	Weight: 12 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

LOAD CASE(S) Standard**BRACING**

TOP CHORD Structural wood sheathing directly applied or
3-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc
bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical,
6=0-3-8
Max Horiz 6=86 (LC 8)
Max Uplift 3=-67 (LC 8), 6=-26 (LC 8)
Max Grav 3=115 (LC 1), 4=70 (LC 3), 6=249
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 2-6=-217/64, 1-2=0/32, 2-3=-74/40
BOT CHORD 5-6=-35/3, 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 6 considers parallel to grain value
using ANSI/TPI 1 angle to grain formula. Building
designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 26 lb uplift at joint
6 and 67 lb uplift at joint 3.



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J17	Jack-Open	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:ea4V_hRVmplpKNRUoA0iO8zX7CD-RfC?PsB70Hq3NSgPqnL8w3uITXb6KWrcD07J42J0C7f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799622
LEE'S SUMMIT, MISSOURI

05/02/2024



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.35	Vert(LL)	-0.02	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.21	Vert(CT)	-0.05	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.02	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.02	4-5	>999	240	Weight: 13 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical, 5=0-3-8
Max Horiz 5=90 (LC 8)
Max Uplift 3=-77 (LC 8), 5=-41 (LC 8)
Max Grav 3=151 (LC 1), 4=91 (LC 3), 5=290 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-252/83, 1-2=0/26, 2-3=-79/45
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) The Fabrication Tolerance at joint 5 = 2%, joint 5 = 2%
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 5) All bearings are assumed to be SPF No.2 .
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 41 lb uplift at joint 5 and 77 lb uplift at joint 3.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J18	Jack-Open	3	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1

ID: iONTsZoFFW3KUEulCYZHlzzX7D2-RfC?PsB70Hq3NSgPqnL8w3ulTXbCKWwCDon7d42a07f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799623
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:31.3

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.10	Vert(LL)	-0.01	6	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.19	Vert(CT)	-0.02	7	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.01	5	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.01	6	>999	240	Weight: 12 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 7-3:2x3 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 4= Mechanical, 5= Mechanical, 8=0-3-8
Max Horiz 8=87 (LC 8)
Max Uplift 4=-34 (LC 8), 5=-25 (LC 8), 8=-27 (LC 8)
Max Grav 4=87 (LC 1), 5=74 (LC 1), 8=247 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-8=-224/53, 1-2=0/31, 2-3=-129/0, 3-4=-21/35
BOT CHORD 7-8=-37/66, 6-7=0/53, 3-6=-22/45, 5-6=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 27 lb uplift at joint 8, 34 lb uplift at joint 4 and 25 lb uplift at joint 5.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J19	Jack-Open	2	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:dwX_6b1Ni6ibovxr4OI7VzX7ML-RfC?PsB70Hq3NSgPqnL8w3ulTXbGK1WrCDoi7J42JG41

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799624
LEE'S SUMMIT, MISSOURI

05/02/2024

-0-10-8	2-2-6
0-10-8	2-2-6



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 7 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
2-2-6 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical,
5=0-3-8
Max Horiz 5=52 (LC 8)
Max Uplift 3=-37 (LC 8), 5=-23 (LC 8)
Max Grav 3=56 (LC 1), 4=38 (LC 3), 5=177
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 2-5=-155/44, 1-2=0/31, 2-3=-42/19
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 23 lb uplift at joint
5 and 37 lb uplift at joint 3.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J20	Jack-Open	3	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:de06QIONNUyA2B6gL0amxvzX7Mc-RfC?PsB70Hq3NSgPqnL8w3uITXb3KWrcDmJ42JC?

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799625
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:23

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.06	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 7 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
2-6-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical,
5=0-3-8
Max Horiz 5=48 (LC 8)
Max Uplift 3=-38 (LC 8), 5=-31 (LC 4)
Max Grav 3=67 (LC 1), 4=44 (LC 3), 5=188
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 2-5=-165/52, 1-2=0/26, 2-3=-40/20
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 31 lb uplift at joint
5 and 38 lb uplift at joint 3.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	J21	Diagonal Hip Girder	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1

ID:poYgJl7lCd88NnBJTU4N0NzX7Dv-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWwCD0i7J4z3087

05/02/2024



Scale = 1:31.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.30	Vert(LL)	-0.03	7	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.53	Vert(CT)	-0.06	7	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.03	5	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.03	6	>999	240	Weight: 18 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
 BOT CHORD 2x4 SPF No.2 *Except* 7-3:2x3 SPF No.2
 WEBS 2x4 SPF No.2 *Except* 4-5:2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 5= Mechanical, 8=0-4-9

Max Horiz 8=94 (LC 5)
 Max Uplift 5=-55 (LC 8), 8=-110 (LC 4)
 Max Grav 5=246 (LC 1), 8=379 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-8=-345/138, 1-2=0/32, 2-3=-242/33,
 3-4=-76/20, 4-5=-120/34
 BOT CHORD 7-8=-46/167, 6-7=0/81, 3-6=-44/60,
 5-6=-24/70

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 110 lb uplift at joint 8 and 55 lb uplift at joint 5.

- 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 78 lb down and 46 lb up at 3-0-14, and 67 lb down and 43 lb up at 3-6-3 on top chord, and 6 lb down at 3-0-14, and 6 lb down at 3-6-3 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (lb/ft)
 Vert: 1-2=-70, 2-4=-70, 7-8=-20, 5-6=-20
 Concentrated Loads (lb)
 Vert: 11=-1 (F), 12=0 (B)



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
 Chesterfield, MO 63017
 314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J22	Jack-Open	3	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1

ID:GP3oon7aZjBHQoQR3OBb2GzX7My-RfC?PsB70Hq3NSgPqnL8w3ulTXH GKWrCDorf342JC?

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799627
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:25.1

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.35	Vert(LL)	-0.02	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.21	Vert(CT)	-0.05	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.02	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.02	4-5	>999	240	Weight: 13 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-11-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical, 5=0-3-8
Max Horiz 5=90 (LC 8)
Max Uplift 3=-77 (LC 8), 5=-41 (LC 8)
Max Grav 3=151 (LC 1), 4=91 (LC 3), 5=290 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-252/83, 1-2=0/26, 2-3=-79/45
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) The Fabrication Tolerance at joint 5 = 2%, joint 5 = 2%
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 5) All bearings are assumed to be SPF No.2 .
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 41 lb uplift at joint 5 and 77 lb uplift at joint 3.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J23	Jack-Closed Girder	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1
ID:OPHG_ITuw1KovU3LJ96jq_zX7EI-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi734z3G%7

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799628
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:20.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.25	Vert(LL)	-0.03	3-4	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.24	Vert(CT)	-0.06	3-4	>998	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.01	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P							Weight: 30 lb	FT = 10%

LUMBER
TOP CHORD 2x10 SP 2400F 2.0E
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2 *Except* 3-1:2x3 SPF No.2

BRACING
TOP CHORD 2-0-0 oc purlins: 1-2, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 3= Mechanical, 4=0-3-8
Max Horiz 4=-47 (LC 4)
Max Uplift 3=-115 (LC 5), 4=-150 (LC 4)
Max Grav 3=941 (LC 15), 4=1349 (LC 16)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-4=-1303/178, 1-2=-17/13, 2-3=-890/137
BOT CHORD 3-4=-41/36
WEBS 1-3=-24/24

- NOTES**
- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Provide adequate drainage to prevent water ponding.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 5) All bearings are assumed to be SPF No.2 .
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 150 lb uplift at joint 4 and 115 lb uplift at joint 3.
 - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

- 9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) . The design/selection of such connection device(s) is the responsibility of others.
 - 10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 3-4=-20
Concentrated Loads (lb)
Vert: 5=-878 (B), 6=-878 (B)



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J24	Jack-Open	1	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1

ID:nKpQcglps3J0MFN1B1SBzzX7Oq-RfC?PsB70Hq3NSgPqnL8w3ulTXbGLWwCD0173429C7#

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799629
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:26

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 7 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
2-2-6 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc
bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical,
5=0-3-8
Max Horiz 5=50 (LC 8)
Max Uplift 3=-37 (LC 8), 5=-23 (LC 8)
Max Grav 3=54 (LC 1), 4=36 (LC 3), 5=179
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 2-5=-157/44, 1-2=0/32, 2-3=-42/18
BOT CHORD 4-5=-19/13

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 5 considers parallel to grain value
using ANSI/TPI 1 angle to grain formula. Building
designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 23 lb uplift at joint
5 and 37 lb uplift at joint 3.



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J25	Jack-Open	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1
ID:Y8qtslz_wXDmWCfB_x_KiEzX7OR-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDofr4423C#f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799630
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:25.5

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 8 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
2-5-2 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc
bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical,
5=0-3-8
Max Horiz 5=46 (LC 8)
Max Uplift 3=-36 (LC 8), 5=-32 (LC 4)
Max Grav 3=62 (LC 1), 4=40 (LC 3), 5=188
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 2-5=-165/52, 1-2=0/27, 2-3=-39/18
BOT CHORD 4-5=-19/12

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Bearing at joint(s) 5 considers parallel to grain value
using ANSI/TPI 1 angle to grain formula. Building
designer should verify capacity of bearing surface.
- 7) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 32 lb uplift at joint
5 and 36 lb uplift at joint 3.



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J26	Diagonal Hip Girder	1	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1

ID:Ojx_EfujUOFC5eJloqLcemzX7Ly-RfC?PsB70Hq3NSgPqnL8w3uITXbGKW/rCDoi7J4ZJG9

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799631
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:24.7

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.49	Vert(LL)	-0.04	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.30	Vert(CT)	-0.09	4-5	>746	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.02	4-5	>999	240	Weight: 18 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2 *Except* 3-4:2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 4= Mechanical, 5=0-4-9
Max Horiz 5=112 (LC 5)
Max Uplift 4=54 (LC 8), 5=112 (LC 4)
Max Grav 4=247 (LC 1), 5=380 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-5=-335/155, 1-2=0/32, 2-3=-135/13,
3-4=-176/79

BOT CHORD 4-5=-30/51

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 112 lb uplift at joint
5 and 54 lb uplift at joint 4.

- 7) Hanger(s) or other connection device(s) shall be
provided sufficient to support concentrated load(s) 67 lb
down and 43 lb up at 3-6-3 on top chord, and 6 lb down
at 3-6-3 on bottom chord. The design/selection of such
connection device(s) is the responsibility of others.

- 8) In the LOAD CASE(S) section, loads applied to the face
of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15,
Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-3=-70, 4-5=-20
Concentrated Loads (lb)
Vert: 7=0 (F)



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	J27	Diagonal Hip Girder	2	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1
ID: ?iDhflldjVV5vhRnaDge6xzX7Q0-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWCCDoi7J422C4

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799632
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:30.1

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.21	Vert(LL)	-0.02	6	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.24	Vert(CT)	-0.03	7	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.01	5	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.02	6	>999	240	Weight: 14 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 7-3:2x3 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-7-4 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 4= Mechanical, 5= Mechanical, 8=0-4-9
Max Horiz 8=75 (LC 4)
Max Uplift 4=-38 (LC 8), 5=-10 (LC 8), 8=-93 (LC 4)
Max Grav 4=110 (LC 1), 5=70 (LC 1), 8=316 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 2-8=-286/114, 1-2=0/31, 2-3=-171/7, 3-4=-17/30
BOT CHORD 7-8=-40/100, 6-7=0/54, 3-6=-17/51, 5-6=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 93 lb uplift at joint 8, 38 lb uplift at joint 4 and 10 lb uplift at joint 5.

- 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 72 lb down and 20 lb up at 1-6-10, and 62 lb down and 20 lb up at 2-0-15 on top chord, and 2 lb down and 3 lb up at 1-6-10, and 3 lb down and 3 lb up at 2-0-15 on bottom chord. The design/selection of such connection device (s) is the responsibility of others.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 2-4=-70, 7-8=-20, 5-6=-20
Concentrated Loads (lb)
Vert: 11=3 (B), 12=3 (F)



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J28	Jack-Open	4	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1

ID:L7zkarORYbrDwDjCNefrRqzX7QT-RfC?PsB70Hq3NSgPqnL8w3uITXbGhWrCDoi7342067

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799633
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:29.3

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.14	Vert(LL)	-0.01	6	>999	360	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.17	Vert(CT)	-0.02	7	>999	240	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.01	5	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.01	6	>999	240	Weight: 11 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2 *Except* 7-3:2x3 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
3-10-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (size) 4= Mechanical, 5= Mechanical,
8=0-3-8
Max Horiz 8=71 (LC 8)
Max Uplift 4=-43 (LC 8), 5=-5 (LC 8), 8=-36
(LC 8)
Max Grav 4=103 (LC 1), 5=59 (LC 3), 8=243
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 2-8=-223/54, 1-2=0/26, 2-3=-134/0,
3-4=-25/34
BOT CHORD 7-8=-41/81, 6-7=0/36, 3-6=0/52, 5-6=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed ; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 36 lb uplift at joint
8, 43 lb uplift at joint 4 and 5 lb uplift at joint 5.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	J29	Jack-Open	2	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1
ID:ftfwohA8n3ammSLkJsKci1zX7Ql-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKvtrCDoi7J4zJCA

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799634
LEE'S SUMMIT, MISSOURI

05/02/2024

-0-10-8	1-4-0
0-10-8	1-4-0



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.06	Vert(LL)	0.00	4-5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.01	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.00	5	>999	240	Weight: 5 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
1-4-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical,
5=0-3-8
Max Horiz 5=31 (LC 5)
Max Uplift 3=-17 (LC 8), 5=-36 (LC 4)
Max Grav 3=20 (LC 1), 4=22 (LC 3), 5=151
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 2-5=-134/46, 1-2=0/26, 2-3=-25/4
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 36 lb uplift at joint
5 and 17 lb uplift at joint 3.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	RELEASE FOR CONSTRUCTION AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 164799635 LEE'S SUMMIT, MISSOURI
B240069	J30	Jack-Open	2	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1
ID: LavtRD_6Y9Z1r?7gNV2s3fzX7R?-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi734zJG4H

05/02/2024

-0-10-8	1-3-6
0-10-8	1-3-6



Scale = 1:25.3

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	0.00	5	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.01	Vert(CT)	0.00	4-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-R		Wind(LL)	0.00	4-5	>999	240	Weight: 5 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
1-3-6 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (size) 3= Mechanical, 4= Mechanical,
5=0-3-8
Max Horiz 5=34 (LC 5)
Max Uplift 3=-19 (LC 8), 5=-23 (LC 8)
Max Grav 3=16 (LC 1), 4=21 (LC 3), 5=150
(LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 2-5=-134/37, 1-2=0/31, 2-3=-29/4
BOT CHORD 4-5=0/0

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp C; Enclosed; MWFRS (envelope) exterior zone;
cantilever left and right exposed; end vertical left and
right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- 4) All bearings are assumed to be SPF No.2 .
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 23 lb uplift at joint
5 and 19 lb uplift at joint 3.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT
B240069	LAY1	Lay-In Gable	1	1	Job Reference (optional)

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:07 Page: 1
ID: mOrqb3swGTgrwrfidRuw_zSPfT-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwVrCDoi7J4ZJG4H

05/02/2024



Scale = 1:55.7

Plate Offsets (X, Y): [5:0-1-10,Edge], [15:0-1-10,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.10	Horiz(TL)	0.01	19	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S							
Weight: 156 lb FT = 10%											

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 5-15.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size)
1=31-0-8, 19=31-0-8, 20=31-0-8, 21=31-0-8, 22=31-0-8, 23=31-0-8, 24=31-0-8, 25=31-0-8, 26=31-0-8, 28=31-0-8, 29=31-0-8, 30=31-0-8, 31=31-0-8, 32=31-0-8, 33=31-0-8, 34=31-0-8, 35=31-0-8
Max Horiz 1=165 (LC 4)
Max Uplift 1=75 (LC 6), 19=33 (LC 7), 20=91 (LC 9), 21=114 (LC 9), 22=84 (LC 9), 24=40 (LC 5), 25=33 (LC 4), 26=34 (LC 5), 28=34 (LC 5), 29=34 (LC 4), 30=34 (LC 5), 31=46 (LC 4), 32=30 (LC 5), 33=90 (LC 8), 34=112 (LC 8), 35=91 (LC 8)
Max Grav 1=143 (LC 8), 19=115 (LC 9), 20=174 (LC 16), 21=203 (LC 16), 22=189 (LC 16), 23=169 (LC 22), 24=187 (LC 21), 25=180 (LC 22), 26=180 (LC 21), 28=180 (LC 1), 29=180 (LC 22), 30=180 (LC 21), 31=187 (LC 22), 32=173 (LC 18), 33=195 (LC 15), 34=201 (LC 15), 35=174 (LC 15)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-220/148, 2-3=-138/119, 3-4=-118/92, 4-5=-91/132, 5-6=-36/113, 6-7=-36/113, 7-8=-36/113, 8-9=-36/113, 9-10=-36/113, 10-11=-36/113, 11-12=-36/113, 12-13=-36/113, 13-14=-36/113, 14-15=-36/113, 15-16=-78/120, 16-17=-76/48, 17-18=-107/58, 18-19=-179/87
BOT CHORD 1-35=-61/144, 34-35=-61/144, 33-34=-61/144, 32-33=-61/144, 31-32=-61/144, 30-31=-61/144, 29-30=-61/144, 28-29=-61/144, 26-28=-61/144, 25-26=-61/144, 24-25=-61/144, 23-24=-61/144, 22-23=-61/144, 21-22=-61/144, 20-21=-61/144, 19-20=-61/144
WEBS 2-35=-137/110, 3-34=-160/137, 4-33=-156/114, 6-32=-133/54, 7-31=-147/70, 8-30=-140/58, 9-29=-140/58, 10-28=-140/58, 11-26=-140/58, 12-25=-140/57, 13-24=-147/64, 14-23=-129/22, 16-22=-149/108, 17-21=-163/139, 18-20=-136/109

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 0-0-0 oc.

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 75 lb uplift at joint 1, 33 lb uplift at joint 19, 91 lb uplift at joint 35, 112 lb uplift at joint 34, 90 lb uplift at joint 33, 30 lb uplift at joint 32, 46 lb uplift at joint 31, 34 lb uplift at joint 30, 34 lb uplift at joint 29, 34 lb uplift at joint 28, 34 lb uplift at joint 26, 33 lb uplift at joint 25, 40 lb uplift at joint 24, 84 lb uplift at joint 22, 114 lb uplift at joint 21 and 91 lb uplift at joint 20.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard




April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com



LUMBER



BRACING

FORCES (lb) - Maximum Compression/Maximum Tension

NOTES

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCdL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) All bearings are assumed to be SPF No.2 .
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 55 lb uplift at joint 1, 20 lb uplift at joint 9, 107 lb uplift at joint 14, 103 lb uplift at joint 15, 117 lb uplift at joint 16, 106 lb uplift at joint 12, 103 lb uplift at joint 11 and 117 lb uplift at joint 10.

LOAD CASE(S) Standard




MiTek®
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	RELEASE FOR CONSTRUCTION
B240069	LAY3	Lay-In Gable	1	1	Job Reference (optional)	AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 164799638 LEE'S SUMMIT, MISSOURI

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:ounGgtZ5Luhnhs5_TjwBgmX7Sr-RfC?PsB70Hq3NSgPqnL8w3uITxbGWrCDoit34z3C74

05/02/2024



Scale = 1:58

Plate Offsets (X, Y): [6:0-1-10,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.32	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.14	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.14	Horiz(TL)	0.00	15	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S							
Weight: 150 lb FT = 10%											

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x4 SPF No.2
OTHERS	2x4 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 6-14.	
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	
WEBS	1 Row at midpt	14-15, 7-23, 8-21, 9-20, 10-19, 11-18, 12-17, 13-16

REACTIONS (size)	1=23-2-9, 15=23-2-9, 16=23-2-9, 17=23-2-9, 18=23-2-9, 19=23-2-9, 20=23-2-9, 21=23-2-9, 23=23-2-9, 24=23-2-9, 25=23-2-9, 26=23-2-9, 27=23-2-9
------------------	--

Max Horiz	1=340 (LC 5)
Max Uplift	1=116 (LC 6), 15=20 (LC 5), 16=50 (LC 4), 17=45 (LC 5), 18=37 (LC 4), 19=35 (LC 5), 20=35 (LC 5), 21=49 (LC 4), 23=99 (LC 5), 24=89 (LC 8), 25=110 (LC 8), 26=104 (LC 8), 27=104 (LC 8)
Max Grav	1=239 (LC 5), 15=33 (LC 1), 16=149 (LC 22), 17=188 (LC 1), 18=178 (LC 1), 19=184 (LC 22), 20=184 (LC 1), 21=185 (LC 22), 23=181 (LC 1), 24=203 (LC 15), 25=194 (LC 15), 26=197 (LC 15), 27=194 (LC 15)

FORCES	(lb) - Maximum Compression/Maximum Tension
--------	--

TOP CHORD	1-2=-353/229, 2-3=-300/194, 3-4=-244/156, 4-5=-221/146, 5-6=-175/122, 6-7=-121/92, 7-8=-121/92, 8-9=-121/92, 9-10=-121/92, 10-11=-121/92, 11-12=-121/92, 12-13=-121/92, 13-14=-121/92, 14-15=-94/85
BOT CHORD	1-27=-122/92, 26-27=-122/92, 25-26=-122/92, 24-25=-122/92, 23-24=-122/92, 21-23=-122/92, 20-21=-122/92, 19-20=-122/92, 18-19=-122/92, 17-18=-122/92, 16-17=-122/92, 15-16=-122/92
WEBS	2-27=-151/122, 3-26=-158/129, 4-25=-154/134, 5-24=-163/113, 7-23=-141/123, 8-21=-145/73, 9-20=-143/60, 10-19=-143/59, 11-18=-138/58, 12-17=-146/60, 13-16=-114/114

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) Provide adequate drainage to prevent water ponding.
- 5) All plates are 2x4 MT20 unless otherwise indicated.
- 6) Gable requires continuous bottom chord bearing.
- 7) Gable studs spaced at 0-0-0 oc.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 10) All bearings are assumed to be SPF No.2 .

- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 116 lb uplift at joint 1, 20 lb uplift at joint 15, 104 lb uplift at joint 27, 104 lb uplift at joint 26, 110 lb uplift at joint 25, 89 lb uplift at joint 24, 99 lb uplift at joint 23, 49 lb uplift at joint 21, 35 lb uplift at joint 20, 35 lb uplift at joint 19, 37 lb uplift at joint 18, 45 lb uplift at joint 17 and 50 lb uplift at joint 16.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	RELEASE FOR CONSTRUCTION AS NOTED FOR PLAN REVIEW DEVELOPMENT SERVICES 164799639 LEE'S SUMMIT, MISSOURI
B240069	LAY4	Lay-In Gable	1	1	Job Reference (optional)	

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1

ID:hB4efs0wOZUOFi?lihc6pnzX7SF-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKwVrCDoi7J42J6P

05/02/2024



Scale = 1:48.4

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.03	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.21	Horiz(TL)	0.00	9	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S						Weight: 69 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x4 SPF No.2
OTHERS	2x4 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	1=13-7-6, 9=13-7-6, 10=13-7-6, 11=13-7-6, 12=13-7-6, 13=13-7-6, 14=13-7-6, 15=13-7-6
Max Horiz	1=230 (LC 5)
Max Uplift	1=121 (LC 4), 9=19 (LC 8), 10=110 (LC 9), 11=104 (LC 9), 12=100 (LC 7), 13=106 (LC 8), 14=103 (LC 8), 15=117 (LC 8)
Max Grav	1=189 (LC 7), 9=51 (LC 18), 10=181 (LC 16), 11=206 (LC 16), 12=246 (LC 4), 13=212 (LC 15), 14=187 (LC 15), 15=221 (LC 15)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-260/234, 2-3=-223/206, 3-4=-198/202, 4-5=-163/209, 5-6=-136/192, 6-7=-101/104, 7-8=-55/49, 8-9=-53/34
BOT CHORD	1-15=-43/36, 14-15=-43/36, 13-14=-43/36, 12-13=-43/36, 11-12=-43/36, 10-11=-43/36, 9-10=-43/36
WEBS	5-12=-223/140, 4-13=-171/130, 3-14=-149/128, 2-15=-170/137, 6-11=-167/129, 7-10=-134/126

NOTES

- 1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) All bearings are assumed to be SPF No.2 .
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 121 lb uplift at joint 1, 19 lb uplift at joint 9, 100 lb uplift at joint 12, 106 lb uplift at joint 13, 103 lb uplift at joint 14, 117 lb uplift at joint 15, 104 lb uplift at joint 11 and 110 lb uplift at joint 10.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	LAY5	Lay-In Gable	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:y19kqhQhnpWlape99lmmw8fzX7Vb-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7342JG/H

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799640
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:66.4

Plate Offsets (X, Y): [6:0-1-4,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	n/a	-	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.03	Vert(TL)	n/a	-	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.18	Horiz(TL)	-0.01	10	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S						Weight: 92 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 6-10.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

WEBS 1 Row at midpt 5-14

REACTIONS (size) 1=15-10-14, 10=15-10-14, 11=15-10-14, 12=15-10-14, 13=15-10-14, 14=15-10-14, 15=15-10-14, 16=15-10-14, 17=15-10-14, 18=15-10-14
Max Horiz 1=432 (LC 8)
Max Uplift 1=140 (LC 6), 10=94 (LC 8), 11=36 (LC 4), 12=37 (LC 5), 13=38 (LC 4), 14=54 (LC 8), 15=50 (LC 15), 16=188 (LC 8), 17=168 (LC 8), 18=178 (LC 8)
Max Grav 1=410 (LC 8), 10=86 (LC 1), 11=195 (LC 1), 12=178 (LC 1), 13=181 (LC 22), 14=161 (LC 1), 15=116 (LC 8), 16=235 (LC 15), 17=220 (LC 15), 18=232 (LC 15)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=532/237, 2-3=362/164, 3-4=189/94, 4-5=84/29, 5-6=69/63, 6-7=31/73, 7-8=31/73, 8-9=31/73, 9-10=31/73
BOT CHORD 1-18=73/31, 17-18=73/31, 16-17=73/31, 15-16=73/31, 14-15=130/76, 13-14=129/68, 12-13=129/67, 11-12=129/68, 10-11=129/60

WEBS

2-18=184/194, 3-17=182/193, 4-16=195/214, 5-14=118/54, 7-13=140/62, 8-12=139/61, 9-11=149/60

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 0-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 140 lb uplift at joint 1, 94 lb uplift at joint 10, 50 lb uplift at joint 15, 178 lb uplift at joint 18, 168 lb uplift at joint 17, 188 lb uplift at joint 16, 54 lb uplift at joint 14, 38 lb uplift at joint 13, 37 lb uplift at joint 12 and 36 lb uplift at joint 11.
- Non Standard bearing condition. Review required.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	LAY6	Lay-In Gable	1	1		


Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1

ID:Y3d9WXdoTE_1y1jBS228fXzX7U2-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCD0i734z3G7

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799641
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:46.1

Plate Offsets (X, Y): [4:0-1-4,Edge]															
Loading		(psf)	Spacing		2-0-0	CSI		DEFL		in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)		25.0	Plate Grip DOL		1.15	TC		0.08	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL		10.0	Lumber DOL		1.15	BC		0.04	Vert(TL)	n/a	-	n/a	999		
BCLL		0.0*	Rep Stress Incr		YES	WB		0.10	Horiz(TL)	0.00	8	n/a	n/a		
BCDL		10.0	Code		IRC2021/TPI2014	Matrix-S								Weight: 60 lb	FT = 10%

LUMBER	
TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x4 SPF No.2
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 4-8.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS (size)	
	1=12-6-14, 8=12-6-14, 9=12-6-14, 10=12-6-14, 11=12-6-14, 12=12-6-14, 13=12-6-14, 14=12-6-14
Max Horiz	1=255 (LC 8)
Max Uplift	1=-39 (LC 6), 8=-48 (LC 8), 9=-36 (LC 4), 10=-41 (LC 5), 11=-18 (LC 15), 12=-38 (LC 4), 13=-56 (LC 8), 14=-233 (LC 8)
Max Grav	1=201 (LC 8), 8=86 (LC 1), 9=196 (LC 22), 10=172 (LC 1), 11=58 (LC 8), 12=177 (LC 22), 13=144 (LC 1), 14=295 (LC 15)
FORCES (lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-275/137, 2-3=-96/37, 3-4=-69/35, 4-5=-20/38, 5-6=-20/38, 6-7=-20/38, 7-8=-20/38
BOT CHORD	1-14=-38/20, 13-14=-38/20, 12-13=-38/20, 11-12=-38/20, 10-11=-65/45, 9-10=-71/50, 8-9=-71/40
WEBS	7-9=-149/60, 6-10=-139/59, 5-12=-141/60, 3-13=-109/83, 2-14=-234/250

NOTES
1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) Provide adequate drainage to prevent water ponding.
- 5) All plates are 2x4 MT20 unless otherwise indicated.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) All bearings are assumed to be SPF No.2 .
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 39 lb uplift at joint 1, 48 lb uplift at joint 8, 18 lb uplift at joint 11, 36 lb uplift at joint 9, 41 lb uplift at joint 10, 38 lb uplift at joint 12, 56 lb uplift at joint 13 and 233 lb uplift at joint 14.
- 11) Non Standard bearing condition. Review required.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	LAY7	Lay-In Gable	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:aw1XSFitzIIIP5JD7H9P5kzSPgz-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWCDoi7J42uCW

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799642
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:31.9

Plate Offsets (X, Y): [3:Edge,0-3-2], [4:0-0-0,Edge]												
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.04	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	0.00	5	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P							Weight: 21 lb	FT = 10%

LUMBER
TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
OTHERS 2x4 SPF No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 5-9-1 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=5-8-11, 5=5-8-11, 6=5-8-11, 7=5-8-11
Max Horiz 1=94 (LC 7)
Max Uplift 1=-10 (LC 6), 5=-8 (LC 7), 6=-135 (LC 9), 7=-136 (LC 8)
Max Grav 1=108 (LC 17), 5=107 (LC 18), 6=192 (LC 16), 7=193 (LC 15)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-144/80, 2-3=-57/12, 3-4=-57/12, 4-5=-143/79
BOT CHORD 1-7=-52/122, 6-7=-52/122, 5-6=-52/122
WEBS 2-7=-155/159, 4-6=-154/158

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) All bearings are assumed to be SPF No.2 .
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 1, 8 lb uplift at joint 5, 136 lb uplift at joint 7 and 135 lb uplift at joint 6.

LOAD CASE(S) Standard

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) Gable requires continuous bottom chord bearing.
 - 5) Gable studs spaced at 0-0-0 oc.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	R1	Flat Girder	1	2		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:06 Page: 1
ID:abN16ahL?CnnQtSOZcBmr0zX5oo-RfC?PsB70Hq3NsGpqnL8w3ulTXbGKWrcDof4423C#f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799643
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:21.1

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.03	3-4	>999	360	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.20	Vert(CT)	-0.07	3-4	>999	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P							Weight: 61 lb	FT = 10%

LUMBER

TOP CHORD 2x6 SP 2400F 2.0E
BOT CHORD 2x4 SPF No.2
WEBS 2x4 SPF No.2

BRACING

TOP CHORD 2-0-0 oc purlins: 1-2, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size) 3=0-3-8, 4=0-3-8
Max Horiz 4=62 (LC 7)
Max Uplift 3=-310 (LC 5), 4=-380 (LC 4)
Max Grav 3=1830 (LC 1), 4=2217 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-4=-2159/415, 1-2=-23/18, 2-3=-1772/336
BOT CHORD 3-4=-54/49
WEBS 1-3=-32/32

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc, 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 380 lb uplift at joint 4 and 310 lb uplift at joint 3.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1183 lb down and 198 lb up at 0-9-0, and 1169 lb down and 191 lb up at 2-9-0, and 1169 lb down and 185 lb up at 4-9-0 on top chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-70, 3-4=-20
Concentrated Loads (lb)
Vert: 5=-1183, 6=-1169, 7=-1169



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	V1	Valley	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:wQBU4twQr06mPP2dkY48wizX7a6-RfC?PsB70Hq3NSgPqnL8w3ulTXbCKWrCDon7d423C7f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799644
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:27.8

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.19	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.10	Vert(LL)	n/a	-	n/a		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.05	Vert(TL)	n/a	-	999		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P		Horiz(TL)	0.00	4	n/a		
										Weight: 18 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2
OTHERS 2x3 SPF No.2

- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 27 lb uplift at joint 4 and 98 lb uplift at joint 5.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size) 1=7-0-14, 4=7-0-14, 5=7-0-14
Max Horiz 1=115 (LC 7)
Max Uplift 4=-27 (LC 8), 5=-98 (LC 8)
Max Grav 1=61 (LC 16), 4=142 (LC 1), 5=370 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-95/49, 2-3=-90/32, 3-4=-111/46
BOT CHORD 1-5=-37/28, 4-5=-37/28
WEBS 2-5=-288/148

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 4-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) All bearings are assumed to be SPF No.2 .



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	V2	Valley	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:sYnpkkl?NPDu55PKLvJdpYZX7aL-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWwCDoi7J4zJG4H

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799645
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:23.4

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.15	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P							Weight: 11 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-8-11 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=4-8-2, 3=4-8-2

Max Horiz 1=71 (LC 5)
Max Uplift 1=-25 (LC 8), 3=-40 (LC 8)
Max Grav 1=174 (LC 1), 3=174 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-63/42, 2-3=-135/63
BOT CHORD 1-3=-23/17

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 2-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) All bearings are assumed to be SPF No.2.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 25 lb uplift at joint 1 and 40 lb uplift at joint 3.



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Wheeler Lumber, Waverly, KS - 66871.

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 '15 4:05:09 Page: 1
ID:5?InF?f GvC08toCtDAIVszX7aT-RfC?PsB70Hq3NSqPanL8w3ulTXbGKVRCDoi7J42C?

05/02/2024



Scale = 1:17

Plate Offsets (X, Y): [2:Edge,0-1-15]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.03	Vert(LL)	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P							Weight: 5 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
WEBS	2x3 SPF No.2

8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 1 and 15 lb uplift at joint 3.

LOAD CASE(S) Standard

BRACING

TOP CHORD	Structural wood sheathing directly applied or 2-3-14 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	1=2-3-5, 3=2-3-5
Max Horiz	1=27 (LC 7)
Max Uplift	1=-10 (LC 8), 3=-15 (LC 8)
Max Grav	1=66 (LC 1), 3=66 (LC 1)

FORCES

(Ib) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-24/16, 2-3=-51/24
BOT CHORD 1-3=-9/7

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 2'-0" oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06" tall by 2'-00" wide will fit between the bottom chord and any other members.
- 7) All bearings are assumed to be SPF No.2 .



April 11, 2024



Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcscomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	V4	Valley	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:ofN8ncZbvok0oolszFY6iOzX7aa-RfC?PsB70Hq3NSgPqnL8w3uITXbGKvtrCDoi7J4zJCA

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799647
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:25.8

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.19	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.10	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.05	Horiz(TL)	0.00	4	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P						Weight: 18 lb	FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2
OTHERS 2x3 SPF No.2

- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 27 lb uplift at joint 4 and 98 lb uplift at joint 5.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 6'-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10'-0-0 oc bracing.

REACTIONS

(size) 1=7-0-13, 4=7-0-13, 5=7-0-13
Max Horiz 1=114 (LC 5)
Max Uplift 4=-27 (LC 8), 5=-98 (LC 8)
Max Grav 1=61 (LC 16), 4=142 (LC 1), 5=370 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-95/49, 2-3=-90/32, 3-4=-111/46
BOT CHORD 1-5=-37/28, 4-5=-37/28
WEBS 2-5=-287/148

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 4'-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06-00 tall by 2'-00-00 wide will fit between the bottom chord and any other members.
- 7) All bearings are assumed to be SPF No.2 .



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	V5	Valley	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:09 Page: 1
ID:GaP5Q8NZhuJHtKXn1uGM30zX7aq-RfC?PsB70Hq3NSgPqnL8w3uITXb6KWrcD0rJ42dC7r

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799648
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:21

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.29	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.16	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P							Weight: 12 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-9-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=4-8-14, 3=4-8-14
Max Horiz 1=72 (LC 7)
Max Uplift 1=-26 (LC 8), 3=-40 (LC 8)
Max Grav 1=177 (LC 1), 3=177 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-64/43, 2-3=-138/64
BOT CHORD 1-3=-23/18

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 2-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) All bearings are assumed to be SPF No.2.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 26 lb uplift at joint 1 and 40 lb uplift at joint 3.



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	V6	Valley	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:09 Page: 1
ID: V1w3IPHYZRIQw6wEZD6UkKzX7ay-RfC?PsB70Hq3NSgPqnL8w3ulTXb6KWrcD0nJ420C7f

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799649
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:17.1

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.04	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.02	Vert(TL)	n/a	-	n/a	999	197/144
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P							Weight: 5 lb FT = 10%

LUMBER

TOP CHORD 2x4 SPF No.2
BOT CHORD 2x4 SPF No.2
WEBS 2x3 SPF No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-4-11 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=2-4-2, 3=2-4-2

Max Horiz 1=28 (LC 7)
Max Uplift 1=-10 (LC 8), 3=-16 (LC 8)
Max Grav 1=69 (LC 1), 3=69 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-25/17, 2-3=-54/25
BOT CHORD 1-3=-9/7

NOTES

- 1) Wind: ASCE 7-16; Vult=115mph (3-second gust)
Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) Gable requires continuous bottom chord bearing.
- 4) Gable studs spaced at 2-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
- 7) All bearings are assumed to be SPF No.2.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 1 and 16 lb uplift at joint 3.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria, and DSB-22 available from Truss Plate Institute (www.tpinst.org) and BCSI Building Component Safety Information available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	V7	Valley	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:03 Page: 1
ID:JwmvRe8e92w_5Qa7QPQvo?zX7b7-RfC?PsB70Hq3NSgPqnL8w3uITXb3KWrcD6WJ42JC?

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799650
LEE'S SUMMIT, MISSOURI

05/02/2024



Scale = 1:25.9

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.28	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.13	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.05	Horiz(TL)	0.00	3	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P						Weight: 22 lb	FT = 10%

LUMBER

TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x3 SPF No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	1=8-11-13, 3=8-11-13, 4=8-11-13
Max Horiz	1=35 (LC 8)
Max Uplift	1=42 (LC 8), 3=48 (LC 9), 4=4 (LC 8)
Max Grav	1=183 (LC 1), 3=183 (LC 1), 4=336 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD	1-2=-88/49, 2-3=-88/35
BOT CHORD	1-4=-1/39, 3-4=-1/39
WEBS	2-4=-238/63

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SPF No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 42 lb uplift at joint 1, 48 lb uplift at joint 3 and 4 lb uplift at joint 4.

LOAD CASE(S) Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com


Job	Truss	Truss Type	Qty	Ply	Lot 183 HT	Job Reference (optional)
B240069	V8	Valley	1	1		

Wheeler Lumber, Waverly, KS - 66871,

Run: 8.73 S Mar 21 2024 Print: 8.730 S Mar 21 2024 MiTek Industries, Inc. Tue Apr 09 15:45:09 Page: 1
ID: 8_0TQROII?6nfurCoNJMHwzX7c5-RfC?PsB70Hq3NSgPqnL8w3uITXbGHWrcD0i734z3C7

RELEASE FOR CONSTRUCTION
AS NOTED FOR PLAN REVIEW
DEVELOPMENT SERVICES
164799651
LEE'S SUMMIT, MISSOURI

05/02/2024



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.08	n/a	-	n/a	999	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.04	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.02	Horiz(TL)	0.00	3	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P						Weight: 13 lb	FT = 10%

LUMBER	
TOP CHORD	2x4 SPF No.2
BOT CHORD	2x4 SPF No.2
OTHERS	2x3 SPF No.2
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 5-8-13 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS (size) 1=5-7-13, 3=5-7-13, 4=5-7-13	
Max Horiz	1=-20 (LC 9)
Max Uplift	1=-24 (LC 8), 3=-28 (LC 9), 4=-2 (LC 8)
Max Grav	1=105 (LC 1), 3=105 (LC 1), 4=192 (LC 1)
FORCES (lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-51/28, 2-3=-51/20
BOT CHORD	1-4=-1/22, 3-4=-1/22
WEBS	2-4=-136/36

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - All bearings are assumed to be SPF No.2 .
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 24 lb uplift at joint 1, 28 lb uplift at joint 3 and 2 lb uplift at joint 4.
- LOAD CASE(S)** Standard



April 11, 2024

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)


MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Symbols

PLATE LOCATION AND ORIENTATION

Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



This symbol indicates the required direction of slots in connector plates.

* Plate location details available in MITek software or upon request.

PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.

Industry Standards:
ANSI/TP11: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-22: Design Standard for Bracing.
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

Numbering System

6-4-8 dimensions shown in ft-in-sixteenths (Drawings not to scale)



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

Product Code Approvals

ICC-ES Reports:

ESR-1988, ESR-2362, ESR-2685, ESR-3282
ESR-4722, ESL-1388

Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 1 section 6.3. These truss designs rely on lumber values established by others.

© 2023 MITek® All Rights Reserved



MITek Engineering Reference Sheet: MII-7473 rev. 1/2/2023

General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.