

PREMIER

BUILDING SUPPLY OF KANSAS CITY

20300 W 207TH St

Spring Hill, KS 66083

Phone: 913.685.1812

www.premierbuildingsupply.com

Customer

Clayton Properties

Job Name:

Wildflower Farmhouse 3Car

Address:

3229 SW Arbortree Dr HR Lot 116

Salesperson:

Kyle Clifford

Designer:

Michael Dueker

Date:

4/29/2024

Job #:

P240420

Scale:

NTS

ROOF TRUSS PLACEMENT
DIAGRAM

Truss Connector Total List		
Qty	Product	Manuf
10	LUS26	Simpson
2	THJA26	Simpson
Top Height		
8-01-02		
9-01-02		

EVERSTEAD
SHOP DRAWINGS/SUBMITTAL REVIEW

SUBMITTAL WAS REVIEWED FOR DESIGN CONFORMITY
AND GENERAL CONFORMANCE TO CONTRACT
DOCUMENTS ONLY. THE CONTRACTOR IS RESPONSIBLE
FOR CONFIRMING AND CORRELATING DIMENSIONS AT
JOBSITE FOR TOLERANCE, CLEARANCE, QUANTITIES,
FABRICATION, COORDINATION OF HIS OR HER WORK
WITH OTHER TRADES, AND FULL COMPLIANCE WITH
CONTRACT DOCUMENTS.

STATUS:
APPROVED

05/14/2024

REVIEWED BY:
HCJ

ENGINEER, EVERSTEAD ENGINEERING & DESIGN LLC.

◀ - EL EXTREMO IZQUIERDO DE LOS TRUSSES (VEA LOS PERFILES)

TODAS LAS DIMENSIONES PARA LAS TRUSSES SON DE FUERA DE LA MADERA
(u.n.o.)

ESTABLECER LOS TRUSSES NIVELADAS CON LA ESTRUCTURA (u.n.o.)

◀ - LEFT END OF TRUSS (SEE TRUSS PROFILES)

ALL ROOF TRUSS DIMENSIONS ARE FROM OUTSIDE EDGE OF STUD (u.n.o.)

SET ROOF TRUSSES FLUSH WITH FRAMING (u.n.o.)

WARNING: Trusses must be handled with care
to prevent damage and injury.

This truss placement diagram is to be used only as
an installation aid; it is not a structural diagram.
These trusses are designed as individual building
components to be incorporated into the building
design at the the specification of the building
designer. See individual design sheets for each
truss design identified on the placement drawing.

Professional advice should be sought regarding
handling, installation, temporary and permanent
bracing before erecting trusses. Temporary and
permanent bracing is required during installation of
trusses to prevent possible collapse.

For general guidance regarding bracing, consult
"BCSI-06" available jointly from WTCA & TPI.

Premier Building Supply must be notified of any
issues requiring a back charge prior to any work
being done. Premier Building Supply reserves the
right to use it's service staff in lieu of being back
charged.

1 - SDWC 15600 REQUIRED AT ALL BEARING LOCATIONS (u.n.o.)
ALL TRUSS TO TRUSS CONNECTIONS = "NAILED" (u.n.o.)
1 - SDWC 15600 NECESARIO EN TODO LOS PUNTOS DE APOYO (u.n.o.)
TODAS LAS CONEXIONES DE TRUSS A TRUSS = "CLAVADAS " (u.n.o.)