BUTLER

a division of BlueScope Buildings North America, Inc. **Butler Manufacturing**

All primary frames and brace rods are to be class III

galvanized per screening

document.

Existing purlins must be fully supported upon removal of the existing frame until the

new frame is in place.

PERMIT SET- For Building Dept. Approval DESCRIPTION DRAWING RELEASE HISTORY DATE 5/9/24 TYPE Permit Set **PAGES** 11-19 20-25 6-10 4-5 DRAWING INDEX STANDARD ERECTION DETAILS DRAWING TITLE SECONDARY STRUCTURAL PLANOGRAPH DETAILS PRIMARY STRUCTURAL ANCHOR ROD PLAN SPECIAL DRAWINGS CODES AND LOADS COVER SHEET COVERING NOTES

GENERAL NOTES

ASTM DESIGNATION 3 PLATE WELDED SECTIONS
COLD FORMED LIGHT GAGE SHAPES
BRACE RODS
HOT ROLLED MILL SHAPES
HOT ROLLED MILL SHAPES
HOLDWA STRUCTURAL SECTION (HSS)
CLADDING

AB29, A572, A1011, A1018 AB23, A4011 AB72, AB10 A36, AE89, A672, A888, A882 AS99, A572, A888, A882 A500, A792

IT IS THE RESPONSIBILITY OF THE ERECTOR TO ENSURE PROPER BOLL THOMNESS IN ACCORDANCE WITH APPLICABLE RECOLLATORS, SEE EXCOLLATORS SEE RECOLLATORS SEE RECOLLATORS SEE RECOLLATIONS SEE RECOLLATION CONTINUED TO RECEIVE THE THE TOTAL THOM THE RECOLLATION OF THE BOLL THOM THE SEE THE SEE THE SEE THE SECONDAY. THE BOLL THOMNESS (I.E. SHAD THAT OF RECTINED ON THE WAS EVICACLAL MISSIONTION OF CONTINUED. GRADE 56
GRADE 60
GRADE 60
GRADE 30
GRADE 30
GRADE 8
GRADE 8 HIGH STRENGTH BOLT TIGHTENING REQUIREMENTS

ALL A80 BOLTS SHALL BE "PRE-TENSIONED". A228 BOLTS IN PRIMARY FRAMING AND BRACING CONNECTIONS MAY "SNUG-TIGHT" EXCEPT AS FOLLONS;

PRE-TENSION A325 BOLT'S IF BUILDING SUPPORT'S A CRANE GREATER THAN 5 TON CAPACITY

PRE-TENSION AZZ3 BOLT'S IF BUILDING SUPPORTS MACHINERY THAT CREATES VIBRATION, IMPACT, OR STRESS REVERSALS ON CONNECTIONS. PRETENSION A228 BOLTS IF LOCATED IN HIGH SEISMIC AREAS, FOR IBC BASED CODES; HIGH SEISMIC IS DESION CATEGORY D, E OR F. SEE CODES AND LOADS SECTION BELOW FOR DETALS.


PRE-TENSION ANY CONNECTION WITH DESIGNATION A28-5C. SUP CRITICAL (SC) CONNECTIONS MUST BE PREIE PREIE PRYIL, CA COTHER MUTIBALLS THAT REDUCE FRICTION AT CONTACT SURFACES. GALVANZED OR LIGHTL. RUSTID SURFACES AREA COCEPTABLE.

IN CANADA, ALL A228 AND A480 BOLTS SHALL BE "PRE-TENSIONED", EXCEPT FOR SECONDARY MEMBERS AND FLANGE BRACES.

SECONDARY WEMBERS AND FLANGE BRACE CONNECTIONS ARE ALWAYS "SAUG TICHT", UNLESS INDICATED OTHERWSE Erection drawing details.

INSPECTION AND TESTING

STECAL INSECTIONS AND TSTIN RECEIBED BY AUTHORITY WAVING JUSTICATION (ALM DIGHT CONSTRUCTION AND MOST STEEL A FABRICATION IS THE RESPONSIBILITY OF THE OWNERS AUTHORIZED AGENT. WHEN RECOIRED. THE OWNER SHALL BRIEF ON A OALIATT ASSISTANCE AGENC! (CAA, APROPOED BY THE AT. THE BUILDER IS RESPONSIBLE TO COORDINATE BRIEF THE OAL AFRIEF AND A BRIEF AT ABBICATION AFCLITIES. THE TYPE AND ETTEM OF SECIAL INSECTIONS AND ROT WELD. TESTING AND RESPECTIVELY. STIPLALLED BOOK MAST OO BUILDER OF SERVIAL LASSES SECIAL INSECTIONS AND ROT TESTING ARE WAVIED AS PERMITTED BY THE BUILDING OOD BRADE ON BRUNK ACALITIES AND ACCOUNTED.



THE BITTE BIND EXPONENTS SELL ADULES ONLY TO THE WORK PRODUCE OF BITTER INC. A ADD DESIGN AND REPRODUCED ON THE PRODUCE ON SELLO DESIGN OF ANY OTHER PRODUCE ON COMPONENT FINENESTED BY BITTER EXCEPT ON THE PREPORTANCE ON TO ANY DESIGN OF ANY OTHER PRODUCE ON TO ANY DESIGN OF ANY OTHER PRODUCE ON THE PRODUCE ON TO ANY DESIGN OF ANY OTHER PRODUCE ON THE PRODUCE ON TH

Ω THE DIMENT NET THE PROMISED STATE FOR PROCESSION OF THE PROCESSION OF THE DIMENS THE PROCESSION OF THE DIMENS THE PROCESSION OF THE PROCES

IULDER: MAR Building Solutions COVER SHEET BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102

LOCATION: Lees Summit, Missouri
PROJECT: LSMO Water Utilities
BUILDERS POR.

ALAN MICHAEL BY

signed and sealed by Alan Jungnitsch, PE using my Digital Signature with PE seal affixed. Printed copies of this document are not considered signed and sealed, and the signature must be verified on any electronic copy 2024.05.09 14:15:11-05'00'

This document has been electronically

RELEASED FOR
CONSTRUCTION
As Noted on Plans Review

Plans

PERMIT SET. For Building Dept. Approval and the second of CODES AND LOADS LOCATION: Lees Summit, Missouri
PROJECT: LSMO Water Utilities
BUIL DERS POR: BUILDER: MAR Building Solutions customire: BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 NTS Ω THE DIMENT INCLUDED THE PROGRATION THE PROGRATION OF BUILD HAVE AT ITS PRODUCED SOLE. YOU RECEITION THE BUILDING DESCRIBED IN THE APPLICABLE BURNINGS GENERAL OF REPRODUCED ONLY FOR THAT PLAGOSE. IT SHALL HAVE BE MODIFIED, REPRODUCED OR HESED FOR ANY THAT PLAGOSE. IT PRIOR WITHER APPROVED, OR BUILDE HAVE A PROPER SOLE OF ANY OF THAT PLAGOSE WITHOUT FOR ANY OF THAT AND PROPER SOLE OF THE SHALL HAVE A ACCURATE GOOD OLALLY WORKHAMEN HER BEETINGH HIS BUILDING HAS COCREAMED. WITH THIS BEANNIO, DEFLAILS FERTERNEED IN THE DOMAING ALL AD PURCHED HER HIT HIS BEAUTION OLDS. AND HOUSE AND HOUSE PRETAMENT OF DEPARTMENT OF THE HIT IS HITCH HIS CLUDING THE SHALL HAVE BURNING ALL AD PROCREED HER HER THIS HIS OF BEETINGH AND ALL AND AND A PROPER SHEATHING TO PROPER ERECTION. Salamic Doad
Lateral Droce Resisting Systems using Equivalent Force Procedure
Lateral Droce Resisting Systems using Equivalent Force Procedure
Mapped MCB Acceleration, Str. 10.00 My
Mapped MCB Acceleration Extending Systems
Set First Sealing Droce 10: 10.00
Set Similar Droce 10: 10.00
Design Acceleration Parameter: Set 0.120
Design Acceleration Parameter: Set 0.1120
Design Acceleration Parameter: Set 0.1120
Design Acceleration Parameter: Set 0.0120
Design Acceleration Parameter: Set 0.00
Design Condition: Parameter
Fundamental Residu Set Used: 19/3/0 System NOT detailed for Sainanes:
System NOT detailed for Sainan
System NOT detailed for Sainan
Fundamenta Period; Ten 0.2893
Fortcoria 2.50
Overstempth Parcori Images 2.50
Base Shear; 71 0.0427 x W Structural: 16AISC - ASD Rainfall: I: 7.00 inches per hour Cold Form: 16AISI - ASD f'c: 3000.00 psi Concrete n-ractor. 3.00 Deflection Amplification Factor: Cd: 3.00 Basg-Shgar: V: 0.0427 x W Roof Live Load Roof Live Load: 20.00 psf Not Reducible Longitudinal Direction Parameters System NOT detailed for Seismic Sedundancy Factor: Rho: 1.00 Fundamental Pariod: Ta: 0.1838 R-Factor: 3.00 Country: United States Covered Parking Addition Roof: A THE BITTLE IN MEC ENGENEES SEAL, APPLES ONLY TO THE WORK PRODUCT OF BITTLE IN MEC AND DESIGN AND PREPORANCE FROMERINES SECHED BY BITTLES THE BITTLE IN THE BITTLE IN THE PRODUCT OR COMPONENT THRUSHED BY BITTLE IN EXCEPT ON ANY DESIGN OF ANY OTHER PRODUCT OR TOWN OFFICE AND SEAL OF SEAL OFFICE ANY OTHER PRODUCT OR TOWN DESIGN OF ANY DESIGN OF SERVING ANY DESIGN OF ANY D ocdes and loads
BERN MULTIPLE BUILDINGS ARE INVOLVED, SPECIFIC LOAD FACTORS FOR DIFFERING OCCUPANCIES, BUILDING DIRENSIONS,
HEIGHTS, FRANKS OFFERS, NOOF SLOBES, FRY, MAY REQUESTED THAN DIRECTED BELOAT. FRANKS STRAIN BUILDING STORE FROM SPECIFIC STRAIN BUILDING SEW SPECIFIC STRAIN STRAIN STATES. WITH LOADS ARE AFFLIED TO OFFERAL BUILDING ENVELORE.
COMMON TALLS SETWER CONNECTED SHARE NOT SERVET STREAM, WIND LOADS. STREET MISSOURT.
CONTROL STREET STREET CONNECTED SHARE STREET AND STREET STREET. Seow load: pp; 20.00 ppf
Ground Snow Lical; 16.00 ppf
Flat Rook Snow; pr; 14.60 ppf
Beal, Show String, 16.00 ppf
Rain Suchaspe; 0.00 pp; 16.00 ppf
Rain Suchaspe; 0.00 pp; 16.00 ppf
Rain Suchaspe; 0.00 ppf
Rain Species: Unbeated - Ce: 1.00
Thermal Pacces: Unbeated - Ce: 1.00
Charturied or Not Slippery Material Dead Weight Roof Covering + Second, Dead Load: Varies Frame Weight (assumed for seismic):2.50 psf Building Code Building Code: 2018 International Building Code Building Risk/Occupancy Category: II (Standard Occupancy Structure) NOT Windborns Dabris Region
Sea Entaction (70/70 ct
Primary Tool Still Midth: 22:12/0/0
Primary Tool Still Midth: 22:12/0/0
Primary Tool Still Midth: Walls, it 6/0/0
Valority Pressure: qq: 24:46, (ct) 34:46 psf Mind load (Mand Specific 115.00 (Vadd: 89.08) pph The 'Envelope Focedure' is Jused The 'Envelope Focedure' is Jused Fortraites Wind Exposure Fortcoir 0.882 Parts Wind Exposure Factor: 0.882 Parts Wind Exposure Partially Open Topographic Factor: Ket: 1.000 Ground Elevation Factor: Ket: 1.000 Dead and Collateral Loads Collateral Gravity: 10.00 psf Collateral Uplift: 0.00 psf

PERMIT SET. For Building Dept. Approved.

As Notes of the Second of the

BUILDER/CONTRACTOR RESPONSIBILITIES

Butler Mfg, follows the guidelines as outlined in the AISC and MBMA Codes of Standard Practice. Blate Mfg, standard protest specifications, design, final choich, quality circuit a shall govern all work unless stipulated otherwise in the contract documents. In case of discrepancies between Butler Mfg, structural plans and plans for other trackes, Butler Mfg, structural plans shall govern.

It is the responsibility of the Bulder to obtain approvals and permits from all governing agencies and perfections as represented. Approval ablief Mit dinwings constitutes the bulders acceptance of Bulder Mit demonstrated in the sorthern or of Bulder Mit demonstrated or the contract of Bulder Mit demonstrated or the contract of Bulder Mits appearance or one-ming interface design and details are furnished as part of the contract, Bulder Mits, design assumptions as alsill govern.

Balter engines are not Policial Engineses or Engineer of Second for the owner project. Butter engineers are not Policial Engineers or Engineer of Second of or the owner planter and the owneral project for use by others to obtain permits, approvals, and coordinate with other or predes. All interfers and/or orapidality of any materials not furnished by Butter are to be considered and coordinated by the builder or AE firm.

CONSTRUCTION & ERECTION RESPONSIBILITY

The Builder is responsible for construction in strict accordance with Butler Mig. FOR ONSTRUCTION'S drawings and all applicable product installation guides. Butler is not responsible for work done from any other Butler drawings that are not marked "FOR CONSTRUCTION", nor any drawings prepared by others.

As evected field assemblies of members shall be as specified in MBMA Code of Standard Practice (in Chair Cask St) with require Diotentars of the flated members are concluded and and flated work including shimmling, cutting, coping, and drilling for finell thusp are concluded part of evection. Specified ald only a melting condition grounding and includer and included or these drawings shall also be included in the evectors scope of work. See Erection Guide for shimming procedure. For building with top riding bridge cranes see Grane Data drawing for column plumb tolerance.

The building erector shall be properly licensed and experienced in erecting metal building systems. The Building is responsible for having howedge of, and sails compy with. all CSHA requirements and all other governing after safety circles. The builder is responsible for designing, supplying, locating and installing the proposony support and braining unique exciton of the building. Builder benefing is designed for code required loads after building completion and shall not be considered as adequate erection bracing. See Erection Guide.

Shimming of steel buildings during erection may be required to accomodate allowable tolerances churing fabrichacin and erection Speid acres as should be basen by the building erection to shim connections where key dimensions must be maintained for building performance as even small tolerances can have a significant impact on tricking dimensions such as beight, clearances and planness, sespecially as the size of the member of building increases. Conditions where ahimming should be expected an include but are not infinited to large done openings, critical clear height requirements, cames, buildings greater than 45 feet in height, clear spans greater than 125 feet and adjacent frames with dirent characteristics (like clear spans greater than 125 feet and adjacent frames with dirent characteristics (like clear span frames adjacent to an endowall by contacting your Project Manager.

EXISTING STRUCTURES

Blate must be advised of any structure that is within 20 ft. of Buller's building. Load effects from any effects, and selects, and selection must be considered to both the read satisfing structures. Buller has designed the new Buller building for these effects. The ownershall end are responsible for employing a fortesioned linghiner to review and verify the existing structure for all load effects from the adjacent Buller building. **3RACING**

Tension brace rods work in pains to balance forces caused by initial tensioning. Care must be taken while lightening beserve rods as as not causes exclored in or misalizement of components. All rods must be installed loses and then tightened. Rods should not shiblist excessive as ag. For long or heavy rods, or angest it may be necessary to support the rods at mid-bay by suspending then from secondary members.

Bracing for selemic or wind loading of objects or equipment that are not a part of the Buffer structure must be delighted by a qualified professional to deliver lateral loads to primary frames and too because structs. Equipment haveing and suspension connections must not impose torsion or minor as is loads, or exerce local distortion in any Buffer components. Buffer accepts no responsibility for design or installation of bracing systems not furnished by Buffer. FIELD WELDING

All field welling shall be done at the direction of design professional, and done in accordance with governing requirements (AMS) in USA, CWB in Canada) by welders qualified to perform the welding as a directed by the applicable welling procedure aspecification (PMS). A WES shall be prepared by the contractor for each welding variation specified. The contractor is responsed by the contractor for each welding variation specified. The contractor is responsed by the contractor for each welding variation specified. The contractor is responsed by the submitted on any appeal welding inspection as equal to Vical Little Mass I be abused as the submitted of the CMS of the

The Builder is responsible for furnishing signs as required by Code and the Building Department including but not limited to exits, occupancy limits, and build subside ilmits. Floor loading signs shall clearly niclate maximum foor live load permitted.
Build storage facilities a shall have signs clearly posted on all loaded wall ancidant for the pop of commodity stored and the maximum storage height. Signs shall be clearly visible when building is fully loaded to design level. Overloading of floors or walls may result in failure.

DELIVERIES

it is the responsibility of the builder to have adequate equipment available at the job site to united trucks in a safe and interly manner. The Builder will be responsible for all retention charges from carriers as a result of 10°s site uniteding delays.

Claims for damage or shorts MUST be noted on the Bill of-Lading or delivery recepts and the abants that carrier by the consignee as the Butter's Terms of States (F.O.B. Plant) under the Uniform Commercial carrier by the consignee as the Butter's Terms of States (F.O.B. Plant) Bill odd. Enting by you have little recourse with the carrier. In minediately upon the delivery or him the carrier in minediately upon the delivery or minediately and another and entire to prome the supporting commercial another and another another and the shipping document when the shipping document is not the carrier is responsible for the shipping documents upon billied on the shipping document is another another and the shipping document is another another and the shipping documents and the special miningiately upon unpacking. Should product again with the miningian and the unpacked and trainburded inmediately to provide adminished and practical miningian and produce again.

SEALANTS

Sealants shall be applied in strict accordance with Butler details or weather tightness will be compromised. Sealant must be applied in temperatures and weather conditions consistent with labeling.

INDEPENDENT MEZZANINES

Independent nezzanines must be designed by a professional engineer. The engineer must ensure that proper isolation from the Buffer building has been provided to avoid siturctural damage due to differential movements, or indeventently apply loads for Buffer siturcture. Buffer accepts no responsibility for the design of the independent mezzanine.

FIRE CODE COMPLIANCE

It is the responsibility of the project design professional and builder to comply with local fire code regulations including consideration of bur too filmstee by cultifiquing use and occupancy, all building construction materials, separation requirements, agress requirements, fire protection systems, etc. Builder shall advise Butler of any special requirements to be furnished by Butler.

FIELD MODIFICATIONS

Modifications to this building from details and instructions contained on these drawings must be approved in writing by gather fifty, and the statement structural regiment. This includes, not a not instruct or, removed of root and indefinite, entrying or moving any frange insers or out a not instruct or, removed of root and indefinite, entrying or moving any frange insers or that is not a shall not increase or the structure because the limit of increase or each of the structure because their is specified for this building in the contract documents. Builder Mits, accepts no responsibility for the consequences of any unauthorized additions, alterations, or added loads to this structure.

If the builder intends to invoice Batter Mfg. for modifications in excess of \$1000. The builder materially during builder bei builder builder bei buil

CONCRETE/MASONRY/CONVENTIONAL STUD WALLS

The engineer responsible for the design of the wall system is responsible for coordinating with, or specifying to Bullst Might, any will a sele to compatibility, separate and deflection or compatibility, special base details, and wall to Bullst ested connections. All tashens; sealant and counter flashing of wall systems are to be provided by contractor. The engineer responsible for the wall half design the anchorage to Bullst supporting elements consistent with Code trequest forces.

Oil canning is an inherent characteristic of cold formed steel panels. It is the result of several integrates the included streets the included streets with the raw manufaction delivered to include shared particular the includence of the control streets will explain integrate the integrate shared particular the integrate of the integrate shared shared and included the integrate of the integrate

Roof rumble is a phenomenon that is caused by wind gusts lifting up on the roof panels and then springible back into please. All panels experience this such to some degree, especially with conceased city Sann panels. Roof rumble notise may be minimized by providing also, of blanke insulation between the penels and my hard support surface such as steel secondary members, substates such as plywood, steel decking, or rigid board insulation. A minimum of 3 inch thick blanket is recommended over steel secondary members, or 2 inch over substrates.

Oil canning, dimpling, and roof rumble do not affect the structural integrity or weather tightness of the panels and is not grounds for rejection of panels.

The Standing Seam joint detail is designed with an interlocking feature for ease of installation. Housever, it is impreative than installed Standing Seam panies be secured to the secondary structural members and properly seamed prior to departure from the job site each day.

Local building departments may require added fail restraint due to conditions that may affect the skylight structural integrify. It he responsibility of the builder to determine and provide any added fail restaint under the skylight as may be required by your building department. SKYLIGHTS

Disalage system must be designed by the project professional to comply this code requirements belief in not responsible for disalaged elegipm, entrope suppers, down piping, etc. The project professional and contractor are responsible to ensure that primary disms and overflow devices such as exceptors and uniting of dims are provided as encluded for the required rain intensity at the building perimeter and at variety contilions to prevent pointing. RAIN WATER RUNOFF

STEEL SHOP COAT

The purpose of Butler's shop coat is to provide protection for the steel members during transportation, during explanted sheath as the provide promised in the protection, and the parties as the property of the provided sheath as the promised is not designed to perform as a finish coat when exposed to environmental conditions. Members shall be kept free of the ground and property drained during jobs this storage. It is the Butlete's responsibility to ensure that if a finish coat is being applied over Butler sho coat that the painting contractor verifies compatibility between its finish coat and Butler's shop coat.

BUTLER MFG. ACCREDITATIONS AND APPROVALS Fabricator Approvals

M. SA ACTZ Approvalic (www.lasonline.org/sen/cesahreata-building-inspection)
Listed under Eluscope Buildings North America, Inc. City of Los Ampelea, CA #FB00031; City of Housine, IX 187;
City of Los Ampelea, CA #FB00031; City of Housine, IX 187;
City of Prosents, CS 1942009; Cist County, NV 42 & 833, San Bernardino County, CA 289;
State of Unia, City of Richmond, Ca.

Design Approvals

IAS AC472 Approvals: (www.lasonline.org/services/metal-building-inspection)
Listed under Butler Manufacturing, a Division of BlueScope Buildings North America,
Canadian CSA A660 Certifications

(www.cwbgroup.org) Listed under BlueScope Buildings North America, Inc.

Engineering Certifications of Authorization
USA-ALEACASSE, LANGESCE, ARBERTS, ELEGADZI, CAMPETOTTSSI; IDAC-2470; IL#184-002649;
USA-ALEACASSES, LANGESCESCE, ARBERTS, BISSE, BOOKTSSI, NOTE-CORONTTSSI, NOTE-CORONTSSI, NOTE-C

					LENMIN OCI-1 OF DA
 THIS DRAWING, INECLURIONS THE RICHORANTON THEREOR, REMANDS THE PROPERTY OF BUTLER MRG. IT IS PROVIDED SOLELY FOR RECTING THE BUILDING DESCRIBED IN THE PROLABLE PREMASE OFDER AND MAY BE REPRODUCED ONLY FOR THAT PHEPOSE. IT SHALL MAY BE AND THE PREPODUCED ONLY FOR THAT PHEPOSE. IT SHALL MAY BE AND THE PREPODUCED ON INSTITUTION.	Ω		1540 GE	BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102	ERECTION NOTES
PRIOR WRITTEN APPROVAL OF BUTLER MFG.	REV:	DATE:	BY:	DESCRIPTION:	BUILDER: MAR Building Solutions
THE GENERAL CONTRACTOR AND/OR ERECTOR IS SOLELY RESPONSIBLE FOR ACCURATE					CUSTOMER
GOOD QUALITY WORKMANSHIP IN ERECTING THIS BUILDING IN ACCORDANCE WITH THIS DRAWNG DETAILS DEFEDENCED IN THIS DRAWNG ALL ADDITIONER FIRE TO MEDIT	H				LOCATION: Lees Summit, Missouri
ERECTION GUIDES, AND INDUSTRY STANDARDS PERTAINING TO PROPER ERECTION,	_				PROJECT: LSMO Water Utilities
INCLUDING THE CORRECT USE OF TEMPORARY BRACING.	DRAWNIC	DRAWING SCALE:		NTS	BUILDER'S PO#:

THE BITTE HAR GENERATES SEAL, APPLES

WILL YO THE WORK PRODUCT OF BITTER

WICH AND DESIGN AND PREPORANCE

FROUIBEMENTS SPECHED BY BITTER

THE BITTER HAVE DESIGN AND THE PRODUCT OR


CORRISOL OF AND TOTHE PREPORANCE OR

TO ANY DESIGN OF BEFOREMANCE OR

TO ANY DESIGN OF BEFOREMANCE

FROUIBEMENTS SPECHED BY BUTTER EXCEPT.

W3/2024



PERMIT SET- For Building Dept Approval

Rob PLAN - DETAILS

Note and the property of the prope BOTTOM OF COLUMN BASE PLATE 7 STD = 1/2" (13mm) FLUSH = 0" (0mm) TYPICAL COLUMN BASE PLATE DETAIL ANCHOR ROD PLAN - DETAILS FRAMED OPENING DETAIL LOCATION: Lees Summit, Missouri
PROJECT: LSMO Water Utilities
BUIL DERS POR: 11/4 OPENING WIDTH BUILDER: MAR Building Solutions customir. THE 4, PROCESTED MANNEY THE BOTTOW OF THE BASE PLATE IS A SUCCESTED MINNAWI TO ENSINE ACCOUNT. ANALOR TO ENDING ANALOR TO ENGINED BY THE FOUNDATION DESCRIBED BY THE ANALOR ENSINED BY THE ANALOR OR PROFESSION MAY NEED TO BE CLIT OFF IF HEREIS INTERPREPERED. ANY SPACE BETWEEN THE FOUNDATION AND COUNTY SPACE SETWEEN THE FOUNDATION AND COLUMN BASE IN ANCHOR ROD LEAGTH PROQUIPEMENT SUGGESTED ANCHOR ROD PROJECTION BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 NTS Ω THE DIMENT INCLUDED THE PROGRATION THE PROGRATION OF BUILD HAVE AT ITS PRODUCED SOLE. YOU RECEITION THE BUILDING DESCRIBED IN THE APPLICABLE BURNINGS GENERAL OF REPRODUCED ONLY FOR THAT PLAGOSE. IT SHALL HAVE BE MODIFIED, REPRODUCED OR HESED FOR ANY THAT PLAGOSE. IT PRIOR WITHER APPROVED, OR BUILDE HAVE A PROPER SOLE OF A STATE PLAGOSE. WITHOUT PRIOR WITHER APPROVED, A BUILDE HAVE SOLE OF HESE SONE HE PRESONER FOR A ACCURANTE GOOD DALLEY WORKHOWS HER BEETINGH HIS BUILDING HESE ORDINGS. THE HIT HIS BURNING, DEFLAILS FERRENCED IN THE DOMINING ALL APPLICABLE THE HIT IS HIR. INCLUDING THE OUTBOOK THE AND SERTAMING TO PROPER ERECTION. 1 (4)1" Dia. Late W=9", L=1"-im: A=5 1/8"


PERMIT SET. For Building Dept Approval


As Note and Dept Approval


As Note PRIMARY AND ROOF BRACING PLAN BRUDER: MAR Building Solutions
CUSTOMER.
LOCATION: Less Summit, Missouri
PROJECT: LSMO Water Utilities
BRUDERS FOR BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 -(a) NTS (m)— Ω Shape Name Covered Parking Addition, Shape = Covered Parking Shape PRIMARY AND ROOF BRACING PLAN ω<u></u> . 🗇 — **Existing Building** (w)— (Sa) 1. LUES AT STATE TOTAL TOTAL TO ADDRESS AND THE TOTAL TOTAL TO ADDRESS SHALD THE THE DATE TO A FOLLOWING THOUS. WO WHATER BACKE DOWNETTONS. BECOMBATCH TO FORWARDS.

LALLES MOTED OTHERWISE.

S. SLO FREMENCEMENT PLATE SEED NOT BE LOCATED ON THE SAME SIDE OF THE WAS ADDRESS. Bracing Part Schedule Part Qty Length 0488400 2 40'-2" 04884004 2 40'-4" 05RS3305 2 33'-5" Tu-ŢŪ P ε (2)







PERMIT SET. For Building Dept Approval


As Note and the second of the se

PRIMARY BRACING SED'S BOLLOER MAR Building Solutions
CUSTOMER
LOCATOR: Lees Summit, Missouri
PROJECT: LSMO Water Utilities
BOLLOERS FOR BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 NTS Ω 1" THE DOWNWING MICHORY THE PROSENTON THE PROSENTON THE PROSENTON THE PROSENTON THE PROSENTON THE PROSENTON THE BUTTER BUTTER THE PROSENTON TH THE BITTLE IN MEC ENGINEER'S SEAL, APPLES ONLY TO THE WORK PRODUCT OF BITTLE IN MEC AND DESIGN AND PREPORANCE TO THE WIRE AND DESIGN AND THE PRODUCT OR DOMINONERS SEAL DOES NOT APPLY TO THE PERFORMANCE OR DOMINONER TO THE PRODUCT OR TO THE PERFORMANCE OR TO ANY DESIGN OF BAY OTHER PRODUCT OR TO ANY DESIGN OF BAY OTHER PRODUCT OR TO ANY DESIGN OF SERVING AND THE PERFORMANCE TO ANY DESIGN OF SERVING AND THE PRODUCT OR TO ANY DESIGN OF SERVING AND THE PERFORMANCE TO ANY DESIGN OF SERVING ANY DESIGN OF SERVING AND THE PERFORMANCE TO ANY DESIGN OF SERVING AND THE PERFORMANCE TO ANY DESIGN OF SERVING AND THE PERFORMANCE TO ANY DESIGN OF SERVING ANY DESIGN OF

I, LISE 74 Y. TAZZAB EGAL GREAM, AND INT (FITA). WO WANEETS SHALD THEITH BOLTS FOR ALL SECONDARY CONNECTIONS. SECONDARY LOW CONNECTIONS. WO PLANCE BRACE CONNECTIONS. UNLESS NOTED OTHERWISE. S. SOFT REMOVEMENT FALLS BEEN OFF ELCOATED ON THE SAME SIDE OF THE WIBS AS THE HILLIDGE WASHER.

A L STATE OF THE PROPERTY OF THE P | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | OF PRODUCT OF REAL OF PARTY OF THE CON-

HONEDATAL GEARANGE DOCUMEN DOC



PERMIT SET- For Building Dept Approved Secondary Set 1, 192 Selections of the Select

ROOF SECONDARY SED'S	BUILDER: MAR Building Solutions	CUST OMER:	LOCATION: Lees Summit, Missouri	PROJECT: LSMO Water Utilities	BUILDER'S POIC	
BUTLER MANUFACTURING I540 GENESSEE ST. KANSAS CITY, MO 64102	DESCRIPTION:				NTS	12:02:16
1540	BY:					/3/2024 SEDSheet
	DATE:				SAWING SCALE:	5/3/2024 S
THIS DRAWING, MICLIDING THE INFORMATION BREEQUE, REALIZING DESCRIBED IN THE BUTTER MICH. IT IS PROVINCED SOLELY FOR BEECHING THE BULLDING DESCRIBED IN THE BUTTER WITH SHE WITH SHE DRAWING THE BULLDING DOIL Y FOR THIS THE	_		GOOD QUALITY WORKMANSHIP IN ERECTING THIS BUILDING IN ACCORDANCE WITH THIS EXCEPT DEAMAND DETAILS DEFEDENCED IN THIS DEAMAND ALL ADDITORS FRITHED MED	_	TLER. INCLUDING THE CORRECT USE OF TEMPORARY BRACING.	
THE BUTLER MFG. ENGINEER'S SEAL APPLIES ONLY TO THE WORK PRODUCT OF BUTLER MFG. AND DESIGN AND PERFORMANCE	REQUIREMENTS SPECIFIED BY BUILER. THE BUTLER MFG. ENGINEER'S SEAL DOES	NOT APPLY TO THE PERFORMANCE OR	DESIGN OF ANY OTHER PRODUCT OR COMPONENT FURNISHED BY BUTLER EXCEPT	TO ANY DESIGN OR PERFORMANCE	EQUIREMENTS SPECIFIED BY BUTLER.	

SSE WAY SAME SEVER TO SERVE SEVER SE CONTROL CONTROL SHARING A CONTROL CONT (2) 1/4-14 + 1.1/ SIBUCE SORING (20027) (0344013) (1) PURIN BRACE
CHARLES
CHARLES
(4) PURIN BRACE
CHARLES (0) 1/4 × 8 1/4 (000 × 14 (00704) (100 × 100 × 100) CONTROL SERVICE SERVICE SERVICE SERVICE SERVICE SERVICE SERVINTENDE SERVICE SERVICE SERVICE SERVICE SERVICE SERVICE SERVICE SE BAY NUMBER
CANOPY (C)/PARTITION(P)/
ROOF(R)/WALL(W) NUMBER BUILDING SHAPE
THE BAY/BUNDLE CODE IDENTIFIES
THE BUILDING CANOPY/PARTITION/
ROOF/WALL PLANE AND BAY AQMST. CDES BO-FILS NORTHS LENGTH FULD (PRIFMAGEN) SHAPE DEPTH COLMERS Digo Par (00724) (The Pile Eath (50) SNELL CHANKL PURLN SPACE DONE AT NAM WES LIGHTON (OP-)(-10) The state of the s Green Commercia USE WEN CHANCE SPACE DOCS NOT LINE UP WITH THE SLOTS IN THE PARLH WEN DRICCIOL NOTE:
PRE A CAUGHT BALCE DOSS NOT LAFE UP WITH AND HER POSSESS NOT LAFE UP WITH WEST YOUNG TO SHARE THE BALCE OF STANDING WEST AND THE CAUGHT WEST TO WITH WEST AND THE A SELL-SHALLIN (GROOT) TO ATTACH. 24/2 HBH = H 227 HD HBH = H 227 = 2 2448 (-ac) DEE WEN CHAPEL BRACE DOCS LINE LP WEN NEL SACTOR IN THE PRICE MET DO NOT CONTROL OF MANY INC.
MET DOS NOT CONTROL OF MANY INC.
MET DOS NOT THE DOK LOOKE

FOR LOW OR THE DOK LOOKE

BROOKS TO CONTROL OF THE PROPERTY OF THE REPORT OF THE PROPERTY OF PAC PULL


VALUES NOTION, LOUIS TO'ST AT A CASE CASE (1680M) AND MUT (INTER)
WO WASHERS SHUGH THE BOLTS FOR ALL SECONDARY CONNECTIONS.
STANDER BACKES, READINETEDED, FOR PRE STABILITY OF THE
STRUCTURAL, SYSTEM AND MATE BE PROPERLY INSTITUTED PRIOR TO BECTION
WERE AND WELL AND DOES SHEETS.

PERMIT SET. For Building Dept Approved Brown of Second Brown o

ER ER	THE DRAWING, INCLUDION THE INCOMATION HEACON, REMAINS THE PROPERTY OF BUTLER MACE, ITS PROVIDED SOLELY FOR RESCRING THE BUILDING DESCRIBED IN THE BUTLER MACE, ITS PROVIDED SOLELY FOR RESCRIBED IN THE BUTLER FOR THE THE PROVIDED SOLELY FOR THAT PROPERTY REPORTS. THE SHALL WITH PRESCRIPE THE SHALL WITH PROVIDED SOLELY FOR THAT PROPERTY FOR THAT PROPERTY.	Ω		1540 G	BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102	ROOF SECONDARY SED'S
Ę,	PRIOR WRITTEN APPROVAL OF BUTLER MFG.	REV:	DATE:	:	DESCRIPTION:	BUILDER: MAR Building Solutions
	THE GENERAL CONTRACTOR AND/OR ERECTOR IS SOLELY RESPONSIBLE FOR ACCURATE					CUSTOMER:
EPT	GOOD QUALITY WORKMANSHIP IN ERECTING THIS BUILDING IN ACCORDANCE WITH THIS DRAWING DETAILS DEFEDENCED IN THIS DRAWING ALL ADDITIONED BY THE DIMED	L				LOCATION: Lees Summit, Missouri
	ERECTION GUIDES, AND INDUSTRY STANDARDS PERTAINING TO PROPER ERECTION,					PROJECT: LSMO Water Utilities
	INCLUDING THE CORRECT USE OF TEMPORARY BRACING.	DRAWN	RAWING SCALE:		NTS	BUIL DER'S PO#:
			5/3/2024 SEDSheet	100	12:02:18	

LULES NOTED LOGIC 27.1 A LOGAZIO EGO (1980) AND MULTI (PIZZO)
WO WASHESS SIND THEIR BOLTS FOR ALL SECONDARY CONFECTIONS
WO WASHESS SIND THEIR BOLTS FOR ALL SECONDARY CONFECTIONS
STRUCTURAL SYSTEM AND INVESTED FOR PROPERLY INSTALLED PRIOR FOR ESTIMATION FOR EMPLOYING SPEETING.
3. REMOVAL OR ALTERATION OF ANY COMPONENT IS PROHEITED.

STATE OF THE PROPERTY OF THE P	i de la companya de l
	100 000 000 000 000 000 000 000 000 000
The state of the s	See a manufacture of the control of
The second secon	See June 2010
3/2 11 2 3/2	The state of the s



PERMIT SET. For Building Dept. Approval

Vidary ELEVATION AT 1

Vidary ELEVATION AT 1


Vide Selections

Vidary ELEVATION AT 1

Vide Selections

Vidary Elevations

Vi SECONDARY ELEVATION AT 1 BULDER MAR Building Solutions customer.
LOCATION: Less Summit, Missouri PROJECT: LSMO Water Utilities BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 NTS Ω Shape Name - Covered Parking Addition, Wall = 2
THIS DRAWING, INCLUDIOTHE REVARANT PRESENTS TREATED THE PROPERTY OF
BUTLER MEN. IT IS PROVIDED SOLLEY FOR BEETHING THE PROLIFE DESCRIPED IN THE
ALL MOLE BUTLER MEN. OF THE PROLIFE DESCRIPED THE PROLIFE PROVED THE PROCESSOR OF THE PROCESSOR OF THE PROLIFE PROLIFE AND THE BUTLER PROCESSOR OF THE PROLIFE PROLIFE AND THE BUTLER PROLIFE AND THE PROLIFE DESCRIPED THE PROLIFE PROLIFE AND THE PROLIFE PROCESSOR OF THE PROLIFE PROLIFE PROLIFE AND THE PROLIFE PROLIFE PROCESSOR OF THE PROLIFE PROLIFE PROLIFE AND THE PROLIFE (4) SECONDARY ELEVATION AT 1 LULES NOTED LOST AT 17 A CAZE OUT, (1890) AND WITH (1712) WO WASHESS SNUOT IDENTIFY CORP. (1890) AND WONESHESS SNUOT IDENTIFY OF THE STANDED TO THE STANDED -30.-0-



PERMIT SET. For Building Dept. Approval

As Noted Consultation

"Upary ELEVATION AT 4

"Up Saldone

"Up Saldo SECONDARY ELEVATION AT 4 SECONDARY ELEVATION AT 4 BULDER MAR Building Solutions customer.
LOCATION: Less Summit, Missouri PROJECT: LSMO Water Utilities **«**)– BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 *0-.8T NTS Ω Shape Name - Covered Parking Addition, Wall = 4
THIS DRAWING, INCLUDIOTHE REVARANT/PRESENTS TREAMIST FREE PROPERTY OF
BUTLER MEN. IT IS PROVIDED SOLLEY FOR BEETHING THE PROLIFIED OF SOLLEY AND ADDITIONAL DESCRIPTION OF BEETHING DESCRIPTION OF BUTLER AND ADDITIONAL DESCRIPTION OF BUTLER AND ADDITIONAL DESCRIPTION OF BUTLER MAY
THE CHERKLA CONTRACTES AND ONE BEETTING IS SOLLEY RESPONSIBLE FOR ACCIDENTE
THE CHERKLA CONTRACTES AND ONE BEETTING IN SUCCESSION OF BUTLER HIT DEPARKING, DEFINITION OF BUTLER WITH DEPARKING, DEFINITION OF BUTLER WITH DEPARKING, DEFINITION OF BUTLER WITH DEPARKING AND ADDITIONAL DEPARTMENT OF BUTLER HIT DEPARTMENT HIT DEPARTMENT OF BUTLER HIT DEPARTMENT HIT DEPARTMENT OF BUTLER HIT DEPARTMENT OF BUTLER HIT DEPARTMENT HIT DEPARTMENT OF BUTLER HIT DEPARTMENT HIT DEPARTME LULES NOTED, LOLLES TO X 14 OAZER COL, REBON, DANNI III (1720)
WOWSHESS SIMOT THEN REDUTS OR ALL SECONDARY CONNECTIONS.
STANDER BACKLES SAND THENSE, MAN TO THE STANDILIY OF THE
STRUCTURAL SYSTEM AND MATE DE PORCHET, WISTALLED PRIOR TO BECTION
WILL AND DOSS SEREIS.
3. REMOVAL OR ALTERATION OF ANY CORPORATE IS PROHIBITED.

For Building Dept. As Noted on Blans Review

As Noted on Blans Review

As Noted on Blans Review

Border Hard Services Department

Bo

	12:62:23	N3/2024 SEDSheet	5/3/2024		
BUILDER'S POR:	NTS		DRAWING SCALE:	INCLUDING THE CORRECT USE OF TEMPORARY BRACING.	ITS SPECIFIED BY BUTLER.
PROJECT: LSMO Water Utilities				ERECTION GUIDES, AND INDUSTRY STANDARDS PERTAINING TO PROPER ERECTION,	SIGN OR PERFORMANCE
LOCATION: Lees Summit, Missouri				GOOD QUALITY WORKMANSHIP IN ERECTING THIS BUILDING IN ACCORDANCE WITH THIS DRAWING, DETAILS DEFEDENCED IN THIS DRAWING ALL ADDITIONS IF BUTHED MED	ANY OTHER PRODUCT OR RNISHED BY BUTLER EXCEPT
CUSTOMER:				THE GENERAL CONTRACTOR AND/OR ERECTOR IS SOLELY RESPONSIBLE FOR ACCURATE	O THE PERFORMANCE OR
BUILDER: MAR Building Solutions	DESCRIPTION:	94:	DATE:	PRIOR WRITTEN APPROVAL OF BUTLER MFG.	II'S SPECIFIED BY BUILER. IFG. ENGINEER'S SEAL DOES
WALL SECONDARY SED'S (a)	BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102	1540	_	THIS DRAWING, INCLUDION THE INFORMATION HEREBO, REMAINS THE REPORENTY OF BUTLER WAR. OT IT PROVIDED SOLELY FOR RECCHING THE BUILDING DESCRIBED IN THE APPLICABLE PREVIACE OF DELEVER AND MAY BE REPRODUCED ONLY TOR THAT UNIFPOSE IT SHALL IN THE MAINTIFF DEPRODUCED ONLY TOR THAT UNIFPOSE IT SHALL INTO THE MAINTIFF DEPRODUCED ON INSTITUTION OF THE PROPOSE WITHOUT THE MAINTIFF DEPRODUCED ON INSTITUTION OF THE PROPOSE WITHOUT THE MAINTIFF DEPRODUCED ON INSTITUTION OF THE PROPOSE WITHOUT THE MAINTIFF DEPRODUCED ON INSTITUTION OF THE PROPOSE WITHOUT THE MAINTIFF DEPRODUCED ON INSTITUTION OF THE PROPOSE WITHOUT THE MAINTIFF DEPRODUCED ON THE PROPOSE WITHOUT THE PROPOSE WITHOUT THE MAINTIFF DEPRODUCED ON THE PROPOSE WITHOUT THE MAINTIFF DEPRODUCED ON THE PROPOSE WITHOUT THE MAINTIFF DEPROPOSE WITHOUT THE PROPOSE WITHOUT THE MAINTIFF DEPROPOSE WITHOUT THE PROPOSE WITHOUT	S
PERMIT SET- For Bu					

LULES NOTED LUCE 12.1 47.4 AZER 2017 (1680 AZER)
WOWNSHESS SAUGH TOHER BOLTS FOR ALL SECONDAY CONNECTIONS.
WOWNSHESS SAUGH TOHER BOLTS FOR ALL SECONDAY CONNECTIONS.
STRUCTURAL SYSTEM AND INVEST OF HE STRUCTURAL SYSTEM AND INVEST ER FORDERLY INSTALLED PRIORY TO BEECHON
WILL AND FOR SYSTEM.
SERIOVAL OR ALTERATION OF ANY CORPORENT SPONHERED.

EFECTION DRAWING PART MARK P TW I B 3 CANGER (C) PARTING(P) FORCE(R) WALL(W) WANGER THE BAY/GHANE CODE DRIFTINEY ROOF /WILL PANA AND BAYTINEY ROOF /WILL PANA AND BAYTINEY ROOF /WILL PANA AND BAYTINEY	BASIBS SECONDARY BLADE LOCATION KEY	
200 200 200 200 200 200 200 200 200 200	ENDING SPECIAL SECONDARY PART MARK KEY CONNENS ENDINGS CONNENS CONNE	
744 50 50 50 50 50 50 50 50 50 50 50 50 50	DISTRICT MARCH NUMBER CONTRACT BARROW WAR NAMEDS	NO 200 100 100 100 100 100 100 100 100 100
COME DESIGNATION OF THE PROPERTY OF THE PROPER	BROGS NITH BRACE RODS HILD NOW, BACC RODS	
The state of the s	## 17 1/2" HELVE RECORD 2 DOCTS AT DECIDIO OF PARTY DAY. ## TYPICAL FLANCE BROLE CONNECTIONS ## SEPCE DOWN, PARTY DAY SHOWS, CONT. OF A SEPCE PLANCE.	TO THE STATE OF TH


PERMIT SET. For Building Dept. As Noted on Blanc Reny Secondary Sed on Blanc Reny Secondary Sed on Blanc Reny Secondary Sed on Blanc Reny Sed on Blanc Reny

WALL SECONDARY SED'S	BUILDER: MAR Building Solutions	CUSTOMER:	LOCATION: Lees Summit, Missouri	PROJECT: LSMO Water Utilities	BUILDER'S PO#:
BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102	DESCRIPTION:				STN
1540	BY:				
	DATE:				AWING SCALE:
Ω	REV:				DRAWN
TY OF D IN THE JRPOSE IT		CURATE	THINE	i N	
THIS DRAWING, INCLUDING THE INCOGRATION HERGAN REMAINS THE REPORTETY OF BILLER MFG. IT IS PROVINGE SOLELY FOR ERECTING THE BULLINKS DESCRIBED IN THE APPLICABLE PURCHASE ORDER AND WAY BE REPRODUCED ONLY FOR THAT PURPOSE IT.	PRIOR WRITTEN APPROVAL OF BUTLER MFG.	THE GENERAL CONTRACTOR AND/OR ERECTOR IS SOLELY RESPONSIBLE FOR ACCURATE	GOOD QUALITY WORKMANSHIP IN ERECTING THIS BUILDING IN ACCORDANCE WITH THIS DEAMING BY A DEFERENCED IN THIS DEAMING BY LABBI ICABLE BY THE DEFENDANCE.	ERECTION GUIDES, AND INDUSTRY STANDARDS PERTAINING TO PROPER ERECTION,	INCLUDING THE CORRECT USE OF TEMPORARY BRACING.

SE S			
### ##################################			
T T T T T T T T T T T T T T T T T T T			
The state of the s	Section 2		
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	The state of the s		

GIRT CONN. AT COLLIAN

LULES NOTED LOGIC 27.1 14 CAZET GENERAL PROFILE CONTROL (PERSONAL PROFILE CONTROL PROFILE CONTROL PROFILE CONTROL PROFILE CONTROL CONTROL PROFILE CONTROL CONT



PERMIT SET. For Building Dept Approved a solutions of the state of the COVERING ELEVATION AT A Q BULDER MAR Building Solutions customer.
LOCATION: Less Summit, Missouri PROJECT: LSMO Water Utilities
BULDERS FOR BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 NTS Ω Shape Name - Covered Parking Addition, Wall = 1
THIS DRAWING, INCLUDIOTHE REVARANT/PRESENTS TREAMIST FREE PROPERTY OF
BUTLER MEN. IT IS PROVIDED SOLLEY FOR BEETHING THE PROLIFIED OF SOLLEY
AND ADDITIONAL PROPERTY OF BUTLER THOUSE DAY OF THE PROPERTY OF BUTLER MAY
PROVINCE ADDITIONAL OF BUTLER MAY
THE CHERKLA CONTRACTES AND ONE BEETON IS SOLLEY RESPONSIBLE FOR ACCIDENTE
THE CHERKLA CONTRACTES AND ONE BEETON IS SOLLEY RESPONSIBLE FOR ACCIDENT
TO CONDULATION OF SOME DESCRIPTION IN INCOMPANY OF THIS DRAWING, DEFINISHED THE SHEET OF THE BUTLES HIT OF
BUTLES AND ADDITIONAL SHEET OF THE SHEET OF THE BUTLES HIT OF
INCLUDION THE CONTRACTES AND ADDITIONAL SHEET OF THE S COVERING ELEVATION AT A 1. THE PORT UNIT OF HOMETER HOLES FOR STRUCTURA, EXTENSES
HAY RECOURSE TO ALL HOLES FOR STRUCTURA, EXTENSES
TO STRUCTURA LEAMES FOR HE STRUCTURA, SYSTEM
EBROWLE, OR ALT TRATION WINDOWN THROUGH THE STRUCTURA, SYSTEM
EBROWLE OF SECTION TROOK MATCHAGATION IS PROJURE
THE DUTTURA SEE THE COMPANIES AMY REQUIRE
THE DUTTURA SEE THE COMPANIES ASSET FOR THE SAFE THE STRUCTURA

5. BET OUT THE SEE THE COMPANIES AND THE STRUCTURAL

5. BET OUT THE SET FOR COMPANIES AND THE STRUCTURAL

5. BET OUT THE SET FOR COMPANIES AND THE STRUCTURAL


5. BET OUT THE STRUCTURAL OF THE STRUCTURAL THE (-)

PERMIT SET. For Building Dept Approved Particular Selections

PERMIT SET. For Building Dept Approved Particular Selections

Proposed Particular Selections

Pr Planograph Schedule Id Details II P-080575, P-080789, P-080949, P-081239 **COVERING ELEVATION AT 1** A BOLLOER MAR Building Solutions
CUSTOMER.
LOGATORE LASS Summit, Missouri
PROJECT LSMO Water Utilities
BULDERS FOR BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 Details ENBOO4, NV667, RCB269 NTS Color Special Color 3 Ω Shape Name - Covered Parking Addition, Wall = 2
THIS DRAWING, INCLUDING THE INVESTMENT TREATMENT REPORTED TO FE
ALL SHAPE OF THE PROVIDED SOLEN'T FOR BECTHING THE BUILDING DESCRIBED THE
FALL NOTE BECHNING DESCRIBED. THE BUILDING DESCRIBED THE THE FALL SOLE BECHNING THE SOLEN'S THE ANALONE THE PROVIDED T COVERING ELEVATION AT 1 Trim Schedule Id Parts Tl (5.1)0630273,(6.4)ST10D,(2)0630393 THE BITTE HAVE GROWNERS SEAL, ADVIESS ON ONLY TO THE WORK MORDALL OF BUTTER HAVE A ADD DESIGN AND PREPORANCE OF THE BITTER HAVE THE BUTTER HAVE A BUTTER HAV 1. HOR COULD WISH ON HOMETS HOUSE ON STRUCTURAL ASTERNESS HAVE RECOVERED FOR HEAVY OACE INSTITUTES HANGER FASTERNEY TO STRUCTURAL SEAMS FOR HEAT STRUCTURAL STRUCTURA STRUCTURA STRUCTURA STRUCTURAL S



PERMIT SET. For Building Dept Approved Programment Pro Planograph Schedule Id Details II P-103223,P-103315,P-104714 IZ P-105224,P-105228 **COVERING ELEVATION AT 4** BOLLOER MAR Building Solutions
custowite
LOCATION: Lees Summit, Missouri
PROJECT: LSMO Water Utilities
BOLLOERS POR BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 Details EN60B1, EN60C1, EN60D1, RCB050 RCB987 NTS Color Special Color 3 Special Color 3 Ω NEGOTION WALLEY STATES THE TOTAL OF THE TOTA COVERING ELEVATION AT 4 Trim Schedule Id Parts TI (3)GFR25 T2 0008738,(2)4CE45,4CE75,(2)CP410 THE BITTE HAVE GROWNERS SEAL, ADVIESS ON ONLY TO THE WORK MORDALL OF BUTTER HAVE A ADD DESIGN AND PREPORANCE OF THE BITTER HAVE THE BUTTER HAVE A BUTTER HAV 1. HOR COULD WISH ON HOMETS HOUSE ON STRUCTURAL ASTERNESS HAVE RECURSED TOOL HEAVY OACE INSTITUTES HANGER ACTIVENESS TO STRUCTURAL ASTERNESS ASTERNESS. (K)

PERMIT SET. For Building Dept. Approximate Control of the Control

COVERING & TRIM SED'S

BULDER MAR Building Solutions customer.
LOCATION: Lees Summit, Missouri PROJECT: LSMO Water Utilities BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 NTS Ω THIS DRAWING, INCLIDING THE INFORMATION HEREON, REMAINS THE PROPERTY OF BELLIE MAY IT IS REVOIDED SOLD THE BULLIAND EXCEPTION THE APPLICABLE HIGHARS CORRERAND MAY BE REPRODUCED ON THE BULL HAND FROM SHALL BY THE MAY POWED. THE PROPOSE WITHOUT PRODY WITHTEN APPROVAL OF BUTTER MAY.

PRODY MINTEN APPROVAL, OF BUTTER MAY.

COOD OUTLY TWO REMAINS HERE THE COURT RESPONSABLE THE PROPOSED FROM SHALL THE WEST COOD OUTLY TWO REMAINS HERE THIS THE BULLIAND MAY CORPARE BUTTER WITH RESPONSABLE AND MUSTER OF STANDING MAY CORPARE BUTTER WITH RESPONSABLE AND MUSTER OF STANDING THE CORPARE BUTTER WITH MICHAEL BUTTER WITH MICHAEL BUTTER WITH THE CORPERCY OF THE SHALL BUTTER WITH MICHAEL BUTTER WITH THE CORPERCY TO SEE OF TELEMONANCE WITH THIS PROPERCY.

1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	NV667 NR-24 STANDING SEAM ROOF PANEL	
to you also do con our control of the control of th	ENBOOM MR-24 ROOF SYSTEM	THE REAL PROPERTY OF THE PROPE
AND THE REAL PROPERTY OF A PARTY	ENAC HEIGHT BEE OF MA-24 N/O INCRMAL RECES	The state of the s
THE PART OF THE PA	ENGCT ENC HOOF UR-24 WITH THERMAL BLOCKS IT 1/2 NOT PURISE	The state of the s
The state of the s	ENECET ENECET ENE HT. WITH WR-24 WITH THERMAL BLOCK IN ENECET EN	The state of the s

BUTLER

COVI CODI NOTE NOTE SEC COVI STAN a division of BlueScope Buildings North America, Inc. **Butler Manufacturing**

DRAWING INDEX		DRAWIN	DRAWING RELEASE HISTORY	HISTORY
DRAWING TITLE	PAGES	TYPE	DATE	DESCRIPTION
OVER SHEET	1	Permit Set	5/1/24	PERMIT SET- For Building Dept. Approve
DES AND LOADS	2			
DTES	9			
CHOR ROD PLAN	4			
UMARY STRUCTURAL	5-10			
CONDARY STRUCTURAL	11-18			
VERING	19-26			
ECIAL DRAWINGS				
ANDARD ERECTION DETAILS				
ANOGRAPH DETAILS				

GENERAL NOTES

ASTM DESIGNATION 3 PLATE WELDED SECTIONS
COLD FORMED LIGHT GAGE SHAPES
BRACE RODS
HOT ROLLED MILL SHAPES
HOT ROLLED MILL SHAPES
HOLDWA STRUCTURAL SECTION (HSS)
CLADDING

A829, A872, A1011, A1018 A823, A1010 A72, A810 A39, A829, A872, A889, A892 A800 A653, A772, A888, A892 A653, A792

IT IS THE RESPONSIBILITY OF THE ERECTOR TO ENSURE PROPER BOLT TROHNESS IN ACCORDANCE WITH APPLICABLE REQUIRED WITH APPLICABLE REQUIRED WITH APPLICABLE SECURITYSES, SEE RECULTANS, SEE RECULTANS SEE RECOVER THE APPLICABLE SEE RECULTANS GUIDE FOR SOLF THE APPLICABLE AND SEE RECOVER MAY BE USED TO DEFERRING THE BOLT THOMITIES (I.E. SHILD THAT OF RECTIPACION (INLESS REQUIRED OTHERWISE BY LOCAL AURSONCTION OR OWNTHACT.) HIGH STRENGTH BOLT TIGHTENING REQUIREMENTS

ALL A89 BOLTS SHALL BE "PRE-TENSIONED". A228 BOLTS IN PRIMARY FRAMING AND BRACING CONNECTIONS MAY I "SNUG-TIGHT" EXCEPT AS FOLLOWS;

PRE-TENSION A325 BOLT'S IF BUILDING SUPPORT'S A CRANE GREATER THAN 5 TON CAPACITY

PRETENSION AZZI BOLTS IF BUILDING SUPPORTS MACHINERY THAT CREATES VIBRATION, IMPACT, OR STRESS REVERSALS ON CONNECTIONS.

PRETENSION A228 BOLTS IF LOCATED IN HIGH SEISMIC AREAS, FOR IBC BASED CODES; HIGH SEISMIC IS DESION CATEGORY D, E OR F. SEE CODES AND LOADS SECTION BELOW FOR DETALS.

PRE-TENSION ANY CONNECTION WITH DESIGNATION A28-5C. SUP CRITICAL (SC) CONNECTIONS MUST BE PREIE PREIE PRYIL, CA COTHER MUTIBALLS THAT REDUCE FRICTION AT CONTACT SURFACES. GALVANZED OR LIGHTL. RUSTID SURFACES AREA COCEPTAELE.

IN CANADA, ALL A228 AND A480 BOLTS SHALL BE "PRE-TENSIONED", EXCEPT FOR SECONDARY MEMBERS AND FLANGE BRACES.

SECONDARY MEMBERS AND FLANCE BRACE CONNECTIONS ARE ALWAYS "SAUG TKRIT", UNLESS INDICATED OTHERMISE ERECTION DRAWIND DETAILS.

INSPECTION AND TESTING

SEECLAL INSECTIONS AND TESTING REQUIRED BY AUTHORITY WINNOL BUSINGTON (MAY) DEMONSTANCE AND WAS TEST A ADMINISTRATION IS THE RESPONSABLE OF THE COMPANIES BY THE COMPANIES WILL USE TO COMPANIE SHALL USE TO COMPANIE THE COMPANIES WILL USE TO COMPANIE THE COMPANIES WILL USE SECRETAL BUSINGS AND WITH THE COMPANIES WILL USE SECRETAL WILL SECRETAL WILL USE THIS ARE WANTED AS PERMITTED THE SECRETAL WAS THE WAS THE SECRETAL WILL WE SECRETAL WHITE STANDINGS WAS THE SECRETAL WAS THE WAS THE WAS THE SECRETAL WAS THE WAS THE SECRETAL WAS THE SECRETA

signed and sealed by Alan Jungnitsch, PE using my Digital Signature with PE seal affixed. Printed copies of this and sealed, and the signature must be This document has been electronically document are not considered signed

verified on any electronic copy 2024.05.01 16:09:47-05'00'

BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 Ω

IULDER: MAR Building Solutions

LOCATION: Lees Summit, Missouri
PROJECT: LSMO Water Utilities
BULL DER'S POR:

COVER SHEET

RELEASED FOR

CONSTRUCTION
As Note on Plans Review

Development Services Department
Lee's Services Missouri
(800 July 2024

1" THE DOWNWAR MELLURON'T REVENDANCH MERCAN RESURVEY REPRESENT OF PRESENT OF BUTTER BROKEN TO BE A BUTTER BUTTER BROKEN TO BE A BUTTER BUTTER

THE BITTLE HAR GENERALES SEAL APPLIES
ONLYTO THE WORK PRODUCT OF BUTTLE
HARG AND DESIGN AND PREPERVANCE
HE AND DESIGN AND PREPERVANCE
HE AND THE HARE BRODUCT OR
COMMONIES THE PRODUCT OR
TO AND TO THE PREPORT OR
TO AND T

PERMIT SET. For Building Dept. Approved to the property of the CODES AND LOADS LOCATION: Lees Summit, Missouri
PROJECT: LSMO Water Utilities
BUIL DERS POR: BUILDER: MAR Building Solutions customire: BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 NTS Ω THE DOWNER, MELLURGH THE PROSENTON THE PROSENTON FER PROSENTON OF BUTTER PROSENTON OF THE PROSENTON OF THE PROPERTON OF THE BUTTER BING IT IS PROVIDED SOLELY FOR PRECIDENT OF THE BULLING DESCRIBED IN THE PREPARED SOLED OF THE PROPERTON OF THE PROSENT OF THE PROSENT OF THE PROPERTON OF THE PROSENT OF THE P Setunic load
Later More Restaing Systems using Equivalent Force Procedure
Later More Restaining Systems using Equivalent Force Procedure
Mapped MCD Acceleration Str. 12 (0) My
Mapped MCD Acceleration Str. 12 (0) My
State Class Str. 15 (1) LO10
Design Acceleration Procedure: Sats 0.1120
Design Acceleration Procedure: Sats 0.1120
Design Cacceleration Stranger 15 (1) LO10
Design Condition: Parkhipe
Fundamental Period Height Used: 18/1/12 inogludinal Direction Parameters

Application of the Control of th System NOT detailed for Sainanes:
System NOT detailed for Sainan
System NOT detailed for Sainan
Fundamenta Period; To 0.246
Fundamenta Period; To 0.246
Overstempth Parcoc; Imagas 2.30
Bass Shear; 77 0.0100 x W. Structural: 16AISC - ASD Rainfall: I: 0.10 inches per hour Cold Form: 16AISI - ASD f'c: 3000.00 psi Concrete Roof Live Load Roof Live Load: 20.00 psf Not Reducible Country: United States Alternate 3 ADDITION Roof: A THE BITTE HAVE GROWNERS SEAL, ADVIESS ON ONLY TO THE WORK MORDALL OF BUTTER HAVE A ADD DESIGN AND PREPORANCE OF THE BITTER HAVE THE BUTTER HAVE A BUTTER HAV ocdes and loads
BERN MULTIPLE BUILDINGS ARE INVOLVED, SPECIFIC LOAD FACTORS FOR DIFFERING OCCUPANCIES, BUILDING DIRENSIONS,
HEIGHTS, FRANKS OFFERS, NOOF SLOBES, FRICE, MAY REQUESTED THAN DIRECTORING FOR THAN BUILDING STREAM SPECIFIC STAND IN STREAM SPECIFIC STAND STREAM SPECIFIC STAND ST Seow load: pp; 20.00 ppf
Ground Snow Lical; le 0.0 ppf
Flat Rook Snow; pr; le 1.6 0 ppf
Design Snow (Sloped): pp: 16.80 ppf
Rain Sucharges: 0.00 pp; (Sough)
Specified Minimum Roof Snow; 20.00 ppf (Gode)
Snow Importance: pr; 11.0012 Sayosed - Ce: 1.00
Thermal Pactor: Unhaward - Ce: 1.20
Ground, Floor Conversion: 0.70
Obstructed or Not Slippery. V Material Dead Weight Roof Covering + Second, Dead Load: 2.46 psf Frame Weight (assumed for seismic):2.50 psf Building Code Building Code: 2018 International Building Code Building Risk/Occupancy Category: II (Standard Occupancy Structure) NOT MINIOROUN DEBLIS Region
Date Missello 2000 of ft
Prisary Good Stip Width: 22: 6/0/0
Prisary Good Stip Width: 22: 6/0/0
Prisary Good Stip Width: 22: 6/0/0
Prisary Fortloan Zone Stip Width:
Walls, at 3/0/0
Voorfel, v. 6/1/0/1/0
Valouty Fessure: qq: 23:30, (qc) 25:30 pxf Wind load
Mind Speed volt: 115.00 (Vasd: 89.08) mph
The 'Investor Eroeduse' 10 Used
Than 150 Will Exposure (- K.E. 10.89)
Parts Wind Exposure (- K.E. 10.89)
Parts Wind Exposure (- K.E. 10.89)
Parts Wind Exposure (- K.E. 10.89)
Shalding Matto: 20.09
Shalding Factor RE. 1.950
Shalding Factor RE. 0.7420
Ground Exposure Reserved RE. 1.0000
Ground Exposure Reserved RE. 1.0000 Dead and Collateral Loads Collateral Gravity: 10.00 psf Collateral Uplift: 0.00 psf

PERMIT SET. For Building Dept. Approved a solutions of the solutions of th

BUILDER/CONTRACTOR RESPONSIBILITIES

Budier Mfg. follows the guidelines as outlined in the AISC and MBMA Codes of Standard Practice. Blater Mfg. standard protest sperifications, design, faint-faint, quality carriers as hall govern all work unless situated otherwise in the contract documents. In case of discrepancies between Budier Mfg. structural plans and plans for other trades, Budier Mfg. structural plans shall govern.

It is the responsibility of the Builder to obtain approvals and permits from all governing agencies and Little defections as represented to the builders acceptance and Little builders acceptance and Caller interpretation of the contract purchase order of their interpretation of the contract purchase order with the contract, Builder Mig. design assumptions interface design and details are furnished as part of the contract, Builder Mig. design assumptions shall govern.

Balter engines are not Policial Engineses or Engineer of Second for the owner project. Butter engineers are not Policial Engineers or Engineer of Second of or the owner planter and the owneral project for use by others to obtain permits, approvals, and coordinate with other or predes. All interfers and/or orapidality of any materials not furnished by Butter are to be considered and coordinated by the builder or AE firm.

CONSTRUCTION & ERECTION RESPONSIBILITY

The Builder is responsible for construction in strict accordance with Butler Mig. FOR ONSTRUCTION'S drawings and all applicable product installation guides. Butler is not responsible for work done from any other Butler drawings that are not marked "FOR CONSTRUCTION", nor any drawings prepared by others.

As evected field assemblies of members shall be as specified in MBMA Code of Standard Practice (in Canada CAS 15) with require Dioterance of included members. Occasional field work including shimming, cutting, coping, and drilling for final fittup are considered part of erection. Specified field work and field widing conditions included to the act of the part of the action of the part of the action of the part of the part

The building erector shall be properly licensed and experienced in erecting metal building systems. The Building is responsible for having howedge of, and sails compy with. all CSHA requirements and all other governing after safety circles. The builder is responsible for designing, supplying, locating and installing the proposony support and braining unique exciton of the building. Builder benefing is designed for code required loads after building completion and shall not be considered as adequate erection bracing. See Erection Guide.

Shimming of steel buildings during erection may be required to accomodate allowable tolerances churing fabrichacin and erection Speid acres as should be basen by the building erection to shim connections where key dimensions must be maintained for building performance as even small tolerances can have a significant impact on tricking dimensions such as beight, clearances and planness, sespecially as the size of the member of building increases. Conditions where ahimming should be expected an include but are not infinited to large done openings, critical clear height requirements, cames, buildings greater than 45 feet in height, clear spans greater than 125 feet and adjacent frames with dirent characteristics (like clear spans greater than 125 feet and adjacent frames with dirent characteristics (like clear span frames adjacent to an endowall by contacting your Project Manager.

EXISTING STRUCTURES

Blate must be advised of any structure that is within 20 ft. of Buller's building. Load effects from any effects, and selects, and selection must be considered to both the read satisfing structures. Buller has designed the new Buller building for these effects. The ownershall end are responsible for employing a fortesioned linghiner to review and verify the existing structure for all load effects from the adjacent Buller building. **3RACING**

Tension brace rods work in pains to balance forces caused by initial tensioning. Care must be taken while lightening beserve rods as as not causes exclored in or misalizement of components. All rods must be installed loses and then tightened. Rods should not shiblist excessive as ag. For long or heavy rods, or angest it may be necessary to support the rods at mid-bay by suspending then from secondary members.

Bracing for selemic or wind loading of objects or equipment that are not a part of the Buffer structure must be delighted by a qualified professional to deliver lateral loads to primary frames and too because structs. Equipment haveing and suspension connections must not impose torsion or minor as is loads, or exerce local distortion in any Buffer components. Buffer accepts no responsibility for design or installation of bracing systems not furnished by Buffer.

FIELD WELDING

All field welling shall be done at the direction of design professional, and done in accordance with governing requirements (AMS) in USA, CWB in Canada) by welders qualified to perform the welding as a directed by the applicable welling procedure aspecification (PMS). A WES shall be prepared by the contractor for each welding variation specified. The contractor is responsed by the contractor for each welding variation specified. The contractor is responsed by the contractor for each welding variation specified. The contractor is responsed by the submitted on any appeal welding inspection as equal to Vical Little Mass I be abused as the submitted of the CMS of the

The Builder is responsible for furnishing signs as required by Code and the Building Department including but not limited to exits, occupancy limits, and build subside ilmits. Floor loading signs shall clearly niclate maximum foor live load permitted.
Build storage facilities a shall have signs clearly posted on all loaded wall ancidant for the pop of commodity stored and the maximum storage height. Signs shall be clearly visible when building is fully loaded to design level. Overloading of floors or walls may result in failure.

DELIVERIES

It is the responsibility of the builder to have adequate equipment available at the job site to unioad trucks in a safe and thrungh manner. The Builder will be responsible for all retention harpers from carriers as a result of Job site unloading delays.

Claims for damage or shorts MUST be noted on the Bill of-Lading or delivery recepts and the abants that carrier by the consignee as the Butter's Terms of States (F.O.B. Plant) under the Uniform Commercial carrier by the consignee as the Butter's Terms of States (F.O.B. Plant) Bill odd. Enting by you have little recourse with the carrier. In minediately upon the delivery or him the carrier in minediately upon the delivery or minediately and another and entire to prome the supporting commercial another and another another and the shipping document when the shipping document is not the carrier is responsible for the shipping documents upon billied on the shipping document is another another and the shipping document is another another and the shipping documents and the special miningiately upon unpacking. Should product again with the miningian and the unpacked and trainburded inmediately to provide adminished and practical miningian and produce again.

SEALANTS

Sealants shall be applied in strict accordance with Butler details or weather tightness will be compromised. Sealant must be applied in temperatures and weather conditions consistent with labeling.

INDEPENDENT MEZZANINES

Independent nezzanires must be designed by a professional engineer. The engineer must ensure that proper isolation from the Buttler buildy gas been provided to avoid sitructural damage due to differential movements, or indeventently apply loads to the Builder sitructure. Builder accepts no responsibility for the design of the independent mezzanire.

FIRE CODE COMPLIANCE

It is the responsibility of the project design professional and builder to comply with local fire code regulations including consideration of bur too filmstee by cultifiquing use and occupancy, all building construction materials, separation requirements, agress requirements, fire protection systems, etc. Builder shall advise Butler of any special requirements to be furnished by Butler.

FIELD MODIFICATIONS

Modifications to this building from details and instructions contained on these drawings must be approved in writing by gather fifty, and the statement structural regiment. This includes, not a not instruct or, removed of root and indefinite, entrying or moving any frange insers or out a not instruct or, removed of root and indefinite, entrying or moving any frange insers or that is not a shall not increase or the structure because the limit of increase or each of the structure because their is specified for this building in the contract documents. Builder Mits, accepts no responsibility for the consequences of any unauthorized additions, alterations, or added loads to this structure.

If the builder intends to invoice Batter Mfg. for modifications in excess of \$1000. The builder materially during builder bei builder builder bei buil

CONCRETE/MASONRY/CONVENTIONAL STUD WALLS

The engineer responsible for the design of the wall system is responsible for coordinating with, or specifying to Bullst Might, any will a sele to compatibility, separate and deflection or compatibility, special base details, and wall to Bullst ested connections. All tashens; sealant and counter flashing of wall systems are to be provided by contractor. The engineer responsible for the wall half design the anchorage to Bullst supporting elements consistent with Code trequest forces.

Oil canning is an inherent characteristic of cold formed steel panels. It is the result of several installed to the control of several installed to the characteristic of the control of the control of the characteristic o

Roof rumble is a phenomenon that is caused by wind gusts lifting up on the roof panels and then springible back into please. All panels experience this such to some degree, especially with conceased city Sann panels. Roof rumble notise may be minimized by providing also, of blanke insulation between the penels and my hard support surface such as steel secondary members, substates such as plywood, steel decking, or rigid board insulation. A minimum of 3 inch thick blanket is recommended over steel secondary members, or 2 inch over substrates.

Oil canning, dimpling, and roof rumble do not affect the structural integrity or weather tightness of the panels and is not grounds for rejection of panels.

The Standing Seam joint detail is designed with an interlocking feature for ease of installation. Housever, it is impreative than installed Standing Seam panies be secured to the secondary structural members and properly seamed prior to departure from the job site each day.

Local building departments may require added fail restraint due to conditions that may affect the skylight structural integrify. It he responsibility of the builder to determine and provide any added fail restaint under the skylight as may be required by your building department. SKYLIGHTS

Disalage system must be designed by the project professional to comply this code requirements belief in not responsible for disalaged elegipm, entrope suppers, down piping, etc. The project professional and contractor are responsible to ensure that primary disms and overflow devices such as exceptors and uniting of dims are provided as encluded for the required rain intensity at the building perimeter and at variety contilions to prevent pointing. RAIN WATER RUNOFF

STEEL SHOP COAT

The purpose of Butler's shop coat is to provide protection for the steel members during transportation, during explanted sheath as the provide promised in the protection, and the parties as the property of the provided sheath as the promised is not designed to perform as a finish coat when exposed to environmental conditions. Members shall be kept free of the ground and property drained during jobs this storage. It is the Butlete's responsibility to ensure that if a finish coat is being applied over Butler sho coat that the painting contractor verifies compatibility between its finish coat and Butler's shop coat.

BUTLER MFG. ACCREDITATIONS AND APPROVALS Fabricator Approvals M. SA ACTZ Approvalic (www.lasonline.org/sen/cesahreata-building-inspection)
Listed under Eluscope Buildings North America, Inc. City of Los Ampelea, CA #FB00031; City of Housine, IX 187;
City of Los Ampelea, CA #FB00031; City of Housine, IX 187;
City of Prosents, CS 1942009; Cist County, NV 42 & 833, San Bernardino County, CA 289;
State of Unia, City of Richmond, Ca.

IAS ACAT? Approvals: (www.laconline.org/services/meal-building-inspection)
Listed under Builer Manuferbring, a Division of BlueScope Buildings North America, Inc.
Canadian CSA A60 O Certifications

(www.cwbgroup.org) Listed under BlueScope Buildings North America, Inc.

Engineering Certifications of Authorization
USA-ALEACASSE, LANGESCE, ARBERTS, ELEGADZI, CAMPETOTTSSI; IDAC-2470; IL#184-002649;
USA-ALEACASSES, LANGESCESCE, ARBERTS, BISSE, BOOKTSSI, NOTE-CORONTTSSI, NOTE-CORONTSSI, NOTE-C

ERECTION NOTES MAR Building Solutions LOCATION: Lees Summit, Missouri PROJECT: LSMO Water Utilites BUILDER: M BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 NTS Ω

THE BITTE HAR GENERATES SEAL, APPLES

WILL YO THE WORK PRODUCT OF BITTER

WICH AND DESIGN AND PREPORANCE

FROUIBEMENTS SPECHED BY BITTER

THE BITTER HAVE DESIGN AND THE PRODUCT OR


CORRISOL OF AND TOTHE PREPORANCE OR


TO ANY DESIGN OF BEFOREMANCE OR


TO ANY DESIGN OF BEFOREMANCE


FROUIBEMENTS SPECHED BY BUTTER EXCEPT.


IN THE DRIVING THE REQUISION THE ROUND THE DILLOHOUS THE DILLOHOUS THE DILLOHOUS THE DILLOHOUS THE PROPERTY OF BETCHEVER THE DILLOHOUS THE DILLOHOUS THE PROPERTY OF THE PROPERTY OF THE MENT ARRESTS THE WALL NOT THE MENDER THE PROPERTY OF THE WEST SHALL NOT THE MENDER THE PROPERTY OF THE WEST SHALL NOT THE MENDER THE WEST SHALL WHICH THE DILLOHOUS THE WEST THE GENERAL CONTRACTOR AND/ONE ERECTROR IS SOLE! YES SHOUGHT FOR ACCURACY THE DILLOHOUS THE MENT SHALL S













RELEASED FOR CONSTRUCTION

As Noted on Plans Review

Development Services Department Lee's Summit, Missouri 08/07/2024






RELEASED FOR CONSTRUCTION

As Noted on Plans Review

Development Services Department Lee's Summit, Missouri 08/07/2024



PERMIT SET- For Building Dept. Approved a solutions of the solutions of th FNB002 BASIC ERECTION GUIDE - STRUCTURAL WIDESPAN STRUCTURAL SYSTEM BUTLER 2013 INSTALLATION GUIDE BASIC ERECTION GUIDE REQUIRED FOR THIS PROJECT: PRIMARY BRACING SED'S LOCATION: Lees Summit, Missouri
PROJECT: LSMO Water Utilities
BUIL DERS POR: BUILDER: MAR Building Solutions customire: REFER TO: CBX*** = CANOPY (PLATE)
CBX*** = PIGGYBACK CANOPY
DCC*** = 8 1/2" GAGE POST
DCE*** = 10" GAGE POST RBX*** = RAFTER (PLATE)
BGX*** = RAFTER (GAGE)
WRX*** = RAFTER (HOTROLL)
TRX*** = TRUSS RAFTER ICX*** - INTERIOR COLUMN
PCX*** - PIPE COLUMN
TCX*** - TUBE COLUMN CX*** = CDLUMN (PLATE)
CGX*** = CDLUMN (GAGE)
WCX*** = CDLUMN (HOTROLL EPX*** = ENDPOST (PLATE) EGX*** = ENDPOST (GAGE) RS - THREADS BOTH ENDS RT = THREADS ONE END - CLEVIS ONE END RU = CLEVIS BOTH ENDS RP = THREAD BOTH ENDS - NO HILLSIDES MARK NUMBER KEY COMMON GENERATED MARK NUMBERS BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 DEPTH LENGTH GAGE ADJUST; CODES INSULATION

1 B 1 3 0 1 0 3 6 0 3 0 W V

* * F F F 1 1 1 1 1 E C C

LENGTH MDTH THK CODE PANEL/COVERING
W 1 3 1 1 7 2 6 1 K T D
+ F F I 1 E G G C C C
LENGTH CODE NTS R0D BRACING 0 3 R S 2 5 1 D 1 E * * F F 1 1 DIA LENGTH EV. DATEOR/29/12 [REV. NO. 01 EN 50B1 TOMOGE BROCK EGLOBECKOON

FULLED - ORGER TRANSPORTED WHICH THE WEARLEN FOR THE PRANK THE RECEIVED WHICH THE WEAR WEAR TOWNED BY TO STORY THE TRANSPORTED WHICH THE WEAR T Ω - FLANCE BRACE WILL THRICALLY CONNECT TO THE WEB OF THE FRAME MEMBER. (CFB-) OR (HFB-) THE DIMENT NET THE PROMISED SELLAY OF RECEIPTOR THE PROGRAM OF THE CLP REG'D W/ £ FRAME BRACE THE BALLOW WILL HAVE TO FILLD IN THE BALLOW THE 91/6" DAME HOLD IN THE 91/6" DAME HOLD IN THE 91/6" DAME HOLD IN THE 17 DAME 17 DAME HOLD IN THE 17 DAME 17 DAME 17 WHEN REQUIRED.) CLEVIS PIN


(WTH SHOULDER)


MAY BE CHENSHED WITHOUT

A SHOULDER, THEN TWO COTTER

PIN WILL BE PROVIDED. THE BUT THE MODE SHOWING SHOULD WE WANTED WITH THE MODE SHOULD WE WANTED THE WANTED WE W ROD BRACING CLEWS ASSEMBLY PIN DIA. 1/4" 1/2" CLEVIS EX. DATE:06/23/11 | REV. NO. 03 | BR02K1 BRACE ROD PERMANDE PROPERTY OF THE PROP WEB REINFORCEMENT PLATE (IF PRESENT) MAY BE SHOP WELDED ON EITHER SIDE OF THE WEB. I. LISE TAY I LAZS TIBE OLI GREAD AND INIT (TAYL). WO WASTERS, SIMOT TOFFITH BOLTS FOR ALL SECONDARY CONNECTIONS, SECONDARY LOCAL FOR PELANCE BRACE CONNECTIONS. UNLESS NOTED OTHERWISE.

S. S. OF TREMPOREMENT ALTER WEB NOTE OF THE SAME SING O'THE WAS AS THE HALLSDEW WASHER. HORIZONTAL CLEARANCE CLEARANCE EXTERIOR VERTICAL SPLICE ROD BRACE WEB SLOT ASSEMBLY ROOF REAM HORIZONTAL OLEARANCE VERTICAL EXTERIOR CLEAR HEI INTERIOR COLUMN SPLICE ROOF BEAM COLUMN OR BEAM ROOF BEAM COLUMN HORIZONTAL SPLICE REV. DATEOR/12/16 REV. NO. 00 PFROO7 18/02/17 REV. NO. 04 ROD-






PERMIT SET- For Building Dept. Approva RACE STRUT PANEL CLIP AT EAVE STRUT REQUIRED RESULP BUT CONNECTION REQUIRED INSERT PANEL CLIP
ADAPTER (0543130)
THRU HOLES AND
BEND TASS AWAY
FROM SPLICE. USE A PANEL CUP ADAPTER AT THE ENDS OF PURLINS OR EAVE STRUTS WHERE A PANEL CLIP OR PANEL EAVE ATTACHMENT MUST BE MADE. PANEL CLIP ADAPTER PURLIN OR— EAVE STRUT RODF BEAM (2) 1/2" X 2" A325 BOLT (097280) LOW EAVE STRUT SHOWN - HIGH EAVE STRUT SINULR RATES/22/PH EAVE STRUT CONNECTION R\$12PH AT END FRAME. *1'-0" AT 7" & 8 1/2" DUTSET 1'-3" AT 10" & 11 1/2" OUTSET BUTLER MANUFACTURING SHIM (SEE C EAVE -—(4) 1/2" A307 THIN HEAD BOLT (096636) & NUT (095032) —EAVE STRUT EAVE STRUT CONNECTION AT INTERIOR FRAME SHIM PLATE . (SEE CHART) EAVE STRUT BRACE STRAP (ESBS_) (2) 1/2" X 2" A325 BOLT (097280) EAVE STRUT-CLIPS MAY BE REQURED FOR PURIN TO FRAME CONNECTIONS. REFR TO INDIVIDUAL FRAME CROSS SECTIONS FOR BOLTED CLIP PART NUMBERS AND THEIR LOCATIONS. BOLTED CUP CONNECTION ALT, CONNECTION PURLIN CONNECTION TO END FRAME CONTINUOUS PURLNS WELDED CLIP CONNECTION ALT. CONNECTION REV. RATEORATAS REV. NO. 02 RSO2T1 CLIPS MAY BE REQUIRED FOR PURLIN TO FRAME CONNECTIONS. REFER TO INDIVIDUAL FRAME CROSS SECTIONS FOR BALTED CLIP PART IUMBERS AND THEIR LOCATIONS. 7 & 8 1/2" PURLIN CONNECTION AT INTERIOR FRAME CONTINUOUS PURLINS VALUES NOTED LUGE LEST AT A TAZA ZERO EL (1980) ANNU IT (FLEXON WON WASHERS SAUGH THEIR BOLTS FOR ALL SECONDARY CONNECTIONS.

WON WASHERS SAUGH SEANINEEDAL PART OF THE STABILITY OF THE STRAILITY OF THE STABILITY OF THE STABILIT MELDED CLIP CONNECTION
ALT. CONNECTION REV. DATE OF TAXABLE NO. DO DO DE PREV. NO. DO DO DE PERO DE DE PERO DE PERO DE DE PERO DE PER

14:40:32

THE BITTLE IN ME CHORLERS SEAL, APPLES ONLY TO THE WORK PRODUCT OF BITTLE IN ME CHORLERS SEAL, APPLES ONLY TO THE WORK PRODUCT OF BITTLE IN THE BITTLE IN THE BITTLE IN THE BITTLE IN THE PRODUCT OR COMPONENT THE WORLD TO THE PRODUCT OR TO THE PROD



PERMIT SET- For Building Dept Approval

"The Passes of Control of SECONDARY ELEVATION AT 1 BOLLOER MAR Building Solutions
CUSTOMER
LOCATOR: Lees Summit, Missouri
PROJECT: LSMO Water Utilities
BOLLOERS FOR BUTLER MANUFACTURING 1540 GENESSEE ST. KANSAS CITY, MO 64102 NTS Ω NHE PRIMING INCLIDING THE BROAD WINNE Additional 3 ADD'ITON, Wall = 2 ADD'ITON, Wall = 2 ADD'ITON, Wall = 2 ADD'ITON, WALL PROPERTING THE BROAD WAS ADDITION. THE APPLY ADDITION OF THE PROPERTING THE PR <u>_</u> 4 THE BUTLER MFO. ENGNEERS SEAL APPLIES ONC. ON TESTON MORE SEAL APPLIES ON THE SEAL OF SECONDARY ELEVATION AT 1 Detail WS12H6, WSROO4, WSRO65, WSRO63, BRRO52 WS12H6, WSRO04, WSRO65, WSRO63, WSRO63 WS12H6, WSRO04, WSRO65, BRRO52, WSRO63 LULES NOTED LOST AT 17 A CASTA COLI, GROON, AND MUT (PICTOR)
WO WASHERS SHUG THERE BOLTS FOR ALL SECONDARY CONNECTIONS.
TAMORE BACKES SHUG THERE AND INTEGRAL AND STORE THE STANGISTY OF THE
STRACTURAL SYSTEM AND INTEGRAT OF THE STANGISTY OF THE
STRACTURAL SYSTEM AND INTEGRATION OF ANY CONNECTION STRAINED PROOFT OF BECTION
3. REMOVAL OR ALTERATION OF ANY COMPONENT SPONBIETED. Lap Thick. 0.1130 0.0730 . Part Schedule Part 0821906411EE10 0821906415EE10 Bracing Part Schedule Part Qty Length 04RS2210 2 22'-10" 4 4'-2 1/2" 3 3'-6" 2 1'-0" 1 6" Dimension Key Second Mark G7 G8

