





TRUSS QUANTITY	56
GABLE AREA	787
HIP LINES	0
HORIZONTAL OVERHANG LINES	92
RAKED OVERHANG LINES	256
RIDGE LINES	84
ROOF AREA	3,115
VALLEY LINES	58

SQUARE FOOTAGE IS ESTIMATED. CONTRACTOR/FRAMER VERIFICATION REQUIRED.

- EL EXTREMO IZQUIERDO DE LOS TRUSSES (VEA LOS PERFILES)

TODAS LAS DIMENSIONES PARA LAS TRUSSES SON DE FUERA DE LA MADERA (u.n.o.)

ESTABLECER LOS TRUSSES NIVELADAS CON LA ESTRUCTURA (u.n.o.)

- LEFT END OF TRUSS (SEE TRUSS PROFILES)

ALL ROOF TRUSS DIMENSIONS ARE FROM OUTSIDE EDGE OF STUD (u.n.o.) SET ROOF TRUSSES FLUSH WITH FRAMING (u.n.o.)

WARNING: Trusses must be handled with care to prevent damage and injury.

This truss placement diagram is to be used only as an installation aid; it is not a structural diagram. These trusses are designed as individual building components to be incorporated into the building design at the the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing.

Professional advice should be sought regarding handling, installation, temporary and permanent bracing before erecting trusses. Temporary and permanent bracing is required during installation of trusses to prevent possible collapse.

For general guidance regarding bracing, consult "BCSI-06" available jointly from WTCA & TPI.

Premier Building Supply must be notified of any issues requiring a back charge prior to any work being done. Premier Building Supply reserves the right to use it's service staff in lieu of being back charged.

			N	1	0-00-00)		_								
8-	Hatch Legend 1-2 (AFF) 1-2 (AFF)								1-03-00	2-00-00	<u>2-00-00</u>	2-00-00	2-00-00	2-00-00	2-00-0Q	2-0
	19-07-00		2-00-00	2-00-00	2-00-00	2-00-00	2-00-0		A02	A02	A02	A02	A02	A02	A02	
52-00-00	8-11-00															
	21-06-00	C01	C02	C02	C02	C02	Ch3			26 26 26	TTIC ACC	1	2-00-00-00-00-00-00-00-00-00-00-00-00-00	VA6	D04 D04 D04 D04 D03 D03	
LOCATE ATTI AS DESIRED MUST BE PLACE TO TRUSS D	C ACCE\$S ACCESS ED PARALLEL IRECTION. 00-00- C							C		26			2-00-00-00-00-00-00-00-00		D03 D03 D02 D02	
		ł	<u></u>	1	<u>0-00-00</u>)		\						0-00-00	D01	

