

Spacing Charts Based on MUTCD			Must be Approved by an Engineer				
Speed (MPH) Prior To Road Work	SIGN SPACING, FT.		BUFFER SPACE, FT.	TAPER LENGTH, FT.		CHANNELIZING SPACING, FT.	
	Non-Divided Highways	Divided Highways		Shoulder (10 ft Width)	Lane (12 ft Width)	Through Taper	Through Buffer/Work Area
0-35	200	200	250	70	245	35	50
40-45	350	500	360	150	540	40	80
50-55	500	1000	495	185	660	50	100
60-70	SA-1000, SB-1500, SC-2640		730	235	840	60	120
	Urban Low Speed - 100 FT						

APPROVED/ACCEPTED BY:
ENGINEER, OWNER, or PRIME CONTRACTOR

Check for Notice to Proceed.

Signature: _____

Company: _____

Road Runner
Safety Services, Inc.

Date: 3/11/2025 Project: NE DOUGLAS - 250 NE ALURA WAY, LEES SUMMIT :
Traffic Control Suggestion For: ERVIN CABLE CONSTRUCTION :
By: Road Runner Safety Services, Inc. : Nathan

Comments:
Drawing not to scale. Traffic control plan must be approved by an engineer. This is a suggestion only. Road Runners Safety Services, Inc. has no liability for this suggested traffic control plan. Actual placement and spacing of all traffic control devices will depend on field conditions and must conform to MUTCD standards.

Legend	Manifest
Channelizer	75 x Channelizer
Work Area	4 x End Road Work
	4 x Keep Right
	1 x Reverse Curve Left
	1 x Reverse Curve Right
	5 x Utility Work Ahead

