RELEASE FOR CONSTRUCTION PREMIER **AS NOTED ON PLANS REVIEW** BUILDING SUPPLY OF KANSAS CITY **DEVELOPMENT SERVICES** TODAS LAS CONEXIONES DE TRUSS A TRUSS = 'CLAVADAS " (u.n.o. Phone: 913.686.1812 LEE'S SUMMIT, MISSOURI Since 1923 04/04/2025 5:01:06 Clayton Properties Carolina Modern Prairie 3 Car 45-04-00 2761 SW 11th St Salesperson: Kyle Clifford Michael Dueker 13 7 **HANGER QUANTI** NTS 3/28/2025 P250279 SCHEDULE ΤY **ROOF TRUSS PLACEMENT J**7 DIAGRAM LUS24 24 LUS26 0 J3 5 J3 HUS26 2-00-0⊄-00-0⊄-00-002-00-0⊄-00-0⊄-00-0⊄-00-0⊄-00-0⊄-00-0⊄-00-0Д ₹ 2-00-0⊄-00-0⊄-00-0⊄-00-0⊄-00-0 5-11-04 5-11-04 **HHUS26-2** 0 J6 J2 J6 HGUS26-2 0 A10 A12 A16 A15 A14 A13 B1 **B**3 B4 ▲ HGUS28-2 0 J1 THJA26 8 J6 TJC37 0 J1 J6 0 J6 THJU26 HUS28 0 EVERSTEAD SHOP DRAWINGS/SUBMITTAL REVIEW J1 J6 HUS28-2 J6 0 AND GENERAL CONFORMANCE TO CONTRACT DOCUMENTS ONLY. THE CONTRACTOR IS RESPONSIBLE FOR CONFIRMING AND CORRELATING DIMENSIONS AT HHUS210-2 0 J1 J6 7-11-04 JOBSITE FOR TOLERANCE, CLEARANCE, QUANTITIES J6 ▲ HHUS28-2 LG1 FABRICATION, COORDINATION OF HIS OR HER WORK WITH OTHER TRADES, AND FULL COMPLIANCE WITH CONTRACT DOCUMENTS. LG2 LUS28 0 J1 J6 0 SUL24 **APPROVED** SUL26 0 J6 J1 04/02/2025 SUR24 0 REVIEWED BY: SUR26 0 J1 HCJ THA422 0 J6 THA426 0 ENGINEER, EVERSTEAD ENGINEERING & DESIGN LL J1 J6 J6 O THAC422 0 △ THAC426 0 J1 THJA26 J6 △ THASL29 0 LG3 LG4 △ THASR29 0 J1 J6 0 0 J1 2-01-092-00-00 HUS26 J3 0 J1 E2 1-01-10 00-00 M6

LUSZ4

00-00 M5

13 00-00 M4

17 00-00 M3 M2 ♀ J2 00 3-11-04 00-00-00-00-00-00 LUS24 C1 J7 J3 15 J3 - EL EXTREMO IZQUIERDO DE LOS TRUSSES (VEA LOS PERFILES) 77 444 M2 9 J7 TODAS LAS DIMENSIONES PARA LAS TRUSSES SON DE FUERA DE LA MADERA ESTABLECER LOS TRUSSES NIVELADAS CON LA ESTRUCTURA (u.n.o.) J7 5-10-00 8-08-12 M1 7 72 17 - LEFT END OF TRUSS (SEE TRUSS PROFILES) **1**9 **1**9 134 (C) ALL ROOF TRUSS DIMENSIONS ARE FROM OUTSIDE EDGE OF STUD (u.n.o.) SET ROOF TRUSSES FLUSH WITH FRAMING (u.n.o.) 13-04-00 11-06-00 13-06-00 9-08-00 3-06-00 3-06-00 WARNING: Trusses must be handled with care to prevent damage and injury. This truss placement diagram is to be used only as 45-04-00 Ihis truss placement diagram is to be used only as an installation aid; it is not a structural diagram. These trusses are designed as individual building components to be incorporated into the building design at the the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. Professional advice should be sought regarding

20300 W 207TH St Spring Hill, KS 66083

handling, installation, temporary and permanent bracing before erecting trusses. Temporary and permanent bracing is required during installation of trusses to prevent possible collapse.

For general guidance regarding bracing, consult "BCSI-06" available jointly from WTCA & TPI.

Premier Building Supply must be notified of any issues requiring a back charge prior to any work being done. Premier Building Supply reserves the right to use it's service staff in lieu of being back charged.

1 - SDWC 15600 REQUIRED AT ALL BEARING LOCATIONS (u.n.o.) ALL TRUSS TO TRUSS CONNECTIONS = 'NAILED" (u.n.o.)

- SDWC 15600 NECESARIO EN TODO LOS PUNTOS DE APOYO (u.n.o.