

RE: P250041-02 - Roof - HM Lot 200 Repairs

MiTek, Inc.
16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200

Site Information:

Project Customer: Clayton Properties Project Name: Charlotte - Mediterranean 3 Car

Lot/Block: 200

Subdivision: Highland Meadows

Model:

Address: 1055 SW Fiord Dr

City: Lee's Summit

State: MO

General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):

Design Code: IRC2018/TPI2014

Wind Code: ASCE 7-16

Wind Speed: 115 mph

Roof Load: 45.0 psf

Mean Roof Height (feet): 35

Design Program: MiTek 20/20 8.6

Design Method: MWFRS (Envelope)/C-C hybrid Wind ASCE 7-16

Floor Load: N/A psf

Exposure Category: C


No.	Seal#	Truss Name	Date
1	I72736202	A4	4/16/25
2	I72736203	A7	4/16/25
3	I72736204	A8	4/16/25
4	I72736205	A10	4/16/25

The truss drawing(s) referenced above have been prepared by MiTek USA, Inc. under my direct supervision based on the parameters provided by Premier Building Supply (Springhill, KS)20300 W 207th Street.

Truss Design Engineer's Name: Lu, Jie

My license renewal date for the state of Missouri is December 31, 2026.

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.




April 16, 2025

Job	Truss	Truss Type	Qty	Ply	Roof - HM Lot 200 Repairs	172736202
P250041-02	A4	Hip	1	1	Job Reference (optional)	

Premier Building Supply (Springhill, KS), Spring Hills, KS - 66083,
REPAIR:
BREAK IN MEMBER 16-17 LOCATED 1-6-0 FROM JOINT 16.
BREAK IN MEMBER 13-14 LOCATED 1-0-0 FROM JOINT 14.

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Mon Apr 14 09:28:33
ID:dfLmCUhkNXUHGcbAltBhFzb2L0-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCD0i7J4zJC?f

Page: 1



Scale = 1:73

Plate Offsets (X, Y): [11:Edge,0-5-8], [12:0-2-8,0-2-0], [18:0-2-8,0-2-0], [19:Edge,0-5-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.72	Vert(LL)	-0.24	15	>999	240	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.96	Vert(CT)	-0.49	13-15	>976	180	MT18HS	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.95	Horz(CT)	0.14	11	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 182 lb	FT = 20%

LUMBER		
TOP CHORD	2x4 SP No.2 *Except* 4-6,6-7:2x4 SP 2400F 2.0E	
BOT CHORD	2x4 SP No.2	
WEBS	2x3 SPF No.2 *Except* 19-2,11-9:2x4 SP No.2	
BRACING		
TOP CHORD	Structural wood sheathing directly applied or 2-9-5 oc purlins, except end verticals, and 2-0-0 oc purlins (4-0-6 max.): 4-7.	
BOT CHORD	Rigid ceiling directly applied or 2-2-0 oc bracing.	
WEBS	1 Row at midpt	5-17, 5-13
REACTIONS (size)		
	11=0-5-8, 19=0-5-8	
	Max Horiz 19=105 (LC 10)	
	Max Uplift 11=216 (LC 13), 19=216 (LC 12)	
	Max Grav 11=1858 (LC 1), 19=1858 (LC 1)	
FORCES (lb) - Maximum Compression/Maximum Tension		
TOP CHORD	1-2=0/32, 2-3=-3033/481, 3-4=-2765/478, 4-5=-2397/468, 5-7=-2398/466, 7-8=-2767/479, 8-9=-3032/478, 9-10=0/32, 2-19=-1784/361, 9-11=-1784/363	
BOT CHORD	18-19=-209/622, 17-18=-359/2625, 15-17=-400/3040, 13-15=-400/3040, 12-13=-330/2623, 11-12=-122/626	
WEBS	3-18=-106/90, 3-17=-273/197, 4-17=-53/743, 5-17=-932/236, 5-15=0/364, 5-13=-928/235, 7-13=-51/737, 8-13=-269/196, 8-12=-105/90, 2-18=-240/2011, 9-12=-236/2006	

NOTES
1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TC DL=6.0psf; BCDL=6.0psf; h=35ft; Ke=1.00; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -0-10-8 to 4-1-8, Interior (1) 4-1-8 to 11-5-6, Exterior(2R) 11-5-6 to 18-6-4, Interior (1) 18-6-4 to 28-6-10, Exterior(2R) 28-6-10 to 35-7-8, Interior (1) 35-7-8 to 40-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) All plates are MT20 plates unless otherwise indicated.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) All bearings are assumed to be SP No.2 crushing capacity of 565 psi.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 216 lb uplift at joint 19 and 216 lb uplift at joint 11.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 16, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcscomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Roof - HM Lot 200 Repairs	I72736203
P250041-02	A7	Hip	1	1	Job Reference (optional)	

Premier Building Supply (Springhill, KS), Spring Hills, KS - 66083,
REPAIR:
BREAK IN MEMBER 19-20 LOCATED 1-0-0 FROM JOINT 19.
BREAK IN MEMBER 15-16 LOCATED 1-6-0 FROM JOINT 16.

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Mon Apr 14 09:28:34
ID:2E1uqVjcgSsr7fKIQ?Luluzb2Kz-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwRCDoi7J4zJC?f

Page: 1



Scale = 1:73.6

Plate Offsets (X, Y): [2:Edge,0-2-4], [4:0-1-10,0-1-8], [10:0-1-10,0-1-8], [14:Edge,0-2-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.61	Vert(LL)	-0.19	15-17	>999	240	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.82	Vert(CT)	-0.39	15-17	>999	180	
BCLL	0.0	Rep Stress Incr	YES	WB	0.90	Horz(CT)	0.16	14	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							
Weight: 196 lb FT = 20%											

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x3 SPF No.2 *Except* 21-2,14-12:2x4 SP 2400F 2.0E

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-0-5 oc purlins, except end verticals, and 2-0-0 oc purlins (4-0-8 max.): 6-8.
BOT CHORD Rigid ceiling directly applied or 8-9-6 oc bracing.

WEBS 1 Row at midpt 3-21, 11-14, 7-18, 7-17
REACTIONS (size) 14=0-5-8, 21=0-5-8
Max Horiz 21=144 (LC 16)
Max Uplift 14=269 (LC 13), 21=269 (LC 12)
Max Grav 14=1858 (LC 1), 21=1858 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/32, 2-3=-893/213, 3-5=-2886/501, 5-6=-2338/490, 6-7=-2011/475, 7-8=-2011/475, 8-9=-2338/490, 9-11=-2886/501, 11-12=-893/213, 12-13=0/32, 2-21=-649/222, 12-14=-649/222
BOT CHORD 20-21=-437/2600, 18-20=-293/2386, 17-18=-179/2072, 15-17=-266/2386, 14-15=-341/2600
WEBS 6-18=-106/721, 8-17=-106/721, 3-21=-2201/308, 11-14=-2201/308, 7-18=-352/137, 7-17=-352/136, 3-20=-164/193, 5-20=-45/348, 5-18=-575/259, 9-17=-575/259, 9-15=-46/348, 11-15=-164/193

NOTES

1) Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Ke=1.00; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -0-10-8 to 4-1-8, Interior (1) 4-1-8 to 16-5-6, Exterior(2E) 16-5-6 to 23-6-10, Exterior(2R) 23-6-10 to 30-7-8, Interior (1) 30-7-8 to 40-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SP No.2 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 269 lb uplift at joint 21 and 269 lb uplift at joint 14.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 16, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®


16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Roof - HM Lot 200 Repairs	
P250041-02	A8	Hip	1	1	Job Reference (optional)	I72736204

Premier Building Supply (Springhill, KS), Spring Hills, KS - 66083,
REPAIR:
REPLACE DAMAGED MEMBERS 3-19 AND 5-19.

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Mon Apr 14 09:28:34
ID:h?iaC_Sprh5zUHeW8NxkPFzb2LJ-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



ATTACH 7/16" OSB GUSSET (7/16" RATED SHEATHING 24/16 EXP 1)
TO EACH FACE OF TRUSS WITH (0.131" X 2.5" MIN.) NAILS PER THE FOLLOWING NAIL SCHEDULE:
2 X 3'S - 2 ROWS, 2 X 4'S - 3 ROWS, 2 X 6'S AND LARGER - 4 ROWS: SPACED @ 4" O.C.
NAILS TO BE DRIVEN FROM BOTH FACES. STAGGER SPACING FROM FRONT TO BACK FACE
FOR A NET 2" O.C. SPACING IN EACH COVERED TRUSS MEMBER. USE 2" MEMBER END DISTANCE.



INSTALL 2 X 4 SPF/DF/SP NO.2
CUT TO FIT TIGHT.

Scale = 1:73.7

Plate Offsets (X, Y): [2:Edge,0-2-4], [11:Edge,0-2-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.69	Vert(LL)	-0.19	14-16	>999	240	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.91	Vert(CT)	-0.42	14-16	>999	180	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.88	Horz(CT)	0.16	13	n/a	n/a	
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							
Weight: 193 lb FT = 20%											

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x3 SPF No.2 *Except* 20-2,13-11:2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-7-15 oc purlins, except end verticals, and 2-0-0 oc purlins (3-2-2 max.): 6-7.
BOT CHORD Rigid ceiling directly applied or 8-5-9 oc bracing.
WEBS 1 Row at midpt 7-17, 5-17, 8-16, 3-20, 10-13

REACTIONS

(size) 13=0-5-8, 20=0-5-8
Max Horiz 20=151 (LC 16)
Max Uplift 13=-276 (LC 13), 20=-276 (LC 12)
Max Grav 13=1858 (LC 1), 20=1858 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/32, 2-3=-837/183, 3-5=-2870/484, 5-6=-2272/478, 6-7=-1949/467, 7-8=-2271/478, 8-10=-2871/484, 10-11=-837/183, 11-12=0/32, 2-20=-613/205, 11-13=-613/205
BOT CHORD 19-20=-467/2609, 17-19=-297/2344, 16-17=-128/1948, 14-16=-245/2344, 13-14=-343/2609
WEBS 6-17=-69/594, 7-17=-222/225, 7-16=-128/606, 3-19=-202/214, 5-19=-39/388, 5-17=-617/273, 8-16=-617/273, 8-14=-39/389, 10-14=-202/214, 3-20=-2263/332, 10-13=-2264/332

NOTES

1) Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Ke=1.00; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -0-10-8 to 4-1-8, Interior (1) 4-1-8 to 17-2-14, Exterior(2E) 17-2-14 to 22-9-2, Exterior(2R) 22-9-2 to 29-9-15, Interior (1) 29-9-15 to 40-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SP No.2 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 276 lb uplift at joint 20 and 276 lb uplift at joint 13.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 16, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Roof - HM Lot 200 Repairs	I72736205
P250041-02	A10	Hip	1	1	Job Reference (optional)	


Premier Building Supply (Springhill, KS), Spring Hills, KS - 66083,

Run: 8.63 S Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Mon Apr 14 09:28:34

Page: 1

REPAIR:
BREAK IN MEMBER 16-17 LOCATED AT MIDPOINT.

ID:F4ZfksFKU0nYNNmezflPAWz8PrC-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f



Scale = 1:73.3

Plate Offsets (X, Y): [12:0-3-0,0-2-4], [13:0-2-8,0-2-0], [19:0-2-8,0-2-0], [20:0-3-0,0-2-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	25.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.18	16	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.75	Vert(CT)	-0.33	16-18	>999	180		
BCLL	0.0	Rep Stress Incr	YES	WB	0.80	Horz(CT)	0.12	12	n/a	n/a		
BCDL	10.0	Code	IRC2018/TPI2014	Matrix-S							Weight: 191 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2 *Except* 3-5,7-9:2x4 SP 2400F 2.0E
BOT CHORD 2x4 SP No.2
WEBS 2x3 SPF No.2 *Except* 20-2,12-10:2x6 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (3-3-0 max.): 5-7.
BOT CHORD Rigid ceiling directly applied or 9-11-1 oc bracing.

REACTIONS

(size) 12=0-5-8, 20=0-5-8
Max Horiz 20=125 (LC 11)
Max Uplift 12=247 (LC 13), 20=247 (LC 12)
Max Grav 12=1857 (LC 1), 20=1857 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/35, 2-4=-3021/482, 4-5=-2545/474, 5-6=-2409/507, 6-7=-2409/507, 7-8=-2545/474, 8-10=-3021/482, 10-11=0/35, 2-20=-1780/372, 10-12=-1780/372
BOT CHORD 19-20=-288/706, 18-19=-347/2601, 16-18=-201/2174, 14-16=-188/2174, 13-14=-318/2601, 12-13=-178/706
WEBS 4-19=-24/180, 4-18=-513/249, 5-18=-51/421, 5-16=-150/543, 6-16=-494/217, 7-16=-150/543, 7-14=-51/421, 8-14=-513/248, 8-13=-24/180, 2-19=-205/1901, 10-13=-203/1901

NOTES

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Ke=1.00; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -0-10-8 to 4-1-8, Interior (1) 4-1-8 to 14-1-13, Exterior(2R) 14-1-13 to 21-2-11, Interior (1) 21-2-11 to 25-10-3, Exterior(2R) 25-10-3 to 32-9-13, Interior (1) 32-9-13 to 40-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SP No.2 crushing capacity of 565 psi.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 247 lb uplift at joint 20 and 247 lb uplift at joint 12.
- 7) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



April 16, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

MiTek®

16023 Swingley Ridge Rd.
Chesterfield, MO 63017
314.434.1200 / MiTek-US.com

Symbols

PLATE LOCATION AND ORIENTATION



* Plate location details available in MITek software or upon request.

PLATE SIZE

4 X 4

The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.

Industry Standards:

ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-22: Design Standard for Bracing.
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

Numbering System



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

Product Code Approvals

ICC-ES Reports:

ESR-1988, ESR-2362, ESR-2685, ESR-3282
ESR-4722, ESL-1388

Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 1 section 6.3. These truss designs rely on lumber values established by others.

© 2023 MITek® All Rights Reserved

MITek®

MITek Engineering Reference Sheet: MII-7473 rev. 1/2/2023

General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.