VAN DEURZEN AND ASSOCIATES, P.A.

CONSULTING STRUCTURAL ENGINEERS 11011 KING STREET, SUITE 130 COMMERCE TERRACE BUILDING D OVERLAND PARK, KANSAS 66210 (913) 451 - 6305 FAX (913) 451 - 1021

Address or Project Name	City	Inspec	tor		Date		Time	
2108 SW Wheatfield Dr	Lee's Summit	Roh	Bob Rowe		5/9/2025		9:00	
Permit #			Contractor		General/Owner		9.00	
		Con						
PRRES 2025 0722 Inspection Type			Concrete Design of KC New Mark Homes					
l				f VC				
Slab - Basement & Garage Areas Inspected			Concrete Design of KC Current Temp 24 hr High 24 hr Low					
Areas inspected		Curre	it remp	24 III FIIGII	ľ	4 III LOW		
Basement & Garage Slabs and Deck Piers								
Site Conditions (all must	comply if applicable)	Slak	(Basemen	t or Garage A	As Marke	ed)		
☐ City approved plot plan and building construction			Formed & Reinforced Per City Approved Dwgs					
plans on site.			Suspended floor slab (over usable space)					
☑ Erosion control is in place and functional (inspection			Garage structural slab per approved plan					
shall not be performed i	f erosion control is not		Basement	structural slab	per appr	oved p	lan	
functionally in compliance with the City			✓ 6 mil vapor barrier installed – not required for garage					
requirements).			slab					
Building setbacks per approved plot plan			Isolation rings or block-outs are provided over pier pads					
Soils – bearing capacity as determined by:			for columns					
Bearing on undisturbed soil @ 1,500 psf			Rubber Membrane installed where required					
	ent or attach report)	Foo	tings					
Fill per engineering report			Reinforced per city approved plans.					
Free of organic material			Deck/porch/balcony piers					
Cold weather protection Type:			Footing – width, depth and location					
Footing Elevation Certification			Solid jumps					
"Footing Elevation Certification" form completed by			Frost depth (min. 36 inches)					
contractor has been reviewed for completeness and			Column pads – basement					
allowable tolerances.			Column pads – basement structural slab					
Drilled Piers (refer to footings for deck piers)			Column pads – garage steel column					
Pier foundation per approved plan			Column/pad at garage structural slab					
Quantity:			Undermined fdn elements (recommendation in comments and/or attached report)					
Size:								
Depth:			Ufer Ground attachment rod provided					
Bearing:		_	Location:					
Approved standard be	scoment clab on grade an	d c+r	ctural garag	o clab and to	wo (3) do	ck 1	l	
Approved standard ba	isement slab on grade an	u Sti U	rini ai garag	e siab, and th	wo (2) de	:CK	l	

Approved standard basement slab on grade and structural garage slab, and two (2) deck piers 24" x 36" min.

This is to certify that I, or qualified individuals working under my direction, inspected and/or tested the above checked items in accordance with the applicable City approved building and site plans, codes and engineering details. The work is complete and to the best of my knowledge was found to be in substantial compliance with the approved plans and specifications.

Signed

Date 5/9/2025

