
DEVELOPMENT SERVICES

Building Permit - Commercial Project Title: EVREN APARTMENTS - TYPE D BUILDING #4 Work Desc: NEW MULTI-FAMILY	Permit No: PRCOM20250328 Date Issued: June 23, 2025
--	--

Project Address: 39 NE TUDOR RD, LEES SUMMIT, MO 64086 Legal Description: SUMMIT PARK N 3 AC OF LOT 4 Parcel No: 52900041000000000 County: JACKSON	Permit Holder: CITYSCAPE CONSTRUCTION - TUDOR LLC 10 W CARMEL DRIVE STE 200 CARMEL, IN 46032
--	--

Activities Included for this Project: zNew Multi-Family, Excise Tax, Excise Tax Credit, Alarm Permit, Sprinkler Permit, Fire Rated Assemblies Permit,

THIS PERMIT IS ISSUED IN RELIANCE UPON INFORMATION SUBMITTED BY THE APPLICANT. THE BUILDING OFFICIAL MAY SUSPEND OR REVOKE WHENEVER THE PERMIT IS ISSUED IN ERROR, OR ON THE BASIS OF INCORRECT INFORMATION SUPPLIED, OR IN VIOLATION OF ANY ADOPTED CODE, CITY ORDINANCE OR REGULATIONS. NOTICE: THE DISPOSAL OF DEMOLITION WASTE IS REGULATED BY THE DEPARTMENT OF NATURAL RESOURCES UNDER CHAPTER 260 RSMO. SUCH WASTE, IN TYPES AND QUANTITIES ESTABLISHED BY THE DEPARTMENT, SHALL BE TAKEN TO A DEMOLITION LANDFILL OR A SANITARY LANDFILL FOR DISPOSAL.

CONDITIONS

One or more divisions have conditions that have not been addressed during the review period. The outstanding conditions provided below shall be met as indicated during the construction period.

Fire Plan Review	Reviewed By: Craig Hill	Approved
-------------------------	--------------------------------	-----------------

1. 2018 IFC 1004.3- Posting of occupant load. Every room or space that is an assembly occupancy shall have the occupant load of the room or space posted in a conspicuous place, near the main exit or exit access doorway from the room or space. Posted signs shall be of an approved legible permanent design and shall be maintained by the owner or authorized agent.

2. 2018 IFC 907.1.1- Construction documents. Construction documents for fire alarm systems shall be submitted for review and approval prior to system installation. Construction documents shall include, but not be limited to, all of the following:
1. A floor plan which indicates the use of all rooms. 2. Locations of alarm-initiating and notification appliances. 3. Alarm control and trouble signaling equipment. 4. Annunciation. 5. Power connection. 6. Battery calculations. 7. Conductor type and sizes. 8. Voltage drop calculations. 9. Manufacturers, model numbers and listing information for equipment, devices and materials. 10. Details of ceiling height and construction. 11. The interface of fire safety control functions.

Provide alarm plans for review and approval.

Provide as a deferred submittal.

3. 2018 IFC 506.1- Where required. Where access to or within a structure or an area is restricted because of secured openings or where immediate access is necessary for life-saving or fire-fighting purposes, the fire code official is authorized

to require a key box to be installed in an approved location. The key box shall be of an approved type and shall contain keys to gain necessary access as required by the fire code official.

4. 2018 IFC 510.1- Identification. Fire protection equipment shall be identified in an approved manner. Rooms containing controls for air-conditioning systems, sprinkler risers and valves, or other fire detection, suppression or control elements shall be identified for the use of the fire department. Approved signs required to identify fire protection equipment and equipment location, shall be constructed of durable materials, permanently installed and readily visible.

5. 2018 IFC 901.2- Construction documents. The fire code official shall have the authority to require construction documents and calculations for all fire protection systems and to require permits be issued for the installation, rehabilitation or modification of any fire protection system. Construction documents for fire protection systems shall be submitted for review and approval prior to system installation.

Provide sprinkler plans for review and approval.

Provide as a deferred submittal.

6. 2018 IFC 506.1.2 Key boxes for non-standardized fire service elevator keys. Key boxes provided for non-standardized fire service elevator keys shall comply with Section 506.1 and 506.2 or as approved by the fire code official.

7. 2018 IFC 906.2- General requirements. Portable fire extinguishers shall be selected, installed and maintained in accordance with this section and NFPA 10.

8. 2018 IFC 505.1- Address numbers. New and existing buildings shall have approved address numbers, building numbers or approved building identification placed in a position that is plainly legible and visible from the street or road fronting the property. These numbers shall contrast with their background. In Multi-tenant commercial building where tenants have multiple entrances located on different sides of the building , each door shall be addressed. Address numbers shall be Arabic numerals or alphabet letters. Numbers shall be a minimum of 4 inches (102 mm) high with a minimum stroke width of 0.5 inch (12.7 mm).

9. Vertical construction cannot begin until interior paved surfaces and area fire hydrants have been approved by the Fire Department.

Building Plan Review	Reviewed By: Joe Frogge	Approved with Conditions
-----------------------------	--------------------------------	---------------------------------

4. For the Health Department review of public pools contact Casey Elledge with the Jackson County Public Works Department, Environmental Services Division, at (816) 223-9769. Health Department approval is required prior to receiving any type of building permit from the City of Lee's Summit.

Action required: Comment is informational.
11/14/2024 - Deferred per request.

5. For the Health Department inspection of public pools contact Casey Elledge with the Jackson County Public Works Department, Environmental Health Division at (816) 223-9769. Health Department approval is required prior to receiving any type of Occupancy from the City of Lee's Summit.

Action required: Comment is informational.
11/12/2024 - Acknowledged in letter.

6. 2018 IBC 502.1 Address identification. New and existing buildings shall be provided with approved address identification. The address identification shall be legible and placed in a position that is visible from the street or road fronting the property. Address identification characters shall contrast with their background. Address numbers shall be Arabic numbers or alphabetical letters. Numbers shall not be spelled out. Each character shall be a minimum of 4 inches high with a

minimum stroke width of ½ inch. Where required by the fire code official, address identification shall be provided in additional approved locations to facilitate emergency response. Where access is by means of a private road and the building address cannot be viewed from the public way, a monument, pole or other approved sign or means shall be used to identify the structure. Address identification shall be maintained.

Action required: Comment is informational. Addressing scenario has not yet been decided upon. You will be made aware of building and suite addresses at a later date.

11/12/2024 - Acknowledged in letter.

7. Copies of the engineered truss package were not provided at the time of permit application.

Action required: Comment is informational. Truss submittals deferred per request.

11/12/2024 - Acknowledged in letter.

8. City of Lee's Summit Code of Ordinances Section 28-177. - Applicability. (of excise/license tax)

(B)(1)(e) Development requiring a building permit and resulting in additional vehicle trips that is constructed by, or by a building contractor on behalf of, a person that is not subject to any Federal, State or local taxes, including Federal, State and local sales, income, personal property, real property, use, earnings, excise or license taxes. The burden of proof shall be on the building contractor claiming this credit to demonstrate to the License Tax Administrator, by clear and convincing evidence, that the development being constructed by, or by a building contractor on behalf of, a person claiming such credit is exempt from all Federal, State and local taxes as described in this subsection;

Action required: Provide verification of tax exempt status.

11/12/2024 - Letter provided is only applicable to sales tax to purchase construction materials. Excise/License tax still applies.

9. Prior to the installation or construction of any elevator equipment, an elevator equipment permit shall be obtained from the Missouri Department of Public Safety or its authorized representative.

Action required: Comment is informational.

11/12/2024 - Acknowledged in letter.

10. Prior to the operation of any new elevator equipment or the issuance of the operating certificate, such elevator equipment shall be inspected by a licensed inspector. Testing must be performed in accordance with these rules and regulations. The testing must be witnessed by a licensed inspector.

Action required: Comment is informational.

11/12/2024 - Acknowledged in letter.

11. Elevator Safety Act and Rules 701.361 - Each privately owned or operated installation and each installation owned or operated by the state of Missouri or any political subdivision of the state shall have a certificate of inspection and meet the safety code promulgated pursuant to sections 701.350 to 701.380.

Action required: Comment is informational.

11/12/2024 - Acknowledged in letter.

14. 2018 IMC 306.5 Equipment and appliances on roofs or elevated structures. Where equipment requiring access or appliances are located on an elevated structure or the roof of a building such that personnel will have to climb higher than 16 feet above grade to access such equipment or appliances, an interior or exterior means of access shall be provided. Such access shall not require climbing over obstructions greater than 30 inches in height or walking on roofs having a slope greater than 4 units vertical in 12 units horizontal. Such access shall not require the use of portable ladders. Where access involves climbing over parapet walls, the height shall be measured to the top of the parapet wall. Permanent ladders installed to provide the required access shall comply with the following minimum design criteria: 1. The side railing shall

extend above the parapet or roof edge not less than 30"
(see code section for additional construction requirements)

Action required: Provide minimum 30" side rail extenders at tops of roof hatches.
11/12/2024 - Per architect this is covered in spec. To be field verified.

Licensed Contractors	Reviewed By: Joe Frogge	Approved
-----------------------------	--------------------------------	-----------------