

TRAFFIC CONTROL EQUIPMENT TOTALS

POSTED SPEED LIMIT	MINIMUM TAPER LENGTH FOR 12-FT LANE MERGING SHIFTING SHOULDER			MAXIMUM CHANNELIZER SPACING		MINIMUM SIGN SPACING (ADVANCE OF TAP & BETWEEN SIGN)
				TAPER	TANGENT	
20 MPH	80 FT.	40 FT.	27 FT.	20 FT.	40 FT.	100 FT.
25 MPH	125 FT.	63 FT.	42 FT.	25 FT.	50 FT.	100 FT.
30 MPH	180 FT.	90 FT.	60 FT.	30 FT.	60 FT.	250 FT.
35 MPH	245 FT.	123 FT.	82 FT.	35 FT.	70 FT.	250 FT.
40 MPH	320 FT.	160 FT.	107 FT.	40 FT.	80 FT.	250 FT.
45 MPH	540 FT.	270 FT.	180 FT.	45 FT.	90 FT.	350 FT.
50 MPH	600 FT.	300 FT.	200 FT.	50 FT.	100 FT.	350 FT.
55 + MPH	660 FT.	330 FT.	220 FT.	50 FT.	100 FT.	PER TABLE 'A'

79 x	Bollard	
10 x	Little Buster Sign Stand	
8 x	R4-7a Keep Right 9"	
2 x	R9-9 Type 1 Sidewalk Closed	
1 x	R9-11a Sidewalk Closed Left Arrow w/Audible	
1 x	R9-11a Sidewalk Closed Right Arrow w/Audible	
2 x	Type 3 Plain	
2 x	Union Certified Flaggers	
1 x	W1-4R Shift Arrow Right	
2 x	W6-3 Two Way Traffic 36"	
1 x	W20-4 one lane road ahead	
2 x	W20-7 Flagger Ahead	
4 x	W21-7 utility work ahead	

